



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : H01B 12/00	A2	(11) International Publication Number: WO 00/31754 (43) International Publication Date: 2 June 2000 (02.06.00)
(21) International Application Number: PCT/DK99/00645 (22) International Filing Date: 22 November 1999 (22.11.99) (30) Priority Data: PA 1998 01533 20 November 1998 (20.11.98) DK (71) Applicant (for all designated States except US): NKT RESEARCH CENTER A/S [DK/DK]; Priorparken 878, DK-2605 Brøndby (DK). (72) Inventor; and (75) Inventor/Applicant (for US only): WILLÉN, Dag [SE/DK]; Søndergårdsvej 8A, DK-2860 Søborg (DK). (74) Common Representative: NKT RESEARCH CENTER A/S; Priorparken 878, DK-2605 Brøndby (DK).		(81) Designated States: AE, AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), DM, EE, EE (Utility model), ES, FI, FI (Utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>In English translation (filed in Danish).</i> <i>Without international search report and to be republished upon receipt of that report.</i>
(54) Title: A METHOD FOR CONSTRUCTING A SUPERCONDUCTING MULTIPHASE CABLE COMPRISING N PHASES		
(57) Abstract		
By a method for constructing a superconducting multiphase cable comprising N phases, the phases are divided into n groups with N phases in each group, all the groups having a common screen. The individual groups may be geometrically formed with coaxial or flat phases. The individual phases in each group may further be divided into individual conductors such as tapes. The insulation between the individual conductors in the groups may be separately insulated from each other or have a common insulation. In a particularly appropriate embodiment, the number of groups is 1 and implemented with a flat or concentric geometry. In this way, a compact superconducting power cable is provided, which is relatively inexpensive in production and has few working operations while maintaining good electrical properties.		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

A method for construction a superconducting multiphase cable comprising N Phases.

The invention relates to a method for constructing a superconducting multiphase cable
5 comprising N phases, wherein each phase in the cable is divided into a number of conductors and wherein insulation means are arranged in the cable, the phases being divided into n groups, each group having N different phases.

Superconductor cables utilize the low resistance in superconductor materials achieved
10 when the superconductor material is exposed to a temperature that is lower than its so-called critical temperature.

This temperature may be e.g. 4-7 K (low temperature superconductor, LTS) or 30-10 K high temperature superconductor, HTS).

For use at ambient temperature, an artificial refrigerant and a thermal insulation are usually
15 required in order to separate the cable conductor thermally from its surroundings.

Superconductor cables may be produced from a superconducting band wound around a central refrigerating channel. A layer of electrically conducting material is then coaxially applied.

20 A coaxial screen which is either superconducting or normally conducting may then be applied.

A thermally insulating layer may be applied either between the inner superconducting layer and the electrical insulation or on the outside of the electrical insulation.

Thus, the electrical insulation is either exposed to a high temperature (ambient temperature) or a low temperature (cryogenic temperature).
25

Further, such a cable may have an outer diameter typically in the range from 8 to 15 cm.

The electric AC loss occurring in the superconductor may be reduced by winding a superconducting band or wire around a refrigerating channel, said winding being made with
30 climbing angles in such a way that an even current distribution among the individual bands/wires is obtained.

They may also be wound around several refrigerating channels, e.g. as disclosed in U.S. Patent No. 4,327,244.

If the current-carrying capacity of cables of this type is to be increased, this may be obtained by increasing the quantity of superconducting material.

However, this leads to an increased generation of reactive power, since the reactance/inductance of the cable becomes relatively high, which may cause undesired phase shifts in the conveyed electrical voltage and current, especially in long cable sections but also in short cable sections to which a low voltage is applied and a high current is conducted.

Normally, this reactance/inductance may be reduced by increasing the diameter of the inner semiconductor by e.g. 30-50 cm.

10 Even though the reactance/inductance is decreased thereby, this reduction also has drawbacks such as e.g. larger dimensions of the cables, increased consumption of materials, and finally an increased heat transfer because of the increased area of the thermal insulation.

15 Other methods are disclosed in the literature, which allow reduction of the reactance/inductance of a superconducting cable system.

Normally, electrical insulation and electrical screening are included in known cable systems for AC single-phase cables, wherein 3 cables with one phase conductor each are used for providing 3 phases.

20

From EP 0 786 783 A1 a multiphase superconducting cable is known, in which the individual phases are divided into a number of individual conductors. Each of the individual conductors is isolated from each other and equipped with a superconducting screen.

Evidently, this results in a rather expensive and bulky cable, since each individual conductor constitutes a "cable" with a conductor, a screen and two layers of insulation.

DE 4340046 A1 discloses a superconducting cable, in which 3 phases are located coaxially in relation to each other and are surrounded by a common return circuit.

Reduced consumption of material is thus rendered possible, since 3 phase conductors have a common screen.

The diameter of the individual phase conductors may be increased with the purpose of reducing the inductance without an increase of the volume being required which would be the case if 3 individual cables were used.

However, the drawback is that a sufficiently reduced inductance will not be obtained, since the relationship between the reactance and the diameter is logarithmic.

Similarly, from JP 1231217 a multiphase superconducting cable is known, in which the individual phase conductors consist of a refrigerating channel, a superconducting phase conductor, an electrical insulation, in which each individual phase conductor is surrounded

5 by a normally conducting screen.

This reduces the consumption of superconducting material.

Since the normally conducting screen is resistive, according to this technique it is necessary to minimize the current induced in these resistive screens by arranging the individual phase conductors in a triangular pattern, in which each individual phase conductor has a

10 different phase as a neighbour.

Both phase divisioning techniques discussed above have the advantage that the reactive power production is reduced, cf. the law of parallel coupling of reactances/inductances.

Reducing the electric current in each individual phase conductor also reduces the magnetic
15 field at the surface of the phase conductor and the electric AC loss in the superconducting material.

Thus, the drawback of these known techniques is that the individual phase conductors consist of complete, independent cables with refrigerating channel, cable conductors, electrical insulation and electrical screen.
20

In practice, it is impossible to produce a compact and inexpensive cable if a high number of groups with a number of phases in each group are desired.

It is now an object of the invention to facilitate the manufacturing of a superconducting
25 power cable, preferably for use at 1 kV-132 kV, said superconducting power cable being less bulky, having a higher efficiency and lower manufacturing costs as compared to the output, also for large number of groups.

It is a further purpose to reduce the reactance/inductance in a superconducting cable system, without the cable system being bulkier or more expensive than known hitherto.

30

The object of the invention is fulfilled by a number of N groups of phase conductors being assembled in groups and by one or more of the groups being equipped with a common electrical screen.

In this way, a cable may be manufactured in such a way that the electrical insulation may be produced in essentially one working step which is performed before the various phase conductors are assembled into a cable either by application on the phase conductors of the individual superconductors and/or by production of an electrically insulating foil.

- 5 Hence, a production is obtained, which is more compact and has lower costs associated thereto, since the number of working operations during production of the cable may be reduced, the individual phases not having individual electrical screens.

- For further minimization of the manufacturing costs, it is preferred, as specified in claim 2,
10 that the individual phases only contain superconducting cable wire and an insulation system.

- For further simplification of the manufacturing process, the groups may, as specified in claim 3, be arranged in n coaxial groups, either with several different phase conductors in
15 each coaxial layer or with each individual phase conductor in a separate coaxial layer.
In this way, a more simple refrigeration system with a limited number of flow paths for refrigerants could be provided.

- By arranging the groups in N flat phases as specified in claim 4, the magnetic field generated by current in the phases will be relatively long, so that the magnetic induction in the
20 cable is reduced.

In this arrangement, preferably, one or more electrically insulating foil systems may be used as electrical insulation, said foil system(s) consisting of one or more layers of insulating and optionally electrically conducting materials.

- 25 Use of electrically conducting layers of foil or surface coatings implies that this coating may optionally be removed from selected parts of the foil or it may be selected not to apply this coating on selected parts of the foil.

- Further, appropriate embodiments of the invention are specified in the dependent claims.
30

The invention will now be described in greater detail with reference to the exemplary embodiments of the invention illustrated in the drawings, in which

- Fig. 1 shows schematically a first embodiment of the cable according to the invention,
35

Fig. 2 is a second embodiment of the cable according to the invention,

Fig. 3 is a first variant of the embodiment according to Fig. 2,

5 Fig. 4 is a second variant of the embodiment according to Fig. 2,

Fig. 5 is a third variant of the embodiment according to Fig. 2, and

Fig. 6 is a third embodiment of the cable according to the invention.

10

In Fig. 1, 1 designates a superconducting cable in its entirety in a first embodiment of the invention.

The cable in the example shown is a 3 phase cable, in which each phase is denoted by one of the letters a, b or c. The phases are divided into a number of individual conductors

15 which are designated by a numeral 1-n. Thus, the designation n_a designates a conductor no. n with the phase a.

As shown, the conductors are divided into a number of groups n, each of the groups having a number of conductors, corresponding to the number of phases which is 3 in the example shown.

20 Around all of the individual conductors, a surrounding neutral conductor 4 is shown, which may constitute a common screen. According to the invention, this common screen may surround one or more phase groups.

The refrigerant may be applied to each individual phase conductor, each individual group, a number of groups, or preferably the entire cable with a pipe system. The refrigerant may

25 flow in one or more directions in this pipe system.

This construction of the cable, especially in the preferred embodiment, provides an extremely compact construction with optimum electrical properties such as low impedance.

30 A second embodiment of a superconducting power cable according to the invention is shown in Fig. 2.

As compared to the embodiment of Fig. 1, a flat 3 phase cable 5 is shown, in which each phase is again designated by a,b,c. In the example shown, the phases are divided into 2

35 groups 6 and 7 but naturally, there is nothing to prevent the number of groups from being 1

or more. As shown, each phase in each group consists of a number of tapes arranged in rows. In the example shown, all the rows are separated by the same insulation 18. Alternatively, a broad band with a corresponding geometry may be implemented as shown in Fig. 5, in which each phase in each group is separated by layers of insulation.

5 Fig. 3 shows a further variant, wherein each individual phase from each group is comprised by the same insulation as in Fig. 3, denoted by 13 and 14.

In this way, an electrical insulation is obtained, in which each individual surface of an insulating band only relates to one specific phase. The risk of leakage current between phases is thus reduced.

10 If, as shown in Fig. 4, cf. reference number 18, the 2 foil systems of Fig. 3 are assembled to a continuous foil, a further extended leakage path is obtained without increased space requirements.

Thus, in the mentioned embodiments, the magnetic fields induced in the cable, which are generated during conduction of current, have to travel a longer distance, which in turn re-

15 sults in a lower cable impedance.

Fig. 6 shows a variant of the embodiment according to Fig. 5, Fig. 6 showing a cable with a circular cross section, in which the individual phases 10-12 are arranged concentrically.

As shown, each layer consists of a number of tapes arranged in a manner analogous to the
20 embodiment of Fig. 4, i.e. there are n tapes in each layer.

Thus, there are several groups of n phase conductors in each layer.

Finally, the figure shows a common channel 9 for refrigerant. However, cooling may be provided in various ways in a pipe system.

The mentioned electrical screen which may surround one or more groups of phases may
25 consist fully or partially of superconducting, metallic, and semiconducting materials, even in combination with non-conducting materials and composites such as e.g. impregnation of paper with coal powder.

One or more of these composites may be impregnated with porous or non-porous polymer
30 or ceramic material which may have a high or a low thermal conductivity, so that cooling may take place by means of solid conduction and/or by means of a medium such as liquid or gaseous N₂, He₂ or Ne penetrating into the porous material and between one or more of the phases or groups of phases.

It may be envisaged that this refrigerant or an alternative refrigerant may impregnate the
35 electrical insulation in order to improve the electrical insulation properties.

Even though the invention has been explained in connection with the specific embodiments - discussed together with the figures 1-3, there is, naturally, nothing to prevent other embodiments from being formed within the scope of the claims. The cross sections of the
5 cables may e.g. take other forms; they may e.g. be oval, angular, and the like.

CLAIMS:

1. A method for constructing a superconducting multiphase cable comprising N phases,
5 wherein each phase in the cable is divided into a number of conductors, and wherein insulation means are arranged in the cable, the phases being divided into n groups, each group having N different phases, c h a r a c t e r i z e d in that a number of N groups of phase conductors are assembled in groups and in that one or more of the groups is/are provided with a common electrical screen.
- 10 2. A method according to claim 1, c h a r a c t e r i z e d in that the individual phases only contain superconducting cable wire and an insulation system.
3. A method according to claims 1-2, c h a r a c t e r i z e d in that the groups are arranged
15 in n coaxial groups, either with several different phase conductors in each coaxial layer or with each individual phase conductor in a separate coaxial layer.
4. A method according to claims 1-2, c h a r a c t e r i z e d in that the groups are arranged in N flat phases.
- 20 5. A method according to claim 4, c h a r a c t e r i z e d in that each of the phases is constructed by one or several individual conductors such as tapes.
6. A method according to claims 1-5, c h a r a c t e r i z e d in that the number of groups is
25 1.
7. A method according to claims 1-3, c h a r a c t e r i z e d in that the number of groups is 1 and in that the N phases are arranged concentrically with concentric insulation between each of the N phases.
- 30 8. A method according to claims 1-7, c h a r a c t e r i z e d in that the phases in each group are separately and electrically isolated from each other.
9. A method according to claims 1-8, c h a r a c t e r i z e d in that the phases in each group
35 are isolated from each other by a common insulator.

10. A method according to any of the claims 1-9, characterized in that the number of groups n is large, preferably larger than 10 and more preferred larger than 100.
- 5 11. A method according to claims 1-10, characterized in that the electrical screen is kept at 0 potential and consists fully or partially of semiconductor material or of a combination of these materials and is positioned close to the electrically insulating material.
12. A method according to claims 1-11, characterized in that the individual phases
10 in each group have such permittivity that they co-operate magnetically.
13. A method according to claims 1-12, characterized in that at least one of the phases is constituted by a neutral conductor.

1/3




Fig 1






Fig 2



3/3




Fig 5




Fig 6