US 20240384972A1

(19) **United States**

(12) **Patent Application Publication** (10) **Pub. No.: US 2024/0384972 A1**

Mahnke (43) **Pub. Date: Nov. 21, 2024**

(54) **PROJECTILE WITH ENHANCED BALLISTICS**

(71) Applicant: **G9 Holdings, LLC**, Lakewood, CO (US)

(72) Inventor: **Joshua Mahnke**, Post Falls, ID (US)

(21) Appl. No.: **18/787,619**

(22) Filed: **Jul. 29, 2024**

Related U.S. Application Data

(62) Division of application No. 16/806,860, filed on Mar. 2, 2020, now Pat. No. 11,181,351, which is a division of application No. 15/651,997, filed on Jul. 17, 2017, now Pat. No. 10,578,410, which is a division of application No. 14/701,519, filed on Apr. 30, 2015, now Pat. No. 9,709,368.

(60) Provisional application No. 62/145,814, filed on Apr. 10, 2015, provisional application No. 61/986,296, filed on Apr. 30, 2014.

Publication Classification

(51) **Int. Cl.**


F42B 12/02	(2006.01)
F42B 10/22	(2006.01)
F42B 10/24	(2006.01)
F42B 10/26	(2006.01)
F42B 10/46	(2006.01)
F42B 12/06	(2006.01)
F42B 12/34	(2006.01)
F42B 12/74	(2006.01)
F42B 30/02	(2006.01)

(52) **U.S. Cl.**

CPC ***F42B 12/02*** (2013.01); ***F42B 10/22*** (2013.01); ***F42B 10/24*** (2013.01); ***F42B 10/26*** (2013.01); ***F42B 10/46*** (2013.01); ***F42B 12/06*** (2013.01); ***F42B 12/34*** (2013.01); ***F42B 12/74*** (2013.01); ***F42B 30/02*** (2013.01)

(57) **ABSTRACT**

The present invention provides a projectile device and a method of manufacture of a projectile device and in particular, to a pistol bullet and a rifle bullet and method of manufacture of same. In one embodiment, the projectile apparatus has a cylindrical body portion having a diameter, a front nose section tapering from a most proximal point of the projectile to the cylindrical body portion, and a rear tail section connected to the body portion and extending to the most distal point of the projectile, in which the front nose portion comprises a plurality of twisting depressions forming troughs.






FIG.1A




FIG.1B




FIG.1C




FIG.1D




FIG.1E




FIG.2A




FIG.2B




FIG.2C




FIG.3A




FIG.3B




FIG.3C




FIG.3D




FIG.3E




FIG.4A




FIG.4B




FIG.4C




FIG.5A




FIG.5B




FIG.5C




FIG.6A




FIG.6B




FIG.6C




FIG.7A




FIG.7B




FIG.7C




FIG.8A




FIG.8B




FIG.8C




FIG.9A




FIG.9B




FIG.9C




FIG.9D




FIG.10A




FIG.10B




FIG.10C




FIG.11A




FIG.11B




FIG.11C




FIG.11D




FIG.11E




FIG.11F




FIG.12A




FIG.12B




FIG.12C




FIG.12D




FIG.13A




FIG.13B




FIG.13C




FIG.13D




FIG.14A




FIG.14B




FIG.14C




FIG.15A




FIG.15B




FIG.15C




FIG.15D




FIG.16A




FIG.16B




FIG.16C




FIG.16D




FIG.17A




FIG.17B




FIG.17C




FIG.18A




FIG.18B




FIG.18C




FIG.18D




FIG.19A




FIG.19B




FIG.19C




FIG.20A




FIG.20B




FIG.20C




FIG.20D




FIG.21A




FIG.21B




FIG.21C




FIG.22A




FIG.22B




FIG.22C




FIG.23A




FIG.23B




FIG.23C




FIG.23D




FIG.23E




FIG.24A




FIG.24B




FIG.24C




FIG.24D




FIG.25A




FIG.25B




FIG.25C




FIG.26A




FIG.26B




FIG.27A




FIG.27B




FIG.27C




FIG.28A




FIG.28B




FIG.28C




FIG.29A




FIG.29B




FIG.29C




FIG.30A




FIG.30B




FIG.30C




FIG.31A




FIG.31B




FIG.31C




FIG.32A




FIG.32B




FIG.32C




FIG.32D




FIG.33A




FIG.33B




FIG.33C




FIG.34A




FIG.34B




FIG.34C




FIG.34D




FIG.35A




FIG.35B




FIG.35C




FIG.35D




FIG.35E




FIG.36A




FIG.36B




FIG.36C




FIG.36D




FIG.37A




FIG.37B




FIG.37C




FIG.37D




FIG.38A




FIG.38B




FIG.38C




FIG.38D




FIG.38E




FIG.39A




FIG.39B




FIG.39C




FIG.40A




FIG.40B




FIG.40C




TABLE 1

Caliber (diameter in inches)	Twist (1/x inches)														
	6	7	8	9	10	11	12	13	14	15	16				
0.224	6.68944	5.74071	5.02736	4.47200	4.02336	3.66047	3.35516								
0.243	7.25104	6.22397	5.45099	4.84889	4.36353	3.97000	3.64009								
0.257	7.66336	6.57950	5.76299	5.12628	4.61599	4.19793	3.84920								
0.264	7.87013	6.75707	5.91896	5.26513	4.74115	4.31184	3.95371								
0.277	8.25246	7.08630	6.20809	5.52283	4.97347	4.52133	4.14774								
0.284	8.45802	7.26369	6.36370	5.66150	5.09850	4.63712	4.25218								
0.308			6.89659	6.13648	5.52679	5.02706	4.61003	4.25677	3.95371						
0.323			7.22869	6.43283	5.79417	5.27054	4.83350	4.46326	4.14563						
0.338			7.56080	6.72889	6.06129	5.51382	5.05683	4.66963	4.33741						
0.355			7.93635	7.06399	6.36370	5.78931	5.30975	4.90338	4.55467						
0.336			7.51216	6.68549	6.02213	5.47815	5.02408	4.63937	4.30928						
0.375			8.37729	7.45760	6.71903	6.11306	5.60703	5.17816	4.81010	4.49078	4.21115				
0.400					7.16046	6.51720	5.97821	5.52131	5.12911	4.78882	4.48078				
0.416					7.44580	6.77851	6.21550	5.74071	5.33312	4.97943	4.66953				
0.423					7.56965	6.88944	6.31925	5.83665	5.42233	5.06278	4.74785				
0.458					8.18780	7.45224	6.83736	6.31583	5.86797	5.47924	5.13868				
0.477					8.52458	7.75770	7.11815	6.57559	6.10958	5.70507	5.35064				
0.510											5.71843				

FIG. 41

PROJECTILE WITH ENHANCED BALLISTICS

CROSS REFERENCE TO RELATED APPLICATIONS

[0001] This application is a divisional application of U.S. patent application Ser. No. 17/533,658 filed on Nov. 23, 2021, entitled "Projectile with Enhanced Ballistics" which is a divisional application of U.S. patent application Ser. No. 16/806,860, filed on Mar. 2, 2020, now U.S. Pat. No. 11,181,351, entitled "Projectile with Enhanced Ballistics" which is a divisional application of U.S. patent application Ser. No. 15/651,997, filed on Jul. 17, 2017, now U.S. Pat. No. 10,578,410, entitled "Projectile with Enhanced Ballistics," which is a divisional application of U.S. patent application Ser. No. 14/701,519, filed on Apr. 30, 2015, now U.S. Pat. No. 9,709,368, entitled "Projectile with Enhanced Ballistics," which claims the benefit of priority from U.S. Provisional Patent Application No. 62/145,814, filed Apr. 10, 2015, entitled "Projectile with Enhanced Ballistics," and U.S. Provisional Patent Application No. 61/986,296, filed Apr. 30, 2014, entitled "Projectile with Enhanced Ballistics," the entire disclosures of which are hereby expressly incorporated by reference in their entireties.

FIELD OF THE INVENTION

[0002] Embodiments of the present invention are generally related to a projectile device and a method of manufacture of the same and in particular to a pistol bullet and a rifle bullet and method of manufacture of the same.

BACKGROUND OF THE INVENTION

[0003] Conventional projectiles, such as bullets, typically comprise a smooth uniform shank or body portion and an axially-symmetrical front or nose portion. Bullet performance is traditionally assessed with respect to parameters including velocity, ballistic coefficient (BC), trajectory, accuracy, and target penetration. Conventional bullets, after leaving the barrel and once under unpowered free-flight, substantially degrade in flight characteristics. For example, conventional bullets begin to wobble during flight, thereby losing accuracy and velocity. Upon striking a target, such reduced velocity and wobbling limits target penetration.

[0004] Various efforts have been made to improve projectile performance and/or enable additional projectile features. For example, U.S. Pat. No. 4,829,904 to Sullivan ("Sullivan") issued May 16, 1989, discloses a substantially full bore diameter bullet that has a plurality of elongated grooves either helically formed or parallel with the longitudinal axis of the bullet and a sabot, which has a body and fingers that engage with the grooves and seal the bullet in a casing. The sabot is configured with a slightly larger diameter than the bullet such that the sabot is engraved by the rifling slots in the barrel through which the round is fired, imparting a rotation to the bullet. In alternative embodiments the grooves contain elongated elements or a plurality of spherical elements to prevent the conically tapered slug or bullet from tilting or cocking in the barrel after firing. However, Sullivan fails to teach several novel features of the present invention, including a projectile design that retains if not enhances the spin of a projectile in flight, so as to achieve flatter and faster external ballistics and further yield improved target penetration. Sullivan is incorporated herein by reference in its entirety.

[0005] U.S. Pat. No. 6,439,125 to Carter ("Carter") issued Aug. 27, 2002, relates to a bullet having a tapered nose and a cylindrical base. The base is provided with an annular groove having a diameter less than the bore diameter of the barrel of the gun to reduce the force required to move the bullet through the barrel, thereby increasing the muzzle velocity and kinetic energy of the bullet. However, Carter fails to teach several novel features of the present invention, including a projectile design that retains if not enhances the spin of a projectile in flight, to achieve flatter and faster external ballistics and further yield improved target penetration. Carter is incorporated herein by reference in its entirety.

[0006] U.S. Pat. No. 6,581,522 to Julien et al., ("Julien") issued Jun. 24, 2003, discloses a projectile comprising a cylindrical body of Type 55 Nitinol material that has a soft martensitic state that is readily deformed by rifling in the bore of a gun barrel to form grooves which ride on the rifling to spin the projectile. The Nitinol material has a low coefficient of friction with the steel barrel and is sufficiently strong to prevent shedding projectile material in the bore. On impact with the target, the Nitinol material undergoes a strain-induced shift to an ultra-high strength state in which the projectile is capable of remaining intact and concentrating its full energy on the small area of contact for maximal penetration and damage to the target. In contrast, a conventional bullet typically mushrooms widely and spreads its energy over a side area. Projectiles in the form of bullets, shotgun slugs, penetrating warheads, caseless ammunition, and artillery shells are described. However, Julien fails to teach several novel features of the present invention, including a projectile design that retains if not enhances the spin of a projectile in flight, to achieve flatter and faster external ballistics and further yield improved target penetration. Julien is incorporated herein by reference in its entirety.

[0007] U.S. Patent Application Publication No. 2006/0027128 to Hober ("Hober") published Feb. 9, 2006, discloses a projectile for small munitions comprising a bullet with an integral housing formed from a resilient, shape-retaining material. The projectile comprises a bullet having a tapered front section, a cylindrical middle section and a tapered end section. The middle section includes a recessed retaining portion over which the resilient housing is securely positioned or formed. The maximum diameter of the bullet is less than the primary bore diameter of the firearm barrel, and the outer diameter of the housing when positioned around the bullet is slightly greater than the primary bore diameter. Thus, rifling in the barrel scores the housing and not the bullet, and imparts spin to the housing during firing and hence to the bullet, which is integral therewith, achieving enhanced gas checking efficiency, accuracy and velocity. The integral housing remains on the bullet after firing and downrange to its ultimate destination. However, Hober fails to teach several novel features of the present invention, including a projectile design that retains if not enhances the spin of a projectile in flight, so as to achieve flatter and faster external ballistics and further yield improved target penetration. Hober is incorporated herein by reference in its entirety.

[0008] U.S. Pat. Nos. 5,116,224 to Kelsey, Jr. ("Kelsey I") issued on May 26, 1992 and 5,133,261 to Kelsey, Jr. ("Kelsey II") issued on Jul. 28, 1992 and disclose a small arms bullet having a truncated conical nose with radial

rearwardly extending ribs. The ribs have a flat edge and form grooves between the ribs. The Kelsey I ribs are formed along a radial, whereas the Kelsey II ribs are curved. In both Kelsey I and Kelsey II, the ribs are engineered to form a flat planar structure defining a rib thickness. However, each of Kelsey I and Kelsey II fail to teach several novel features of the present invention, including a projectile design that retains if not enhances the spin of a projectile in flight, to achieve flatter and faster external ballistics and further yield improved target penetration. Both Kelsey I and Kelsey II are incorporated herein by reference in entirety.

[0009] U.S. Statutory Invention Registration No. H770 to Kline et al., ("Kline") discloses a tracer training bullet which can be assembled into a conventional cartridge case and fired in a conventional M2 machine gun. The bullet consists of a main body of relatively low strength material which is segmented so that, if not restrained, it will bend under the centrifugal rotational force imparted to the segments by the spinning action of the projectile when fired. The bending of the projectile segments away from their central axis is ordinarily prevented by a retainer in the form of a spider. The spider is made of a relatively low temperature melting material, preferably aluminum, having a given thermal mass. The burn of the tracer material during the flight of the bullet toward a target weakens the retainer to the point of rupture after the bullet has travelled a given distance toward a target position. After the target position is passed, the securement member is destroyed by the high temperature burning action and the segments of the projectile bend or flex apart. This destroys the aerodynamic characteristics of the bullet and reduces its maximum range beyond the target distance. However, Kline fails to teach several novel features of the present invention, including a projectile design that retains if not enhances the spin of a projectile in flight, so as to achieve flatter and faster external ballistics and further yield improved target penetration. Kline is incorporated herein by reference in its entirety.

[0010] Thus, there is a long-felt need for a projectile design, and method of making the same, that retains, enhances, or counters the spin of a projectile in flight, to achieve flatter and faster external ballistics and further yield improved target penetration, as provided in embodiments of the present invention. The projectile design of the present invention may be configured to create several embodiments, for example to include rifle embodiments and pistol embodiments.

SUMMARY OF THE INVENTION

[0011] What is needed is a projectile that does not substantially degrade in flight characteristics once leaving the gun barrel, so as to achieve flatter and faster external ballistics and further yield improved target penetration. The present invention solves these needs by providing a projectile that retains if not enhances the spin of a bullet in flight and, in some embodiments, provides a cutting edge to promote and enhance target penetration and/or expansion in soft targets.

[0012] It is one aspect of the present invention to provide a projectile device and a method of manufacture of a projectile device. In particular, a pistol bullet and a rifle bullet are provided, along with methods of manufacture of the same.

[0013] Another aspect of the present invention is to provide a projectile with improved accuracy and performance.

[0014] In general, a projectile with a non-congruent twist penetrates less into the target and the larger end mill cut penetrates less into the target. These projectiles create a cavitation and slow down in soft tissue. The advantages generally include the case of manufacturing and the non-expanding bullet (i.e., no housing and cavities). Further, the projectile does not deflect in auto glass, it shoots through sheet metal and body armor using its cutting edges, and it creates a cavitation in tissue to help it slow down in the soft tissue. A congruent twist will increase the depth of the projectile's penetration in soft media. The shorter the distance the projectile travels in the target, the more energy is released in that short distance. Thus, a wider tissue area is affected in order to absorb the energy.

[0015] In one embodiment of the invention, a projectile with enhanced performance characteristics adapted for use with a firearm is disclosed, the projectile comprising: a cylindrical body portion having a predetermined diameter; a front nose section tapering from a forward most point of the projectile to the cylindrical body portion; and a rear tail section connected to the body opposite the front nose portion; and wherein the front nose portion comprises at least one twisting depression forming a trough at a predetermined angle oriented with respect to a longitudinal centerline of the projectile.

[0016] In one embodiment, a projectile device is disclosed comprising: a cylindrical body with a longitudinal axis and a first end and a second end which defines a first length therebetween; a nose integrally interconnected to the second end of said cylindrical portion and having a second length, said nose further comprising: a) a plurality of cutout portions originating proximate to an apex of said nose and having a predetermined angle with respect to the longitudinal axis of the cylindrical body; b) a non-distorted nose portion positioned between each of the cutout portions, and wherein the intersection of the plurality of cutout portions and each of the non-distorted nose portions form a distinct edge which extends proximate to the apex of the nose portion.

[0017] In another embodiment, a projectile with enhanced performance characteristics for use with a firearm is disclosed, the projectile comprising: a first end having a tip; a second end having a base, the second end opposite the first end; a cylindrical portion having a predetermined diameter, the cylindrical portion positioned between the first end and the second end; a nose portion tapering from the tip to the cylindrical portion, wherein the nose portion is integrally interconnected to the cylindrical portion at a first junction; a first depression forming a first trough extending from a portion of the projectile proximate the first junction proximate to the tip of the projectile, wherein a first centerline of the first depression is positioned at a first angle relative to a longitudinal centerline of the projectile, and wherein the first trough has a first radius of curvature; a second depression forming a second trough extending from the portion of the projectile proximate the first junction proximate to the tip of the projectile, wherein a second centerline of the second depression is positioned at a second angle relative to the longitudinal centerline of the projectile, and wherein the second trough has a second radius of curvature; a first remaining nose portion positioned between the first depression and the second depression, the first remaining nose portion having a substantially triangular shape and forming a first cutting edge proximate the tip; a third depression forming a third trough extending from the portion of the

projectile proximate the first junction proximate to the tip of the projectile, wherein a third centerline of the third depression is positioned at a third angle relative to the longitudinal centerline of the projectile, and wherein the third trough has a third radius of curvature; a second remaining nose portion positioned between the second depression and the third depression, the second remaining nose portion having a substantially triangular shape and forming a second cutting edge proximate the tip; and a third remaining nose portion positioned between the first depression and the third depression, the third remaining nose portion having a substantially triangular shape and forming a third cutting edge proximate the tip.

[0018] In yet another embodiment, a projectile device is disclosed comprising: a cylindrical body with a longitudinal axis defined therethrough; a nose integrally interconnected to a forward end of the cylindrical body; an alternating pattern of arcuate shaped cutout portions extending from approximately the tip of the nose to the cylindrical body and non-distorted nose portions having a substantially triangular shape, the intersection defining a cutting edge which is oriented at a specific angle with respect to the longitudinal axis of the cylindrical body.

[0019] In some embodiments, further features comprise: wherein the non-distorted nose portion has a substantially triangular shape; wherein the plurality of cutout portions has a length of approximately the nose second length; three distinct cutting edges formed at the intersection of the cutout portions; wherein the cutout portions have either a right or a left twist with respect to the longitudinal axis of the projectile; wherein the metallic projectile comprises three twisting cutout portions and three non-distorted nose portions; wherein the first length of the cylindrical portion is greater than the second length of the nose; wherein the projectile is made of a metallic material; wherein the metallic projectile has a caliber of at least one of 0.380 inch, 9 mm, 0.40 inch, and 0.45 inch and is adapted for use with a handgun; wherein the projectile is comprised of at least one of lead, copper, steel, magnesium, titanium, and other alloy; a second cutting edge formed at the intersection of the first depression and second depression and the second depression and third depression, and positioned above the first cutting edge; a second cutting edge defined by the intersection if each cutout portion above the non-distorted nose portion and extending upwardly to the apex of the nose; and wherein there are three distinct cutout portions and three distinct non-distorted nose portions.

[0020] The term "projectile" and variations thereof, as used herein, refers to any object projected into space by the exertion of a force, to include bullets, bombs, and rockets.

[0021] The term "ballistics" and variations thereof, as used herein, refers to the physics of projecting a projectile into space, to include the range and accuracy of projectiles and the effects of projectiles upon impact with an object.

[0022] The term "ballistics coefficient (BC)" and variations thereof, as used herein, refers to the ability of a projectile to overcome air resistance in flight; a high number indicates a greater ability to overcome air resistance.

[0023] The term "internal ballistics" and variations thereof, as used herein, refers to the behavior and effects of a projectile from propellant ignition to exit from a gun barrel.

[0024] The term "external ballistics" and variations thereof, as used herein, refers to the behavior and effects of a projectile from leaving a gun barrel until striking a target.

[0025] The term "terminal ballistics" and variations thereof, as used herein, refers to the behavior and effects of a projectile when it hits a target.

[0026] This Summary of the Invention is neither intended nor should it be construed as being representative of the full extent and scope of the present disclosure. The present disclosure is set forth in various levels of detail in the Summary of the Invention as well as in the attached drawings and the Detailed Description of the Invention, and no limitation as to the scope of the present disclosure is intended by either the inclusion or non-inclusion of elements, components, etc. in this Summary of the Invention. Additional aspects of the present disclosure will become more readily apparent from the Detailed Description, particularly when taken together with the drawings.

[0027] The above-described benefits, embodiments, and/or characterizations are not necessarily complete or exhaustive, and in particular, as to the patentable subject matter disclosed herein. Other benefits, embodiments, and/or characterizations of the present disclosure are possible utilizing, alone or in combination, as set forth above and/or described in the accompanying figures and/or in the description herein below. However, the Detailed Description of the Invention, the drawing figures, and the exemplary claims set forth herein, taken in conjunction with this Summary of the Invention, define the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

[0028] Those of skill in the art will recognize that the following description is merely illustrative of the principles of the invention, which may be applied in various ways to provide many different alternative embodiments. This description is made for illustrating the general principles of the teachings of this invention and is not meant to limit the inventive concepts disclosed herein.

[0029] The accompanying drawings, which are incorporated in and constitute a part of the specification, illustrate embodiments of the invention and together with the general description of the invention given above and the detailed description of the drawings given below, serve to explain the principles of the invention.

[0030] FIGS. **1**A-E show a projectile according to a first embodiment of the invention;

[0031] FIGS. **2**A-C show a projectile according to a second embodiment of the invention;

[0032] FIGS. **3**A-E show a projectile according to a third embodiment of the invention;

[0033] FIGS. **4**A-C show a projectile according to a fourth embodiment of the invention;

[0034] FIGS. **5**A-C show a projectile according to a fifth embodiment of the invention;

[0035] FIGS. **6**A-C show a projectile according to a sixth embodiment of the invention;

[0036] FIGS. **7**A-C show a projectile according to a seventh embodiment of the invention;

[0037] FIGS. **8**A-C show a projectile according to an eighth embodiment of the invention;

[0038] FIGS. **9**A-D show a projectile according to a ninth embodiment of the invention;

[0039] FIGS. **10**A-C show a projectile according to a tenth embodiment of the invention;

[0040] FIGS. **11**A-F show a projectile according to an eleventh embodiment of the invention;

[0041] FIGS. **12**A-D show a projectile according to a twelfth embodiment of the invention;

[0042] FIGS. **13**A-D show a projectile according to a thirteenth embodiment of the invention;

[0043] FIGS. **14**A-C show a projectile according to a fourteenth embodiment of the invention;

[0044] FIGS. **15**A-D show a projectile according to a fifteenth embodiment of the invention;

[0045] FIGS. **16**A-D show a projectile according to a sixteenth embodiment of the invention;

[0046] FIGS. **17**A-C show a projectile according to a seventeenth embodiment of the invention;

[0047] FIGS. **18**A-D show a projectile according to an eighteenth embodiment of the invention;

[0048] FIGS. **19**A-C show a projectile according to a nineteenth embodiment of the invention;

[0049] FIGS. **20**A-D show a projectile according to a twentieth embodiment of the invention;

[0050] FIGS. **21**A-C show a projectile according to a twenty-first embodiment of the invention;

[0051] FIGS. **22**A-C show a projectile according to a twenty-second embodiment of the invention;

[0052] FIGS. **23**A-E show a projectile according to a twenty-third embodiment of the invention;

[0053] FIGS. **24**A-D show a projectile according to a twenty-fourth embodiment of the invention;

[0054] FIGS. **25**A-C show a projectile according to a twenty-fifth embodiment of the invention;

[0055] FIGS. **26**A-B show the projectile housing of FIGS. **25**A-C;

[0056] FIGS. **27**A-C show the projectile insert of FIGS. **25**A-C;

[0057] FIGS. **28**A-C show a projectile insert according to another embodiment of the invention;

[0058] FIGS. **29**A-C show a projectile insert according to alternate embodiment of the invention;

[0059] FIGS. **30**A-C show the projectile of FIGS. **25**A-C after being fired;

[0060] FIGS. **31**A-C show a projectile according to a twenty-sixth embodiment of the invention after being fired;

[0061] FIGS. **32**A-D show a projectile according to a twenty-seventh embodiment of the invention;

[0062] FIGS. **33**A-C show a projectile according to a twenty-eighth embodiment of the invention;

[0063] FIGS. **34**A-D are exploded views of the projectile housing and insert of FIGS. **33**A-C;

[0064] FIGS. **35**A-E show a projectile according to a twenty-ninth embodiment of the invention;

[0065] FIGS. **36**A-D show a projectile according to a thirtieth embodiment of the invention;

[0066] FIGS. **37**A-D show a projectile according to a thirty-first embodiment of the invention;

[0067] FIGS. **38**A-E show a projectile according to a thirty-second embodiment of the invention;

[0068] FIGS. **39**A-C show a projectile according to a thirty-third embodiment of the invention;

[0069] FIGS. **40**A-C show a projectile according to a thirty-fourth embodiment of the invention; and

[0070] FIG. **41** shows a table for alpha angles corresponding to the rate of twist and the caliber.

[0071] To assist in the understanding of the embodiments of the present invention, the following list of components and associated numbering found in the drawings is provided herein:

No.	Component
2	Projectile
4	Tip or Apex
6	Nose Portion (or Front Portion)
8	Nose Depression (or Cutout or Trough)
10	Centerline of Nose Depression
12	Ogive
14	Secant Ogive
16	Tangent Ogive
18	Shoulder
20	Cylindrical Portion (i.e., Shank)
22	Nose Remaining Portion (or Non-Distorted Portion or Uncut Portion; i.e., portion between nose depressions)
24	Cavity
26	Driving Band
26A	Angled Driving Band
28	Relief Cut
28A	Angled (or Curved) Relief Cut
30	Base
32	Linear Portion
34	Tail Depression
36	Centerline of Tail Depression
38	Boat Tail
40	Housing
42	Insert
42A	First Insert
42B	Second Insert
42C	Third Insert
44	Longitudinal Axis (of Projectile, Insert, or Housing)
46	Tail Remaining Portion (or Non-Distorted Portion or Uncut Portion; i.e., portion between tail depressions)
48	Arrowhead (of Insert)
50	Stem (of Insert)
52	Lower Portion or Underside (of Arrowhead)
54	Lower Portion or Underside (of Stem)
56	Front (of Housing)
58	Receiving Portion (of Housing)
60	Rifling Marks
62	Pealed Portion (of Housing)
64	Rolled Portion (of Housing)
66	First Nose Portion (or Front Nose Portion)
68	Second Nose Portion (or Rear Nose Portion)
70	Rear Edge (of Housing)
72	Cutter Edge
92	Edge (of Nose Depression)
α	Alpha Angle, Angle of Nose Depression
β	Beta Angle
Δ	Delta Angle, Tail Depression Angle
θ	Theta Angle, Boat Tail Angle
γ	Gamma Angle, Angle between Angled Driving Band and Angled Relief Cut
σ	Sigma Angle, Angle between Drive Band and Relief Cut
D1	Cylindrical Portion Diameter (i.e., Caliber)
D2	Diameter of Relief Cut
D3	Diameter of Drive Band
D4	Diameter of Insert Stem
D5	Diameter of Arrowhead of Insert
L1	Length of Projectile
L2	Length of Nose Portion
L3	Length of Cylindrical Portion
L4	Length of Boat Tail
L5	Length of Housing
L6	Length of Insert
L6A	Length of First Insert
L6B	Length of Second Insert
L6C	Length of Third Insert
L7	Length of Broach-type Cut
L8	Length of First Nose Portion
L9	Length of Linear Portion
L10	Length of Second Nose Portion
W1	Width of Broach-type Cut

-continued

No.	Component
R1	Radius of Curvature of Ogive
R2	Radius of Curvature of Tangent Ogive
R3	Radius of Curvature of Secant Ogive
R4	Radius of Curvature of Nose Depression
R5	Radius of Curvature of Tail Depression
R6	Radius of Curvature of Relief Cut
R7	Radius of Curvature of Tip
R8	Radius of Curvature between Boat Tail and Base

[0072] It should be understood that the drawings are not necessarily to scale, and various dimensions may be altered. However, drawings that are to scale, are so marked or otherwise indicated. In certain instances, details that are not necessary for an understanding of the invention or that render other details difficult to perceive may have been omitted. It should be understood, of course, that the invention is not necessarily limited to the particular embodiments illustrated herein.

DETAILED DESCRIPTION

[0073] The accompanying drawings, which are incorporated in and constitute a part of the specification, illustrate embodiments of the invention and together with the general description of the invention given above, and the detailed description of the drawings given below, serve to explain the principals of this invention.

[0074] The attached drawings are generally to scale, although there may be certain exceptions. In certain instances, details that are not necessary for an understanding of the invention or that render other details difficult to perceive may have been omitted. It should be understood, of course, that the invention is not necessarily limited to the particular embodiments illustrated herein or specific dimensions.

[0075] Embodiments of pistol and rifle projectiles are provided herein. Some embodiments comprise three or more angled cuts or depressions and are manufactured with a circular or a flat cutter. The depressions or cuts are in part defined by multiple angles. The first angle of the depressions or cuts is the alpha angle, which can, in some embodiments, determine the sharpness of the tip and cutter edges and is best viewed from a side elevation view. The alpha angle can also control the depth of penetration of the projectile in its target and the amount of media the projectile will cast off during penetration. A steeper alpha angle will result in deeper penetration and a blunter alpha angle will create a wider wound path. In a preferred embodiment, the alpha angle is between 2 degrees and about 45 degrees; in a more preferred embodiment the alpha angle range is between about 5 and 30 degrees. In some embodiments, this angle is not constant.

[0076] Projectiles have been tested with increasing bluntness (i.e., a curve) and resulted in massive terminal ballistics trajectories. The beginning angle was nearly 0 degrees and the end angle was nearly 45 degrees off of centerline. This embodiment was manufactured by running a ball end mill at an angle (which can be the alpha angle) relative to the centerline of the projectile. The size of the cutter varies by caliber, projectile weight, and desired performance characteristics. In some embodiments, the radius of the cutter is roughly one caliber; a cutter smaller than one caliber will result in deeper troughs and sharper ridges.

[0077] The beta angle is the amount that the cut is off from a radius line as viewed from the front of the projectile. The beta angle and the alpha angle will determine the spin or rate of twist of the projectile during penetration. Typically, pistol barrel twist rates vary more than rifle barrel twist rates by manufacturer or brand. A barrel twist rate is expressed as one turn per a number of inches of barrel; a 1:10 or "1 in 10 inches" barrel twist means a bullet makes one rotation or twist while traveling 10 inches in a gun barrel. To obtain the greatest penetration possible, the alpha angle matches or exceeds the barrel rate of twist and is in the same direction. This allows the projectile to corkscrew or drill into the media. For most embodiments, the alpha angle is between about 7 to 15 degrees in a right-hand twist and alternating 4-25 degrees. In another embodiment, if a design objective is to have a pistol bullet that penetrates armor and then stops in tissue, the alpha angle will be in the opposite direction of the barrel twist (this condition is also referred to as a "reversed angle to twist rate" or "reversing the barrel twist rate"). From testing, the congruency of barrel twist rate has little effect on penetrating sheet metal, Kevlar, glass, and other hard surfaces. When the barrel twist rate is in the opposite direction as the alpha angle, it has a substantial effect on the depth of penetration in soft media. A reversed angle to barrel twist rate results in permanent wound channels with secondary wounds. A secondary wound is where an object, such as a bone, in the terminal media is cast off the projectile and creates a new wound path.

[0078] There are two basic embodiments of pistol projectiles: a two-piece projectile (which may be called a jacketed projectile) and non-jacketed projectile. The non-jacketed embodiment is not intended to change shape during terminal ballistics and has the deepest and straightest penetration. Reversing the barrel twist rate (i.e., an alpha angle in the opposite direction to the barrel twist rate) results in less penetration and greater destruction but not to the same degree as the two-piece projectile. However, typically only pistol projectiles have reversed twist rates because rifle projectiles tend to be unstable with a reversed twist rate. But, one embodiment includes a rifle projectile with a reversed twist rate. Some embodiments have a zero alpha angle and the projectile still displays the characteristics of penetrating hard surfaces and woven material well. FIGS. **1-2**, **12**, **20-23**, and **25-31** present non-jacketed pistol projectile embodiments.

[0079] FIGS. **3-11**, **13-19**, **24**, and **32-40** present rifle projectile embodiments.

[0080] FIGS. **3-11**, **13-19**, **24**, and **32-40** are scaled drawings of projectile embodiments. Intended users include big game hunters and long range target shooters. Among other things, these embodiments provide deep, straight penetration with transfer of energy. These embodiments may be manufactured of materials comprising brass, copper, lead, tungsten-carbide, and alloys associated therewith.

[0081] The fronts of various embodiments of projectiles are made up of several cuts that form troughs and ridges. The number of ridges may be equal to the number of lands and grooves in a barrel. Generally, the number of ridges should equal the number of lands and grooves in the barrel or be a multiple thereof.

[0082] In the rifle projectiles, the twist rate of the ridges will likely correlate to or be greater than the rate of twist in

the barrel although by no more than 1-2 degrees. In one preferred embodiment, the twist rate on the front of the projectile varies from 2-16 degrees; in a more preferred embodiment the twist rate on the front of the projectile varies between 4-12 degrees, depending on the rifle barrel's twist rate.

[0083] The barrel degree of twist may be referenced as a rate of twist such as 1 revolution in X amount of inches (e.g., 1 in 8" twist rate). The fins at the back of the rifle projectile correspond to-but are not necessarily in line with-the twist rate of the ridges at the front of the projectile. The design of the rifle projectile affects the flight of the projectile (external ballistics) and further affects the time in the barrel (internal ballistics). The depth and length of the twisting depressions, in some embodiments, is not as critical as the rate of twist. The twisting elements cannot extend through the center section or shaft of the projectile. Deeper twisting elements will create sharper ridges between the twisting depressions. The diameter of the trough will change with the caliber of the projectile. These twisting depressions will not only twist around the projectile, but will follow the convex shape of the front of the projectile. In some embodiments, the twist rate is approximately a 7 degree right-hand twist rate, corresponding to a 1-in-8 rate of twist.

[0084] When looking at a rifle projectile from a side elevation view, the curve from the tip to the elongated side wall of the cartridge is called the ogive, divided generally into three parts: the tip, the secant ogive and tangent ogive. As bullets are scalable, one refers to the sizes in calibers. Caliber is the diameter of the shaft. The entire ogive of the projectile may be greater in length than the length of two calibers and in other embodiments may be greater than the length of three calibers. This length will be determined by the maximum case length subtracted from the case overall length ("COL"). The COL is typically determined by the internal length of the magazine, but is sometimes limited by the throat of the chamber where the lands and the grooves disappear into the chamber.

[0085] As mentioned, the ogive is broken into three distinct parts. The tip is made of a cone with a non-curved profile and extends back for approximately the length of a half caliber or less. The tip is blended into a secant ogive that comprises the majority of the entire ogive. The secant ogive is based on a circle with a radius of approximately 8 times the caliber. There are grooves that run the length of the secant ogive and these grooves match identically the pitch and number of the lands and grooves of the rifling in the barrel. Typically, the secant ogive will be approximately two calibers in length depending on the intended rifle and chambering. These grooves that cut at a 7 to 8 degree angle through the secant ogive in many embodiments, are congruent with the rifling and are produced with a ball end mill and have smooth entrance and exit points. In the center of the secant ogive, the ball cut is at its deepest and forms a ridge with the cuts on either side running parallel to one another. The diameter of the cutter is approximately one third of a caliber. This sharp ridge runs the majority of the secant ogive and is intended to maintain the spin of the projectile in flight and aid in penetration during terminal ballistics. The last portion of the ogive, approximately half of a caliber in length, is comprised of a tangent ogive. The tangent ogive is the curve of a circle with a radius of approximately four calibers. The grooves cut in the secant ogive dissipate before the secant ogive's junction with the tangent ogive, thus ensuring that the grooves will never interact with the rifling, which would create a variable with the free bore portion of the projectile path during firing.

[0086] The shaft of the projectile will now be described. The shaft is the cylindrical center section that interfaces with the barrel and the case neck. The proportional length varies with desired weight and is composed of driving bands (i.e., ridges) and relief cuts (i.e., troughs). The junction of these surfaces is angular and smoothed to minimize interaction with the atmosphere during exterior ballistics. The depth of the relief cut is just beyond the inner dimension of the lands. There is a minimal number of driving bands, located at the front and back of the shaft with at least one more in the center section near the end of the case neck near the junction of the case's shoulder and neck. The relief cuts will lower the total friction in the barrel during internal ballistics.

[0087] The tail section of the bullet may include many geometric shapes, including a boat tail. The boat tail reduces diameter from the shaft in a cone shape at a 7.5 degree angle. In one embodiment, the boat tail is about 0.7 of a caliber in length. The boat tail can also extend, at the 7.5 degree reduction, to a point making it over two times a given caliber in length. This section may be grooved with a mill. These tail twisting depressions also run congruent with the pitch of the rifling. In a preferred embodiment, the tail twisting depressions are cut to between a 2-15 degree right-hand twist. In a more preferred embodiment, the tail twisting depressions are cut to between a 4-10 degree right-hand twist. In a most preferred embodiment, the tail twisting depressions are cut at a 7 to 8 degree right-hand twist. In one embodiment, the tail twisting depressions are cut at either a 7 or an 8 degree right-hand twist. In another embodiment, the tail twisting depressions are cut with a left-hand twist. These tail twisting depressions line up with the twisting depressions on the secant ogive, if extended. At the back of the boat tail, the tail twisting depressions come together and form sharp ridges that direct the atmosphere and maintain the projectile's flight. The tail twisting depressions end abruptly, shortly before the junction with the shaft.

[0088] The aforementioned tail twisting depressions provide interaction with the rapidly expanding propellant and help to twist the projectile through the rifling, thus greatly reducing friction with the barrel. These reductions in friction produce significantly higher than normal muzzle velocities and allow the barrel to heat at a significantly lower rate. The boat tails that extend all the way to a point may eliminate or reduce the audible supersonic crack of the bullet in flight. The twisting depressions at the front in combination with the tail twisting depressions at the back may reduce the rotational friction with the atmosphere and eliminate the whistle associated with the flight of a bullet. The twisting depressions (front and back) may also maintain the rate of twist during external ballistics, which may reduce the long range deterioration of accuracy.

[0089] The two-piece projectile embodiments are comprised of two parts: the housing and the insert. The housing is a cup that holds the insert and forms the bearing surface with the barrel. The housings may be formed by a lathe or swaging process and out of a material suitable for interaction with a barrel (brass or copper, for example). In some embodiments, the leading edge of the housing will intersect with the trailing edge of the ridge on the insert. In various embodiments, the troughs of the insert protrude below the mouth of the housing and into the cavity of the housing. This

is an important feature because these troughs are the mechanism that transfer the media into the housing and initiate the deformation or opening of the housing. This process will increase the wound channel and limit the penetration depth. When the barrel twist rate is the opposite (or "reverse") of the alpha angle, the process just described becomes exponentially more rapid and therefore the wound channel increases laterally but penetration is limited and controlled. The housing is in contact with the insert at the housing mouth and the portion at the back designed to hold the insert. The insert can be chemically bonded to the housing at the back or lower surface of the insert in some embodiments. In other embodiments, the insert is compression fit into the housing. There is generally a void or receiving portion through the center section of the housing. This void aids in the uniform deformation of the housing and aids the housing to open unilaterally. The material for the insert is made from, but not limited to, steel, aluminum, brass, and polymers. FIGS. **2**, **10**, **12-16**, **18**, **20**, **24-31**, **33-36**, and **38** are embodiments of two-piece projectiles.

[0090] Referring to FIGS. **1**A-**2**C, which are pistol projectile embodiments that, among other things, provide deep straight penetration. These projectiles **2** are different from the prior art because they can pierce armor and stop in soft tissue. The sharp tip **4** and sharp cutter edges **72** allow these projectiles **2** to cut through armor, including Kevlar. Additionally, the shoulders **18** of the projectile **2** enable the projectile **2** to stop in soft tissue because the shoulders slow the projectile **2** down once it hits soft tissue. Further, these projectiles **2** create a lot of cavitation in soft tissue, thus making a wound larger than it would be with a projectile of the prior art. Intended users of these projectiles comprise military and law enforcement.

[0091] The construction of these projectiles may be accomplished using a press or mill and lathe. One unique and innovative feature is the shape of the front of the projectile **2**, which has a slight radius coming off the bearing surface (the cylindrical portion **20** or the shaft) but is largely formed by angled or slightly twisting depressions **8** pointed to the front. The depressions **8** form troughs and ridges (and remaining portions **22** between the depressions) that possess an angle or a slight radius off the centerline **44** (longitudinal axis) of the projectile **2**. In some embodiments, the twist angle of the depressions **8** corresponds to (i.e., is equal to) or is greater than the barrel twist rate (i.e., the twist rate of the rifling in the barrel) and turns in the same direction as the barrel's rifling. In other embodiments, the twist angle of the depressions **8** is equal to or greater than the barrel twist rate and turns in the opposite direction as the barrel's rifling. These depressions **8** do not affect the projectile during internal ballistics but they greatly enhance the performance during external and/or terminal ballistics. In some embodiments, at the center of the tip **4** or a portion of the nose **6** proximate the tip **4**, the ridges **8** meet to form a cutting surface or cutting edge **72**. These edges **72** initiate a cut in the target, greatly reducing resistance through media such as sheet metal, fabrics, and soft armor. The twisting troughs **8** move media away from the projectile **2** further reducing resistance and promoting and maintaining the spin to ensure the projectile **2** penetrates deep and straight. The troughs **8** may rapidly move liquids and soft tissue away from the path of the projectile and therefore increase the wound channel.

[0092] In one embodiment of the pistol projectile, terminal ballistics traits are emphasized. The tip **4** of the projectile **2** is formed such that the trough **8** is at an angle (alpha or a) relative to the longitudinal axis **44** of the projectile. Due to magazine and chamber constraints, projectiles have a maximum length. The density of the material will determine this alpha angle because a steeper alpha angle cuts better, but has a lower weight. The steeper alpha angle will also transfer media at a greater rate into the housing for a faster opening and expansion upon impact with the terminal media for the two-piece projectiles.

[0093] In some embodiments, the twist rate of the ridges can equal to or exceeds, by up to double, the twist rate of the barrel. In one embodiment, the projectile would increase the rate of twist once it struck the terminal media. In one embodiment, an insert with a counter twist to (i.e., in the opposite direction of) the rifling is provided, therefore limiting penetration once the projectile cuts through the outer layer of its target. The twist rate in the insert may also be reversed (i.e., in the opposite direction to the barrel twist). Twist rates in most handguns, run from 4-7 degrees, but could be between 2-10 degrees.

[0094] FIGS. **1**A-E show a projectile **2** according to a first embodiment. FIG. **1**A is a perspective view of the projectile **2**. FIG. **1**B is a side elevation view of the projectile **2**. FIG. **1**C is another side elevation view of the projectile **2**. FIG. **1**D is a top plan view of the projectile **2**. FIG. **1**E is a cross-sectional view of the projectile **2** taken along cut E-E of FIG. **1**D. Note that FIGS. **1**A-C are to scale.

[0095] The projectile **2** is for pistols and comprises a tip **4** on one end opposite a base **30** on the other end. The projectile **2** comprises a nose portion **6** and a cylindrical portion **20** (also called a shank). The nose portion **6** includes nose depressions **8** (also called cutouts or troughs) and nose remaining portions **22** (also called non-distorted portions or uncut portions) between two nose depressions **8**. The remaining portions **22** are the uncut portions having the projectile's original ogive. The remaining portions **22** have a generally triangular shape with the tip of the triangle positioned proximate to the tip **4** of the projectile and the base of the triangle positioned proximate to the rear of the nose **6** and the forward portion of the cylindrical portion **20**. A first edge is formed between a nose depression **8** and a remaining portion **22** and a second edge proximate the tip **4** is formed between two nose depressions **8**. The first edge and/or the second edge may be referred to as a cutter edge **72** in some embodiments. The nose depressions **8** terminate in a substantially flat shoulder **18** proximate to the junction between the nose portion **6** and the cylindrical portion **20**. The nose depressions **8** have a curved shape meaning that the trough or bottom surface of the nose depression **8** is curved and has a radius of curvature R**4**. In one embodiment, the nose depressions are cut using a ⅜ inch flat end mill.

[0096] The longitudinal axis **44** of the projectile **2** is shown in FIG. **1**C. Accordingly, the angle α of the nose depressions **8** can be measured relative to the longitudinal axis **44** and the centerline **10** of the nose depression **8**. In some embodiments, the angle α is measured relative to the original ogive of the projectile nose portion **6**. Alternatively, the orientation of the depressions **8** or cutout portions can be oriented or measured with respect to the ogive of the remaining portion. In some embodiments, all nose depressions **8** have the same angle α. In other embodiments, each nose depression **8** has a different angle α. In still other embodiments, some nose depressions **8** have the same angle a while other nose depressions **8** have different angles α. In

the embodiment shown, the nose depressions **8** are right-hand nose depressions **8** because the angle α is positioned to the right of the longitudinal axis **44**. Further, when looking at the projectile from a top plan view (FIG. **1**D), the nose depressions **8** appear to turn in a counter-clockwise direction. In one embodiment, the projectile **2** has at least three nose depressions **8**. However, the projectile **2** can have more or fewer nose depressions **8**.

[0097] In one embodiment, the radius of curvature R**4** of the nose depressions **8** is between about 1/16 inches and about 0.750 inches. In a preferred embodiment, the radius of curvature R**4** of the nose depressions **8** is between about 3/32 inches and about 3/8 inches. In a more preferred embodiment, the radius of curvature R**4** of the nose depressions **8** is about 0.1875 inches. In one embodiment, the length L**1** of the projectile **2** is between about 0.400 inches and about 0.900 inches. In a preferred embodiment, the length L**1** of the projectile **2** is between about 0.550 inches and about 0.750 inches. In a more preferred embodiment, the length L**1** of the projectile **2** is about 0.643 inches. In one embodiment, the length L**2** of the nose portion **6** is between about 0.150 inches and about 0.500 inches. In a preferred embodiment, the length L**2** of the nose portion **6** is between about 0.250inches and about 0.400 inches. In a more preferred embodiment, the length L**2** of the nose portion **6** is about 0.343 inches. In one embodiment, the length L**3** of the cylindrical portion **20** is between about 0.100 inches and about 0.500 inches. In a preferred embodiment, the length L**3** of the cylindrical portion **20** is between about 0.200 inches and about 0.400inches. In a more preferred embodiment, the length L**3** of the cylindrical portion **20** is about 0.300 inches. The diameter D**1** of the projectile **2** (also called the caliber) varies according to the various embodiments. In one embodiment, the diameter D**1** of the projectile **2** is between about 0.200 inches and about 0.500 inches. In a preferred embodiment, the diameter D**1** of the projectile **2** is between about 0.300 inches and about 0.450 inches. In the embodiment shown, the diameter D**1** of the projectile **2** is about 0.355inches (about 9 mm). In another preferred embodiment, the diameter D**1** of the projectile **2** is about 0.400 inches. In yet another preferred embodiment, the diameter D**1** of the projectile **2** is about 0.450 inches. In one embodiment, the angle α of the nose depressions **8** is between about 5 degrees and about 35 degrees. In a preferred embodiment, the angle α of the nose depressions **8** is between about 15 degrees and about 25 degrees. In a more preferred embodiment, the angle α of the nose depressions **8** is about 20 degrees.

[0098] FIGS. **2**A-C show a projectile according to a second embodiment of the invention. This projectile is similar to the projectile of FIG. **1**, except that this projectile **2** is two pieces: a nose portion **6** insert that is compression fit into a cylindrical portion **20** housing. Each piece may be a different material in one embodiment. For example, the nose portion **6** insert is made of steel and the cylindrical portion **20** housing is made of brass. However, the projectile **2** can be made of any projectile or bullet material, such as any metal alloy, brass, steel, tungsten, polymers, ceramics, aluminum, Inconel, or any other material known in the art. FIG. **2**A is a perspective view of the projectile **2**. FIG. **2**B is a side elevation view of the projectile **2**. FIG. **2**C is a top plan view of the projectile **2**. Note that FIGS. **2**A-C are to scale.

[0099] The projectile **2** comprises a tip **4** on one end opposite a base **30** on the other end. The projectile **2** comprises a nose portion **6** and a cylindrical portion **20**. The nose portion **6** includes nose depressions **8** and nose remaining portions **22** between the nose depressions **8**. The remaining portions **22** are the uncut portions having the projectile's original ogive. The remaining portions **22** have a generally triangular shape with the tip of the triangle positioned proximate to the tip **4** of the projectile **2** and the base of the triangle positioned proximate to the rear of the nose **6** and the forward portion of the cylindrical portion **20**. A first edge is formed between a nose depression **8** and a remaining portion **22** and a second edge proximate the tip **4** is formed between two nose depressions **8**. The first edge and/or the second edge may be referred to as a cutter edge **72** in some embodiments. The nose depressions **8** terminate in a substantially flat shoulder **18**. The nose depressions **8** have a curved shape meaning that the trough or bottom of the nose depression **8** is curved and has a radius of curvature R**4**. In one embodiment, the nose depressions are cut using a 3/8 inch flat end mill.

[0100] The longitudinal axis **44** of the projectile **2** is shown in FIG. **2**B. Accordingly, the angle α of the nose depressions **8** can be measured relative to the longitudinal axis **44**. In some embodiments, the angle α is measured relative to the original ogive of the projectile nose portion **6**. In some embodiments, all nose depressions **8** have the same angle α. In other embodiments, each nose depression **8** has a different angle α. In still other embodiments, some nose depressions **8** have the same angle α while other nose depressions **8** have different angles α. In the embodiment shown, the nose depressions **8** are left-hand nose depressions **8** because the angle α is positioned to the left of the longitudinal axis **44**. Further, when looking at the projectile from a top plan view (FIG. **2**C), the nose depressions **8** appear to turn in a clockwise direction. In one embodiment, the projectile **2** has at least three nose depressions **8**. However, the projectile **2** can have more or fewer nose depressions **8**.

[0101] In one embodiment, the radius of curvature R**4** of the nose depressions **8** is between about 1/16 inches and about 0.750 inches. In a preferred embodiment, the radius of curvature R**4** of the nose depressions **8** is between about 3/32 inches and about 3/8 inches. In a more preferred embodiment, the radius of curvature R**4** of the nose depressions **8** is about 0.1875 inches. In one embodiment, the length L**1** of the projectile **2** is between about 0.400 inches and about 0.900 inches. In a preferred embodiment, the length L**1** of the projectile **2** is between about 0.550 inches and about 0.750 inches. In a more preferred embodiment, the length L**1** of the projectile **2** is about 0.643 inches. In one embodiment, the length L**2** of the nose portion **6** is between about 0.150 inches and about 0.500 inches. In a preferred embodiment, the length L**2** of the nose portion **6** is between about 0.250inches and about 0.400 inches. In a more preferred embodiment, the length L**2** of the nose portion **6** is about 0.343 inches. In one embodiment, the length L**3** of the cylindrical portion **20** is between about 0.100 inches and about 0.500 inches. In a preferred embodiment, the length L**3** of the cylindrical portion **20** is between about 0.200 inches and about 0.400inches. In a more preferred embodiment, the length L**3** of the cylindrical portion **20** is about 0.300 inches. The diameter D**1** of the projectile **2** (also called the caliber) varies according to the various embodiments. In one embodiment, the diameter D**1** of the projectile **2** is between about 0.200 inches and about 0.500 inches. In a

preferred embodiment, the diameter D1 of the projectile **2** is between about 0.300 inches and about 0.450 inches. In the embodiment shown, the diameter D1 of the projectile **2** is about 0.355inches (about 9 mm). In another preferred embodiment, the diameter D1 of the projectile **2** is about 0.400 inches. In yet another preferred embodiment, the diameter D1 of the projectile **2** is about 0.450 inches. In one embodiment, the angle α of the nose depressions **8** is between about 5 degrees and about 35 degrees. In a preferred embodiment, the angle a of the nose depressions **8** is between about 15 degrees and about 25 degrees. In a more preferred embodiment, the angle α of the nose depressions **8** is about 20 degrees.

[0102] FIGS. **3**A-**11**F are projectiles with unique and novel tail geometries. Some embodiments of the present invention include tail depressions **34** cut into the boat tail **38** of the projectile **2**. The tail design is almost entirely for the internal ballistics of the projectile, i.e., while the projectile is in the gun barrel. The tail depressions **34** act like a propeller to make the projectile **2** rotate. If the projectile **2** is rotating at the same twist rate or a similar twist rate to the barrel's twist rate, then the projectile **2** will barely slow down when it hits the lands and grooves in the barrel. This reduces the pressure exerted on the barrel of the gun and reduces the wear on the barrel. Typically, if a gun barrel has four lands and grooves, then the projectile will have four tail depressions **34**. The same is true for fewer or more lands and grooves, i.e., the number of lands and grooves typically equals the number of tail depressions **34**. Additionally, the tail depressions **34** are defined by a delta angle Δ. In one embodiment, the delta angle Δ is congruent to or greater than the twist rate. Nominal twist rates will be between about 3.5 and 9.0 degrees. The delta angle Δ of the tail depressions **34** may exceed the twist rate by about 10.0 degrees. An optimal delta angle will be no more than about 1.5 degrees beyond the rate of twist angle. FIG. **9** has a boat tail **38** with depressions **34** that also help the projectile **2** perform better during terminal ballistics because the boat tail **38** with depressions **34** keeps the projectile **2** flying straight after it enters the soft tissue of an animal.

[0103] FIGS. **3**A-E show a projectile **2** according to a third embodiment of the invention. FIG. **3**A is a perspective view of the projectile **2**. FIG. **3**B is a side elevation view of the projectile **2**. FIG. **3**C is a top plan view of the projectile **2**. FIG. **3**D is a cross section of the projectile **2** taken along cut D-D in FIG. **3**C. FIG. **3**E is an enlarged view of a portion of the projectile **2** shown in FIG. **3**B. Note that FIGS. **3**A-**3**D are to scale.

[0104] The projectile **2** comprises a tip **4** on one end opposite a base **30** on the other end. The projectile **2** comprises a nose portion **6** proximate the tip **4** on one end and interconnected to a cylindrical portion **20** on the other end. The cylindrical portion **20** is interconnected to a boat tail **38** on the end opposite the nose. The boat tail **38** terminates in the base **30** with a radius of curvature R**8** between the boat tail **38** and the base **30**. In alternate embodiments, the driving bands **26**A vary in number, comprising one driving band **26**A, a plurality of driving bands **26**A, two driving bands **26**A, three driving bands **26**A, and four or more driving bands **26**A.

[0105] The cylindrical portion **20** can comprise multiple angled relief bands **28**A and angled driving bands **26**A. The driving bands **26**A alternate with the relief bands **28**A. The angles between the driving bands **26**A and relief cuts **28**A (relative to the horizontal) are between about 7 degrees and about 10 degrees. In one embodiment, angles between the driving bands **26**A and relief cuts **28**A (relative to the horizontal) are about 7.5 degrees. In another embodiment, angles between the driving bands **26**A and relief cuts **28**A (relative to the horizontal) are about 8.5 degrees. In one embodiment, the weight of the projectile is about 154 grams.

[0106] In one embodiment, the radius of curvature R**2** of the tangent ogive is between about 2.0 inches and about 5.0 inches. In a preferred embodiment, the radius of curvature R**2** of the tangent ogive is between about 3.0 inches and about 4.0 inches. In a more preferred embodiment, the radius of curvature R**2** of the tangent ogive is about 3.5 inches. In one embodiment, the radius of curvature R**3** of the secant ogive is between about 0.5inches and about 1.5 inches. In a preferred embodiment, the radius of curvature R**3** of the secant ogive is between about 0.75 inches and about 1.25 inches. In a more preferred embodiment, the radius of curvature R**3** of the secant ogive is about 1.00 inch. In one embodiment, the radius of curvature R**7** of the tip **4** is between about 0.030 inches and about 0.005 inches. In a preferred embodiment, the radius of curvature R**7** of the tip **4** is between about 0.020 inches and about 0.010 inches. In a more preferred embodiment, the radius of curvature R**7** of the tip **4** is about 0.015 inches. In one embodiment, the radius of curvature R**8** between the boat tail **38** and the base **30** is between about 0.035 inches and about 0.010 inches. In a preferred embodiment, the radius of curvature R**8** between the boat tail **38** and the base **30** is between about 0.025 inches and about 0.015 inches. In a more preferred embodiment, the radius of curvature R**8** between the boat tail **38** and the base **30** is about 0.020 inches.

[0107] In one embodiment, the length L**1** of the projectile **2** is between about 1.25 inches and about 1.75 inches. In a preferred embodiment, the length L**1** of the projectile **2** is between about 1.4 inches and about 1.5 inches. In a more preferred embodiment, the length L**1** of the projectile **2** is about 1.435 inches. In one embodiment, the length L**2** of the nose portion **6** is between about 0.50 inches and about 1.10 inches. In a preferred embodiment, the length L**2** of the nose portion **6** is between about 0.75 inches and about 1.00 inch. In a more preferred embodiment, the length L**2** of the nose portion **6** is about 0.8633 inches. In one embodiment, the length L**3** of the cylindrical portion **20** is between about 0.25 inches and about 0.50 inches. In a preferred embodiment, the length L**3** of the cylindrical portion **20** is between about 0.30 inches and about 0.40 inches. In a more preferred embodiment, the length L**3** of the cylindrical portion **20** is about 0.322 inches. In one embodiment, the length L**4** of the boat tail **38** is between about 0.10 inches and about 0.35 inches. In a preferred embodiment, the length L**4** of the boat tail **38** is between about 0.15 inches and about 0.25 inches. In a more preferred embodiment, the length L**4** of the boat tail **38** is about 0.215 inches. The diameter D**1** of the projectile **2** (also called the caliber) varies according to the various embodiments. In one embodiment, the diameter D**1** of the projectile **2** is between about 0.220 inches and about 0.450 inches. In a preferred embodiment, the diameter D**1** of the projectile **2** is between about 0.290 inches and about 0.350 inches. In the embodiment shown, the diameter D**1** of the projectile **2** is about 0.3080inches. In one embodiment, the diameter D**2** of the angled relief cut **28**A is between about 0.20 inches and about 0.40 inches. In a preferred embodiment, the diameter D**2** of the angled relief cut **28**A is

between about 0.25 inches and about 0.31 inches. In the embodiment shown, the diameter D2 of the angled relief cut **28**A is about 0.298 inches. In one embodiment, the diameter D3 of the angled driving band **26**A is between about 0.25inches and about 0.32 inches. In a preferred embodiment, the diameter D3 of the angled driving band **26**A is between about 0.30 inches and about 0.31 inches. In the embodiment shown, the diameter D3 of the angled driving band **26**A is about 0.307 inches. In one embodiment, the angle θ of the boat tail **38** is between about 5 degrees and about 10degrees. In a preferred embodiment, the angle θ of the boat tail **38** is between about 6.5degrees and about 8.0 degrees. In a more preferred embodiment, the angle θ of the boat tail **38** is about 7 degrees.

[0108] In alternate embodiments, the projectile **2** can have nose depressions and/or tail depressions. This projectile **2** is different from the prior art because it can pierce armor and fly for an extended range. This projectile **2** is also capable of flying supersonic. The projectile **2** is extremely accurate even at long distances.

[0109] FIGS. **4**A-C show a projectile according to a fourth embodiment of the invention. FIG. **4**A is a bottom perspective view of the projectile **2**. FIG. **4**B is a side elevation view of the projectile **2**. FIG. **4**C is a bottom plan view of the projectile **2**. Note that FIGS. **4**A-C are to scale.

[0110] The projectile **2** comprises a tip **4** on one end opposite a base **30** on the other end. The projectile **2** comprises a nose portion **6**, a cylindrical portion **20**, and a boat tail **38**. The nose portion **6** includes nose depressions **8** and nose remaining portions **22** between the nose depressions **8**. The remaining portions **22** are the uncut portions having the projectile's original ogive. The nose depressions **8** run from the tip **4** to a portion of the projectile **2** proximate the central portion **20**. The nose depressions **8** have a curved shape meaning that the trough or bottom of the nose depression **8** is curved and has a radius of curvature R**4**. The boat tail **34** includes tail depressions **34** and tail remaining portions between the tail depressions **34**. The remaining portions are the uncut portions. The tail depressions **34** run from the base **30** to a portion of the boat tail **38**. The tail depressions **34** have a curved shape meaning that the trough or bottom of the tail depression **34** is curved and has a radius of curvature. In one embodiment, the nose depressions **8** are cut using a 3/16 inch to a 3/8 inch ball end mill and the tail depressions **34** are cut using a 1/8 inch ball end mill. The cylindrical portion **20** of the projectile can also comprise driving bands **26** and relief cuts **28**. Some embodiments have one or more driving bands **26** and relief cuts **28**. The widths of the driving bands **26** and relief cuts **28** can vary or they can all be the same.

[0111] The longitudinal axis **44** of the projectile **2** is shown in FIG. **4**B. Accordingly, the angle α of the nose depressions **8** can be measured relative to the longitudinal axis **44**. In some embodiments, the angle α is measured relative to the original ogive of the projectile nose portion **6**. In some embodiments, all nose depressions **8** have the same angle α. In other embodiments, each nose depression **8** has a different angle α. In still other embodiments, some nose depressions **8** have the same angle α while other nose depressions **8** have different angles α. In the embodiment shown, the nose depressions **8** are right-hand nose depressions **8** because the angle α is positioned to the right of the longitudinal axis **44**. In one embodiment, the projectile **2** has at least three nose depressions **8**. However, the projectile **2** can have more or fewer nose depressions **8**. Accordingly, the angle Δ of the tail depressions **34** can be measured by measuring the angle of the tail depression centerline **36** relative to the longitudinal axis **44**. In some embodiments, all tail depressions **34** have the same angle Δ. In other embodiments, each tail depression **34** has a different angle Δ. In still other embodiments, some tail depressions **34** have the same angle Δ while other tail depressions **34** have different angles Δ. In the embodiment shown, the tail depressions **34** are right-hand tail depressions **34** because the angle Δ is positioned to the right of the longitudinal axis **44**. Further, when looking at the projectile **2** from a bottom plan view (FIG. **4**C), the tail depressions **34** appear to turn in a counterclockwise direction. In one embodiment, the projectile **2** has at least 6 tail depressions **34**. However, the projectile **2** can have more or fewer tail depressions **34**.

[0112] In one embodiment, the radius of curvature R**2** of the tangent ogive is between about 2.0 inches and about 5.0 inches. In a preferred embodiment, the radius of curvature R**2** of the tangent ogive is between about 3.0 inches and about 4.0 inches. In a more preferred embodiment, the radius of curvature R**2** of the tangent ogive is about 3.5 inches. In one embodiment, the radius of curvature R**3** of the secant ogive is between about 0.5inches and about 1.5 inches. In a preferred embodiment, the radius of curvature R**3** of the secant ogive is between about 0.75 inches and about 1.25 inches. In a more preferred embodiment, the radius of curvature R**3** of the secant ogive is about 1.00 inch. In one embodiment, the radius of curvature R**4** of the nose depressions **8** is between about 0.05inches and about 0.15 inches. In a preferred embodiment, the radius of curvature R**4** of the nose depressions **8** is between about 0.75 inches and about 0.1 inches. In a more preferred embodiment, the radius of curvature R**4** of the nose depressions **8** is about 0.09375 inches. In one embodiment, the radius of curvature of the tail depression **34** is between about 0.040inches and about 0.080 inches. In a preferred embodiment, the radius of curvature of the tail depression **34** is between about 0.030 inches and about 0.050 inches. In a more preferred embodiment, the radius of curvature of the tail depression **34** is about 0.0625inches. In one embodiment, the length L**1** of the projectile **2** is between about 1.50 inches and about 2.75 inches. In a preferred embodiment, the length L**1** of the projectile **2** is between about 2.0 inches and about 2.3 inches. In a more preferred embodiment, the length L**1** of the projectile **2** is about 2.150 inches. In one embodiment, the length L**2** of the nose portion **6** is between about 0.600 inches and about 1.00 inch. In a preferred embodiment, the length L**2** of the nose portion **6** is between about 0.700 inches and about 0.900 inches. In a more preferred embodiment, the length L**2** of the nose portion **6** is about 0.800 inches. In one embodiment, the length L**3** of the cylindrical portion **20** is between about 0.20 inches and about 0.60 inches. In a preferred embodiment, the length L**3** of the cylindrical portion **20** is between about 0.30 inches and about 0.50 inches. In a more preferred embodiment, the length L**3** of the cylindrical portion **20** is about 0.400 inches. In one embodiment, the length L**4** of the boat tail **38** is between about 0.50 inches and about 1.50 inches. In a preferred embodiment, the length L**4** of the boat tail **38** is between about 0.75 inches and about 1.25 inches. In a more preferred embodiment, the length L**4** of the boat tail **38** is about 0.950 inches. The diameter D**1** of the projectile **2** (also called the caliber) varies according the various embodi-

ments. In one embodiment, the diameter D**1** of the projectile **2** is between about 0.220 inches and about 0.45 inches. In a preferred embodiment, the diameter D**1** of the projectile **2** is between about 0.29 inches and about 0.32 inches. In the embodiment shown, the diameter D**1** of the projectile **2** is about 0.308 inches. In one embodiment, the angle α of the nose depressions **8** is between about 2 degrees and about 10 degrees. In a preferred embodiment, the angle α of the nose depressions **8** is between about 4 degrees and about 7 degrees. In a more preferred embodiment, the angle α of the nose depressions **8** is about 5.5 degrees. In one embodiment, the angle Δ of the boat tail **38** is between about 5 degrees and about 10 degrees. In a preferred embodiment, the angle Δ of the boat tail **38** is between about 6 degrees and about 9 degrees. In a more preferred embodiment the angle Δ of the boat tail **38** is about 7.5 degrees.

[0113] This projectile **2** is different from the prior art because it can pierce armor and stop in soft tissue. The intended users of the projectile are African big game hunters. The attributes of this projectile are deep straight penetration with transfer of energy. The projectile is comprised of brass, copper, bronze, tungsten-carbide, alloys of these metals, or any material known in the art, including plastics and ceramics.

[0114] FIGS. **5**A-C show a projectile according to a fifth embodiment of the invention. FIG. **5**A is a bottom perspective view of the projectile **2**. FIG. **5**B is a side elevation view of the projectile **2**. FIG. **5**C is a bottom plan view of the projectile **2**. Note that FIGS. **5**A-C are to scale.

[0115] The projectile **2** comprises a tip **4** on one end opposite a base **30** on the other end. The projectile **2** comprises a nose portion **6**, a cylindrical portion **20**, and a boat tail **38**. The boat tail **38** includes tail depressions **34** and tail remaining portions **46** between the tail depressions **34**. The remaining portions **46** are the uncut portions. The tail depressions **34** run from the base **30** to a portion of the boat tail **38**. The tail depressions **34** have a curved shape meaning that the trough or bottom of the tail depression **34** is curved and has a radius of curvature R**5**. In one embodiment, the tail depressions **34** are cut using a ⅜ inch flat end mill. The cylindrical portion **20** of the projectile can also comprise angled driving bands **26**A and angled relief cuts **28**A. Some embodiments have one or more angled driving bands **26**A and angled relief cuts **28**A. The widths of the angled driving bands **26**A and angled relief cuts **28**A can vary or they can all be the same. The angled driving bands **26**A alternate with the angled relief cuts **28**A. The angles between the driving bands **26**A and relief cuts **28**A (relative to the horizontal) are between about 7 degrees and about 10degrees. In one embodiment, angles between the driving bands **26**A and relief cuts **28**A (relative to the horizontal) are about 7.5 degrees. In another embodiment, the angles between the driving bands **26**A and relief cuts **28**A (relative to the horizontal) are about 8.5 degrees.

[0116] The angle Δ of the centerline **36** of the tail depressions **34** can be measured relative to the longitudinal axis **44**. In some embodiments, all tail depressions **34** have the same angle Δ. In other embodiments, each tail depression **34** has a different angle Δ. In still other embodiments, some tail depressions **34** have the same angle Δ while other tail depressions **34** have different angles Δ. In the embodiment shown, the tail depressions **34** are right-hand tail depressions **34** because the angle Δ is positioned to the right of the longitudinal axis **44**. Further, when looking at the projectile from a bottom plan view (FIG. **5**C), the tail depressions **34** appear to turn in a counter-clockwise direction. In one embodiment, the projectile **2** has at least six tail depressions **34**. In the embodiment shown, the projectile **2** has four tail depressions **34**. However, the projectile **2** can have more or fewer tail depressions **34**.

[0117] In one embodiment, the radius of curvature R**2** of the tangent ogive is between about 2.0 inches and about 5.0 inches. In a preferred embodiment, the radius of curvature R**2** of the tangent ogive is between about 3.0 inches and about 4.0 inches. In a more preferred embodiment, the radius of curvature R**2** of the tangent ogive is about 3.5 inches. In one embodiment, the radius of curvature R**3** of the secant ogive is between about 0.5inches and about 1.5 inches. In a preferred embodiment, the radius of curvature R**3** of the secant ogive is between about 0.75 inches and about 1.25 inches. In a more preferred embodiment, the radius of curvature R**3** of the secant ogive is about 1.00 inch. In one embodiment, the radius of curvature R**7** of the tip **4** is between about 0.030 inches and about 0.005 inches. In a preferred embodiment, the radius of curvature R**7** of the tip **4** is between about 0.020 inches and about 0.010 inches. In a more preferred embodiment, the radius of curvature R**7** of the tip **4** is about 0.015 inches.

[0118] In one embodiment, the length L**1** of the projectile **2** is between about 1.0 inch and about 1.6 inches. In a preferred embodiment, the length L**1** of the projectile **2** is between about 1.15 inches and about 1.45 inches. In a more preferred embodiment, the length L**1** of the projectile **2** is about 1.30 inches. In one embodiment, the length L**2** of the nose portion **6** is between about 0.75 inches and about 1.25 inches. In a preferred embodiment, the length L**2** of the nose portion **6** is between about 0.80 inches and about 1.0 inch. In a more preferred embodiment, the length L**2** of the nose portion **6** is about 0.900 inches. In one embodiment, the length L**3** of the cylindrical portion **20** is between about 0.10 inches and about 0.40 inches. In a preferred embodiment, the length L**3** of the cylindrical portion **20** is between about 0.20 inches and about 0.30 inches. In a more preferred embodiment, the length L**3** of the cylindrical portion **20** is about 0.225 inches. In one embodiment, the length L**4** of the boat tail **38** is between about 0.10 inches and about 0.30 inches. In a preferred embodiment, the length L**4** of the boat tail **38** is between about 0.15 inches and about 0.20 inches. In a more preferred embodiment, the length L**4** of the boat tail **38** is about 0.175 inches. The diameter D**1** of the projectile **2** varies according the various embodiments. In one embodiment, the diameter D**1** of the projectile **2** is between about 0.20 inches and about 0.40 inches. In a preferred embodiment, the diameter D**1** of the projectile **2** is between about 0.25 inches and about 0.35 inches. In the embodiment shown, the diameter D**1** of the projectile **2** is about 0.300 inches. In one embodiment, the angle θ of the boat tail **38** is between about 5 degrees and about 10 degrees. In a preferred embodiment, the angle θ of the boat tail **38** is between about 6.5 degrees and about 8.0degrees. In a more preferred embodiment, the angle θ of the boat tail **38** is about 7.5degrees. In one embodiment, the angle Δ of the tail depressions is between about 5 degrees and about 10 degrees. In a preferred embodiment, the angle Δ of the tail depressions is between about 7.0 degrees and about 8.0 degrees. In a more preferred embodiment the angle Δ of the tail depressions **34** is about 7.8 degrees. In one embodiment, angles between the driving bands **26**A and relief cuts **28**A

(relative to the horizontal) are about 7.5 degrees. In another embodiment, angles between the driving bands **26**A and relief cuts **28**A (relative to the horizontal) are about 8.5 degrees.

[0119] In alternate embodiments, the projectile **2** can have nose depressions and/or tail depressions. This projectile **2** is different from the prior art because it can pierce armor fly an extended range. This projectile is also capable of flying supersonic. It is also extremely accurate even at long distances.

[0120] FIGS. **6**A-C show a projectile according to a sixth embodiment of the invention. FIG. **6**A is a bottom perspective view of the projectile **2**. FIG. **6**B is a side elevation view of the projectile **2**. FIG. **6**C is a bottom plan view of the projectile **2**. Note that FIGS. **6**A-C are to scale.

[0121] The projectile **2** comprises a tip **4** on one end opposite a base **30** on the other end. The projectile **2** comprises a nose portion **6**, a cylindrical portion **20**, and a boat tail **38**. The nose portion **6** includes nose depressions **8** and nose remaining portions **22** between two nose depressions **8**. The remaining portions **22** are the uncut portions having the projectile's original ogive. The nose depressions **8** run from the tip **4** to a portion of the projectile proximate the central portion **20**. The nose depressions **8** have a curved shape meaning that the trough or bottom of the nose depression **8** is curved and has a radius of curvature. The boat tail **34** includes tail depressions **34** and tail remaining portions **46** between the tail depressions **34**. The remaining portions **46** are the uncut portions. The tail depressions **34** run from the base **30** to a portion of the boat tail **38**. The tail depressions **34** have a curved shape meaning that the trough or bottom of the tail depression **34** is curved and has a radius of curvature R**5**. In one embodiment, the nose depressions **8** are cut using a 3/16 inch to a 3/8 inch ball end mill and the tail depressions **34** are cut using a 3/8 inch flat end mill. The cylindrical portion **20** of the projectile can also comprise driving bands **26** and relief cuts **28**. Some embodiments have one or more driving bands **26** and relief cuts **28**. The widths of the driving bands **26** and relief cuts **28** can vary or they can all be the same.

[0122] The longitudinal axis **44** of the projectile **2** is shown in FIG. **6**B. Accordingly, the angle α of the nose depressions **8** can be measured relative to the longitudinal axis **44**. In some embodiments, the angle α is measured relative to the original ogive of the projectile nose portion **6**. In some embodiments, all nose depressions **8** have the same angle α. In other embodiments, each nose depression **8** has a different angle α. In still other embodiments, some nose depressions **8** have the same angle α while other nose depressions **8** have different angles α. In the embodiment shown, the nose depressions **8** are right-hand nose depressions **8** because the angle α is positioned to the right of the longitudinal axis **44**. In one embodiment, the projectile **2** has at least three nose depressions **8**. However, the projectile **2** can have more or fewer nose depressions **8**. The angle of the tail depressions **34** can also be measured relative to the longitudinal axis **44**. In some embodiments, all tail depressions **34** have the same angle. In other embodiments, each tail depression **34** has a different angle. In still other embodiments, some tail depressions **34** have the same angle while other tail depressions **34** have different angles. In the embodiment shown, the tail depressions **34** are right-hand tail depressions **34** because the angle is positioned to the right of the longitudinal axis **44**. Further, when looking at the projectile from a bottom plan view (FIG. **6**C), the tail depressions **34** appear to turn in a counterclockwise direction. In one embodiment, the projectile **2** has at least six tail depressions **34**. However, the projectile **2** can have more or fewer tail depressions **34**.

[0123] In one embodiment, the radius of curvature of the nose depression **8** is between about 0.20 inches and about 0.05 inches. In a preferred embodiment, the radius of curvature of the nose depression **8** is between about 0.15 inches and about 0.07 inches. In a more preferred embodiment, the radius of curvature of the nose depression **8** is about 0.09375 inches. In one embodiment, the radius of curvature R**5** of the tail depressions **34** is between about 0.10 inches and about 0.30 inches. In a preferred embodiment, the radius of curvature R**5** of the tail depressions **34** is between about 0.15 inches and about 0.20inches. In a more preferred embodiment, the radius of curvature R**5** of the tail depressions **34** is about 0.1875 inches. In one embodiment, the length L**1** of the projectile **2** is between about 1.0 inch and about 2.5 inches. In a preferred embodiment, the length L**1** of the projectile **2** is between about 1.5 inches and about 2.0 inches. In a more preferred embodiment, the length L**1** of the projectile **2** is about 1.80 inches. In one embodiment, the length L**2** of the nose portion **6** is between about 0.50 inches and about 1.0 inch. In a preferred embodiment, the length L**2** of the nose portion **6** is between about 0.70 inches and about 0.80 inches. In a more preferred embodiment, the length L**2** of the nose portion **6** is about 0.750 inches. In one embodiment, the length L**3** of the cylindrical portion **20** is between about 0.40 inches and about 0.90 inches. In a preferred embodiment, the length L**3** of the cylindrical portion **20** is between about 0.55 inches and about 0.75 inches. In a more preferred embodiment, the length L**3** of the cylindrical portion **20** is about 0.65inches. In one embodiment, the length L**4** of the boat tail **38** is between about 0.20 inches and about 0.60 inches. In a preferred embodiment, the length L**4** of the boat tail **38** is between about 0.30 inches and about 0.50 inches. In a more preferred embodiment, the length L**4** of the boat tail **38** is about 0.400 inches. The diameter D**1** of the projectile **2** (also called the caliber) varies according the various embodiments. In one embodiment, the diameter D**1** of the projectile **2** is between about 0.22 inches and about 0.50 inches. In a preferred embodiment, the diameter D**1** of the projectile **2** is between about 0.30 inches and about 0.40 inches. In the embodiment shown, the diameter D**1** of the projectile **2** is about 0.338 inches. In one embodiment, the angle α of the nose depressions **8** is between about 5 degrees and about 10 degrees. In a preferred embodiment, the angle α of the nose depressions **8** is between about 6 degrees and about 9 degrees. In a more preferred embodiment, the angle α of the nose depressions **8** is about 7.5 degrees. In one embodiment, the angle θ of the boat tail **38** is between about 5 degrees and about 10degrees. In a preferred embodiment, the angle of the boat tail **38** is between about 6.5degrees and about 8.0 degrees. In a more preferred embodiment, the angle of the boat tail **38** is about 7.5 degrees. In one embodiment, the angle Δ of the tail depressions **34** is between about 4.0 degrees and about 10.0 degrees. In a preferred embodiment, the angle Δ of the tail depressions **34** is between about 5.0 degrees and about 7.0 degrees. In a more preferred embodiment the angle Δ of the tail depressions **34** is about 6.0 degrees. The angle Δ of the tail depression **34** is measured from the centerline **36** of the tail depression **34** relative to the longitudinal axis **44**.

[0124] This projectile **2** is different from the prior art because it can pierce armor and stop in soft tissue. The intended users of the projectile are African big game hunters. The attributes of this projectile are deep straight penetration with transfer of energy. The projectile is comprised of brass, copper, bronze, tungsten-carbide, alloys of these metals, or any material known in the art, including plastics and ceramics.

[0125] FIGS. **7**A-C show a projectile according to a seventh embodiment of the invention. FIG. **7**A is a bottom perspective view of the projectile **2**. FIG. **7**B is a side elevation view of the projectile **2**. FIG. **7**C is a bottom plan view of the projectile **2**. Note that FIGS. **7**A-C are to scale.

[0126] The projectile **2** comprises a tip **4** on one end opposite a base **30** on the other end. The projectile **2** comprises a nose portion **6**, a cylindrical portion **20**, and a boat tail **38**. The nose portion **6** includes nose depressions **8** and nose remaining portions **22** between the nose depressions **8**, where each nose remaining portion **22** is positioned between two nose depressions **8**.

[0127] The nose remaining portions **22** are the uncut portions having the projectile's original ogive. The nose depressions **8** run from the tip **4** to a portion of the projectile proximate the cylindrical portion **20**. The nose depressions **8** have a curved shape meaning that the trough or bottom of the nose depression **8** is curved and has a radius of curvature R**4**. The boat tail **38** includes tail depressions **34** and tail remaining portions **46** between the tail depressions **34**, where each tail remaining portion **46** is positioned between two tail depressions **34**. The tail remaining portions **46** are the uncut portions. The tail depressions **34** run from the base **30** to a portion of the boat tail **38** proximate the cylindrical portion **20**. The tail depressions **34** can have a curved shape meaning that the trough or bottom of the tail depression **34** is curved and has a radius of curvature R**5**. In one embodiment, the nose depressions **8** are cut using a **120** degree cutter and the tail depressions **34** are cut using a ⅜ inch flat end mill. The cylindrical portion **20** of the projectile can also comprise driving bands **26** and relief cuts **28**. Some embodiments have one or more driving bands **26** and relief cuts **28**. The widths of the driving bands **26** and relief cuts **28** can vary or they can all be the same.

[0128] The longitudinal axis **44** of the projectile **2** is shown in FIG. **7**B. Accordingly, the angle α of the nose depressions **8** can be measured relative to the longitudinal axis **44**. In some embodiments, the angle α is measured from the centerline **10** of the nose depressions **8** relative to the original ogive of the projectile nose portion **6**. In some embodiments, all nose depressions **8** have the same angle α. In other embodiments, each nose depression **8** has a different angle α. In still other embodiments, some nose depressions **8** have the same angle α while other nose depressions **8** have different angles α. In the embodiment shown, the nose depressions **8** are right-hand nose depressions **8** because the angle α is positioned to the right of the longitudinal axis **44**. In one embodiment, the projectile **2** has at least three nose depressions **8**. However, the projectile **2** can have more or fewer nose depressions **8**. The angle Δ of the tail depressions **34** can be measured from the centerline **36** of the tail depression **34** relative to the longitudinal axis **44**. In some embodiments, all tail depressions **34** have the same angle Δ. In other embodiments, each tail depression **34** has a different angle Δ. In still other embodiments, some tail depressions **34** have the same angle Δ while other tail depressions **34** have different angles Δ. In the embodiment shown, the tail depressions **34** are right-hand tail depressions **34** because the angle Δ is positioned to the right of the longitudinal axis **44**. Further, when looking at the projectile from a bottom plan view (FIG. **7**C), the tail depressions **34** appear to turn in a counterclockwise direction. In one embodiment, the projectile **2** has at least 6 tail depressions **34**. However, the projectile **2** can have more or fewer tail depressions **34**.

[0129] In one embodiment, the radius of curvature R**5** of the tail depressions **34** is between about 0.10 inches and about 0.30 inches. In a preferred embodiment, the radius of curvature R**5** of the tail depressions **34** is between about 0.15 inches and about 0.20 inches. In a more preferred embodiment, the radius of curvature R**5** of the tail depressions **34** is about 0.1875 inches. In one embodiment, the length L**1** of the projectile **2** is between about 1.0 inch and about 2.5 inches. In a preferred embodiment, the length L**1** of the projectile **2** is between about 1.5 inches and about 2.0 inches. In a more preferred embodiment, the length L**1** of the projectile **2** is about 1.80 inches. In one embodiment, the length L**2** of the nose portion **6** is between about 0.50 inches and about 1.0 inch. In a preferred embodiment, the length L**2** of the nose portion **6** is between about 0.70 inches and about 0.80 inches. In a more preferred embodiment, the length L**2** of the nose portion **6** is about 0.750 inches. In one embodiment, the length L**3** of the cylindrical portion **20** is between about 0.40 inches and about 0.90 inches. In a preferred embodiment, the length L**3** of the cylindrical portion **20** is between about 0.55 inches and about 0.75 inches. In a more preferred embodiment, the length L**3** of the cylindrical portion **20** is about 0.65 inches. In one embodiment, the length L**4** of the boat tail **38** is between about 0.20 inches and about 0.60 inches. In a preferred embodiment, the length L**4** of the boat tail **38** is between about 0.30 inches and about 0.50 inches. In a more preferred embodiment, the length L**4** of the boat tail **38** is about 0.400 inches. The diameter of the projectile **2** varies according the various embodiments. In one embodiment, the diameter of the projectile **2** is between about 0.22inches and about 0.45 inches. In a preferred embodiment, the diameter of the projectile **2** is between about 0.29 inches and about 0.31 inches. In the embodiment shown, the diameter of the projectile **2** is about 0.308 inches. In one embodiment, the angle α of the nose depressions **8** is between about 2 degrees and about 10 degrees. In a preferred embodiment, the angle α of the nose depressions **8** is between about 4 degrees and about 7degrees. In a more preferred embodiment, the angle α of the nose depressions **8** is about 5.5 degrees. In one embodiment, the angle θ of the boat tail **38** is between about 5 degrees and about 10 degrees. In a preferred embodiment, the angle θ of the boat tail **38** is between about 6.5 degrees and about 8.0 degrees. In a more preferred embodiment, the angle θ of the boat tail **38** is about 7.5 degrees. In one embodiment, the angle Δ of the tail depressions **34** is between about 6 degrees and about 9 degrees. In a preferred embodiment, the angle A of the tail depressions **34** is between about 7.0 degrees and about 8.5 degrees. In a more preferred embodiment the angle Δ of the tail depressions **34** is about 7.8 degrees.

[0130] This projectile **2** is different from the prior art because it can pierce armor and stop in soft tissue. The intended users of the projectile are African big game hunters. The attributes of this projectile are deep straight penetration with transfer of energy. The projectile is comprised of brass,

copper, bronze, tungsten-carbide, alloys of these metals, or any material known in the art, including plastics and ceramics.

[0131] FIGS. **8**A-C show a projectile according to an eighth embodiment of the invention. FIG. **8**A is a bottom perspective view of the projectile **2**. FIG. **8**B is a side elevation view of the projectile **2**. FIG. **8**C is a bottom plan view of the projectile **2**. Note that FIGS. **8**A-C are to scale.

[0132] The projectile **2** comprises a tip **4** on one end opposite a base **30** on the other end. The projectile **2** comprises a nose portion **6**, a cylindrical portion **20**, and a boat tail **38**. The boat tail **34** includes tail depressions **34** and tail remaining portions **46** between the tail depressions **34** where each tail remaining portion **46** is positioned between two tail depressions **34**. The remaining portions **46** are the uncut portions. The tail depressions **34** run from the base **30** to a portion of the boat tail **38** proximate the cylindrical portion **20**. The tail depressions **34** can have a curved shape, meaning that the trough or bottom of the tail depression **34** is curved and has a radius of curvature R**5**. In one embodiment, the tail depressions **34** are cut using a ⅜ inch flat end mill. The cylindrical portion **20** of the projectile can also comprise angled driving bands **26**A and angled relief cuts **28**A. Some embodiments have one or more angled driving bands **26**A and angled relief cuts **28**A. The widths of the angled driving bands **26**A and angled relief cuts **28**A can vary or they can all be the same. The driving bands **28**A alternate with the relief bands **26**A. The angles between the driving bands **26**A and angled relief cuts **28**A (relative to the horizontal) are between about 7 degrees and about 10 degrees. In one embodiment, angles between the driving bands **26**A and, angled relief cuts **28**A (relative to the horizontal) are about 7.5degrees. In another embodiment, angles between the driving bands **26**A and relief cuts **28**A (relative to the horizontal) are about 8.5 degrees.

[0133] The angle Δ of the tail depressions **34** can be measured from the centerline **36** of the tail depression **34** relative to the longitudinal axis **44**. In some embodiments, all tail depressions **34** have the same angle Δ. In other embodiments, each tail depression **34** has a different angle Δ. In still other embodiments, some tail depressions **34** have the same angle Δ while other tail depressions **34** have different angles Δ. In the embodiment shown, the tail depressions **34** are right-hand tail depressions **34** because the angle Δ is positioned to the right of the longitudinal axis **44**. Further, when looking at the projectile **2** from a bottom plan view (FIG. **8**C), the tail depressions **34** appear to turn in a counterclockwise direction. In one embodiment, the projectile **2** has at least six tail depressions **34**. However, the projectile **2** can have more or fewer tail depressions **34**.

[0134] In one embodiment, the radius of curvature R**2** of the tangent ogive is between about 2.0 inches and about 5.0 inches. In a preferred embodiment, the radius of curvature R**2** of the tangent ogive is between about 3.0 inches and about 4.0 inches. In a more preferred embodiment, the radius of curvature R**2** of the tangent ogive is about 3.5 inches. In one embodiment, the radius of curvature R**3** of the secant ogive is between about 0.5inches and about 1.5 inches. In a preferred embodiment, the radius of curvature R**3** of the secant ogive is between about 0.75 inches and about 1.25 inches. In a more preferred embodiment, the radius of curvature R**3** of the secant ogive is about 1.00 inch.

[0135] In one embodiment, the length L**1** of the projectile **2** is between about 1.5 inches and about 2.5 inches. In a preferred embodiment, the length L**1** of the projectile **2** is between about 1.75 inches and about 2.25 inches. In a more preferred embodiment, the length L**1** of the projectile **2** is about **2**.**1** inches. In one embodiment, the length L**2** of the nose portion **6** is between about 0.50 inches and about 1.10 inches. In a preferred embodiment, the length L**2** of the nose portion **6** is between about 0.75 inches and about 1.00 inch. In a more preferred embodiment, the length L**2** of the nose portion **6** is about 0.8633 inches. In one embodiment, the length L**3** of the cylindrical portion **20** is between about 0.25 inches and about 0.50 inches. In a preferred embodiment, the length L**3** of the cylindrical portion **20** is between about 0.30 inches and about 0.40 inches. In a more preferred embodiment, the length L**3** of the cylindrical portion **20** is about 0.322 inches. In one embodiment, the length L**4** of the boat tail **38** is between about 0.10 inches and about 0.45 inches. In a preferred embodiment, the length L**4** of the boat tail **38** is between about 0.15 inches and about 0.30 inches. In a more preferred embodiment, the length L**4** of the boat tail **38** is about 0.275 inches. The diameter of the projectile **2** (also called the caliber) varies according the various embodiments. In one embodiment, the diameter of the projectile **2** is between about 0.220 inches and about 0.450 inches. In a preferred embodiment, the diameter of the projectile **2** is between about 0.290 inches and about 0.350inches. In the embodiment shown, the diameter of the projectile **2** is about 0.3080 inches. In one embodiment, the diameter of the angled relief cut **28**A is between about 0.20 inches and about 0.40 inches. In a preferred embodiment, the diameter of the angled relief cut **28**A is between about 0.25 inches and about 0.31 inches. In the embodiment shown, the diameter of the angled relief cut **28**A is about 0.298 inches. In one embodiment, the diameter of the angled driving band **26**A is between about 0.25 inches and about 0.32inches. In a preferred embodiment, the diameter of the angled driving band **26**A is between about 0.30 inches and about 0.31 inches. In the embodiment shown, the diameter of the angled driving band **26**A is about 0.307 inches. In one embodiment, the angle θ of the boat tail **38** is between about 5 degrees and about 10 degrees. In a preferred embodiment, the angle θ of the boat tail **38** is between about 7.0 degrees and about 8.0 degrees. In a more preferred embodiment, the angle θ of the boat tail **38** is about 7.5 degrees. In one embodiment, the angle Δ of the tail depressions **34** is between about 5 degrees and about 10 degrees. In a preferred embodiment, the angle Δ of the tail depressions **34** is between about 7.0 degrees and about 8.0 degrees. In a more preferred embodiment the angle Δ of the tail depressions **34** is about 7.8 degrees.

[0136] In alternate embodiments, the projectile **2** can have nose depressions and/or tail depressions. This projectile **2** is different from the prior art because it can pierce armor fly an extended range. This projectile is also capable of flying supersonic. It is extremely accurate even at long distances.

[0137] FIGS. **9**A-D show a projectile according to a ninth embodiment of the invention. FIG. **9**A is a bottom perspective view of the projectile **2**. FIG. **9**B is a side elevation view of the projectile **2**. FIG. **9**C is a bottom plan view of the projectile **2**. FIG. **9**D is a cross sectional view taken at cut D-D of FIG. **9**C. Note that FIGS. **9**A-D are to scale. The projectile **2** comprises a tip **4** on one end opposite a base **30** on the other end. The projectile **2** comprises a nose portion **6**, a cylindrical portion **20**, and a boat tail **38**. The nose portion **6** includes nose depressions **8** and nose remaining portions **22** between the nose depressions **8**, where each nose

remaining portion **22** is positioned between two nose depressions **8**. The remaining portions **22** are the uncut portions having the projectile's original ogive. The nose depressions **8** run from the tip **4** to a portion of the projectile proximate the cylindrical portion **20**. The nose depressions **8** have a curved shape meaning that the trough or bottom of the nose depression **8** is curved and has a radius of curvature. The boat tail **34** includes tail depressions **34** and tail remaining portions **46** between the tail depressions **34** where each tail remaining portion **46** is positioned between two tail depressions **34**. The remaining portions **46** are the uncut portions. The tail depressions **34** run from the base **30** to a portion of the boat tail **38** proximate the cylindrical portion **20**. The tail depressions **34** have a curved shape meaning that the trough or bottom of the tail depression **34** is curved and has a radius of curvature R**5**. In one embodiment, the nose depressions **8** are cut using a 3/16 inch to a ⅜ inch ball end mill and the tail depressions **34** are cut using a ⅜ inch flat end mill. The cylindrical portion **20** of the projectile can also comprise driving bands **26** and relief cuts **28**. Some embodiments have one or more driving bands **26** and relief cuts **28**. The widths of the driving bands **26** and relief cuts **28** can vary or they can all be the same.

[0138] The angle Δ of the tail depressions **34** can be measured from the centerline **36** of the tail depression **34** relative to the longitudinal axis **44**. In some embodiments, all tail depressions **34** have the same angle Δ. In other embodiments, each tail depression **34** has a different angle Δ. In still other embodiments, some tail depressions **34** have the same angle Δ while other tail depressions **34** have different angles Δ. In the embodiment shown, the tail depressions **34** are right-hand tail depressions **34** because the angle Δ is positioned to the right of the longitudinal axis **44**. Further, when looking at the projectile from a bottom plan view (FIG. **9**C), the tail depressions **34** appear to turn in a counterclockwise direction. In one embodiment, the projectile **2** has at least six tail depressions **34**. However, the projectile **2** can have more or fewer tail depressions **34**.

[0139] In one embodiment, the radius of curvature R**4** (not shown in FIGS. **9**A-**9**D, but shown in other Figs.) of the nose depressions **8** is between about 0.10 inches and about 0.40 inches. In a preferred embodiment, the radius of curvature of the nose depressions **8** is between about 0.20 inches and about 0.30 inches. In a more preferred embodiment, the radius of curvature of the nose depressions **8** is about 0.25 inches. In one embodiment, the radius of curvature R**5** of the tail depressions **34** is between about 0.10 inches and about 0.30 inches. In a preferred embodiment, the radius of curvature R**5** of the tail depressions **34** is between about 0.15 inches and about 0.20 inches. In a more preferred embodiment, the radius of curvature R**5** of the tail depressions **34** is about 0.1875 inches. In one embodiment, the length L**1** of the projectile **2** is between about 1.0 inch and about 2.0inches. In a preferred embodiment, the length L**1** of the projectile **2** is between about 1.25inches and about 1.75 inches. In a more preferred embodiment, the length L**1** of the projectile **2** is about 1.492 inches. In one embodiment, the length L**2** of the nose portion **6** is between about 0.10 inches and about 0.40 inches. In a preferred embodiment, the length L**2** of the nose portion **6** is between about 0.20 inches and about 0.35 inches. In a more preferred embodiment, the length L**2** of the nose portion **6** is about 0.29 inches. In one embodiment, the length L**3** of the cylindrical portion **20** is between about 0.75 inches and about 1.25 inches. In a preferred embodiment, the length L**3** of the cylindrical portion **20** is between about 0.90 inches and about 1.1 inches. In a more preferred embodiment, the length L**3** of the cylindrical portion **20** is about 1.01 inches.

[0140] In one embodiment, the length L**4** of the boat tail **38** is between about 0.10 inches and about 0.30 inches. In a preferred embodiment, the length L**4** of the boat tail **38** is between about 0.15 inches and about 0.25 inches. In a more preferred embodiment, the length L**4** of the boat tail **38** is about 0.19 inches. The diameter of the projectile **2** varies according the various embodiments. In one embodiment, the diameter of the projectile **2** is between about 0.20 inches and about 0.50 inches. In a preferred embodiment, the diameter of the projectile **2** is between about 0.30 inches and about 0.45 inches. In the embodiment shown, the diameter of the projectile **2** is about 0.375 inches. In one embodiment, the angle α of the nose depressions **8** is between about 3 degrees and about 8 degrees. In a preferred embodiment, the angle α of the nose depressions **8** is between about 5 degrees and about 6degrees. In a more preferred embodiment, the angle α of the nose depressions **8** is about 5.6 degrees. In one embodiment, the angle θ of the boat tail **38** is between about 1 degree and about 5 degrees. In a preferred embodiment, the angle θ of the boat tail **38** is between about 2.0 degrees and about 4.0 degrees. In a more preferred embodiment, the angle θ of the of the boat tail **38** is about 3.0 degrees. In one embodiment, the angle Δ of the tail depressions **34** is between about 4.0 degrees and about 8.0 degrees. In a preferred embodiment, the angle Δ of the tail depressions **34** is between about 5.0 degrees and about 6.0 degrees. In a more preferred embodiment the angle Δ of the tail depressions **34** is about 5.6 degrees.

[0141] This projectile **2** is designed to shoot into a large animal, e.g., an elephant, and not yaw once it inserts the body. The boat tail **38** of the projectile **2** allows the projectile **2** to perform like this in the soft tissue of an animal. The intended users of the projectile **2** are

[0142] African big game hunters. The attributes of this projectile **2** are deep straight penetration with transfer of energy. The projectile is comprised of brass, copper, bronze, tungsten-carbide, alloys of these metals, or any material known in the art, including plastics and ceramics. Note that the nose portion **6** of this projectile **2** can be the same or similar to the nose portions shown in FIGS. **21**-**23**.

[0143] FIGS. **10**A-C show a projectile according to a tenth embodiment of the invention. FIG. **10**A is a top perspective view of the projectile **2**. FIG. **10**B is a side elevation view of the projectile **2**. FIG. **10**C is a bottom plan view of the projectile **2**.

[0144] The projectile **2** comprises a housing **40** with a tip **4** on one end and rear edge **70** on the opposite end. The projectile **2** also includes an insert **42** with a base **30** opposite the tip **4**. The housing **40** comprises a nose portion **6** extending from the tip **4** on to a cylindrical portion **20**. The cylindrical portion **20** extends from the nose portion **6** to the boat tail **38**A. The housing **40** includes a portion of the boat tail **38**A. The insert **42** comprises the rest of the boat tail **38**B. In one embodiment, the insert **42** is the same insert shown and described in FIGS. **25** and **27**. In additional embodiments, the cylindrical portion **20** can comprise multiple angled relief bands and angled driving bands. The driving bands alternate with the relief bands. The angles between the driving bands and relief cuts are between about 7 degrees and about 10 degrees.

[0145] In one embodiment, the radius of curvature R**2** of the tangent ogive is between about 2.0 inches and about 5.0 inches. In a preferred embodiment, the radius of curvature R**2** of the tangent ogive is between about 3.0 inches and about 4.0 inches. In a more preferred embodiment, the radius of curvature R**2** of the tangent ogive is about 3.5 inches. In one embodiment, the radius of curvature R**3** of the secant ogive is between about 0.5inches and about 1.5 inches. In a preferred embodiment, the radius of curvature R**3** of the secant ogive is between about 0.75 inches and about 1.25 inches. In a more preferred embodiment, the radius of curvature R**3** of the secant ogive is about 1.00 inch. In one embodiment, the radius of curvature R**7** of the tip **4** is between about 0.030 inches and about 0.005 inches. In a preferred embodiment, the radius of curvature R**7** of the tip **4** is between about 0.020 inches and about 0.010 inches. In a more preferred embodiment, the radius of curvature R**7** of the tip **4** is about 0.015 inches.

[0146] In one embodiment, the length L**1** of the projectile **2** is between about 1.25 inches and about 2.25 inches. In a preferred embodiment, the length L**1** of the projectile **2** is between about 1.4 inches and about 2.0 inches. In a more preferred embodiment, the length L**1** of the projectile **2** is about 1.75 inches. In one embodiment, the length L**2** of the nose portion **6** is between about 0.50 inches and about 1.10 inches. In a preferred embodiment, the length L**2** of the nose portion **6** is between about 0.75 inches and about 1.00 inch. In a more preferred embodiment, the length L**2** of the nose portion **6** is about 0.863 inches. The diameter D**1** of the projectile **2** (also called the caliber) varies according the various embodiments. In one embodiment, the diameter D**1** of the projectile **2** is between about 0.220 inches and about 0.450 inches. In a preferred embodiment, the diameter D**1** of the projectile **2** is between about 0.290 inches and about 0.350 inches. In the embodiment shown, the diameter D**1** of the projectile **2** is about 0.3080 inches. In one embodiment, the angle θ of the boat tail **38** is between about 5 degrees and about 10 degrees. In a preferred embodiment, the angle θ of the boat tail **38** is between about 6.5 degrees and about 8.0degrees. In a more preferred embodiment, the angle θ of the boat tail **38** is about 7 degrees. In one embodiment, the length L**5** of the housing **40** is between about 1.0 inch and about 2.0 inches. In a preferred embodiment, the length L**5** of the housing **40** is between about 1.1 inches and about 1.6 inches. In a more preferred embodiment, the length L**5** of the housing **40** is about 1.3 inches.

[0147] In this embodiment, the insert **42** acts like a propeller in the gun barrel. Thus, the insert **42** relieves pressure on the gun barrel and increases the speed of the bullet. Relieving pressure reduces the wear on the gun barrel because the projectile is already twisting when it hits the barrel's rifling. Thus, there is not a pressure jump where the rifling begins. Further, the shape of the tail formed by the insert **42** is the ideal shape to interact with the gun powder. The depressions on the tail or insert **42** have a 15 degree twist in one embodiment. The tail shape only enhances performance during internal ballistics because the tail is riding in the slip screen of the projectile during external ballistics.

[0148] FIGS. **11**A-F show a projectile according to an eleventh embodiment of the invention. FIG. **11**A is a perspective view of the projectile **2**. FIG. **11**B is a side elevation view of the projectile **2**. FIG. **11**C is a top plan view of the projectile **2**. FIG. **11**D is a cross section taken at cut D-D of FIG. **11**C. FIG. **11**E is a cross section taken at cut E-E of FIG. **11**B. FIG. **11**F is a cross section taken at cut F-F of FIG. **11**B. Note that FIGS. **11**A-D are to scale. FIGS. **11**E and **11**F are enlarged as compared to FIGS. **11**A-D. The projectile **2** comprises a tip **4** on one end opposite a base **30** on the other end. The projectile **2** comprises a nose portion **6**, a cylindrical portion **20**, and a boat tail **38**. The nose portion **6** includes nose depressions **8** and nose remaining portions **22** between the nose depressions **8**, where each nose remaining portion **22** is positioned between two nose depressions **8**. The nose remaining portions **22** are the uncut portions having the projectile's original ogive. The nose depressions **8** run from the tip **4** to a portion of the projectile proximate the cylindrical portion **20**. The nose depressions **8** have a curved shape meaning that the trough or bottom of the nose depression **8** is curved and has a radius of curvature R**4**. The boat tail **34** includes tail depressions **34** and tail remaining portions **46** between the tail depressions **34** where each tail remaining portion **46** is positioned between two tail depressions **34**. The tail remaining portions **46** are the uncut portions. The tail depressions **34** run from the base **30** to a portion of the boat tail **38** proximate the cylindrical portion **20**. The tail depressions **34** have a curved shape meaning that the trough or bottom of the tail depression **34** is curved and has a radius of curvature R**5**. In one embodiment, the nose depressions **8** are cut using a 0.25 inch ball end mill and the tail depressions **34** are cut using a 0.25 inch flat end mill. The cylindrical portion **20** of the projectile can also comprise driving bands **26** and relief cuts **28**. Some embodiments have one or more driving bands **26** and relief cuts **28**. The widths of the driving bands **26** and relief cuts **28** can vary or they can all be the same.

[0149] The longitudinal axis **44** of the projectile **2** is shown in FIG. **11**B. Accordingly, the angle α of the nose depressions **8** can be measured from the centerline **10** of the nose depressions **8** relative to the longitudinal axis **44**. In some embodiments, the angle α is measured relative to the original ogive of the projectile nose portion **6**. In some embodiments, all nose depressions **8** have the same angle α. In other embodiments, each nose depression **8** has a different angle α. In still other embodiments, some nose depressions **8** have the same angle α while other nose depressions **8** have different angles α. In the embodiment shown, the nose depressions **8** are right-hand nose depressions **8** because the angle α is positioned to the right of the longitudinal axis **44**. In one embodiment, the projectile **2** has at least three nose depressions **8**. However, the projectile **2** can have more or fewer nose depressions **8**. The angle Δ of the tail depressions **34** can be measured from the centerline **36** of the tail depression **34** relative to the longitudinal axis **44**. In some embodiments, all tail depressions **34** have the same angle Δ. In other embodiments, each tail depression **34** has a different angle **4**. In still other embodiments, some tail depressions **34** have the same angle Δ while other tail depressions **34** have different angles Δ. In one embodiment, the projectile **2** has at least six tail depressions **34**. However, the projectile **2** can have more or fewer tail depressions **34**.

[0150] In one embodiment, the radius of curvature R**2** of the tangent ogive is between about 1.0 inch and about 4.0 inches. In a preferred embodiment, the radius of curvature R**2** of the tangent ogive is between about 2.0 inches and about 3.5 inches. In a more preferred embodiment, the radius of curvature R**2** of the tangent ogive is about 2.71 inches. In one embodiment, the radius of curvature R**3** of the secant

ogive is between about 0.5inches and about 2.5 inches. In a preferred embodiment, the radius of curvature R**3** of the secant ogive is between about 1.0 inch and about 1.5 inches. In a more preferred embodiment, the radius of curvature R**3** of the secant ogive is about 1.35 inches. In one embodiment, the radius of curvature R**4** of the nose depressions **8** is between about 0.05inches and about 0.20 inches. In a preferred embodiment, the radius of curvature R**4** of the nose depressions **8** is between about 0.10 inches and about 0.15 inches. In a more preferred embodiment, the radius of curvature R**4** of the nose depressions **8** is about 0.125 inches. In one embodiment, the radius of curvature R**5** of the tail depressions **34** is between about 0.05 inches and about 0.20 inches. In a preferred embodiment, the radius of curvature R**5** of the tail depressions **34** is between about 0.10 inches and about 0.15 inches. In a more preferred embodiment, the radius of curvature R**5** of the tail depressions **34** is about 0.125inches. In one embodiment, the length L**1** of the projectile **2** is between about 1.0 inch and about 2.5 inches. In a preferred embodiment, the length L**1** of the projectile **2** is between about 1.5 inches and about 2.0 inches. In a more preferred embodiment, the length L**1** of the projectile **2** is about 1.75 inches. In one embodiment, the length of the nose portion **6** is between about 0.050 inches and about 1.5 inches. In a preferred embodiment, the length of the nose portion **6** is between about 0.60 inches and about 1.0 inch. In a more preferred embodiment, the length of the nose portion **6** is about 0.80 inches. In one embodiment, the length L**3** of the cylindrical portion **20** is between about 0.25 inches and about 1.5 inches. In a preferred embodiment, the length L**3** of the cylindrical portion **20** is between about 0.50 inches and about 1.0 inch. In a more preferred embodiment, the length L**3** of the cylindrical portion **20** is about 0.70 inches. In one embodiment, the length L**4** of the boat tail **38** is between about 0.10 inches and about 0.50 inches. In a preferred embodiment, the length L**4** of the boat tail **38** is between about 0.20 inches and about 0.30 inches. In a more preferred embodiment, the length L**4** of the boat tail **38** is about 0.25 inches. The diameter D**1** of the projectile **2** varies according the various embodiments. In one embodiment, the diameter D**1** of the projectile **2** is between about 0.22 inches and about 0.50 inches. In a preferred embodiment, the diameter D**1** of the projectile **2** is between about 0.30 inches and about 0.35 inches. In the embodiment shown, the diameter D**1** of the projectile **2** is about 0.338 inches. In the embodiment shown, the diameter D**2** of the relief cut **28** is about 0.32 inches. In the embodiment shown, the diameter D**3** of the driving band is about 0.338inches. In one embodiment, the ≠of the nose depressions **8** is between about 5degrees and about 10 degrees. In a preferred embodiment, the angle α of the nose depressions **8** is between about 6 degrees and about 8 degrees. In a more preferred embodiment, the angle α of the nose depressions **8** is about 7.5 degrees. In one embodiment, the angle θ of the boat tail **38** is between about 5 degrees and about 10degrees. In a preferred embodiment, the angle θ of the boat tail **38** is between about 6.5 degrees and about 8.0 degrees. In a more preferred embodiment, the angle θ of the boat tail **38** is about 7.5 degrees. In one embodiment, the angle Δ of the tail depressions **34** is between about 5 degrees and about 10 degrees. In a preferred embodiment, the angle Δ of the tail depressions **34** is between about 7.0 degrees and about 8.0 degrees. In a more preferred embodiment the angle Δ of the tail depressions **34** is about 7.5 degrees.

[0151] This projectile **2** is different from the prior art because it can pierce armor and stop in soft tissue. The intended users of the projectile **2** are African big game hunters. The attributes of this projectile **2** are deep straight penetration with transfer of energy. The projectile **2** is comprised of brass, copper, bronze, tungsten-carbide, alloys of these metals, or any material known in the art, including plastics and ceramics.

[0152] Referring to FIGS. **12-16** and **18**, these projectiles comprise a housing and an insert. Upon impact, the housing will peel back toward the base of the projectile and away from the tip of the projectile when it hits soft tissue. The housing expands rapidly to peel backward The projectile will remain in its original shape when the projectile hits hard tissue. The tip or point keeps the projectile moving in the correct direction after the projectile initially hits soft tissue and the housing peels back toward the base. However, the insert may separate from the housing in soft tissue and the two pieces may go in separate directions. The cavities of these projectiles fill with material when the projectile hits soft tissue. However, material does not go into cavities when the projectile hits hard material. These projectiles are designed mostly for civilian use.

[0153] FIGS. **12**A-D show a projectile according to a twelfth embodiment of the invention. FIG. **12**A is a perspective view of the projectile **2**. FIG. **12**B is a side elevation view of the projectile **2**. FIG. **12**C is a top plan view of the projectile **2**. FIG. **12**D is a cross section taken at cut D-D of FIG. **12**C. Note that FIGS. **12**A-D are to scale.

[0154] The projectile **2** comprises a tip **4** on one end opposite a base **30** on the other end. The projectile **2** comprises a nose portion **6** and a cylindrical portion **20**. The projectile **2** is two-pieces and includes a housing **40** and an insert **42**. The tip **4** is substantially flat and is a part of the insert **42**. The insert **42** has an arrowhead portion **48** that is wider than its stem **50**, which extends from the lower portion **52** of the arrowhead **48** to the underside **54** of the stem **50**. The base **30** of the projectile is substantially flat and is part of the housing **40**. The housing has a cavity **24** extending down from the opening of the housing **40**. The lower surface of the cavity **24** is substantially flat and has side portions that extend into the center of the cavity **24** to receive the lower portion or underside **54** of the stem **50** of the insert **42**. In some embodiments, the stem **50** has a constant diameter. In other embodiments, the stem **50** gets wider near the bottom **54** of the stem **50**. The nose portion **6** includes nose depressions **8** and a nose remaining portion **22** between the nose depressions **8**, where each nose remaining portion **22** is positioned between two nose depressions **8**. The remaining portions **22** are the uncut portions having the projectile's original ogive. The nose depressions **8** have a curved shape meaning that the trough or bottom of the nose depression **8** is curved and has a radius of curvature R**4**. The nose depressions **8** extend along the insert such that they extend into the cavity **24** of the housing **40** creating cavities **24** for tissue and other material to collect when the projectile hits its target. In one embodiment, the nose depressions are cut using a ⅜-inch ball end mill.

[0155] In one embodiment, the projectile **2** has at least three nose depressions **8**. However, the projectile **2** can have more or fewer nose depressions **8**. In one embodiment, the radius of curvature R**4** of the nose depressions **8** is between about 0.10 inches and about 0.30 inches. In a preferred embodiment, the radius of curvature R**4** of the nose depres-

sions **8** is between about 0.15 inches and about 0.25 inches. In a more preferred embodiment, the radius of curvature R**4** of the nose depressions **8** is about 3/16 inches. In one embodiment, the length L**1** of the projectile **2** is between about 0.50 inches and about 1.0 inch. In a preferred embodiment, the length L**1** of the projectile **2** is between about 0.55 inches and about 0.75 inches. In a more preferred embodiment, the length L**1** of the projectile **2** is about 0.625 inches. In one embodiment, the length L**5** of the housing **40** is between about 0.30 inches and about 0.70 inches. In a preferred embodiment, the length L**5** of the housing is between about 0.45 inches and about 0.50 inches. In a more preferred embodiment, the length L**5** of the housing **40** is about 0.485 inches. The diameter D**1** of the projectile **2** (also called the caliber) varies according the various embodiments. In one embodiment, the diameter D**1** of the projectile **2** is between about 0.25 inches and about 0.60 inches. In a preferred embodiment, the diameter D**1** of the projectile **2** is between about 0.35 inches and about 0.55 inches. In the embodiment shown, the diameter D**1** of the projectile **2** is about 0.45 inches. In one embodiment, the angle α of the nose depression **8** is about 0degrees. The width of the opening of the housing **40** is about 0.330 inches.

[0156] FIGS. **13**A-D show a projectile according to a thirteenth embodiment of the invention. FIG. **13**A is a perspective view of the projectile **2**. FIG. **13**B is a side elevation view of the projectile **2**. FIG. **13**C is a top plan view of the projectile **2**. FIG. **13**D is a cross section taken at cut D-D of FIG. **13**C. Note that FIGS. **13**A-D are to scale.

[0157] The projectile **2** comprises a tip **4** on one end opposite a base **30** on the other end. The projectile **2** comprises a nose portion, a cylindrical portion **20**, and a boat tail **38**. The cylindrical portion **20** can comprise one or more relief cuts **28**. The cylindrical portion **20** may also comprise at least one driving band. The projectile **2** is two-pieces and includes a housing **40** and an insert **42**. The tip **4** is a part of the insert **42**. The insert **42** has an arrowhead portion **48** that is wider than its stem **50**, which extends from the lower portion **52** of the arrowhead **48** to the underside **54** of the stem **50**. The base **30** of the projectile is substantially flat and is part of the housing **40**. The housing has a cavity **24** extending down from the opening of the housing **40** in a conical shape that transitions into a cylindrical shape. The lower surface of the cavity **24** is substantially flat and the sides of the cavity **24** form a receiving portion **58** to receive the stem **50** of the insert **42**. In some embodiments, the stem **50** has a constant diameter. The nose portion **6** includes nose depressions **8** and a nose remaining portion **22** between the nose depressions **8**, where each nose remaining portion **22** is positioned between two nose depressions **8**. The remaining portions **22** are the uncut portions having the projectile's original ogive. The nose depressions **8** have a curved shape meaning that the trough or bottom of the nose depression **8** is curved and has a radius of curvature R**4**. The nose depressions **8** extend along the arrowhead **48** of the insert **42** such that they extend into the cavity **24** of the housing **40** creating cavities **24** for tissue and other material to collect when the projectile **2** hits its target. Additional cavities **24** are created by the conical shape of the housing cavity **24** and the flat underside **52** of the arrowhead **48**. In one embodiment, the nose depressions are cut using a ⅛ inch ball end mill.

[0158] The longitudinal axis **44** of the projectile **2** is shown in FIG. **13**B. Accordingly, the angle α of the nose depressions **8** can be measured from the centerline **10** of the nose depressions **8** relative to the longitudinal axis **44**. In some embodiments, the angle α is measured relative to the original ogive of the projectile nose portion **6**. In some embodiments, all nose depressions **8** have the same angle α. In other embodiments, each nose depression **8** has a different angle α. In still other embodiments, some nose depressions **8** have the same angle α while other nose depressions **8** have different angles α. In the embodiment shown, the nose depressions **8** are left-hand nose depressions **8** because the angle α is positioned to the left of the longitudinal axis **44**. In one embodiment, the projectile **2** has at least three nose depressions **8**. In another embodiment, the nose portion **6** has six nose depressions **8**. However, the projectile **2** can have more or fewer nose depressions **8**.

[0159] In one embodiment, the radius of curvature R**4** of the nose depressions **8** is between about 0.040 inches and about 0.090 inches. In a preferred embodiment, the radius of curvature R**4** of the nose depressions **8** is between about 0.050 inches and about 0.070inches. In a more preferred embodiment, the radius of curvature R**4** of the nose depressions **8** is about 0.0625 inches. In one embodiment, the length L**1** of the projectile **2** is between about 0.40 inches and about 2.0 inches. In a preferred embodiment, the length L**1** of the projectile **2** is between about 0.60 inches and about 1.20 inches. In a more preferred embodiment, the length L**1** of the projectile **2** is about 0.912 inches. In one embodiment, the length L**2** of the nose portion **6** is between about 0.30 inches and about 0.60 inches. In a preferred embodiment, the length L**2** of the nose portion **6** is between about 0.40 inches and about 0.55 inches. In a more preferred embodiment, the length L**2** of the nose portion **6** is about 0.485 inches. In one embodiment, the length L**3** of the cylindrical portion **20** is between about 0.10 inches and about 0.30 inches. In a preferred embodiment, the length L**3** of the cylindrical portion **20** is between about 0.15 inches and about 0.25 inches. In a more preferred embodiment, the length L**3** of the cylindrical portion **20** is about 0.20inches. In one embodiment, the length L**4** of the boat tail **38** is between about 0.10 inches and about 0.50 inches. In a preferred embodiment, the length L**4** of the boat tail **38** is between about 0.20 inches and about 0.30 inches. In a more preferred embodiment, the length L**3** of the cylindrical portion **20** is about 0.225 inches. The diameter D**1** of the projectile **2** varies according the various embodiments. In one embodiment, the diameter D**1** of the projectile **2** is between about 0.10 inches and about 0.40 inches. In a preferred embodiment, the diameter D**1** of the projectile **2** is between about 0.20 inches and about 0.25 inches. In the embodiment shown, the diameter D**1** of the projectile **2** is about 0.224inches. In the embodiment shown, the width of the housing opening is about 0.200 inches. In one embodiment, the angle α of the nose depressions **8** is between about 3.0 degrees and about 8.0 degrees. In a preferred embodiment, the angle α of the nose depressions **8** is between about 4.5 degrees and about 6.5 degrees. In a more preferred embodiment, the angle α of the nose depressions **8** is about 5.5 degrees. In one embodiment, the angle θ of the boat tail **38** is between about 5 degrees and about 10 degrees. In a preferred embodiment, the angle θ of the boat tail **38** is between about 6.5 degrees and about 8.0degrees. In a more preferred embodiment, the angle θ of the boat tail **38** is about 7 degrees.

[0160] FIGS. **14**A-C show a projectile according to a fourteenth embodiment of the invention. FIG. **14**A is a

perspective view of the projectile **2**. FIG. **14**B is a side elevation view of the projectile **2**. FIG. **14**C is a top plan view of the projectile **2**. Note that FIGS. **14**A-C are to scale.

[0161] The projectile **2** comprises a tip **4** on one end opposite a base **30** on the other end. The projectile **2** comprises a nose portion **6**, a cylindrical portion **20**, and a boat tail **38**. The cylindrical portion **20** can comprise at least one relief cut **28**. The cylindrical portion may comprise one or more driving bands and relief cuts. The projectile **2** is two-pieces and includes a housing **40** and an insert **42**. The tip **4** is a part of the insert **42**. The insert **42** is lincar. In some embodiments, the cylindrical portion of the insert **42** has a constant diameter. The base **30** of the projectile is substantially flat and is part of the housing **40**. The housing **40** has a cavity extending down from the opening of the housing **40**. The nose portion **6** includes nose depressions **8** and a nose remaining portion **22** between the nose depressions **8**, where each nose remaining portion **22** is positioned between two nose depressions **8**. The remaining portions **22** are the uncut portions having the projectile's original ogive. The nose depressions **8** have a curved shape meaning that the trough or bottom of the nose depression **8** is curved and has a radius of curvature R**4**. The nose depressions **8** extend along the insert **42** such that they extend into the cavity of the housing **40** creating cavities **24** for tissue and other material to collect when the projectile **2** hits its target. In one embodiment, the nose depressions **8** are cut using a 3/16 inch flat end mill.

[0162] The longitudinal axis **44** of the projectile **2** is shown in FIG. **13**B. Accordingly, the angle α of the nose depressions **8** can be measured from the centerline **10** of the nose depressions **8** relative to the longitudinal axis **44**. In some embodiments, the angle α is measured relative to the original ogive of the projectile nose portion **6**. In some embodiments, all nose depressions **8** have the same angle α. In other embodiments, each nose depression **8** has a different angle α. In still other embodiments, some nose depressions **8** have the same angle α while other nose depressions **8** have different angles α. In one embodiment, the projectile **2** has at least three nose depressions **8**. In another embodiment, the nose portion has six nose depressions. However, the projectile **2** can have more or fewer nose depressions **8**.

[0163] In one embodiment, the radius of curvature R**4** of the nose depressions **8** is between about 0.040 inches and about 0.080 inches. In a preferred embodiment, the radius of curvature R**4** of the nose depressions **8** is between about 0.050 inches and about 0.070inches. In a more preferred embodiment, the radius of curvature R**4** of the nose depressions **8** is about 0.0625 inches. In one embodiment, the length L**1** of the projectile **2** is between about 1.0 inch and about 2.5 inches. In a preferred embodiment, the length L**1** of the projectile **2** is between about 1.25 inches and about 1.5 inches. In a more preferred embodiment, the length L**1** of the projectile **2** is about 1.387 inches. In one embodiment, the length L**2** of the nose portion **6** is between about 0.40 inches and about 0.80 inches. In a preferred embodiment, the length L**2** of the nose portion **6** is between about 0.60 inches and about 0.70 inches. In a more preferred embodiment, the length L**2** of the nose portion **6** is about 0.674 inches. In one embodiment, the length L**3** of the cylindrical portion **20** is between about 0.30 inches and about 0.70 inches. In a preferred embodiment, the length L**3** of the cylindrical portion **20** is between about 0.40 inches and about 0.45 inches. In a more preferred embodiment, the length L**3** of the cylindrical portion **20** is about 0.413inches. In one embodiment, the length L**4** of the boat tail **38** is between about 0.2 inches and about 0.40 inches. In a preferred embodiment, the length L**4** of the boat tail **38** is between about 0.25 inches and about 0.35 inches. In a more preferred embodiment, the length L**4** of the boat tail **38** is about 0.30 inches. In one embodiment, the length L**5** of the projectile **2** is between about 0.8 inches and about 1.4 inches. In a preferred embodiment, the length L**5** of the projectile **2** is between about 1.0 inch and about 1.2 inches. In a more preferred embodiment, the length L**5** of the projectile **2** is about 1.1 inches. The diameter D**1** of the projectile **2** varies according the various embodiments. In one embodiment, the diameter D**1** of the projectile **2** is between about 0.20 inches and about 0.50 inches. In a preferred embodiment, the diameter D**1** of the projectile **2** is between about 0.25 inches and about 0.35 inches. In the embodiment shown, the diameter D**1** of the projectile **2** is about 0.308 inches. In one embodiment, the angle α of the nose depression **8** is about 0degrees.

[0164] FIGS. **15**A-D show a projectile according to a fifteenth embodiment of the invention. FIG. **15**A is a perspective view of the projectile **2**. FIG. **15**B is a side elevation view of the projectile **2**. FIG. **15**C is a top plan view of the projectile **2**. FIG. **15**D is a cross sectional view taken along line D-D of FIG. **15**C. Note that FIGS. **15**A-D are to scale. The projectile **2** comprises a tip **4** on one end opposite a base **30** on the other end. The projectile **2** comprises a nose portion **6** and a cylindrical portion **20** (also called a shank). The nose portion **6** includes nose depressions **8** (also called cutouts or troughs) and a nose remaining portion **22** between the nose depressions **8**, where each nose remaining portion **22** is positioned between two nose depressions **8**. The remaining portions **22** are the uncut portions having the projectile's original ogive. In some embodiments, the nose depressions **8** terminate in a substantially flat shoulder **18** (not shown). The nose depressions **8** have a curved shape meaning that the trough or bottom of the nose depression **8** is curved and has a radius of curvature R**4**. In one embodiment, the nose depressions are cut using a 1/8 inch ball end mill.

[0165] The longitudinal axis **44** of the projectile **2** is shown in FIG. **15**B. Accordingly, the angle α of the nose depressions **8** can be measured from the centerline **10** of the nose depressions **8** relative to the longitudinal axis **44**. In some embodiments, the angle α is measured relative to the original ogive of the projectile nose portion **6**. In some embodiments, all nose depressions **8** have the same angle α. In other embodiments, each nose depression **8** has a different angle α. In still other embodiments, some nose depressions **8** have the same angle α while other nose depressions **8** have different angles α. In the embodiment shown, the nose depressions **8** are right-hand nose depressions **8** because the angle α is positioned to the right of the longitudinal axis **44**. However, the projectile **2** can have more or fewer nose depressions **8**.

[0166] In one embodiment, the radius of curvature R**4** of the nose depressions **8** is between about 0.06 inches and about 0.20 inches. In a preferred embodiment, the radius of curvature R**4** of the nose depressions **8** is between about 0.08 inches and about 0.15 inches. In a more preferred embodiment, the radius of curvature R**4** of the nose depressions **8** is about 0.09375 inches. In one embodiment, the length L**1** of the projectile **2** is between about 1.206 inches and about 1.606 inches. In a preferred embodiment, the length L**1** of the projectile **2** is between about 1.306 inches and about

1.506 inches. In a more preferred embodiment, the length L**1** of the projectile **2** is about 1.406 inches. In one embodiment, the length L**2** of the nose portion **6** is between about 0.497 inches and about 0.897 inches. In a preferred embodiment, the length L**2** of the nose portion **6** is between about 0.597inches and about 0.797 inches. In a more preferred embodiment, the length L**2** of the nose portion **6** is about 0.697 inches. In one embodiment, the length L**3** of the cylindrical portion **20** is between about 0.209 inches and about 0.609 inches. In a preferred embodiment, the length L**3** of the cylindrical portion **20** is between about 0.309 inches and about 0.509 inches. In a more preferred embodiment, the length L**3** of the cylindrical portion **20** is about 0.409 inches. In one embodiment, the length L**4** of the boat tail **38** is between about 0.10 inches and about 0.50 inches. In a preferred embodiment, the length L**4** of the boat tail **38** is between about 0.20 inches and about 0.40 inches. In a more preferred embodiment, the length L**4** of the boat tail **38** is about 0.30 inches. The diameter D**1** of the projectile **2** (also called the caliber) varies according the various embodiments. In one embodiment, the diameter D**1** of the projectile **2** is between about 0.108 inches and about 0.508 inches. In a preferred embodiment, the diameter D**1** of the projectile **2** is between about 0.208 inches and about 0.408 inches. In the embodiment shown, the diameter D**1** of the projectile **2** is about 0.308 inches. In one embodiment, the angle α of the nose depressions **8** is between about 5 degrees and about 13 degrees. In a preferred embodiment, the angle α of the nose depressions **8** is between about 7 degrees and about 11 degrees. In a more preferred embodiment, the angle α of the nose depressions **8** is about 9.0 degrees.

[0167] FIGS. **16**A-D show a projectile according to a sixteenth embodiment of the invention. FIG. **16**A is a perspective view of the projectile **2**. FIG. **16**B is a side elevation view of the projectile **2**. FIG. **16**C is a top plan view of the projectile **2**. FIG. **16**D is a cross section. Note that FIGS. **16**A-D are to scale. The projectile **2** comprises a tip **4** on one end opposite a base **30** on the other end. The projectile **2** comprises a nose portion **6** and a cylindrical portion **20** (also called a shank). The nose portion **6** includes nose depressions **8** (also called cutouts or troughs) and a nose remaining portion **22** between the nose depressions **8**, where each nose remaining portion **22** is positioned between two nose depressions **8**. The remaining portions **22** are the uncut portions having the projectile's original ogive. In some embodiments, the nose depressions **8** terminate in a substantially flat shoulder **18** (not shown). The nose depressions **8** have a curved shape meaning that the trough or bottom of the nose depression **8** is curved and has a radius of curvature R**4**. In one embodiment, the nose depressions are cut using a 3/16 inch flat end mill.

[0168] The longitudinal axis **44** of the projectile **2** is shown in FIG. **16**B. Accordingly, the angle α of the nose depressions **8** can be measured relative to the longitudinal axis **44**. In some embodiments, the angle α is measured from the centerline **10** of the nose depressions **8** relative to the original ogive of the projectile nose portion **6**. In some embodiments, all nose depressions **8** have the same angle α. In other embodiments, each nose depression **8** has a different angle α. In still other embodiments, some nose depressions **8** have the same angle α while other nose depressions **8** have different angles α. In the embodiment shown, the nose depressions **8** are right-hand nose depressions **8** because the angle α is positioned to the right of the longitudinal axis **44**. In one embodiment, the projectile **2** has at least three nose depressions **8**. However, the projectile **2** can have more or fewer nose depressions **8**.

[0169] In one embodiment, the radius of curvature R**4** of the nose depressions **8** is between about 0.06 inches and about 0.20 inches. In a preferred embodiment, the radius of curvature R**4** of the nose depressions **8** is between about 0.08 inches and about 0.15 inches.

[0170] In a more preferred embodiment, the radius of curvature R**4** of the nose depressions **8** is about 0.09375 inches. In one embodiment, the length L**1** of the projectile **2** is between about 1.206 inches and about 1.606 inches. In a preferred embodiment, the length L**1** of the projectile **2** is between about 1.306 inches and about 1.506 inches. In a more preferred embodiment, the length L**1** of the projectile **2** is about 1.406 inches. In one embodiment, the length L**2** of the nose portion **6** is between about 0.627 inches and about 1.027 inches. In a preferred embodiment, the length L**2** of the nose portion **6** is between about 0.727inches and about 0.927 inches. In a more preferred embodiment, the length L**2** of the nose portion **6** is about 0.827 inches. In one embodiment, the length L**3** of the cylindrical portion **20** is between about 0.149 inches and about 0.549 inches. In a preferred embodiment, the length L**3** of the cylindrical portion **20** is between about 0.249 inches and about 0.449inches. In a more preferred embodiment, the length L**3** of the cylindrical portion **20** is about 0.349 inches. In one embodiment, the length L**4** of the boat tail **38** is between about 0.08 inches and about 0.38 inches. In a preferred embodiment, the length L**4** of the boat tail **38** is between about 0.18 inches and about 0.28 inches. In a more preferred embodiment, the length L**4** of the boat tail **38** is about 0.23 inches. The diameter D**1** of the projectile **2** (also called the caliber) varies according the various embodiments. In one embodiment, the diameter D**1** of the projectile **2** is between about 0.108 inches and about 0.508 inches. In a preferred embodiment, the diameter D**1** of the projectile **2** is between about 0.208 inches and about 0.408 inches. In the embodiment shown, the diameter D**1** of the projectile **2** is about 0.308 inches. In one embodiment, the angle α of the nose depressions **8** is between about 3.5 degrees and about 7.5 degrees. In a preferred embodiment, the angle α of the nose depressions **8** is between about 4.5 degrees and about 6.5 degrees. In a more preferred embodiment, the angle α of the nose depressions **8** is about 5.5 degrees. In one embodiment, the angle θ of the boat tail **38** is between about 5degrees and about 10 degrees. In a preferred embodiment, the angle θ of the boat tail **38** is between about 6.5 degrees and about 8.0 degrees. In a more preferred embodiment, the angle θ of the boat tail **38** is about 7.5 degrees.

[0171] FIGS. **17**A-C show a projectile according to a seventeenth embodiment of the invention. FIG. **17**A is a perspective view of the projectile **2**. FIG. **17**B is a side elevation view of the projectile **2**. FIG. **17**C is a top plan view of the projectile **2**. Note that FIGS. **17**A-C are to scale.

[0172] The projectile **2** comprises a tip **4** on one end opposite a base **30** on the other end. The projectile **2** comprises a nose portion **6** and a cylindrical portion **20** (also called a shank). The nose portion **6** includes nose depressions **8** (also called cutouts or troughs) and a nose remaining portion **22** between two nose depressions **8**. The remaining portions **22** are the uncut portions having the projectile's original ogive. The nose depressions **8** have a curved shape meaning that the trough or bottom of the nose depression **8**

is curved and has a radius of curvature R4. In one embodiment, the nose depressions are cut using a ⅛ inch ball end mill.

[0173] The angle of the nose depressions **8** can be measured relative to the longitudinal axis **44**. In some embodiments, the angle is measured from the centerline **10** of the nose depressions **8** relative to the original ogive of the projectile nose portion **6**. In some embodiments, all nose depressions **8** have the same angle. In other embodiments, each nose depression **8** has a different angle. In still other embodiments, some nose depressions **8** have the same angle while other nose depressions **8** have different angles. In one embodiment, the projectile **2** has at least three nose depressions **8**. However, the projectile **2** can have more or fewer nose depressions **8**.

[0174] In one embodiment, the length L1 of the projectile **2** is between about 1.20 inches and about 1.60 inches. In a preferred embodiment, the length L1 of the projectile **2** is between about 1.30 inches and about 1.50 inches. In a more preferred embodiment, the length L1 of the projectile **2** is about 1.40 inches. In one embodiment, the length L2 of the nose portion **6** is between about 1 inch and about 1.4 inches. In one embodiment, the length L3 of the cylindrical portion **20** is between about 0.5 inches and about 0.8 inches. In one embodiment, the length L4 of the boat tail **38** is between about 0.2 inches and about 0.5inches. The diameter D1 of the projectile **2** (also called the caliber) varies according the various embodiments. In one embodiment, the diameter D1 of the projectile **2** is between about 0.108 inches and about 0.508 inches. In a preferred embodiment, the diameter D1 of the projectile **2** is between about 0.208 inches and about 0.408 inches. In the embodiment shown, the diameter D1 of the projectile **2** is about 0.308 inches.

[0175] This projectile is armor-piercing. The large, long cuts or depressions in the nose ensure the projectile can penetrate and go through metal and other tough or hard material. This projectile is for military and civilian use. Other intended users of the projectile are African big game hunters. The attributes of this projectile are deep straight penetration with transfer of energy. The projectile is comprised of brass, copper, bronze, tungsten-carbide, alloys of these metals, or any material known in the art, including plastics and ceramics.

[0176] FIGS. **18**A-D show a projectile according to an eighteenth embodiment of the invention. FIG. **18**A is a perspective view of the projectile **2**. FIG. **18**B is a side elevation view of the projectile **2**. FIG. **18**C is a top plan view of the projectile **2**. FIG. **18**D is a cross section taken along cut D-D of FIG. **18**C. Note that FIGS. **18**A-D are to scale. This projectile is two pieces and includes a housing **40** and an insert **42**.

[0177] The projectile **2** comprises a tip **4** on one end opposite a base **30** on the other end. The projectile **2** comprises a nose portion **6** and a cylindrical portion **20** (also called a shank). The nose portion **6** includes nose depressions **8** (also called cutouts or troughs) and nose remaining portions **22** between the nose depressions **8**. The remaining portions **22** are the uncut portions having the projectile's original ogive. In some embodiments, the nose depressions **8** terminate in a substantially flat shoulder **18** (not shown). The nose depressions **8** have a curved shape meaning that the trough or bottom of the nose depression **8** is curved and has a radius of curvature R4. In one embodiment, the nose depressions are cut using a 3/16 inch flat end mill.

[0178] The longitudinal axis **44** of the projectile **2** is shown in FIG. **18**B. Accordingly, the angle α of the nose depressions **8** can be measured from the centerline **10** of the nose depressions **8** relative to the longitudinal axis **44**. In some embodiments, the angle α is measured relative to the original ogive of the projectile nose portion **6**. In some embodiments, all nose depressions **8** have the same angle α. In other embodiments, each nose depression **8** has a different angle α. In still other embodiments, some nose depressions **8** have the same angle α while other nose depressions **8** have different angles α. In one embodiment, the projectile **2** has at least three nose depressions **8**. However, the projectile **2** can have more or fewer nose depressions **8**.

[0179] In one embodiment, the radius of curvature R4 of the nose depressions **8** is between about 0.010 inches and about 0.325 inches. In a preferred embodiment, the radius of curvature R4 of the nose depressions **8** is between about 0.025 inches and about 0.225inches. In a more preferred embodiment, the radius of curvature R4 of the nose depressions **8** is about 0.125 inches. In one embodiment, the length L1 of the projectile **2** is between about 1.206 inches and about 1.606 inches. In a preferred embodiment, the length L1 of the projectile **2** is between about 1.306 inches and about 1.506 inches. In a more preferred embodiment, the length L1 of the projectile **2** is about 1.406 inches. In one embodiment, the length L2 of the nose portion **6** is between about 0.627 inches and about 1.027 inches. In a preferred embodiment, the length L2 of the nose portion **6** is between about 0.727inches and about 0.927 inches. In a more preferred embodiment, the length L2 of the nose portion **6** is about 0.827 inches. In one embodiment, the length L3 of the cylindrical portion **20** is between about 0.149 inches and about 0.459 inches. In a preferred embodiment, the length L3 of the cylindrical portion **20** is between about 0.249 inches and about 0.449inches. In a more preferred embodiment, the length L3 of the cylindrical portion **20** is about 0.349 inches. In one embodiment, the length L4 of the boat tail **38** is between about 0.08 inches and about 0.38 inches. In a preferred embodiment, the length L4 of the boat tail **38** is between about 0.18 inches and about 0.28 inches. In a more preferred embodiment, the length L4 of the boat tail **38** is about 0.23 inches. In one embodiment, the length L5 of the housing **40** is between about 0.627 inches and about 1.027 inches. In a preferred embodiment, the length L5 of the housing **40** is between about 0.727 inches and about 0.927 inches. In a more preferred embodiment, the length L5 of the housing **40** is about 0.827 inches. The diameter D1 of the projectile **2** (also called the caliber) varies according the various embodiments. In one embodiment, the diameter D1 of the projectile **2** is between about 0.108 inches and about 0.508 inches. In a preferred embodiment, the diameter D1 of the projectile **2** is between about 0.208 inches and about 0.408 inches. In the embodiment shown, the diameter D1 of the projectile **2** is about 0.308 inches. In one embodiment, the angle α of the nose depressions **8** is between about 3.5 degrees and about 7.5 degrees. In a preferred embodiment, the angle α of the nose depressions **8** is between about 4.5 degrees and about 6.5 degrees. In a more preferred embodiment, the angle α of the nose depressions **8** is about 5.5 degrees.

[0180] FIGS. **19**A-C show a projectile according to a nineteenth embodiment of the invention. FIG. **19**A is a perspective view of the projectile **2**. FIG. **19**B is a side

elevation view of the projectile **2**. FIG. **19**C is a top plan view of the projectile **2**. Note that FIGS. **19**A-C are to scale.

[0181] The projectile **2** comprises a tip **4** on one end opposite a base **30** on the other end. The rounded tip **4** acts like pointed tip due to its aerodynamic properties. The projectile **2** comprises a nose portion **6** and a cylindrical portion **20**. The nose portion **6** includes nose depressions **8** and nose remaining portion **22** between the nose depressions **8**, where each nose remaining portion **22** is positioned between two nose depressions **8**. The remaining portions **22** are the uncut portions having the projectile's original ogive. The nose depressions **8** have a curved shape meaning that the trough or bottom of the nose depression **8** is curved and has a radius of curvature R**4**. In one embodiment, the nose depressions are cut using a ⅜ inch ball end mill. In the embodiment of FIGS. **19**A-C, the projectile **2** has one relief cut **28**. In some embodiments, the projectile **2** includes a plurality of relief cuts **28**.

[0182] The longitudinal axis **44** of the projectile **2** is shown in FIG. **19**B. The angle α of the nose depressions **8** can be measured from the centerline **10** of the nose depressions **8** relative to the longitudinal axis **44**. In some embodiments, the angle α is measured relative to the original ogive of the projectile nose portion **6**. In some embodiments, all nose depressions **8** have the same angle α. In other embodiments, each nose depression **8** has a different angle α. In still other embodiments, some nose depressions **8** have the same angle a while other nose depressions **8** have different angles α. In the embodiment shown, the nose depressions **8** are right-hand nose depressions **8** because the angle α is positioned to the right of the longitudinal axis **44**. In one embodiment, the projectile **2** has at least three nose depressions **8**. However, the projectile **2** can have more or fewer nose depressions **8**. As shown in FIGS. **19**A and **19**C, the nose depressions **8** do not extend all the way to the tip **4** and the nose depressions **8** do not intersect one another. Thus, the remaining portions **22** extend to the tip **4**. Additionally, the nose depressions **8** do not extend all the way to a forward portion of the cylindrical portion **20**.

[0183] In one embodiment, the radius of curvature R**4** of the nose depressions **8** is between about 0.05 inches and about 0.30 inches. In a preferred embodiment, the radius of curvature R**4** of the nose depressions **8** is between about 0.10 inches and about 0.25 inches. In a more preferred embodiment, the radius of curvature R**4** of the nose depressions **8** is about 0.1875 inches. In one embodiment, the length L**1** of the projectile **2** is between about 0.5 inches and about 1.5 inches. In a preferred embodiment, the length L**1** of the projectile **2** is between about 0.75 inches and about 1.25 inches. In a more preferred embodiment, the length L**1** of the projectile **2** is about 1.0 inch. In one embodiment, the length L**2** of the nose portion **6** is between about 0.25 inches and about 0.75 inches. In a preferred embodiment, the length L**2** of the nose portion **6** is between about 0.4 inches and about 0.6inches. In a more preferred embodiment, the length L**2** of the nose portion **6** is about 0.500inches. In one embodiment, the length L**3** of the cylindrical portion **20** is between about 0.30 inches and about 0.70 inches. In a preferred embodiment, the length L**3** of the cylindrical portion **20** is between about 0.40 inches and about 0.60 inches. In a more preferred embodiment, the length L**3** of the cylindrical portion **20** is about 0.500 inches.

[0184] The diameter D**1** of the projectile **2** (also called the caliber) varies according the various embodiments. In one embodiment, the diameter D**1** of the projectile **2** is between about 0.20 inches and about 0.50 inches. In a preferred embodiment, the diameter D**1** of the projectile **2** is between about 0.30 inches and about 0.40 inches. In the embodiment shown, the diameter D**1** of the projectile **2** is about 0.3075 inches. In one embodiment, the angle a of the nose depressions **8** is between about 3.0 degrees and about 10.0 degrees. In a preferred embodiment, the angle α of the nose depressions **8** is between about 4.5 degrees and about 6.5 degrees. In a more preferred embodiment, the angle α of the nose depressions **8** is about 5.5 degrees.

[0185] FIGS. **20**A-D show a projectile according to a twentieth embodiment of the invention. FIG. **20**A is a perspective view of the projectile **2**. FIG. **20**B is a side elevation view of the projectile **2**. FIG. **20**C is a top plan view of the projectile **2**. FIG. **20**D is a cross section taken at cut D-D of FIG. **20**C.

[0186] The projectile **2** comprises a tip **4** on one end opposite a base **30** on the other end. The projectile **2** comprises a nose portion **6** and a cylindrical portion **20**. The nose portion **6** includes nose depressions **8** and nose remaining portions **22** between the nose depressions **8**, where each nose remaining portion **22** is positioned between two nose depressions **8**. The remaining portions **22** are the uncut portions having the projectile's original ogive. The remaining portions **22** have a generally triangular shape with the tip of the triangle positioned proximate to the tip **4** of the projectile and the base of the triangle positioned proximate to the rear of the nose **6** and the forward portion of the cylindrical portion **20**. A first edge **92** is formed between a nose depression **8** and a remaining portion **22** and a second edge **72** proximate the tip **4** is formed between two nose depressions **8**. The first edge **92** and/or the second edge **72** may be referred to as a cutter edge in some embodiments. The nose depressions **8** can terminate in a substantially flat shoulder **18** in some embodiments. In other embodiments, a shoulder is not present between the nose depressions **8** and the front **56** of the housing **40**. The nose depressions **8** have a curved shape meaning that the trough or bottom of the nose depression **8** is curved and has a radius of curvature R**4**. In one embodiment, the nose depressions are cut using a ⅜ inch ball end mill.

[0187] The longitudinal axis **44** of the projectile **2** is shown in FIG. **20**B. The angle α of the nose depressions **8** can be measured from the centerline **10** of the nose depressions **8** relative to the longitudinal axis **44**. In some embodiments, the angle α is measured relative to the original ogive of the projectile nose portion **6** or the remaining portion **22**. In some embodiments, all nose depressions **8** have the same angle α. In other embodiments, each nose depression **8** has a different angle α. In still other embodiments, some nose depressions **8** have the same angle α while other nose depressions **8** have different angles α. In the embodiment shown, the nose depressions **8** are right-hand nose depressions **8** because the angle α is positioned to the right of the longitudinal axis **44**. In one embodiment, the projectile **2** has at least three nose depressions **8**. However, the projectile **2** can have more or fewer nose depressions **8**.

[0188] In one embodiment, the radius of curvature R**4** of the nose depressions **8** is between about 1/32 inches and about 0.50 inches. In a preferred embodiment, the radius of curvature R**4** of the nose depressions **8** is between about 3/32 inches and about ⅜ inches. In a more preferred embodiment, the radius of curvature R**4** of the nose depressions **8** is about

0.1875 inches. In one embodiment, the length L**1** of the projectile **2** is between about 0.400 inches and about 1.00 inch. In a preferred embodiment, the length L**1** of the projectile **2** is between about 0.550 inches and about 0.850 inches. In a more preferred embodiment, the length L**1** of the projectile **2** is about 0.710 inches. In one embodiment, the length L**2** of the nose portion **6** is between about 0.150 inches and about 0.500 inches. In a preferred embodiment, the length L**2** of the nose portion **6** is between about 0.350inches and about 0.450 inches. In a more preferred embodiment, the length L**2** of the nose portion **6** is about 0.400 inches. In one embodiment, the length L**3** of the cylindrical portion **20** is between about 0.100 inches and about 0.500 inches. In a preferred embodiment, the length L**3** of the cylindrical portion **20** is between about 0.200 inches and about 0.400inches. In a more preferred embodiment, the length L**3** of the cylindrical portion **20** is about 0.310 inches. The diameter D**1** of the projectile **2** (also called the caliber) varies according the various embodiments. In one embodiment, the diameter D**1** of the projectile **2** is between about 0.200 inches and about 0.500 inches. In a preferred embodiment, the diameter D**1** of the projectile **2** is between about 0.300 inches and about 0.450 inches. In the embodiment shown, the diameter D**1** of the projectile **2** is about 0.355 inches (about 9mm). In another preferred embodiment, the diameter D**1** of the projectile **2** is about 0.400inches. In yet another preferred embodiment, the diameter D**1** of the projectile **2** is about 0.450 inches. In one embodiment, the angle α of the nose depressions **8** is between about 5 degrees and about 15 degrees. In a preferred embodiment, the angle α of the nose depressions **8** is between about 6 degrees and about 9 degrees. In a more preferred embodiment, the angle α of the nose depressions **8** is about 7.5 degrees.

[0189] The advantage of this projectile is that it can shoot through armor. This projectile **2** is different from the prior art because it can pierce armor and stop in soft tissue. The sharp tip **4** and sharp cutter edges **72** allow this projectile **2** to cut through armor, including Kevlar. Additionally, the shoulders **18** of the projectile enable the projectile **2** to stop in soft tissue because the shoulders **18** slow the projectile down once it hits soft tissue. This projectile **2** is likely for military use only.

[0190] The construction of this projectile **2** may be accomplished using a press or mill and lathe. One unique and innovative feature is the shape of the front of the projectile **2**, which has a slight radius coming off the bearing surface **20** (the cylindrical portion or the shaft) but is largely formed by angled or slightly twisting depressions **8** pointed to the front. The depressions **8** form troughs and ridges **22** (or remaining portions between the depressions **8**) that possess an angle or a slight radius off the centerline **44** (longitudinal axis) of the projectile. In some embodiments, the twist angle α of the depressions **8** corresponds to (i.e., is equal to) or is greater than the barrel twist rate (i.e., the twist rate of the rifling in the barrel) and turns in the same direction as the barrel's rifling. In other embodiments, the twist angle α of the depressions **8** is equal to or greater than the barrel twist rate and turns in the opposite direction as the barrel's rifling. These depressions **8** do not affect the projectile during internal ballistics but they greatly enhance the performance during external and/or terminal ballistics. In some embodiments, at the center of the tip **4** or a portion of the nose **6** proximate the tip **4**, the ridges **92** meet to form a cutting surface or cutting edge **72**. These edges **72** initiate a cut in the target, greatly reducing resistance through media such as sheet metal, fabrics, and soft armor. The twisting troughs **8** move media away from the projectile **2** further reducing resistance and promote and maintain the spin to ensure the projectile **2** penetrates deep and straight. The troughs **8** may rapidly move liquids and soft tissue away from the path of the projectile **2** and therefore increase the wound channel.

[0191] Referring to FIGS. **21**A-**23**E, which are pistol projectile embodiments that, among other things, provide deep straight penetration. These pistol projectiles **2** are homogenous in nature and intended for deep, straight penetration. In one embodiment, the pistol projectile **2** is comprised of brass. These projectiles **2** are different from the prior art because they can pierce armor and stop in soft tissue. The sharp tip **4** and sharp cutter edges **72** allow these projectiles **2** to cut through armor, including Kevlar. Further, these projectiles **2** create a lot of cavitation in soft tissue, thus making a wound larger than it would be with a projectile of the prior art. Intended users of these projectiles **2** comprise military and law enforcement.

[0192] The construction of these projectiles **2** may be accomplished using a press or mill and lathe. One unique and innovative feature is the shape of the front of the projectile **2**, which has a slight radius coming off the bearing surface **20** (the cylindrical portion or the shaft) but is largely formed by angled or slightly twisting depressions **8** pointed to the front. The depressions **8** form troughs and ridges **22** (or remaining portions between the depressions) that possess an angle or a slight radius off the centerline **44** (longitudinal axis) of the projectile **2**. In some embodiments, the twist angle α of the depressions **8** corresponds to (i.e., is equal to) or is greater than the barrel twist rate (i.e., the twist rate of the rifling in the barrel) and turns in the same direction as the barrel's rifling. In other embodiments, the twist angle α of the depressions **8** is equal to or greater than the barrel twist rate and turns in the opposite direction as the barrel's rifling. These depressions **8** do not affect the projectile **2** during internal ballistics but they greatly enhance the performance during external and/or terminal ballistics. In some embodiments, at the center of the tip **4** or a portion of the nose **6** proximate the tip **4**, the ridges **92** meet to form a cutting surface or cutting edge **72**. These edges **72** initiate a cut in the target, greatly reducing resistance through media such as sheet metal, fabrics, and soft armor. The twisting troughs **8** move media away from the projectile **2** further reducing resistance and promote and maintain the spin to ensure the projectile **2** penetrates deep and straight. The troughs **8** may rapidly move liquids and soft tissue away from the path of the projectile **2** and therefore increase the wound channel.

[0193] In one embodiment, the pistol projectile **2** is manufactured via a Swiss Turn machine or the combination of a lathe and mill. Alternatively, the pistol projectile **2** is manufactured via a powdered or gilding metal that is then pressed into a die at high pressure. Due to the direct interface with the barrel, a softer metal may be used. The sharp edges **72** in the front create the ability to penetrate armor (hard and soft) and metal. Testing has revealed that the **78** grain 9 mm projectile moving at 1550 fps will penetrate the following materials: 16 sheets of 22-gauge steel and Level IIIA soft Kevlar. This same projectile fired from a 380 moving 830 fps will penetrate Level IIIA soft armor. If the twist (angle α from centerline **44**) of the trough **8** is in the same direction

of the rifling, it will increase the penetration in tissue. The angle α is to be equal to or greater than the angle of the rifling.

[0194] The angle of the rifling is subject to change by barrel twist rate and caliber. For example, a 9 mm (0.355") with a 1 in 10" rate of twist will have a different alpha (α) angle than the same rate of twist in a 45 ACP (0.451"). Different barrels will have different rates of twist and can differ in the direction of the twist. In FIGS. **21-23**, all the alpha angles are set to 15 degrees or 25 degrees. When this projectile **2** is fired from a barrel that twists in the opposing direction of the alpha angle, the penetration lessens but the tissue damage increases. A lower alpha angle or thicker/fatter front to the projectile **2** will have greater tissue damage and a lesser ability to penetrate armor. A higher alpha angle or sharper projectile will penetrate better but do less tissue damage.

[0195] In one embodiment of the pistol projectile, terminal ballistics traits are emphasized. The tip **4** of the projectile **2** is formed such that the trough **8** is at an angle α relative to the longitudinal axis **44** of the projectile **2**. Due to magazine and chamber constraints, projectiles have a maximum length. The density of the material will determine this alpha angle because a steeper alpha angle cuts better, but has a lower weight.

[0196] In some embodiments, the twist rate a of the ridges **92** can equal to or exceeds, by up to double, the twist rate of the barrel. In one embodiment, the projectile **2** would increase the rate of twist once it struck the terminal media. In one embodiment, a projectile **2** with a counter twist to (i.e., in the opposite direction of) the rifling is provided, therefore limiting penetration once it cuts through the outer layer of its target. Twist rates in most handguns, run from 4-7 degrees, but could be between 2-10 degrees.

[0197] In general, the non-congruent twist penetrates less into the target and larger end mill cuts penetrate less into the target. These projectiles **2** create cavitation and slow down in soft tissue. The advantages generally include the case of manufacturing and the non-expanding bullet (i.e., no housing and cavities). Further, the projectile **2** does not deflect in auto glass, it shoots through sheet metal and body armor using its cutting edges **72**, and it creates a cavitation in tissue to help the projectile **2** slow down in the soft tissue. A congruent twist will increase the depth of the projectile's penetration in soft media. The shorter the distance the projectile travels in the target, the more energy is released in a shorter distance. Thus, a wider tissue area is affected in order to absorb the energy.

[0198] This projectile **2** is different from the prior art because it can pierce armor and stop in soft tissue. The sharp tip **4** and sharp cutter edges **72** allow this projectile **2** to cut through armor, including Kevlar. Additionally, the nose depressions **8** positioned at an angle α greater than about 10 degrees create cavitation to collect the target medium such that the projectile **2** stops in soft tissue. This projectile is likely for military and civilian use. The density of the projectiles may be about 7 g/cm^3.

[0199] FIGS. **21**A-C show a projectile according to a twenty-first embodiment of the invention. FIG. **21**A is a perspective view of the projectile **2**. FIG. **21**B is a side elevation view of the projectile **2**. FIG. **21**C is a top plan view of the projectile **2**. Note that FIGS. **21**A-C are to scale.

[0200] The projectile **2** comprises a tip **4** on one end opposite a base **30** on the other end. The projectile **2** comprises a nose portion **6** and a cylindrical portion **20**. The nose portion **6** includes nose depressions **8** and nose remaining portions **22** between the nose depressions **8**, where each nose remaining portion **22** is positioned between two nose depressions **8**. The remaining portions **22** are the uncut portions having the projectile's original ogive. The nose depressions **8** have a curved shape meaning that the trough or bottom of the nose depression **8** is curved and has a radius of curvature R**4**. In one embodiment, the nose depressions are cut using a 3/16 inch ball end mill. The nose depressions **8** extend from a front portion of the cylindrical portion **20** to the tip **4** of the projectile.

[0201] The longitudinal axis **44** of the projectile **2** is shown in FIG. **21**B. The angle α of the nose depressions **8** can be measured from the centerline **10** of the nose depressions **8** relative to the longitudinal axis **44**. As with all embodiments described herein, the nose depressions **8** can be right or left-hand depressions **8**. In some embodiments, the angle α is measured relative to the original ogive of the projectile nose portion **6**. In some embodiments, all nose depressions **8** have the same angle α. In other embodiments, each nose depression **8** has a different angle α. In still other embodiments, some nose depressions **8** have the same angle α while other nose depressions **8** have different angles α. In the embodiment shown, the nose depressions **8** are left-hand nose depressions **8** because the angle α is positioned to the left of the longitudinal axis **44**. In one embodiment, the projectile **2** has at least three nose depressions **8**. However, the projectile **2** can have more or fewer nose depressions **8**.

[0202] In one embodiment, the radius of curvature R**4** of the nose depressions **8** is between about 0.05 inches and about 0.15 inches. In a preferred embodiment, the radius of curvature R**4** of the nose depressions **8** is between about 0.075 inches and about 0.11inches. In a more preferred embodiment, the radius of curvature R**4** of the nose depressions **8** is about 0.09375 inches. In one embodiment, the length L**1** of the projectile **2** is between about 0.40 inches and about 0.80 inches. In a preferred embodiment, the length L**1** of the projectile **2** is between about 0.50 inches and about 0.60 inches. In a more preferred embodiment, the length L**1** of the projectile **2** is about 0.600 inches. In one embodiment, the length L**2** of the nose portion **6** is between about 0.20 inches and about 0.40 inches. In a preferred embodiment, the length L**2** of the nose portion **6** is between about 0.25 inches and about 0.35 inches. In a more preferred embodiment, the length L**2** of the nose portion **6** is about 0.315 inches. In one embodiment, the length L**3** of the cylindrical portion **20** is between about 0.20 inches and about 0.50 inches. In a preferred embodiment, the length L**3** of the cylindrical portion **20** is between about 0.25 inches and about 0.35 inches. In a more preferred embodiment, the length L**3** of the cylindrical portion **20** is about 0.285inches. The diameter D**1** of the projectile **2** varies according the various embodiments. In one embodiment, the diameter D**1** of the projectile **2** is between about 0.200 inches and about 0.500 inches. In a preferred embodiment, the diameter D**1** of the projectile **2** is between about 0.300 inches and about 0.450 inches. In the embodiment shown, the diameter D**1** of the projectile **2** is about 0.355 inches (about 9 mm). In another preferred embodiment, the diameter D**1** of the projectile **2** is about 0.400 inches. In yet another preferred embodiment, the diameter D**1** of the projectile **2** is about 0.450 inches. In one embodiment, the angle α of the nose depressions **8** is between about 5 degrees and about 45 degrees. In a pre-

ferred embodiment, the angle α of the nose depressions **8** is between about 20 degrees and about 30 degrees. In a more preferred embodiment, the angle α of the nose depressions **8** is about 25 degrees.

[0203] FIGS. **22**A-C show a projectile according to a twenty-second embodiment of the invention. FIG. **22**A is a perspective view of the projectile **2**. FIG. **22**B is a side elevation view of the projectile **2**. FIG. **22**C is a top plan view of the projectile **2**. Note that FIGS. **22**A-C are to scale.

[0204] FIGS. **22**A-C are the same as FIGS. **21**A-C except that the nose depressions **8** are right-hand nose depressions **8** because the angle α is positioned to the right of the longitudinal axis **44**. Further, the nose depressions **8** are cut using a ⅜ inch ball end mill. The nose depressions **8** in FIG. **22**A-C may be shorter and deeper than the nose depression **8** of FIGS. **21**A-C. In one embodiment, the radius of curvature R**4** of the nose depressions **8** is between about 0.10 inches and about 0.30 inches. In a preferred embodiment, the radius of curvature R**4** of the nose depressions **8** is between about 0.15 inches and about 0.25 inches. In a more preferred embodiment, the radius of curvature R**4** of the nose depressions **8** is about 0.1875 inches.

[0205] FIGS. **23**A-E show a projectile according to a twenty-third embodiment of the invention. FIG. **23**A is a perspective view of the projectile **2**. FIG. **23**B is a side elevation view of the projectile **2**. FIG. **23**C is a top plan view of the projectile **2**. FIG. **23**D is a cross section taken at cut D-D. FIG. **23**E is a cross section taken at cut E-E. Note that FIGS. **23**A-E are to scale.

[0206] FIGS. **23**A-E are the same as FIGS. **21**A-C except that the nose depressions **8** are cut using a 0.50 inch ball end mill. Each nose depression **8** has a radius of curvature R**4** because it has a curved or rounded bottom. The radius of curvature R**4** of the depression **8** is shown in FIGS. **23**C and **23**E. In one embodiment, the radius of curvature R**4** of the nose depressions **8** is between about 0.10 inches and about 0.50 inches. In a preferred embodiment, the radius of curvature R**4** of the nose depressions **8** is between about 0.20inches and about 0.30 inches. In a more preferred embodiment, the radius of curvature R**4** of the nose depressions **8** is about 0.25 inches. Further, the diameter D**1** of the projectile **2** varies according the various embodiments. In one embodiment, the diameter D**1** of the projectile **2** is between about 0.200 inches and about 0.600 inches. In a preferred embodiment, the diameter D**1** of the projectile **2** is between about 0.300 inches and about 0.50 inches. In the embodiment shown, the diameter D**1** of the projectile **2** is about 0.400inches. In another preferred embodiment, the diameter D**1** of the projectile **2** is about 0.450 inches.

[0207] FIGS. **24**A-D show a projectile according to a twenty-fourth embodiment of the invention. FIG. **24**A is a perspective view of the projectile **2**. FIG. **24**B is a side elevation view of the projectile **2**. FIG. **24**C is a top plan view of the projectile **2**. FIG. **24**D shows a cross section of the projectile **2** taken along cut D-D of FIG. **24**B. Note that FIGS. **24**A-D are to scale. FIG. **24** is the same as FIG. **35** except that the projectile of FIG. **24** has three inserts, **42**A, **42**B, **42**C. Further, the first insert **42**A is metal, for example, steel, Inconel, or another hard metal. The second insert **42**B is aluminum or other soft metal. The third insert **42**C is tungsten or another hard metal. Cavities **24** are positioned between the inserts **42**A, **42**B, **42**C and the housing **40**.

[0208] The longitudinal axis **44** of the projectile **2** is shown in FIG. **24**B. Accordingly, the angle α of the nose depressions **8** can be measured from the centerline **10** of the nose depressions **8** relative to the longitudinal axis **44**. In the embodiment shown, the nose depressions **8** are right-hand nose depressions **8** because the angle α is positioned to the right of the longitudinal axis **44**. In one embodiment, the projectile **2** has at least three nose depressions **8**. The depressions **8** create cavities **24** between the inserts **42**A, **42**B, **42**C, and the housing **40** such that when the projectile **2** hits a soft medium target, the cavities **24** fill with the soft medium and the projectile slows down. The steeper (i.e., greater) alpha angle will also transfer media at a greater rate into the housing for a faster opening and expansion of the housing **40** upon impact with the terminal media.

[0209] The cylindrical portion **20** comprises angled drive bands **26**A and angled relief cuts **28**A. The angled drive bands **26**A and angled relief cuts **28**A create air disturbances that stabilize the projectile **2** in flight allowing the projectile **2** to fly straighter and be less affected by cross winds than projectiles of the prior art.

[0210] FIGS. **25**A-C show a projectile **2** according to a twenty-fifth embodiment of the invention. This projectile **2** creates large cavitations and giant wounds. When the projectile **2** hits soft tissue, the housing **40** flowers and peels backward as shown in FIG. **30**. This projectile **2** can also be accurately shot through glass because it maintains its original flight path. The projectile **2** keeps its shape through hard material (e.g., glass or steel) and it keeps its trajectory: tip forward flight. It can also penetrate body armor and stop in soft tissue because when it hits soft tissue it opens up (see FIGS. **30**A-**31**C). FIG. **25**A is a perspective view of the projectile **2**. FIG. **25**B is a side elevation view of the projectile **2**. FIG. **25**C is a top plan view of the projectile **2**. Note that FIGS. **25**A-C are to scale.

[0211] FIGS. **27**A-C show the insert **42** used in the projectile **2** of FIGS. **25**A-C. FIGS. **26**A-B show the housing **40** used in the projectile **2** of FIG. **25**A-C. FIGS. **25**A-C depict a two-piece bullet embodiment. Intended users comprise military, law enforcement, and private citizens. Among other things, these embodiments provide deep straight penetration in, for example, sheet metal, clothing, soft armor, and fabrics, but may provide limited penetration in tissue. These embodiments may be manufactured of materials comprising brass, copper, aluminum, tungsten-carbide, or alloys to form the insert **42** and copper or brass, for example, to form the housing **40**.

[0212] The construction of these projectiles **2** may be accomplished using a press or mill and lathe. One feature is the shape of the insert **42** of the projectile **2**, largely formed by slightly twisting depressions **8** pointed to the front of the insert **42**. The depressions **8** form troughs and ridges that form the point **4** of the insert **42**. The tip **4** of the insert is positioned forward of the housing **40** and the terminal ends of the troughs **8** and ridges **22** extend into the housing **40**. Proximate the tip **4**, the depressions **8** intersect forming cutting edges **72**. The cutting edges **72** initiate a cut in the target to promote the penetration through the outer layer and because a portion of the troughs **8** are inside the housing **40** results in rapid and violent expansion of the housing **40** upon impact with the projectile's target. The twist of the depressions **8** corresponds to or is greater than the twist rate of the rifling in the barrel and the depressions **8** turn in the same direction or the opposite direction of the barrel. The projectile can also have a cut perpendicular to the radius line which would generate a zero twist degree. At the center of the tip

4, the ridges **72** join together to form a cutting surface. These edges **72** initiate a cut, greatly reducing resistance through media such as sheet metal, fabrics, and soft armor. The twisting troughs **8** move media away from the projectile **2** and rapidly open the housing **40** to create greater frontal surface area of the projectile **2** during terminal ballistics. In one embodiment, a cap is pressed into place that covers the insert and is held by the housing, which provides a first media to initiate the opening of the housing during the first stages of terminal ballistics.

[0213] One advantage of the housing is the ability to make the insert **42** out of almost any material (e.g., brass, aluminum, steel, polymers, etc.). The insert **42** does not interface with the barrel so the use of hard materials or even steel is also feasible. Both steel and aluminum in both similar and opposed twist directions have been tested and are further embodiments. When the twist rate is opposed to the rifling, in particular with the aluminum insert, the tissue destruction is immense. All testing has shown that all these designs will penetrate in similar fashion on both hard and soft armor. The steeper (i.e., greater) alpha angle will also transfer media at a greater rate into the housing for a faster opening and expansion of the housing **40** upon impact with the terminal media.

[0214] The projectile **2** comprises a tip **4** on one end opposite a base **30** on the other end. The projectile **2** comprises a nose portion **6** and a cylindrical portion **20** (also called a shank). The nose portion **6** includes nose depressions **8** (also called cutouts or troughs) and a nose remaining portion **22** between the nose depressions **8**, where each nose remaining portion **22** is positioned between two nose depressions **8**. The remaining portions **22** are the uncut portions having the projectile's original ogive. The nose depressions **8** have a curved shape meaning that the trough or bottom of the nose depression **8** is curved and has a radius of curvature R**4**.

[0215] The longitudinal axis **44** of the projectile **2** is shown in FIG. **27**B. Accordingly, the angle α of the nose depressions **8** can be measured from the centerline **10** of the nose depressions **8** relative to the longitudinal axis **44**. In some embodiments, the angle α is measured relative to the original ogive of the projectile nose portion **6**. In some embodiments, all nose depressions **8** have the same angle α. In other embodiments, each nose depression **8** has a different angle α. In still other embodiments, some nose depressions **8** have the same angle α while other nose depressions **8** have different angles α. In one embodiment, the projectile **2** has at least three nose depressions **8**. However, the projectile **2** can have more or fewer nose depressions **8**. In one embodiment, the radius of curvature R**4** of the nose depressions **8** is between about ¼ and ¾ inch. In a preferred embodiment, the radius of curvature R**4** of the nose depressions **8** is between about ⅜ and 1/2 inch. In one embodiment, the length L**1** of the projectile **2** is between about inches and about inches. In a preferred embodiment, the length L**1** of the projectile **2** is between about 0.69 inches and about 0.71inches. In a more preferred embodiment, the length L**1** of the projectile **2** is about 0.670 inches. In one embodiment, the length L**2** of the nose portion **6** is between about 0.35inches and about 0.39 inches. In a preferred embodiment, the length L**2** of the nose portion **6** is between about 0.36 inches and about 0.38 inches. In a more preferred embodiment, the length L**2** of the nose portion **6** is about 0.37 inches. In one embodiment, the length L**5** of the housing **40** is between about 0.316 inches and about 0.716 inches. In a preferred embodiment, the length L**5** of the housing **40** is between about 0.416 inches and about 0.616 inches. In a more preferred embodiment, the length L**5** of the housing **40** is about 0.516 inches. The diameter D**1** of the projectile **2** (also called the caliber) varies according the various embodiments. In one embodiment, the diameter D**1** of the projectile **2** is between about 11 mm and about 7 mm. In a preferred embodiment, the diameter D**1** of the projectile **2** is between about 10 mm and about 8 mm. In the embodiment shown, the diameter D**1** of the projectile **2** is about 9 mm.

[0216] FIGS. **26**A-B show the projectile housing **40** of FIGS. **25**A-C. FIG. **26**A is a perspective view of the housing **40**. FIG. **26**B is a top plan view of the housing **40**. Note that FIGS. **26**A-B are to scale.

[0217] In a preferred embodiment, the dimension W**1** of the projectile **2** is between about 0.070 inches and about 0.470 inches. In a more preferred embodiment, the dimension W**1** of the projectile **2** is about 0.270 inches. In one embodiment, the length L**7** is between about 0.145 inches and about 0.345 inches. In a preferred embodiment, the length L**7** is about 0.245 inches.

[0218] FIGS. **27**A-**29**C detail the insert **42** mounted inside a housing **40**. These housings can be formed on a lathe or press and may be made from copper or brass. Any material that will not harm a barrel would be also be acceptable and form alternative embodiments of the housing **40**. The addition of the housing **40** lessens the penetration in tissue by creating greater frontal surface area and therefore increases trauma. FIGS. **27**A-**29**C detail the insert **42** mounted inside a housing **40**. By varying the alpha and beta angles of the insert **42**, one can control the penetration in armor and the destruction in tissue.

[0219] The tip of the insert is formed such that the depression or trough **8** is at an angle α relative to the longitudinal axis **44** of the insert **42**. Due to magazine and chamber constraints, projectiles have a maximum length. The density of the material used and the size of the insert **42** and projectile will determine this alpha angle because a steeper alpha angle cuts better, but has a lower weight. The steeper alpha angle will also transfer media at a greater rate into the housing for a faster opening and expansion upon impact with the terminal media.

[0220] In some embodiments, the twist rate of the depressions **8** can equal or exceed, by up to double, the twist rate of the gun barrel. In one embodiment, the projectile would increase the rate of twist once it struck the terminal media. In one embodiment, an insert **42** with a counter twist to (i.e., in the opposite direction of) the rifling is provided, therefore limiting penetration once it cuts through the outer layer of its target. The twist rate of the depressions **8** of the insert **42** may also be reversed (i.e., in the opposite direction to the barrel twist). Twist rates in most handguns run from about 4-7 degrees, but could be between about 2-10 degrees.

[0221] FIGS. **27**A-C show the projectile insert **42** of FIGS. **25**A-C. FIG. **27**A is a perspective view of the insert **42**. FIG. **27**B is a side elevation view of the insert **42**. FIG. **27**C is a top plan view of the insert **42**. Note that FIGS. **27**A-C are to scale.

[0222] The insert **42** comprises a tip **4** on one end opposite a lower portion **54** on the other end. The insert **42** comprises an arrowhead portion **48** and a stem portion **50**. The underside **52** of the arrowhead **48** can be flat, angled, or rounded.

The insert **42** includes nose depressions **8** (also called cutouts or troughs) and a nose remaining portion **22** between the nose depressions **8**, where each nose remaining portion **22** is positioned between two nose depressions **8**. The remaining portions **22** are the uncut portions having the insert's original ogive and radius of curvature R**1**. The nose depressions **8** have a curved shape meaning that the trough or bottom of the nose depression **8** is curved and has a radius of curvature R**4**. In one embodiment, the nose depressions are cut using a ⅜ inch flat end mill.

[0223] The longitudinal axis **44** of the insert **42** is shown in FIG. **27**B. Accordingly, the angle α of the nose depressions **8** can be measured from the centerline **10** of the nose depressions **8** relative to the longitudinal axis **44**. In some embodiments, all nose depressions **8** have the same angle α. In other embodiments, each nose depression **8** has a different angle α. In still other embodiments, some nose depressions **8** have the same angle a while other nose depressions **8** have different angles α. In one embodiment, the projectile **2** has at least three nose depressions **8**. However, the projectile **2** can have more or fewer nose depressions **8**. The nose depressions **8** intersect one another to form cutter edges **72** extending to the tip **4** of the insert **42**.

[0224] In one embodiment, the radius of curvature R**4** of the nose depressions **8** is between about 0.05 inches and about 0.75 inches. In a preferred embodiment, the radius of curvature R**4** of the nose depressions **8** is between about 0.10 inches and about 0.5 inches. In a more preferred embodiment, the radius of curvature R**4** of the nose depressions **8** is about 0.4 inches. In one embodiment, the length L**6** of the insert **42** is between about 0.513inches and about 0.713 inches. In a preferred embodiment, the length L**6** of the insert **42** is between about 0.413 inches and about 0.613 inches. In a more preferred embodiment, the length L**6** of the insert **422** is about 0.513 inches. However, the length L**6** varies with the embodiment and with the caliber of the projectile. The diameter D**4** of the stem **50** of the insert **42** varies according the various embodiments. In one embodiment, the diameter D**4** of the projectile **2** is between about 0.1 inches and about 0.4 inches. In a preferred embodiment, the diameter D**4** of the stem **50** of the insert **42** is between about 0.2 inches and about 0.28 inches. In the embodiment shown, the diameter D**4** of the stem **50** of the insert **42** is about 0.225 inches. In one embodiment, the diameter D**5** of the arrowhead **48** of the insert **42** is between about 0.1 inches and about 0.4 inches. In a preferred embodiment, the diameter D**5** of the arrowhead **48** is between about 0.2 inches and about 0.3 inches. In the embodiment shown, the diameter D**5** of the arrowhead **48** is about 0.25inches. In one embodiment, the angle α of the nose depressions **8** is between about 5degrees and about 25 degrees. In a preferred embodiment, the angle α of the nose depressions **8** is between about 8 degrees and about 12 degrees. In a more preferred embodiment, the angle α of the nose depressions **8** is about 10 degrees.

[0225] This insert **42** is different from the prior art because it can pierce armor and the projectile stops in soft tissue. The sharp tip **4** and sharp cutter edges **72** allow this insert **42** to cut through armor, including Kevlar.

[0226] FIGS. **28**A-C show a projectile insert **42** according to another embodiment of the invention. This is the civilian insert of FIG. **27**. FIG. **28**A is a perspective view of the insert **42**. FIG. **28**B is a side elevation view of the insert **42**. FIG. **28**C is a top plan view of the insert **42**. Note that FIGS. **28**A-C are to scale.

[0227] The insert **42** comprises a tip **4** on one end opposite a lower portion **54** on the other end. The insert **42** comprises an arrowhead portion **48** and a stem portion **50**. The underside **52** of the arrowhead **48** can be angled, flat, or curved. The insert **42** includes nose depressions **8** (also called cutouts or troughs) and nose remaining portions **22** between the nose depressions **8**, where each nose remaining portion **22** is positioned between two nose depressions **8**. The remaining portions **22** are the uncut portions having the insert's original ogive and radius of curvature R**1**. The nose depression **8** has a curved shape meaning that the trough or bottom of the nose depression **8** is curved and has a radius of curvature R**4**. In one embodiment, the nose depressions **8** are cut using a 3⁄32 inch flat end mill.

[0228] The longitudinal axis **44** of the insert **42** is shown in FIG. **28**B. Accordingly, the angle α of the nose depressions **8** can be measured from the centerline **10** of the nose depressions **8** relative to the longitudinal axis **44**. In some embodiments, all nose depressions **8** have the same angle α. In other embodiments, each nose depression **8** has a different angle α. In still other embodiments, some nose depressions **8** have the same angle a while other nose depressions **8** have different angles α. In one embodiment, the insert **42** has at least three nose depressions **8**. However, the insert **42** can have more or fewer nose depressions **8**. In this embodiment, the depressions **8** do not extend all the way to the tip **4** and do not intersect. Rather, the remaining portions **22** extend to the tip **4**.

[0229] In one embodiment, the radius of curvature R**4** of the nose depressions **8** is between about 0.01 and about 0.5 inches. In a preferred embodiment, the radius of curvature R**4** of the nose depressions **8** is between about 0.03 inches and about 0.375 inches. In a more preferred embodiment, the radius of curvature R**4** of the nose depressions **8** is about 0.25inches. In one embodiment, the length L**6** of the insert **42** is between about 0.426 inches and about 0.826 inches. In a preferred embodiment, the length L**6** of the insert **42** is between about 0.526 inches and about 0.726 inches. In a more preferred embodiment, the length L**6** of the insert **42** is about 0.626 inches. The diameter D**4** of the projectile **2** varies according the various embodiments. In one embodiment, the diameter D**4** of the stem **50** is between about 0.1 inches and about 0.4 inches. In a preferred embodiment, the diameter D**4** of the stem **50** is between about 0.2 inches and about 0.3 inches. In the embodiment shown, the diameter D**4** of the stem **50** is about 0.225 inches. In one embodiment, the diameter D**5** of the arrowhead **48** of the insert **42** is between about 0.1 inches and about 0.5inches. In a preferred embodiment, the diameter D**5** of the arrowhead **48** is between about 0.2 inches and about 0.4 inches. In the embodiment shown, the diameter D**5** of the arrowhead **48** is about 0.30 inches. In one embodiment, the angle α of the nose depressions **8** is between about 5 degrees and about 25 degrees. In a preferred embodiment, the angle a of the nose depressions **8** is between about 8 degrees and about 12 degrees. In a more preferred embodiment, the angle α of the nose depressions **8** is about 10 degrees. FIGS. **29**A-C show a projectile insert **42** according to an alternate embodiment of the invention. The insert **42** can be made of any projectile or bullet material, such as brass or steel. FIG. **29**A is a perspective view of the insert **42**. FIG. **29**B is a side elevation view of

the insert **42**. FIG. **29**C is a top plan view of the insert **42**. Note that FIGS. **29**A-C are to scale.

[0230] The insert **42** comprises a tip **4** on one end opposite a lower portion **54** on the other end. The insert **42** comprises an arrowhead portion **48** and a stem portion **50**. The insert **42** includes nose depressions **8** (also called cutouts or troughs) and nose remaining portion **22** between the nose depressions **8**, where each nose remaining portion **22** is positioned between two nose depressions **8**. The remaining portions **22** are the uncut portions having the insert's original ogive and radius of curvature R**1**. The nose depressions **8** have a curved shape meaning that the trough or bottom of the nose depression **8** is curved and has a radius of curvature R**4**. In one embodiment, the nose depressions **8** are cut using a 3/16 inch flat end mill.

[0231] The longitudinal axis **44** of the projectile **2** is shown in FIG. **29**B. The angle α of the nose depressions **8** can be measured from the centerline **10** of the nose depressions **8** relative to the longitudinal axis **44**. In some embodiments, all nose depressions **8** have the same angle α. In other embodiments, each nose depression **8** has a different angle α. In still other embodiments, some nose depressions **8** have the same angle α while other nose depressions **8** have different angles α. In one embodiment, the insert **42** has at least three nose depressions **8**. However, the insert **42** can have more or fewer nose depressions **8**. Also, like FIGS. **28**A-C, the depressions **8** do not intersect. Rather, the nose remaining portions **22** extend to the tip **4** of the insert **42**.

[0232] In one embodiment, the radius of curvature R**4** of the nose depressions **8** is between about 0.05 inches and about 0.5 inches. In a preferred embodiment, the radius of curvature R**4** of the nose depressions **8** is between about 0.08 inches and about 0.375 inches. In a more preferred embodiment, the radius of curvature R**4** of the nose depressions **8** is about 0.25 inches. In another more preferred embodiment, the radius of curvature of the depression **8** is about 0.09375 inches. In one embodiment, the length L**6** of the insert **42** is between about 0.436 inches and about 0.836 inches. In a preferred embodiment, the length L**6** of the insert **42** is between about 0.536 inches and about 0.736 inches. In a more preferred embodiment, the length L**6** of the insert **42** is about 0.636 inches. The diameter D**4** of the stem **50** of the insert varies according the various embodiments. In one embodiment, the diameter D**4** of the stem **50** is between about 0.025 inches and about 0.425inches. In a preferred embodiment, the diameter D**4** of the stem **50** is between about 0.125inches and about 0.325 inches. In the embodiment shown, the diameter D**4** of the stem **50** is about 0.225 inches. In one embodiment, the diameter D**5** of the arrowhead **48** of the insert **42** is between about 0.1 inches and about 0.5 inches. In a preferred embodiment, the diameter D**5** of the arrowhead **48** is between about 0.2 inches and about 0.4 inches. In the embodiment shown, the diameter D**5** of the arrowhead **48** is about 0.3 inches. In one embodiment, the angle α of the nose depressions **8** is between about 5 degrees and about 25 degrees. In a preferred embodiment, the angle α of the nose depressions **8** is between about 8 degrees and about 12 degrees. In a more preferred embodiment, the angle α of the nose depressions **8** is about 10 degrees.

[0233] FIGS. **30**A-C show the projectile **2** of FIGS. **25**A-C after being fired and after hitting the target. FIG. **30**A is a perspective view of the projectile **2**. FIG. **30**B is a side elevation view of the projectile **2**. FIG. **30**C is a top plan view of the projectile **2**. Rifling marks **60** from the gun barrel are shown on the projectile **2**.

[0234] FIGS. **31**A-C show a projectile **2** according to a twenty-sixth embodiment of the invention after being fired and after hitting the target. FIG. **31**A is a perspective view of the projectile **2**. FIG. **31**B is a side elevation view of the projectile **2**. FIG. **31**C is a top plan view of the projectile **2**. This insert **42** is the insert shown in FIGS. **28**A-C. The projectile **2** of FIGS. **30**A-C has perforations on the housing **40** whereas the projectile **2** of FIGS. **31**A-C does not have perforations. The perforations cause the housing **40** to flower upon impact as shown in FIG. **30**, whereas the housing **40** of FIGS. **31**A-C rolls backward in one piece upon impact.

[0235] FIGS. **32**A-D show a projectile according to a twenty-seventh embodiment of the invention. FIG. **32**A is a perspective view of the projectile **2**. FIG. **32**B is a side elevation view of the projectile **2**. FIG. **32**C is a top plan view of the projectile **2**. FIG. **32**D is a cross-sectional view of the projectile **2** taken along cut D-D of FIG. **32**C. Note that FIGS. **32**A-**32**D are to scale.

[0236] The projectile **2** comprises a tip **4** on one end opposite a base **30** on the other end. In one embodiment, the length L**1** of the projectile **2** is between about 1.125 inches and about 1.725 inches. In a preferred embodiment, the length L**1** of the projectile **2** is between about 1.225 inches and about 1.625 inches. In a more preferred embodiment, the length L**1** of the projectile **2** is about 1.425 inches. In one embodiment, the length L**2** of the nose portion **6** is between about 0.699 inches and about 1.099 inches. In a preferred embodiment, the length L**2** of the nose portion **6** is between about 0.799 inches and about 0.999 inches. In a more preferred embodiment, the length L**2** of the nose portion **6** is about 0.899 inches. In one embodiment, the length L**3** of the cylindrical portion **20** is between about 0.522 inches and about 0.122 inches. In a preferred embodiment, the length L**3** of the cylindrical portion **20** is between about 0.422 inches and about 0.222 inches. In a more preferred embodiment, the length L**3** of the cylindrical portion **20** is about 0.322 inches. The diameter D**1** of the projectile **2** (also called the caliber) varies according the various embodiments. In one embodiment, the diameter D**1** of the projectile **2** is between about 0.108 inches and about 0.508 inches. In a preferred embodiment, the diameter D**1** of the projectile **2** is between about 0.208 inches and about 0.408 inches. In the embodiment shown, the diameter D**1** of the projectile **2** is about 0.308 inches.

[0237] The projectile **2** also has a boat tail **38** with an angle θ proximate the base **30**. The cylindrical portion **30** has angled driving bands **26**A and angled relief cuts **28**A. The projectile **2** also has a flat or linear portion **32** between the first nose portion **66** and the second nose portion **68**.

[0238] Referring to FIGS. **33**-**36**, these projectiles are "smart bullets" because they penetrate armor and slow down in soft tissue. Like other embodiments with a housing **40** and an insert **42**, these projectiles **2** have cavities **24** to receive soft tissue to slow the projectile down in soft tissue. These projectiles **2** have a hardened steel tip insert **42**. Further, the different angle of the front or first ogive of the first nose portion **66** from the second ogive of the second nose portion **68** means that a minimal amount of surface area is in contact with the wind, making the projectile's BC higher. Thus, there are two ogive angles: a front or first ogive and rear or second ogive.

[0239] FIGS. **33**A-C show a projectile according to a twenty-eighth embodiment of the invention. FIG. **33**A is a perspective view of the projectile **2**. FIG. **33**B is a side elevation view of the projectile **2**. FIG. **33**C is a top plan view of the projectile **2**. Note that FIGS. **33**A-**33**C are to scale. FIGS. **34**A-D are exploded views of the projectile housing **40** and insert **42** of FIGS. **33**A-C. FIG. **34**A is a perspective view of the projectile **2**. FIG. **34**B is a side elevation view of the projectile **2**. FIG. **34**C is a top plan view of the projectile **2**. FIG. **34**D is a cross-sectional view. Note that FIGS. **34**A-**34**D are to scale.

[0240] The projectile **2** comprises a tip **4** on one end opposite a base **30** on the other end. The projectile includes an insert **42** that fits into a housing **40**. The projectile **2** comprises a nose portion **6** and a cylindrical portion **20** (also called a shank). The nose portion **6** includes a first nose portion **66** and a second nose portion **68**. A linear portion **32** is positioned between the first nose portion **66** and second nose portion **68**. In one embodiment, the projectile **2** has a hardened steel tip **4**. The cylindrical portion **20** includes angled driving bands **26**A with diameter D**3** and angled relief cuts **28**A with diameter D**2** and radius of curvature R**6**. See FIG. **35**E for detail on the angled driving bands **26**A and angled relief cuts **28**A. The projectile also has a boat tail **38** at an angle θ.

[0241] In one embodiment, the length L**1** of the projectile **2** is between about 1.125 inches and about 1.725 inches. In a preferred embodiment, the length L**1** of the projectile **2** is between about 1.225 inches and about 1.625 inches. In a more preferred embodiment, the length L**1** of the projectile **2** is about 1.425 inches. In one embodiment, the length L**2** of the nose portion **6** is between about 0.699 inches and about 1.099 inches. In a preferred embodiment, the length L**2** of the nose portion **6** is between about 0.799 inches and about 0.999 inches. In a more preferred embodiment, the length L**2** of the nose portion **6** is about 0.899 inches. In one embodiment, the length L**3** of the cylindrical portion **20** is between about 0.522 inches and about 0.122 inches. In a preferred embodiment, the length L**3** of the cylindrical portion **20** is between about 0.422 inches and about 0.222 inches. In a more preferred embodiment, the length L**3** of the cylindrical portion **20** is about 0.322 inches. The diameter D**1** of the projectile **2** (also called the caliber) varies according the various embodiments. In one embodiment, the diameter D**1** of the projectile **2** is between about 0.108 inches and about 0.508 inches. In a preferred embodiment, the diameter D**1** of the projectile **2** is between about 0.208 inches and about 0.408 inches. In the embodiment shown, the diameter D**1** of the projectile **2** is about 0.308 inches.

[0242] As shown in FIG. **34**D, the receiving portion **58** of the housing **40** has a step or shoulder **18**. Additionally, the front **56** of the housing **40** is substantially flat and parallel to the base **30**.

[0243] FIGS. **35**A-E show a projectile according to a twenty-ninth embodiment of the invention. FIG. **35**A is a perspective view of the projectile **2**. FIG. **35**B is a side elevation view of the projectile **2**. FIG. **35**C is a top plan view of the projectile **2**. FIG. **35**D is a cross-sectional view. FIG. **35**E is a close-up view. Note that FIGS. **35**A-E are to scale. The projectile of FIG. **35** is the same as the projectile of FIG. **24** except that the projectile of FIG. **35** has one insert **42** and the projectile of FIG. **24** has three inserts. This projectile **2** is also similar to the projectile **2** of FIGS. **33**A-**34**D, but the linear portion **32** is shorter in FIGS. **35**A-D. Additionally, the projectile **2** of FIGS. **35**A-E has depressions **8** on the insert **42**. The depressions **8** create a high-pressure area in the depressions **8** to move air around the depression **8** and not into the cavity **24** when traveling through air or in hard media.

[0244] The longitudinal axis **44** of the projectile **2** is shown in FIG. **35**B. The angle α of the nose depressions **8** can be measured from the centerline **10** of the nose depressions **8** relative to the longitudinal axis **44**. In some embodiments, the angle α is measured relative to the original ogive of the projectile nose portion **6**. In some embodiments, all nose depressions **8** have the same angle α. In other embodiments, each nose depression **8** has a different angle α. In still other embodiments, some nose depressions **8** have the same angle a while other nose depressions **8** have different angles α. In the embodiment shown, the nose depressions **8** are right-hand nose depressions **8** because the angle α is positioned to the right of the longitudinal axis **44**. Further, when looking at the projectile from a top plan view (FIG. **35**C), the nose depressions **8** appear to turn in a counter-clockwise direction. In one embodiment, the projectile **2** has at least four nose depressions **8**. However, the projectile **2** can have more or fewer nose depressions **8**. The depressions **8** create cavities **24** between the insert **42** and the housing **40** such that when the projectile **2** hits a soft medium target, the cavities **24** fill with the soft medium and the projectile **2** slows down. The steeper (i.e., greater) alpha angle will also transfer media at a greater rate into the housing for a faster opening and expansion of the housing **40** upon impact with the terminal media.

[0245] The nose portion **6** comprises a first nose portion **66** with a radius of curvature R**1** and a second nose portion **66** with a radius of curvature R**2**. The projectile **2** also has a boat tail **38** with an angle θ.

[0246] In one embodiment, the length L**1** of the projectile **2** is between about 1.0 inch and about 2.0 inches. In a preferred embodiment, the length L**1** of the projectile **2** is between about 1.3 inches and about 1.6 inches. In a more preferred embodiment, the length L**1** of the projectile **2** is about 1.405 inches. The diameter D**1** of the projectile **2** varies according the various embodiments. In one embodiment, the diameter D**1** of the projectile **2** is between about 0.20 inches and about 0.50 inches. In a preferred embodiment, the diameter D**1** of the projectile **2** is between about 0.25 inches and about 0.35 inches. In the embodiment shown, the diameter D**1** of the projectile **2** is about 0.308 inches. In one embodiment, the length of the first nose portion **66** extending from the tip **4** to the linear portion **32** is between about 0.10 inches and about 0.30 inches. In a preferred embodiment, the length of the first nose portion **66** extending from the tip **4** to the linear portion **32** is between about 0.14 inches and about 0.20 inches. In a more preferred embodiment, the length of the first nose portion **66** extending from the tip **4** to the linear portion **32** is about 0.17 inches. In one embodiment, the length L**5** of the housing **40** is between about 1.0 inch and about 1.3 inches. In a preferred embodiment, the length L**5** of the housing **40** is about 1.145 inches. In one embodiment, the length L**6** of the insert **42** is between about 1.0 inch and about 1.3 inches. In a preferred embodiment, the length L**6** of the insert **42** is about 1.175 inches. In one embodiment, the length of the linear portion **32** is between about 0.10and 0.15 inches. In one embodiment, the length of the second nose portion **68** extending from the front **56** of the housing **40** to the

cylindrical portion **20** is between about 0.55 and about 0.70 inches. In a preferred embodiment, the length of the second nose portion **68** extending from the front **56** of the housing **40** to the cylindrical portion **20** is about 0.62inches.

[0247] In one embodiment, the length L**4** of the boat tail **38** is between about 0.10 inches and about 0.40 inches. In a preferred embodiment, the length L**4** of the boat tail **38** is between about 0.15 inches and about 0.35 inches. In a more preferred embodiment, the length L**4** of the boat tail **38** is about 0.23 inches. In another more preferred embodiment, the length L**4** of the boat tail **38** is about 0.30 inches.

[0248] In one embodiment, the radius of curvature R**2** of the tangent ogive is between about 2.0 inches and about 5.0 inches. In a preferred embodiment, the radius of curvature R**2** of the tangent ogive is between about 3.0 inches and about 4.0 inches. In a more preferred embodiment, the radius of curvature R**2** of the tangent ogive is about 3.5 inches. In one embodiment, the radius of curvature R**3** of the secant ogive is between about 0.5inches and about 1.5 inches. In a preferred embodiment, the radius of curvature R**3** of the secant ogive is between about 0.75 inches and about 1.25 inches. In a more preferred embodiment, the radius of curvature R**3** of the secant ogive is about 1.00 inch. In one embodiment, the angle θ of the boat tail **38** is between about 5 degrees and about 10degrees. In a preferred embodiment, the angle θ of the boat tail **38** is between about 6.5degrees and about 8.0 degrees. In a more preferred embodiment, the angle θ of the boat tail **38** is about 7.5 degrees.

[0249] The cylindrical portion **20** comprises angled drive bands **26**A and angled relief cuts **28**A. In one embodiment, the angled drive bands **26**A and angled relief cuts **28**A are positioned at an angle σ relative to a horizontal line or the longitudinal axis **44** between about 5 degrees and about 10 degrees. In a preferred embodiment, the angled drive bands **26**A and angled relief cuts **28**A are positioned at an angle σ relative to a horizontal line or the longitudinal axis **44** between about 6 degrees and about 9 degrees. In a more preferred embodiment, the angled drive bands **26**A and angled relief cuts **28**A are positioned at an angle o relative to a horizontal line or the longitudinal axis **44** about 7.5 degrees. In another preferred embodiment, the angled drive bands **26**A and angled relief cuts **28**A are positioned at an angle σ relative to a horizontal line or the longitudinal axis **44** about 8.5degrees. In alternate embodiments, the driving bands **26**A vary in number, comprising one driving band **26**A, a plurality of driving bands **26**A, two driving bands **26**A, three driving bands **26**A, and four or more driving bands **26**A. The angled drive bands **26**A and angled relief cuts **28**A create air disturbances that stabilize the projectile **2** in flight allowing the projectile **2** to fly straighter and be less affected by cross winds than projectiles of the prior art.

[0250] FIGS. **36**A-D show a projectile according to a thirtieth embodiment of the invention. FIG. **36**A is a perspective view of the projectile **2**. FIG. **36**B is a side elevation view of the projectile **2**. FIG. **36**C is a top plan view of the projectile **2**. FIG. **36**D is a cross-sectional view of the projectile **2**. Note that FIGS. **36**A-D are to scale.

[0251] The projectile **2** comprises a tip **4** on one end opposite a base **30** on the other end. The projectile **2** comprises a nose portion **6** interconnected to a cylindrical portion **20** interconnected to a boat tail **38**. The nose portion **6** includes a first nose portion **66**, a second nose portion **68**, and a linear portion **32** positioned between the first nose portion **66** and the second nose portion **68**. The cylindrical portion **20** includes angled driving bands **26**A and angled relief cuts **28**A. In one embodiment, the length L**1** of the projectile **2** is between about 1.0 inch and about 2.0 inches. In a preferred embodiment, the length L**1** of the projectile **2** is between about 1.3 inches and about 1.6 inches. In a more preferred embodiment, the length L**1** of the projectile **2** is about 1.405 inches. The diameter D**1** of the projectile **2** varies according the various embodiments. In one embodiment, the diameter D**1** of the projectile **2** is between about 0.20 inches and about 0.50 inches. In a preferred embodiment, the diameter D**1** of the projectile **2** is between about 0.25 inches and about 0.35 inches. In the embodiment shown, the diameter D**1** of the projectile **2** is about 0.308 inches. In one embodiment, the length of the first nose portion **66** is between 0.10 inches and about 0.30 inches, or preferably 0.23 inches. In one embodiment, the length of the housing is between about 1.0 inch and about 1.3 inches. In a preferred embodiment, the length of the housing is about 1.145 inches. In one embodiment, the length of the linear portion **32** is between about 0.04 and 0.06 inches. In one embodiment, the length of the second nose portion **68** is between about 0.55 and about 0.70 inches.

[0252] The projectiles of FIGS. **37**A-**38**E are designed for high-speed silent flight.

[0253] FIGS. **37**A-D show a projectile according to a thirty-first embodiment of the invention. FIG. **37**A is a perspective view of the projectile **2**. FIG. **37**B is a side elevation view of the projectile **2**. FIG. **37**C is a top plan view of the projectile **2**. FIG. **37**D is a bottom plan view of the projectile **2**. Note that FIGS. **37**A-D are to scale. The projectile **2** comprises a tip **4** on one end opposite a base **30** on the other end. The projectile **2** comprises a nose portion **6** interconnected to a cylindrical portion **20** (also called a shank) interconnected to a boat tail **38** with an angle θ. The nose portion **6** includes nose depressions **8** (also called cutouts or troughs) and nose remaining portions **22** between the nose depressions **8**, where each nose remaining portion **22** is positioned between two nose depressions **8**. The remaining portions **22** are the uncut portions having the projectile's original ogive. The nose depressions **8** have a curved shape meaning that the trough or bottom of the nose depression **8** is curved and has a radius of curvature R**4**.

[0254] The longitudinal axis **44** of the projectile **2** is shown in FIG. **37**B. The angle α of the nose depressions **8** can be measured from the centerline **10** of the nose depressions **8** relative to the longitudinal axis **44**. In some embodiments, the angle α is measured relative to the original ogive of the projectile nose portion **6**. In some embodiments, all nose depressions **8** have the same angle α. In other embodiments, each nose depression **8** has a different angle α. In still other embodiments, some nose depressions **8** have the same angle a while other nose depressions **8** have different angles α. In the embodiment shown, the nose depressions **8** are right-hand nose depressions **8** because the angle α is positioned to the right of the longitudinal axis **44**. Further, when looking at the projectile **2** from a top plan view (FIG. **37**C), the nose depressions **8** appear to turn in a counter-clockwise direction. In one embodiment, the projectile **2** has at least six nose depressions **8**. However, the projectile **2** can have more or fewer nose depressions **8**.

[0255] In one embodiment, the length L**1** of the projectile **2** is between about 1.0 inch and about 3.0 inches. In a preferred embodiment, the length L**1** of the projectile **2** is between about 1.5 inches and about 2.5 inches. In a more

preferred embodiment, the length L1 of the projectile **2** is about 1.96 inches. In one embodiment, the length L2 of the nose portion **6** is between about 1.00 inch and about 0.600 inches. In a preferred embodiment, the length L2 of the nose portion **6** is between about 0.900 inches and about 0.700 inches. In a more preferred embodiment, the length L2 of the nose portion **6** is about 0.800 inches. In one embodiment, the length L3 of the cylindrical portion **20** is between about 0.550 inches and about 0.150 inches. In a preferred embodiment, the length L3 of the cylindrical portion **20** is between about 0.450 inches and about 0.250 inches. In a more preferred embodiment, the length L3 of the cylindrical portion **20** is about 0.350 inches. In a more preferred embodiment, the length L4 is about 1.2 inches. The diameter D1 of the projectile **2** varies according the various embodiments. In one embodiment, the diameter D1 of the projectile **2** is between about 0.20 inches and about 0.50 inches. In a preferred embodiment, the diameter D1 of the projectile **2** is between about 0.25 inches and about 0.35 inches. In the embodiment shown, the diameter D1 of the projectile **2** is about 0.308 inches.

[0256] FIGS. **38**A-E show a projectile according to a thirty-second embodiment of the invention. FIG. **38**A is a perspective view of the projectile **2**. FIG. **38**B is a side elevation view of the projectile **2**. FIG. **38**C is a top plan view of the projectile **2**. FIG. **38**D is a bottom plan view. FIG. **38**E is a cross-sectional view. Note that FIGS. **38**A-E are to scale.

[0257] The projectile **2** comprises a housing **40** and an insert **42**. The projectile **2** comprises a tip **4** on one end opposite a base **30** on the other end. The projectile **2** comprises a nose portion **6** interconnected to a cylindrical portion **20** interconnected to a boat tail **38**. The nose portion **6** includes nose depressions **8** and nose remaining portions **22** between the nose depressions **8**, where each nose remaining portion **22** is positioned between two nose depressions **8**. The remaining portions **22** are the uncut portions having the projectile's original ogive.

[0258] The nose depressions **8** are right-hand depressions **8** because when looking at the projectile from a top plan view (FIG. **38**C), the nose depressions **8** appear to turn in a clockwise direction. In one embodiment, the projectile **2** has at least six nose depressions **8**. However, the projectile **2** can have more or fewer nose depressions **8**.

[0259] In one embodiment, the length L1 of the projectile **2** is between about 1.0 inch and about 2.0 inches. In a preferred embodiment, the length L1 of the projectile **2** is between about 1.5 inches and about 2.5 inches. In a more preferred embodiment, the length L1 of the projectile **2** is about 1.88 inches. In one embodiment, the length L5 of the housing **40** is about 1.2 inches. The diameter D1 of the projectile **2** varies according the various embodiments. In one embodiment, the diameter D1 of the projectile **2** is between about 0.20 inches and about 0.50 inches. In a preferred embodiment, the diameter D1 of the projectile **2** is between about 0.25 inches and about 0.35 inches. In the embodiment shown, the diameter D1 of the projectile **2** is about 0.308 inches.

[0260] FIGS. **39**A-C show a projectile according to a thirty-third embodiment of the invention. FIG. **39**A is a perspective view of the projectile **2**. FIG. **39**B is a side elevation view of the projectile **2**. FIG. **39**C is a top plan view of the projectile **2**. Note that FIGS. **39**A-C are to scale.

[0261] The projectile **2** comprises a tip **4** on one end opposite a base **30** on the other end. The projectile **2** comprises a nose portion **6** interconnected to a cylindrical portion **20** interconnected to a boat tail **38**. The nose portion **6** includes nose depressions **8** (also called cutouts or troughs) and nose remaining portions **22** between the nose depressions **8**, where each nose remaining portion **22** is positioned between two nose depressions **8**. The remaining portions **22** are the uncut portions having the projectile's original ogive. The nose depressions **8** have a curved shape meaning that the trough or bottom of the nose depression **8** is curved and has a radius of curvature R4. In one embodiment, the projectile **2** further comprises a tungsten or Inconel insert.

[0262] The longitudinal axis **44** of the projectile **2** is shown in FIG. **39**B. In one embodiment, the projectile **2** has at least six nose depressions **8**. However, the projectile **2** can have more or fewer nose depressions **8**.

[0263] The diameter D1 of the projectile **2** (also called the caliber) varies according the various embodiments. In one embodiment, the diameter D1 of the projectile **2** is between about 0.508 inches and about 0.108 inches. In a preferred embodiment, the diameter D1 of the projectile **2** is between about 0.408 inches and about 0.208 inches. In the embodiment shown, the diameter D1 of the projectile **2** is about 0.308 inches.

[0264] The intended users of the projectile **2** are African big game hunters. The attributes of this projectile **2** are deep straight penetration with transfer of energy. The projectile **2** is comprised of brass, copper, bronze, tungsten-carbide, alloys of these metals, or any material known in the art, including plastics and ceramics. In some embodiments, this projectile **2** will be two pieces and will have a tungsten or Inconel insert. This projectile **2** is armor penetrating. This projectile **2** is designed to go and never quit. Further, the tip **4** is designed to relieve material as it penetrates its target.

[0265] FIGS. **40**A-C show a projectile according to a thirty-fourth embodiment of the invention. FIG. **40**A is a perspective view of the projectile **2**. FIG. **40**B is a side elevation view of the projectile **2**. FIG. **40**C is a top plan view of the projectile **2**. Note that FIGS. **40**A-C are to scale. Some embodiments may also have angled driving bands and angled relief bands.

[0266] The projectile **2** comprises a tip **4** on one end opposite a base **30** on the other end. The projectile **2** comprises a nose portion **6** interconnected to a cylindrical portion **20** interconnected to a boat tail **38**. The nose portion **6** includes nose depressions **8** (also called cutouts or troughs) and nose remaining portions **22** between the nose depressions **8**, where each nose remaining portion **22** is positioned between two nose depressions **8**. The remaining portions **22** are the uncut portions having the projectile's original ogive.

[0267] The longitudinal axis **44** of the projectile **2** is shown in FIG. **40**B. In one embodiment, the projectile **2** has at least six nose depressions **8**. However, the projectile **2** can have more or fewer nose depressions **8**.

[0268] The diameter D1 of the projectile **2** (also called the caliber) varies according the various embodiments. In one embodiment, the diameter D1 of the projectile **2** is between about 0.138 inches and about 0.538 inches. In a preferred embodiment, the diameter D1 of the projectile **2** is between

about 0.238 inches and about 0.438 inches. In the embodiment shown, the diameter D**1** of the projectile **2** is about 0.338 inches.

[0269] The intended users of the projectile are African big game hunters. The attributes of this projectile are deep straight penetration with transfer of energy. The projectile is comprised of brass, copper, bronze, tungsten-carbide, alloys of these metals, or any material known in the art, including plastics and ceramics.

[0270] The projectiles described herein can be comprised of brass, copper, bronze, tungsten-carbide, alloys of these metals, or any material known in the art, including plastics and ceramics.

[0271] In some embodiments, the angle of the depressions, troughs, or cutout portions can be oriented or measured with respect to the longitudinal axis of the projectile or the ogive of the remaining portion. In various embodiments, the angle of the depression's centerline or the lowest point of the trough relative to the projectile's ogive is constant. Thus, the angle of the depression's centerline or the lowest point of the trough relative to the projectile's centerline may not be a constant angle; rather the angle may actually be a multitude of angles because the line of the trough follows the ogive and, therefore, is parabolic relative to the projectile's centerline.

[0272] The cylindrical portion can comprise sections that are equal to the diameter of the rifle barrel's grooves (driving bands) and alternate with a diameter equal to the diameter of lands in the rifle's bore (relief cuts). The angle of transition between these driving bands and relief cuts is 7.5-8.5 degrees in one embodiment.

[0273] FIG. **41** shows Table 1, which is a design chart for alpha angles for given barrel rates of twist and calibers. For example, for a 0.308 caliber bullet fired from a barrel having a barrel rate of twist of 10 (i.e., 1 bullet rotation every 10 inches of barrel travel), the alpha angle is 5.526794 degrees. The alpha angle designs provided are representative of embodiments that have a perfect correlation to the rate of twist.

Experimental Results

[0274] The rifled projectiles have exhibited excessive velocity with no apparent gain in pressure. This is an unexpected result, as under normal circumstances this should be impossible. This unexpected result may be due to less friction within the barrel. The twisting depressions are twisting the bullet in the barrel and reducing friction when the projectile engages with the rifling. This occurs when pressures exceed roughly 50,000 PSI. As the barrel warms slightly and pressures increase, the velocity increases exponentially. The greatest increase recorded was 1400 ft/s over the standard rifle projectile. This is substantial because it represents a 40% increase over normal velocity.

[0275] Also, the barrel heats at a slower rate and heats differently than with traditional bullets, lending further evidence of reduced friction in the barrel. Under normal circumstances, the greatest heat in a barrel is experienced an inch or two after the chamber. In contrast, with respect to the projectiles disclosed herein, the barrel gets hottest near the muzzle. The high pressures are helping to twist the projectile through the rifling and thus lowering friction. When the pressures drop near the muzzle, the heat and the friction return to the barrel.

[0276] There are many benefits of these results. With lower friction and less heating, barrels will last substantially longer. A lower rate of heating would have an impact on the manufacturing of machine guns, e.g., they could have lighter barrels that would last longer. Cyclic rates could be raised; longer bursts and sustained fire would be possible. Greater velocities mean flatter trajectories with the same case and similar weight projectiles. For a given projectile weight and caliber, a much smaller case could be employed. This means smaller lighter actions and more ammunition could be supplied for a given weight weapon system.

[0277] The functional aspects of the projectile may eliminate the sound of the bullet in flight, i.e., the whistle associated with a projectile in flight. The supersonic crack of the bullet passing is still audible but lessened. In one series of tests, a bullet flew at supersonic velocity without a supersonic crack until destabilizing, after which a yaw resulted and whistling began. Thus, a lower sound signature is provided.

[0278] These projectiles fly flatter than traditional ones, i.e., they have a higher ballistic coefficient. The fact they do not make a whistle means there is less friction as they slide through the atmosphere.

[0279] The penetration exhibited by these projectiles is greater than standard projectiles, and penetrate straighter than normal. Also, the projectiles of the invention have righted themselves after glancing off an object. The shape lends itself to reestablishing the spin after the projectile has struck an object. When a normal projectile begins to yaw, penetration decreases rapidly. With the subject projectiles, the spin ensures that yaw does not result.

[0280] The shape of the front of the projectile provides the capability to produce secondaries and enlarging wound channels. This will increase the size cavity of a wound inflicted by this projectile. The rapid sideways movement of media upon impact with this projectile may also explain the extra penetration that has been shown.

[0281] In one embodiment of a method of manufacture, a projectile is manufactured comprising steps as follows: the basic projectile shape, i.e. the nose and profile, is cut using a lathe; depressions are cut using a combination CNC Swiss screw machine (broadly, a combination CNC and lathe machine), Swiss screw machine and/or CNC turning machine. The projectile is rotated as the mill machine is cutting the material (one turns the front half or the back half of the projectile as appropriate, that is, depending on which portion of projectile is being worked). The forward-most portion of the projectile is contacted while the projectile is rotating. A mill is used to cut depressions in a straight line while the projectile turns. Then, cut any required driving bands; cut a radius on the back of the projectile as required; cut off back of projectile at base as required; and cut tail depression(s) as required (alternately, one can start tail portion of projectile and end with the nose portion of the projectile).

[0282] While various embodiments of the present invention have been described in detail, it is apparent that modifications and alterations of those embodiments will occur to those skilled in the art. However, it is to be expressly understood that such modifications and alterations are within the scope and spirit of the present invention, as set forth in the following claims. Further, the invention(s) described herein is capable of other embodiments and of being practiced or of being carried out in various ways. It is to be

understood that the phraseology and terminology used herein is for the purpose of description and should not be regarded as limiting.

1. A projectile for use in a handheld weapon, comprising:
- a front end having a tip;
- a rear end having a base and positioned opposite the front end;
- a longitudinal axis extending from the tip to the base;
- a boat tail portion extending from the rear end to a first point between the front end and the rear end, wherein the boat tail portion tapers inwardly toward the longitudinal axis such that the rear end has an end diameter that is smaller than a first diameter at the first point;
- a cylindrical portion integrally interconnected on a first end to the boat tail portion at the first point, the cylindrical portion extending from the first point to a second point between the front end and the first point, wherein the cylindrical portion comprises:
  - a plurality of angled driving bands; and
  - a plurality of angled relief cuts,
  - wherein each angled driving band in the plurality of angled driving bands is positioned between two angled relief cuts in the plurality of angled relief cuts, wherein each angled driving band in the plurality of angled driving bands has a rounded peak and a driving band diameter measured at a top of the rounded peak, wherein each angled relief cut in the plurality of angled relief cuts has a rounded valley having a radius of curvature and a relief cut diameter measured at a bottom of the rounded valley, and wherein each driving band diameter is larger than each relief cut diameter; and
- a nose portion tapering outward from the tip to the second point, wherein the nose portion is integrally interconnected to the cylindrical portion at the second point.

2. The projectile of claim **1**, wherein an angle between each angled driving band in the plurality of angled driving bands and each angled relief cut in the plurality of angled relief cuts is between about 7 degrees and about 10 degrees relative to the longitudinal axis.

3. The projectile of claim **1**, wherein the plurality of angled relief cuts comprises at least three angled relief cuts and the plurality of angled driving bands comprises at least two angled driving bands.

4. The projectile of claim **1**, wherein a projectile diameter is measured at the cylindrical portion and each driving band diameter is approximately the same as the projectile diameter, and wherein each relief cut diameter is approximately 0.01 inch smaller than each driving band diameter.

5. The projectile of claim **1**, further comprising a plurality of arcuate-shaped cutout portions extending from the tip to a third point between the tip and the second point.

6. The projectile of claim **1**, further comprising a plurality of arcuate-shaped cutout portions extending from a fourth point between the tip and the second point to a third point between the fourth point and the second point.

7. The projectile of claim **6**, wherein each arcuate-shaped cutout portion in the plurality of arcuate-shaped cutout portions is positioned at an angle of between 5 degrees and 45 degrees with respect to the longitudinal axis, such that the arcuate-shaped cutout portions twist about the longitudinal axis of the projectile.

8. The projectile of claim **6**, further comprising a plurality of non-distorted nose portions, each of the non-distorted nose portions being positioned between two of the plurality of arcuate-shaped cutout portions, wherein each of the plurality of non-distorted nose portions extends to the tip.

9. The projectile of claim **1**, further comprising a plurality of tail depressions cut into the boat tail portion of the projectile.

10. The projectile of claim **9**, wherein each tail depression in the plurality of tail depressions is positioned at an angle between about 3.5 degrees and 19.0 degrees with respect to the longitudinal axis, such that the plurality of tail depressions twist about the longitudinal axis.

11. The projectile of claim **1**, wherein the cylindrical portion has a first length, and wherein the nose portion has a second length that is greater than the first length.

12. A bullet adapted for insertion into a casing filled with an explosive propellant, comprising:
- a front end having a rounded tip;
- a rear end having a base and positioned opposite the front end;
- a longitudinal axis extending from the rounded tip to the base;
- a boat tail portion extending from the base to a first point between the front end and the rear end, wherein the boat tail portion tapers inwardly from the first point to the rear end at a boat tail angle measured relative to the longitudinal axis;
- a cylindrical portion integrally interconnected on a first end to the boat tail portion at the first point, the cylindrical portion extending from the first point to a second point between the front end and the first point,
- wherein a projectile diameter is measured at the cylindrical portion,
- wherein the cylindrical portion comprises:
  - a plurality of angled driving bands; and
  - a plurality of angled relief cuts,
- wherein each angled driving band in the plurality of angled driving bands is positioned between two angled relief cuts in the plurality of angled relief cuts,
- wherein each angled driving band in the plurality of angled driving bands has a rounded peak and a driving band diameter measured at a top of the rounded peak,
- wherein each driving band diameter is approximately the same as the projectile diameter,
- wherein each angled relief cut in the plurality of angled relief cuts has a rounded valley having a radius of curvature and a relief cut diameter measured at a bottom of the rounded valley,
- wherein each relief cut diameter is approximately 0.01 inch smaller than each driving band diameter, and
- wherein an angle between each angled driving band in the plurality of angled driving bands and each angled relief cut in the plurality of angled relief cuts is between about 7 degrees and about 10 degrees relative to the longitudinal axis; and
- a nose portion tapering from the rounded tip to the cylindrical portion at the second point, wherein the nose portion is integrally interconnected to the cylindrical portion at the second point.

13. The bullet of claim **12**, further comprising a plurality of arcuate-shaped cutout portions extending from a third point between the rounded tip and the second point to a fourth point between the third point and the second point.

14. The bullet of claim **13**, wherein each arcuate-shaped cutout portion in the plurality of arcuate-shaped cutout portions forms a curved trough with a distinct radius of curvature.

15. The bullet of claim **14**, wherein a lowermost portion of each of the troughs is positioned at a predetermined angle with respect to the longitudinal axis.

16. The bullet of claim **12**, further comprising a cavity and an insert, wherein the insert is positioned in the cavity, wherein the insert includes an apex at a first end opposite a base at a second end and a plurality of arcuate-shaped cutout portions extending from the apex of the insert to a point between the apex and the base.

17. The bullet of claim **12**, wherein the rounded tip of has a flattened leading edge oriented substantially perpendicular to the longitudinal axis.

18. A projectile for use in a handheld weapon, comprising:

a tip on a first end;

a base on a second end opposite the tip;

a longitudinal axis extending from the tip to the base;

a nose portion extending from the tip and having a nose length between about 0.75inches and about 1.0 inches;

a cylindrical portion connected to an end of the nose portion, wherein the cylindrical portion comprises a plurality of angled relief cuts and a plurality of angled driving bands, wherein each angled relief cut in the plurality of angled relief cuts is positioned between two angled driving bands in the plurality of angled driving bands, wherein an angle between each angled driving band and each relief cut is between about 7.0 degrees and 10.0 degrees relative to the longitudinal axis, and wherein an upper portion of each angled driving band has a curved convex shape when viewed in cross-section and a lower portion of each angled relief cut has a curved concave shape when viewed in cross-section, and wherein a height measured between the lower portion of each angled relief cut and the upper portion of each angled driving band is about 0.009 inch;

a tapered boat tail connected to an end of the cylindrical portion and terminating at the base, wherein the tapered boat tail tapers inwardly from the cylindrical portion to the base at an angle between about 6.5 degrees and about 8.0 degrees.

19. The projectile of claim **18**, further comprising a plurality of tail depressions originating at the base and extending along sides of the tapered boat tail, wherein the plurality of tail depression are cut into a surface of the tapered boat tail, wherein each tail depression in the plurality of tail depressions forms a curved trough with a radius of curvature, and wherein a centerline of each tail depression is positioned on a straight line at an angle between about 5 degrees and about 10 degrees relative to the longitudinal axis.

20. The projectile of claim **18**, wherein the nose portion has a tangent ogive having a radius of curvature between about 3.0 inches and about 4.0 inches, and wherein

a length from the tip to the base is between about 1.25 inches and about 1.75 inches.

* * * * *