




(86) Date de dépôt PCT/PCT Filing Date: 2013/10/17
(87) Date publication PCT/PCT Publication Date: 2014/12/24
(45) Date de délivrance/Issue Date: 2017/01/17
(85) Entrée phase nationale/National Entry: 2014/11/27
(86) N° demande PCT/PCT Application No.: JP 2013/078116
(87) N° publication PCT/PCT Publication No.: 2014/203415
(30) Priorité/Priority: 2013/06/18 (JP2013-127574)

(51) Cl.Int./Int.Cl. *A43C 11/16* (2006.01),
A43B 11/00 (2006.01), *A43B 23/02* (2006.01),
A43C 7/00 (2006.01)
(72) Inventeur/Inventor:
MIDORIKAWA, SHINOBU, JP
(73) Propriétaire/Owner:
JAPANA CO., LTD., JP
(74) Agent: OYEN WIGGS GREEN & MUTALA LLP

(54) Titre : DISPOSITIF D'ENROULEMENT DE LACETS
(54) Title: SHOELACE WINDING DEVICE



(57) Abrégé/Abstract:

A small-sized and light weighted shoelace winding device having superior durability, operability, and maintenance, and that can conveniently be used in various types of shoes is provided. The present invention provides a shoelace winding device 1 provided with: a base member 3 including a reel storing section 32 for storing a shoelace winding reel 4; a shaft member 7 for attaching a dial 6 for rotatively driving the reel 4 to the base member 3, and retaining and guiding the dial 6 in a state of being movable between a lock position and a release position; and a spring member 8 having its one end portion axially supported by a bearing section of the shaft member 7, and having its other end portion making constant contact with an engaging portion 62 provided on an inner surface of the dial 6, wherein it is configured to switch from a lock state of the reel 4 to a release state, an inversion position where the spring member 8 is compressed the most is set at a position between the lock position and the release position, and a direction along which the spring member 8 is compressed is switched between the lock position and the release position.

ABSTRACT

A small-sized and light weighted shoelace winding device having superior durability, operability, and maintenance, and that can conveniently be used in various types of shoes is provided.

The present invention provides a shoelace winding device 1 provided with: a base member 3 including a reel storing section 32 for storing a shoelace winding reel 4; a shaft member 7 for attaching a dial 6 for rotatively driving the reel 4 to the base member 3, and retaining and guiding the dial 6 in a state of being movable between a lock position and a release position; and a spring member 8 having its one end portion axially supported by a bearing section of the shaft member 7, and having its other end portion making constant contact with an engaging portion 62 provided on an inner surface of the dial 6, wherein it is configured to switch from a lock state of the reel 4 to a release state, an inversion position where the spring member 8 is compressed the most is set at a position between the lock position and the release position, and a direction along which the spring member 8 is compressed is switched between the lock position and the release position.

SHOELACE WINDING DEVICE

Technical Field

[0001]

The present invention relates to a shoelace winding device that is suitable not only for boots for skiing, snowboarding, skating, mountain climbing, and biking, but also for sports shoes used in golf and jogging, and moreover suitable for tightening shoelaces of general shoes such as business shoes.

Background Art

[0002]

Conventionally, to tighten a boot shoelace used in skiing, snowboarding, skating and the like, a shoelace winding device that can tighten the shoelace by rotating a dial (disk-shaped tab) and release the tightening of the shoelace in a one-touch manner has been proposed (Patent Document 1).

[0003]

In such a shoelace winding device, an operation to switch between a lock state in which the shoelace can be tightened by the dial and a release state in which the tightening of the shoelace can be released is enabled by slidably moving a resin-made

projection (indent washer) to engage with one of a "coupled recess" and a "uncoupled recess".

[0004]

However, in such a shoelace winding device, the operation of riding over a "peak" between the "coupled recess" and the "uncoupled recess" is repeated by the slide movement of the projection, and there is a problem that the projection and the "peak" are worn to the extent that the switch between the lock state and the release state cannot be performed normally.

[0005]

Furthermore, even in an embodiment in which a spring formed of steel wire is used instead of the projection, and the spring is moved between the "coupled recess" and the "uncoupled recess", the "peak" between the "coupled recess" and the "uncoupled recess" is worn, and there is a problem of insufficient durability and reliability.

[0006]

Moreover, in such a shoelace winding device, size and weight reduction as well as simplification of an assembling work and a disassembling work upon repair are being required, and resolution of these problems is necessary in order to employ the shoelace winding device to an even greater variety of shoes.

Citation List

Patent Literatures

[0007]

Patent Document 1: JP 2010-148927 A

SUMMARY OF INVENTION

Technical Problem

[0008]

Therefore, the present invention aims to solve the problem that, in the conventional shoelace winding device, damage is easily caused by the wear generated by repeating the operation to switch between the lock state in which the shoelace can be tightened and the release state in which the tightening of the shoelace can be released, and there is the need to use a large number of metal components and make resin components large in order to improve strength and durability. The purpose of the present invention is to provide a shoelace winding device that can improve the size and weight reduction as well as the durability and reliability, facilitate the assembling work and the disassembling work upon repair, has superior operability, and can be used in the even greater variety of shoes.

Solution to Problem

[0009]

The primary feature of the present invention is a shoelace winding device comprising: a reel for winding a shoelace; a base member including a reel storing section for storing the reel; a dial for rotatively driving the reel, including a stopper member for realizing a lock state in which rotation of the dial can be transmitted to the reel and a release state in which the reel is disconnected from the dial so that the reel can rotate freely; a shaft member to be fixed to the base member to attach the dial to the base member, the shaft member being configured to retain and guide the dial in a state of being movable between a lock position where the dial is caused to approach the base member and a release position where the dial is separated away from the base member; and a spring member having its one end portion axially supported along a direction orthogonally intersecting an axial direction of the shaft member by a bearing section formed at a side portion of the shaft member, and having its other end portion making constant contact with an engaging portion provided on an inner surface of the dial. The shoelace winding device is configured to switch from a lock state of the reel to a release state by the dial moving from the lock position to the release position, an inversion position where the spring member is

compressed the most is set at a position between the lock position and the release position, and a direction along which the spring member is compressed is switched between the lock position and the release position.

[0010]

The stopper member may be fitted inside the dial and integrated with the dial, and the engaging portion where the other end portion of the spring member makes contact may be provided at an outer end narrowest portion of a spring storing space formed in a cuneate shape at a boundary portion between the dial and the stopper member.

[0011]

The spring member may be assembled to the dial by the other end portion of the spring member being inserted into the spring storing space from an expanded portion where an axial hole of the dial is expanded, and further the other end portion being guided to be moved around from an inner end side of the spring storing space toward an outer end narrowest portion side when the spring member is inserted into axial holes formed on the dial and the stopper member.

[0012]

Further, the spring member may be a spring member that is formed by being curved in a substantially U-shape, a linear-shaped

shaft portion of the spring member on one end side may be axially supported along the direction orthogonally intersecting the axial direction of the shaft member by the bearing section formed at the side portion of the shaft member, and a curved spring portion on the other end side may make contact with the engaging portion.

[0013]

Moreover, one spring member may be located at each of positions separated about 180 degrees apart on the shaft member.

Advantageous Effects of Invention

[0014]

In the shoelace winding device of the present invention configured as above, the other end portion of the spring member having its one end portion axially supported by the bearing section of the shaft member fixed to the base member for mounting the dial, which rotatively drives the reel for winding the shoelace, to the base member, is in the state of making constant contact with the engaging portion provided on the inner surface of the dial upon the switching of the lock state and the release state of the dial.

Thus, since the positions where the components such as the dial is making contact with the spring member are not displaced while the dial moves from the lock position to the release position, the components such as the dial and the spring member can be

prevented from being rubbed against each other thereby to wear out.

[0015]

Moreover, since the inversion position where the spring member is compressed the most is set at the position between the lock position and the release position of the dial, a force to compress the spring member needs to be applied to move the dial from the lock position to the release position, so the dial can be prevented from inadvertently moving from the lock position to the release position.

Moreover, since the direction along which the spring member is compressed is switched between the lock position and the release position of the dial, a superior operability is obtained, and at the same time a state of the dial can clearly be understood.

[0016]

A component having a complicated shape can easily be provided by configuring the stopper member to be fitted inside the dial and be integrated therewith. Further, by providing the engaging portion where the other end portion of the spring member makes contact at the outer end narrowest portion of the spring storing space formed in the cuneate shape at the boundary portion between the dial and the stopper member, accommodating performance of the spring member is excellent, reliability and durability of

the device can be improved, and an operation range of the spring member can correctly be regulated.

[0017]

The spring member is assembled to the dial in such a manner that the other end portion of the spring member is inserted into the spring storing space from an expanded portion where an axial hole of the dial is expanded, and further the other end portion is guided to be moved around from an inner end side of the spring storing space toward an outer end narrowest portion side when the spring member is inserted into axial holes formed on the dial and the stopper member. With this configuration, the assembly of the spring member can easily be performed simply by pressing in the spring member to the dial.

[0018]

Further, the spring member is curvedly formed in a substantially U-shape. Its linear-shaped shaft portion on one end side is axially supported along the direction orthogonally intersecting the axial direction of the shaft member by the bearing section formed at the side portion of the shaft member. A curved spring portion on the other end side makes contact with the engaging portion. With this configuration, the spring member is enabled to rotatively move about the shaft portion.

[0019]

Further, since the spring portion is curved, the spring portion and the engaging portion smoothly make contact upon when the spring member deforms by being compressed, whereby the deformation of the spring member can be performed smoothly.

That is, the compressing operation of the spring member can be performed smoothly, and the operability thereof can be made superior in changing the dial position.

[0020]

Moreover, by positioning one spring member at each of the positions on the shaft member that are separated about 180 degrees apart, symmetry of the shaft member and the dial and the like can be obtained, whereby a balance of the shoelace winding device becomes superior, which contributes to the improvements of durability, reliability, operability, and maintenance performance.

BRIEF DESCRIPTION OF DRAWINGS

[0021]

FIG. 1 is a perspective view of a shoe on which a shoelace winding device embodying the present invention is installed, and FIGS 1(a) and 1(b) are cross sectional views of the shoelace winding device, where 1(a) shows a state in which a dial is in

a lock position, and 1(b) shows a state in which the dial is in a release position.

FIG. 2 is a perspective view of configurational components by disassembling the shoelace winding device embodying the present invention.

FIG. 3 is a perspective view of a base member and a reel of the shoelace winding device embodying the present invention.

FIG. 4 is a perspective view of the dial and a stopper member of the shoelace winding device embodying the present invention.

FIGS. 5(a) to 5(c) show a shaft member and a spring member of the shoelace winding device embodying the present invention, where 5(a) and 5(b) are perspective views, and 5(c) is a plan view.

FIG. 6 is a cross sectional diagram showing a manner upon when the shaft member is assembled onto the dial of the shoelace winding device embodying the present invention.

FIG. 7 is a side diagram showing a positional relationship of the dial and the shaft member, and a manner upon when the spring member rotates of the shoelace winding device embodying the present invention.

Description of Embodiments

[0022]

The present invention is "a shoelace winding device comprising: a reel for winding a shoelace; a base member including a reel storing section for storing the reel; a dial for rotatively driving the reel, including a stopper member for realizing a lock state in which rotation of the dial can be transmitted to the reel and a release state in which the reel is disconnected from the dial so that the reel can rotate freely; a shaft member to be fixed to the base member to attach the dial to the base member, the shaft member being configured to retain and guide the dial in a state of being movable between a lock position where the dial is caused to approach the base member and a release position where the dial is separated away from the base member; and a spring member having its one end portion axially supported along a direction orthogonally intersecting an axial direction of the shaft member by a bearing section formed at a side portion of the shaft member, and having its other end portion making constant contact with an engaging portion provided on an inner surface of the dial, wherein the shoelace winding device is configured to switch from a lock state of the reel to a release state by the dial moving from the lock position to the release position, an inversion position where the spring member is compressed the most is set at a position

between the lock position and the release position, and a direction along which the spring member is compressed is switched between the lock position and the release position", and can suitably be implemented by embodiments and the like to be described below.

[0023]

Hereinbelow, an embodiment that implemented the shoelace winding device of the present invention in sports shoes will be described.

FIG. 1 shows a shoelace winding device 1 according to the embodiment of the present invention, and a shoe S equipped with the shoelace winding device 1 at a position corresponding to an ankle, and this shoe S is configured such that an instep portion of the shoe S can be tightened by the shoelace 2 configured of a resin-coated metal wire.

[0024]

The shoelace winding device 1 is configured of a base member 3, a reel 4 for winding the shoelace 2, a stopper member 5 for controlling rotation and stop of the reel, a dial 6 for rotatively driving the reel 4, a shaft member 7 to be rotatably fixed to the base member 3 for attaching the dial 6 and the stopper member 5 onto the base member 3, a spring member 8 having its one end portion axially supported by the shaft member 7, and the like.

[0025]

The base member 3 can fix the shoelace winding device 1 to the shoe S by having a thin plate-shaped U-shaped flange 31 sewn onto the shoe S and fixed thereto, and includes a bottomed cylindrical-shaped reel storing section 32 for rotatably storing the reel 4.

[0026]

The reel storing section 32 has a rotation shaft 33 for axially supporting the reel 4 projectingly formed at its bottom center, and a gear 34 is formed on an inner circumferential surface thereof.

The gear 34 configures a ratchet mechanism by cooperating with claws 51 formed on the stopper member 5, and has a cross section formed in a shape of "saw-teeth" so that the claws 51 can only move in a direction to wind the shoelace 2 (forward rotation).

[0027]

Further, the base member 3 has shoelace draw-out openings 35 opened to a bottom of the reel storing section 32 and formed at two portions, and the shoelace 2 wound on the reel 4 can be drawn outside from the reel storing section 32.

[0028]

The reel 4 includes a shoelace winding drum 41 for winding the shoelace 2, a rotation shaft portion 42 arranged on an inner

side of the shoelace winding drum 41, an annular portion 43 connecting an inner circumferential surface of the shoelace winding drum 41 and an outer circumferential surface of the rotation shaft portion 42, and an annular groove portion 44 formed by the shoelace winding drum 41, the rotation shaft portion 42, and the annular portion 43.

[0029]

The rotation shaft 33 of the base member 3 is inserted to an inner surface side of the rotation shaft portion 42, and the reel 4 is rotatable within the reel storing section 32.

The groove portion 44 of the reel 4 is arranged on a side facing the bottom of the base member 3 (hereafter referred to as a "lower side", and an opposite side thereof as an "upper side" for the sake of convenience of explanation), and engagement projections 45 for clamping a distal end of the shoelace 2 to be guided in the groove portion 44 from an outer circumferential surface side of the shoelace winding drum 41 and retaining the same in the groove portion 44 are provided within the groove portion 44.

[0030]

A plurality of fins 46 is formed along the inner circumferential surface of the shoelace winding drum 41 on the upper side of the reel 4, and they can transmit the rotation of

the dial 6 to the reel by meshing with fins 52 formed on the lower side of the stopper member 5.

[0031]

The stopper member 5 is integrated with the dial 6 by engaging with an inner side (lower side) of the dial 6 with attachment claw portions 53 formed at its four corners being engaged with engagement holes 61 formed through the dial 6, and it can realize the lock state in which the rotation of the dial 6 can be transmitted to the reel 4 by being intervened between the reel 4 and the dial 6, and the release state in which the reel 4 is disconnected from the dial 6 so that the reel 4 can freely rotate.

[0032]

The shaft member 7 is fixed to the base member 3 by a screw 9 so as to rotatably attach the integrated dial 6 and stopper member 5 onto the base member 3, and it can retain and guide the integrated dial 6 and stopper member 5 in a state of being movable between the lock position in which the integrated dial 6 and stopper member 5 are set close to the base member 3 and the release position in which they are separated from the base member 3.

[0033]

The shaft member 7 is formed in a square column shape, and axially supports the spring members 8 in a rotatable manner by

one end portion which is linear-shaped (a shaft portion 81) and is formed on the spring members 8 being inserted into bearing sections 71 formed by cutting out two opposing side portions of the shaft member in a direction orthogonally intersecting an axial direction of the shaft member 7. That is, the spring members 8 are arranged one each at positions of the shaft member 7 that are separated about 180 degrees apart.

[0034]

Further, due to the shaft member 7 being in the square column shape, the strength of the bearing sections 71 can be increased, which can contribute to making the size of the shaft member 7 compact.

Moreover, the bearing sections 71 of the shaft member 7 are formed with their inner diameter in the vicinity of their center portions to be the smallest for easy separation from a mold.

[0035]

Each spring member 8 has its entirety formed by being curved in a substantially U shape, and a curved spring portion 82 on the other end side makes contact with an engaging portion 62 provided on an inner surface of the integrated dial 6 and stopper member 5.

The engaging portion 62 where the other end portion (spring portion 82) of the spring member 8 makes contact is provided at

an outer end narrowest portion of a spring storing space 63 formed in a cuneate shape at a boundary portion between the dial 6 and the stopper member 5.

Further, the reel 4 can be switched from a lock state to a release state by the integrated dial 6 and stopper member 5 being moved from the lock position to the release position.

[0036]

Moreover, an inversion position L where the spring portions 82 of the spring members 8 are most compressed toward the shaft member side is set to be present at a position between the lock position and the release position.

A disk-shaped cap 10 is engaged with an upper side of the dial 6 so that dust and the like do not enter the inside of the shoelace winding device 1.

[0037]

Meanwhile, a through hole 11 is formed at a center portion of the cap 10, and the reel 4, the dial 6, and the shaft member 7 can be disassembled from the base member 3 by operating the screw 9 within the inner side (lower side) of the cap 10 through this through hole 11.

[0038]

As the wire-shaped shoelace 2 formed of a composite material of resin and metal, a wire rope in which 49 strings of stainless

wires with a diameter of 0.11 to 0.13 mm are twisted that is processed by a swaging machine and coated by nylon resin can suitably be used.

[0039]

Next, a method of manufacturing the shoelace winding device 1 described above by assembling the respective components will be described.

Firstly, in order to attach the reel 4 to the base member 3 of the shoelace winding device 1, tip ends of the shoelace 2 are inserted to the shoelace draw-out openings 35 provided at two positions, and the both ends of the shoelace 2 are drawn out from the reel storing section 32 side.

Then, the both ends of the shoelace 2 are fixed to the reel 4 by sequentially inserting the tip ends of the shoelace 2 into wire insertion holes provided at six positions on the reel 4 in a sewing manner, and the reel 4 is arranged inside the reel storing section 32.

[0040]

Next, the stopper member 5 and the dial 6 are integrated by engaging the stopper member 5 to the inner side (lower side) of the dial 6, and the shaft member 7 and the spring members 8 are assembled thereto.

[0041]

In this case, the shaft member 7 is inserted into a substantially square-shaped axial hole 64 formed in the dial 6 and a substantially square-shaped axial hole 54 formed in the stopper member 5, whereas the spring portions 82 of the spring members 8 are inserted into spring storing spaces 63 from expanded portions where the axial hole 64 of the dial 6 is expanded, and moreover each spring portion 82 is guided to rotatably move to the outer end narrowest portion side from the inner end side of the spring storing space 63, and is assembled to the dial 6.

Meanwhile, a flange 72 formed at an upper end portion of the shaft member 7 makes contact with an engaging step portion 65 formed at an edge of the axial hole 64 of the dial 6, whereby the dial 6 does not come off from the shaft member 7.

[0042]

The spring portions 82 of the spring members 8 being guided to rotatably move from the inner end side of the spring storing spaces 63 toward the outer end narrowest portion side is realized because an angled surface 55 facing an upper side (dial side) is formed at an edge of the axial hole 54 of the stopper member 5.

[0043]

After having assembled the stopper member 5, the dial 6, the shaft member 7, and the spring members 8 by the above procedures, the screw 9 is inserted into a screw insertion hole 73

penetratingly formed along an axis of the shaft member 7, and the shaft member 7 and the other parts are attached to the base member 3.

[0044]

The shoelace winding device 1 can be assembled by fitting the cap 10 onto the dial 6 at last.

In disassembling the shoelace winding device 1 for maintenance or repair, a screwdriver is inserted from the through hole 11 of the cap 10 and the screw 9 is taken off, whereby the stopper member 5, the dial 6, the shaft member 7, and the spring members 8 that were assembled can be taken off from the base member 3.

[0045]

As cases where the maintenance or repair is necessary, a case where the shoelace 2 has been torn and a case where the shoelace 2 is entangled within the reel storing section 32 are most likely to happen, so being able to disconnect the stopper member 5, the dial 6, the shaft member 7, and the spring members 8 while they are being assembled from the base member 3 is very effective in improving the efficiency of the maintenance or repair work.

[0046]

Meanwhile, as materials configuring the respective components in the shoelace winding device 1 of the present embodiment, the followings were used as an example in consideration of their strength, durability, elasticity and the like; however, materials are not limited thereto.

Base member 3: Nylon

Reel 4, stopper member 5, and shaft member 7: POM (polyacetal)

Dial 6: Nylon and TPE (thermoplastic elastomer) at a periphery thereof

Spring members 8: Stainless steel

Screw 9: Carbon steel

Cap 10: ABS resin

[0047]

A method of use of the shoelace winding device 1 configured as above will be described.

In order to tighten the shoelace 2 after the shoe S is put on, the dial 6 of the shoelace winding device 1 is operated to rotate at the lock position where the dial 6 is caused to approach the base member 3, and the shoelace 2 is wound on the reel 4 thereby.

In this case, the reel 4 does not rotate in a direction with which the shoelace 2 is loosened by the claws 51 of the stopper member 5 making contact with the gear 34.

[0048]

Further, since the inversion position L where the spring members 8 are compressed the most is set at the position between the lock position and the release position, the spring members 8 are in the state shown in left side of FIG. 7 when the dial 6 is in the lock position, wherein the dial 6 is retained in the lock position.

At this occasion, the spring members 8 are oriented in a direction along which the shaft member 7 is lifted and the dial 6 is pressed down.

[0049]

Next, in order to loosen the tightened shoelace 2, the dial 6 of the shoelace winding device 1 is pulled to the upper side.

At this occasion, the spring members 8 are compressed, and by further pulling the dial 6 to the upper side against the repelling force thereof, the spring members 8 go beyond the inversion position L where they are compressed the most, the direction toward which the spring members 8 are compressed switches between the lock position and the release position,

whereby the dial 6 is moved to the release position separated away from the base member 3 (state shown in right side of FIG. 7).

At this occasion, the spring members 8 are oriented in a direction along which the shaft member 7 is pressed down and the dial 6 is lifted.

[0050]

The other end portions (spring portions 82) of the spring members 8 are making constant contact with the engaging portions 62 provided on the inner surface of the dial 6, whereby the wear of the components can be prevented.

Meanwhile, "making constant contact" is employed to improve the reliability, durability, and operability of the shoelace winding device 1 and omit fluctuation of the dial 6, and it does not intend to exclude the presence of some "play", so long as it does not affect the operation of the shoelace winding device 1.

[0051]

Since the spring members 8 switch clearly between the lock position and the release position, not only the operability is improved, but also it is easy to understand the state of the position where the dial 6 resides.

As above, when the dial 6 moves from the lock position to the release position, engagement between the fins 46 of the reel 4 and the fins 52 of the stopper member 5 is released, whereby

the reel 4 becomes freely rotatable, and the shoelace 2 is loosened thereby.

[0052]

By contrast, if the dial 6 is pressed down so as to move from the release position to the lock position, the spring members 8 go, in the opposite direction, beyond the inversion position L where they are compressed the most, and the fins 46 of the reel 4 and the fins 52 of the stopper member 5 again engage with one another; thus the shoelace 2 can be tightened by winding the shoelace 2 onto the reel 4.

[0053]

Meanwhile, in the description, a shape of the "dial" is not specifically limited so long as it functions as an operating section for rotatively driving the reel 4, and it may have a polygonal shape.

[0054]

The present invention is not limited to the shoelace winding device 1 for tightening the shoelace 2 arranged as in the configuration shown in the drawings, and may be embodied in a shoelace winding device for tightening a shoelace 2 which tightens a different portion of the shoe S.

[0055]

Furthermore, implementations can be made while suitably making changes to materials, shapes, dimensions, angles, arranged positions, sizes, numbers and the like of the respective parts of the shoelace winding device.

Industrial Applicability

[0056]

The present invention is small-sized and light weight, has superior durability, operability, and maintenance, and can suitably be used as a shoelace winding device that can conveniently be used in various types of shoes.

Reference Signs List

[0057]

1 Shoelace Winding Device

2 Shoelace

3 Base Member

31 Flange

32 Reel Storing Section

33 Rotation Shaft

34 Gear

35 Shoelace Draw-out Opening

4 Reel

41 Shoelace Winding Drum
42 Rotation Shaft Portion
43 Annular Portion
44 Groove Portion
45 Engagement Projection
46 Fin
5 Stopper Member
51 Claw
52 Fin
53 Attachment Claw Portion
54 Axial Hole
55 Angled Surface
6 Dial
61 Engagement Hole
62 Engaging Portion
63 Spring Storing Space
64 Axial Hole
65 Engaging Step Portion
7 Shaft Member
71 Bearing Section
72 Flange
73 Screw Insertion Hole

8 Spring Member

81 Shaft Portion (one end portion)

82 Spring Portion (the other end portion)

9 Screw

10 Cap

11 Through Hole

S Shoe

L Inversion Position

CLAIMS

1. A shoelace winding device comprising:
 - a reel for winding a shoelace;
 - a base member comprising a reel storing section for storing the reel;
 - a dial for rotatively driving the reel, the dial comprising a stopper member for realizing a lock state in which rotation of the dial can be transmitted to the reel and a release state in which the reel is disconnected from the dial so that the reel can rotate freely;
 - a shaft member coupling the dial to the base member, the shaft member configured to retain and guide the dial to be movable between a lock position where the dial is caused to approach the base member and a release position where the dial is spaced from the base member; and
 - a spring member comprising a first end portion and a second end portion, the first end portion axially supported along a direction orthogonally intersecting an axial direction of the shaft member by a bearing section formed at a side portion of the shaft member, the second end portion making constant contact with an engaging portion, the engaging portion provided on an inner surface of the dial,

wherein:

the shoelace winding device is configured to switch from the lock state to the release state by moving the dial from the lock position to the release position; and

the spring member is compressed to the maximum extent at an inversion position set between the lock position and the release position such that the direction along which the spring member is compressed is switched between the lock position and the release position.

2. The shoelace winding device according to claim 1, wherein:

the stopper member is fitted inside the dial and integrated with the dial; and

the engaging portion is provided at the narrowest portion of an outer end of a cuneate shaped spring storing space formed at a boundary portion between the dial and the stopper member.

3. The shoelace winding device according to claim 2, wherein the spring member is coupled to the dial by inserting the second end portion of the spring member into the spring storing space from an expanded portion where an axial hole of the dial is expanded, the second end portion being guided from an inner end of the spring storing space towards the narrowest portion of the outer end when

the spring member is inserted into the axial holes formed on the dial and the stopper member.

4. The shoelace winding device according to claim 1, wherein:

the spring member is curved to resemble a U-Shape with a linear first end portion and a curved second end portion;

the side of the first end portion is axially supported along the direction orthogonally intersecting the axial direction of the shaft member by the bearing section formed at the side portion of the shaft member; and

the side of the second end portion makes contact with the engaging portion.

5. The shoelace winding device according to claim 1, wherein

the spring member is a first spring member, and the shoelace winding device includes a second spring member that is spaced from the first spring member by 180 degrees.

Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6







Fig. 7



(a)



(b)



Lock position

Release position

