



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : A43B	A2	(11) International Publication Number: WO 00/65942 (43) International Publication Date: 9 November 2000 (09.11.00)
(21) International Application Number: PCT/US99/09567 (22) International Filing Date: 30 April 1999 (30.04.99) (71) Applicant: PECA CORPORATION [US/US]; 2443 Seaman Avenue, S. El Monte, CA 91733 (US). (71)(72) Applicant and Inventor: SHIH, Liang-Kun [-/US]; 2443 Seaman Avenue, S. El Monte, CA 91733 (US). (74) Agent: CHAN, Raymond, Yat; 516 San Luis Rey Road, Arcadia, CA 91007 (US).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DE (Utility model), DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KR (Utility model), KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>Without international search report and to be republished upon receipt of that report.</i>
(54) Title: WADERS AND THE METHOD FOR MANUFACTURING THEM (57) Abstract A pair of waders includes a gas permeable layer having a first side and a second end, a water-proof film fixedly mounted on the first side of the gas permeable layer, an outer cover fixedly mounted on the water-proof film, and a lining fixedly mounted on the side of the gas permeable layer.		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

Title of Invention

Waders and the Method for Manufacturing Them

5 Field of the Invention

The present invention relates to waders, and more particularly to waders and the method for manufacturing them.

Background of the Invention

10 Conventional pair of waders are shown in Fig. 6, and an illustration will follow in the detailed description of the preferred embodiments. The present invention has arisen to mitigate and/or obviate the disadvantage of the conventional fishing trousers.

Summary of the Invention

15 In accordance with one aspect of the present invention, there is provided a pair of waders comprising a gas permeable layer including a first side and a second side, a water-proof film fixedly mounted on the first side of the gas permeable layer, an outer cover fixedly mounted on the water-proof film, and lining fixedly mounted on the second side of the gas permeable layer.

20 In accordance with another aspect of the present invention, there is provided a method for manufacturing a pair of waders and comprising the steps of: (a) providing a lining, a gas permeable layer including a first side and second side, a water-proof film, and an outer cover; (b) forming a plurality of vent holes through the gas permeable layer; (c) mounting the water-proof film on the first side of the gas permeable layer; (d) mounting the outer cover on the water-proof film; (e) mounting the lining on the second side of the gas permeable layer to form a laminated layer including the lining, the gas permeable layer, the water-proof film and
25 the outer cover; (f) cutting the laminated layer so as to form a plurality of peripheral cut edges; (g) adhering the peripheral cut-edges of the laminated layer to form a product of the pair of waders.

Further features of the present invention will become apparent after a careful reading of the detailed description with appropriate reference to the accompanying drawings.

Brief Description of Drawings

Fig. 1 is a flow chart of a method for manufacturing a pair of waders in accordance with the present invention;

5

Fig. 2 is a perspective view of the waders in accordance with the present invention;

Fig. 3 is a partially exploded view of the waders shown in Fig. 2;

10

Fig. 4 is a front plan cross-sectional assembly view of the waders shown in Fig. 3;

Fig. 5 is a front plan partially cross-sectional view showing two heating rolls for coupling a gas permeable layer and a water-proof film; and

15

Fig. 6 is a perspective view of a conventional pair of waders in accordance with the prior art.

20

25

30

Detailed Description of the Preferred Embodiments

For a better understanding of features and benefits of the present invention, reference is now made to Fig. 6, illustrating a conventional pair of waders 50 in accordance with the prior art. The conventional waders 50 are water-proof and can be adapted to suit a fisherman, a yachtsman, etc, thereby preventing the wearer's trunk and legs from getting wet. However, the conventional waders 50 are impermeable to gas such that they cannot provide a ventilating effect to the wearer, thereby easily causing an uncomfortable sensation due to moisture accumulating therein. In addition, the conventional waders 50 are heavy, thereby causing an inconvenience to the wearer.

Referring to the remaining drawings, and initially to Figs. 2-4, a pair of waders 1 according to the present invention comprises a gas permeable layer 20 including a first side and a second side, a water-proof film 30 fixedly mounted on the first side of the gas permeable layer 20, an outer cover 40 fixedly mounted on the water-proof film 30, and a lining 10 fixedly mounted on the second side of the gas permeable layer 20.

The gas permeable layer 20 is made of foamable material or synthetic rubber and defines a plurality of vent holes 21 therethrough. The water-proof film 30 is preferably made of polyurethane (P.U.). The outer cover 40 and the lining 10 are made of nylon cloth respectively.

In operation, a person can put on the waders 1 with the lining 10 directly contacting on her skin and with the outer cover 40 exposed to surroundings. In such a manner, the gas permeable layer 20 can be adapted to provide a ventilating effect to the wearer by means of the vent holes 21, thereby incurring a comfortable sensation.

In addition, the water-proof film 30 can be adapted to efficiently to prevent water from entering and wetting the lining 10 via the vent holes 21, thereby achieving a water-proof function.

Referring now to Figs. 1-5, a method in accordance with present invention can be adapted for manufacturing a pair of waders 1 and comprises the following steps.

First of all, the lining 10, the gas permeable layer 20 including the first side and a second side, the water-proof film 30, and the outer cover 40 are initially selected, wherein the gas permeable layer 20 is made of foamable material or synthetic rubber, the water-proof film 30 is made of polyurethane (P.U.), the outer cover 40 and the lining 10 are made of nylon cloth respectively.

Preferably, the gas permeable layer 20 together with the water-proof film 30 can be conveyed to be heated and pressurized between a pair of heating rolls 60 as shown in Fig. 5 such that the water-proof film 30 can be tightly adhered on the first side of the gas permeable layer 20. The heating temperature for heating the gas permeable layer 20 together with the water-proof film 30 ranges between 110°C and 130°C.

Then, the outer cover 40 can be mounted on the water-proof film 30 by means of such as adhesion, and the lining 10 can be mounted on the second side of the gas permeable layer 20 by means of such as adhesion, thereby forming a laminated layer including the lining 10, the gas permeable layer 20, the water-proof film 30 and the outer cover 40.

The laminated layer can then be cut according to the shape of the waders 1 so as to form a plurality of peripheral cut edges. The peripheral cut edges of the laminating layer can then be adhered together to form a semi-product of the waders 1.

Finally, the peripheral cut edges of the laminated layer can be sewed, thereby forming a product of the pair of waders 1 as shown in Fig. 4.

It should be clear to those skilled in the art that further embodiments may be made without departing from the scope and spirit of the present invention.

What is claimed is:

1. A pair of waders, comprising

5 a gas permeable layer (20) including a first side and a second side;

a water-proof film (30) fixedly mounted on said first side of said gas permeable layer (20);

10 an outer cover (40) fixedly mounted on said water-proof film (30); and
a lining (10) fixedly mounted on said second side of said gas permeable layer (20).

2. The waders in accordance with claim 1, wherein said gas permeable layer (20) defines a plurality of vent holes (21) therethrough.

15

3. The waders in accordance with claim 1, wherein said gas permeable layer (20) is made of foamable material.

20

4. The waders in accordance with claim 1, wherein said gas permeable layer (20) is made of synthetic rubber.

5. The waders in accordance with claim 1, wherein said outer cover (30) is made of polyurethane.

25

6. The waders in accordance with claim 1, wherein said outer cover (40) is made of nylon cloth.

7. The waders in accordance with claim 1, wherein said lining (10) is made of nylon cloth.

30

8. A method for manufacturing a pair of waders and comprising the steps of:

(a) providing a lining (10), a gas permeable layer (20) including a first side and a second side, a water-proof film, (30), and an outer cover (40);

(b) forming a plurality of vent holes (21) through said gas permeable layer (20);

(c) mounting said water-proof film (30) on said first side of said gas permeable layer (20);

5

(d) mounting said outer cover (40) on said water-proof film (30);

(e) mounting said lining (10) on said second side of said gas permeable layer (20) to form a laminated layer including said lining (10), said gas permeable layer (20), said water-proof film (30) and said outer cover (40);

10

(f) cutting said laminated layer so as to form a plurality of peripheral cut edges;

15

(g) adhering said peripheral cutting edges of said laminated layer to form a semi-product of a pair of waders; and

(h) sewing up said peripheral cut edges of said laminated layer to form a product of said pair of waders.

20

9. The method in accordance with claim 8, wherein said gas permeable layer (20) is made of foamable material.

10. The method in accordance with claim 8, wherein said gas permeable layer (20) is made of synthetic rubber.

25

11. The method in accordance with claim 8, after said step (c) further comprising the steps of: providing a pair of a heating rolls (60); and conveying said gas permeable layer (20) together with said water-proof film (30) to be heated and pressurized between said pair of heating rolls (60).

30

12. The method in accordance with claim 11, wherein the heating temperature for heating said gas permeable layer (20) together with said water-proof film (30) ranges between 110°C and 130°C.