



- (51) **International Patent Classification:**
F21V 21/14 (2006.01) *F21V 14/02* (2006.01)
F21V 17/10 (2006.01)
- (21) **International Application Number:**
PCT/US2015/068116
- (22) **International Filing Date:**
30 December 2015 (30.12.2015)
- (25) **Filing Language:** English
- (26) **Publication Language:** English
- (30) **Priority Data:**
62/104,387 16 January 2015 (16.01.2015) US
- (71) **Applicant:** HUBBELL INCORPORATED [US/US]; 40 Waterview Drive, P.O. Box 1000, Shelton, CT 06484 (US).
- (72) **Inventors:** VANG, Seng; 707 Poplar Drive, Apt. 105, Greer, SC 29651 (US). WERR, Martin, Carl; 401 Watson Road, Easley, SC 29642 (US). RECTOR, David, John; 517 Cranberry Hill Circle, Mauldin, SC 29667 (US). LEWIS, Randy, Kent; 201 Peppercorn Court, Greenville, SC 29607 (US). SIMONI, David, Arthur; 6 Ketydiel Lane, Piedmont, SC 29673 (US).
- (74) **Agent:** HEPNER, Kyle, G.; Michael Best & Friedrich LLP, 601 Pennsylvania Avenue NW, Suite 700 South, Washington, DC 20004 (US).
- (81) **Designated States** (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.
- (84) **Designated States** (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

[Continued on next page]


(54) **Title:** DIMENSIONALLY ADJUSTABLE LUMINAIRE HOUSING

FIG. 3

(57) **Abstract:** A luminaire includes a wall assembly, a support, and a door. The wall assembly has a first side wall, a second side wall, a first end wall connected to the first and second side walls, and a second end wall connected to the first and second side walls. The support is connected to the wall assembly. The door includes a lens and is connected to the wall assembly. The door is moveable between an open position and a closed position. The side walls and end walls can be formed with various lengths and selectively connected together to form different sized wall assemblies.



Published:

— with international search report (Art. 21(3))

— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))

PATENT APPLICATION
OF
SENG VANG
MARTIN WERR
DAVID RECTOR
RANDY LEWIS
DAVID SIMONI
FOR
DIMENSIONALLY ADJUSTABLE LUMINAIRE HOUSING

RELATED APPLICATION

[0001] This application is based on U.S. Provisional Application Serial No. 62/104,387, filed January 16, 2015, the disclosure of which is incorporated herein by reference in its entirety and to which priority is claimed.

FIELD

[0002] Various exemplary embodiments of the invention relate to luminaires, for example recessed luminaires.

BACKGROUND

[0003] Luminaires, or light fixtures, are used with electric light sources to provide aesthetic and functional housing in both interior and exterior applications. Various types of interior luminaires include overhead, ceiling, ceiling system, or suspended luminaires, which are designed to be positioned near, or suspended from, the ceiling.

SUMMARY

[0004] According to an exemplary embodiment, a luminaire housing includes a first set of side walls having a first length, a second set of side walls having a second length different than the first length, a first set of end walls having a third length, and a second set of end walls having a fourth length different than the third length. One of the first and second sets of side walls is connected to one of the first and second sets of end walls to form a wall assembly for a luminaire housing.

[0005] According to another exemplary embodiment, a luminaire housing includes a first wall assembly having a first side wall, a second side wall, a first end wall connected to the first and second side walls, and a second end wall connected to the first and second side walls. A mounting plate is connected to the wall assembly so that the position of the mounting plate can be adjusted with respect to the wall assembly. A door having a lens is connected to the wall assembly and moveable between an open position and a closed position.

[0006] According to another exemplary embodiment, a luminaire housing includes a first side wall and a second sidewall connected to a first end wall and a second endwall. A top cover is connected to the first and second sidewalls and the first and second endwalls. A recess is positioned in the top cover to receive a control component for a light emitter.

BRIEF DESCRIPTION OF THE DRAWINGS

[0007] The aspects and features of various exemplary embodiments will be more apparent from the description of those exemplary embodiments taken with reference to the accompanying drawings, in which:

[0008] FIG. 1 is a bottom perspective view of an exemplary luminaire;

[0009] FIG. 2 is a top perspective view of the luminaire of FIG. 1;

[0010] FIG. 3 is a bottom perspective view of the luminaire of FIG. 1 with the door open and the mounting plate partially removed;

[0011] FIG. 4 is a top perspective, exploded, view of the luminaire of FIG. 1;

[0012] FIG. 5 is a top perspective view of another exemplary luminaire;

[0013] FIG. 6 is a bottom perspective view of the luminaire of FIG. 5 with the door assembly in an open position;

[0014] FIG. 7 is a bottom perspective view of the luminaire of FIG. 5 with the door removed;

[0015] FIG. 8 is a bottom perspective view of an exemplary mounting plate;

[0016] FIG. 9 is a top perspective, exploded view of the luminaire of FIG. 5;

[0017] FIG. 10 is a top perspective view of the luminaire of FIG. 5;

[0018] FIG. 11 is a top perspective view of another exemplary luminaire;

- [0019] FIG. 12 is a bottom perspective view of the luminaire of FIG. 11 with the door assembly in an open position;
- [0020] FIG. 13 is a bottom perspective view of another exemplary luminaire;
- [0021] FIG. 14 is a top perspective view of the luminaire of FIG. 13;
- [0022] FIG. 15 is a bottom perspective view of the luminaire of FIG. 13 with the door assembly in an open position;
- [0023] FIG. 16 is a top perspective view of an exemplary end wall;
- [0024] FIG. 17 is a front view of the end wall of FIG. 16;
- [0025] FIG. 18 is a left side view of the end wall of FIG. 16;
- [0026] FIG. 19 is a top view of an exemplary mounting plate;
- [0027] FIG. 20 is a bottom view of the mounting plate of FIG. 19;
- [0028] FIG. 21 is a magnified view of detail A of FIG. 19;
- [0029] FIG. 22 is a sectional view of FIG. 21 taken along line B-B;
- [0030] FIG. 23 is a sectional view of FIG. 19 taken along line C-C;
- [0031] FIG. 24 is a left side view of an exemplary side wall;
- [0032] FIG. 25 is a front view of the side wall of FIG. 24;
- [0033] FIG. 26 is a magnified view of detail A of FIG. 24;
- [0034] FIG. 27 is a bottom view of an exemplary housing assembly;
- [0035] FIG. 28 is a right side view of the housing assembly of FIG. 27;
- [0036] FIG. 29 is a magnified view of detail A of FIG. 27;
- [0037] FIG. 30 is a sectional view of FIG. 29 taken along line B-B;
- [0038] FIG. 31 is a sectional view of FIG. 27 taken along line C-C;
- [0039] FIG. 32 is a sectional view of FIG. 28 taken along line E-E;
- [0040] FIG. 33 is a bottom perspective view of an exemplary housing assembly;
- [0041] FIG. 34 is a bottom, unfolded view of the housing assembly of FIG. 33;
- [0042] FIG. 35 is a bottom view of the housing assembly of FIG. 33;
- [0043] FIG. 36 is a sectional view of FIG. 35 taken along line A-A;
- [0044] FIG. 37 is a bottom perspective view of an exemplary housing assembly;
- [0045] FIG. 38 is a bottom view of the housing assembly of FIG. 37; and
- [0046] FIG. 39 is a front view of the housing assembly of FIG. 37.

DETAILED DESCRIPTION OF EXEMPLARY EMBODIMENTS

[0047] FIGS. 1-4 depict an exemplary embodiment of a luminaire 10 having a housing assembly 12 and one or more light emitting devices (not shown). The light emitting device can include one or more Light Emitting Diodes (LEDs), fluorescents, halogens, or other light emitters. The luminaire 10 has a 1x4 configuration – that is, it is 4 times longer in one dimension, length or width, than it is in the other. For example, a 1 foot by 4 foot luminaire.

[0048] In an exemplary embodiment the housing assembly 12 includes a first side wall 14, a second side wall 16, a first end wall 18, and a second end wall 20, a support for retaining the light emitting device, for example a mounting plate 22, a cover 24, and a door 26. The various components of the housing assembly 12 can be a single piece or formed from multiple pieces and connected together, for example through brackets, rivets, fasteners, or other mounting features. In an exemplary embodiment, the side walls 14, 16 and end walls 18, 20 are made from sheet metal, or other stiff, lightweight material.

[0049] As best shown in FIGS. 1-4, and according to various exemplary embodiments, each of the first and second side walls 14, 16 and first and second end walls 18, 20 includes a bottom flange 28A, 28B, 28C, 28D that combines when assembled to form a mounting flange 28 for the housing assembly 12. The mounting flange 28 can be used as a grip or grip-slot type mounting flange when placed in recessed ceiling.

[0050] In an exemplary embodiment, the door 26 includes a frame 30 surrounding an optical element 32, for example a lens or diffuser, which can be removably received by the door 26. The door 26 is moveably and removably connected to the remainder of the housing assembly 12, for example to the side walls 14, 16, so that different door types can be used with the housing assembly 12. The mounting plate 22 is removably and moveably connected to the first and second end walls 18, 20.

[0051] FIGS. 5-10 depict another exemplary embodiment of a luminaire 100 having a housing assembly 112 and one or more light emitting devices 102. The luminaire 100 is configured to have a 2x2 size. The housing assembly 112 includes first and second side walls, 114, 116, first and second end walls, 118, 120, a mounting

plate 122, a cover 124. A door 126 having a frame 130 and an optical element 132. The door 126 can optionally include a cross member 134. The cross member 134 can separate the optical element 132 into four different segments or retain four separate optical elements 132.

[0052] In the exemplary embodiment shown in FIG. 7, the flange 128 of the first side wall 114 includes a pair of cutout portions 136 to act as a hinge to pivotably receive a portion of the door 126, for example a protrusion on the door 126. The second side wall 116, includes one or more latches 138 for retaining the door 126 in the closed position. The cutout portions 136 and latches 138 can be incorporated into any of the exemplary embodiments described herein.

[0053] As best shown in FIG. 9, the light emitting device 102 includes a substrate 104 containing a plurality of LED packages or modules 106. The substrates are connected to the mounting plate 122, for example through one or more fasteners. FIG. 9 shows 8 LED substrates 104, although different numbers can be used depending on the size and configuration of the luminaire 100. As best shown in the exemplary embodiment of FIG. 10, the top of the mounting plate 122 receives one or more power or control components 108, for example an LED ballasts or driver. The top and bottom surfaces of the mounting plate 122 can include a number of grooves and openings for connecting the light emitting devices 102 and power control component 108, and to provide pathways or conduits for connectors between the two. The light emitting device 102 can be incorporated into any of the exemplary embodiments described herein.

[0054] FIGS. 11 and 12 depict an exemplary embodiment of a luminaire 200 having a housing assembly 212 configured to have a 2x4 size. The housing assembly 212 includes first and second side walls 214, 216, first and second end walls 218, 220, a mounting plate 222, and a cover 224. A door 226 having a frame 230 and one or more optical elements 232 is connected to the housing 212. The door 226 can also include an optional cross member 234. The cross member 234 can separate the optical element 232 into six different segments or retain six separate optical elements 232.

[0055] FIGS. 13-15 depict an exemplary embodiment of a luminaire 300 having a housing assembly 312 configured as an edge lighting device. The housing assembly 312 includes first and second side walls, 314, 316, first and second end walls, 318, 320, a cover 324, and a door 326 having a frame 330 and one or more optical elements 332. In this assembly, the mounting plate is removed and the light emitting device (not shown) and cover are positioned on, and connected to, the door 326. The exemplary optical element 332 shown curves toward the light emitting device.

[0056] FIGS. 16-18, depict an exemplary end wall 18 that can be used with any of the exemplary embodiments described herein. The end wall 18 includes a set of ladder adjustment features 40, for example a first ladder adjustment feature and a second ladder adjustment feature. The ladder adjustment feature 40 includes a vertical slot 42 with a plurality of branching slots 44 extending therefrom. The branching slots 44 extend away from the vertical slot 42 and curve downward towards the flange 28. In various exemplary embodiments, the mounting plate 22 includes a plurality of posts or other protrusions extending from a first end and a second end to be removeably received in a respective ladder adjustment feature 40. Adjusting the position of the mounting plate 22 in the ladder adjustment features 40 adjusts the spacing of the light emitting device to the ceiling and to the optical component 32 in the door 26. By adjusting the distance to the optical component 32, the characteristics of the light emitted to a room can be modified. For example, the optical component 32 may contain a plurality of diffuser elements that disperse the light based on the position of the light source.

[0057] FIGS. 19-23, depict an exemplary mounting plate 22 having a bottom surface and a top surface. One or more light emitting devices are connected to the bottom surface of the mounting plate 22 and hardware associated with the light emitting devices, for example a driver or ballast, is positioned on top of the mounting plate 22. The mounting plate 22 can include various mounting features to connect hardware and apertures, including slots and openings, to provide a passage for electrically connecting a light emitting device to the hardware. FIGS. 19-22 depict a mounting plate 22 having one or more clips 48 to retain drivers and one or more slots 46 to provide a conduit for one or more conductors.

[0058] FIGS. 24-26 depict an exemplary sidewall 14. The sidewall 14 includes a cut out portion 50 that acts as a hinge to pivotally receive a portion of the door 26. As best shown in the exemplary embodiments of FIGS. 3, 6, 12, and 15, one side of the door 26, 126, 226, 326 can be pivoted with respect to the cutout portion 50 and the mounting plate 22 can be pivoted about the two ladder adjustment features 40 on opposite end walls 18, 20 to provide access from below the luminaire 10, without having to remove the entire light housing assembly 12. This can allow a user to install or replace components of the luminaire without removing the housing from the ceiling or removing ceiling components to gain access to the top of the luminaire.

[0059] The sidewalls 12, 14 can be formed at any length and the end walls 18, 20 may also be formed at any length. Different sizes of side walls 12, 14 and end walls 18, 20 can be connected together, providing a modular unit that can be used in different applications. For example, a set of end walls 18, 20 having a length of two feet can be used with sets of side walls 12, 14 having a length of two through six feet to form different length luminaires.

[0060] FIGS. 27-32 depict an exemplary embodiment of a single piece luminaire housing 412 that can be formed or molded as a single piece, unitary and/or monolithic structure. The housing assembly 412 includes first and second side walls 414, 416, first and second end walls 418, 420, a top cover 424, and a bottom flange 428. The first side wall includes one or more hinge cut outs 450 to pivotally receive a door assembly (not shown). The housing 412 can be formed in different sizes and shapes.

[0061] FIGS. 33-36 depict an exemplary housing assembly 612 having first and second side walls 614, 616, first and second end walls 618, 620, a top cover 624, and a bottom flange 628. The cover 624 includes a pair of recesses 652 to receive one or more power or control components, for example an LED driver. One or more plates, or other structures or substrates, containing LEDs can be placed into the interior of the housing assembly 612 and connected to one or more control components positioned in the recess 652. FIGS. 37-39 depict a similar housing assembly 712 having a substantially rectangular configuration. The housings 612, 712 can be formed in different sizes and shapes.

[0062] The foregoing detailed description of the certain exemplary embodiments has been provided for the purpose of explaining the principles of the invention and its practical application, thereby enabling others skilled in the art to understand the invention for various embodiments and with various modifications as are suited to the particular use contemplated. This description is not necessarily intended to be exhaustive or to limit the invention to the exemplary embodiments disclosed. Any of the embodiments and/or elements disclosed herein may be combined with one another to form various additional embodiments not specifically disclosed. Accordingly, additional embodiments are possible and are intended to be encompassed within this specification and the scope of the appended claims. The specification describes specific examples to accomplish a more general goal that may be accomplished in another way.

[0063] As used in this application, the terms “front,” “rear,” “upper,” “lower,” “upwardly,” “downwardly,” and other orientational descriptors are intended to facilitate the description of the exemplary embodiments of the present invention, and are not intended to limit the structure of the exemplary embodiments of the present invention to any particular position or orientation. Terms of degree, such as “substantially” or “approximately” are understood by those of ordinary skill to refer to reasonable ranges outside of the given value, for example, general tolerances associated with manufacturing, assembly, and use of the described embodiments.

What Is Claimed:

1. A modular luminaire system comprising:
 - a first set of side walls having a first length;
 - a second set of side walls having a second length different than the first length;
 - a first set of end walls having a third length; and
 - a second set of end walls having a fourth length different than the third length,wherein one of the first and second sets of side walls is connected to one of the first and second sets of end walls to form a wall assembly for a luminaire housing.
2. The modular luminaire system of claim 1, wherein the first and second sets of side walls are formed to have a length in the range of approximately 1 foot to approximately ten feet and the first and second sets of end walls are formed to have a length in the range of approximately 1 foot to approximately ten feet.
3. The modular luminaire system of claim 1, further comprising a support connected to the wall assembly and a lens connected to the wall assembly.
4. The modular luminaire system of claim 3, wherein the lens is connected to a door that is moveably connected to the wall assembly.
5. The modular luminaire system of claim 3, wherein the position of the support with respect to the wall assembly is adjustable.
6. The modular luminaire system of claim 3, wherein the end walls includes a height adjustment feature and the support is connected to the height adjustment feature.
7. The modular luminaire system of claim 6, wherein the height adjustment feature includes a ladder adjustment feature having a vertical slot and a plurality of branching slots.

8. The modular luminaire system of claim 1, further comprising a door having a lens and connected to the wall assembly and a support connected to the door.
9. A luminaire housing comprising:
 - a wall assembly having a first side wall, a second side wall, a first end wall connected to the first and second side walls, and a second end wall connected to the first and second side walls;
 - a mounting plate connected to the wall assembly so that the position of the mounting plate can be adjusted with respect to the wall assembly; and
 - a door having a lens connected to the wall assembly and moveable between an open position and a closed position.
10. The luminaire housing of claim 9, wherein the mounting plate is pivotally connected to the wall assembly.
11. The luminaire housing of claim 9, wherein the first and second end walls includes a height adjustment feature and the mounting plate is connected to the height adjustment feature.
12. The luminaire housing of claim 9, wherein the height adjustment feature includes a ladder adjustment feature having a vertical slot and a plurality of branching slots.
13. The luminaire housing of claim 12, wherein the branching slots include a downward curve.
14. The luminaire housing of claim 9, wherein the door is pivotally connected to the wall assembly.
15. The luminaire housing of claim 9, further comprising one or more light emitters connected to the mounting plate.

16. The luminaire housing of claim 15, further comprising a control component connected to the mounting plate and operably connected to the one or more light emitters.
17. A luminaire housing comprising:
 - a first side wall and a second sidewall connected to a first end wall and a second endwall;
 - a top cover connected to the first and second sidewalls and the first and second endwalls; and
 - a recess positioned in the top cover to receive a control component for a light emitter.
18. The luminaire housing of claim 17, wherein the recess is sized to receive a driver.
19. The luminaire housing of claim 17, wherein the first and second sidewalls, the first and second endwalls, and the recess are integrally formed.
20. The luminaire housing of claim 17, further comprising a second recess positioned in the top cover to receive a control component for a light emitter.

1/12




FIG. 1




FIG. 2




FIG. 3




FIG. 4

3/12




FIG. 5




FIG. 6




FIG. 7

4/12




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12

6/12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18

8/12




FIG. 19




FIG. 20






FIG. 21



SECTION B-B

FIG. 22



SECTION C-C

FIG. 23




FIG. 24




FIG. 25

FIG. 26

10/12




FIG. 27




FIG. 28




FIG. 29




SECTION B-B

FIG. 30



SECTION C-C

FIG. 31



SECTION E-E

FIG. 32

11/12




FIG. 33




FIG. 34





FIG. 35



SECTION A-A
FIG. 36

12/12




FIG. 37




FIG. 38




FIG. 39

INTERNATIONAL SEARCH REPORT

International application No.

PCT/US15/68116

A. CLASSIFICATION OF SUBJECT MATTER

IPC(8) - F21V 21/14, 17/10, 14/02 (2016.01)

CPC - F21V 17/002, 21/14, 14/02

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC(8): F21V 1/08, 11/04, 14/02, 14/08, 15/01, 17/02, 17/10, 21/04, 21/14; F21S 8/00, 8/04, 8/06, 8/08 (2016.01)

CPC: F21V 1/08, 11/04, 14/02, 14/08, 15/012, 17/002, 17/02, 17/10, 17/18, 21/04, 21/14; F21S 8/026, 8/043, 8/086

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

PatSeer (US, EP, WO, JP, DE, GB, CN, FR, KR, ES, AU, IN, CA, INPADOC Data); Google Scholar; EBSCO Discovery Service; IP.com; Keywords: lighting*, luminaire*, modular*, adjustable*, interchang*, housing*, enclosure*, troffer*, lens*, end* wall*, side* wall*, door*, ratchet*, channel lock*

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X --- Y	US 3,983,387 A (VAN STEENHOVEN, F et al.) September 28, 1976; abstract; figures 1-6; column 1, lines 52-68; column 2, lines 1-12 and 39-68; column 3, lines 3-19	1 and 3-8 --- 2
Y	US 3,796,870 A (PETTYJOHN, W) March 12, 1974; figures 1 and 2; column 3, lines 26-68; column 4, lines 1-8	2
A	US 2013/0128558 A1 (RISLEY, J et al.) May 23, 2013; entire document	1-8
A	US 8,220,961 B2 (BELKNAP, L et al.) July 17, 2012; entire document	1-8
A	US 7,234,832 B2 (LIPPIS, M et al.) June 26, 2007; entire document	1-8
A	US 3,810,085 A (WOLOSKI, L) May 7, 1974; entire document	1-8
A	US 3,643,079 A (GLICKMAN, R) February 15, 1972; entire document	1-8

☐ Further documents are listed in the continuation of Box C.☐ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

14 April 2016 (14.04.2016)

Date of mailing of the international search report

11 MAY 2016

Name and mailing address of the ISA/

Mail Stop PCT, Attn: ISA/US, Commissioner for Patents
P.O. Box 1450, Alexandria, Virginia 22313-1450

Facsimile No. 571-273-8300

Authorized officer

Shane Thomas

PCT Helpdesk: 571-272-4300
PCT OSP: 571-272-7774

---Continued from Box III: Observations where unity of invention is lacking---

This application contains the following inventions or groups of inventions which are not so linked as to form a single general inventive concept under PCT Rule 13.1. In order for all inventions to be examined, the appropriate additional examination fee must be paid.

Group I: Claims 1-8 are directed towards a luminaire system comprising a first set of side walls having a first length; a second set of side walls having a second length different than the first length; a first set of end walls having a third length; and a second set of end walls having a fourth length different than the third length.

Group II: Claims 9-16 are directed towards a mounting plate connected to the wall assembly so that the position of the mounting plate can be adjusted with respect to the wall assembly; and a door having a lens connected to the wall assembly and moveable between an open position and a closed position.

Group III: Claims 17-20 appear to be directed towards a top cover connected to the first and second sidewalls and the first and second endwalls; and a recess positioned in the top cover to receive a control component for a light emitter.

The inventions listed as Groups I-III do not relate to a single general inventive concept under PCT Rule 13.1 because, under PCT Rule 13.2, they lack the same or corresponding special technical features.

The special technical features of Group I are at least a first set of side walls having a first length; a second set of side walls having a second length different than the first length; a first set of end walls having a third length; and a second set of end walls having a fourth length different than the third length, which Groups II & III do not have. Group II has at least a mounting plate connected to the wall assembly so that the position of the mounting plate can be adjusted with respect to the wall assembly; and a door having a lens connected to the wall assembly and moveable between an open position and a closed position, which Groups I & III do not have. Group III has at least a top cover connected to the first and second sidewalls and the first and second endwalls; and a recess positioned in the top cover to receive a control component for a light emitter, which Groups I & II do not have.

The common technical features are at least a luminaire housing comprising: a wall assembly having a first side wall, a second side wall, a first end wall connected to the first and second side walls, and a second end wall connected to the first and second side walls, forming a wall assembly for the luminaire housing. These common technical features are previously disclosed by US 8,220,961 A to Belknap, Lines et al. (hereinafter 'Belknap'). Belknap discloses a luminaire housing (an LED light fixture with a housing; figure 3, column 4, lines 10-43) comprising: a wall assembly having a first side wall (a left wall; figure 3), a second side wall (a right wall; figure 3), a first end wall connected to the first and second side walls (a forward wall connected to the left and right walls, respectively; figure 3), and a second end wall connected to the first and second side walls (a rearward wall connected to the left and right walls, respectively; figure 3), forming a wall assembly for the luminaire housing (the walls form the LED light fixture housing; figure 3).

Since these features are previously disclosed by Belknap, these are not special and so Groups I-III lack unity.

INTERNATIONAL SEARCH REPORT

International application No.

PCT/US15/68116

Box No. II Observations where certain claims were found unsearchable (Continuation of item 2 of first sheet)

This international search report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:
because they relate to subject matter not required to be searched by this Authority, namely:

2. ☐ Claims Nos.:
because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out, specifically:

3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box No. III Observations where unity of invention is lacking (Continuation of item 3 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

See additional sheet

1. ☐ As all required additional search fees were timely paid by the applicant, this international search report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying additional fees, this Authority did not invite payment of additional fees.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☒ No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:
Claims 1-8

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest and, where applicable, the payment of a protest fee.
- ☐ The additional search fees were accompanied by the applicant's protest but the applicable protest fee was not paid within the time limit specified in the invitation.
- ☐ No protest accompanied the payment of additional search fees.