



(43) International Publication Date
31 January 2013 (31.01.2013)

- (51) International Patent Classification:
A61F 5/443 (2006.01) *A61F 5/445* (2006.01)
- (21) International Application Number:
PCT/EP2012/064692
- (22) International Filing Date:
26 July 2012 (26.07.2012)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
11175758.9 28 July 2011 (28.07.2011) EP
- (71) Applicant (for all designated States except US): **HOLLISTER INCORPORATED** [US/US]; 2000 Hollister Drive, Libertyville, Illinois 60048-3781 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **GRUM-SCHWENSEN, Christen** [DK/DK]; Gribskovvænget 12, Gadevang, DK-3400 Hillerød (DK). **HANNESTAD, Vigdis** [NO/NO]; Kroken 9A, N-5003 Bergen (NO).

(74) Agent: **HØIBERG A/S**; St. Kongensgade 59 A, DK-1264 Copenhagen K (DK).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM,

[Continued on next page]

(54) Title: AN OSTOMY SEALING MEMBER PACKAGE AND AN OSTOMY SEALING MEMBER THEREFORE




FIG. 9

(57) Abstract: The present disclosure concerns a package for an ostomy sealing member for sealing around a stoma in relation to an ostomy appliance, said sealing member comprising a hypo-allergenic, mouldable adhesive material, said sealing member having an annular periphery and an opening therein for receiving a stoma, wherein the opening is non-concentric with the periphery.

WO 2013/014231 A1



TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, **Published:**
ML, MR, NE, SN, TD, TG).

— *with international search report (Art. 21(3))*

An Ostomy Sealing Member package and an ostomy sealing member therefore

5 The present invention relates to an ostomy sealing member for providing a snugly and tight sealing around a stoma and a protective package for accommodating such ostomy sealing member.

Ostomy appliances are well known and may be provided as one-piece or two piece appliances. A body-side member or faceplate is attached to the wearer's abdomen and a bag is attached to the body-side member for receiving exudates from the ostomy. The bag and
10 faceplate are permanently connected in a one-piece appliance and detachably connectable in a two piece appliance.

When using a one-piece appliance, the whole appliance including the faceplate adhesively securing the appliance to the skin is removed and replaced by a fresh appliance. In two-piece
15 appliances, the faceplate is left in place and only the collection bag is replaced. The advantage of such a two-piece appliance over a conventional one-piece appliance is that a number of bags may be used successively with a single faceplate. The user of a two-piece appliance may therefore leave a faceplate adhesively attached to the skin for an extended period, without the discomfort, inconvenience, and skin irritation that frequent removal and
20 replacement of an adhesive faceplate may involve, and simply remove a used bag and replace it with a fresh one whenever needed. Further, a two-piece device allows for seeing the stoma while attaching the pouch over the faceplate.

It is known to place a barrier ring on the skin on the faceplate or to make a filling paste
25 between the edge of the stoma in order to form a seal between the stoma and the ostomy appliance to avoid exudates contacting the skin around the stoma. The barrier ring is made of an adhesive material which is mouldable, bendable and stretchable for use on oval or otherwise irregularly shaped stomas. The ring is provided in the shape of a disc which is usually first placed on the skin-side of the faceplate and for fitting around the stoma and
30 mouldable to a customized convexity in the skin surface around the stoma before placing the faceplate of the ostomy appliance on the skin. The barrier sealing ring is intended to be easy to use even for users with limited dexterity. This has to a large extent been achieved with the sealing members known in the art but with the present disclosure it is realised that an ostomy sealing member with improved user-friendliness may be provided.

35 Improved user-friendliness is also achieved by a package accommodating an ostomy sealing member for sealing around a stoma in relation to an ostomy appliance, said ostomy sealing member comprising a mouldable adhesive material, said sealing member having an annular periphery and an opening therein for receiving a stoma, wherein the ostomy sealing member
40 is accommodated in a tray portion having a cavity dimensioned for snugly receiving the ostomy sealing member and which is integrally formed with a lid portion for removably

closing the tray and with a hinge portion between said try and said lid portions, and wherein a first release film is provided in the cavity between the tray portion and the sealing member and wherein a second release film is provided on the sealing member on the side thereof facing the lid portion of the package.

5

This allows for a simple and discrete protective package accommodating an ostomy sealing member, which a user can easily store and carry in his or her hand luggage. In order to protect the ostomy sealing member in the package and to facilitate easy removal from the package, a first release film is provided in the cavity between the tray portion and the sealing member. Furthermore, a second release film is provided on the sealing member on the side thereof facing the lid portion of the package to protect the adhesive ostomy sealing member from being contaminated by residuals of exudates from the ostomy or the like weakening its adhesive capabilities.

15 Preferably, a projection extends from the cavity configured for receipt in the opening. Furthermore, the cavity may have an outer substantially circular contour and that said projection is substantially circular corresponding to the opening of the sealing member so that said projection is provided non-concentric in the cavity. This ensures a tight and snugly fit of the package around the ostomy sealing member.

20

In a preferred embodiment, the package is made of a single polymeric material flexible sheet, which is vacuum-formed to the required package shape. Hereby, an inexpensive manufacturing of the package may be achieved.

25 In one preferred embodiment, the lid portion is provided with a peripheral outer contour for snap locking over a correspondingly shaped outer contour of the tray portion for releasably closing the package. In an alternative embodiment, the lid portion is formed with at least one snap locking closure protrusion, which cooperates with at least one corresponding closure cavity of the tray portion and so that the lid portion releasably closes the package around the sealing member by snap locking the at least one closure protrusion into the at least one closure cavity of the tray portion.

30

According to a second aspect of the present disclosure, there is provided an ostomy sealing member for sealing around a stoma in relation to an ostomy appliance, said sealing member comprising a hypo-allergenic, mouldable adhesive material, said sealing member having an annular periphery and an opening therein for receiving a stoma, wherein the opening is non-concentric with the periphery.

35

By providing such an ostomy sealing member with an off-centred stoma opening, the possibility of an easier and more flexible use of a sealing member may be achieved. The off-centred sealing ring provides for forming a customized convexity and adapting the sealing for

40

receiving an adhesive wafer for directly or indirectly securing an ostomy pouch to a person's skin depending on whether a one piece or a two piece ostomy system is used.

5 This ostomy sealing member is also advantageous in relation to a recently developed type of adhesive wafer which comprises a starter hole surrounded by a plurality of cutting guidelines for enabling the person to cut the hole into a desired aperture size, wherein the cutting guidelines substantially converge with the starter hole at an upper region of the hole. Such ostomy appliance is described in WO 2010/106039.

10 By the term "converge" should be understood that the annular cutting guidelines come close together to each other or to the hole at one region which may, but do not necessarily unite in a common point.

15 On the adhesive wafer the cutting guidelines substantially converge with the starter hole at a radial corresponding to the longitudinal direction of the pouch. Hereby, the "dead" volume in the head space in the top of the pouch may be minimized.

20 The sealing member of the present disclosure may advantageously be used in connection with such adhesive wafer with a starter hole off-centered towards the top, since the opening is off-centred from the substantially circular periphery. Accordingly, the sealing member has a varying radial width of material around the annular periphery. This is also advantageous since the sealing member according to the present disclosure may be oriented with the most and the least material corresponding to the unevenness of the surface of the skin around the stoma.

25 In a preferred embodiment of the sealing member, the material is mouldable so that the user can easily form the putty-like adhesive material even for users with limited dexterity in their fingers.

30 In one embodiment, in its form of origin the sealing member has substantially uniform thickness. This facilitates manufacturing of the sealing members. It is however realised that it may be advantageous in a variant to provide the sealing member with tapered peripheral edges at the outer periphery of the sealing member and/or the inner periphery thereof.

35 In order to facilitate the handling during unpacking and application of the sealing member, it is found advantageous to provide the member with a first and a second release liner on each side of the sealing member. Moreover, the sealing member is preferably accommodated in a sealing member cover preferably as a flexible tray-like structure having a cavity matching the shape of the sealing member and wherein the sealing member is accommodated with a
40 release liner enclosed between the sealing member and the cavity surface of the flexible tray cover.

The stoma receiving opening of the sealing member may be substantially circular. This facilitates the manufacture of the sealing member. However, it is realised that other shapes may also be suitable, such as an oval shape of the outer periphery and/or the inner periphery of the sealing member.

In the following the invention is described in more detail with reference to the accompanying drawings, in which:

Fig. 1 is a schematic top view of an ostomy sealing member according to the invention, fig. 2 is a perspective view thereof, figures 3 and 4 are side and top views of an ostomy sealing member package, figures 5 and 6 are side and top views of a multipack of ostomy sealing member packages, figures 7 and 8 are perspective top and bottom views of a sealing member package according to a first embodiment of the invention, fig. 9 is an exploded perspective view of a sealing member package according to this first embodiment of the invention, fig. 10 is a top view of a second embodiment of a sealing member package, fig. 11 is a front view of the package in fig. 10, fig. 12 is a side view of the package in fig. 10, fig. 13 is a detailed view of the hinge portion, fig. 14 is a perspective view of the sealing member package in fig. 10 in an open position, fig. 15 is a top view of a third embodiment of a sealing member package, fig. 16 is a front view of the package in fig. 15, fig. 17 is a side view of the package in fig. 15, fig. 18 is a detailed view of the hinge portion, and fig. 19 is a perspective view of the sealing member package in fig. 15 in an open position.

With reference to figures 1 and 2, an ostomy sealing member for providing a snugly and tight sealing around a stoma is shown. The sealing member 1 is disc-shaped with a substantially circular outer periphery 3 and with a substantially circular stoma opening 2, which is off-centred relative to the outer periphery 3. The disc-shaped sealing member 1 is preferably provided with a substantially uniform thickness. The sealing member 1 is made of an adhesive material which is bendable, stretchable and mouldable whereby the user is able to adapt the sealing member to the actual size and form of the stoma. A presently particularly suitable material is available under the trade name "Flextend M".

The sealing member 1 is preferably supplied in individual packages 6, such as shown in the various embodiments in the figures 3 to 19. Due to the adhesive material of the sealing member, the sealing member 1 is provided with a first, outermost release film 4 and a second, innermost release film 5 and accommodated in a tray 62 (see e.g. fig. 9) with an

annular cavity 6b wherein the sealing member 1 is accommodated and with a protrusion 6a supporting the stoma opening 2 of the sealing member 1. The annular cavity 6b is dimensioned so that the tray 62 and thereby also the package 6 snugly fits around the sealing member 1. A first embodiment of the package 6 is shown in figures 3 to 9. As shown in the figures, the cavity 6b is formed with a generally circular outer peripheral contour and an inner annular periphery formed by a protrusion 6a, which appears non-concentric relative to the outer periphery. After the sealing member 1 is fitted into the cavity 6b of the tray 62, a cover film (not shown) may be applied. As shown in figures 5 and 6, the packages 6 may be stacked in for instance two stacks and wrapped or boxed together. As shown in the exploded view in fig. 9, the ostomy sealing member 1 is provided with a top and bottom release liner 4, 5 on each side of the sealing member 1. The second release liner 5 is provided with a gripping tab extending from the outer periphery to facilitate gripping and thereby removal from the tray. The first release liner 4 is also provided with a gripping tab for easy removal so as to expose the adhesive surface of the sealing member once the sealing member has been removed from the package 6.

In figures 10 to 14 and figures 15 to 19, respectively, two other embodiments of a package for an ostomy sealing member are shown.

With reference to the figures 10-14, the package 6 includes a tray portion 62 and a lid portion 61 which are integrally formed with a hinge portion 63 there between. The tray portion 62 is provided with the annular cavity 6b and the protrusion 6a for closely fitting the sealing member 1 in the cavity 6b. In this embodiment, the lid portion 61 is formed so that it narrowly circumscribes the outer contour of the tray portion 62 and so that the lid portion 61 releasably closes the package around the sealing member 1 by snap locking around the tray portion 62. Grip portions 61a, 62a are provided on both the lid and the tray portions 61, 62 which are shaped for easy gripping in order to open the package 6.

The lid portion 61, tray portion 62, and the hinge portion 63 are integrally formed for instance by blow moulding of a plastic film or injection moulding the package portions from a plastic material.

With reference to the figures 15-19, the package 6 like the embodiment above includes a tray portion 62 and a lid portion 61 which are integrally formed with a hinge portion 63 there between. The lid portion 61, tray portion 62, and the hinge portion 63 are integrally formed for instance by vacuum-forming or blow moulding of a plastic film or injection moulding the package portions from a plastic material. The tray portion 62 is provided with the annular cavity 6b and the protrusion 6a for closely fitting the sealing member 1 in the cavity 6b.

However in this embodiment, the lid portion 61 is formed with at least one snap locking closure protrusion 61b which cooperates with corresponding closure cavity 62b of the tray

portion 62 and so that the lid portion 61 releasably closes the package around the sealing member 1 by snap locking the closure protrusion 61b into the closure cavity 62b of the tray portion 62. Grip portions 61a, 62a are provided on both the lid and the tray portions 61, 62 which are shaped for easy gripping in order to open the package 6.

Claims

1. A package accommodating an ostomy sealing member for sealing around a stoma in relation to an ostomy appliance,
- 5 said ostomy sealing member comprising a mouldable adhesive material, said sealing member having an annular periphery and an opening therein for receiving a stoma, wherein
- the ostomy sealing member is accommodated in a tray portion having a cavity dimensioned
- 10 for snugly receiving the ostomy sealing member and which is integrally formed with a lid portion for removably closing the tray and with a hinge portion between said tray and said lid portions, and wherein
- a first release film is provided in the cavity between the tray portion and the sealing member and wherein
- 15 a second release film is provided on the sealing member on the side thereof facing the lid portion of the package.
2. A package according to claim 1, wherein a projection extends from the cavity configured for receipt in the opening.
- 20 3. A package according to claim 2, wherein the cavity has an outer substantially circular contour and that said projection is substantially circular corresponding to the opening of the sealing member so that said projection is provided non-concentric in the cavity.
- 25 4. A package according to any of the preceding claims, wherein the package is made of a single polymeric material flexible sheet, which is vacuum-formed to the required package shape.
- 30 5. A package according to any of the preceding claims, wherein the lid portion is provided with a peripheral outer contour for snap locking over a correspondingly shaped outer contour of the tray portion for releasably closing the package.
6. A package according to any of the preceding claims, wherein the lid portion is formed with at least one snap locking closure protrusion, which cooperates with at least one
- 35 corresponding closure cavity of the tray portion and so that the lid portion releasably closes the package around the sealing member by snap locking the at least one closure protrusion into the at least one closure cavity of the tray portion.
- 40 7. An ostomy sealing member for a package according to any of the preceding claims, said sealing member being adapted for sealing around a stoma in relation to an ostomy appliance, wherein said sealing member comprises a mouldable adhesive material, said

sealing member having an annular periphery and an opening therein for receiving a stoma, wherein the opening is non-concentric with the periphery.

5 8. An ostomy sealing member according to claim 3 and 7, wherein the opening is off-centred from the substantially circular periphery.

9. An ostomy sealing member according to any of the preceding claims, wherein the member has substantially uniform thickness.

10 10. An ostomy sealing member according to any of the preceding claims, wherein said sealing member is accommodated in a sealing member cover.

11. An ostomy sealing member according to any of the preceding claims, wherein the stoma receiving opening is substantially circular.

15

1/9




FIG. 1




FIG. 2

2/9




FIG. 3




FIG. 4



FIG. 5




FIG. 6

3/9




FIG. 7




FIG. 8

4/9




FIG. 9

5/9




FIG. 10




FIG. 11

6/9




FIG. 12




FIG. 13

7/9




FIG. 14




FIG. 15

8/9




FIG. 16




FIG. 17




FIG. 18

9/9




FIG. 19

INTERNATIONAL SEARCH REPORT

International application No
PCT/EP2012/064692

A. CLASSIFICATION OF SUBJECT MATTER

INV. A61F5/443 A61F5/445
ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

A61F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EP0-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 2007/134612 A1 (COLOPLAST AS [DK]; STROEBECH ESBEN [DK]; BACH ANDERS [DK]; CHRISTENSEN) 29 November 2007 (2007-11-29)	7-11
Y	abstract; figures	1,4-6
A	page 1, lines 6-10 page 4, lines 12-28 page 5, lines 14-24 page 11, line 23 - page 12, line 23	2,3
Y	EP 0 652 155 A1 (MECAPLASTIC [FR]) 10 May 1995 (1995-05-10)	1,4-6
A	abstract; figures	2,3,7-11
X	US 5 051 259 A (OLSEN HANS [DK] ET AL) 24 September 1991 (1991-09-24)	7-11
A	abstract; figures 5,8	1-6
	----- -/--	



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

25 October 2012

Date of mailing of the international search report

05/11/2012

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Lager, Johan

INTERNATIONAL SEARCH REPORT

International application No
PCT/EP2012/064692

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 98/17212 A1 (COLOPLAST AS [DK]; NIELSEN INGER MANN [DK]; OLSEN ESKIL HOEJLAND [DK];) 30 April 1998 (1998-04-30) abstract; claims; figures -----	7-11
A	GB 2 152 387 A (HOLLISTER INC) 7 August 1985 (1985-08-07) abstract; figures 1,2,9 -----	7-11

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/EP2012/064692

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 2007134612 A1	29-11-2007	AT 502611 T AU 2007252109 A1 BR PI0712259 A2 CA 2653088 A1 CN 101448472 A EP 2029069 A1 ES 2362939 T3 JP 2009537263 A RU 2008151158 A US 2009148661 A1 WO 2007134612 A1	15-04-2011 29-11-2007 17-01-2012 29-11-2007 03-06-2009 04-03-2009 15-07-2011 29-10-2009 27-06-2010 11-06-2009 29-11-2007
EP 0652155 A1	10-05-1995	DE 69416933 D1 DE 69416933 T2 EP 0652155 A1 ES 2131651 T3 FR 2712253 A1 US 5603203 A	15-04-1999 15-02-2001 10-05-1995 01-08-1999 19-05-1995 18-02-1997
US 5051259 A	24-09-1991	AT 80992 T AU 608408 B2 CA 1323270 C DE 3875112 T2 DK 657187 A EP 0345331 A1 ES 2009459 A6 IE 61425 B1 JP 2752207 B2 JP H02502884 A RU 2060035 C1 US 5051259 A WO 8905619 A1	15-10-1992 28-03-1991 19-10-1993 15-04-1993 16-06-1989 13-12-1989 16-09-1989 02-11-1994 18-05-1998 13-09-1990 20-05-1996 24-09-1991 29-06-1989
WO 9817212 A1	30-04-1998	AT 320779 T AU 721675 B2 AU 4616397 A CA 2269575 A1 CN 1233945 A DE 69735550 T2 EP 0998247 A1 ES 2260801 T3 JP 4584360 B2 JP 2001502570 A NO 991905 A US 2003004477 A1 WO 9817212 A1	15-04-2006 13-07-2000 15-05-1998 30-04-1998 03-11-1999 28-12-2006 10-05-2000 01-11-2006 17-11-2010 27-02-2001 22-06-1999 02-01-2003 30-04-1998
GB 2152387 A	07-08-1985	AU 559535 B2 AU 1199883 A CA 1190823 A1 DE 3309083 A1 DK 102883 A ES 279833 U FR 2523435 A1 GB 2116849 A GB 2152387 A HK 52087 A HK 83087 A	12-03-1987 22-09-1983 23-07-1985 22-09-1983 17-09-1983 16-11-1984 23-09-1983 05-10-1983 07-08-1985 10-07-1987 13-11-1987

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/EP2012/064692

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
		IE 53994 B1	10-05-1989
		JP 1500596 C	28-06-1989
		JP 58165843 A	30-09-1983
		JP 63052900 B	20-10-1988
		SE 454238 B	18-04-1988
		SE 8301349 A	17-09-1983
		US 4445898 A	01-05-1984
