



US010874487B2

(12) **United States Patent**
Phan et al.

(10) **Patent No.:** **US 10,874,487 B2**

(45) **Date of Patent:** ***Dec. 29, 2020**

(54) **SYSTEMS AND METHODS FOR
FABRICATING A DENTAL TEMPLATE**

(71) Applicant: **ALIGN TECHNOLOGY, INC.**, San Jose, CA (US)

(72) Inventors: **Loc X. Phan**, San Jose, CA (US);
Peter G. Knopp, Palo Alto, CA (US);
Eric E. Kuo, Foster City, CA (US);
Amir Abolfathi, Woodside, CA (US);
Huafeng Wen, Redwood Shores, CA (US)

(73) Assignee: **ALIGN TECHNOLOGY, INC.**, San Jose, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 332 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **15/216,171**

(22) Filed: **Jul. 21, 2016**

(65) **Prior Publication Data**

US 2016/0324601 A1 Nov. 10, 2016

Related U.S. Application Data

(63) Continuation of application No. 14/931,681, filed on Nov. 3, 2015, now Pat. No. 9,433,479, which is a (Continued)

(51) **Int. Cl.**

A61C 7/14 (2006.01)
A61C 7/00 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC **A61C 7/146** (2013.01); **A61C 7/002** (2013.01); **A61C 13/0004** (2013.01); (Continued)

(58) **Field of Classification Search**

CPC **A61C 7/146**; **A61C 7/002**; **A61C 13/0004**; **B29C 64/135**

(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,467,432 A 4/1949 Kesling
3,407,500 A 10/1968 Kesling
(Continued)

FOREIGN PATENT DOCUMENTS

AU 3031677 A 5/1979
AU 517102 B2 7/1981
(Continued)

OTHER PUBLICATIONS

AADR. American Association for Dental Research, Summary of Activities, Mar. 20-23, 1980, Los Angeles, CA, p. 195.

(Continued)


Primary Examiner — Yogesh P Patel

(74) *Attorney, Agent, or Firm* — Wilson Sonsini Goodrich & Rosati

(57) **ABSTRACT**

A dental template to position an object on a patient's tooth includes digitizing the patient's tooth; adding virtual objects to predetermined locations on the digitized tooth; and fabricating the dental template to locate the object on the patient's tooth. The template can be used for etching or for positioning brackets on teeth.

8 Claims, 5 Drawing Sheets



Related U.S. Application Data

continuation of application No. 14/268,976, filed on May 2, 2014, now Pat. No. 9,204,942, which is a continuation of application No. 13/620,209, filed on Sep. 14, 2012, now Pat. No. 8,734,149, which is a continuation of application No. 11/297,129, filed on Dec. 7, 2005, now Pat. No. 8,496,473, which is a continuation of application No. 10/870,808, filed on Jun. 17, 2004, now Pat. No. 7,056,115, which is a continuation of application No. 10/375,223, filed on Feb. 26, 2003, now abandoned.

(51) **Int. Cl.**

A61C 13/00 (2006.01)
B33Y 80/00 (2015.01)
B33Y 50/02 (2015.01)
B29C 64/135 (2017.01)
B29L 31/00 (2006.01)

(52) **U.S. Cl.**

CPC **B33Y 50/02** (2014.12); **B33Y 80/00** (2014.12); *B29C 64/135* (2017.08); *B29L 2031/753* (2013.01); *Y10T 29/49568* (2015.01)

(58) **Field of Classification Search**

USPC 433/8–24
 See application file for complete search history.

(56)

References Cited

U.S. PATENT DOCUMENTS

3,600,808 A	8/1971	James	4,798,534 A	1/1989	Breads
3,660,900 A	5/1972	Lawrence	4,812,118 A	3/1989	Creekmore
3,683,502 A	8/1972	Melvin	4,836,778 A	6/1989	Baumrind et al.
3,738,005 A	6/1973	Cohen et al.	4,837,732 A	6/1989	Brandestini et al.
3,848,335 A	11/1974	Bergersen	4,850,864 A	7/1989	Diamond
3,860,803 A	1/1975	Levine	4,850,865 A	7/1989	Napolitano
3,916,526 A	11/1975	Schudy	4,856,991 A	8/1989	Breads et al.
3,922,786 A	12/1975	Lavin	4,877,398 A	10/1989	Kesling
3,949,478 A	4/1976	Schinhammer	4,880,380 A	11/1989	Martz
3,950,851 A	4/1976	Bergersen	4,889,238 A	12/1989	Batchelor
3,983,628 A	10/1976	Acevedo	4,890,608 A	1/1990	Steer
4,014,096 A	3/1977	Dellinger	4,935,635 A	6/1990	O'Harra
4,183,141 A	1/1980	Dellinger et al.	4,936,862 A	6/1990	Walker et al.
4,195,046 A	3/1980	Kesling	4,937,928 A	7/1990	Van Der Zel
4,253,828 A	3/1981	Coles et al.	4,941,826 A	7/1990	Loran et al.
4,324,546 A	4/1982	Heitlinger et al.	4,964,770 A	10/1990	Steinbichler et al.
4,324,547 A	4/1982	Arcan et al.	4,975,052 A	12/1990	Spencer et al.
4,348,178 A	9/1982	Kurz	4,983,334 A	1/1991	Adell
4,360,341 A	11/1982	Dellinger	5,011,405 A	4/1991	Lemchen
4,368,040 A *	1/1983	Weissman A61C 9/0006 433/223	5,015,180 A	5/1991	Randklev
4,478,580 A	10/1984	Barrut	5,017,133 A	5/1991	Miura
4,500,294 A	2/1985	Lewis	5,027,281 A	6/1991	Rekow et al.
4,501,554 A	2/1985	Hickham	5,035,613 A	7/1991	Breads et al.
4,504,225 A	3/1985	Yoshii	5,055,039 A	10/1991	Abbatte et al.
4,505,673 A	3/1985	Yoshii	5,059,118 A	10/1991	Breads et al.
4,526,540 A	7/1985	Dellinger	5,078,599 A	1/1992	Eenboom et al.
4,551,096 A	11/1985	Dellinger	5,100,316 A	3/1992	Wildman
4,575,330 A	3/1986	Hull	5,121,333 A	6/1992	Riley et al.
4,575,805 A	3/1986	Moermann et al.	5,125,832 A	6/1992	Kesling
4,591,341 A	5/1986	Andrews	5,128,870 A	7/1992	Erdman et al.
4,609,349 A	9/1986	Cain	5,130,064 A	7/1992	Smalley et al.
4,611,288 A	9/1986	Duret et al.	5,131,843 A	7/1992	Hilgers et al.
4,634,377 A	1/1987	Behrend	5,131,844 A	7/1992	Marinaccio et al.
4,656,860 A	4/1987	Orthuber et al.	5,139,419 A	8/1992	Andreiko et al.
4,657,508 A	4/1987	Dellinger	5,144,339 A	9/1992	Ohashi et al.
4,663,720 A	5/1987	Duret et al.	5,145,364 A	9/1992	Martz et al.
4,664,626 A	5/1987	Kesling	5,172,809 A	12/1992	Jacobs et al.
4,676,747 A	6/1987	Kesling	5,176,517 A	1/1993	Truax
4,742,464 A	5/1988	Duret et al.	5,184,306 A	2/1993	Erdman et al.
4,755,139 A	7/1988	Abbatte et al.	5,186,623 A *	2/1993	Breads A61C 7/08 433/214
4,763,791 A	8/1988	Halverson et al.	5,257,203 A	10/1993	Riley et al.
4,793,803 A	12/1988	Martz	5,273,429 A	12/1993	Rekow et al.
			5,278,756 A	1/1994	Lemchen et al.
			5,328,362 A	7/1994	Watson et al.
			5,338,198 A	8/1994	Wu et al.
			5,340,309 A	8/1994	Robertson
			5,342,202 A	8/1994	Deshayes
			5,354,199 A	10/1994	Jacobs et al.
			5,368,478 A	11/1994	Andreiko et al.
			5,372,502 A	12/1994	Massen et al.
			5,382,164 A	1/1995	Stern
			5,395,238 A	3/1995	Andreiko et al.
			5,429,229 A	7/1995	Chester et al.
			5,431,562 A	7/1995	Andreiko et al.
			5,440,326 A	8/1995	Quinn
			5,440,496 A	8/1995	Andersson et al.
			5,447,432 A	9/1995	Andreiko et al.
			5,452,219 A	9/1995	Dehoff et al.
			5,454,717 A	10/1995	Andreiko et al.
			5,456,600 A	10/1995	Andreiko et al.
			5,474,448 A	12/1995	Andreiko et al.
			RE35,169 E	3/1996	Lemchen et al.
			5,518,397 A	5/1996	Andreiko et al.
			5,528,735 A	6/1996	Strasnick et al.
			5,533,895 A	7/1996	Andreiko et al.
			5,542,842 A	8/1996	Andreiko et al.
			5,549,476 A	8/1996	Stern
			5,562,448 A	10/1996	Mushabac
			5,587,912 A	12/1996	Andersson et al.
			5,605,459 A	2/1997	Kuroda et al.
			5,607,305 A	3/1997	Andersson et al.
			5,614,075 A	3/1997	Andre, Sr.
			5,621,648 A	4/1997	Crump
			5,645,420 A	7/1997	Bergersen
			5,645,421 A	7/1997	Slootsky
			5,655,653 A	8/1997	Chester
			5,683,243 A	11/1997	Andreiko et al.

(56)

References Cited

FOREIGN PATENT DOCUMENTS

WO	WO-02067186	A2	8/2002
WO	WO-2006065955	A2	6/2006
WO	WO-2007101245	A2	9/2007
WO	WO-2007103377	A2	9/2007

OTHER PUBLICATIONS

- Alcaniz, et al., "An Advanced System for the Simulation and Planning of Orthodontic Treatments," Karl Heinz Hohne and Ron Kikinis (eds.), *Visualization in Biomedical Computing*, 4th Intl. Conf., VBC '96, Hamburg, Germany, Sep. 22-25, 1996, Springer-Verlag, pp. 511-520.
- Alexander et al., "The DigiGraph Work Station Part 2 Clinical Management," *JCO*, pp. 402-407 (Jul. 1990).
- Altschuler, "3D Mapping of Maxillo-Facial Prosthesis," *AADR Abstract #607*, 2 pages total, (1980).
- Altschuler et al., "Analysis of 3-D Data for Comparative 3-D Serial Growth Pattern Studies of Oral-Facial Structures," *AADR Abstracts, Program and Abstracts of Papers, 57th General Session, IADR HP Annual Session, Mar. 29, 1979—Apr. 1, 1979, New Orleans Marriott, Journal of Dental Research*, vol. 58, Jan. 1979, Special Issue A, p. 221.
- Altschuler et al., "Laser Electro-Optic System for Rapid Three-Dimensional (3D) Topographic Mapping of Surfaces," *Optical Engineering*, 20(6):953-961 (1981).
- Altschuler et al., "Measuring Surfaces Space-Coded by a Laser-Projected Dot Matrix," *SPIE Imaging Applications for Automated Industrial Inspection and Assembly*, vol. 182, p. 187-191 (1979).
- Andersson et al., "Clinical Results with Titanium Crowns Fabricated with Machine Duplication and Spark Erosion," *Acta. Odontol. Scand.*, 47:279-286 (1989).
- Andrews, *The Six Keys to Optimal Occlusion Straight Wire*, Chapter 3, pp. 13-24 (1989).
- Bartels, et al., *An Introduction to Splines for Use in Computer Graphics and Geometric Modeling*, Morgan Kaufmann Publishers, pp. 422-425 (1987).
- Baumrind, "A System for Craniofacial Mapping Through the Integration of Data from Stereo X-Ray Films and Stereo Photographs," an invited paper submitted to the 1975 American Society of Photogram Symposium on Close-Range Photogram Systems, University of Ill., Aug. 26-30, 1975, pp. 142-166.
- Baumrind et al., "A Stereophotogrammetric System for the Detection of Prosthesis Loosening in Total Hip Arthroplasty," *NATO Symposium on Applications of Human Biostereometrics*, Jul. 9-13, 1978, *SPIE*, vol. 166, pp. 112-123.
- Baumrind et al., "Mapping the Skull in 3-D," reprinted from *J. Calif. Dent. Assoc.*, 48(2), 11 pages total, (1972 Fall Issue).
- Baumrind, "Integrated Three-Dimensional Craniofacial Mapping: Background, Principles, and Perspectives," *Semin. in Orthod.*, 7(4):223-232 (Dec. 2001).
- Begole et al., "A Computer System for the Analysis of Dental Casts," *The Angle Orthod.*, 51(3):253-259 (Jul. 1981).
- Bernard et al., "Computerized Diagnosis in Orthodontics for Epidemiological Studies: A Progress Report," *Abstract, J. Dental Res. Special Issue*, vol. 67, p. 169, paper presented at International Association for Dental Research 66th General Session, Mar. 9-13, 1988, Montreal, Canada.
- Bhatia et al., "A Computer-Aided Design for Orthognathic Surgery," *Br. J. Oral Maxillofac. Surg.*, 22:237-253 (1984).
- Biggerstaff, "Computerized Diagnostic Setups and Simulations," *Angle Orthod.*, 40(1):28-36 (Jan. 1970).
- Biggerstaff et al., "Computerized Analysis of Occlusion in the Postcanine Dentition," *Am. J. Orthod.*, 61(3): 245-254 (Mar. 1972).
- Biostar Operation & Training Manual. Great Lakes Orthodontics, Ltd. 199 Fire Tower Drive, Tonawanda, New York. 14150-5890, 20 pages total (1990).
- Blu, et al., "Linear interpolation revitalized", *IEEE Trans. Image Proc.*, 13(5):710-719 (May 2004).
- Bourke, "Coordinate System Transformation," (Jun. 1996), p. 1, retrieved from the Internet Nov. 5, 2004, URL < <http://astronomy.swin.edu.au/~pbourke/projection/coords>>.
- Boyd et al., "Three Dimensional Diagnosis and Orthodontic Treatment of Complex Malocclusions With the Invisalipn Appliance," *Semin. Orthod.*, 7(4):274-293 (Dec. 2001).
- Brandestini et al., "Computer Machined Ceramic Inlays: In Vitro Marginal Adaptation," *J. Dent. Res. Special Issue, Abstract 305*, vol. 64, p. 208 (1985).
- Brook et al., "An Image Analysis System for the Determination of Tooth Dimensions from Study Casts: Comparison with Manual Measurements of Mesio-distal Diameter," *J. Dent. Res.*, 65(3):428-431 (Mar. 1986).
- Burstone et al., Precision Adjustment of the Transpalatal Lingual Arch: Computer Arch Form in Predetermination, *Am. Journal of Orthodontics*, vol. 79, No. 2 (Feb. 1981), pp. 115-133.
- Burstone (interview), "Dr. Charles J. Burstone on The Uses of the Computer in Orthodontic Practice (Part 1)," *J. Clin. Orthod.*, 13(7):442-453 (Jul. 1979).
- Burstone (interview), "Dr. Charles J. Burstone on The Uses of the Computer in Orthodontic Practice (Part 2)," *J. Clin. Orthod.*, 13(8):539-551 (Aug. 1979).
- Cardinal Industrial Finishes, Powder Coatings information posted at < <http://www.cardinalpaint.com>> on Aug. 25, 2000, 2 pages.
- Carnaghan, "An Alternative to Holograms for the Portrayal of Human Teeth," 4th Intl. Conf. on Holographic Systems, Components and Applications, Sep. 15, 1993, pp. 228-231.
- Chaconas et al., "The DigiGraph Work Station, Part 1, Basic Concepts," *JCO*, pp. 360-367 (Jun. 1990).
- Chafetz et al., "Subsidence of the Femoral Prosthesis, A Stereophotogrammetric Evaluation," *Clin. Orthop. Relat. Res.*, No. 201, pp. 60-67 (Dec. 1985).
- Chiappone, (1980). Constructing the Gnathologic Setup and Positioner, *J. Clin. Orthod.*, vol. 14, pp. 121-133.
- Cottingham, (1969). Gnathologic Clear Plastic Positioner, *Am. J. Orthod.*, vol. 55, pp. 23-31.
- Crawford, "CAD/CAM in the Dental Office: Does It Work?," *Canadian Dental Journal*, vol. 57, No. 2, pp. 121-123 (Feb. 1991).
- Crawford, "Computers in Dentistry: Part 1 CAD/CAM: The Computer Moves Chairside, Part 2 F. Duret—A Man with a Vision, Part 3 The Computer Gives New Vision—Literally, Part 4 Bytes 'N Bites—The Computer Moves from the Front Desk to the Operatory," *Canadian Dental Journal*, vol. 54 (9), pp. 661-666 (1988).
- Crooks, "CAD/CAM Comes to USC," *USC Dentistry*, pp. 14-17 (Spring 1990).
- Cureton, Correcting Malaligned Mandibular Incisors with Removable Retainers, *J. Clin. Orthod.*, vol. 30, No. 7 (1996) pp. 390-395.
- Curry et al., "Integrated Three-Dimensional Craniofacial Mapping at the Craniofacial Research Instrumentation Laboratory/University of the Pacific," *Semin. Orthod.*, 7(4):258-265 (Dec. 2001).
- Cutting et al., "Three-Dimensional Computer-Assisted Design of Craniofacial Surgical Procedures: Optimization and Interaction with Cephalometric and CT-Based Models," *Plast. 77(6):877-885* (Jun. 1986).
- DCS Dental AG, "The CAD/CAM 'DCS Titan System' for Production of Crowns/Bridges," *DSC Production AG*, pp. 1-7 (Jan. 1992).
- Definition for gingiva. Dictionary.com pp. 1-3. Retrieved from the internet Nov. 5, 2004 < <http://reference.com/search/search?q=gingiva>>.
- Defranco et al., "Three-Dimensional Large Displacement Analysis of Orthodontic Appliances," *J. Biomechanics*, 9:793-801 (1976).
- Dental Institute University of Zurich Switzerland, Program for International Symposium JD on Computer Restorations: State of the Art of the CEREC-Method, May 1991, 2 pages total.
- Dentrac Corporation, Dentrac document, pp. 4-13 (1992).
- Dent-X posted on Sep. 24, 1998 at < <http://www.dent-x.com/DentSim.htm>>, 6 pages.
- Doyle, "Digital Dentistry," *Computer Graphics World*, pp. 50-52, 54 (Oct. 2000).
- DuraClear™ product information, Allesee Orthodontic Appliances-Pro Lab, 1 page (1997).

(56)

References Cited

OTHER PUBLICATIONS

- Duret et al., "CAD/CAM Imaging in Dentistry," *Curr. Opin. Dent.*, 1:150-154 (1991).
- Duret et al., "CAD-CAM in Dentistry," *J. Am. Dent. Assoc.* 117:715-720 (Nov. 1988).
- Duret, "The Dental CAD/CAM, General Description of the Project," Henson International Product Brochure, 18 pages total, Jan. 1986.
- Duret, "Vers Une Prothese Informatisee," (English translation attached), *Tonus*, vol. 75, pp. 55-57 (Nov. 15, 1985).
- Economides, "The Microcomputer in the Orthodontic Office," *JCO*, pp. 767-772 (Nov. 1979).
- Elsasser, Some Observations on the History and Uses of the Kesling Positioner, *Am. J. Orthod.* (1950) 36:368-374.
- English translation of Japanese Laid-Open Publication No. 63-11148 to inventor T. Ozukuri (Laid-Open on Jan. 18, 1998) pp. 1-7.
- Felton et al., "A Computerized Analysis of the Shape and Stability of Mandibular Arch Form," *Am. J. Orthod. Dentofacial Orthop.*, 92(6):478-483 (Dec. 1987).
- Friede et al., "Accuracy of Cephalometric Prediction in Orthognathic Surgery," *Abstract of Papers, J. Dent. Res.*, 70:754-760 (1987).
- Futterling et al., "Automated Finite Element Modeling of a Human Mandible with Dental Implants," *JS WSCG '98 -Conference Program*, retrieved from the Internet < http://wscg.zcu.cz/wscg98/papers98/Strasser_98.pdf>, 8 pages.
- Gao et al., "3-D element Generation for Multi-Connected Complex Dental and Mandibular Structure," *Proc. Intl Workshop on Medical Imaging and Augmented Reality*, pp. 267-271 (Jun. 12, 2001).
- Gim-Allident Deutschland, "Das DUX System: Die Technik," 2 pages total (2002).
- Gottlieb et al., "JCO Interviews Dr. James A. McNamara, Jr., on the Frankel Appliance: Part 2: Clinical 1-1 Management," *J. Clin. Orthod.*, 16(6):390-407 (Jun. 1982).
- Grayson, "New Methods for Three Dimensional Analysis of Craniofacial Deformity, Symposium: JW Computerized Facial Imaging in Oral and Maxillofacial Surgery," *AAOMS*, 3 pages total, (Sep. 13, 1990).
- Guess et al., "Computer Treatment Estimates In Orthodontics and Orthognathic Surgery," *JCO*, pp. 262-28 (Apr. 1989).
- Heaven et al., "Computer-Based Image Analysis of Artificial Root Surface Caries," *Abstracts of Papers, J. Dent. Res.*, 70:528 (Apr. 17-21, 1991).
- Highbeam Research, "Simulating Stress Put on Jaw," *Tooling & Production [online]*, Nov. 1996, n. pp. 1-2, retrieved from the Internet on Nov. 5, 2004, URL <http://static.highbeam.com/t/toolingampproduction/november011996/simulatingstressputonfa...>
- Hikage, "Integrated Orthodontic Management System for Virtual Three-Dimensional Computer Graphic Simulation and Optical Video Image Database for Diagnosis and Treatment Planning", *Journal of Japan KA Orthodontic Society*, Feb. 1987, English translation, pp. 1-38, Japanese version, 46(2), pp. 248-269 (60 pages total).
- Hoffmann, et al., "Role of Cephalometry for Planning of Jaw Orthopedics and Jaw Surgery Procedures," (Article Summary in English, article in German), *Informatbnen*, pp. 375-396 (Mar. 1991).
- Hojjatie et al., "Three-Dimensional Finite Element Analysis of Glass-Ceramic Dental Crowns," *J. Biomech.*, 23(11):1157-1166 (1990).
- Huckins, "CAD-CAM Generated Mandibular Model Prototype from MRI Data," *AAOMS*, p. 96 (1999).
- Important Tip About Wearing the Red White & Blue Active Clear Retainer System, *Allesee Orthodontic Appliances-Pro Lab*, 1 page (1998).
- JCO Interviews, Craig Andreiko, DDS, MS on the Elan and Orthos Systems, *JCO*, pp. 459-468 (Aug. 1994).
- JCO Interviews, Dr. Homer W. Phillips on Computers in Orthodontic Practice, Part 2, *JCO*, 1997; 1983:819-831.
- Jerrold, "The Problem, Electronic Data Transmission and the Law," *AJO-DO*, pp. 478-479 (Apr. 1988).
- Jones et al., "An Assessment of the Fit of a Parabolic Curve to Pre- and Post-Treatment Dental Arches," *Br. J. Orthod.*, 16:85-93 (1989).
- JP Faber et al., "Computerized Interactive Orthodontic Treatment Planning," *Am. J. Orthod.*, 73(1):36-46 (Jan. 1978).
- Kamada et al., *Case Reports On Tooth Positioners Using LTV Vinyl Silicone Rubber*, J. Nihon University School of Dentistry (1984) 26(1): 11-29.
- Kamada et al., *Construction of Tooth Positioners with LTV Vinyl Silicone Rubber and Some Case KJ Reports*, J. Nihon University School of Dentistry (1982) 24(1):1-27.
- Kanazawa et al., "Three-Dimensional Measurements of the Occlusal Surfaces of Upper Molars in a Dutch Population," *J. Dent Res.*, 63(11):1298-1301 (Nov. 1984).
- Kesling, *Coordinating the Predetermined Pattern and Tooth Positioner with Conventional Treatment*, *KN Am. J. Orthod. Oral Surg.* (1946) 32:285-293.
- Kesling et al., *The Philosophy of the Tooth Positioning Appliance*, *American Journal of Orthodontics and Oral surgery*. 1945; 31:297-304.
- Kleeman et al., *The Speed Positioner*, *J. Clin. Orthod.* (1996) 30:673-680.
- Kochanek, "Interpolating Splines with Local Tension, Continuity and Bias Control," *Computer Graphics*, 18(3):33-41 (Jul. 1984).
- KM *Oral Surgery* (1945) 31 :297-30.
- Kunii et al., "Articulation Simulation for an Intelligent Dental Care System," *Displays* 15:181-188 (1994).
- Kuroda et al., *Three-Dimensional Dental Cast Analyzing System Using Laser Scanning*, *Am. J. Orthod. Dentofac. Orthop.* (1996) 110:365-369.
- Laurendeau, et al., "A Computer-Vision Technique for the Acquisition and Processing of 3-D Profiles of 7 KR Dental Imprints: An Application in Orthodontics," *IEEE Transactions on Medical Imaging*, 10(3):453-461 (Sep. 1991).
- Leinfelder, et al., "A New Method for Generating Ceramic Restorations: a CAD-CAM System," *J. Am. 1-1 Dent. Assoc.*, 118(6):703-707 (Jun. 1989).
- Manetti, et al., "Computer-Aided Cefalometry and New Mechanics in Orthodontics," (Article Summary in English, article in German), *Fortschr Kieferorthop.* 44, 370-376 (Nr. 5), 1983.
- McCann, "Inside the Ada," *J. Amer. Dent. Assoc.*, 118:286-294 (Mar. 1989).
- McNamara et al., "Invisible Retainers," *J. Cfin. Orthod.*, pp. 570-578 (Aug. 1985).
- McNamara et al., *Orthodontic and Orthopedic Treatment in the Mixed Dentition*, Needham Press, pp. 347-353 (Jan. 1993).
- Moermann et al., "Computer Machined Adhesive Porcelain Inlays: Margin Adaptation after Fatigue Stress," *IADR Abstract* 339, *J. Dent. Res.*, 66(a):763 (1987).
- Moles, "Correcting Mild Malalignments—As Easy As One, Two, Three," *AOA/Pro Corner*, vol. 11, No. 1, 2 pages (2002).
- Mormann et al., "Marginale Adaptation von adhasiven Porzellaninlays in vitro," *Separatdruck aus: Schweiz. Mschr. Zahnmed.* 95: 1118-1129, 1985.
- Nahoum, "The Vacuum Formed Dental Contour Appliance," *N. Y. State Dent. J.*, 30(9):385-390 (Nov. 1964).
- Nash, "CEREC CAD/CAM Inlays: Aesthetics and Durability in a Single Appointment," *Dent. Today*, 9(8):20, 22-23 (Oct. 1990).
- Nishiyama et al., "A New Construction of Tooth Repositioner by LTV Vinyl Silicone Rubber," *J. Nihon Univ. Sch. Dent.*, 19(2):93-102 (1977).
- Paul et al., "Digital Documentation of Individual Human Jaw and Tooth Forms for Applications in Orthodontics, Oral Surgery and Forensic Medicine" *Proc. Of the 24th Annual Conf. of the IEEE Industrial Electronics Society (IECON '98)*, Sep. 4, 1998, pp. 2415-2418.
- Pinkham, "Foolish Concept Propels Technology," *Dentist*, 3 pages total, Jan./Feb. 1989.
- Pinkham, "Inventor's CAD/CAM May Transform Dentistry," *Dentist*, 3 pages total, Sep. 1990.
- Ponitz, "Invisible Retainers," *Am. J. Orthod.*, 59(3):266-272 (Mar. 1971).
- Procera Research Projects, "Procera Research Projects 1993—Abstract Collection," pp. 3-7; 28 (1993).

(56)

References Cited

OTHER PUBLICATIONS

- Proffit et al., *Contemporary Orthodontics*, (Second Ed.), Chapter 15, Mosby Inc., pp. 470-533 (Oct. 1993).
- Raintree Essix & ARS Materials, Inc., Raintree Essix, Technical Magazine Table of contents and Essix Appliances, < <http://www.essix.com/magazine/default.html> > Aug. 13, 1997.
- Redmond et al., "Clinical Implications of Digital Orthodontics," *Am. J. Orthod. Dentofacial Orthop.*, 117(2):240-242 (2000).
- Rekow, "A Review of the Developments in Dental CAD/CAM Systems," (contains references to Japanese efforts and content of the papers of particular interest to the clinician are indicated with a one line summary of their content in the bibliography), *Curr. Opin. Dent.*, 2:25-33 (Jun. 1992).
- Rekow, "CAD/CAM in Dentistry: A Historical Perspective and View of the Future," *J. Can. Dent. Assoc.*, 58(4):283, 287-288 (Apr. 1992).
- Rekow, "Computer-Aided Design and Manufacturing in Dentistry: A Review of the State of the Art," *J. Prosthet. Dent.*, 58(4):512-516 (Oct. 1987).
- Rekow, "Dental CAD-CAM Systems: What is the State of the Art?," *J. Amer. Dent. Assoc.*, 122:43-48 1991.
- Rekow et al., "CAD/CAM for Dental Restorations—Some of the Curious Challenges," *IEEE Trans. Biomed. Eng.*, 38(4):314-318 (Apr. 1991).
- Rekow et al., "Comparison of Three Data Acquisition Techniques for 3-D Tooth Surface Mapping," *Annual International Conference of the IEEE Engineering in Medicine and Biology Society*, 13(1):344-345 1991.
- Rekow, "Feasibility of an Automated System for Production of Dental Restorations, Ph.D. Thesis," Univ. of Minnesota, 244 pages total, Nov. 1988.
- Richmond et al., "The Development of a 3D Cast Analysis System," *Br. J. Orthod.*, 13(1):53-54 (Jan. 1986).
- Richmond et al., "The Development of the PAR Index (Peer Assessment Rating): Reliability and Validity," *Eur. J. Orthod.*, 14:125-139 (1992).
- Richmond, "Recording The Dental Cast in Three Dimensions," *Am. J. Orthod. Dentofacial Orthop.*, 92(3):199-206 (Sep. 1987).
- Rudge, "Dental Arch Analysis: Arch Form, A Review of the Literature," *Eur. J. Orthod.*, 3(4):279-284 1981.
- Sakuda et al., "Integrated Information-Processing System in Clinical Orthodontics: An Approach with Use of a Computer Network System," *Am. J. Orthod. Dentofacial Orthop.*, 101(3): 210-220 (Mar. 1992).
- Schellhas et al., "Three-Dimensional Computed Tomography in Maxillofacial Surgical Planning," *Arch. Otolamp. Head Neck Sur*, 114:438-442 (Apr. 1988).
- Schroeder et al., Eds. *The Visual Toolkit*, Prentice Hall PTR, New Jersey (1998) Chapters 6, 8 & 9, (pp. 153-210,309-354, and 355-428, respectively).
- Shilliday, (1971). Minimizing finishing problems with the mini-positioner, *Am. J. Orthod.* 59:596-599.
- Siemens, "CEREC—Computer-Reconstruction," *High Tech in der Zahnmedizin*, 14 pages total (2004).
- Sinclair, "The Readers' Corner," *J. Clin. Orthod.*, 26(6):369-372 (Jun. 1992).
- Sirona Dental Systems GmbH, CEREC 3D, Manuel utiisiateur, Version 2.0X (in French), 2003,114 pages total.
- Stoll et al., "Computer-aided Technologies in Dentistry," (article summary in English, article in German), *Dtsch Zahna'rztl Z* 45, pp. 314-322 (1990).
- Sturman, "Interactive Keyframe Animation of 3-D Articulated Models," *Proceedings Graphics Interface '84*, May-Jun. 1984, pp. 35-40.
- The Choice Is Clear: Red, White & Blue . . . The Simple, Affordable, No-Braces Treatment, Allesee HI Orthodontic Appliances-Pro Lab product information for doctors. <http://ormco.com/aoa/applianceservices/RWB/doctorhtml> >, 5 pages (May 19, 2003).
- The Choice is Clear: Red, White & Blue . . . The Simple, Affordable, No-Braces Treatment, Allesee HJ Orthodontic Appliances-Pro Lab product information for patients, < <http://ormco.com/aoa/applianceservices/RWB/patients.html> >, 2 pages (May 19, 2003).
- The Choice Is Clear: Red, White & Blue . . . The Simple, Affordable, No-Braces Treatment, Allesee Orthodontic Appliances-Pro Lab product information, 6 pages (2003).
- The Red, White & Blue Way to Improve Your Smile!Allesee Orthodontic Appliances-Pro Lab product information for patients, 2 pages 1992.
- Truax L., "Truax Clasp-Less(TM) Appliance System," *Funct. Orthod.*, 9(5):22-4, 26-8 (Sep.-Oct. 1992).
- Tru-Tain Orthodontic & Dental Supplies, Product Brochure, Rochester, Minnesota 55902, 16 pages total (1996).
- U.S. Department of Commerce, National Technical Information Service, "Automated Crown Replication Using Solid Photography SM," Solid Photography Inc., Melville NY, Oct. 1977, 20 pages total.
- U.S. Department of Commerce, National Technical Information Service, "Holodontography: An Introduction to Dental Laser Holography," School of Aerospace Medicine Brooks AFB Tex, Mar. 1973, 37 pages total.
- U.S. Provisional Patent Application No. 60/050342, filed on Jun. 20, 1997, 41 pages total.
- Van Der Linden, "A New Method to Determine Tooth Positions and Dental Arch Dimensions," *J. Dent. Res.*, 51(4):1104 (Jul.-Aug. 1972).
- Van Der Linden et al., "Three-Dimensional Analysis of Dental Casts by Means of the Optocom," *J. Dent. Res.*, p. 1100 (Jul.-Aug. 1972).
- Van Der Zel, "Ceramic-Fused-to-Metal Restorations with a New CAD/CAM System," *Quintessence Int.*, 24(11):769-778 (1993).
- Varady et al., "Reverse Engineering Of Geometric Models—An Introduction," *Computer-Aided Design*, 29(4):255-268, 1997.
- Verstreken et al., "An Image-Guided Planning System for Endosseous Oral Implants," *IEEE Trans. Med. Imaging*, 17(5):842-852 (Oct. 1998).
- Warunek et al., Physical and Mechanical Properties of Elastomers in Orthodontic Positioners, *Am J. Orthod. Dentofac. Orthop*, vol. 95, No. 5, (May 1989) pp. 399-400.
- Warunek et al., Clinical Use of Silicone Elastomer Applicances, *JCO* (1989) XXIII(10):694-700.
- Wells, Application of the Positioner Appliance in Orthodontic Treatment, *Am. J. Orthodont.* (1970) 58:351-366.
- Williams, "Dentistry and CAD/CAM: Another French Revolution," *J. Dent. Practice Admin.*, pp. 2-5 (Jan./Mar. 1987).
- Williams, "The Switzerland and Minnesota Developments in CAD/CAM," *J. Dent. Practice Admin.*, pp. 50-55 (Apr./Jun. 1987).
- Wishan, "New Advances in Personal Computer Applications for Cephalometric Analysis, Growth Prediction, Surgical Treatment Planning and Imaging Processing," *Symposium: Computerized Facial Imaging in Oral and Maxillofacial Surgery Presented on Sep. 13, 1990.*
- WSCG'98—Conference Program, "The Sixth International Conference in Central Europe on Computer Graphics and Visualization '98," Feb. 9-13, 1998, pp. 1-7, retrieved from the Internet on Nov. 5, 2004, URL <<http://wscg.zcu.cz/wscg98/wscg98.h>>.
- Xia et al., "Three-Dimensional Virtual-Reality Surgical Planning and Soft-Tissue Prediction for Orthognathic Surgery," *IEEE Trans. Inf. Technol. Biomed.*, 5(2):97-107 (Jun. 2001).
- Yamamoto et al., "Optical Measurement of Dental Cast Profile and Application to Analysis of Three-Dimensional Tooth Movement in Orthodontics," *Front. Med. Biol. Eng.*, 1(2):119-130 (1988).
- Yamamoto et al., "Three-Dimensional Measurement of Dental Cast Profiles and Its Applications to Orthodontics," *Conf. Proc. IEEE Eng. Med. Biol. Soc.*, 12(5):2051-2053 (1990).
- Yamany et al., "A System for Human Jaw Modeling Using Intra-Oral Images," *Proc. of the 20th Annual Conf. of the IEEE Engineering in Medicine and Biology Society*, Nov. 1, 1998, vol. 2, pp. 563-566.
- Yoshii, "Research on a New Orthodontic Appliance: The Dynamic Positioner (D.P.); I. The D.P. Concept and Implementation of Transparent Silicone Resin (Orthocon)," *Nippon Dental Review*, 45:2:61-74 (Jun. 1980).

(56)

References Cited

OTHER PUBLICATIONS

- Yoshii, "Research on a New Orthodontic Appliance: the Dynamic Positioner (D.P.); II. The D.P. Manufacturing Procedure and Clinical Applications," *Nippon Dental Review*, 454:107-130 (Aug. 1980).
- Yoshii, "Research on a New Orthodontic Appliance: The Dynamic Positioner (D.P.); III. The General Concept of the D.P. Method and Its Therapeutic Effect, Part 1, Dental and Functional Reversed Occlusion Case Reports," *Nippon Dental Review*, 457:146-164 (Nov. 1980).
- Yoshii, "Research on a New Orthodontic Appliance: The Dynamic Positioner (D.P.); III.- The General Concept of the D.P. Method and Its Therapeutic Effect, Part 2. Skeletal Reversed Occlusion Case Reports," *Nippon Dental Review*, 458:112-129 (Dec. 1980).
- You May Be A Candidate For This Invisible No-Braces Treatment, Allesee Orthodontic Appliances-Pro Lab product information for patients, 2 pages (2002).
- Ackerman et al., An Evaluation of Dynamic Lip-Tooth Characteristics During Speech and Smile in Adolescents, *Angle Orthodontist*, vol. 74, No. 1, 43-50 (2004).
- Ackerman et al., Smile Analysis and Design in the Digital Era, *Journal of Clinical Orthodontics: JCO* 36(4):221-236, (May 2002).
- Ackerman et al., Soft Tissue Limitations in Orthodontics: Treatment Planning Guidelines, *Angle Orthodontist*, vol. 67, No. 5, 327-336 (1997).
- Basting et al., Comparative Study of Smile Analysis by Subjective and Computerized Methods, *Operative Dentistry*, 31-6, 652-659, (2006).
- Bell et al., Tridimensional Planning for Surgical/Orthodontic Treatment of Mandibular Excess, *Am. J. Orthod.*, 263-288, (Sep. 1981).
- Berland, "Anatomy of a smile makeover," *Dentistry IQ*, <<https://www.dentistryiq.com/clinical/restorative-cosmetic-and-whitening/article/16348488/anatomy-of-a-smile-makeover>>, last accessed on Oct. 29, 2019, 26 pages (Mar. 2003).
- Berland, "The Use of Smile Libraries for Cosmetic Dentistry," *Dental Tribune, Asia Pacific Edition*, 1-2, 16-18 (Mar. 2006).
- Chenin. et al., Orthodontic Treatment With a Series of Removable Appliances, *JADA*, vol. 134, No. 9, 1232-1239 (Sep. 2003).
- Davis, Nicholas C., Smile Design, *Dent Clin N Am* 51, 299-318, (2007).
- Garber, David A., The aesthetic smile: diagnosis and treatment, *Periodontol* 2000.; 11:18-28, (Jun. 1996).
- Gaylon, E., Aesthetic Lip Advancement, *The American Journal of Cosmetic Surgery* vol. 13, No. 3, 207-212 (1996).
- Gomez et al., Biometric Identification System by Lip Shape, In: *Proc. of Carnahan Conference on Security Technology*, pp. 39-42 (2002).
- Jacobs, Joe, Control of the Transverse Dimension With Surgery and Orthodontics, *American Journal of Orthodontics*, vol. 77 No. 3, 284-306, (Mar. 1980).
- Mackley, Ronald, An Evaluation of Smiles Before and After Orthodontic Treatment, *Angle Orthod.* 63(3):183-189, (1993 Fall).
- Maulik, Christopher M., Dynamic Smile Analysis in Young Adults, *SoDM Masters Theses.87*, https://opencommons.uconn.edu/sodm_masters/87, 83 pages (2005).
- Maulik et al., Dynamic Smile Analysis in Young Adults, *Am J Orthod. Dentofacial Orthop.* 132(3): p. 307-315, (2007).
- Modgil et al., Combining Biometric and Symbolic Models for Customized, Automated Prosthesis Design, *Artificial Intelligence in Medicine* Jul;25(3):227-245 (2002).
- Nanda et al., Three-Dimensional Facial Analysis Using a Video Imaging System, *Orthodontics, The Angle Orthod.*; 66(3):181-188 (1996).
- Naylor, Craig Kirkham, Esthetic Treatment Planning: The Grid Analysis System, *Journal of Esthetic and Restorative Dentistry*, vol. 14, No. 2, 76-84, (2002).
- Parekh et al., The Acceptability of Variations in Smile Arc and Buccal Corridor Space, *Orthod Craniofacial Res.* 10(1): 15-21 (2007).
- Peck, Sheldon, The Gingival Smile Line, *The Angle Orthod.*; 62(2):91-100 (1992).
- Pinho et al., Impact of Dental Asymmetries on the Perception of Smile Esthetics, *American Journal of Orthodontics and Dentofacial Orthopedics*, vol. 132, No. 6, 748-753 (2006).
- Romani et al., Evaluation of Horizontal and Vertical Differences in Facial Profiles by Orthodontists and Lay People, *The Angle Orthod.*; 63(3):175-182 (1993).
- Sarver, David M., The Importance of Incisor Positioning in the Esthetic Smile: The Smile Arc, *American Journal of Orthodontics and Dentofacial Orthopedics*, vol. 120, No. 2, 98-111, (Aug. 2001).
- Sarver, David M., Video cephalometric diagnosis (VCD): A new concept in treatment planning?, *American Journal of Orthodontics and Dentofacial Orthopedics*, vol. 110, No. 2, 128- 136, (Aug. 1996).
- Sarver et al., Dynamic Smile Visualization and Quantification: Part 1. Evolution of the Concept and Dynamic Records for Smile Capture, *American Journal of Orthodontics and Dentofacial Orthopedics*, vol. 124, No. 1, 4-12, (Jul. 2003).
- Sarver et al., Dynamic Smile Visualization and Quantification: Part 2. Smile Analysis and Treatment Strategies, *American Journal of Orthodontics and Dentofacial Orthopedics*, vol. 124, No. 2, 116-127, (Aug. 2003).
- Sarver et al., Principles of Cosmetic Dentistry in Orthodontics: Part 2. Soft Tissue Laser Technology and Cosmetic Gingival Contouring, *American Journal of Orthodontics and Dentofacial Orthopedics*, vol. 127, No. 2, 85-90, (Jan. 2005).
- Soares, Giulliana Panfiglio, Esthetic analysis of the smile, *Braz J Oral Sci.*, vol. 6, No. 21, 1313-1319 (Apr.-Jun. 2007).
- Sondhi, Anoop, Efficient and Effective Indirect Bonding, *Am. J. Orthod. Dentofacial Orthop.* 1999; 115: 352-359 (Apr. 1999).
- Tarantili, Vicky, The Spontaneous Smile in Dynamic Motion, *American Journal of Orthodontics and Dentofacial Orthopedics*, vol. 128, No. 1, 8-15 (Jul. 2005).
- Van Der Geld et al., Digital Videographic Measurement of Tooth Display and Lip Position in Smiling and Speech: Reliability and Clinical Application, *American Journal of Orthodontics and Dentofacial Orthopedics*, vol. 131, No. 3, 301.e1-301.e8 (Mar. 2007).
- Wiedmann, Oliver, According to the laws of harmony to find the tooth shape with the assistance of the computer, *Digital Dental News*, 2nd Volume, 20-23 (Apr. 2008).

* cited by examiner




FIG. 1




FIG. 2A




FIG. 2B




FIG. 3A




FIG. 3B




FIG. 4A




FIG. 4B




FIG. 4C




FIG. 4D




FIG. 5A




FIG. 5B

SYSTEMS AND METHODS FOR FABRICATING A DENTAL TEMPLATE

CROSS-REFERENCE

This application is a continuation of U.S. patent application Ser. No. 14/931,681, filed Nov. 3, 2015, now U.S. Pat. No. 9,433,479, issued Sep. 6, 2016, which is a continuation of U.S. patent application Ser. No. 14/268,976, filed on May 2, 2014, now U.S. Pat. No. 9,204,942, issued Dec. 8, 2015, which is a continuation of U.S. patent application Ser. No. 13/620,209, filed on Sep. 14, 2012, now U.S. Pat. No. 8,734,149, issued May 27, 2014, which is a continuation of U.S. patent application Ser. No. 11/297,129, filed on Dec. 7, 2005, now U.S. Pat. No. 8,496,473, issued Jul. 30, 2013, which is a continuation of U.S. patent application Ser. No. 10/870,808, filed on Jun. 17, 2004, now U.S. Pat. No. 7,056,115, issued Jun. 6, 2006, which is a continuation of U.S. patent application Ser. No. 10/375,223, filed on Feb. 26, 2003, now abandoned, the full disclosures of which are incorporated herein by reference.

BACKGROUND OF THE INVENTION

The present invention relates generally to the field of orthodontics.

One objective in orthodontics is to move a patient's teeth to a position where the teeth function optimally and are also aesthetically pleasing. Conventional appliances such as braces and wires can be positioned on a patient's teeth by a treatment provider such as an orthodontist or a suitably trained dentist. Once mounted on the teeth, the hardware exerts continual forces on the teeth and gradually urges the teeth toward their ideal positions. Over a period of time, the treatment provider adjusts the braces and the wires to move the teeth toward their final destination.

Orthodontic brackets are often bonded directly to the patient's teeth. Typically, a small quantity of adhesive is placed on the base of each bracket and the bracket is then placed on a selected tooth. Before the adhesive is set, the bracket is maneuvered to a desired location on the tooth. Once the adhesive has hardened, the bracket is bonded to the tooth with sufficient strength to withstand subsequent orthodontic forces as treatment progresses. One shortcoming with this technique is the difficulty in accessing the optimal surface for bracket placement on severely crowded teeth or in teeth where the bonding surface is obstructed by teeth in the opposing arch during jaw closure. With posterior teeth, the treatment provider may have difficulty seeing the precise position of the bracket relative to the tooth surface. The amount of time needed to carry out the bonding procedure may be a nuisance both to the patient as well as to the treatment provider. Also, the necessity of minimizing moisture contamination from the patient's saliva can prolong the procedure and also unduly impair the accuracy of placement of the brackets on the teeth. All of these factors increase the chance that the ultimate adhesive bond will not have sufficient strength to retain the brackets on the teeth during treatment. One way to overcome some of the limitations of direct bracket placement is with indirect bonding. Typically, an impression of each of the patient's dental arches is taken and a replica plaster or "stone" model is made from each impression and sealed. Brackets are bonded to the sealed stone models using a temporary cement. A transfer tray is then made by placing matrix material over both the model and the brackets on the model. For example, a heated plastic sheet matrix material may be placed over the model and

brackets and then under pressure. The plastic sheet material then assumes a configuration that precisely matches the shape of the replica teeth of the stone model with the brackets in the desired position. The plastic material is then allowed to cool and harden to form a tray. The temporary adhesive is removed, permanent adhesive is placed on the base of each bracket in the tray, and the tray with the embedded brackets then placed over matching portions of the patient's dental arches. Since the configuration of the interior surface of the tray closely matches the respective portions of the patient's dental arches, each bracket is ultimately positioned on the patient's teeth at precisely the same location that corresponds to the previous location of the same bracket on the stone model. The adhesive is hardened and the matrix material removed, leaving the brackets in the desired positions. This method however, is labor intensive. An additional problem with the indirect method is that brackets may become dislodged during the removal of the matrix from the dental arches. The problem of proper access to tooth surfaces for optimal placement in the event of severely crooked teeth or teeth which interfere with the opposing arch such that brackets cannot be placed is also not addressed.

New methods such as those described in U.S. Pat. No. 5,975,893, commonly assigned to the assignee of the instant invention, allow the treatment to be planned in advance and a plurality of polymeric shell appliances are fabricated at the outset of treatment. The use of polymeric shell appliances provides treatments that are more comfortable; less visible, and removable by the patient, and greatly improves patient compliance, comfort, and satisfaction.

Since each patient is unique and requires customized treatment, on occasion, a patient may need to utilize a combination of braces/wires and shell appliances. Ideally, a device would enable precise placement of brackets on teeth with minimal risk of displacing the brackets upon removal of the matrix and allow final placement to be independent of adjacent geometries. In other words, placement of obscured tooth surfaces may be accomplished at a later time when the tooth surfaces have been exposed through initial uncrowding of severely overlapped teeth.

SUMMARY OF THE INVENTION

A dental template is disclosed to support positioning an object on a patient's tooth oriented in such a way that all the objects as a whole are lined up to a user defined ideal arrangement. Also, a method is disclosed for fabricating the template. The method includes digitizing the patient's teeth; adding virtual objects to predetermined locations on the digitized teeth; and fabricating the dental template to locate the object on the patient's teeth.

Advantages of the template may include one or more of the following. The template can be used for etching or for positioning brackets on teeth. The treatment can be done virtually and the placement of the brackets can be done using a template device that is a removable guide. This device allows precise placement of the bracket and enables bracket placement onto specific teeth independent of overall arch geometry. The template makes it easier for a less well-trained or an untrained person to bond a bracket. The system minimizes variations in the perception of distance and angles. The template provides a very precise control on the placement of the bracket. Since bracket placement is one of the critical variables to successful treatment, the template improves treatment precision from patient to patient and from tooth to tooth.

The device itself may not necessarily contain the bracket as with traditional indirect bonding (IDB) templates, but rather, directs the user as to the precise location where the bracket should be placed based on geometric fit.

INCORPORATION BY REFERENCE

All publications, patents, and patent applications mentioned in this specification are herein incorporated by reference to the same extent as if each individual publication, patent, or patent application was specifically and individually indicated to be incorporated by reference.

BRIEF DESCRIPTION OF THE DRAWINGS

The novel features of the invention are set forth with particularity in the appended claims. A better understanding of the features and advantages of the present invention will be obtained by reference to the following detailed description that sets forth illustrative embodiments, in which the principles of the invention are utilized, and the accompanying drawings of which:

FIG. 1 shows an exemplary method or process to fabricate a dental template to position an object on a patient's tooth.

FIG. 2A shows an exemplary method or process for placing an orthodontic object on a patient's tooth.

FIG. 2B shows a second method of placing the orthodontic object on a patient's tooth.

FIG. 3A illustrates an exemplary process for fabricating the dental template.

FIG. 3B shows a process for providing four possible templates.

FIGS. 4A-4D show perspective views of various templates.

FIGS. 5A and 5B illustrate two embodiments of articulated templates.

DETAILED DESCRIPTION OF THE INVENTION

FIG. 1 shows an exemplary method or process to fabricate a dental template to position an object on a patient's tooth. First, the process digitizes the patient's tooth (10). Next, virtual objects are added to pre-determined locations on the digitized tooth (12). Finally, the process fabricates the dental template to locate the object on the patient's tooth (14). One detailed implementation of FIG. 1 is described in FIGS. 3A and 3B below.

FIG. 2A shows an exemplary method or process for placing an orthodontic object on a patient's tooth. The process uses the template fabricated in the process of FIG. 1. The process includes placing the template on the patient's teeth (20); mounting the orthodontic object between the template and the tooth (22); and bonding the orthodontic object to the tooth (24). In the bonding operation, chemical curing or light curing adhesives can be used. In chemical curing, separately supplied curing components are mixed together and a small quantity of the mixture is placed on the back of the bracket prior to placing the bracket on the tooth. Light-curable adhesives include a photo-initiator that initiates the curing reaction once the adhesive is exposed to a sufficient amount of light. A common method of using light-curable adhesives for direct bonding includes the steps of placing a small quantity of the adhesive on the base of the bracket and then placing the bracket on the patient's tooth. The practitioner then shifts the bracket on the tooth as may be needed. Once the bracket is in its precise, intended

location, light from a dental curing unit is directed toward the adhesive for a time period sufficient to satisfactorily cure the adhesive.

FIG. 2B shows a second method of placing the orthodontic object on a patient's tooth. In this process, the orthodontic object is placed in the template (30). Next, the process includes inserting the template containing the orthodontic object onto the patient's teeth (32). Finally, the process includes bonding the orthodontic object to the tooth (34).

FIG. 3A illustrates an exemplary process for fabricating the dental template. First, a digital model of a patient's teeth of a patient is obtained (102). The digital model can be obtained in a variety of ways. For example, the patient's teeth may be scanned or imaged using well known technology, such as X-rays, three-dimensional x-rays, computer-aided tomographic images or data sets, magnetic resonance images, etc. There are a variety of range acquisition systems, generally categorized by whether the process of acquisition requires contact with the three dimensional object. A contact-type range acquisition system utilizes a probe, having multiple degrees of translational and/or rotational freedom. By recording the physical displacement of the probe as it is drawn across the sample surface, a computer-readable representation of the sample object is made. A non-contact-type range acquisition device can be either a reflective-type or transmissive-type system. There are a variety of reflective systems in use. Some of these reflective systems utilize non-optical incident energy sources such as microwave radar or sonar. Others utilize optical energy. Those non-contact-type systems working by reflected optical energy further contain special instrumentation configured to permit certain measuring techniques to be performed (e.g., imaging radar, triangulation and interferometry).

Next, virtual brackets are selected (104). The virtual brackets are 3D models of existing brackets. The 3D models may be a computer aided design (CAD) model or may be scanned using scanners described above. The brackets may be positioned on a digitized tooth using a computer or workstation having a suitable graphical user interface (GUI) and software appropriate for viewing and modifying the images. The above-described component identification and component manipulation software is designed to operate at sophistication commensurate with the operator's training level. For example, the component manipulation software can assist a computer operator, lacking orthodontic training, by providing feedback regarding permissible and forbidden manipulations of the teeth. On the other hand, an orthodontist, having greater skill in intra-oral physiology and teeth-moving dynamics, can simply use the component identification and manipulation software as a tool and disable or otherwise ignore the advice.

While the methods will rely on computer manipulation of digital data, the dental templates or appliance may be produced by non-computer-aided techniques. For example, plaster casts obtained as described above may be cut using knives, saws, or other cutting tools in order to permit repositioning of individual teeth within the casting. The disconnected teeth may then be held in place by soft wax or other malleable material, and a plurality of intermediate tooth arrangements can then be prepared using such a modified plaster casting of the patient's teeth. The different arrangements can be used to prepare the template using pressure and vacuum molding techniques. While such manual creation of the appliance systems of the present invention will generally be much less preferred, systems so produced will come within the scope of the present invention.

Using the CAD workstation, a combined digital model of the virtual brackets and the teeth is produced (106).

In one implementation, four template embodiments can be selected: Direct-Articulated, Indirect-Articulated, Direct-Unified, and Indirect-Unified, as discussed in more detail in FIG. 3B.

Once the template has been fabricated, in one embodiment, the system sets the template over the model of the patient's arches or otherwise positions the template in the approximate locations of their respective teeth. A thermoformed, cast, or otherwise formed layer of flexible material is deposited on the bodies. The layer makes intimate and relatively durable contact with the bodies of the templates. This may be accomplished, among other ways, by adding or subtracting geometries to the bodies to engage well with the material layer. This method could be performed either by a factory or in the orthodontist's office.

The system produces both the template bodies and the inter-tooth portion(s) at the same time and subsequently alter the stiffness of the various parts. One way of achieving this would be to produce the entire arch with a 3-D printer, mask the tooth bodies from the inter-tooth portions, embed the tooth bodies with a rigidifying agent and the inter-tooth portions with an agent to create flexibility.

From 110, if a directly formed template is produced, the process proceeds to 114 where each tooth is scaled; a cavity is formed to enclose the tooth when the dental template or appliance is inserted over the patient's teeth. Next, unnecessary structures are removed from the digital model. The digital model is produced as a physical model. A flexible pliable layer is formed and the resulting combination is trimmed to allow proper fit and function.

Alternatively, from 110 if indirect forming is to be done, the process forms and aligner, and cuts and removes excess material (112).

From 108, for direct fabrication of a template of a whole arch (116) using an indirectly-produced template, the process forms an aligner, cuts and removes excess material (118). In the case of a directly formed whole arch template (116), the process proceeds to 120 where the entire arch is scaled; a cavity is formed to enclose the arch when the dental template or appliance is inserted over the patient's teeth. Next, unnecessary structures are removed from the digital model. The digital model is produced as a physical model. A flexible pliable layer is formed and the resulting combination is trimmed to allow proper fit and function.

FIG. 3B shows a process for providing four possible templates. First, the process acquires a digital model of dentition, adds virtual brackets to teeth, and creates a combined model (180). Next, one of four templates options can be selected. The first option is unified (or single piece)—direct bonding option where the process scales the arch (est. 105-150%), locates original arch and scaled arch in same 3D space, creates cavity of original inside scaled arch, removes gingival portions, substantial part of lingual tooth surfaces, buccogingival surfaces covering virtual brackets, and produces real arch model from digital model (182).

In the second option (unified indirect bonding), the process produces real arch model from digital model and forms a removable appliance (aligner) template on real model of arch. The template is removed from the real model, and the process then removes gingival portions, substantial part of lingual tooth surfaces, buccogingival surfaces covering virtual brackets (184).

In the third option (articulated direct bonding), the process scales individual tooth (est. 105-150%), locates each original tooth and its scaled version in same 3D space,

creates a cavity of each original inside its scaled version, removes gingival portions, substantial part of lingual tooth surfaces, buccogingival surfaces covering virtual brackets, produces real tooth models from digital models, positions teeth in appropriate locations and orientations, forms a flexible or pliable material over teeth, and trims excess material from the template (186).

In the fourth option (articulated indirect bonding), the process forms an aligner-like template on a mold of an arch. The template is removed from the mold and gingival portions, substantial part of lingual tooth surfaces and buccogingival surface covering virtual brackets are trimmed. The process cuts an arch template onto an individual tooth. A flexible or pliable layer over the template is formed, and excess material is trimmed (188).

In yet another embodiment, a process obtains tooth geometries. If direct bonding is to be used, the process performs the following:

Scale the arch to a value likely within the range 105-150%.

Co-locate the original (100%) arch and the scaled arch in the same 3D space

Place a virtual bracket or other appropriate geometry at a specific location and in a specific orientation on each tooth to be treated.

Cavity the original arch and the brackets in the scaled arch.

Remove from the resulting template or body those aspects that would be below the gingival line. Remove the portions of the resultant body buccal and gingival to the brackets remove a substantial portion or all of the lingual aspect of the resultant body.

Convert this computer model to a real part, likely through the use of a rapid prototyping method (e.g. Fused Deposition Modeling, 3-D Printing, stereolithography).

If indirect bonding is to be done, the following operations are done using an arch model:

Form an Aligner-like appliance or template over an arch model that has brackets or other appropriate geometries properly located on the teeth.

Remove from the Aligner or template those aspects that would be below the gingival line or in direct interproximal contact with adjacent teeth. Remove the portions of the Aligner buccal and gingival to the bracket. Remove a substantial portion or all of the lingual aspect of the Aligner.

After completion, the process ships the templates, bodies or the completed appliance to the orthodontist either at the onset of treatment or when it is requested.

FIG. 4A shows one embodiment of a dental template 220 or appliance formed over a mold 210. The template looks like a removable appliance; however, it has openings 222 or "port-holes" approximating the footprint, key portions of the footprint, and/or possibly other geometrical features of a bracket to guide the precise placement of the bracket on its respective tooth. The template 220 with the openings 222 or "port-holes" may also be a guide for enamel etching or adhesive placement.

The mold 210 is a physical rendition of a digital model that has been fabricated using rapid prototyping methods. A bump or projection 212 rises from the mold 210 so when the dental template or appliance is thermal-formed, an opening 222 is formed on the template 220. The opening 222 is where the template is cut out along the edge of the bump or projection 212. The opening 222 has a bracket support edge 226, whose operation is described in more detail in FIG. 4B. In addition to the support edge 226, the template 220 may

have features that will minimize the retention of it on the dental anatomy. For example, the lingual side of the device may not have maximum coverage.

Fabrication methods for the mold **210** employ a rapid prototyping device such as a stereolithography machine or a fused deposition modeling machine. A suitable rapid prototyping machine is Model SLA-250/50 available from 3D System, Valencia, Calif. The rapid prototyping machine selectively hardens a liquid or other non-hardened resin into a three-dimensional structure, which can be separated from the remaining non-hardened resin, washed, and used either directly as the appliance or indirectly as a mold for producing the appliance. The prototyping machine receives the individual digital data sets and produces one structure corresponding to each of the desired appliances. Generally, because the stereolithography machine may utilize a resin having non-optimum mechanical properties and which may not be generally acceptable for patient use, the prototyping machine produces the mold **210**. After the positive model is prepared, a conventional pressure or vacuum molding machine may be used to produce the appliances from a more suitable material, such as 0.03 inch thermal forming dental material, available from Tru-Tain Plastics, Rochester, Minn. 55902. Suitable pressure molding equipment is available under the trade name BIOSTAR from Great Lakes Orthodontics, Ltd., Tonawanda, N.Y. 14150. The molding machine produces each of the appliances directly from the positive tooth model and the desired material. Suitable vacuum molding machines are available from Raintree Essix, Inc.

In one embodiment, the template is made from a thick material (for example 0.03 inches or more) to provide the user with more guidance in the depth direction. Furthermore, the thick template allows easier lining the bracket to the tooth.

More information on the fabrication of the dental template or appliance is disclosed in U.S. Pat. No. 6,499,997 "Manipulable dental model system for fabrication of a dental appliance"; U.S. Pat. No. 6,497,574 "Modified tooth positioning appliances and methods and systems for their manufacture"; U.S. Pat. No. 6,488,499 "Methods for correcting deviations in preplanned tooth rearrangements"; U.S. Pat. No. 6,485,298 "System and method for releasing tooth positioning appliances"; U.S. Pat. No. 6,471,511 "Defining tooth-moving appliances computationally"; U.S. Pat. No. 6,463,344 "Efficient data representation of tooth model"; U.S. Pat. No. 6,457,972 "System for determining final position of teeth"; U.S. Pat. No. 6,454,565 "Systems and methods for varying elastic modulus appliances"; U.S. Pat. No. 6,450,807 "System and method for positioning teeth"; U.S. Pat. No. 6,409,504 "Manipulating a digital dentition model to form models of individual dentition components"; U.S. Pat. No. 6,406,292 "System for determining final position of teeth"; U.S. Pat. No. 6,398,548 "Method and system for incrementally moving teeth"; U.S. Pat. No. 6,394,801 "Manipulable dental model system for fabrication of dental appliances"; U.S. Pat. No. 6,390,812 "System and method for releasing tooth positioning appliances"; U.S. Pat. No. 6,386,878 "Systems and methods for removing gingiva from teeth"; U.S. Pat. No. 6,386,864 "Stress indicators for tooth positioning appliances"; U.S. Pat. No. 6,371,761 "Flexible plane for separating teeth models"; U.S. Pat. No. 6,318,994 "Tooth path treatment plan"; U.S. Pat. No. 6,309,215 "Attachment devices and method for a dental appliance"; U.S. Pat. No. 6,299,440 "System and method for producing tooth movement"; U.S. Pat. No. 6,227,851 "Manipulable dental model system for

fabrication of a dental appliance"; U.S. Pat. No. 6,227,850 "Teeth viewing system"; U.S. Pat. No. 6,217,325 "Method and system for incrementally moving teeth"; U.S. Pat. No. 6,210,162 "Creating a positive mold of a patient's dentition for use in forming an orthodontic appliance"; and U.S. Pat. No. 5,975,893 "Method and system for incrementally moving teeth," the contents of which are hereby incorporated by reference.

Turning now to FIG. 4B, the template **220** is separated from the mold **210**. The opening **222** allows a bracket base to fit into the opening **222**. Bracket support edge **226** is needed to securely position the bracket in the template **220**. In this embodiment, the bracket support edge **226** is curved. If the edge **226** had been terminated as a simple flat edge, the bracket can be located in X and Y surfaces on the tooth, but the Z direction (buccal lingual direction) would not be controlled. The edge **226** provides the needed control of the bracket's degree of freedom in the Z direction to allow orientation of the bracket about any given axis. Those features allow the bracket to be secured in the proper position and orientation on its respective tooth. The edge **226** can change, depending on vendor-to-vendor or prescription-to-prescription.

Another embodiment of the template can be used for etching bonding chemicals on the patient's teeth. The etching template directs the user to predetermined locations on the teeth surfaces that need to be bonded. The etching template can be either the format of a windowed template or a concave surfaced template where bonding gel is loaded or pre-loaded into the concavity.

FIG. 4C shows a template wherein each of the openings, cut-outs, port-holes, or slots **222** in the template **220** are designed to fit particular brackets **4A**, **4B** and a **4C**, each of which fits into its respective portion on the template.

FIG. 4D shows that the system is not limited to bracket design or shape. In FIG. 4D, a molar tube bracket **215** can be placed on the opening **222**. Hence, the template **220** is not limited to any specific bracket. Rather, any form of fixed orthodontic appliances placed on a tooth could be accommodated.

FIGS. 5A and 5B illustrate two exemplary embodiments of articulated templates. FIG. 5A shows two segments joined at the interproximal regions of two adjacent teeth. A number of alternate methods to join the teeth can be used, including that the joining methods could be alternate or vary from one interproximal region to the next. Further, the joining method could also be a layer or layers that cover additional or different surfaces of the teeth as depicted in FIG. 5B.

In FIG. 5A, the template is made up of a number of movable template components **250**. Each of the template components **250** can be mounted on a patient's tooth to facilitate bracket bonding. The movable template components **250** are physically linked together by a sheet of material **252** deposited above the components **250** so that they do not break-up or otherwise become disassembled upon removal from its mold or stereolithography apparatus (SLA) model. The articulated templates are advantageous in that they provide greater adjustment flexibility.

The template can additionally be used as an etching template. An etching template allows the doctor to precisely etch the areas of the teeth on which the brackets will be placed. The small windows bound the regions that will be etched to minimize teeth sensitivity to etching or unwanted enamel removal. In another version of the etching template, the cut outs would not be formed. Instead those areas would be concavities facing the tooth surfaces. These concavities

would contain an etching compound. The user would expose or activate the etching compound prior to setting the template on the teeth.

The template 220 may be made from materials that contain physical property switches for ease of removal. These switches might include temperature responsive, pH responsive, moisture responsive or a multi-layer system wherein the layers have varying physical properties. The section 500 represents a flexible or pliable material. Additionally, the material could be fiber, cord, fiber mesh, or a fiber-reinforced solid. The interproximal material can be homogenous or heterogeneous.

Various alternatives, modifications, and equivalents may be used in lieu of the above components. Additionally, the techniques described here may be implemented in hardware or software, or a combination of the two. The techniques may be implemented in computer programs executing on programmable computers that each includes a processor, a storage medium readable by the processor (including volatile and nonvolatile memory and/or storage elements), and suitable input and output devices. Program code is applied to data entered using an input device to perform the functions described and to generate output information. The output information is applied to one or more output devices. Each program can be implemented in a high level procedural or object-oriented programming language to operate in conjunction with a computer system. However, the programs can be implemented in assembly or machine language, if desired. In any case, the language may be a compiled or interpreted language. Each such computer program can be stored on a storage medium or device (e.g., CD-ROM, hard disk or magnetic diskette) that is readable by a general or special purpose programmable computer for configuring and operating the computer when the storage medium or device is read by the computer to perform the procedures described. The system also may be implemented as a computer-readable storage medium, configured with a computer program, where the storage medium so configured causes a computer to operate in a specific and predefined manner. Further, while the invention has been shown and described with reference to an embodiment thereof, those skilled in the art will understand that the above and other changes in form and detail may be made without departing from the spirit and scope of the following claims.

While preferred embodiments of the present invention have been shown and described herein, it will be obvious to those skilled in the art that such embodiments are provided by way of example only. Numerous variations, changes, and substitutions will now occur to those skilled in the art without departing from the invention. It should be under-

stood that various alternatives to the embodiments of the invention described herein may be employed in practicing the invention. It is intended that the following claims define the scope of the invention and that methods and structures within the scope of these claims and their equivalents be covered thereby.

What is claimed is:

1. An apparatus configured for positioning an orthodontic object on teeth of a patient, comprising:
 - a template adapted for placement over the patient's teeth and including a plurality of teeth receiving cavities, each of the plurality of teeth receiving cavities shaped to receive a corresponding tooth of the patient and having a shape corresponding to a shape of the corresponding tooth and also including one or more openings through a sidewall, the sidewall extending from an occlusal end of a respective tooth receiving cavity to a gingival edge of the respective tooth receiving cavity and the one or more openings defining one or more object support edges, wherein the one or more object support edges are shaped to receive and position one or more orthodontic objects at respective locations and orientations on the patient's teeth, and wherein the one or more openings each comprise a cut-out open to the gingival edge of the respective tooth receiving cavity of the template, wherein the plurality of teeth receiving cavities have a geometry corresponding to a shape of the corresponding tooth of the patient.
 2. The apparatus of claim 1, wherein the template includes a variable physical property material such that the template has a first state for retention of the template on the patient's teeth and a second state for facilitating removal of the template from the patient's teeth.
 3. The apparatus of claim 2, wherein the variable physical property material are physical property switches.
 4. The apparatus of claim 3, wherein the physical property switches are temperature responsive, pH responsive, moisture responsive, or a multilayer system wherein layers of the multilayer system have varying physical properties.
 5. The apparatus of claim 1, wherein the orthodontic object is a bracket.
 6. The apparatus of claim 1, wherein a thickness of the template is at least 0.03 inches in a buccal-lingual direction.
 7. The apparatus of claim 1, wherein the template is unified.
 8. The apparatus of claim 1, wherein the template is articulated, having a plurality of movable template components linked together by sheet material.

* * * * *