US 20070021797A1

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2007/0021797 A1

Kieval et al. (43) Pub. Date: Jan. 25, 2007

(54) BAROREFLEX STIMULATION SYNCHRONIZED TO CIRCADIAN RHYTHM

(75) Inventors: **Robert S. Kieval**, Medina, MN (US); **Matthew M. Burns**, Orono, MN (US); **David J. Serdar**, Shorewood, MN (US); **Martin A. Rossing**, Coon Rapids, MN (US)

Correspondence Address:
TOWNSEND AND TOWNSEND AND CREW, LLP
TWO EMBARCADERO CENTER
EIGHTH FLOOR
SAN FRANCISCO, CA 94111-3834 (US)

(73) Assignee: **CVRx, Inc.**, Maple Grove, MN

(21) Appl. No.: **11/482,453**

(22) Filed: **Jul. 7, 2006**

Related U.S. Application Data

(63) Continuation of application No. 10/402,911, filed on Mar. 27, 2003, and which is a continuation-in-part of application No. 09/963,777, filed on Sep. 26, 2001, which is a continuation-in-part of application No. 09/671,850, filed on Sep. 27, 2000, now Pat. No. 6,522,926.

(60) Provisional application No. 60/368,222, filed on Mar. 27, 2002.


Publication Classification

(51) **Int. Cl.**
A61N 1/00 (2006.01)

(52) **U.S. Cl.** **607/44**

(57) **ABSTRACT**

A baroreflex stimulator is provided. The baroreflex stimulator includes a driver adapted to provide a control signal through a baroreceptor activation device, and a controller to periodically modulate the control signal based on an algorithm.






FIG. 1



50
52
VESSELS
54
BRAIN
KIDNEYS
BP/CO
55
53
HEART
11
51
38
30
40
32

FIG. 2B



19
38
30
14
18
20

FIG. 2A



60
61
62
63
CONTROL
MEMORY
(DATA & SOFTWARE)
PROCESSOR
CONTROL SIGNAL
DRIVER
66
65
DISPLAY
INPUT DEVICE
64
72
20
18
19
21
14
15
16
17
11
12
13
70
80
82

FIG. 3




FIG. 4B




FIG. 4A




FIG. 5A




FIG. 5B




FIG. 5C




FIG. 5D




FIG. 5E




FIG. 5F




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11



308
311
309
19
302
306
300
18
313
304
312
311
314
315
14
304
311

FIG. 12



302
300
316
317
312
316
304

FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26



910d
900
910e
910c
910b
906a
906c
904
902
910a
910b
910c
906b
920
906d
910e
910d

FIG. 27



IC
EC
922
906a
920
906d
900
CC
924

FIG. 28




FIG. 29




FIG. 30



410
412
414
416
PF
A
BW
BF
PW
D
SIGNAL
450
ARTERIAL PRESSURE
460
ECG
T

FIG. 31

BAROREFLEX STIMULATION SYNCHRONIZED TO CIRCADIAN RHYTHM

CROSS-REFERENCES TO RELATED APPLICATIONS

[0001] This application is a continuation of U.S. patent application Ser. No. 10/402,911 (Attorney Docket No.: 021433-000410US), filed on Mar. 27, 2003, which (1) is a continuation-in-part of U.S. patent application Ser. No. 09/963,777 (Attorney Docket No.: 021433-000120US), filed on Sep. 26, 2001, which is a continuation-in-part of U.S. patent application Ser. No. 09/671,850 (Attorney Docket No.: 021433-000100US), filed on Sep. 27, 2000, now issued as U.S. Pat. No. 6,522,926; and (ii) claims the benefit of U.S. Provisional Patent Application No. 60/368,222 (Attorney Docket No.: 021433-000400US), filed on Mar. 27, 2002, the disclosures of each of the above being hereby incorporated by reference in their entirety. The parent application for this application has incorporated by reference the disclosures of the following U.S. patent applications: U.S. patent application Ser. No. 09/964,079 (Attorney Docket No.: 021433-000110US), filed on Sep. 26, 2001, now issued as U.S. Pat. No. 6,985,774, and U.S. patent application Ser. No. 09/963,991 (Attorney Docket No.: 021433-000130US), filed on Sep. 26, 2001, now issued as U.S. Pat. No. 6,850,801, now issued as U.S. Pat. No. 6,850,801, the disclosures of which are also effectively incorporated by reference herein.

BACKGROUND OF THE INVENTION

Field of the Invention

[0002] The present invention generally relates to medical devices and methods of use for the treatment and/or management of cardiovascular and renal disorders. Specifically, the present invention relates to devices and methods for controlling the baroreflex system for the treatment and/or management of cardiovascular and renal disorders and their underlying causes and conditions.

[0003] Cardiovascular disease is a major contributor to patient illness and mortality. It also is a primary driver of health care expenditure, costing more than $326 billion each year in the United States. Hypertension, or high blood pressure, is a major cardiovascular disorder that is estimated to affect over 50 million people in the United Sates alone. Of those with hypertension, it is reported that fewer than 30% have their blood pressure under control. Hypertension is a leading cause of heart failure and stroke. It is the primary cause of death in over 42,000 patients per year and is listed as a primary or contributing cause of death in over 200,000 patients per year in the U.S. Accordingly, hypertension is a serious health problem demanding significant research and development for the treatment thereof.

[0004] Hypertension occurs when the body's smaller blood vessels (arterioles) constrict, causing an increase in blood pressure. Because the blood vessels constrict, the heart must work harder to maintain blood flow at the higher pressures. Although the body may tolerate short periods of increased blood pressure, sustained hypertension may eventually result in damage to multiple body organs, including the kidneys, brain, eyes and other tissues, causing a variety of maladies associated therewith. The elevated blood pressure may also damage the lining of the blood vessels, accelerating the process of atherosclerosis and increasing the likelihood that a blood clot may develop. This could lead to a heart attack and/or stroke. Sustained high blood pressure may eventually result in an enlarged and damaged heart (hypertrophy), which may lead to heart failure.

[0005] Heart failure is the final common expression of a variety of cardiovascular disorders, including ischemic heart disease. It is characterized by an inability of the heart to pump enough blood to meet the body's needs and results in fatigue, reduced exercise capacity and poor survival. It is estimated that approximately 5,000,000 people in the United States suffer from heart failure, directly leading to 39,000 deaths per year and contributing to another 225,000 deaths per year. It is also estimated that greater than 400,000 new cases of heart failure are diagnosed each year. Heart failure accounts for over 900,000 hospital admissions annually, and is the most common discharge diagnosis in patients over the age of 65 years. It has been reported that the cost of treating heart failure in the United States exceeds $20 billion annually. Accordingly, heart failure is also a serious health problem demanding significant research and development for the treatment and/or management thereof.

[0006] Heart failure results in the activation of a number of body systems to compensate for the heart's inability to pump sufficient blood. Many of these responses are mediated by an increase in the level of activation of the sympathetic nervous system, as well as by activation of multiple other neurohormonal responses. Generally speaking, this sympathetic nervous system activation signals the heart to increase heart rate and force of contraction to increase the cardiac output; it signals the kidneys to expand the blood volume by retaining sodium and water; and it signals the arterioles to constrict to elevate the blood pressure. The cardiac, renal and vascular responses increase the workload of the heart, further accelerating myocardial damage and exacerbating the heart failure state. Accordingly, it is desirable to reduce the level of sympathetic nervous system activation in order to stop or at least minimize this vicious cycle and thereby treat or manage the heart failure.

[0007] A number of drug treatments have been proposed for the management of hypertension, heart failure and other cardiovascular disorders. These include vasodilators to reduce the blood pressure and ease the workload of the heart, diuretics to reduce fluid overload, inhibitors and blocking agents of the body's neurohormonal responses, and other medicaments.

[0008] Various surgical procedures have also been proposed for these maladies. For example, heart transplantation has been proposed for patients who suffer from severe, refractory heart failure. Alternatively, an implantable medical device such as a ventricular assist device (VAD) may be implanted in the chest to increase the pumping action of the heart. Alternatively, an intra-aortic balloon pump (IABP) may be used for maintaining heart function for short periods of time, but typically no longer than one month. Other surgical procedures are available as well.

[0009] It has been known for decades that the wall of the carotid sinus, a structure at the bifurcation of the common carotid arteries, contains stretch receptors (baroreceptors) that are sensitive to the blood pressure. These receptors send signals via the carotid sinus nerve to the brain, which in turn

regulates the cardiovascular system to maintain normal blood pressure (the baroreflex), in part through activation of the sympathetic nervous system. Electrical stimulation of the carotid sinus nerve (baropacing) has previously been proposed to reduce blood pressure and the workload of the heart in the treatment of high blood pressure and angina. For example, U.S. Pat. No. 6,073,048 to Kieval et al. discloses a baroreflex modulation system and method for stimulating the baroreflex arc based on various cardiovascular and pulmonary parameters.

[0010] Although each of these alternative approaches is beneficial in some ways, each of the therapies has its own disadvantages. For example, drug therapy is often incompletely effective. Some patients may be unresponsive (refractory) to medical therapy. Drugs often have unwanted side effects and may need to be given in complex regimens. These and other factors contribute to poor patient compliance with medical therapy. Drug therapy may also be expensive, adding to the health care costs associated with these disorders. Likewise, surgical approaches are very costly, may be associated with significant patient morbidity and mortality and may not alter the natural history of the disease. Baropacing also has not gained acceptance. Several problems with electrical carotid sinus nerve stimulation have been reported in the medical literature. These include the invasiveness of the surgical procedure to implant the nerve electrodes, and postoperative pain in the jaw, throat, face and head during stimulation. In addition, it has been noted that high voltages sometimes required for nerve stimulation may damage the carotid sinus nerves. Accordingly, there continues to be a substantial and long felt need for new devices and methods for treating and/or managing high blood pressure, heart failure and their associated cardiovascular and nervous system disorders.

[0011] U.S. Pat. No. 6,522,926, signed to the Assignee of the present application, describes a number of systems and methods intended to activate baroreceptors in the carotid sinus and elsewhere in order to induce the baroreflex. Numerous specific approaches are described, including the use of coil electrodes placed over the exterior of the carotid sinus near the carotid bifurcation. While such electrode designs offer substantial promise, there is room for improvement in a number of specific design areas. For example, it would be desirable to provide designs which permit electrode structures to be closely and conformably secured over the exterior of a carotid sinus or other blood vessels so that efficient activation of the underlying baroreceptors can be achieved. It would be further desirable to provide specific electrode structures which can be variably positioned at different locations over the carotid sinus wall or elsewhere. At least some of these objectives will be met by these inventions described hereinbelow.

BRIEF SUMMARY OF THE INVENTION

[0012] To address hypertension, heart failure and their associated cardiovascular and nervous system disorders, the present invention provides a number of devices, systems and methods by which the blood pressure, nervous system activity, and neurohormonal activity may be selectively and controllably regulated by activating baroreceptors. By selectively and controllably activating baroreceptors, the present invention reduces excessive blood pressure, sympathetic nervous system activation and neurohormonal activation, thereby minimizing their deleterious effects on the heart, vasculature and other organs and tissues.

[0013] The present invention provides systems and methods for treating a patient by inducing a baroreceptor signal to effect a change in the baroreflex system (e.g., reduced heart rate, reduced blood pressure, etc.). The baroreceptor signal is activated or otherwise modified by selectively activating baroreceptors. To accomplish this, the system and method of the present invention utilize a baroreceptor activation device positioned near a baroreceptor in the carotid sinus, aortic arch, heart, common carotid arteries, subclavian arteries, and/or brachiocephalic artery. Preferably, the baroreceptor activation device is located in the right and/or left carotid sinus (near the bifurcation of the common carotid artery) and/or the aortic arch. By way of example, not limitation, the present invention is described with reference to the carotid sinus location.

[0014] Generally speaking, the baroreceptor activation device may be activated, deactivated or otherwise modulated to activate one or more baroreceptors and induce a baroreceptor signal or a change in the baroreceptor signal to thereby effect a change in the baroreflex system. The baroreceptor activation device may be activated, deactivated, or otherwise modulated continuously, periodically, or episodically. The baroreceptor activation device may comprise a wide variety of devices which utilize electrodes to directly or indirectly activate the baroreceptor. The baroreceptor may be activated directly, or activated indirectly via the adjacent vascular tissue. The baroreceptor activation device will be positioned outside the vascular wall. To maximize therapeutic efficacy, mapping methods may be employed to precisely locate or position the baroreceptor activation device.

[0015] The present invention is directed particularly at electrical means and methods to activate baroreceptors, and various electrode designs are provided. The electrode designs may be particularly suitable for connection to the carotid arteries at or near the carotid sinus, and may be designed to minimize extraneous tissue stimulation. While being particularly suitable for use on the carotid arteries at or near the carotid sinus, the electrode structures and assemblies of the present invention will also find use for external placement and securement of electrodes about other arteries, and in some cases veins, having baroreceptor and other electrically activated receptors therein.

[0016] In a first aspect of the present invention, a baroreceptor activation device or other electrode useful for a carotid sinus or other blood vessel comprises a base having one or more electrodes connected to the base. The base has a length sufficient to extend around at least a substantial portion of the circumference of a blood vessel, usually an artery, more usually a carotid artery at or near the carotid sinus. By "substantial portion," it is meant that the base will extend over at least 25% of the vessel circumference, usually at least 50%, more usually at least 66%, and often at least 75% or over the entire circumference. Usually, the base is sufficiently elastic to conform to said circumference or portion thereof when placed therearound. The electrode connected to the base is oriented at least partly in the circumferential direction and is sufficiently stretchable to both conform to the shape of the carotid sinus when the base is conformed thereover and accommodate changes in the shape and size of the sinus as they vary over time with heart

pulse and other factors, including body movement which causes the blood vessel circumference to change.

[0017] Usually, at least two electrodes will be positioned circumferentially and adjacent to each other on the base. The electrode(s) may extend over the entire length of the base, but in some cases will extend over less than 75% of the circumferential length of the base, often being less than 50% of the circumferential length, and sometimes less than 25% of the circumferential length. Thus, the electrode structures may cover from a small portion up to the entire circumferential length of the carotid artery or other blood vessel. Usually, the circumferential length of the elongate electrodes will cover at least 10% of the circumference of the blood vessel, typically being at least 25%, often at least 50%, 75%, or the entire length. The base will usually have first and second ends, wherein the ends are adapted to be joined, and will have sufficient structural integrity to grasp the carotid sinus.

[0018] In a further aspect of the present invention, an extravascular electrode assembly comprises an elastic base and a stretchable electrode. The elastic base is adapted to be conformably attached over the outside of a target blood vessel, such as a carotid artery at or near the carotid sinus, and the stretchable electrode is secured over the elastic base and capable of expanding and contracting together with the base. In this way, the electrode assembly is conformable to the exterior of the carotid sinus or other blood vessel. Preferably, the elastic base is planar, typically comprising an elastomeric sheet. While the sheet may be reinforced, the reinforcement will be arranged so that the sheet remains elastic and stretchable, at least in the circumferential direction, so that the base and electrode assembly may be placed and conformed over the exterior of the blood vessel. Suitable elastomeric sheets may be composed of silicone, latex, and the like.

[0019] To assist in mounting the extravascular electrode over the carotid sinus or other blood vessel, the assembly will usually include two or more attachment tabs extending from the elastomeric sheet at locations which allow the tabs to overlap the elastic base and/or be directly attached to the blood vessel wall when the base is wrapped around or otherwise secured over a blood vessel. In this way, the tabs may be fastened to secure the backing over the blood vessel.

[0020] Preferred stretchable electrodes comprise elongated coils, where the coils may stretch and shorten in a spring-like manner. In particularly preferred embodiments, the elongated coils will be flattened over at least a portion of their lengths, where the flattened portion is oriented in parallel to the elastic base. The flattened coil provides improved electrical contact when placed against the exterior of the carotid sinus or other blood vessel.

[0021] In a further aspect of the present invention, an extravascular electrode assembly comprises a base and an electrode structure. The base is adapted to be attached over the outside of a carotid artery or other blood vessel and has an electrode-carrying surface formed over at least a portion thereof. A plurality of attachment tabs extend away from the electrode-carrying surface, where the tabs are arranged to permit selective ones thereof to be wrapped around a blood vessel while others of the tabs may be selectively removed. The electrode structure on or over the electrode-carrying surface.

[0022] In preferred embodiments, the base includes at least one tab which extends longitudinally from the electrode-carrying surface and at least two tabs which extend away from the surface at opposite, transverse angles. In an even more preferred embodiment, the electrode-carrying surface is rectangular, and at least two longitudinally extending tabs extend from adjacent corners of the rectangular surface. The two transversely angled tabs extend at a transverse angle away from the same two corners.

[0023] As with prior embodiments, the electrode structure preferably includes one or more stretchable electrodes secured to the electrode-carrying surface. The stretchable electrodes are preferably elongated coils, more preferably being "flattened coils" to enhance electrical contact with the blood vessel to be treated. The base is preferably an elastic base, more preferably being formed from an elastomeric sheet. The phrase "flattened coil," as used herein, refers to an elongate electrode structure including a plurality of successive turns where the cross-sectional profile is non-circular and which includes at least one generally flat or minimally curved face. Such coils may be formed by physically deforming (flattening) a circular coil, e.g., as shown in FIG. **24** described below. Usually, the flattened coils will have a cross-section that has a width in the plane of the electrode assembly greater than its height normal to the electrode assembly plane. Alternatively, the coils may be initially fabricated in the desired geometry having one generally flat (or minimally curved) face for contacting tissue. Fully flattened coils, e.g., those having planar serpentine configurations, may also find use, but usually it will be preferred to retain at least some thickness in the direction normal to the flat or minimally curved tissue-contacting surface. Such thickness helps the coiled electrode protrude from the base and provide improved tissue contact over the entire flattened surface.

[0024] In a still further aspect of the present invention, a method for wrapping an electrode assembly over a blood vessel comprises providing an electrode assembly having an elastic base and one or more stretchable electrodes. The base is conformed over an exterior of the blood vessel, such as a carotid artery, and at least a portion of an electrode is stretched along with the base. Ends of the elastic base are secured together to hold the electrode assembly in place, typically with both the elastic backing and stretchable electrode remaining under at least slight tension to promote conformance to the vessel exterior. The electrode assembly will be located over a target site in the blood vessel, typically a target site having an electrically activated receptor. Advantageously, the electrode structures of the present invention when wrapped under tension will flex and stretch with expansions and contractions of the blood vessel. A presently preferred target site is a baroreceptor, particularly baroreceptors in or near the carotid sinus.

[0025] In a still further aspect of the present invention, a method for wrapping an electrode assembly over a blood vessel comprises providing an electrode assembly including a base having an electrode-carrying surface and an electrode structure on the electrode-carrying surface. The base is wrapped over a blood vessel, and some but not all of a plurality of attachment tags on the base are secured over the blood vessel. Usually, the tabs which are not used to secure an electrode assembly will be removed, typically by cutting. Preferred target sites are electrically activated receptors,

usually baroreceptors, more usually baroreceptors on the carotid sinus. The use of such electrode assemblies having multiple attachment tabs is particularly beneficial when securing the electrode assembly on a carotid artery near the carotid sinus. By using particular tabs, as described in more detail below, the active electrode area can be positioned at any of a variety of locations on the common, internal, and/or external carotid arteries.

[0026] In another aspect, the present invention comprises pressure measuring assemblies including an elastic base adapted to be mounted on the outer wall of a blood vessel under circumferential tension. A strain measurement sensor is positioned on the base to measure strain resulting from circumferential expansion of the vessel due to a blood pressure increase. Usually, the base will wrap about the entire circumference of the vessel, although only a portion of the base need be elastic. Alternatively, a smaller base may be stapled, glued, clipped or otherwise secured over a "patch" of the vessel wall to detect strain variations over the underlying surface. Exemplary sensors include strain gauges and micro machined sensors (MEMS).

[0027] In yet another aspect, electrode assemblies according to the present invention comprise a base and at least three parallel elongate electrode structures secured over a surface of the base. The base is attachable to an outside surface of a blood vessel, such as a carotid artery, particularly a carotid artery near the carotid sinus, and has a length sufficient to extend around at least a substantial portion of the circumference of the blood vessel, typically extending around at least 25% of the circumference, usually extending around at least 50% of the circumference, preferably extending at least 66% of the circumference, and often extending around at least 75% of or the entire circumference of the blood vessel. As with prior embodiments, the base will preferably be elastic and composed of any of the materials set forth previously.

[0028] The at least three parallel elongate electrode structures will preferably be aligned in the circumferential direction of the base, i.e., the axis or direction of the base which will be aligned circumferentially over the blood vessel when the base is mounted on the blood vessel. The electrode structures will preferably be stretchable, typically being elongate coils, often being flattened elongate coils, as also described previously.

[0029] At least an outer pair of the electrode structures will be electrically isolated from an inner electrode structure, and the outer electrode structures will preferably be arranged in a U-pattern in order to surround the inner electrode structure. In this way, the outer pair of electrodes can be connected using a single conductor taken from the base, and the outer electrode structures and inner electrode structure may be connected to separate poles on a power supply in order to operate in the "pseudo" tripolar mode described hereinbelow.

[0030] To address low blood pressure and other conditions requiring blood pressure augmentation, the present invention provides electrode designs and methods utilizing such electrodes by which the blood pressure may be selectively and controllably regulated by inhibiting or dampening baroreceptor signals. By selectively and controllably inhibiting or dampening baroreceptor signals, the present invention reduces conditions associated with low blood pressure.

BRIEF DESCRIPTION OF THE DRAWINGS

[0031] FIG. **1** is a schematic illustration of the upper torso of a human body showing the major arteries and veins and associated anatomy.

[0032] FIG. **2**A is a cross-sectional schematic illustration of the carotid sinus and baroreceptors within the vascular wall.

[0033] FIG. **2**B is a schematic illustration of baroreceptors within the vascular wall and the baroreflex system.

[0034] FIG. **3** is a schematic illustration of a baroreceptor activation system in accordance with the present invention.

[0035] FIGS. **4**A and **4**B are schematic illustrations of a baroreceptor activation device in the form of an implantable extraluminal conductive structure which electrically induces a baroreceptor signal in accordance with an embodiment of the present invention.

[0036] FIGS. **5**A-**5**F are schematic illustrations of various possible arrangements of electrodes around the carotid sinus for extravascular electrical activation embodiments.

[0037] FIG. **6** is a schematic illustration of a serpentine shaped electrode for extravascular electrical activation embodiments.

[0038] FIG. **7** is a schematic illustration of a plurality of electrodes aligned orthogonal to the direction of wrapping around the carotid sinus for extravascular electrical activation embodiments.

[0039] FIGS. **8-11** are schematic illustrations of various multi-channel electrodes for extravascular electrical activation embodiments.

[0040] FIG. **12** is a schematic illustration of an extravascular electrical activation device

[0041] FIG. **13** is a schematic illustration of an alternative extravascular electrical activation device including a plurality of ribs and a spine.

[0042] FIG. **14** is a schematic illustration of an electrode assembly for extravascular electrical activation embodiments.

[0043] FIG. **15** is a schematic illustration of a fragment of an alternative cable for use with an electrode assembly such as shown in FIG. **14**.

[0044] FIG. **16** illustrates a foil strain gauge for measuring expansion force of a carotid artery or other blood vessel.

[0045] FIG. **17** illustrates a transducer which is adhesively connected to the wall of an artery.

[0046] FIG. **18** is a cross-sectional view of the transducer of FIG. **17**.

[0047] FIG. **19** illustrates a first exemplary electrode assembly having an elastic base and plurality of attachment tabs.

[0048] FIG. **20** is a more detailed illustration of the electrode-carrying surface of the electrode assembly of FIG. **19**.

[0049] FIG. **21** is a detailed illustration of electrode coils which are present in an elongate lead of the electrode assembly of FIG. **19**.

[0050] FIG. **22** is a detailed view of the electrode-carrying surface of an electrode assembly similar to that shown in FIG. **20**, except that the electrodes have been flattened.

[0051] FIG. **23** is a cross-sectional view of the electrode structure of FIG. **22**.

[0052] FIG. **24** illustrates the transition between the flattened and non-flattened regions of the electrode coil of the electrode assembly FIG. **20**.

[0053] FIG. **25** is a cross-sectional view taken along the line **25-25** of FIG. **24**.

[0054] FIG. **26** is a cross-sectional view taken along the line **26-26** of FIG. **24**.

[0055] FIG. **28** illustrates the electrode assembly of FIG. **27** wrapped around the common carotid artery near the carotid bifurcation.

[0056] FIG. **29** illustrates the electrode assembly of FIG. **27** wrapped around the internal carotid artery.

[0057] FIG. **30** is similar to FIG. **29**, but with the carotid bifurcation having a different geometry.

[0058] FIG. **31** illustrates an arterial pressure signal, an ECG signal and a control/output signal as a function of time.

DETAILED DESCRIPTION OF THE INVENTION

[0059] The following detailed description should be read with reference to the drawings in which similar elements in different drawings are numbered the same. The drawings, which are not necessarily to scale, depict illustrative embodiments and are not intended to limit the scope of the invention.

[0060] To better understand the present invention, it may be useful to explain some of the basic vascular anatomy associated with the cardiovascular system. Refer to FIG. **1** which is a schematic illustration of the upper torso of a human body **10** showing some of the major arteries and veins of the cardiovascular system. The left ventricle of the heart **11** pumps oxygenated blood up into the aortic arch **12**. The right subclavian artery **13**, the right common carotid artery **14**, the left common carotid artery **15** and the left subclavian artery **16** branch off the aortic arch **12** proximal of the descending thoracic aorta **17**. Although relatively short, a distinct vascular segment referred to as the brachiocephalic artery **22** connects the right subclavian artery **13** and the right common carotid artery **14** to the aortic arch **12**. The right carotid artery **14** bifurcates into the right external carotid artery **18** and the right internal carotid artery **19** at the right carotid sinus **20**. Although not shown for purposes of clarity only, the left carotid artery **15** similarly bifurcates into the left external carotid artery and the left internal carotid artery at the left carotid sinus.

[0061] From the aortic arch **12**, oxygenated blood flows into the carotid arteries **18/19** and the subclavian arteries **13/16**. From the carotid arteries **18/19**, oxygenated blood circulates through the head and cerebral vasculature and oxygen depleted blood returns to the heart **11** by way of the jugular veins, of which only the right internal jugular vein **21** is shown for sake of clarity. From the subclavian arteries **13/16**, oxygenated blood circulates through the upper peripheral vasculature and oxygen depleted blood returns to the heart by way of the subclavian veins, of which only the right subclavian vein **23** is shown, also for sake of clarity. The heart **11** pumps the oxygen depleted blood through the pulmonary system where it is reoxygenated. The re-oxygenated blood returns to the heart **11** which pumps the re-oxygenated blood into the aortic arch as described above, and the cycle repeats.

[0062] Within the arterial walls of the aortic arch **12**, common carotid arteries **14/15** (near the right carotid sinus **20** and left carotid sinus), subclavian arteries **13/16** and brachiocephalic artery **22** there are baroreceptors **30**. For example, as best seen in FIG. **2**A, baroreceptors **30** reside within the vascular walls of the carotid sinus **20**. Baroreceptors **30** are a type of stretch receptor used by the body to sense blood pressure. An increase in blood pressure causes the arterial wall to stretch, and a decrease in blood pressure causes the arterial wall to return to its original size. Such a cycle is repeated with each beat of the heart. Because baroreceptors **30** are located within the arterial wall, they are able to sense deformation of the adjacent tissue, which is indicative of a change in blood pressure. The baroreceptors **30** located in the right carotid sinus **20**, the left carotid sinus and the aortic arch **12** play the most significant role in sensing blood pressure that affects the baroreflex system **50**, which is described in more detail with reference to FIG. **2**B.

[0063] Refer now to FIG. **2**B, which shows a schematic illustration of baroreceptors **30** disposed in a generic vascular wall **40** and a schematic flow chart of the baroreflex system **50**. Baroreceptors **30** are profusely distributed within the arterial walls **40** of the major arteries discussed previously, and generally form an arbor **32**. The baroreceptor arbor **32** comprises a plurality of baroreceptors **30**, each of which transmits baroreceptor signals to the brain **52** via nerve **38**. The baroreceptors **30** are so profusely distributed and arborized within the vascular wall **40** that discrete baroreceptor arbors **32** are not readily discernable. To this end, those skilled in the art will appreciate that the baroreceptors **30** shown in FIG. **2**B are primarily schematic for purposes of illustration and discussion.

[0064] Baroreceptor signals are used to activate a number of body systems which collectively may be referred to as the baroreflex system **50**. Baroreceptors **30** are connected to the brain **52** via the nervous system **51**. Thus, the brain **52** is able to detect changes in blood pressure, which is indicative of cardiac output. If cardiac output is insufficient to meet demand (i.e., the heart **11** is unable to pump sufficient blood), the baroreflex system **50** activates a number of body systems, including the heart **11**, kidneys **53**, vessels **54**, and other organs/tissues. Such activation of the baroreflex system **50** generally corresponds to an increase in neurohormonal activity. Specifically, the baroreflex system **50** initiates a neurohormonal sequence that signals the heart **11** to increase heart rate and increase contraction force in order to increase cardiac output, signals the kidneys **53** to increase blood volume by retaining sodium and water, and signals the vessels **54** to constrict to elevate blood pressure. The cardiac, renal and vascular responses increase blood pressure and cardiac output **55**, and thus increase the workload of the heart **11**. In a patient with heart failure, this further accelerates myocardial damage and exacerbates the heart failure state.

[0065] To address the problems of hypertension, heart failure, other cardiovascular disorders and renal disorders,

the present invention basically provides a number of devices, systems and methods by which the baroreflex system **50** is activated to reduce excessive blood pressure, autonomic nervous system activity and neurohormonal activation. In particular, the present invention provides a number of devices, systems and methods by which baroreceptors **30** may be activated, thereby indicating an increase in blood pressure and signaling the brain **52** to reduce the body's blood pressure and level of sympathetic nervous system and neurohormonal activation, and increase parasympathetic nervous system activation, thus having a beneficial effect on the cardiovascular system and other body systems.

[**0066**] With reference to FIG. **3**, the present invention generally provides a system including a control system **60**, a baroreceptor activation device **70**, and a sensor **80** (optional), which generally operate in the following manner. The sensor(s) **80** optionally senses and/or monitors a parameter (e.g., cardiovascular function) indicative of the need to modify the baroreflex system and generates a signal indicative of the parameter. The control system **60** generates a control signal as a function of the received sensor signal. The control signal activates, deactivates or otherwise modulates the baroreceptor activation device **70**. Typically, activation of the device **70** results in activation of the baroreceptors **30**. Alternatively, deactivation or modulation of the baroreceptor activation device **70** may cause or modify activation of the baroreceptors **30**. The baroreceptor activation device **70** may comprise a wide variety of devices which utilize electrical means to activate baroreceptors **30**. Thus, when the sensor **80** detects a parameter indicative of the need to modify the baroreflex system activity (e.g., excessive blood pressure), the control system **60** generates a control signal to modulate (e.g. activate) the baroreceptor activation device **70** thereby inducing a baroreceptor **30** signal that is perceived by the brain **52** to be apparent excessive blood pressure. When the sensor **80** detects a parameter indicative of normal body function (e.g., normal blood pressure), the control system **60** generates a control signal to modulate (e.g., deactivate) the baroreceptor activation device **70**.

[**0067**] As mentioned previously, the baroreceptor activation device **70** may comprise a wide variety of devices which utilize electrical means to activate the baroreceptors **30**. The baroreceptor activation device **70** of the present invention comprises an electrode structure which directly activates one or more baroreceptors **30** by changing the electrical potential across the baroreceptors **30**. It is possible that changing the electrical potential across the tissue surrounding the baroreceptors **30** may cause the surrounding tissue to stretch or otherwise deform, thus mechanically activating the baroreceptors **30**, in which case the stretchable and elastic electrode structures of the present invention may provide significant advantages.

[**0068**] All of the specific embodiments of the electrode structures of the present invention are suitable for implantation, and are preferably implanted using a minimally invasive surgical approach. The baroreceptor activation device **70** may be positioned anywhere baroreceptors **30** are present. Such potential implantation sites are numerous, such as the aortic arch **12**, in the common carotid arteries **18**/**19** near the carotid sinus **20**, in the subclavian arteries **13**/**16**, in the brachiocephalic artery **22**, or in other arterial or venous locations. The electrode structures of the present invention will be implanted such that they are positioned on or over a vascular structure immediately adjacent the baroreceptors **30**. Preferably, the electrode structure of the baroreceptor activation device **70** is implanted near the right carotid sinus **20** and/or the left carotid sinus (near the bifurcation of the common carotid artery) and/or the aortic arch **12**, where baroreceptors **30** have a significant impact on the baroreflex system **50**. For purposes of illustration only, the present invention is described with reference to baroreceptor activation device **70** positioned near the carotid sinus **20**.

[**0069**] The optional sensor **80** is operably coupled to the control system **60** by electric sensor cable or lead **82**. The sensor **80** may comprise any suitable device that measures or monitors a parameter indicative of the need to modify the activity of the baroreflex system. For example, the sensor **80** may comprise a physiologic transducer or gauge that measures ECG, blood pressure (systolic, diastolic, average or pulse pressure), blood volumetric flow rate, blood flow velocity, blood pH, O2 or CO2 content, mixed venous oxygen saturation (SVO2), vasoactivity, nerve activity, tissue activity, body movement, activity levels, respiration, or composition. Examples of suitable transducers or gauges for the sensor **80** include ECG electrodes, a piezoelectric pressure transducer, an ultrasonic flow velocity transducer, an ultrasonic volumetric flow rate transducer, a thermodilution flow velocity transducer, a capacitive pressure transducer, a membrane pH electrode, an optical detector (SVO2), tissue impedance (electrical), or a strain gauge. Although only one sensor **80** is shown, multiple sensors **80** of the same or different type at the same or different locations may be utilized.

[**0070**] An example of an implantable blood pressure measurement device that may be disposed about a blood vessel is disclosed in U.S. Pat. No. 6,106,477 to Miesel et al., the entire disclosure of which is incorporated herein by reference. An example of a subcutaneous ECG monitor is available from Medtronic under the trade name REVEAL ILR and is disclosed in PCT Publication No. WO 98/02209, the entire disclosure of which is incorporated herein by reference. Other examples are disclosed in U.S. Pat. Nos. 5,987,352 and 5,331,966, the entire disclosures of which are incorporated herein by reference. Examples of devices and methods for measuring absolute blood pressure utilizing an ambient pressure reference are disclosed in U.S. Pat. No. 5,810,735 to Halperin et al., U.S. Pat. No. 5,904,708 to Goedeke, and PCT Publication No. WO 00/16686 to Brockway et al., the entire disclosures of which are incorporated herein by reference. The sensor **80** described herein may take the form of any of these devices or other devices that generally serve the same purpose.

[**0071**] The parameter information provided by sensor **80** may be used in a variety of ways to control therapy. As mentioned previously, absolute blood pressure (systolic, diastolic, or mean) or changes in absolute pressure may be used to control therapy. One potential limitation of absolute pressure is that it usually requires use of an external (ambient) pressure reference.

[**0072**] As an alternative to such correction techniques, surrogate measures for absolute blood pressure may be used. Examples include heart rate, pulse pressure dP/dt and others. One limitation of any individual surrogate measure is that it may not always correlate with blood pressure or a change in

blood pressure. For example, with heart rate, changes in heart rate during physical activity would tend to track changes in blood pressure (increased BP, increased HR). In addition, during shock or hemorrhage, heart rate may correlate inversely with blood pressure (decreased BP, increased HR).

[0073] The use of two or more parameters in combination may help determine the body's physiologic state more accurately than the use of a single parameter. For example, although absolute blood pressure monitoring may be difficult to implement in a single implanted device, pulse pressure (PP, the difference between systolic and diastolic BP, which does not require an ambient pressure reference) may be obtained more readily. By way of example, not limitation, both heart rate and pulse pressure may be monitored. The addition of pulse pressure to heart rate data may provide more meaningful information. For example, during physical activity, BP is increased, HR is increased, and PP is increased. During shock or hemorrhage, BP is decreased, HR is increased, and PP is decrease. Other examples include the use of an accelerometer to sense patient posture or an activity sensor to sense patient motion which may also provide useful information in combination with other physiological sensors an sensed parameters as descried above.

[0074] The relationships between HR, PP and BP under various circumstances may be derived and programmed into the control system **60** for use in feedback control. Alternatively, these relationships may be determined empirically and could even be patient-specific. This would also apply to other combinations of parameters.

[0075] Note that while sensed physiologic parameter information may be useful for closed loop control of the activation device **70**, this information may also be useful to the medical professional (physician, nurse, etc.) or the patient as an indication of the patient's condition. The medical professional, in turn, may utilize such information to assess or alter the treatment regimen.

[0076] The sensor **80** is preferably positioned in a chamber of the heart **11**, or in/on a major artery such as the aortic arch **12**, a common carotid artery **14**/**15**, a subclavian artery **13**/**16** or the brachiocephalic artery **22**, such that the parameter of interest may be readily ascertained. The sensor **80** may be disposed inside the body such as in or on an artery, a vein or a nerve (e.g. vagus nerve), or disposed outside the body, depending on the type of transducer or gauge utilized. The sensor **80** may be separate from the baroreceptor activation device **70** or combined therewith. For purposes of illustration only, the sensor **80** is shown positioned on the right subclavian artery **13**.

[0077] By way of example, the control system **60** includes a control block **61** comprising a processor **63** and a memory **62**. Control system **60** is connected to the sensor **80** by way of sensor cable **82**. Control system **60** is also connected to the baroreceptor activation device **70** by way of electric control cable **72**. Thus, the control system **60** receives a sensor signal from the sensor **80** by way of sensor cable **82**, and transmits a control signal to the baroreceptor activation device **70** by way of control cable **72**.

[0078] The system components **60**/**70**/**80** may be directly linked via cables **72**/**82** or by indirect means such as RF signal transceivers, ultrasonic transceivers or galvanic couplings. Examples of such indirect interconnection devices are disclosed in U.S. Pat. No. 4,987,897 to Funke and U.S. Pat. No. 5,113,859 to Funke, the entire disclosures of which are incorporated herein by reference.

[0079] The memory **62** may contain data related to the sensor signal, the control signal, and/or values and commands provided by the input device **64**. The memory **62** may also include software containing one or more algorithms defining one or more functions or relationships between the control signal and the sensor signal. The algorithm may dictate activation or deactivation control signals depending on the sensor signal or a mathematical derivative thereof. The algorithm may dictate an activation or deactivation control signal when the sensor signal falls below a lower predetermined threshold value, rises above an upper predetermined threshold value or when the sensor signal indicates a specific physiologic event. The algorithm may dynamically alter the threshold value as determined by the sensor input values.

[0080] The algorithm may also utilize or dictate auto initialization and auto capture techniques. As used herein, "capture" refers to the condition wherein the stimulus delivered by activation device **70** has an effect or the desired degree of effect on the modulation of the baroreflex system. Auto initialization and capture techniques automatically sample and monitor (via sensor **80**, for example) whether the stimulus regimen is having the desired effect. With this information, the auto capture feature of the algorithm may be used to detect the presence or absence of the desired stimulus effect, and if the desired effect is not present, modify (e.g., increase) the stimulus regimen to obtain the desired effect. Alternatively or in addition to this function, the auto capture feature of the algorithm may be used to minimize the stimulus to maintain the desired effect in order to conserve power and/or maintain long term efficacy as will be described in more detail hereinafter. Examples of auto capture techniques that may be implemented in the algorithm contained in memory **62** are disclosed in U.S. Pat. No. 5,324,310 to Greeinger et al., U.S. Pat. No. 5,134,997 to Bennett et al., and U.S. Pat. No. 5,861,012 to Stroebel, the entire disclosures of which are incorporated herein by reference.

[0081] The algorithm may also utilize or dictate different attack and decay curves. With this approach, the time interval required for the activation signal to change between a current setting and a subsequent setting may be made constant or variable, depending on the clinical status of the patient and the corresponding needs of the patient to modify the stimulus regimen. It is contemplated that varying the "rate" of the activation signal according to the present invention will encompass both varying the frequency of the signal (including monophasic or biphasic signals at predetermined/averaged current or voltage levels), as well as varying the amplitude or intensity of the signal over a period of time (whether signals are delivered at a constant or pulsed basis). the rate at which the stimulus is turned on or otherwise increased ay be referred to as the "attack" curve, and the rate at which the stimulus is turned off or otherwise decreased may be referred to as the "decay" curve. The attack and decay curves may be linear or non-linear (e.g., logarithmic). Examples of such attack and decay curves that may be implemented in the algorithm contained in memory **62** are disclosed in U.S. Pat. No. 5,134,997 to Bennett et al.,

U.S. Pat. No. 5,154,170 to Bennett et al., and U.S. Pat. No. 5,158,078 to Bennett et al. the entire disclosures of which are incorporated herein by reference.

[0082] As mentioned previously, the baroreceptor activation device **70** activates baroreceptors **30** electrically, optionally in combination with mechanical, thermal, chemical, biological or other co-activation. In some instances, the control system **60** includes a driver **66** to provide the desired power mode for the baroreceptor activation device **70**. For example, the driver **66** may comprise a power amplifier or the like and the cable **72** may comprise electrical lead(s). In other instances, the driver **66** may not be necessary, particularly if the processor **63** generates a sufficiently strong electrical signal for low level electrical actuation of the baroreceptor activation device **70**.

[0083] The control system **60** may operate as a closed loop utilizing feedback from the sensor **80**, or other sensors, such as heart rate sensors which may be incorporated or the electrode assembly, or as an open loop utilizing reprogramming commands received by input device **64**. The closed loop operation of the control system **60** preferably utilizes some feedback from the transducer **80**, but may also operate in an open loop mode without feedback. Programming commands received by the input device **64** may directly influence the control signal, the output activation parameters, or may alter the software and related algorithms contained in memory **62**. The treating physician and/or patient may provide commands to input device **64**. Display **65** may be used to view the sensor signal, control signal and/or the software/data contained in memory **62**.

[0084] The control signal generated by the control system **60** may be continuous, periodic, alternating, episodic or a combination thereof, as dictated by an algorithm contained in memory **62**. Continuous control signals include a constant pulse, a constant train of pulses, a triggered pulse and a triggered train of pulses. Examples of periodic control signals include each of the continuous control signals described above which have a designated start time (e.g., beginning of each period as designated by minutes, hours, or days in combinations of) and a designated duration (e.g., seconds, minutes, hours, or days in combinations of). Examples of alternating control signals include each of the continuous control signals as described above which alternate between the right and left output channels. Examples of episodic control signals include each of the continuous control signals described above which are triggered by an episode (e.g., activation by the physician/patient, an increase/decrease in blood pressure above a certain threshold, heart rate above/below certain levels, etc.).

[0085] The stimulus regimen governed by the control system **60** may be selected to promote long term efficacy. It is theorized that uninterrupted or otherwise unchanging activation of the baroreceptors **30** may result in the baroreceptors and/or the baroreflex system becoming less responsive over time, thereby diminishing the long term effectiveness of the therapy. Therefore, the stimulus regimen maybe selected to activate, deactivate or otherwise modulate the baroreceptor activation device **70** in such a way that therapeutic efficacy is maintained preferably for years.

[0086] In addition to maintaining therapeutic efficacy over time, the stimulus regimens of the present invention may be selected reduce power requirement/consumption of the system **60**. As will be described in more detail hereinafter, the stimulus regimen may dictate that the baroreceptor activation device **70** be initially activated at a relatively higher energy and/or power level, and subsequently activated at a relatively lower energy and/or power level. The first level attains the desired initial therapeutic effect, and the second (lower) level sustains the desired therapeutic effect long term. By reducing the energy and/or power levels after the desired therapeutic effect is initially attained, the energy required or consumed by the activation device **70** is also reduced long term. This may correlate into systems having greater longevity and/or reduced size (due to reductions in the size of the power supply and associated components).

[0087] Another advantage of the stimulus regimens of the present invention is the reduction of unwanted collateral tissue stimulation. As mentioned above, the stimulus regimen may dictate that the baroreceptor activation device **70** be initially activated at a relatively higher energy and/or power level to attain the desired effect, and subsequently activated at a relatively lower energy and/or power level to maintain the desired effect. By reducing the output energy and/or power level, the stimulus may not travel as far from the target site, thereby reducing the likelihood of inadvertently stimulating adjacent tissues such as muscles in the neck and head.

[0088] Such stimulus regimens may be applied to all baroreceptor activation embodiments described herein. In addition to baroreceptor activation devices **70**, such stimulus regimens may be applied to the stimulation of the carotid sinus nerves or other nerves affecting the baroreflex system. In particular, the stimulus regimens described herein may be applied to baropacing (i.e., electrical stimulation of the carotid sinus nerve), which has been proposed to reduce blood pressure and the workload of the heart in the treatment of high blood pressure and angina. For example, the stimulus regimens of the present invention may be applied to the baropacing system disclosed in U.S. Pat. No. 6,073,048 to Kieval et al., the entire disclosure of which is incorporated herein by reference.

[0089] The stimulus regimen may be described in terms of the control signal and/or the output signal from the baroreceptor activation device **70**. Generally speaking, changes in the control signal result in corresponding changes in the output of the baroreceptor activation device **70** which affect corresponding changes in the baroreceptors **30**. The correlation between changes in the control signal and changes in the baroreceptor activation device **70** may be proportional or disproportional, direct or indirect (inverse), or any other known or predictable mathematical relationship. For purposes of illustration only, the stimulus regimen may be described herein in such a way that assumes the output of the baroreceptor activation device **70** is directly proportional to the control signal.

[0090] A first general approach for a stimulus regimen which promotes long term efficacy and reduces power requirements/consumption involves generating a control signal to cause the baroreceptor activation device **70** to have a first output level of relatively higher energy and/or power, and subsequently changing the control signal to cause the baroreceptor activation device **70** to have a second output level of relatively lower energy and/or power. The first output level may be selected and maintained for sufficient

time to attain the desired initial effect (e.g., reduced heart rate and/or blood pressure), after which the output level may be reduced to the second level for sufficient time to sustain the desired effect for the desired period of time.

[0091] For example, if the first output level has a power and/or energy value of X1, the second output level may have a power and/or energy value of X2, wherein X2 is less than X1. In some instances, X2 may be equal to zero, such that the first level is "on" and the second level is "off". It is recognized that power and energy refer to two different parameters, and in some cases, a change in one of the parameters (power or energy) may not correlate to the same or similar change in the other parameter. In the present invention, it is contemplated that a change in one or both of the parameters may be suitable to obtain the desired result of promoting long term efficacy.

[0092] It is also contemplated that more than two levels may be used. Each further level may increase the output energy or power to attain the desired effect, or decrease the output energy or power to retain the desired effect. For example, in some instances, it may be desirable to have further reductions in the output level if the desired effect may be sustained at lower power or energy levels. In other instances, particularly when the desired effect is diminishing or is otherwise not sustained, it may be desirable to increase the output level until the desired effect is reestablished, and subsequently decrease the output level to sustain the effect.

[0093] The transition from each level may be a step function (e.g., a single step or a series of steps), a gradual transition over a period of time, or a combination thereof. In addition, the signal levels may be continuous, periodic, alternating, or episodic as discussed previously.

[0094] In electrical activation using a non modulated signal, the output (power or energy) level of the baroreceptor activation device **70** may be changed by adjusting the output signal voltage level, current level and/or signal duration. The output signal of the baroreceptor activation device **70** may be, for example, constant current or constant voltage. In electrical activation embodiments using a modulated signal, wherein the output signal comprises, for example, a series of pulses, several pulse characteristics may be changed individually or in combination to change the power or energy level of the output signal. Such pulse characteristics include, but are not limited to: pulse amplitude (PA), pulse frequency (PF), pulse width or duration (PW), pulse waveform (square, triangular, sinusoidal, etc.), pulse polarity (for bipolar electrodes) and pulse phase (monophasic, biphasic).

[0095] In electrical activation embodiments wherein the output signal comprises a pulse train, several other signal characteristics may be changed in addition to the pulse characteristics described above. As illustrated in FIG. **31**, the control or output signal **410** may comprise a pulse train **412** which generally includes a series of pulses **414** occurring in bursts **416**. Pulse train **412** characteristics which may be changed include, but are not limited to: burst amplitude (equal to pulse amplitude if constant within burst packet **416**), burst waveform (i.e., pulse amplitude variation within burst packet **416**), burst frequency (BF), and burst width or duration (BW). The signal **410** or a portion thereof (e.g., burst **416** within the pulse train **412**) may be triggered by any of the events discussed previously, or by a particular portion of the arterial pressure signal **450** or the ECG signal **460** (e.g., R wave as shown in FIG. **31**), or another physiologic timing indicator. If the signal **410** or a portion thereof is triggered, the triggering event may be changed and/or the delay from the triggering event may be changed.

[0096] FIGS. **4**A and **4**B show schematic illustrations of a baroreceptor activation device **300** in the form of an extravascular electrically conductive structure or electrode **302**. The electrode structure **302** may comprise a coil, braid or other structure capable of surrounding the vascular wall. Alternatively, the electrode structure **302** may comprise one or more electrode patches distributed around the outside surface of the vascular wall. Because the electrode structure **302** is disposed on the outside surface of the vascular wall, intravascular delivery techniques may not be practical, but minimally invasive surgical techniques will suffice. The extravascular electrode structure **302** may receive electrical signals directly from the driver **66** of the control system **60** by way of electrical lead **304**, or indirectly by utilizing an inductor (not shown) as described in co-pending commonly assigned application Ser. No. 10/402,393, the full disclosure of which is incorporated herein by reference.

[0097] The electrode structure **302** is connected to electric lead **304** which is connected to the driver **66** of the control system **60**. The driver **66**, in this embodiment, may comprise a power amplifier, pulse generator or the like to selectively deliver electrical control signals to electrode structure **302**. As mentioned previously, the electrical control signal generated by the driver **66** may be continuous, periodic, episodic or a combination thereof, as dictated by an algorithm contained in memory **62** of the control system **60**. Continuous control signals include a constant pulse, a constant train of pulses, a triggered pulse and a triggered train of pulses. Periodic control signals include each of the continuous control signals described above which have a designated start time and a designated duration. Episodic control signals include each of the continuous control signals described above which are triggered by an episode.

[0098] By selectively activating, deactivating or otherwise modulating the electrical control signal transmitted to the electrode structure **302**, electrical energy may be delivered to the vascular wall to activate the baroreceptors **30**. As discussed previously, activation of the baroreceptors **30** may occur directly or indirectly. In particular, the electrical signal delivered to the vascular wall **40** by the electrode structure **302** may cause the vascular wall to stretch or otherwise deform thereby indirectly activating the baroreceptors **30** disposed therein.

[0099] Refer now to FIGS. **5**A-**5**F which show schematic illustrations of various possible arrangements of electrodes around the carotid sinus **20** for extravascular electrical activation embodiments, such as baroreceptor activation device **300** described with reference to FIGS. **4**A and **4**B. The electrode designs illustrated and described hereinafter may be particularly suitable for connection to the carotid arteries at or near the carotid sinus, and may be designed to minimize extraneous tissue stimulation.

[0100] In FIGS. **5**A-**5**F, the carotid arteries are shown, including the common **14**, the external **18** and the internal **19** carotid arteries. The location of the carotid sinus **20** may be identified by a landmark bulge **21**, which is typically located on the internal carotid artery **19** just distal of the bifurcation, or extends across the bifurcation from the common carotid artery **14** to the internal carotid artery **19**.

[0101] The carotid sinus **20**, and in particular the bulge **21** of the carotid sinus, may contain a relatively high density of baroreceptors **30** (not shown) in the vascular wall. For this reason, it may be desirable to position the electrodes **302** of the activation device **300** on and/or around the sinus bulge **21** to maximize baroreceptor responsiveness and to minimize extraneous tissue stimulation.

[0102] It should be understood that the device **300** and electrodes **302** are merely schematic, and only a portion of which may be shown, for purposes of illustrating various positions of the electrodes **302** on and/or around the carotid sinus **20** and the sinus bulge **21**. In each of the embodiments described herein, the electrodes **302** may be monopolar, bipolar, or tripolar (anode-cathode-anode or cathode-anode-cathode sets). Specific extravascular electrode designs are described in more detail hereinafter.

[0103] In FIG. **5**A, the electrodes **302** of the extravascular electrical activation device **300** extend around a portion or the entire circumference of the sinus **20** in a circular fashion. Often, it would be desirable to reverse the illustrated electrode configuration in actual use. In FIG. **5**B, the electrodes **302** of the extravascular electrical activation device **300** extend around a portion or the entire circumference of the sinus **20** in a helical fashion. In the helical arrangement shown in FIG. **5**B, the electrodes **302** may wrap around the sinus **20** any number of times to establish the desired electrode **302** contact and coverage. In the circular arrangement shown in FIG. **5**A, a single pair of electrodes **302** may wrap around the sinus **20**, or a plurality of electrode pairs **302** may be wrapped around the sinus **20** as shown in FIG. **5**C to establish more electrode **302** contact and coverage.

[0104] The plurality of electrode pairs **302** may extend from a point proximal of the sinus **20** or bulge **21**, to a point distal of the sinus **20** or bulge **21** to ensure activation of baroreceptors **30** throughout the sinus **20** region. The electrodes **302** may be connected to a single channel or multiple channels as discussed in more detail hereinafter. The plurality of electrode pairs **302** may be selectively activated for purposes of targeting a specific area of the sinus **20** to increase baroreceptor responsiveness, or for purposes of reducing the exposure of tissue areas to activation to maintain baroreceptor responsiveness long term.

[0105] In FIG. **5**D, the electrodes **302** extend around the entire circumference of the sinus **20** in a criss cross fashion. The criss cross arrangement of the electrodes **302** establishes contact with both the internal **19** and external **18** carotid arteries around the carotid sinus **20**. Similarly, in FIG. **5**E, the electrodes **302** extend around all or a portion of the circumference of the sinus **20**, including the internal **19** and external **18** carotid arteries at the bifurcation, and in some instances the common carotid artery **14**. In FIG. **5**F, the electrodes **302** extend around all or a portion of the circumference of the sinus **20**, including the internal **19** and external **18** carotid arteries distal of the bifurcation. In FIGS. **5**E and **5**F, the extravascular electrical activation devices **300** are shown to include a substrate or base structure **306** which may encapsulate and insulate the electrodes **302** and may provide a means for attachment to the sinus **20** as described in more detail hereinafter.

[0106] From the foregoing discussion with reference to FIGS. **5**A-**5**F, it should be apparent that there are a number of suitable arrangements for the electrodes **302** of the activation device **300**, relative to the carotid sinus **20** and associated anatomy. In each of the examples given above, the electrodes **302** are wrapped around a portion of the carotid structure, which may require deformation of the electrodes **302** from their relaxed geometry (e.g., straight). To reduce or eliminate such deformation, the electrodes **302** and/or the base structure **306** may have a relaxed geometry that substantially conforms to the shape of the carotid anatomy at the point of attachment. In other words, the electrodes **302** and the base structure or backing **306** may be pre shaped to conform to the carotid anatomy in a substantially relaxed state. Alternatively, the electrodes **302** may have a geometry and/or orientation that reduces the amount of electrode **302** strain. Optionally, as described in more detail below, the backing or base structure **306** may be elastic or stretchable to facilitate wrapping of and conforming to the carotid sinus or other vascular structure.

[0107] For example, in FIG. **6**, the electrodes **302** are shown to have a serpentine or wavy shape. The serpentine shape of the electrodes **302** reduces the amount of strain seen by the electrode material when wrapped around a carotid structure. In addition, the serpentine shape of the electrodes increases the contact surface area of the electrode **302** with the carotid tissue. As an alternative, the electrodes **302** may be arranged to be substantially orthogonal to the wrap direction (i.e., substantially parallel to the axis of the carotid arteries) as shown in FIG. **7**. In this alternative, the electrodes **302** each have a length and a width or diameter, wherein the length is substantially greater than the width or diameter. The electrodes **302** each have a longitudinal axis parallel to the length thereof, wherein the longitudinal axis is orthogonal to the wrap direction and substantially parallel to the longitudinal axis of the carotid artery about which the device **300** is wrapped. As with the multiple electrode embodiments described previously, the electrodes **302** may be connected to a single channel or multiple channels as discussed in more detail hereinafter.

[0108] Refer now to FIGS. **8**-**11** which schematically illustrate various multi-channel electrodes for the extravascular electrical activation device **300**. FIG. **8** illustrates a six (6) channel electrode assembly including six (6) separate elongate electrodes **302** extending adjacent to and parallel with each other. The electrodes **302** are each connected to multi-channel cable **304**. Some of the electrodes **302** may be common, thereby reducing the number of conductors necessary in the cable **304**.

[0109] Base structure or substrate **306** may comprise a flexible and electrically insulating material suitable for implantation, such as silicone, perhaps reinforced with a flexible material such as polyester fabric. The base **306** may have a length suitable to wrap around all (360.degree.) or a portion (i.e., less than 360.degree.) of the circumference of one or more of the carotid arteries adjacent the carotid sinus **20**. The electrodes **302** may extend around a portion (i.e., less than 360.degree. such as 270.degree., 180.degree. or 90.degree.) of the circumference of one or more of the carotid arteries adjacent the carotid sinus **20**. To this end, the electrodes **302** may have a length that is less than (e.g., 75%, 50% or 25%) the length of the base **206**. The electrodes **302** may be parallel, orthogonal or oblique to the length of the base **306**, which is generally orthogonal to the axis of the carotid artery to which it is disposed about. Preferably, the base structure or backing will be elastic (i.e., stretchable),

typically being composed of at least in part of silicone, latex, or other elastomer. If such elastic structures are reinforced, the reinforcement should be arranged so that it does not interfere with the ability of the base to stretch and conform to the vascular surface.

[0110] The electrodes **302** may comprise round wire, rectangular ribbon or foil formed of an electrically conductive and radiopaque material such as platinum. The base structure **306** substantially encapsulates the electrodes **302**, leaving only an exposed area for electrical connection to extravascular carotid sinus tissue. For example, each electrode **302** may be partially recessed in the base **206** and may have one side exposed along all or a portion of its length for electrical connection to carotid tissue. Electrical paths through the carotid tissues may be defined by one or more pairs of the elongate electrodes **302**.

[0111] In all embodiments described with reference to FIGS. **8-11**, the multi-channel electrodes **302** may be selectively activated for purposes of mapping and targeting a specific area of the carotid sinus **20** to determine the best combination of electrodes **302** (e.g., individual pair, or groups of pairs) to activate for maximum baroreceptor responsiveness, as described elsewhere herein. In addition, the multi-channel electrodes **302** may be selectively activated for purposes of reducing the exposure of tissue areas to activation to maintain long term efficacy as described, as described elsewhere herein. For these purposes, it may be useful to utilize more than two (2) electrode channels. Alternatively, the electrodes **302** may be connected to a single channel whereby baroreceptors are uniformly activated throughout the sinus **20** region.

[0112] An alternative multi-channel electrode design is illustrated in FIG. **9**. In this embodiment, the device **300** includes sixteen (16) individual electrode pads **302** connected to 16 channel cable **304** via 4 channel connectors **303**. In this embodiment, the circular electrode pads **302** are partially encapsulated by the base structure **306** to leave one face of each button electrode **302** exposed for electrical connection to carotid tissues. With this arrangement, electrical paths through the carotid tissues may be defined by one or more pairs (bipolar) or groups (tripolar) of electrode pads **302**.

[0113] A variation of the multi-channel pad type electrode design is illustrated in FIG. **10**. In this embodiment, the device **300** includes sixteen (16) individual circular pad electrodes **302** surrounded by sixteen (16) rings **305**, which collectively may be referred to as concentric electrode pads **302/305**. Pad electrodes **302** are connected to 17 channel cable **304** via 4 channel connectors **303**, and rings **305** are commonly connected to 17 channel cable **304** via a single channel connector **307**. In this embodiment, the circular shaped electrodes **302** and the rings **305** are partially encapsulated by the base structure **306** to leave one face of each pad electrode **302** and one side of each ring **305** exposed for electrical connection to carotid tissues. As an alternative, two rings **305** may surround each electrode **302**, with the rings **305** being commonly connected. With these arrangements, electrical paths through the carotid tissues may be defined between one or more pad electrode **302**/ring **305** sets to create localized electrical paths.

[0114] Another variation of the multi-channel pad electrode design is illustrated in FIG. **11**. In this embodiment, the device **300** includes a control IC chip **310** connected to 3 channel cable **304**. The control chip **310** is also connected to sixteen (16) individual pad electrodes **302** via 4 channel connectors **303**. The control chip **310** permits the number of channels in cable **304** to be reduced by utilizing a coding system. The control system **60** sends a coded control signal which is received by chip **310**. The chip **310** converts the code and enables or disables selected electrode **302** pairs in accordance with the code.

[0115] For example, the control signal may comprise a pulse wave form, wherein each pulse includes a different code. The code for each pulse causes the chip **310** to enable one or more pairs of electrodes, and to disable the remaining electrodes. Thus, the pulse is only transmitted to the enabled electrode pair(s) corresponding to the code sent with that pulse. Each subsequent pulse would have a different code than the preceding pulse, such that the chip **310** enables and disables a different set of electrodes **302** corresponding to the different code. Thus, virtually any number of electrode pairs may be selectively activated using control chip **310**, without the need for a separate channel in cable **304** for each electrode **302**. By reducing the number of channels in cable **304**, the size and cost thereof may be reduced.

[0116] Optionally, the IC chip **310** may be connected to feedback sensor **80**, taking advantage of the same functions as described with reference to FIG. **3**. In addition, one or more of the electrodes **302** may be used as feedback sensors when not enabled for activation. For example, such a feedback sensor electrode may be used to measure or monitor electrical conduction in the vascular wall to provide data analogous to an ECG. Alternatively, such a feedback sensor electrode may be used to sense a change in impedance due to changes in blood volume during a pulse pressure to provide data indicative of heart rate, blood pressure, or other physiologic parameter.

[0117] Refer now to FIG. **12** which schematically illustrates an extravascular electrical activation device **300** including a support collar or anchor **312**. In this embodiment, the activation device **300** is wrapped around the internal carotid artery **19** at the carotid sinus **20**, and the support collar **312** is wrapped around the common carotid artery **14**. The activation device **300** is connected to the support collar **312** by cables **304**, which act as a loose tether. With this arrangement, the collar **312** isolates the activation device from movements and forces transmitted by the cables **304** proximal of the support collar, such as may be encountered by movement of the control system **60** and/or driver **66**. As an alternative to support collar **312**, a strain relief (not shown) may be connected to the base structure **306** of the activation device **300** at the juncture between the cables **304** and the base **306**. With either approach, the position of the device **300** relative to the carotid anatomy may be better maintained despite movements of other parts of the system.

[0118] In this embodiment, the base structure **306** of the activation device **300** may comprise molded tube, a tubular extrusion, or a sheet of material wrapped into a tube shape utilizing a suture flap **308** with sutures **309** as shown. The base structure **306** may be formed of a flexible and biocompatible material such as silicone, which may be reinforced with a flexible material such as polyester fabric available under the trade name DACRON.RTM. to form a composite structure. The inside diameter of the base structure **306** may

correspond to the outside diameter of the carotid artery at the location of implantation, for example 6 to 8 mm. The wall thickness of the base structure **306** may be very thin to maintain flexibility and a low profile, for example less than 1 mm. If the device **300** is to be disposed about a sinus bulge **21**, a correspondingly shaped bulge may be formed into the base structure for added support and assistance in positioning.

[**0119**] The electrodes **302** (shown in phantom) may comprise round wire, rectangular ribbon or foil, formed of an electrically conductive and radiopaque material such as platinum or platinum iridium. The electrodes may be molded into the base structure **306** or adhesively connected to the inside diameter thereof, leaving a portion of the electrode exposed for electrical connection to carotid tissues. The electrodes **302** may encompass less than the entire inside circumference (e.g., 300.degree.) of the base structure **306** to avoid shorting. The electrodes **302** may have any of the shapes and arrangements described previously. For example, as shown in FIG. **12**, two rectangular ribbon electrodes **302** may be used, each having a width of 1 mm spaced 1.5 mm apart.

[**0120**] The support collar **312** may be formed similarly to base structure **306**. For example, the support collar may comprise molded tube, a tubular extrusion, or a sheet of material wrapped into a tube shape utilizing a suture flap **315** with sutures **313** as shown. The support collar **312** may be formed of a flexible and biocompatible material such as silicone, which may be reinforced to form a composite structure. The cables **304** are secured to the support collar **312**, leaving slack in the cables **304** between the support collar **312** and the activation device **300**.

[**0121**] In all embodiments described herein, it may be desirable to secure the activation device to the vascular wall using sutures or other fixation means. For example, sutures **311** may be used to maintain the position of the electrical activation device **300** relative to the carotid anatomy (or other vascular site containing baroreceptors). Such sutures **311** may be connected to base structure **306**, and pass through all or a portion of the vascular wall. For example, the sutures **311** may be threaded through the base structure **306**, through the adventitia of the vascular wall, and tied. If the base structure **306** comprises a patch or otherwise partially surrounds the carotid anatomy, the corners and/or ends of the base structure may be sutured, with additional sutures evenly distributed therebetween. In order to minimize the propagation of a hole or a tear through the base structure **306**, a reinforcement material such as polyester fabric may be embedded in the silicone material. In addition to sutures, other fixation means may be employed such as staples or a biocompatible adhesive, for example.

[**0122**] Refer now to FIG. **13** which schematically illustrates an alternative extravascular electrical activation device **300** including one or more electrode ribs **316** interconnected by spine **317**. Optionally, a support collar **312** having one or more (non electrode) ribs **316** may be used to isolate the activation device **300** from movements and forces transmitted by the cables **304** proximal of the support collar **312**.

[**0123**] The ribs **316** of the activation device **300** are sized to fit about the carotid anatomy, such as the internal carotid artery **19** adjacent the carotid sinus **20**. Similarly, the ribs **316** of the support collar **312** may be sized to fit about the carotid anatomy, such as the common carotid artery **14** proximal of the carotid sinus **20**. The ribs **316** may be separated, placed on a carotid artery, and closed thereabout to secure the device **300** to the carotid anatomy.

[**0124**] Each of the ribs **316** of the device **300** includes an electrode **302** on the inside surface thereof for electrical connection to carotid tissues. The ribs **316** provide insulating material around the electrodes **302**, leaving only an inside portion exposed to the vascular wall. The electrodes **302** are coupled to the multi-channel cable **304** through spine **317**. Spine **317** also acts as a tether to ribs **316** of the support collar **312**, which do not include electrodes since their function is to provide support. The multi-channel electrode **302** functions discussed with reference to FIGS. **8-11** are equally applicable to this embodiment.

[**0125**] The ends of the ribs **316** may be connected (e.g., sutured) after being disposed about a carotid artery, or may remain open as shown. If the ends remain open, the ribs **316** may be formed of a relatively stiff material to ensure a mechanical lock around the carotid artery. For example, the ribs **316** may be formed of polyethylene, polypropylene, PTFE, or other similar insulating and biocompatible material. Alternatively, the ribs **316** may be formed of a metal such as stainless steel or a nickel titanium alloy, as long as the metallic material was electrically isolated from the electrodes **302**. As a further alternative, the ribs **316** may comprise an insulating and biocompatible polymeric material with the structural integrity provided by metallic (e.g., stainless steel, nickel titanium alloy, etc.) reinforcement. In this latter alternative, the electrodes **302** may comprise the metallic reinforcement.

[**0126**] Refer now to FIG. **14** which schematically illustrates a specific example of an electrode assembly for an extravascular electrical activation device **300**. In this specific example, the base structure **306** comprises a silicone sheet having a length of 5.0 inches, a thickness of 0.007 inches, and a width of 0.312 inches. The electrodes **302** comprise platinum ribbon having a length of 0.47 inches, a thickness of 0.0005 inches, and a width of 0.040 inches. The electrodes **302** are adhesively connected to one side of the silicone sheet **306**.

[**0127**] The electrodes **302** are connected to a modified bipolar endocardial pacing lead, available under the trade name CONIFIX from Innomedica (now BIOMEC Cardiovascular, Inc.), model number 501112. The proximal end of the cable **304** is connected to the control system **60** or driver **66** as described previously. The pacing lead is modified by removing the pacing electrode to form the cable body **304**. The MP35 wires are extracted from the distal end thereof to form two coils **318** positioned side by side having a diameter of about 0.020 inches. The coils **318** are then attached to the electrodes utilizing **316** type stainless steel crimp terminals laser welded to one end of the platinum electrodes **302**. The distal end of the cable **304** and the connection between the coils **318** and the ends of the electrodes **302** are encapsulated by silicone.

[**0128**] The cable **304** illustrated in FIG. **14** comprises a coaxial type cable including two coaxially disposed coil leads separated into two separate coils **318** for attachment to the electrodes **302**. An alternative cable **304** construction is illustrated in FIG. **15**. FIG. **15** illustrates an alternative cable

body **304** which may be formed in a curvilinear shape such as a sinusoidal configuration, prior to implantation. The curvilinear configuration readily accommodates a change in distance between the device **300** and the control system **60** or the driver **66**. Such a change in distance may be encountered during flexion and/or extension of the neck of the patient.

[**0129**] In this alternative embodiment, the cable body **304** may comprise two or more conductive wires **304***a* arranged coaxially or collinearly as shown. Each conductive wire **304***a* may comprise a multifilament structure of suitable conductive material such as stainless steel or MP35N. An insulating material may surround the wire conductors **304***a* individually and/or collectively. For purposes of illustration only, a pair of electrically conductive wires **304***a* having an insulating material surrounding each wire **304***a* individually is shown. The insulated wires **304***a* may be connected by a spacer **304***b* comprising, for example, an insulating material. An additional jacket of suitable insulating material may surround each of the conductors **304***a*. The insulating jacket may be formed to have the same curvilinear shape of the insulated wires **304***a* to help maintain the shape of the cable body **304** during implantation.

[**0130**] If a sinusoidal configuration is chosen for the curvilinear shape, the amplitude (A) may range from 1 mm to 10 mm, and preferably ranges from 2 mm to 3 mm. The wavelength (WL) of the sinusoid may range from 2 mm to 20 mm, and preferably ranges from 4 mm to 10 mm. The curvilinear or sinusoidal shape may be formed by a heat setting procedure utilizing a fixture which holds the cable **304** in the desired shape while the cable is exposed to heat. Sufficient heat is used to heat set the conductive wires **304***a* and/or the surrounding insulating material. After cooling, the cable **304** may be removed from the fixture, and the cable **304** retains the desired shape.

[**0131**] Refer now to FIGS. **16-18** which illustrate various transducers that may be mounted to the wall of a vessel such as a carotid artery **14** to monitor wall expansion or contraction using strain, force and/or pressure gauges. An example of an implantable blood pressure measurement device that may be disposed about a blood vessel is disclosed in U.S. Pat. No. 6,106,477 to Miesel et al., the entire disclosure of which is incorporated herein by reference. The output from such gauges may be correlated to blood pressure and/or heart rate, for example, and may be used to provide feedback to the control system **60** as described previously herein. In FIG. **16**, an implantable pressure measuring assembly comprises a foil strain gauge or force sensing resistor device **740** disposed about an artery such as common carotid artery **14**. A transducer portion **742** may be mounted to a silicone base or backing **744** which is wrapped around and sutured or otherwise attached to the artery **14**.

[**0132**] Alternatively, the transducer **750** may be adhesively connected to the wall of the artery **14** using a biologically compatible adhesive such as cyanoacrylate as shown in FIG. **17**. In this embodiment, the transducer **750** comprises a micro machined sensor (MEMS) that measures force or pressure. The MEMS transducer **750** includes a micro arm **752** (shown in section in FIG. **18**) coupled to a silicon force sensor contained over an elastic base **754**. A cap **756** covers the arm **752** a top portion of the base **754**. The base **754** include an interior opening creating access from the vessel wall **14** to the arm **752**. An incompressible gel **756** fills the space between the arm **752** and the vessel wall **14** such that force is transmitted to the arm upon expansion and contraction of the vessel wall. In both cases, changes in blood pressure within the artery cause changes in vessel wall stress which are detected by the transducer and which may be correlated with the blood pressure.

[**0133**] Refer now to FIGS. **19-21** which illustrate an alternative extravascular electrical activation device **700**, which, may also be referred to as an electrode cuff device or more generally as an "electrode assembly." Except as described herein and shown in the drawings, device **700** may be the same in design and function as extravascular electrical activation device **300** described previously.

[**0134**] As seen in FIGS. **19** and **20**, electrode assembly or cuff device **700** includes coiled electrode conductors **702/704** embedded in a flexible support **706**. In the embodiment shown, an outer electrode coil **702** and an inner electrode coil **704** are used to provide a pseudo tripolar arrangement, but other polar arrangements are applicable as well as described previously. The coiled electrodes **702/704** may be formed of fine round, flat or ellipsoidal wire such as 0.002 inch diameter round PtIr alloy wire wound into a coil form having a nominal diameter of 0.015 inches with a pitch of 0.004 inches, for example. The flexible support or base **706** may be formed of a biocompatible and flexible (preferably elastic) material such as silicone or other suitable thin walled elastomeric material having a wall thickness of 0.005 inches and a length (e.g., 2.95 inches) sufficient to surround the carotid sinus, for example.

[**0135**] Each turn of the coil in the contact area of the electrodes **702/704** is exposed from the flexible support **706** and any adhesive to form a conductive path to the artery wall. The exposed electrodes **702/704** may have a length (e.g., 0.236 inches) sufficient to extend around at least a portion of the carotid sinus, for example. The electrode cuff **700** is assembled flat with the contact surfaces of the coil electrodes **702/704** tangent to the inside plane of the flexible support **706**. When the electrode cuff **700** is wrapped around the artery, the inside contact surfaces of the coiled electrodes **702/704** are naturally forced to extend slightly above the adjacent surface of the flexible support, thereby improving contact to the artery wall.

[**0136**] The ratio of the diameter of the coiled electrodes **702/704** to the wire diameter is preferably large enough to allow the coil to bend and elongate without significant bending stress or torsional stress in the wire. Flexibility is a significant advantage of this design which allows the electrode cuff **700** to conform to the shape of the carotid artery and sinus, and permits expansion and contraction of the artery or sinus without encountering significant stress or fatigue. In particular, the flexible electrode cuff **700** may be wrapped around and stretched to conform to the shape of the carotid sinus and artery during implantation. This may be achieved without collapsing or distorting the shape of the artery and carotid sinus due to the compliance of the electrode cuff **700**. The flexible support **706** is able to flex and stretch with the conductor coils **702/704** because of the absence of fabric reinforcement in the electrode contact portion of the cuff **700**. By conforming to the artery shape, and by the edge of the flexible support **706** sealing against the artery wall, the amount of stray electrical field and extraneous stimulation will likely be reduced.

[0137] The pitch of the coil electrodes **702/704** may be greater than the wire diameter in order to provide a space between each turn of the wire to thereby permit bending without necessarily requiring axial elongation thereof. For example, the pitch of the contact coils **702/704** may be 0.004 inches per turn with a 0.002 inch diameter wire, which allows for a 0.002 inch space between the wires in each turn. The inside of the coil may be filled with a flexible adhesive material such as silicone adhesive which may fill the spaces between adjacent wire turns. By filling the small spaces between the adjacent coil turns, the chance of pinching tissue between coil turns is minimized thereby avoiding abrasion to the artery wall. Thus, the embedded coil electrodes **702/704** are mechanically captured and chemically bonded into the flexible support **706**. In the unlikely event that a coil electrode **702/704** comes loose from the support **706**, the diameter of the coil is large enough to be atraumatic to the artery wall. Preferably, the centerline of the coil electrodes **702/704** lie near the neutral axis of electrode cuff structure **700** and the flexible support **706** comprises a material with isotropic elasticity such as silicone in order to minimize the shear forces on the adhesive bonds between the coil electrodes **702/704** and the support **706**.

[0138] The electrode coils **702/704** are connected to corresponding conductive coils **712/714**, respectively, in an elongate lead **710** which is connected to the control system **60**. Anchoring wings **718** may be provided on the lead **710** to tether the lead **710** to adjacent tissue and minimize the effects or relative movement between the lead **710** and the electrode cuff **700**. As seen in FIG. **21**, the conductive coils **712/714** may be formed of 0.003 MP35N bifilar wires wound into 0.018 inch diameter coils which are electrically connected to electrode coils **702/704** by splice wires **716**. The conductive coils **712/714** may be individually covered by an insulating covering **718** such as silicone tubing and collectively covered by insulating covering **720**.

[0139] The conductive material of the electrodes **702/704** may be a metal as described above or a conductive polymer such as a silicone material filled with metallic particles such as Pt particles. In this latter embodiment, the polymeric electrodes may be integrally formed with the flexible support **706** with the electrode contacts comprising raised areas on the inside surface of the flexible support **706** electrically coupled to the lead **710** by wires or wire coils. The use of polymeric electrodes may be applied to other electrode design embodiments described elsewhere herein.

[0140] Reinforcement patches **708** such as DACRON-.RTM. fabric may be selectively incorporated into the flexible support **706**. For example, reinforcement patches **708** may be incorporated into the ends or other areas of the flexible support **706** to accommodate suture anchors. The reinforcement patches **708** provide points where the electrode cuff **700** may be sutured to the vessel wall and may also provide tissue in growth to further anchor the device **700** to the exterior of the vessel wall. For example, the fabric reinforcement patches **708** may extend beyond the edge of the flexible support **706** so that tissue in growth may help anchor the electrode assembly or cuff **700** to the vessel wall and may reduce reliance on the sutures to retain the electrode assembly **700** in place. As a substitute for or in addition to the sutures and tissue in growth, bioadhesives such as cyanoacrylate may be employed to secure the device **700** to the vessel wall. In addition, an adhesive incorporating conductive particles such as Pt coated micro spheres may be applied to the exposed inside surfaces of the electrodes **702/704** to enhance electrical conduction to the tissue and possibly limit conduction along one axis to limit extraneous tissue stimulation.

[0141] The reinforcement patches **708** may also be incorporated into the flexible support **706** for strain relief purposes and to help retain the coils **702/704** to the support **706** where the leads **710** attach to the electrode assembly **700** as well as where the outer coil **702** loops back around the inner coil **704**. Preferably, the patches **708** are selectively incorporated into the flexible support **706** to permit expansion and contraction of the device **700**, particularly in the area of the electrodes **702/704**. In particular, the flexible support **706** is only fabric reinforced in selected areas thereby maintaining the ability of the electrode cuff **700** to stretch.

[0142] Referring now to FIGS. **22-26**, the electrode assembly of FIGS. **19-21** can be modified to have "flattened" coil electrodes in the region of the assembly where the electrodes contact the extravascular tissue. As shown in FIG. **22**, an electrode-carrying surface **801** of the electrode assembly, is located generally between parallel reinforcement strips or tabs **808**. The flattened coil section **810** will generally be exposed on a lower surface **803** of the base **806** (FIG. **23**) and will be covered or encapsulated by a parylene or other polymeric structure or material **802** over an upper surface **805** thereof. The coil is formed with a generally circular periphery **809**, as best seen in FIGS. **24** and **26**, and may be mechanically flattened, typically over a silicone or other supporting insert **815**, as best seen in FIG. **25**. The use of the flattened coil structure is particularly beneficial since it retains flexibility, allowing the electrodes to bend, stretch, and flex together with the elastomeric base **806**, while also increasing the flat electrode area available to contact the extravascular surface.

[0143] Referring now to FIGS. **27-30**, an additional electrode assembly **900** constructed in accordance with the principles of the present invention will be described. Electrode assembly **900** comprises an electrode base, typically an elastic base **902**, typically formed from silicone or other elastomeric material, having an electrode-carrying surface **904** and a plurality of attachment tabs **906** (**906***a*, **906***b*, **906***c*, and **906***d*) extending from the electrode-carrying surface. The attachment tabs **906** are preferably formed from the same material as the electrode-carrying surface **904** of the base **902**, but could be formed from other elastomeric materials as well. In the latter case, the base will be molded, stretched or otherwise assembled from the various pieces. In the illustrated embodiment, the attachment tabs **906** are formed integrally with the remainder of the base **902**, i.e., typically being cut from a single sheet of the elastomeric material.

[0144] The geometry of the electrode assembly **900**, and in particular the geometry of the base **902**, is selected to permit a number of different attachment modes to the blood vessel. In particular, the geometry of the assembly **902** of FIG. **27** is intended to permit attachment to various locations on the carotid arteries at or near the carotid sinus and carotid bifurcation.

[0145] A number of reinforcement regions **910** (**910***a*, **910***b*, **910***c*, **910***d*, and **910***e*) are attached to different locations on the base **902** to permit suturing, clipping, stapling,

or other fastening of the attachment tabs **906** to each other and/or the electrode-carrying surface **904** of the base **902**. In the preferred embodiment intended for attachment at or around the carotid sinus, a first reinforcement strip **910***a* is provided over an end of the base **902** opposite to the end which carries the attachment tabs. Pairs of reinforcement strips **910***b* and **910***c* are provided on each of the axially aligned attachment tabs **906***a* and **906***b*, while similar pairs of reinforcement strips **910***d* and **910***e* are provided on each of the transversely angled attachment tabs **906***c* and **906***d*. In the illustrated embodiment, all attachment tabs will be provided on one side of the base, preferably emanating from adjacent corners of the rectangular electrode-carrying surface **904**.

[**0146**] The structure of electrode assembly **900** permits the surgeon to implant the electrode assembly so that the electrodes **920** (which are preferably stretchable, flat-coil electrodes as described in detail above), are located at a preferred location relative to the target baroreceptors. The preferred location may be determined, for example, as described in copending application Ser. No. 09/963,991, filed on Sep. 26, 2001, the full disclosure of which incorporated herein by reference.

[**0147**] Once the preferred location for the electrodes **920** of the electrode assembly **900** is determined, the surgeon may position the base **902** so that the electrodes **920** are located appropriately relative to the underlying baroreceptors. Thus, the electrodes **920** may be positioned over the common carotid artery CC as shown in FIG. **28**, or over the internal carotid artery IC, as shown in FIGS. **29** and **30**. In FIG. **28**, the assembly **900** may be attached by stretching the base **902** and attachment tabs **906***a* and **906***b* over the exterior of the common carotid artery. The reinforcement tabs **906***a* or **906***b* may then be secured to the reinforcement strip **910***a*, either by suturing, stapling, fastening, gluing, welding, or other well-known means. Usually, the reinforcement tabs **906***c* and **906***d* will be cut off at their bases, as shown at **922** and **924**, respectively.

[**0148**] In other cases, the bulge of the carotid sinus and the baroreceptors may be located differently with respect to the carotid bifurcation. For example, as shown in FIG. **29**, the receptors may be located further up the internal carotid artery IC so that the placement of electrode assembly **900** as shown in FIG. **28** will not work. The assembly **900**, however, may still be successfully attached by utilizing the transversely angled attachment tabs **906***c* and **906***d* rather than the central or axial tabs **906***a* and **906***b*. As shown in FIG. **29**, the lower tab **906***d* is wrapped around the common carotid artery CC, while the upper attachment tab **906***c* is wrapped around the internal carotid artery IC. The axial attachment tabs **906***a* and **906***b* will usually be cut off (at locations **926**), although neither of them could in some instances also be wrapped around the internal carotid artery IC. Again, the tabs which are used may be stretched and attached to reinforcement strip **910***a*, as generally described above.

[**0149**] Referring to FIG. **30**, in instances where the carotid bifurcation has less of an angle, the assembly **900** may be attached using the upper axial attachment tab **906***a* and be lower transversely angled attachment tab **906***d*. Attachment tabs **906***b* and **906***c* may be cut off, as shown at locations **928** and **930**, respectively. In all instances, the elastic nature of the base **902** and the stretchable nature of the electrodes **920** permit the desired conformance and secure mounting of the electrode assembly over the carotid sinus. It would be appreciated that these or similar structures would also be useful for mounting electrode structures at other locations in the vascular system.

[**0150**] In most activation device embodiments described herein, it may be desirable to incorporate anti-inflammatory agents (e.g., steroid eluting electrodes) such as described in U.S. Pat. No. 4,711,251 to Stokes, U.S. Pat. No. 5,522,874 to Gates and U.S. Pat. No. 4,972,848 to Di Domenico et al., the entire disclosures of which are incorporated herein by reference. Such agents reduce tissue inflammation at the chronic interface between the device (e.g., electrodes) and the vascular wall tissue, to thereby increase the efficiency of stimulus transfer, reduce power consumption, and maintain activation efficiency, for example.

[**0151**] Those skilled in the art will recognize that the present invention may be manifested in a variety of forms other than the specific embodiments described and contemplated herein. Accordingly, departures in form and detail may be made without departing from the scope and spirit of the present invention as described in the appended claims.

What is claimed is:

1. A baroreflex stimulator, comprising:

a pulse generator to provide a baroreflex stimulation signal through an electrode; and

a modulator to modulate the baroreflex stimulation signal based on a circadian rhythm template.

2. The stimulator of claim 1, wherein the baroreflex signal has a characteristic selected from the set of: an amplitude, a frequency and a desired morphology, and the modulator includes a modulator to modulate the characteristic based on the circadian rhythm template.

3. The stimulator of claim 1, wherein the circadian rhythm template includes a template selected from the set of a pre-programmed circadian rhythm template, a patient-specific circadian rhythm template, a mean arterial pressure template, a heart rate template, a stroke volume template, a cardiac output template, and a total peripheral resistance template.

4. The stimulator of claim 1, wherein the electrode includes an electrode adapted to stimulate baroreceptors in a vessel wall.

5. A baroreflex stimulator, comprising:

a pulse generator to provide a baroreflex stimulation signal through an electrode; and

means for modulating the baroreflex stimulation signal based on a circadian rhythm template.

6. The stimulator of claim 5, wherein the circadian rhythm template includes a template selected from the set of a pre-programmed circadian rhythm template, a patient-specific circadian rhythm template, a mean arterial pressure template, a heart rate template, a stroke volume template, a cardiac output template, and a total peripheral resistance template.

7. The stimulator of claim 5, wherein the baroreflex signal has a characteristic selected from the set of: an amplitude, a frequency, a burst frequency and a waveform and the means for modulating the baroreflex stimulation signal based on a circadian rhythm template includes means for modulating

the characteristic of the baroreflex stimulation signal based on a circadian rhythm template.

8. A method for operating an implantable medical device, comprising:

applying a baroreflex stimulation therapy using a baroreflex stimulator in the implantable medical device; and

modulating the baroreflex stimulation therapy based on a circadian rhythm template.

9. The method of claim 8, wherein modulating the baroreflex stimulation therapy includes modulating a characteristic of the baroreflex stimulation signal, wherein the characteristic is selected from the set of: an amplitude, a frequency, a burst frequency, and a waveform.

10. The method of claim 8, wherein the modulating the baroreflex stimulation therapy uses a circadian rhythm template that is a pre-programmed circadian rhythm template.

11. The method of claim 8, further comprising: sensing and recording parameters related to hypertension; and generating a patient-specific circadian rhythm template based on the recorded parameters, wherein the baroreflex stimulation therapy is modulated based on the patient-specific circadian rhythm template.

12. The method of claim 8, wherein the modulating the baroreflex stimulation therapy uses a circadian rhythm template that includes a template selected from the set of: a mean arterial pressure template, a heart rate template, a stroke volume template, a cardiac output template, and a total peripheral resistance template.

13. The method of claim 8, wherein applying baroreflex therapy includes stimulating a baroreceptor in a vessel wall.

14. A baroreflex stimulator, comprising:

a driver adapted to provide a control signal through a baroreceptor activation device; and

a controller to periodically modulate the control signal based on an algorithm.

15. A baroreflex stimulator, comprising:

a driver adapted to provide a control signal through a baroreceptor activation device; and

means for periodically modulating the control signal based on an algorithm.

16. A method for operating an implantable medical device, comprising:

applying a baroreflex stimulation therapy using a baroreceptor activation device in the implantable medical device; and

periodically modulating the baroreflex stimulation therapy based on an algorithm.

* * * * *