




(86) Date de dépôt PCT/PCT Filing Date: 2009/03/27
(87) Date publication PCT/PCT Publication Date: 2009/10/01
(45) Date de délivrance/Issue Date: 2015/03/03
(85) Entrée phase nationale/National Entry: 2010/08/06
(86) N° demande PCT/PCT Application No.: JP 2009/056321
(87) N° publication PCT/PCT Publication No.: 2009/119818
(30) Priorités/Priorities: 2008/03/28 (JP2008-088819);
2009/03/24 (JP2009-072961)

(51) Cl.Int./Int.Cl. *H04W 72/12* (2009.01),
H04W 72/04 (2009.01)
(72) Inventeurs/Inventors:
ISHII, HIROYUKI, JP;
UMESH, ANIL, JP
(73) Propriétaire/Owner:
NTT DOCOMO INC., JP
(74) Agent: OYEN WIGGS GREEN & MUTALA LLP

(54) Titre : PROCEDE DE SELECTION DE RESSOURCES RADIO, STATION MOBILE ET STATION DE BASE RADIO
(54) Title: RADIO RESOURCE SELECTING METHOD, MOBILE STATION AND RADIO BASE STATION



(57) Abrégé/Abstract:

A mobile communication method according to the present invention includes the steps of; (A) notifying, from a radio base station (eNB) to a mobile station (UE), a first cycle and information on the uplink radio resource; and (B) determining, at the mobile station (UE), a first allocation starting time, receiving a downlink data via a downlink radio resource and transmitting an acknowledgement information via an uplink radio resource at and after the first allocation starting time, when receiving a fixed allocation signal from the radio base station (UE). In the step (B), the uplink radio resource is adjusted by an adjustment signal included in the fixed allocation signal and the acknowledgement information is transmitted via the adjusted uplink radio resource.

ABSTRACT

A mobile communication method according to the present invention includes the steps of; (A) notifying, from a radio
5 base station (eNB) to a mobile station (UE), a first cycle and information on the uplink radio resource; and (B) determining, at the mobile station (UE), a first allocation starting time, receiving a downlink data via a downlink radio resource and transmitting an acknowledgement information via an uplink radio
10 resource at and after the first allocation starting time, when receiving a fixed allocation signal from the radio base station (UE). In the step (B), the uplink radio resource is adjusted by an adjustment signal included in the fixed allocation signal and the acknowledgement information is transmitted via the
15 adjusted uplink radio resource.

DESCRIPTION

RADIO RESOURCE SELECTING METHOD, MOBILE STATION AND RADIO BASE
STATION

5 TECHNICAL FIELD

[0001]

The present invention relates to a radio resource
selecting method in which a mobile station receives downlink
data, transmitted from a radio base station, by using a downlink
10 radio resource fixedly allocated in first cycles starting from
a first allocation starting time, and transmits acknowledgement
information for the downlink data by using a fixedly allocated
uplink radio resource, and relates to the mobile station and
the radio base station.

15

BACKGROUND ART

[0002]

A communication method as a successor of the W-CDMA and
the HSDPA, namely, the Long Term Evolution (LTE) has been
20 considered by the W-CDMA standardization organization 3GPP, and
the specification setting work is underway.

[0003]

As a radio access method of the LTE, use of the OFDMA in
the downlink and the SC-FDMA (Single-Carrier Frequency Division
25 Multiple Access) in the uplink is under consideration.

[0004]

The OFDMA is a method for dividing a frequency band into
a plurality of narrow frequency bands (sub-carriers) and
transmitting data loaded on the respective divided frequency

bands. In this method, high-speed transmission can be achieved and frequency utilization efficiency can be improved by arranging sub-carriers densely on the frequency bands in such a manner that the sub-carriers partially overlap but do not
5 interfere with each other.

[0005]

The SC-FDMA is a transmission method which can reduce interference between terminals by dividing a frequency band and transmitting data by using frequency bands different among
10 plural terminals. The SC-FDMA has a feature of less fluctuation in the transmission power, which can achieve low power consumption of terminals and wide coverage.

[0006]

The LTE is a system in which a plurality of mobile stations
15 communicate with each other by sharing one or more physical channels in both uplink and downlink.

[0007]

A channel shared by a plurality of mobile stations is generally called a shared channel, which is, in the LTE system,
20 a "Physical Uplink Shared Channel (PUSCH)" in the uplink and a "Physical Downlink Shared Channel (PDSCH)" in the downlink.

[0008]

Also, such a shared channel is, as a transport channel, an "Uplink Shared Channel (UL-SCH)" in the uplink and a
25 "Downlink Shared Channel (DL-SCH)" in the downlink.

[0009]

In such a communication system using shared channels described above, it is necessary to select which mobile station UE the shared channel is to be allocated to, and to signal

information indicating that the shared channel is allocated to the selected mobile station UE, for each sub-frame (1ms, in the LTE).

[0010]

5 In the LTE, a control channel used for the signaling is called the "Physical Downlink Control Channel (PDCCH)" or "Downlink L1/L2 Control Channel (DL L1/L2 Control Channel)".

[0011]

10 Meanwhile, the processing for each sub-frame of selecting which mobile station UE the shared channel is to be allocated to is generally called the "scheduling". In this case, the processing may also be called the "dynamic scheduling", because the mobile station UE to which the shared channel is allocated is dynamically selected for each sub-frame. Furthermore, 15 "allocating the shared channel" described above may be alternatively expressed as "allocating a radio resource for the shared channel".

[0012]

20 Information of the physical downlink control channel includes, for example, the "downlink scheduling information", "the uplink scheduling grant", and the like.

[0013]

25 The downlink scheduling information includes, for example, downlink resource block allocation information on the downlink shared channel, ID of UE, the number of streams, information on the precoding vector, data size, modulation scheme, information on the HARQ (hybrid automatic repeat request), and the like.

[0014]

Meanwhile, the "uplink scheduling grant" includes, for example, uplink resource block allocation information on the uplink shared channel, ID of UE, data size, modulation scheme, uplink transmission power information, information on demodulation reference signal in the uplink MIMO, and the like.
[0015]

Note that, the "downlink scheduling information" and the "uplink scheduling grant" described above may be collectively referred to as "downlink control information (DCI)".
10 [0016]

In the LTE system, the HARQ is applied to a communication using the shared channel described above. For example, on the downlink, the mobile station UE decodes the downlink shared channel and sends the radio base station eNB acknowledgement information (ACK/NACK) based on the decoding result (CRC check result) using the physical uplink control channel (PUCCH).
15 [0017]

Then, the radio base station eNB performs retransmission control according to a content of the acknowledgement information, which is expressed either with a positive response (ACK) indicating that the transmitted signal is received properly or a negative response (NACK) indicating that the transmitted signal is not received properly.
20 [0018]

FIG. 8 shows the downlink dynamic scheduling and the HARQ processing in the LTE mobile communication system described above.
25 [0019]

In the sub-frame #3, the radio base station eNB transmits

downlink scheduling information via the PDCCH and downlink data via the PDSCH to the mobile station UE.

[0020]

Then, the mobile station UE receives downlink data via PDSCH on the basis of the downlink scheduling information received via PDCCH.

[0021]

In the sub-frame #7, the mobile station UE transmits the acknowledgement information for the downlink data using PUCCH, and the radio base station eNB receives the acknowledgement information (ACK/NACK) mapped to the PUCCH.

[0022]

The radio resource of the PDSCH described above is dynamically allocated as being notified by the PDCCH. Also, the radio resource of PUCCH described above is associated with the radio resource number of PDCCH described above. Dynamic allocation of such radio resource of PDCCH also results in dynamic allocation of such radio resource of PUCCH.

[0023]

That is, in the normal downlink scheduling of the LTE mobile communication system, the radio base station eNB is configured to dynamically allocate a downlink radio resource and an uplink radio resource to the mobile station UE through the PDCCH, the downlink radio resource being for transmitting downlink data to the mobile station UE while the uplink radio resource being for transmitting acknowledgement information for the downlink data.

[0024]

Furthermore, in the dynamic scheduling described above,

a time difference is fixed between a sub-frame in which a PUCCH signal is transmitted and a sub-frame in which a PDCCH signal and a PDSCH signal are transmitted.

[0025]

5 On the other hand, in the "persistent scheduling" that is under consideration to achieve the VoIP and the like, the radio base station eNB is configured to fixedly allocate the downlink radio resource (PDSCH) to a mobile station in first cycles starting from a sub-frame (first allocation starting
10 time) in which the downlink scheduling information is transmitted to the mobile station UE through the PDCCH, and to fixedly allocate the uplink radio resource (PUCCH) to the mobile station UE through the upper layer (Radio Resource Control: RRC) signaling.

15 [0026]

In the "persistent scheduling", the downlink scheduling information is transmitted via PDCCH in a first transmission only, and the downlink scheduling information is not transmitted via PDCCH in the subsequent transmissions. For
20 this reason, the method for associating a radio resource of the PUCCH with a radio resource number of the PDCCH cannot be applied unlike the "dynamic scheduling" described above.

[0027]

Accordingly, the uplink radio resource (PUCCH) in the
25 "persistent scheduling" is fixedly allocated to the mobile station UE by using the upper layer (RRC) signaling.

[0028]

Here, the uplink radio resource represents, for example, a code resource in the code multiplexing or a frequency resource

in the frequency multiplexing.

[0029]

The frequency resource may be designated by a resource block number of a resource block (aggregate of sub-carriers) in which the PUCCH is transmitted.

[0030]

Furthermore, when a plurality of pieces of acknowledgement information are multiplexed within one resource block, the uplink radio resource may be designated by a predetermined identification number. For example, an identification number may be used to designate an amount of cyclic shift in the multiplexing of CAZAC sequence cyclic shift or an orthogonal cover number in the block spreading.

[0031]

Furthermore, generally in the HARQ, a time difference is fixed between a time point where the downlink radio resource (PDSCH) is allocated and a time point where the uplink radio resource (PUCCH) is allocated. Accordingly, a transmission timing of PUCCH is uniquely determined by designating a first allocation starting time through the PDCCH.

[0032]

In the example shown in FIG. 9, the downlink radio resource (PDSCH) described above is fixedly allocated in cycles of 20 ms, and the uplink radio resource (PUCCH) is fixedly allocated for respective downlink radio resources (PDSCH).

[0033]

Specifically, the downlink radio resource (PDSCH) is fixedly allocated in sub-frames #3, #23, ..., while the acknowledgement information is transmitted in sub-frames #7,

#27, ...

[0034]

Note that, in the sub-frame #3 of the example shown in FIG. 9, a first allocation starting time is designated by PDCCH.

5 [0035]

Here, in a prior art, a time difference between a time point where the downlink radio resource (PDSCH) described above is allocated and a time point where the uplink radio resource (PUCCH) is allocated, is provided to become a predetermined
10 period of time (for example, four sub-frames).

[0036]

Accordingly, when a timing of the downlink radio resource (PDSCH) allocated in the "persistent scheduling" is changed, a timing allocated to the uplink radio resource (PUCCH) is also
15 changed similarly.

[0037]

Note that, even in the case where a timing for allocating the uplink radio resource (PUCCH) is changed, an uplink radio resource (PUCCH) such as a code resource and a frequency
20 resource is not changed. This is because, in the persistent scheduling, the uplink radio resource (PUCCH) such as a code resource in the code multiplexing and a frequency resource in the frequency multiplexing is fixedly allocated to the mobile station UE by using the upper layer signaling as described
25 above.

[0038]

At this time, if an uplink radio resource (PUCCH) to be allocated at a changed timing is already used by a different mobile station UE, the uplink radio resource (PUCCH) after the

change collides with an uplink radio resource (PUCCH) of the different mobile station UE. Thus, there has been a problem that changing the timing of the downlink radio resource (PDSCH) allocated in the "persistent scheduling" cannot be processed.

5 [0039]

In other words, there has been a problem that a timing of the downlink radio resource (PDSCH) allocated in the "persistent scheduling" cannot be changed freely, since a time difference is fixed between a time point where the downlink
10 radio resource (PDSCH) is allocated and a time point where the uplink radio resource (PUCCH) is allocated, and the uplink radio resource (PUCCH) is set in advance.

DISCLOSURE OF THE INVENTION

15 [0040]

Accordingly, the present invention has been made to solve the above problems. An object of the present invention is to provide a radio resource selecting method, a mobile station and a radio base station which are capable of flexibly setting a
20 timing of a downlink radio resource (PDSCH) allocated in the "persistent scheduling".

[0041]

A first aspect of the present invention is summarized as a mobile communication method in which a mobile station receives
25 downlink data transmitted from a radio base station by using a downlink radio resource fixedly allocated in first cycles starting from a first allocation starting time, and transmits acknowledgement information for the downlink data using a fixedly allocated uplink radio resource, the method including

the steps of: (A) notifying, from the radio base station to the mobile station, the first cycle and information on the uplink radio resource; and (B) determining, at the mobile station, a first allocation starting time, receiving the downlink data via the downlink radio resource and transmitting the acknowledgement information via the uplink radio resource at and after the first allocation starting point, when receiving the fixed allocation signal from the radio base station. In the step (B), the uplink radio resource is adjusted by an adjustment signal included in the fixed allocation signal and the acknowledgement information is transmitted via the adjusted uplink radio resource.

[0042]

In the first aspect of the present invention, in the step (A), the information on the uplink radio resource may be an identification number which designates a number of the orthogonal cover sequence in the block spreading or an amount of cyclic shift of the CAZAC sequence.

[0043]

In the first aspect of the present invention, in the step (B), the uplink radio resource may be adjusted by changing the identification number by the adjustment signal.

[0044]

In the first aspect of the present invention, in the step (B), when a signal format of the fixed allocation signal is the same as a signal format of the dynamic allocation signal used in a scheduling in which the downlink radio resource is dynamically allocated, the adjustment signal may be notified with a power control command or a bit designating the redundancy

version of the HARQ contained in the dynamic allocation signal.
[0045]

In other words, the first aspect of the present invention is summarized as a radio resource selecting method for selecting, 5 semi-fixedly, a radio resource to be allocated to an uplink response signal indicating a reception state of a fixedly allocated downlink signal, from a plurality of radio resources defined successively on a radio resource space formed with the frequency axis and the code axis, the method including the steps 10 of: (A) generating specification information for specifying, from the plural radio resources, allocation radio resources to be allocated to the uplink response signal; (B) notifying the generated specification information; and (C) selecting the allocation radio resources on the basis of the notified 15 specification information. In the step (A), when the plurality of radio resources are classified into a plurality of groups, basic specification information for specifying a group including one or more unused allocation radio resources and one or more pieces of relative specification information indicating 20 a relative position of one or more allocation radio resources within the group on the radio resource space are generated as the specification information.

[0046]

A second aspect of the present invention is summarized 25 as a mobile station configured to receive downlink data transmitted from a radio base station using a downlink radio resource fixedly allocated in first cycles starting from a first allocation starting time and transmit acknowledgement information for the downlink data using a fixedly allocated

uplink radio resource, the mobile station including: a fixed communication information receiver unit configured to receive the first cycle and the information on the uplink radio resource from the radio base station; and a communication unit configured
5 to determine the first allocation starting time, receive the downlink data via the downlink radio resource and transmit the acknowledgement information via the uplink radio resource at and after the first allocation starting time, when receiving a fixed allocation signal from the radio base station. The
10 communication unit is configured to adjust the uplink radio resource by the adjustment signal included in the fixed allocation signal and to transmit the acknowledgement information via the adjusted uplink radio resource.

[0047]

15 In the second aspect of the present invention, the information on the uplink radio resource may be an identification number which designates a number of the orthogonal cover sequence in the block spreading or an amount of cyclic shift of the CAZAC sequence.

20 [0048]

In the second aspect of the present invention, the communication unit may be configured to adjust the uplink radio resource by changing the identification number with the adjustment signal.

25 [0049]

In the second aspect of the present invention, when a signal format of the fixed allocation signal is the same as a signal format of the dynamic allocation signal used in a scheduling in which the downlink radio resource is dynamically

allocated, the communication unit may be configured to obtain the adjustment signal on the basis of a power control command or a bit designating the redundancy version of the HARQ contained in the dynamic allocation signal.

5 [0050]

In other words, the second aspect of the present invention is summarized as a mobile station used in a mobile communication system in which a radio resource to be allocated to an uplink response signal indicating a reception state of a fixedly
10 allocated downlink signal is semi-fixedly selected from a plurality of radio resources defined successively on a radio resource space formed with the frequency axis and the code axis, the mobile station including: a specification information receiver unit configured to receive, from the radio base station,
15 specification information for specifying allocation radio resources to be allocated to the uplink response signal; and a radio resource selector unit configured to select the allocation radio resources on the basis of the specification information received by the specification information receiver
20 unit. When the plurality of radio resources are classified into a plurality of groups, the specification information is configured to include basic specification information for specifying a group including one or more unused allocation radio resources, and one or more pieces of relative specification
25 information indicating a relative position of one or more allocation radio resources within the group on the radio resource space.

[0051]

A third aspect of the present invention is summarized as

a radio base station used in a mobile communication system in which a mobile station receives downlink data transmitted from the radio base station by using a downlink radio resource fixedly allocated in first cycles starting from a first allocation starting time and transmits acknowledgement information for the downlink data by using a fixedly allocated uplink radio resource, the radio base station including: a fixed communication information transmitter unit configured to notify the mobile station of the first cycle and the information on the uplink radio resource; a fixed allocation signal transmitter unit configured to transmit a fixed allocation signal to the mobile station; and a communication unit configured to transmit the downlink data via the downlink radio resource and receive the acknowledgement information via the uplink radio resource at and after a first allocation starting time determined by the fixed allocation signal. The communication unit is configured to adjust the uplink radio resource by an adjustment signal included in the fixed allocation signal and to receive the acknowledgement information via the adjusted uplink radio resource.

[0052]

In the third aspect of the present invention, the information on the uplink radio resource may be an identification number which designates a number of the orthogonal cover sequence in the block spreading or an amount of cyclic shift of the CAZAC sequence.

[0053]

In the third aspect of the present invention, the communication unit may be configured to adjust the uplink radio

resource by changing the identification number with the adjustment signal.

[0054]

In the third aspect of the present invention, when a signal
5 format of the fixed allocation signal is the same as a signal
format of the dynamic allocation signal used in a scheduling
in which the downlink radio resource is dynamically allocated,
the communication unit may be configured to notify the
adjustment signal by a power control command or a bit
10 designating the redundancy version of the HARQ included in the
dynamic allocation signal.

[0055]

In the third aspect of the present invention, the fixed
allocation signal transmitter unit may be configured to set the
15 adjustment signal in such a manner that the uplink radio
resource does not collide with an uplink radio resource
allocated to another mobile station.

[0056]

In other words, the third aspect of the present invention
20 is summarized as a radio base station configured to select,
semi-fixedly, a radio resource to be allocated to an uplink
response signal indicating a reception state of a fixedly
allocated downlink signal, from a plurality of radio resources
defined successively on a radio resource space formed with the
25 frequency axis and the code axis, the radio base station
including: an specification information generator unit
configured to generate specification information for
specifying, from the plurality of radio resources, allocation
radio resources to be allocated to the uplink response signal;

and an specification information notifying unit configured to notify the generated specification information. When the plurality of radio resources are classified into a plurality of groups, the specification information generator unit is
5 configured to generate, as the specification information, basic specification information for specifying a group including one or more unused allocation radio resources and one or more pieces of relative specification information indicating a relative position of one or more allocation radio resources within the
10 group on a radio resource space.

BRIEF DESCRIPTION OF THE DRAWINGS

[0057]

[FIG. 1] FIG. 1 is a functional block diagram of a mobile
15 station according to a first embodiment of the present invention.

[FIG. 2] FIG. 2 is a diagram for explaining a scheduling performed in a mobile communication system according to the first embodiment of the present invention.

20 [FIG. 3] FIG. 3 is a diagram for explaining a method of determining an uplink radio resource (PUCCH) performed in a mobile communication system according to the first embodiment of the present invention.

[FIG. 4] FIG. 4 is a functional block diagram of a radio base
25 station according to the first embodiment of the present invention.

[FIG. 5] FIG. 5 is a diagram for explaining a method of determining contents of the uplink radio resource adjustment signal, performed in a mobile communication system according

to the first embodiment of the present invention.

[FIG. 6] FIG. 6 is a flow chart showing operations of a mobile station according to the first embodiment of the present invention.

5 [FIG. 7] FIG. 7 is a flow chart showing operations of a radio base station according to the first embodiment of the present invention.

[FIG. 8] FIG. 8 is a diagram for setting up a scheduling in a general LTE mobile communication system.

10 [FIG. 9] FIG. 9 is a diagram for setting up a scheduling in a general LTE mobile communication system.

BEST MODES FOR CARRYING OUT THE INVENTION

[0058]

15 (Configuration of Mobile Communication System according to First Embodiment of Present Invention)

Referring to FIG. 1 and FIG. 2, a configuration of a mobile communication system according to a first embodiment of the present invention is described. This embodiment is described
20 by citing the LTE mobile communication system, but the present invention can also be applied to mobile communication systems to which any other mode is applied.

[0059]

In a mobile communication system according to this
25 embodiment, the mobile station UE is configured to receive downlink data transmitted from the radio base station eNB using a downlink radio resource (PDSCH) fixedly allocated in first cycles starting from a first allocation starting time, and transmit acknowledgement information (ACK/NACK) for the

downlink data by using an uplink radio resource (PUCCH).

[0060]

Here, a time difference is fixed between a reception timing of the downlink data and a transmission timing of the
5 acknowledgement information.

[0061]

As shown in FIG. 1, the mobile station UE includes a persistent information receiver unit 11, a persistent allocation signal receiver unit 12, a downlink data receiver
10 unit 13 and an ACK/NACK transmitter unit 14.

[0062]

The persistent information receiver unit 11 is configured to receive, from the radio base station eNB, persistent information (fixed communication information) including the
15 first cycle and the information on the uplink radio resource (PUCCH).

[0063]

Specifically, the persistent information receiver unit 11 is configured to acquire the persistent information based
20 on an RRC message transmitted by the radio base station eNB.

[0064]

Here, the information on the uplink radio resource (PUCCH) represents, for example, a resource block number of a resource block (aggregate of sub-carriers) in which PUCCH is
25 transmitted or an identification number of a plurality of pieces of acknowledgement information multiplexed within one resource block.

[0065]

For example, an amount of cyclic shift in the multiplexing

of the CAZAC sequence cyclic shift or an orthogonal cover number in the block spreading may be designated by such identification number.

[0066]

5 Meanwhile, the information on the uplink radio resource (PUCCH) described above may be in any form as long as the radio resource can be identified.

[0067]

10 For example, the information on the uplink radio resource (PUCCH) may be an identification number of a code resource in the code multiplexing described above, an identification number of a frequency resource in the frequency multiplexing, an identification number of a time resource in the time multiplexing, or an identification number of a resource in a
15 hybrid multiplexing such as the code multiplexing, the frequency multiplexing and the time multiplexing described above.

[0068]

20 Furthermore, such information on the uplink radio resource (PUCCH) is given to the ACK/NACK transmitter unit 14.

[0069]

 Furthermore, in the LTE mobile communication system, information on the first allocation starting time described above is not included in such persistent information.

25 [0070]

 This is intended to make the radio base station eNB flexibly determine a time resource to allocate the downlink radio resource (PDSCH) described above, whereby utilization efficiency of the radio resource is improved when the

"persistent scheduling" is applied.

[0071]

Meanwhile, it is not necessary that transmission timing of the uplink radio resource (PUCCH) is included as the persistent information, since this information is uniquely determined based on a reception timing of the downlink radio resource (PDSCH) described above and a fixedly defined time offset.

[0072]

10 For example, transmission timing of the uplink radio resource (PUCCH) may be defined as follows:

(Transmission timing of uplink radio resource (PUCCH)) =
(reception timing of downlink radio resource PDSCH) + 4ms

[0073]

15 Meanwhile, the above value of 4ms is just an example and therefore may be other than 4ms. Alternatively, 4ms may be expressed as four sub-frames.

[0074]

20 The persistent allocation signal receiver unit 12 is configured to receive a fixed allocation signal from the radio base station eNB.

[0075]

Specifically, the persistent allocation signal receiver unit 12 is configured to receive, from the radio base station eNB, PDCCH instructing fixed allocation of the downlink radio resource (PDSCH) for the "persistent scheduling", as a fixed allocation signal.

[0076]

For example, the persistent allocation signal receiver

unit 12 may be configured to determine, on the basis of RNTI or the like set to PDCCH, whether the PDCCH is a PDCCH to instruct fixed allocation of the downlink radio resource (PDSCH) for the "persistent scheduling" or a PDCCH to dynamically allocate the
5 downlink radio resource (PDSCH) for normal downlink scheduling.
[0077]

Meanwhile, the persistent allocation signal receiver unit 12 may be configured to determine, on the basis of one specific bit in the PDCCH, whether the PDCCH is a PDCCH to
10 instruct fixed allocation of the downlink radio resource (PDSCH) for the "persistent scheduling" or a PDCCH to dynamically allocate the downlink radio resource (PDSCH) for normal downlink scheduling.
[0078]

15 Alternatively, when the persistent allocation signal receiver unit 12 is configured to indicate whether a part of information elements in a PDCCH is a PDCCH to instruct fixed allocation of the PDSCH (the downlink radio resource) for the "persistent scheduling", or the part of information elements
20 in the PDCCH is a PDCCH to dynamically allocating the PDSCH (the downlink radio resource) for the normal downlink scheduling, the persistent allocation signal receiver unit 12 may be configured to determine whether the PDCCH is a PDCCH to instruct fixed allocation of the PDSCH (the downlink radio resource) for
25 the "persistent scheduling", or the PDCCH is a PDCCH to dynamically allocating the PDSCH (the downlink radio resource) for the normal downlink scheduling, on the basis of the part of information elements in the above PDCCH.

[0079]

Furthermore, the fixed allocation signal includes, in addition to the information to instruct fixed allocation of the downlink radio resource (PDSCH) for the "persistent scheduling", an uplink radio resource adjustment signal for adjusting a resource block number of the uplink radio resource (PUCCH) and the identification number when plural pieces of acknowledgement information are multiplexed within one resource block. Details of the uplink radio resource will be described later.

[0080]

10 Such an uplink radio resource adjustment signal is given to the ACK/NACK transmitter unit 14.

[0081]

15 The downlink data receiver unit 13 is configured to receive downlink data transmitted via the downlink radio resource (PDSCH) allocated by the PDCCH.

[0082]

20 Specifically, the downlink data receiver unit 13 is configured to, when the persistent allocation signal (fixed allocation signal) is received by the persistent allocation signal receiver unit 12, determine a sub-frame, which has received such PDCCH, as a first allocation starting time, and receive the downlink data via the downlink radio resource (PDSCH) for "persistent scheduling" fixedly in the first cycles starting from the first allocation starting time.

25 [0083]

In the example shown in FIG. 2, since the persistent allocation signal receiver unit 12 has received the persistent allocation signal via PDCCH, the downlink data receiver unit 13 is configured to receive the downlink data via the downlink

radio resource (PDSCH) mapped to a resource block (aggregate of sub-carriers) within the sub-frame #3 designated by PDCCH.
[0084]

Furthermore, the downlink data receiver unit 13 is
5 configured to receive downlink data via a downlink radio resource (PDSCH) mapped to a resource block (aggregate of sub-carriers) designated by the PDCCH in the cycle of 20ms starting from the sub-frame #3.
[0085]

10 That is, the downlink data receiver unit 13 is configured to receive downlink data via the PDSCH (downlink radio resource) mapped to a resource block (aggregate of sub-carriers) designated by the PDCCH in sub-frames #3, #23, #43,
[0086]

15 The ACK/NACK transmitter unit 14 is configured to receive, from the persistent information receiver unit 11, information on an uplink radio resource (PUCCH) notified by the persistent information.
[0087]

20 Furthermore, the ACK/NACK transmitter unit 14 receives, from the persistent allocation signal receiver unit 12, an uplink radio resource adjustment signal described above for adjusting a resource block number of the PUCCH (uplink radio resource) and the identification number when a plurality of
25 pieces of acknowledgement information are multiplexed within one resource block.
[0088]

The ACK/NACK transmitter unit 14 is configured to determine an uplink radio resource (PUCCH) based on the

information on the uplink radio resource (PUCCH) notified by the persistent information and the uplink radio resource adjustment signal, and to transmit the acknowledgement information (ACK/NACK) for the downlink data received via the uplink radio resource (PUCCH). The acknowledgement information (ACK/NACK) is determined on the basis of decoding results of the downlink data in the downlink data receiver unit 13.

[0089]

10 Hereinafter, using FIG. 3, description is given of a method for determining the uplink radio resource (PUCCH) based on the information on the uplink radio resource (PUCCH) notified by the persistent information and the uplink radio resource adjustment signal.

15 [0090]

In FIG. 3, eight radio resources are defined as uplink radio resources (PUCCH), and #0, #1, #2, ... #7 are defined as corresponding identification numbers thereof. For example, such identification numbers may be identification numbers in the multiplexing of a plurality of pieces of acknowledgement information within one resource block described above.

[0091]

Then, assume the case where a radio resource of identification number #2 is designated by the information on the uplink radio resource (PUCCH) notified by the persistent information and "+3" is designated by the uplink radio resource adjustment signal.

[0092]

In this case, the ACK/NACK transmitter unit 14 determines

a radio resource of the identification number #5 as a radio resource for transmitting the acknowledgement information (ACK/NACK) for the received downlink data, that is, as an uplink radio resource (PUCCH), by adding "+3" to the identification number #2.

[0093]

That is, a radio resource designated by the information on the uplink radio resource (PUCCH) notified by the persistent information is adjusted by the uplink radio resource adjustment signal described above.

[0094]

Meanwhile, in the example described above, the identification number in the multiplexing of a plurality of pieces of acknowledgement information within one resource block is adjusted by the uplink radio resource adjustment signal, but, instead, the resource block number of the PUCCH may be adjusted by the uplink radio resource adjustment signal.

[0095]

Alternatively, both the identification number in the multiplexing of a plurality of pieces of acknowledgement information within one resource block and a resource block number of the PUCCH may be adjusted by the uplink radio resource adjustment signal described above.

[0096]

Alternatively, an identification number for identifying a resource other than the above may be defined, and such identification number may be adjusted by the uplink radio resource adjustment signal described above.

[0097]

Furthermore, although the identification number described above is adjusted just by "+3" by the uplink radio resource adjustment signal, such "+3" is just an example and, therefore, may be a value other than "+3" such as "+2" or "+4",
5 or a negative value such as "-3" or "-2". Alternatively, the identification number may be "0". Further alternatively, the uplink radio resource adjustment signal may be a signal having a significance other than described above as long as such identification number can be adjusted.

10 [0098]

Furthermore, although eight radio resources are defined in the example described above, a similar uplink radio resource (PUCCH) determining method is also applicable to a case where other than eight radio resources are defined.

15 [0099]

Meanwhile, although, in the above example, an identification number designated by the information on the uplink radio resource (PUCCH) notified by the persistent information is adjusted by the uplink radio resource adjustment
20 signal, instead, an identification number of the uplink radio resource (PUCCH) used in a previous "Talk Spurt" may be adjusted by the uplink radio resource adjustment signal, and a radio resource of the adjusted identification number may be used as an uplink radio resource (PUCCH).

25 [0100]

In this case, only when the uplink radio resource (PUCCH) is transmitted for the first time, an identification number designated by the information on the uplink radio resource (PUCCH) notified by the persistent information is adjusted by

the uplink radio resource adjustment signal.

[0101]

Alternatively, although, in the example described above,
an identification number designated by the information on the
5 uplink radio resource (PUCCH) notified by the persistent
information is adjusted by the uplink radio resource adjustment
signal, instead, depending on the persistent information,
information on the uplink radio resource (PUCCH) may be notified
by the PDCCH without notifying the information on the uplink
10 radio resource (PUCCH).

[0102]

In this case, there is a disadvantage of increasing the
bit number for the information on the uplink radio resource
(PUCCH), while there is an advantage in that the uplink radio
15 resource (PUCCH) can be set up flexibly.

[0103]

Furthermore, in the above example, the information on the
uplink radio resource (PUCCH) notified by the PDCCH may be, for
example, information of "identification #2" and "+3", or may
20 be, more directly, information of "identification number #5".

[0104]

Meanwhile, the uplink radio resource adjustment signal
is defined as a part of the information elements notified by
the persistent allocation signal (fixed allocation signal).

25 [0105]

Here, for example, when a signal format of the persistent
allocation signal is the same as a signal format of the dynamic
allocation signal in the dynamic scheduling, bits of the power
control command used for transmission power control in the

dynamic allocation signal may be used as the uplink radio resource adjustment signal.

[0106]

5 In the persistent scheduling, since there is less significance of notifying the power control command used in such transmission power control, bits of the command used for transmission power control may be used as the uplink radio resource adjustment signal.

[0107]

10 Alternatively, when a signal format of the persistent allocation signal is the same as a signal format of the dynamic allocation signal in the dynamic scheduling, bits designating the "redundancy version" in the dynamic allocation signal may be used as the uplink radio resource adjustment signal.

15 [0108]

In the persistent scheduling, since there is less significance of notifying a bit designating such redundancy version, bits of the power control command used for transmission power control may be used as the uplink radio resource
20 adjustment signal.

[0109]

In this case, the redundancy version is a predetermined redundancy version.

[0110]

25 Alternatively, when a signal format of the persistent allocation signal is the same as a signal format of the dynamic allocation signal in the dynamic scheduling, bits designating the "MCS (Modulation and Coding Scheme)" in the dynamic allocation signal may be used as the uplink radio resource

adjustment signal.

[0111]

Since the bit number designating such MCS in the persistent scheduling is smaller compared with the dynamic
5 scheduling, a part of such bits designating MCS may be used as the uplink radio resource adjustment signal.

[0112]

Meanwhile, a timing when the acknowledgement information (ACK/NACK) for the downlink data received via the uplink radio
10 resource (PUCCH) is a timing uniquely determined based on the reception timing of the downlink radio resource (PDSCH) and the fixedly defined time offset, as described above.

[0113]

Furthermore, in the example described above, although the
15 acknowledgement information (ACK/NACK) for the PDSCH (downlink data) is transmitted by the PUCCH, the acknowledgement information for the downlink data may be transmitted by multiplexing with PUSCH, when a physical uplink shared channel for transmitting uplink data is transmitted in a sub-frame when
20 the acknowledgment information (ACK/NACK) is transmitted.

[0114]

Alternatively, when a physical uplink shared channel for transmitting uplink data in a sub-frame when the acknowledgement information (ACK/NACK) is transmitted is
25 allocated, acknowledgement information for such downlink data may be transmitted as partial information within the PUSCH.

[0115]

On the other hand, the radio base station eNB according to the present invention is configured to notify the mobile

station UE of the first cycle and the information on an uplink radio resource (PUCCH).

[0116]

Description of such information on the uplink radio resource (PUCCH) is omitted as it is the same as the description given of the mobile station UE.

[0117]

As shown in FIG. 4, the radio base station eNB includes a persistent information transmitter unit 21, a persistent allocation signal transmitter unit 22, a downlink data transmitter unit 23 and an ACK/NACK transmitter unit 24.

[0118]

The persistent information transmitter unit 21 is configured to transmit, to the mobile station UE, persistent information (fixed communication information) including the first cycle and the information on the uplink radio resource (PUCCH).

[0119]

Specifically, the persistent information transmitter unit 21 is configured to notify the mobile station UE of the persistent information using an RRC message.

[0120]

Description of the information on the uplink radio resource (PUCCH) is omitted as it is the same as the description given of the mobile station UE. Meanwhile, such information on the uplink radio resource (PUCCH) is given to the ACK/NACK receiver unit 24.

[0121]

The persistent allocation signal transmitter unit 22 is

configured to transmit a fixed allocation signal from the mobile station UE.

[0122]

Specifically, the persistent allocation signal transmitter unit 22 is configured to transmit, to the mobile station UE, a PDCCH instructing fixed allocation of the downlink radio resource (PDSCH) for the "persistent scheduling", as a fixed allocation signal.

[0123]

Note that, such a fixed allocation signal includes, in addition to the information to instruct fixed allocation of the downlink radio resource (PDSCH) for the "persistent scheduling", an uplink radio resource adjustment signal for adjusting a resource block number of the uplink radio resource (PUCCH) and the identification number when a plurality of pieces of acknowledgement information are multiplexed within one resource block.

[0124]

Such an uplink radio resource adjustment signal is given to the ACK/NACK receiver unit 24.

[0125]

Additionally, the persistent allocation signal transmitter unit 22 may be configured to determine contents of the uplink radio resource adjustment signal in such a manner that the radio resource of the acknowledgement information for the downlink data does not collide with an acknowledgement information transmitted from another mobile station.

[0126]

Using FIG. 5, one example of a method for determining

contents of the uplink radio resource adjustment signal is shown,
wherein the contents are determined in such a manner that a radio
resource of acknowledgement information for the downlink data
does not collide with a radio resource of the acknowledgement
5 information transmitted from another mobile station.

[0127]

In FIG. 5, eight radio resources are defined as uplink
radio resources (PUCCH), and #0, #1, #2, ... #7 are defined as
corresponding identification numbers thereof.

10 [0128]

Additionally, in the transmission timing of the
acknowledgement information, radio resources of
identification numbers #2, #3, and #4 are already used by other
mobile stations UE#A, UE#B and UE#C.

15 [0129]

In this case, when the identification number of the uplink
radio resource (PUCCH) of the mobile station UE is not adjusted
by the uplink radio resource adjustment signal, an uplink radio
resource (PUCCH) transmitted by a different mobile station UE#A
20 collides with an uplink radio resource (PUCCH) transmitted by
the mobile station UE, whereby transmission characteristics of
uplink radio resources (PUCCH) of the different mobile station
UE#A and the mobile station UE degrade significantly.

[0130]

25 Accordingly, the persistent allocation signal
transmitter unit 22 determines that the identification number
of the uplink radio resource (PUCCH) of the mobile station UE
should be adjusted by "+3" with the uplink radio resource
adjustment signal in order to prevent the collision described

above.

[0131]

In this case, the identification number of the uplink radio resource (PUCCH) of the mobile station UE becomes #2+3=#5, so that the uplink radio resource (PUCCH) does not collide with an uplink radio resource (PUCCH) transmitted by other mobile stations UE.

[0132]

The downlink data transmitter unit 23 is configured to transmit downlink data transmitted via the downlink radio resource (PDSCH) allocated by the PDCCH.

[0133]

Specifically, the downlink data transmitter unit 23 is configured to, when the persistent allocation signal (fixed allocation signal) is transmitted by the persistent allocation signal transmitter unit 22, determine a sub-frame, which has transmitted such PDCCH, as a first allocation starting time, and transmit the downlink data via the downlink radio resource (PDSCH) for "persistent scheduling" fixedly in the first cycles starting from the first allocation starting time.

[0134]

The ACK/NACK receiver unit 24 is configured to receive, from the persistent information transmitter unit 21, information on an uplink radio resource (PUCCH) notified by the persistent information.

[0135]

Furthermore, the ACK/NACK receiver unit 24 receives, from the persistent allocation signal transmitter unit 22, an uplink radio resource adjustment signal described above for adjusting

a resource block number of the PUCCH (uplink radio resource) and the identification number when a plurality of pieces of acknowledgement information are multiplexed within one resource block.

5 [0136]

The ACK/NACK receiver unit 24 is configured to determine an uplink radio resource (PUCCH) based on the information on the uplink radio resource (PUCCH) notified by the persistent information and the uplink radio resource adjustment signal,
10 and to receive the acknowledgement information (ACK/NACK) for the downlink data transmitted via the uplink radio resource (PUCCH).

[0137]

Description of the method of determining the information
15 on the uplink radio resource (PUCCH) notified by the persistent information and an uplink resource (PUCCH) based on the uplink radio resource adjustment signal is also omitted as it is the same as the description given of the mobile station UE.

[0138]

20 (Operations of Mobile Communication System according to First Embodiment of Present Invention)

Referring to FIG. 6, operations of a mobile communication system according to the first embodiment of the present invention is described.

25 [0139]

As shown in FIG. 6, in the step S101, the mobile station UE receives, from the radio base station eNB, persistent information including the first cycle and information on the uplink radio resource (PUCCH) through an RRC message or the

like.

[0140]

In the step S102, the mobile station UE receives the persistent allocation signal (fixed allocation signal) transmitted by the radio base station eNB via the PDCCH. The persistent allocation signal includes the uplink radio resource adjustment signal.

[0141]

In the step S102, the mobile station UE determines a reception timing of the persistent allocation signal as a first allocation starting time.

[0142]

In the step S103, the mobile station UE determines an uplink radio resource (PUCCH) based on the information on the uplink radio resource (PUCCH) and the uplink radio resource adjustment signal.

[0143]

A method for determining the uplink radio resource (PUCCH) based on the information on the uplink radio resource (PUCCH) and the uplink radio resource adjustment signal is the same as a method for determining the uplink radio resource (PUCCH) already described in the ACK/NACK transmitter unit 14 of the mobile station UE.

[0144]

In the step S104, the mobile station UE receives downlink data via the PDSCH (downlink radio resource) for the "persistent scheduling" designated by the persistent allocation signal at a reception timing of the "persistent scheduling" calculated from the first allocation starting time and the first cycle.

[0145]

In the step S105, the mobile station UE transmits the acknowledgement information (AK/NACK) for the downlink data received in step S104 via the uplink radio resource (PUCCH) determined in step S103.

[0146]

Then, the mobile station UE receives downlink data via the PDSCH (downlink radio resource) fixedly allocated in the first cycle (step S104) and transmits the acknowledgement information (AK/NACK) for the downlink data via the PUCCH (uplink radio resource) (step S105).

[0147]

Referring to FIG. 7, operations of the radio base station according to the first embodiment of the present invention is described.

[0148]

As shown in FIG. 7, in the step S201, the radio base station eNB transmits, to the mobile station UE, persistent information including the first cycle and information on the uplink radio resource (PUCCH) through an RRC message or the like.

[0149]

In step S202, the radio base station eNB determines that the persistent allocation signal (fixed allocation signal) transmitted via the PDCCH should be transmitted to the mobile station UE.

[0150]

In step S203, the radio base station eNB determines whether or not an uplink radio resource (PUCCH) designated by the information on the uplink radio resource (PUCCH) collides

with an uplink radio resource (PUCCH) of a different mobile station UE.

[0151]

If the radio base station eNB determines that the uplink
5 radio resource (PUCCH) designated by the information on the
uplink radio resource (PUCCH) collides with an uplink radio
resource (PUCCH) of the different mobile station UE (step S203:
YES), operation of the radio base station eNB proceeds to step
S204. Otherwise (step S203: NO), operation of the radio base
10 station eNB proceeds to step S205.

[0152]

In step S204, the radio base station eNB determines that
the uplink radio resource (PUCCH) designated by the information
on the uplink radio resource (PUCCH) should be adjusted.

15 [0153]

Specifically, the radio base station eNB sets up, for
example, a value of "+3" as the uplink radio resource adjustment
signal. The uplink radio resource adjustment signal is
included in the persistent allocation signal determined to be
20 transmitted in step S202.

[0154]

In step S204, the radio base station eNB determines that
the uplink radio resource (PUCCH) designated by information on
the uplink radio resource (PUCCH) should not be adjusted.

25 [0155]

Specifically, the radio base station eNB sets up, for
example, a value of "0" as the uplink radio resource adjustment
signal. The uplink radio resource adjustment signal is
included in the persistent adjustment signal determined to be

transmitted in step S202.

[0156]

(Advantageous Effects of Mobile Communication System according to First Embodiment of Present Invention)

5 In a mobile communication system according to the first embodiment of the present invention, when timing to allocate the downlink radio resource (PDSCH) is changed and the uplink radio resource (PUCCH) collides with an uplink radio resource (PUCCH) of another mobile station, the collision can be avoided
10 by adjusting the uplink radio resource (PUCCH), whereby timing of allocating the downlink radio resource (PDSCH) through the "persistent scheduling" can be set flexibly and radio utilization efficiency can be improved.

[0157]

15 Features according to this embodiment described above may be expressed as follows.

[0158]

 A first aspect of the present embodiment is summarized as a radio resource selecting method for selecting,
20 semi-fixedly, a radio resource to be allocated to an uplink response signal indicating a reception state of a fixedly allocated downlink signal, from a plurality of radio resources defined successively on a radio resource space formed with the frequency axis and the code axis, the method including the steps
25 of: (A) generating specification information for specifying, from the plurality of radio resources, allocation radio resources to be allocated to the uplink response signal; (B) notifying the generated specification information; and (C) selecting the allocation radio resources on the basis of the

notified specification information; and wherein, in the step (A), when the plurality of radio resources are classified into a plurality of groups, basic specification information for specifying a group including one or more unused allocation radio resources and one or more pieces of relative specification information indicating a relative position of one or more allocation radio resources within the group on the radio resource space are generated as the specification information.

[0159]

Here, the "fixedly allocated downlink signal" corresponds to downlink data transmitted using a downlink radio resource (PDSCH) allocated in the "persistent scheduling".

[0160]

Also, the "uplink response signal in which a reception state of the downlink signal is indicated" corresponds to an "acknowledgement information for the downlink data" described above.

[0161]

Also, the "basic specification information" corresponds to the "information on the uplink radio resource (PUCCH)" described above, and the "relative specification information" corresponds to the "uplink radio resource adjustment signal" described above. The "allocation radio resource" corresponds to, for example, respective radio resources shown in FIG. 3.

[0162]

In the first aspect of the present embodiment, in the step (A), the relative specification information may be generated for unused allocation radio resources.

[0163]

In the first aspect of the present embodiment, in the step (A), the basic specification information may be frequency information (for example, resource block number) of any of allocation radio resources within the groups.

5 [0164]

A second aspect of the present embodiment is summarized as a radio base station configured to select, semi-fixedly, a radio resource to be allocated to an uplink response signal indicating a reception state of a fixedly allocated downlink
10 signal, from a plurality of radio resources defined successively on a radio resource space formed with the frequency axis and the code axis, the radio base station including: a persistent information transmitter unit 21 configured to generate information on an uplink radio resource (PUCCH) (basic
15 specification information), and to notify the generated information on an uplink radio resource (PUCCH); and a persistent allocation signal transmitter unit 22 configured to generate an uplink radio resource adjustment signal (relative specification information), and to notify the generated uplink
20 radio resource adjustment signal.

[0165]

In the second aspect of the present embodiment, the persistent allocation signal transmitter unit 22 may be configured to generate the uplink radio resource adjustment
25 signal for unused allocation radio resources.

[0166]

In the second aspect of the present embodiment, the persistent information transmitter unit 21 may be configured to use, as the information on an uplink radio resource (PUCCH),

frequency information (for example, resource block number) of any of allocation radio resources within the groups

[0167]

A third aspect of the present embodiment is summarized
5 as a mobile station UE used in a mobile communication system in which a radio resource to be allocated to an uplink response signal indicating a reception state of a fixedly allocated downlink signal is semi-fixedly selected from a plurality of radio resources defined successively on a radio resource space
10 formed with the frequency axis and the code axis, the mobile station UE including: a persistent information receiver unit 11 configured to receive, from a radio base station eNB, information on an uplink radio resource (PUCCH) (specification information); and a persistent allocation signal receiver unit
15 configured to receive, from the radio base station eNB, an uplink radio resource adjustment signal (relative specification information); and an ACK/NACK transmitter unit 14 configured to select an allocation radio resource on the basis of the received information on an uplink radio resource
20 (PUCCH) and the received uplink radio resource adjustment signal.

[0168]

Note that operation of the above described mobile station UE and the radio base station eNB may be implemented by means
25 of hardware, a software module executed by a processor, or a combination of both.

[0169]

The software module may be provided in any type of storage medium such as an RAM (Random Access Memory), a flash memory,

a ROM (Read Only Memory), an EPROM (Erasable Programmable ROM), an EEPROM (Electrically Erasable and Programmable ROM), a register, a hard disk, a removable disk, or a CD-ROM.

[0170]

5 The storage medium is connected to the processor so that the processor can read and write information from and to the storage medium. Also, the storage medium may be integrated into the processor. Also, the storage medium and the processor may be provided in an ASIC. The ASIC may be provided in the mobile station UE and the radio base station eNB. Also, the storage medium and the processor may be provided in the mobile station UE and the radio base station eNB as a discrete component.

[0171]

15 The scope of the claims should not be limited by the preferred embodiments set forth herein, but should be given the broadest interpretation consistent with the description as a whole.

20

Industrial Applicability

25 [0172]

As described above, the present invention can provide a mobile communication method, a mobile station and a radio base station which are capable of flexibly setting a timing of a downlink radio resource (PDSCH) allocated in the "persistent

scheduling".

WHAT IS CLAIMED IS:

1. A radio resource selecting method for selecting, semi-fixedly, a radio resource to be allocated to an uplink response signal indicating a reception state of a fixedly allocated downlink signal, from a plurality of radio resources defined successively on a radio resource space formed with the frequency axis and the code axis, the method comprising the steps of:
 - (A) a radio base station (eNB) generating first specification information for specifying, from the plurality of radio resources, radio resources to be allocated to the uplink response signal;
 - (B) the radio base station (eNB) notifying the generated first specification information to a mobile station (UE);
 - (C) the radio base station (eNB) generating second specification information for specifying, from the plurality of radio resources, radio resources to be allocated to the uplink response signal;
 - (D) the radio base station (eNB) notifying the generated second specification information to the mobile station (UE); and
 - (E) the mobile station (UE) selecting radio resources to be allocated to the uplink response signal, on the basis of the notified first specification information and the notified second specification information.
2. The radio resource selecting method according to claim 1, wherein the second specification information is information for further specifying radio resources from the radio resources specified by the first specification information.
3. The radio resource selecting method according to claim 1, wherein the first specification information is information for specifying absolute identification information of radio resources to be allocated to

the uplink response signal, from the plurality of radio resources;
and

the second specification information is information for specifying
relative identification information for further specifying radio
resources from the radio resources specified by the first specifi-
cation information.

4. The radio resource selecting method according to claim 1, wherein
the second specification information is information for further adjust-
ing the radio resources specified by the first specification infor-
mation.
5. The radio resource selecting method according to claim 1, wherein
the first specification information is notified by a radio resource con-
trol (RRC) message; and
the second specification information is notified by a physical downlink
control channel (PDCCH).
6. The radio resource selecting method according to claim 5, wherein
the second specification information is notified by a command used in
transmission power control in the PDCCH.
7. A radio base station (eNB) configured to select, semi-fixedly, a radio
resource to be allocated to an uplink response signal indicating a
reception state of a fixedly allocated downlink signal, from a plurality
of radio resources defined successively on a radio resource space
formed with the frequency axis and the code axis, the radio base
station comprising:
a first specification information generator unit configured to generate
first specification information for specifying, from the plurality

- of radio resources, radio resources to be allocated to the uplink response signal;
- a first specification information notifying unit configured to notify the generated first specification information;
- 5 a second specification information generator unit configured to generate second specification information for specifying, from the plurality of radio resources, radio resources to be allocated to the uplink response signal; and
- a second specification information notifying unit configured to notify
- 10 the generated second specification information;
- wherein said first and second specification information notifying units are configured to notify to a mobile station (UE) said first and second specification information for use in a selection of the radio resources to be allocated to the uplink response signal by
- 15 the mobile station (UE).
8. The radio base station (eNB) according to claim 7, wherein the second specification information generator unit is configured to generate, as the second specification information, information
- 20 for further specifying radio resources from the radio resources specified by the first specification information.
9. The radio base station (eNB) according to claim 8, wherein the first specification information generator unit is configured to generate, as the first specification information, information for specifying absolute identification information of radio resources to be
- 25 allocated to the uplink response signal, from the plurality of radio resources; and
- the second specification information generator unit is configured to
- 30 generate, as the second specification information, information for specifying relative identification information for further

specifying radio resources from the radio resources specified by the first specification information.

10. The radio base station (eNB) according to claim 7, wherein
5 the second specification information generator unit is configured to generate, as the second specification information, information for further adjusting the radio resources specified by the first specification information.
- 10 11. The radio base station (eNB) according to claim 7, wherein
the first specification information notifying unit is configured to notify
the first specification information by a radio resource control
(RRC) message; and
the second specification information notifying unit is configured to
15 notify the second specification information by a physical
downlink control channel (PDCCH).
12. The radio base station (eNB) according to claim 11, wherein
the second specification information notifying unit is configured to
20 notify the second specification information by a command used
in transmission power control in the PDCCH.
13. A mobile station (UE) used in a mobile communication system in
which a radio resource to be allocated to an uplink response signal
25 indicating a reception state of a fixedly allocated downlink signal is
semi-fixedly selected from a plurality of radio resources defined
successively on a radio resource space formed with the frequency axis
and the code axis, the mobile station comprising:
a first specification information receiver unit configured to receive,
30 from a radio base station, first specification information for

specifying radio resources to be allocated to the uplink response signal;

a second specification information receiver unit configured to receive, from the radio base station, second specification information for specifying radio resources to be allocated to the uplink response signal; and

a radio resource selector unit configured to select radio resources to be allocated to the uplink response signal, on the basis of the first specification information received by the first specification information receiver unit and the second specification information received by the second specification information receiver unit.

14. The mobile station (UE) according to claim 13, wherein the second specification information receiver unit is configured to receive, as the second specification information, information for further specifying radio resources from the radio resources specified by the first specification information.

15. The mobile station (UE) according to claim 13, wherein the first specification information receiver unit is configured to receive, as the first specification information, information for specifying absolute identification information of radio resources to be allocated to the uplink response signal, from the plurality of radio resources; and

the second specification information receiver unit is configured to receive, as the second specification information, information for specifying relative identification information for further specifying radio resources from the radio resources specified by the first specification information.

16. The mobile station (UE) according to claim 13, wherein
the second specification information receiver unit is configured to
receive, as the second specification information, information for
further adjusting the radio resources specified by the first speci-
fication information.
17. The mobile station (UE) according to claim 13, wherein
the first specification information receiver unit is configured to receive
the first specification information by a radio resource control
(RRC) message; and
the second specification information receiver unit is configured to
receive the second specification information by a physical
downlink control channel (PDCCH).
18. The mobile station (UE) according to claim 17, wherein
the second specification information receiver unit is configured to
receive the second specification information by a command used
in transmission power control in the PDCCH.
19. A radio resource selecting method for selecting, semi-fixedly, a radio
resource to be allocated to an uplink response signal indicating a
reception state of a fixedly allocated downlink signal, from a plurality
of radio resources defined successively on a radio resource space
formed with the frequency axis and the code axis, the method compris-
ing the steps of:
- (A) generating first specification information for specifying, from
the plurality of radio resources, radio resources to be allocated
to the uplink response signal;
 - (B) notifying the generated first specification information by a radio
resource control (RRC) message;

- (C) generating second specification information for specifying, from the plurality of radio resources, radio resources to be allocated to the uplink response signal;
- (D) notifying the generated second specification information by a physical downlink control channel (PDCCH); and
- (E) selecting radio resources to be allocated to the uplink response signal, on the basis of the notified first specification information and the notified second specification information, wherein the first specification information is information for specifying absolute identification information of radio resources to be allocated to the uplink response signal, from the plurality of radio resources; and
- the second specification information is information for specifying relative identification information for further specifying radio resources from the radio resources specified by the first specification information.
20. The radio resource selecting method according to claim 19, wherein in the step (B) , the second specification information is notified by a command used in transmission power control in the PDCCH.
21. A radio base station configured to select, semi-fixedly, a radio resource to be allocated to an uplink response signal indicating a reception state of a fixedly allocated downlink signal, from a plurality of radio resources defined successively on a radio resource space formed with the frequency axis and the code axis, the radio base station comprising:
- a first specification information generator unit configured to generate first specification information for specifying, from the plurality of radio resources, radio resources to be allocated to the uplink response signal;

- a first specification information notifying unit configured to notify the generated first specification information by a radio resource control (RRC) message;
- a second specification information generator unit configured to generate second specification information for specifying, from the plurality of radio resources, radio resources to be allocated to the uplink response signal; and
- a second specification information notifying unit configured to notify the generated second specification information by a physical downlink control channel (PDCCH), wherein
- the first specification information generator unit is configured to generate, as the first specification information, information for specifying absolute identification information of radio resources to be allocated to the uplink response signal, from the plurality of radio resources; and
- the second specification information generator unit is configured to generate, as the second specification information, information for specifying relative identification information for further specifying radio resources from the radio resources specified by the first specification information.
22. The radio base station according to claim 21, wherein the second specification information notifying unit is configured to notify the second specification information by a command used in transmission power control in the PDCCH.
23. A mobile station used in a mobile communication system in which a radio resource to be allocated to an uplink response signal indicating a reception state of a fixedly allocated downlink signal is semi-fixedly selected from a plurality of radio resources defined successively on a

radio resource space formed with the frequency axis and the code axis,
the mobile station comprising:

- 5 a first specification information receiver unit configured to receive,
from a radio base station, first specification information for
specifying radio resources to be allocated to the uplink response
signal by a radio resource control (RRC) message;
- 10 a second specification information receiver unit configured to receive,
from the radio base station, second specification information for
specifying radio resources to be allocated to the uplink response
signal by a physical downlink control channel (PDCCH); and
- 15 a radio resource selector unit configured to select radio resources to be
allocated to the uplink response signal, on the basis of the first
specification information received by the first specification
information receiver unit and the second specification informa-
tion received by the second specification information receiver
unit, wherein
- 20 the first specification information receiver unit is configured to re-
ceive, as the first specification information, information for
specifying absolute identification information of radio resources
to be allocated to the uplink response signal, from the plurality
of radio resources; and
- 25 the second specification information receiver unit is configured to
receive, as the second specification information, information for
specifying relative identification information for further specify-
ing radio resources from the radio resources specified by the
first specification information.

24. The mobile station according to claim 23, wherein
- 30 the second specification information receiver unit is configured to
receive the second specification information by a command used
in transmission power control in the PDCCH.

FIG. 1





FIG. 2



3/6

FIG. 3





FIG. 4



4/6

FIG. 5




FIG. 6




FIG. 7




FIG. 8





FIG. 9



RADIO RESOURCE OF IDENTIFICATION NUMBER #0
RADIO RESOURCE OF IDENTIFICATION NUMBER #1
RADIO RESOURCE OF IDENTIFICATION NUMBER #2(UE#A)
RADIO RESOURCE OF IDENTIFICATION NUMBER #3(UE#B)
RADIO RESOURCE OF IDENTIFICATION NUMBER #4(UE#C)
RADIO RESOURCE OF IDENTIFICATION NUMBER #5
RADIO RESOURCE OF IDENTIFICATION NUMBER #6
RADIO RESOURCE OF IDENTIFICATION NUMBER #7

IDENTIFICATION NUMBER
DESIGNATED BY INFORMATION ON
UPLINK RADIO RESOURCE (PUCCH)



IDENTIFICATION NUMBER
ADJUSTED BY UPLINK RADIO
RESOURCE ADJUSTMENT SIGNAL



ASSUME THAT UPLINK RADIO RESOURCE
ADJUSTMENT SIGNAL IS "+3":(#5=#2+3)