



Office de la Propriété
Intellectuelle
du Canada

Un organisme
d'Industrie Canada

Canadian
Intellectual Property
Office

An agency of
Industry Canada

CA 2573035 C 2013/03/19

(11)(21) **2 573 035**

(12) **BREVET CANADIEN
CANADIAN PATENT**

(13) **C**

(86) Date de dépôt PCT/PCT Filing Date: 2005/07/08
(87) Date publication PCT/PCT Publication Date: 2006/01/19
(45) Date de délivrance/Issue Date: 2013/03/19
(85) Entrée phase nationale/National Entry: 2007/01/05
(86) N° demande PCT/PCT Application No.: FI 2005/000324
(87) N° publication PCT/PCT Publication No.: 2006/005797
(30) Priorité/Priority: 2004/07/09 (FI20040967)

(51) Cl.Int./Int.Cl. *D21C 9/10* (2006.01),
C02F 1/52 (2006.01)

(72) Inventeurs/Inventors:
PALONEN, HEIKKI, FI;
PALONIEMI, ARJA, FI;
TAITTONEN, REETTA, FI;
ROUSU, PAIVI, FI


(73) Propriétaire/Owner:
KEMIRA OYJ, FI

(74) Agent: CASSAN MACLEAN

(54) Titre : PROCEDE POUR EVACUER LA LIGNINE CONTENUE DANS L'EAU
(54) Title: METHOD FOR REMOVING LIGNIN FROM WATER

(57) **Abrégé/Abstract:**

The invention relates to a method for removing lignin from an aqueous solution. It is accomplished by adding a calcium compound and an aluminium compound to said solution. Said calcium compound is preferably calcium chloride and said aluminium compound is preferably a polymeric aluminium hydroxide salt.



(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
19 January 2006 (19.01.2006)

PCT

(10) International Publication Number
WO 2006/005797 A1

(51) International Patent Classification⁷: **D21C 9/10**,
C02F 9/00

(21) International Application Number:
PCT/FI2005/000324

(22) International Filing Date: 8 July 2005 (08.07.2005)

(25) Filing Language: Finnish

(26) Publication Language: English

(30) Priority Data:
20040967 9 July 2004 (09.07.2004) FI

(71) Applicant (for all designated States except US): **KEMIRA OYJ** [FI/FI]; Porkkalankatu 3, FI-00180 Helsinki (FI).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **PALONEN, Heikki** [FI/FI]; Teeriniemenkatu 12 as 13, FI-65320 Vaasa (FI). **PALONIEMI, Arja** [FI/FI]; Vöyrantie 101, FI-66500 Vähäkyrö (FI). **TAITTONEN, Reetta** [FI/FI]; Maunulantie 7, FI-66400 Laihia (FI). **ROUSU, Päivi** [FI/FI]; Sääskitie 43, FI-90550 Oulu (FI).

(74) Agent: **BERGGREN OY AB**; P.O. Box 16 (Jaakonkatu 3 A), FI-00101 Helsinki (FI).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).


Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: METHOD FOR REMOVING LIGNIN FROM WATER

(57) Abstract: The invention relates to a method for removing lignin from an aqueous solution. It is accomplished by adding a calcium compound and an aluminium compound to said solution. Said calcium compound is preferably calcium chloride and said aluminium compound is preferably a polymeric aluminium hydroxide salt.



WO 2006/005797 A1

Method for removing lignin from water

The invention relates to a method for removing lignin from an aqueous solution by adding a calcium compound and an aluminium compound thereto.

5

The bleaching sequence of chemical pulp often comprises one or several peroxide steps. The bleaching conditions with respect to pH are alkaline, also being relatively hot ($> 60^{\circ}\text{C}$). Under these conditions, the lignin contained in the pulp is partly dissolved and partly becomes less coloured on the fiber surface. After
10 bleaching, the pulp is washed and the drained water is normally passed to a water treatment unit. Lignin dissolving in water results in a yellowish brown colour thereof. Lignin is considered as a sparingly biodegradable substance, thus having a great influence on the properties of purified waste water. Therefore it would be desirable to be able to remove lignin from the waste water prior to biological
15 treatment thereof.

It is known that calcium precipitates lignin. Several references, even recent ones, to this issue may be found in the literature. However, the precipitating power thereof is rather limited. See Table 2 below.

20

US 4,420,369 discloses the addition of an acid liquid containing calcium and aluminium to an aqueous solution containing lignin, thus resulting in neutralization of the liquid mixture for lignin precipitation. See also Bakhshi, N. and MacDonald, D, AIChE Symposium Series, Am. Inst. Chem. Eng; NY, Vol. 76(1980) 104-113
25 and Eaton, D. and Chang H-m., Tappi Vol. 65/1982, No. 5, 167-170. The result of these precipitations are, however, unsatisfactory.

Accordingly, the object of the invention is to provide a more effective method for removing lignin from an aqueous solution such as waste water from bleaching of
30 chemical pulp. The object has now been achieved by adding a calcium compound and an aluminium compound to said aqueous solution for lignin removal. It was found that the precipitation result could be improved by avoiding the acidic step of said US-publication.

35 As is mentioned, the invention closely relates to lignin removal from bleaching water of chemical pulp. Normally, this bleaching water is basic having a pH of about 10. In this case, it is preferable for the invention to adjust the pH value of the aqueous solution between 5 and 6. This may for instance be carried out by adding an inorganic acid e.g. sulphuric acid. In case the aluminium compound used
40 causes an acidic reaction in water, the pH may also otherwise reach the desired level.

2

It has also been found that the order of addition of the calcium and aluminium compounds is important when removing lignin according to the invention. In the method, it is preferable to add the calcium compound to alkaline water containing lignin, and allow the reaction to proceed for a period of time, followed by adjusting
5 the pH to a neutral or slightly acidic value, and finally adding the aluminium compound. Thus, an ample precipitate is formed accompanied by the almost total disappearance of the yellowish colour of lignin. Sedimentation of the precipitate may be enhanced with a flocculant.

10 A parameter illustrating the lignin content is the UV absorbance at the wavelength of 280 nm. In best cases, the absorbance was reduced from a level of 3.7 to a level of 1.8.

Preferably an amount from 10 to 10,000 mg/l, more preferably from 50 to 1000
15 mg/l of the calcium compound is added to the aqueous solution, calculated as calcium. Preferably an amount from 100 to 10,000 mg/l, more preferably from 300 to 1000 mg/l of the aluminium compound is added to the aqueous solution.

The calcium compound used in the invention is preferably selected from the group
20 consisting of calcium oxide, calcium hydroxide, and inorganic calcium salts. More preferably, the calcium compound is calcium chloride or calcium sulphate, preferably calcium chloride.

The aluminium compound is preferably a polymeric aluminium hydroxide, or a
25 polymeric aluminium hydroxide salt. The polymeric structure is obtained from a compound with hydroxylic groups building oxo bridges. Even more preferably, the aluminium compound is a polymeric aluminium hydroxide sulphate, polymeric aluminium hydroxide chloride, or a polymeric aluminium hydroxide diformate. Most preferably, the aluminium compound is aluminium hydroxide chloride having a
30 ratio of OH to Al between 1:10 and 9:10.

In the following, the invention is illustrated by means of working and reference examples only meant for illustration.

35 Examples

Background

Waste waters from bleaching of straw contain dissolved lignin. The removal
40 thereof with biological treatment methods is assumed to be difficult. In this work,

3

precipitation of lignin using various chemicals e.g. polyvalent cations and organic polymers was studied.

Summary

5

In this work, the influence of Ca, Fe, and Al salts on turbidity, COD, and TOC of waste waters, as well as on its UV absorbance at a wavelength of 280 nm, reflecting the lignin content thereof was studied.

- 10 Concurrent use of calcium and a polymeric aluminium salt (Kempac 18) was clearly shown as the most efficient combination. In Table below, calcium is added as an aqueous CaCl_2 solution.

	Ca mg/l	Kempac18 mg/l	pH	Turbidity NTU	UV abs 280 nm	COD mg/l	TOC mg/l
0	-	-	10,2	66	3.673	2326	803
1	1000	1000	5,3	5	1.861	1276	375
2	100	1000	5,8	3	2.316	1374	393

- 15 CaCl_2 may be replaced with more sparingly soluble calcium oxide or gypsum. Precipitation result is slightly weaker.

Neither the precipitation, floc formation, nor sedimentation was made more efficient by the use of organic flocculants.

20

Results

The sample was designated as a mixture of raw and wash waters of WS, 21st of April, 2004. Following properties were determined:

25

Table 1 Original water

		Not centrifuged	Centrifuged
pH		10.2	10.2
Turbidity	NTU		66.4
COD	mg/l	2170	2326
TOC	mg/l	797.3	802.9
Cat.need	meq/l	2.259	2.342
UV abs	280 nm		3.673
SS	mg/l	52	

Tables 2 – 5 show experimental results in small groups. In these experiments, calcium is added as CaCl_2 (the amount shown in the Table is calculated as Ca).

Advantages of the concurrent use of calcium, and a polymeric aluminium salt are clearly shown by the results. Also the need for pH adjustment is substantial.

5 It is to be noted that the UV absorption is not reduced at all by only lowering the pH to a value of 3.

10 It was attempted to improve the efficiency of precipitation and flocculation by using polymers (Fennopols A321, K1384, K3450, and K506). The effects of these agents were very minimal, and often the addition of the polymer even impaired the flocculation. The polymer may, however, still work under practical conditions.

15 Table 6 presents the so-called confirmation test for a sample of 1 litre. Clarification of the precipitation was observed visually. Higher Ca doses clearly improved the sedimentation and compacted the precipitate.

20 In Table 7, the influence of different calcium salts on precipitation is compared. Reduction of the dose to a value below 1 g/l has an immediate effect on UV absorbance. Calcium oxide and gypsum are almost equivalent, gypsum being perhaps slightly more efficient. The reduction of the amount of Kempac to half immediately made both of the Ca salts inefficient.

Procedure

25 The testing was carried out with samples of 50 – 100 ml. The calcium salt was added first, mixed for about 2 minutes, or 30 minutes in cases the salt was solid. This was followed by the adjustment of the pH to 7, and the addition of the other coagulant. A mixing for a few minutes followed. Finally, the water was centrifuged and the particular properties were determined from the clarified sample.

Table 2

Test no.	Coagulant mg/l		pH	Turbidity NTU	UV abs 280 nm	COD mg/l	TOC mg/l	Note
1	Ca	10	10.2	66	3.673	2326	803	added as a solid
2	Ca	100	10.1	52				
3	Ca	1000	10.0	32				
4	Ca	1000	9.7	13	3.645	1564	555	
5	Ca	5000	9.4	3				
6	Ca	5000	9.3	2				
7	Fennoferri	100	10.1	53				
8	Fennoferri	500	9.8	63	4.000	2202	801	
9	Fennoferri	1000	8.8	77				
10	Kempac18	100	10.1	56				
11	Kempac18	500	9.7	64	3.831	2260	803	
12	Kempac18	1000	8.3	83				
13	Alum	10	10.2	54				
14	Alum	100	10.1	59				
15	Alum	500	9.2	59				
16	Alum	1000	7.0	74	3.588	2232	788	

5 **Table 3**

Test no.	Coagulant mg/l		1M H ₂ SO ₄ μl/50 ml	pH	Turbidity NTU	UV abs 280 nm	COD mg/l	TOC mg/l
15	-	-	675	3	146	3.854	2240	699
16	Ca	1000	225	6.8	1	3.591	1660	537
17	Fennoferri	500	150	7.0	63	3.700	2354	754
18	Kempac18	500	125	6.9	60	3.529	2406	747
19	Alum	500	100	6.9	67	3.822	2378	897

Table 4

Test no.	Coagulant mg/l		Coagulant mg/l		pH	Turbidity NTU	UV abs 280 nm	COD mg/l	TOC mg/l
20	Ca	1000	Kempac18	100	6.4	18	3.523	1590	530.2
21	Ca	1000	Kempac18	500	5.4	3	1.795	1286	405.9
22	Ca	1000	Kempac18	1000	5.3	2	1.605	1264	396.5
23	Ca	1000	Fennoferi	500	6.1	39	3.528	1492	473.3
24	Ca	1000	PEO	5	7.0	5	3.492		
25	Ca	1000	PEO	10	7.0	5	3.531		
30	Ca	100	Kempac18	1000	5.8	1	1.919		
31	Ca	500	Kempac18	1000	5.7	3	2.169		
34			FF240	400	7.2	335	3.800		
35			FF240	800	7.4	7	3.370		
36			ORC2003	400	6.8	124	4.000		
37			Orc2003	800	6.4	155	3.790		

Table 5

5

Test no.	Coagulant mg/l		Coagulant mg/l		pH	Turbidity NTU	UV abs 280 nm
26	Ca	100	Kempac18	1000	8.4	63	3.596
27	Ca	500	Kempac18	1000	7.8	18	3.654
28	Ca	1000	Kempac18	1000	8.4	6	3.480
29	Ca	1000	Kempac18	5000	9.3	5	3.586
32	FF240	400				272	3.772
33	FF240	800				373	4.000

Without pH adjustment

Table 6

	Ca mg/l	Kempac18 mg/l	pH	Turbidity NTU	UV abs 280 nm	COD mg/l	TOC mg/l
0	-	-	10.2	66	3.673	2326	803
1	1000	1000	5.3	5	1.861	1276	375
2	100	1000	5.8	3	2.316	1374	393

Rapid mixing at 400 rpm for 10 sec during which Ca was added, slow mixing for 5 min.
 pH was adjusted using magnetic stirring
 Rapid mixing at 400 rpm for 10 sec during which Kempac was added, slow mixing for 5 min.
 Sedimentation over night
 In test 1, proportion of precipitate of about 100 ml/500 ml
 In test 2, proportion of precipitate of about 200 ml/500 ml
 In test 3, sedimentation of the precipitate was slower, the precipitate being lighter and partly floating.

Table 7 Forms of addition of calcium

Test no.	Coagulant			Coagulant	1M H ₂ SO ₄ μl/100 ml	pH	Turbidity NTU	UV abs 280 nm	COD mg/l	TOC mg/l
0	-	-	-	-	-	10.2	66	3.673	2326	803
1	CaO	Ca	1000	Kempac18	560	5.9	1	1.978	1372	391
2	CaSO ₄	Ca	1000	Kempac18	400	5.8	1	1.928	1356	391
3	Ca(OH) ₂	Ca	1000	Kempac18	600	5.9	2	2.167	1406	410
5	CaO	Ca		Kempac18		6.2	33	3.016	1552	472
4	CaO	Ca		Kempac18	500	6.8	7	2.469	1478	446
7	CaSO ₄	Ca		Kempac18		6.1	10	2.274	1434	426
6	CaSO ₄	Ca		Kempac18		6.3	7	2.387	1420	432
8	CaO	Ca		Kempac18	500	6.5	43	3.595		
9	CaO	Ca		Kempac18	100	6.9	64	3.622		
10	CaSO ₄	Ca		Kempac18	500	6.3	24	3.606		
11	CaSO ₄	Ca		Kempac18	100	6.7	22	3.688		

What is claimed is:

1. Method for removing lignin from waste water from the bleaching of chemical pulp by adding a calcium and aluminium compound thereto,
5 characterized in that said calcium compound is selected from the group consisting of calcium oxide, calcium hydroxide and inorganic calcium salts and said aluminium compound is selected from the group consisting of polymeric aluminium hydroxide and polymeric aluminium hydroxide salts, and that first, said calcium compound and said waste water are combined into a
10 solution having a pH of from 4.5 to 7, and thereafter, said aluminium compound is added to this solution to precipitate the lignin.
2. Method of Claim 1, characterized in that said waste water is basic waste
15 water from the bleaching of chemical pulp.
3. Method of Claim 1, characterized in that said waste water is waste water from the bleaching of straw.
4. Method of Claim 1, 2 or 3, characterized in that the pH of the solution is
20 adjusted to a value from 5 to 6.
5. Method according to any one of Claims 1 to 4, characterized in that an amount from 10 to 10,000 mg/l of said calcium compound is added to said waste water, calculated as calcium.
25
6. Method of Claim 5, characterized in that an amount from 50 to 1000 mg/l of said calcium compound is added to said waste water, calculated as calcium.
- 30 7. Method according to any one of Claims 1 to 6, characterized in that an amount from 100 to 10,000 mg/l of said aluminium compound is added to said waste water.
8. Method of Claim 7, characterized in that an amount from 300 to 1000
35 mg/l of said aluminium compound is added to said waste water.
9. Method according to any one of Claims 1 to 8, characterized in that said calcium compound is calcium chloride, or calcium sulphate.

10. Method according to any one of Claims 1 to 9, characterized in that said aluminium compound is a polymeric aluminium hydroxide sulphate, polymeric aluminium hydroxide chloride, or a polymeric aluminium hydroxide formate.

5

11. Method of Claim 10, characterized in that said aluminium compound is aluminium hydroxide chloride having a ratio of OH to Al between 1:10 and 9:10.

10 12. The method according to Claim 3, characterized in that said waste water is waste water from the sulphur-free bleaching thereof.

13. The method according to Claim 9, characterized in that said calcium compound is calcium chloride.

15