



US012265432B2

(12) **United States Patent**  
**Lee et al.**

(10) **Patent No.:** **US 12,265,432 B2**  
(45) **Date of Patent:** **Apr. 1, 2025**

(54) **PORTABLE SOLID-STATE DRIVE MODULE**

(58) **Field of Classification Search**

(71) Applicant: **SAMSUNG ELECTRONICS CO., LTD.**, Suwon-si (KR)

CPC .. G06F 1/182; G06F 2203/0338; H05K 5/026  
See application file for complete search history.

(72) Inventors: **Hanhong Lee**, Suwon-si (KR);  
**Jaehong Park**, Suwon-si (KR); **Yusuf Cinar**, Yongin-si (KR); **Seongyun Baek**, Suwon-si (KR)

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,612,927 A 3/1997 Morrison et al.  
5,886,869 A 3/1999 Fussell et al.  
(Continued)

(73) Assignee: **SAMSUNG ELECTRONICS CO., LTD.**, Suwon-si (KR)

FOREIGN PATENT DOCUMENTS

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 274 days.

JP 2004-213837 A2 7/2004  
KR 10-2002-0075087 10/2002  
(Continued)

(21) Appl. No.: **18/047,126**

OTHER PUBLICATIONS

(22) Filed: **Oct. 17, 2022**

Notice of Allowance dated May 6, 2021 in related U.S. Appl. No. 16/878,925 (12 pages).

(65) **Prior Publication Data**

US 2023/0060271 A1 Mar. 2, 2023

(Continued)

**Related U.S. Application Data**

*Primary Examiner* — James Wu

*Assistant Examiner* — Dakota M Talbert

(63) Continuation of application No. 16/909,337, filed on Jun. 23, 2020, now Pat. No. 11,507,148.

(74) *Attorney, Agent, or Firm* — F. CHAU & ASSOCIATES, LLC

(30) **Foreign Application Priority Data**

Nov. 25, 2019 (KR) ..... 10-2019-0152241

(57) **ABSTRACT**


(51) **Int. Cl.**  
**G06F 1/18** (2006.01)  
**F21V 17/10** (2006.01)

(Continued)

The present disclosure relates to a portable solid-state drive (SSD) module. The portable SSD module includes a case, an SSD, a light-emitting device (LED) module and a main bracket. The case may have a window. The SSD may be arranged in the case. The LED module may be arranged in the case to indicate an operation of the SSD through the window. The main bracket may be arranged in the case to support the LED module. Therefore, the LED module may be readily and firmly combined with the case.

(52) **U.S. Cl.**  
CPC ..... **G06F 1/182** (2013.01); **F21V 17/104** (2013.01); **F21V 33/0052** (2013.01); **H05K 5/026** (2013.01); **F21Y 2115/10** (2016.08)

**20 Claims, 20 Drawing Sheets**



(51)	<b>Int. Cl.</b>		2019/0377126 A1	12/2019	Itabashi et al.
	<b>F21V 33/00</b>	(2006.01)	2020/0201972 A1	6/2020	Park et al.
	<b>H05K 5/02</b>	(2006.01)	2021/0081518 A1	3/2021	Park et al.
	<b>F21Y 115/10</b>	(2016.01)	2021/0157372 A1	5/2021	Lee et al.

FOREIGN PATENT DOCUMENTS

(56) **References Cited**

U.S. PATENT DOCUMENTS

7,333,328 B2	2/2008	Funawatari et al.
8,797,297 B2	8/2014	Yabuta et al.
9,543,638 B2	1/2017	Kim
9,845,935 B1	12/2017	Cheng et al.
9,875,773 B1	1/2018	Waters et al.
10,068,619 B1	9/2018	Chew et al.
10,104,796 B1	10/2018	Lin
10,237,383 B2	3/2019	Park
2002/0175632 A1	11/2002	Takeguchi
2004/0190192 A1	9/2004	Huang
2005/0013127 A1	1/2005	Tsai
2009/0316351 A1	12/2009	Zadesky et al.
2011/0194305 A1	8/2011	Chen et al.
2014/0269240 A1	9/2014	Phelan et al.
2014/0362576 A1	12/2014	Degner et al.
2016/0004899 A1	1/2016	Pi et al.
2016/0327724 A1	11/2016	Wu et al.
2016/0349800 A1	12/2016	Kim et al.
2018/0034948 A1	2/2018	Yu et al.
2018/0157891 A1*	6/2018	Wang ..... H05K 5/0278
2018/0232509 A1	8/2018	Park et al.
2018/0341290 A1	11/2018	Sim et al.
2018/0365543 A1	12/2018	Cha et al.
2019/0179438 A1	6/2019	Benkley, III et al.
2019/0236256 A1	8/2019	Ogawa
2019/0303640 A1	10/2019	Song et al.

KR	20-2010-0000239	1/2010
KR	10-1147400	5/2012
KR	10-1248092	3/2013
KR	10-2013-0077709	7/2013
KR	10-1327931	11/2013
KR	10-1411460	6/2014
KR	10-2014-0131152	11/2014
KR	10-2014-0135478	11/2014
KR	10-2014-0144667	12/2014
KR	10-2017-0021147	2/2017
KR	10-1726993	4/2017
KR	10-1738394	5/2017
KR	10-2018-0014914	2/2018
KR	10-2018-0094205	8/2018
KR	10-2018-0136719	12/2018

OTHER PUBLICATIONS

Office Action issued on Dec. 10, 2020 in co-pending U.S. Appl. No. 16/878,925.  
 Notice of Allowance dated Sep. 8, 2023 in related U.S. Appl. No. 17/391,346.  
 Notice of Allowance dated May 30, 2024 in related Korean Patent Application No. 10-2019-0152241 (in Korean), 7 pages.  
 Korean Office Action dated Sep. 19, 2023 in corresponding Korean Patent Application No. 10-2019-0152241, (in Korean), 9 pages.

\* cited by examiner

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 30





FIG. 31



**PORTABLE SOLID-STATE DRIVE MODULE****CROSS-REFERENCE TO RELATED APPLICATION**

This application is a continuation application of U.S. patent application Ser. No. 16/909,337 filed Jun. 23, 2020, which is based on and claims priority and benefit to Korean Patent Application No. 10-2019-0152241, filed on Nov. 25, 2019 in the Korean Intellectual Property Office (KIPO), the disclosures of which are incorporated by reference herein in their entirety.

**BACKGROUND**

## 1. Field

Example embodiments relate to a portable solid-state drive (SSD) module.

## 2. Description of the Related Art

Electronic devices that are tasked with retaining information may contain a storage device. Storage devices include hard disk drives (HDD) and solid-state drives (SSD). Speed and reliability have created a high demand for SSDs.

An SSD may also be usable outside of an electronic device. This configuration may be referred to as an external SSD. For example, an external SSD may be placed on a desk to supplement storage usage for a computer. A case may surround the SSD device to protect sensitive components from shock or external elements.

An SSD case design may include a light-emitting diode (LED) used to indicate operation of the SSD. However, in certain situations, the LED may not be robustly fastened to the case. Additionally, the LED may not provide uniform brightness (e.g., based on the shape of the LED). Therefore, there is a need in the art for an SSD with a case arranged in such a way to firmly mount the LED module to the case and uniformly diffuse light from the LED module.

**SUMMARY**

Embodiments of the present disclosure relate to an external solid-state drive (SSD). Example embodiments provide a portable solid-state drive (SSD) module that may be capable of readily and firmly combining an LED module with a case and uniformly diffusing a light from the LED module.

According to example embodiments, a portable SSD module is provided that may include a case, an SSD, a light-emitting device (LED) module and a main bracket. The SSD may be arranged in the case. In some cases, the case may have a window, and the LED module may be arranged in the case to indicate an operation of the SSD through the window. The main bracket may be arranged in the case to support the LED module.

In some cases, the portable SSD module may include a case, an SSD, a fingerprint sensor, a main bracket and a front bracket. The case may have an open front surface, an open rear surface and a window. The SSD may be arranged in the case. The fingerprint sensor may be exposed through the window to recognize a fingerprint a user for securing the SSD. The main bracket may be inserted into the case through the open rear surface of the case to support the fingerprint sensor. The front bracket may be inserted into the case

through the open front surface of the case to support connectors for electrically connecting the SSD with the fingerprint sensor.

According to example embodiments, a portable SSD module may include a case, an SSD, an LED module, a fingerprint sensor, a main bracket and a front bracket. The case may have an open front surface, an open rear surface and a window. The SSD may be arranged in the case. The LED module may be arranged in the case to indicate an operation of the SSD through the window. The fingerprint sensor may be installed at the LED module. The fingerprint sensor may be exposed through the window to recognize a fingerprint a user for securing the SSD. The main bracket may be inserted into the case through the open rear surface of the case to support the LED module and the fingerprint sensor. The front bracket may be inserted into the case through the open front surface of the case to support connectors for electrically connecting the SSD with the LED module and the fingerprint sensor.

According to example embodiments, a portable SSD module may include a case, an SSD, an LED module, a fingerprint sensor, a main bracket, a front bracket and a thermal pad. The case may have an open front surface, an open rear surface, an upper surface having a window and a lower surface. The SSD may be arranged on the lower surface of the case. The LED module may include at least one LED arranged in the case and an indicator configured to indicate a light emitted from the LED through the window. The indicator may include a diffusing groove configured to diffuse the light emitted from the LED into the indicator. The diffusing groove may include a triangular shape having at least two diffusing surfaces. The fingerprint sensor may be installed at the LED module. The fingerprint sensor may be exposed through the window to recognize a fingerprint a user for securing the SSD.

The main bracket may include a body portion, a pair of horizontal supporting portions and a vertical supporting portion. The body portion may be inserted into the case through the open rear surface of the case. The body portion may be positioned between the case and the SSD. The horizontal supporting portions may be horizontally extended from both portions of a front surface of the body portion to support both side surfaces of the LED module. The vertical supporting portion may be arranged between the horizontal supporting portions to support a lower surface of the LED module. The vertical supporting portion may include at least one rib formed on an upper surface of the vertical supporting portion. The rib may be downwardly inclined from the rear surface to the front surface of the case. The rib may slidably make contact with the lower surface of the LED module. The front bracket may be inserted into the case through the open front surface of the case to support connectors for electrically connecting the SSD with the LED module and the fingerprint sensor. The thermal pad may be interposed between the main bracket and the SSD to dissipate a heat from the SSD.

According to example embodiments, there may be provided a portable SSD module. The portable SSD module may include a case, an SSD, a main bracket and a front bracket. The case may have a window. The SSD may be arranged in the case. The main bracket may be arranged in the case to support the SSD. The front bracket may be arranged in the case to support at least one connector extended from the SSD.

According to example embodiments, the main bracket may support the LED module. Particularly, the slant rib of the main bracket inserted into the rear surface of the case

may slidably make contact with the lower surface of the LED module. Therefore, the LED module may be readily and firmly combined with the case.

Further, the indicator of the LED module may have the triangular diffusing groove so that the light from the LED may uniformly diffuse toward the whole indicator through the diffusing groove. Particularly, the light may diffuse toward a corner of the indicator. As a result, the indicator may have uniform brightness.

According to example embodiments, an apparatus may include a case comprising a top surface, a bottom surface, two side surfaces, an open front surface and an open rear surface, wherein the top surface comprises a window; a memory device arranged in the case; a lighting element arranged in the case, wherein the lighting element is configured to indicate an operation of the memory device through the window; a main bracket arranged in the case to support the lighting element, wherein the main bracket extends in a first direction from the open rear surface to the window.

In some examples, the apparatus further comprises a PCB arranged in the case and connected to the memory device; a connector connecting the lighting element to the PCB; and a front bracket arranged in the case and configured to support the connector, wherein the front bracket extends in the first direction from the connector to the open front surface. In some examples, the apparatus further comprises a fingerprint sensor disposed adjacent to the lighting element, wherein the fingerprint sensor is configured to receive fingerprint information through the window.

#### BRIEF DESCRIPTION OF THE DRAWINGS

Example embodiments will be more clearly understood from the following detailed description taken in conjunction with the accompanying drawings. FIGS. 1 to 31 represent non-limiting, example embodiments as described herein.

FIG. 1 is an exploded perspective view illustrating a portable SSD module in accordance with example embodiments;

FIG. 2 is a cross-sectional view illustrating an internal structure of the portable SSD module in FIG. 1;

FIG. 3 is an enlarged perspective view illustrating a main bracket of the portable SSD module in FIG. 1;

FIG. 4 is a perspective view illustrating an LED module supported by the main bracket in FIG. 3;

FIG. 5 is an enlarged perspective view illustrating a rib of the main bracket in FIG. 3;

FIG. 6 is a perspective view illustrating a main bracket of a portable SSD module in accordance with example embodiments;

FIGS. 7 and 8 are perspective views illustrating main brackets of a portable SSD module in accordance with example embodiments;

FIG. 9 is a cross-sectional view illustrating a front internal structure of the SSD module in FIG. 1;

FIG. 10 is an enlarged perspective view illustrating an LED module of the portable SSD module in FIG. 1;

FIG. 11 is a plan view illustrating the LED module in FIG. 10;

FIGS. 12 and 13 are plan views illustrating an angle range of a diffusing groove of the LED module in FIG. 11;

FIG. 14 is a plan view illustrating an LED module in accordance with example embodiments;

FIG. 15 is a plan view illustrating an LED module in accordance with example embodiments;

FIGS. 16 to 20 are perspective views illustrating processes for combining the portable SSD module in FIG. 1;

FIG. 21 is an exploded perspective view illustrating a portable SSD module in accordance with example embodiments;

FIG. 22 is a cross-sectional view illustrating an internal structure of the portable SSD module in FIG. 21;

FIGS. 23 to 28 are perspective views illustrating processes for combining the portable SSD module in FIG. 21;

FIG. 29 is an exploded perspective view illustrating a portable SSD module in accordance with example embodiments;

FIG. 30 is a cross-sectional view illustrating a portable SSD module in accordance with example embodiments; and

FIG. 31 is an enlarged cross-sectional view illustrating a portion "A" in FIG. 30.

#### DETAILED DESCRIPTION OF THE EMBODIMENTS

The present disclosure relates generally to a storage device and a light source connected to the storage device. The storage device may be a portable solid-state drive (SSD) module. The portable SSD module may include a case, a storage drive, a light-emitting device (LED) module and a main bracket. The case may have a window for use of a fingerprint sensor or the like. The SSD may be arranged inside the case. The LED module may be arranged inside the case to indicate an active operation of the SSD through the window. The main bracket may be arranged in the case to support the LED module. Therefore, the LED module may be readily and firmly combined with the case.

A main bracket may support the LED module. A slanted piece, of the main bracket, inserted into the rear surface of the case may contact the lower surface of the LED module. As a result, the LED module may be readily and firmly combined with the case.

The LED module may contain grooves to uniformly distribute light. A number of diffusing grooves may be formed at a number of outer surfaces of an indicating area. The LEDs may be arranged in the diffusing grooves.

Hereinafter, example embodiments will be explained in detail with reference to the accompanying drawings.

Hereinafter, some example embodiments will be explained in detail with reference to the accompanying drawings.

FIG. 1 is an exploded perspective view illustrating a portable SSD module in accordance with some example embodiments, and FIG. 2 is a cross-sectional view illustrating an internal structure of the portable SSD module in FIG. 1. FIG. 9 is a cross-sectional view illustrating a front internal structure of the SSD module in FIG. 1.

Referring to FIGS. 1 and 2, a portable SSD module 100 of some example embodiments may include a case 110, an SSD 120, a fingerprint sensor 140, an LED module 150, a main bracket 160 and a front bracket 180.

The case 110 may have a rectangular parallelepiped shape having an empty internal space and a shallow height. Thus, the case 110 may have an opened front surface 111, an opened rear surface 112, two side surfaces 115, an upper surface 113 and a lower surface 114. The side surfaces 115 may have a height less than a width and a length of the upper surface 113. The side surfaces 115 may have a rounded shape toward an outside of the case 110. Alternatively, the side surfaces 115 may have a vertical planar shape. Particularly, the side surfaces 115 may be integrally formed with the

upper surface **113** and the lower surface **114** so that the case **110** may have one body. The case **110** may be formed by an extrusion process.

The case **110** may include a window **116**. The window **116** may be formed through the upper surface **113** of the case **110**. The LED module **150** and the fingerprint sensor **140** may be exposed through the window **116**. In some example embodiments, the window **116** may be arranged within a region having a length of about 10% to about 90% of a length of the upper surface **113** of the case **110**. That is, a position of the window **116** may not be restricted within a specific region of the upper surface **113** of the case **110**.

The SSD **120** may be arranged in the case **110**. The SSD **120** may be attached to the lower surface **114** of the case **110**. In order to reduce a transfer of an external impact to the SSD **120** through the case **110**, a cushion **126** may be interposed between the SSD **120** and the lower surface **114** of the case **110**.

The SSD **120** may include a first connector **122** and a second connector **124**. The SSD **120** may be electrically connected with an external device through the first connector **122**. The first connector **122** may include a USB connector. The SSD **120** may be electrically connected with the LED module **150** and the fingerprint sensor **140** through the second connector **124**. In some example embodiments, the first connector **122** may be installed at a central portion of front end of an upper surface of the SSD **120** adjacent to the front surface **111** of the case **110**. The second connector **124** may be installed at a side of the first connector **122**.

The LED module **150** may be arranged in the case **110**. The LED module **150** may be configured to indicate operations of the SSD **120**. That is, when the SSD **120** may be operated, the LED module **150** may generate (e.g., emit) a light that indicates operations of the SSD **120**. The LED module **150** may be attached to an inner portion of the upper surface **113** of the case **110** configured to surround the window **116** using an adhesive **134**.

The LED module **150** may be attached to a printed circuit board (PCB) **130** using the adhesive **134**. The PCB **130** may include a third connector **138** connected with the PCB **130** via a flexible cable **132**. The third connector **138** may be connected to the second connector **124** of the SSD **120**. A cushion **136** may be interposed between the PCB **130** and the upper surface **113** of the case **110**.

The fingerprint sensor **140** may be mounted on the PCB **130**. The fingerprint sensor **140** may be combined with the LED module **150**. The fingerprint sensor **140** may be received in a central portion of the LED module **150**. The fingerprint sensor **140** may be configured to recognize a fingerprint of a user so as to a security of the SSD **120**.

The main bracket **160** may be arranged in the case **110** to support the LED module **150** and the fingerprint sensor **140**. In some example embodiments, the main bracket **160** may be configured to upwardly support a lower surface of the PCB **130** with the LED module **150** and the fingerprint sensor **140**. The main bracket **160** may enter into the case **110** through the opened rear surface **112** of the case **110** in a first direction. That is, the first direction may correspond to an entering direction of the main bracket **160** into the case **110**. Particularly, the main bracket **160** may be inserted into the case **110** with the main bracket **160** being slidably contacted with the lower surface of the PCB **130**. A sheet **166** may be attached to a rear surface of the main bracket **160**.

A thermal pad **168** may be interposed between the main bracket **160** and the SSD **120**. The thermal pad **168** may be configured to transfer a heat generated from the SSD **120** to

the case **110** through the main bracket **160**. Thus, the thermal pad **168** may be configured to make contact with the lower surface of the main bracket **160** and the upper surface of the SSD **120**.

The front bracket **180** may be arranged in the case **110** to support the second connector **124** and the third connector **138**. As shown in FIG. 9, the front bracket **180** may downwardly compress an upper surface of the third connector **138**. The front bracket **180** may be inserted into the case **110** through the opened front surface **111** of the case **110** in a second direction. That is, the second direction may be opposite to the first direction. The second direction may correspond to an entering direction of the front bracket **180** into the case **110**. A cushion **182** may be interposed between the front bracket **180** and the upper surface of the third connector **138**. A sheet **184** may be attached to a front surface of the front bracket **180**.

FIG. 3 is an enlarged perspective view illustrating a main bracket of the portable SSD module in FIG. 1, FIG. 4 is a perspective view illustrating an LED module supported by the main bracket in FIG. 3, and FIG. 5 is an enlarged perspective view illustrating a rib of the main bracket in FIG. 3.

Referring to FIGS. 3 to 5, the main bracket **160** may include a body portion **162**, a pair of horizontal supporting portion **164** and a vertical supporting portion **170**.

The body portion **162** may have a rectangular plate shape. The body portion **162** may be arranged between the case **110** and the SSD **120**, particularly, the upper surface **113** of the case **110** and the thermal pad **168**. The body portion **162** may have an upper surface higher than the lower surface of the LED module **150**, particularly, the lower surface of the PCB **130**.

The horizontal supporting portions **164** may be extended from both side portions of a front surface of the body portion **162** in the first direction. The vertical supporting portion **170** may be arranged between the horizontal supporting portions **164**. That is, the vertical supporting portion **170** may be extended from a central portion of the front surface of the body portion **162** in the first direction. A length of the vertical supporting portion **170** in the first direction may be shorter than a length of the horizontal supporting portions **164** in the first direction. Thus, a space defined by inner surfaces of the vertical supporting portion **170** and the horizontal supporting portions **164** may be formed. The first connector **122** and the second connector **124** of the SSD **120** may be upwardly exposed through the space. That is, front surfaces of the horizontal supporting portions **164** and the vertical supporting portion **170** may be positioned between the first connector **122** and a bridge IC of the SSD **120**.

The vertical supporting portion **170** may have an upper surface lower than upper surfaces of the body portion **162** and the horizontal supporting portions **164**. Thus, an upper portion of the front surface of the body portion **162** and upper portions of the inner surfaces of the horizontal supporting portions **164** may be exposed to form a receiving groove **178** defined by the upper portion of the front surface of the body portion **162**, the upper portions of the inner surfaces of the horizontal supporting portions **164** and the upper surface of the vertical supporting portion **170**. The PCB **130** with the LED module **150** and the fingerprint sensor **140** may be received in the receiving groove **178**. That is, the vertical supporting portion **170** may have a height less than a height of the body portion **162** due to the receiving groove **178** so that the vertical supporting portion **170** may be configured to support the PCB **130** with the fingerprint sensor **140**.

In some example embodiments, a sum of the height of the vertical supporting portion 170 and the height of the fingerprint sensor 140 may be greater than the height of the body portion 162. Further, the sum of the height of the vertical supporting portion 170 and the height of the fingerprint sensor 140 may be about 90% to about 110% of a height from the PCB 130 to the upper surface 113 of the case 110.

Therefore, the inner surfaces of the horizontal supporting portions 164 may be configured to support both side surfaces of the PCB 130 in the receiving groove 178. The vertical supporting portion 170 may be configured to support the lower surface of the PCB 130. Further, as mentioned above, because the upper surface of the body portion 162 may be higher than the lower surface of the PCB 130, the exposed upper portion of the front surface of the body portion 162 may be configured to support the rear surface of the PCB 130.

The vertical supporting portion 170 may include a central supporting portion 172 and a pair of edge supporting portions 174. The central supporting portion 172 may be arranged at a central portion of the receiving groove 178 to support a central portion of the lower surface of the LED module, particularly, a central portion of the lower surface of the PCB 130. The edge supporting portions 174 may be arranged in both edge portions of the receiving groove 178 at both sides of the central supporting portion 172 to support edge portions of the lower surface of the PCB 130. Thus, a space may be formed between the central supporting portion 172 and the edge supporting portions 174. Electronic components, which may be mounted on the lower surface of the PCB 130 to control the LED module 150 and the fingerprint sensor 140, may be received in the space.

Ribs 176 may be formed on upper surfaces of the central supporting portion 172 and the edge supporting portions 174 in the first direction. Each of the ribs 176 may include a first slant surface 176a. The first slant surface 176a may be downwardly slantly formed on a front end of the rib 176 in the first direction. When the main bracket 160 may be inserted through the opened rear surface 112 of the case 110 in the first direction, the front end of the rib 176 may firstly make contact with the rear surface of the PCB 130. Because the first slant surface 176a may be formed on the front end of the rib 176, the lower surface of the PCB 130 may slidably make contact with the first slant surface 176a. Thus, an interference may not be generated between the main bracket 160 and the LED module 150, particularly, the main bracket 160 and the PCB 130. As a result, the main bracket 160 may be readily combined with the case 110.

Additionally, each of the ribs 176 may further include a second slant surface 176b. The second slant surface 176b may be downwardly slantly formed on a rear end of the rib 176 in the second direction.

Further, slant surfaces 172a and 174a may be formed at the front portions of the upper surfaces of the central supporting portions 172 and the edge supporting portions 174. The slant surfaces 172a and 174a may be downwardly slantly formed along the first direction. Thus, because the slant surfaces 172a and 174a may function as to remove angular structures of the upper ends of the front surfaces of the central supporting portion 172 and the edge supporting portions 174, the upper ends of the front surfaces of the central supporting portion 172 and the edge supporting portions 174 may not collide against the PCB 130.

FIG. 6 is a perspective view illustrating a main bracket of a portable SSD module in accordance with some example embodiments.

Referring to FIG. 6, a main bracket 160a of some example embodiments may not include a rib. The vertical supporting portion 170 of the main bracket 160a may have a slant upper surface in place of the rib. That is, the central supporting portion 172 and the edge supporting portions 174 of the vertical supporting portion 170 may include slant upper surfaces 172a and 174a. Because the slant upper surfaces 172a and 174a may have a structure and a function substantially the same as those of the rib 176, the structure and the function of the slant upper surfaces 172a and 174a may be omitted herein for brevity.

FIGS. 7 and 8 are perspective views illustrating main brackets of a portable SSD module in accordance with some example embodiments.

Referring to FIG. 7, an opening 179 may be formed through the central supporting portion 172. Alternatively, referring to FIG. 8, an opening 179a having an opened front surface may be formed through the central supporting portion 172. The electronic components on the lower surface of the PCB 130 or the SSD 120 may be received in the openings 179 or 179a.

FIG. 10 is an enlarged perspective view illustrating an LED module of the portable SSD module in FIG. 1, and FIG. 11 is a plan view illustrating the LED module in FIG. 10.

Referring to FIGS. 10 and 11, the LED module 150 may include at least one LED 158 and an indicator 153. FIGS. 10-11 illustrate an LED module 150 including four LEDs 158, but it will be understood that in some example embodiments an LED module 150 may include a single, individual LED 158 instead of multiple LEDs 158. In some example embodiments the LED module 150 may include two or more LEDs 158. In some example embodiments, an LED as described herein (e.g., any or all of LEDs 158 as described herein) may be a Light-Emitting Diode under the well-known meaning of the term and may include any or all well-known elements of Light-Emitting Diodes, such that an LED module that includes at least one Light-Emitting Diode LED 158 may be understood to be a Light-Emitting Diode Module under the well-known meaning of the term and may include any or all well-known elements of Light-Emitting Diode Modules. It will be understood that an LED 158 as described herein may include a light-emitting device that is different from a Light-Emitting Diode, for example LED 158 may be any well-known device configured to emit light based on an electric current being passed through any portion thereof (e.g., due to electroluminescence), for example a laser diode. The indicator 153 may include an indicating plate 152 and an indicating channel 154 arranged at a central portion of the indicating plate 152.

In some example embodiments, the indicating plate 152 may have a rectangular shape, particularly, a square shape. The indicating plate 152 may have rounded corners. However, the indicating plate 152 may have other shapes such as a circular shape, a triangular shape, a pentagonal shape, etc., in place of the square shape. The indicating plate 152 may have an opening 156, which may be defined by one or more inner surfaces 152is of the indicating plate 152. The fingerprint sensor 140 may be received in the opening 156. Because the fingerprint sensor 140 may have the square shape, the opening 156 may also have a square shape. Thus, the shape of the opening 156 may be changed in accordance with the shape of the fingerprint sensor 140.

The indicating plate 152 may have (e.g., may include) at least one diffusing groove 190, where one or more outer surfaces of the indicating plate 152 facing a given LED 158, shown in FIGS. 10-11 as diffusing surfaces 192 and 194, define the diffusing groove 190. The LED 158 may be

received in (e.g., located in) the diffusing groove **190**, such that the LED **158** is partially or entirely located within a volume space **190V** that is at least partially defined by the diffusing surfaces **192** and **194**. The volume space **190V** may be further defined by one or more outer surfaces **152os** of the indicating plate **152** as shown in FIGS. **10-11**, and each LED **158** may be partially or entirely within separate, respective volume spaces **190V** as shown, but example embodiments are not limited thereto and the LED **158** may, in some example embodiments, be located in a volume space **190V** that is at least partially defined by diffusing surfaces **192** and **194** and extends beyond a boundary defined by the one or more outer surfaces **152os**. Alight emitted from the LED **158** may diffuse into an interior of the indicator **153** (e.g., the interior of the indicating plate **152**) through the diffusing groove **190**. Restated, the diffusing groove **190** may be configured to diffuse a light beam (e.g., a light) emitted from the LED **158** towards the diffusing groove **190**. The diffusing groove **190** may have an angular shape including at least two diffusing surfaces **192** and **194** configured to diffuse the light. It will be understood that diffusing light includes scattering or diffusing a light beam received at a surface of an object to propagate in multiple directions simultaneously upon passing through the surface into the interior of the object, where such diffusion may be based on the angle range of the surface and/or the material composition of the object. For example, as further described below, the diffusing groove **190** may be configured, based on the angle range of the diffusing groove **190**, for example based on the angle of the one or more diffusing surfaces **192** and **194** in relation to the orientation of the LED **158** located in the volume space **190V** defined by said one or more diffusing surfaces **192** and **194**, to receive an incident light beam **158x** emitted by the LED **158** and incident on the one or more diffusing surfaces **192** and **194** and cause the incident light beam **158x** to be scattered **158y** by the one or more diffusing surfaces **192** and **194** into the interior of the indicator **153** (e.g., the interior of the indicating plate **152**) as shown. Accordingly, it will be understood that a diffusing surface of a diffusing groove **190** as described herein may be configured to diffuse light emitting by an LED **158** received in said diffusing groove **190** based on the angle of the diffusing surface in relation to the orientation of the LED **158** in the diffusing groove **190**. It will be understood that in some example embodiments the diffusing groove **190** may be defined by a single diffusing surface that is at least partially curved (e.g., diffusing surfaces **192** and **194** may be part of a singular, continuous surface that curves at vertex **191**).

In some example embodiments, a diffusing groove **190** is formed at an outer surface **152os** of the indicating plate **152** such that the one or more diffusing surfaces of the diffusing groove **190** define at least a portion of an outer boundary of the indicating plate **152**. In some example embodiments, including the example embodiments shown in FIGS. **10-11**, the diffusing groove **190** may include four diffusing grooves **190** formed at four outer surfaces **152os** of the indicating plate **152**, respectively, such that the diffusing surfaces **192** and **194** of the diffusing grooves **190** are portions of the respective outer surfaces **152os** of the indicating plate **152**. Thus, the four LEDs **158** may be arranged in the four diffusing grooves **190**, respectively. However, the diffusing groove **190** may be formed at any one, two surfaces or three surfaces of the four outer surfaces **152os** of the indicating plate **152**.

The indicating channel **154** may be arranged along one or more inner surfaces **152is** of the indicating plate **152** that defines the opening **156**, where the inner surface(s) **152is**

may also be referred to as inner surface(s) of the opening **156**. As shown, the indicating channel **154** may be arranged at a central portion of the indicating plate **152**, for example such that a center **152-C** of the indicating plate **152** is located within the opening **156** and/or is at a same location as a center of the indicating channel **154**, but example embodiments are not limited thereto, and in some example embodiments the center of the indicating channel **154** and the center **152-C** of the indicating plate **152** may be horizontally offset from each other. Because the opening **156** may have the square shape, the indicating channel **154** may have a square frame shape. Thus, the indicating channel **154** may have an inner corner **154a** and an outer corner **154b**. As shown in FIGS. **10-11**, the indicating channel **154** may have a rectangular frame shape having four inner corners **154a** and four outer corners **154b**, but example embodiments are not limited thereto.

The indicating channel **154** may have an upper surface **154us** higher than an upper surface **152us** of the indicating plate **152**. The indicating plate **152** may be configured to make contact with the upper surface **113** of the case **110** so that only the indicating channel **154** may be exposed through the window **116**. The indicating channel **154** may have an outer surface **154os** configured to make contact with the inner surface of the window **116**. Thus, the user may recognize only the light diffused through the indicating channel **154**. Therefore, the diffusing groove **190** may be provided with a structure for uniformly diffusing the light into the indicating channel **154**. Particularly, the diffusing groove **190** may be provided with a structure for more diffusing the light into the inner corner **154a** and the outer corner **154b** of the indicating channel **154**.

In some example embodiments, the diffusing groove **190** may be positioned on a center line **C** crossing a central portion of the indicating plate **152** (e.g., a center **152-C** of the indicating plate **152**). That is, as shown in at least FIGS. **12-13**, the diffusing groove **190** may be formed at a central portion **152os-C** of an outer surface **152os** of the indicating plate **152**. Further, the diffusing groove **190** may have an isosceles triangular shape that is at least partially defined by two diffusing surfaces that have the same length or substantially the same length. Thus, the diffusing groove **190** may include the two diffusing surfaces **192** and **194** having a same length or substantially same length. The diffusing groove **190** may have a vertex **191** positioned on the center line **C** of the indicating plate **152** so that a distance between the diffusing surface **192** and a left corner of the indicating channel **154** may be substantially the same as a distance between the diffusing surface **194** and a right corner of the indicating channel **154**. The diffusing surfaces **192** and **194** may be configured to diffuse the light toward the both corners of the indicating channel **154**. Thus, the light may be uniformly distributed in the indicating channel **154**. Accordingly, the indicating channel **154** may be configured to emit the light emitted from the LED **158** and diffused into the interior of the indicator **153** (e.g., the interior of the indicating plate **152**) to an exterior of the LED module **150** (e.g., in a direction that is normal to the upper surface **154us** of the indicating channel **154**).

In some example embodiments, the indicating channel **154** and/or the indicating plate **152** having one or more diffusing grooves **190** may be omitted from the indicator **153**.

It will be understood that lengths, distances, or the like described herein as being the “substantially” the same encompasses lengths, distances, or the like that are the same within manufacturing tolerances and/or material tolerances

## 11

and/or lengths, distances, or the like that have a relative difference in magnitude that is equal to or less than 10%.

FIGS. 12 and 13 are plan views illustrating an angle range of a diffusing groove of the LED module in FIG. 11.

Referring to FIG. 12, when the light vertically passing through the central portion of the diffusing surface 192 of the diffusing groove 190 (e.g., pass through a central portion of the diffusing groove 190) may reach to the inner corner 154a of the indicating channel 154 and thus may be incident to the inner corner 154a, a first angle between the diffusing groove 190 and the outer surface of the indicating plate 152 may be  $\theta_1$ . Restated, the first angle  $\theta_1$  may be defined by incident light (e.g., as 158x) that is incident on, and passes through, the central portion of the diffusing groove 190 (e.g., a central portion of diffusing surface 192 as shown) and is incident (e.g., at least a portion of 158y) to any one of the inner corners 154a. When the first angle may be below the  $\theta_1$ , the light vertically passing through the central portion of the diffusing surface 192 may be incident to the opening 156 through the inner corner 154a.

Referring to FIG. 13, when the light vertically passing through the central portion of the diffusing surface 192 of the diffusing groove 190 (e.g., pass through a central portion of the diffusing groove 190) may reach to the outer corner 154b of the indicating channel 154 and thus may be incident to the outer corner 154b, a second angle between the diffusing groove 190 and the outer surface of the indicating plate 152 may be  $\theta_2$ . Restated, the second angle  $\theta_2$  may be defined by incident light (e.g., as 158x) that is incident on, and passes through, the central portion of the diffusing groove 190 (e.g., a central portion of diffusing surface 192 as shown) and is incident (e.g., at least a portion of 158y) to any one of the outer corners 154b. When the second angle may be above the  $\theta_2$ , the light vertically passing through the central portion of the diffusing surface 192 may be incident into the indicating plate 152 through the outer corner 154b.

Therefore, in some example embodiments, including example embodiments wherein the indicating channel 154 includes a rectangular frame shape having four inner corners 154a and four outer corners 154b, an slant angle of the diffusing groove 190 with respect to the outer surface 152os of the indicating plate 152 may have a range between the first angle  $\theta_1$  for allowing the light, which may vertically pass through the central portion of the diffusing groove 190, to be incident to the inner corner 154a of the indicating channel 154 and the second angle  $\theta_2$  for allowing the light to be incident to the outer corner 154b of the indicating channel 154. Restated, the slant angle of the diffusion groove with respect to the outer surface 152os of the indicating plate may have a range between the first angle  $\theta_1$  as defined herein and the second angle  $\theta_2$  as defined herein.

FIG. 14 is a plan view illustrating an LED module in accordance with some example embodiments.

Referring to FIG. 14, an LED module 150a of some example embodiments may include a diffusing groove 190a. The diffusing groove 190a may include a first diffusing surface 192a and a second diffusing surface 194a having different lengths. The diffusing groove 190a may be formed at a portion of the outer surface of the indication plate 152 offset from the center line C crossing the central portion (e.g., the center 152-C) of the indication plate 152, for example such that the diffusing groove 190 does not intersect with the center line C at all and/or that vertex 191 is not on the center line C. Accordingly, as shown in FIG. 14, the diffusing groove 190 may be located at a position that is offset from a center line C that extends normal to the outer surface 152os and intersects the center 152-C of the indi-

## 12

cating plate 152. Thus, a distance between the first diffusing surface 192a and the corner of the indicating channel 154 adjacent to the first diffusing surface 192a may be different from a distance between the second diffusing surface 194a and the corner of the indicating channel 154 adjacent to the second diffusing surface 194a.

In some example embodiments, the diffusing groove 190a may be arranged at a left portion of the center line C. Thus, the distance between the first diffusing surface 192a and the corner of the indicating channel 154 may be shorter than the distance between the second diffusing surface 194a and the corner of the indicating channel 154. In order to induce the light, which may vertically pass through central portions of the first diffusing surface 192a and the second diffusing surface 194a, to the adjacent corners of the indicating channel 154, a first slant angle  $\theta_1$  of the first diffusing surface 192a with respect to the outer surface of the indicating plate 152 may be less than a second slant angle  $\theta_2$  of the second diffusing surface 194a with respect to the outer surface of the indicating plate 152. That is, the length of the first diffusing surface 192a may be longer than the length of the second diffusing surface 194a.

Alternatively, in contrast, the diffusing groove 190a may be arranged at a right portion of the center line C. Thus, a distance between the first diffusing surface 192a and the corner of the indicating channel 154 may be longer than a distance between the second diffusing surface 194a and the corner of the indicating channel 154. In order to induce the light, which may vertically pass through central portions of the first diffusing surface 192a and the second diffusing surface 194a, to the adjacent corners of the indicating channel 154, a first slant angle  $\theta_1$  of the first diffusing surface 192a with respect to the outer surface of the indicating plate 152 may be greater than a second slant angle  $\theta_2$  of the second diffusing surface 194a with respect to the outer surface of the indicating plate 152. That is, the length of the first diffusing surface 192a may be shorter than the length of the second diffusing surface 194a.

FIG. 15 is a plan view illustrating an LED module in accordance with some example embodiments.

Referring to FIG. 15, an LED module 150b of some example embodiments may include a diffusing groove 190b. The diffusing groove 190b may have an isosceles trapezoidal shape, defined by at least three diffusing surfaces 192b, 194b, 196b. The diffusing groove 190b may be positioned on the center line C crossing the central portion of the indicating plate 152.

Therefore, the diffusing groove 190b may include two first diffusing surfaces 192b and 194b having a same length or substantially a same length, and a second diffusing surface 196b connected between ends 195b (e.g., proximate edges) of the first diffusing surfaces 192b and 194b. The light may vertically pass through central portions of the first diffusing surfaces 192b and 194b. The light may then be incident to the both corners of the indicating channel 154. Further, the light may vertically pass through a central portion of the second diffusing surface 196b. The light may then be incident to the central portion of the indicating channel 154.

FIGS. 16, 17, 18, 19, and 20 are perspective views illustrating processes for combining the portable SSD module in FIG. 1.

Referring to FIG. 16, the SSD 120 may be combined with the main bracket 160. Additionally, the thermal pad 168 may be interposed between the SSD 120 and the main bracket 160.

## 13

Referring to FIG. 17, the PCB 130 with the fingerprint sensor 140 and the LED module 150 may be inserted into the case 110 through the opened front surface 111 of the case 110 in the second direction. The PCB 130 may be attached to the upper surface 113 of the case 110 around the window 116 using the adhesive 134. The fingerprint sensor 140 and the LED module 150, particularly, the indicating channel 154 may be exposed through the window 116. Additionally, the cushion 136 may be interposed between the PCB 130 and the upper surface 113 of the case 110.

Referring to FIG. 18, the main bracket 160 with the SSD 120 may be inserted into the case 110 through the opened rear surface 112 of the case 110 in the first direction. The inclined surfaces of the ribs 176 may slidably make contact with the lower surface of the PCB 130 during inserting the main bracket 160 into the case 110.

The PCB 130 may be received in the receiving groove 178 of the main bracket 160. The both side surfaces of the PCB 130 in the receiving groove 178 may be supported by the horizontal supporting portions 164. The rear surface of the PCB 130 in the receiving groove 178 may be supported by the upper portion of the front surface of the body portion 162 in the main bracket 160. The lower surface of the PCB 130 in the receiving groove 178 may be supported by the vertical supporting portion 170. Particularly, the central supporting portion 172 of the vertical supporting portion 170 may be configured to support a central portion of the lower surface of the PCB 130. The edge supporting portions 174 of the vertical supporting portion 170 may be configured to support edge portions of the lower surface of the PCB 130.

Referring to FIG. 19, the front bracket 180 may be inserted into the case 110 through the opened front surface 111 of the case 110 in the second direction. The front bracket 180 may downwardly press the connectors to support the connectors.

Referring to FIG. 20, the sheets 166 and 168 may be attached to the rear surface of the main bracket 160 and the front surface of the front bracket 180 to complete the portable SSD module 100 in FIG. 1.

FIG. 21 is an exploded perspective view illustrating a portable SSD module in accordance with some example embodiments, and FIG. 22 is a cross-sectional view illustrating an internal structure of the portable SSD module in FIG. 21.

A portable SSD module 100a of this example embodiment may include elements substantially the same as those of the portable SSD module 100 in FIG. 1 except for a main bracket, a front bracket and an indicator. Thus, the same reference numerals may refer to the same elements and any further illustrations with respect to the same elements may be omitted herein for brevity.

Referring to FIGS. 21 and 22, the LED may be installed at the SSD 120. Thus, the portable SSD module 100a of this example embodiment may not include a PCB for driving the fingerprint sensor 140. Further, the fingerprint sensor 140 and the indicator 153 of the LED module 150 may be inserted into the case 110 through an upper surface of the window 116.

The indicator 153 may be supported by a front bracket 180a. Particularly, an indicating plate 152a may include a supporting groove 151. The front bracket 180a may include a supporting portion 186 inserted into the supporting groove 151. In contrast, a main bracket 160a may be configured to directly support the indicator 153. In order to expose the LED on the SSD 120, the main bracket 160a may have an opening 169.

## 14

In some example embodiments, the supporting groove 151 may be formed at both side surfaces of the indicating plate 152a in the second direction. The supporting portion 186 may be extended from both side portions of a rear surface of the front bracket 180a. The supporting portions 186 may be inserted into the supporting grooves 151, respectively, to support the indicator 153 by the front bracket 180a.

FIGS. 23, 24, 25, 26, 27, and 28 are perspective views illustrating processes for combining the portable SSD module in FIG. 21.

Referring to FIG. 23, the SSD 120 may be combined with the main bracket 160. The LED may be installed at the SSD 120. Additionally, the thermal pad 168 may be interposed between the SSD 120 and the main bracket 160a.

Referring to FIG. 24, the main bracket 160a with the SSD 120 may be inserted into the case 110 through the opened rear surface 112 of the case 110 in the first direction. The LED on the SSD 120 may be exposed through the opening 169 of the main bracket 160a.

Referring to FIG. 25, the fingerprint sensor 140 may be inserted into the case 110 through the window 116.

Referring to FIG. 26, the indicator 153 of the LED module 150 may be inserted into the case 110 through the window 116. The fingerprint sensor 140 may be positioned in the opening 153-O of the indicator 153.

Referring to FIG. 27, the front bracket 180a may be inserted into the case 110 through the opened front surface 111 of the case 110 in the second direction. The supporting portions 186 of the front bracket 180a may be inserted into the supporting grooves 151 of the indicator 153.

Referring to FIG. 28, the sheets 166 and 168 may be attached to the rear surface of the main bracket 160a and the front surface of the front bracket 180a to complete the portable SSD module 100a in FIG. 21.

FIG. 29 is an exploded perspective view illustrating a portable SSD module in accordance with some example embodiments.

Referring to FIG. 29, a portable SSD module 100b of some example embodiments may include a case 110, an SSD 120, a main bracket 160 and a front bracket 180. That is, the portable SSD module 100b of this example embodiment may not include the fingerprint sensor 140 and the LED module 150 in the portable SSD module 100 of FIG. 1. This, because it may not be required to expose the fingerprint sensor 140 and the LED module 150 through the window 116 in FIG. 1, the case 110 may not have the window 116 in FIG. 1.

The case 110, the SSD 120, the main bracket 160 and the front bracket 180 may have structures substantially the same as those in FIG. 1. Thus, any further illustrations with respect to the case 110, the SSD 120, the main bracket 160 and the front bracket 180 may be omitted herein for brevity.

The main bracket 160 may be arranged in the case 110 to support the SSD 120. Particularly, the rib 176 of the main bracket 160 may slidably make contact with the upper surface of the case 110. The front bracket 180 may be arranged in the case 110 to support the connectors 122 and 124 extended from the SSD 120.

FIG. 30 is a cross-sectional view illustrating a portable SSD module in accordance with some example embodiments, and FIG. 31 is an enlarged cross-sectional view illustrating a portion "A" in FIG. 30.

A portable SSD module 100c of this example embodiment may include elements substantially the same as those of the portable SSD module 100 in FIG. 1 except for an indicator of an LED module. Thus, the same reference numerals may

15

refer to the same elements and any further illustrations with respect to the same elements may be omitted herein for brevity.

Referring to FIGS. 30 and 31, an indicator 153 of this example embodiment may include an indicating plate 152 and an indicating channel 154c. The indicating plate 152 may have a structure substantially the same as that of the indicating plate 152 in FIG. 1. Thus, any further illustrations with respect to the indicating plate 152 may be omitted herein for brevity.

The indicating channel 154c may be configured to enter through the window 116 between the case 110 and the fingerprint sensor 140. In order to accurately align the indicator 153 and the fingerprint sensor 140 with a center of the window 116 when assembling the indicator 153 and the fingerprint sensor 140 with the window 116, the indicating channel 154c may have a gradient shape.

Particularly, as shown in FIGS. 30-31, the indicating channel 154c may have the gradient shape from a lower portion to an upper portion of the indicating channel 154c toward the center of the window 116, such that an outer boundary of the lower portion 154L of the indicating channel 154 may be distal (154OBL) from the central portion (e.g., center 152-C) of the indicating plate 152 in relation to the outer boundary of the upper portion 154U of the indicating channel 154 (154OBU). Similarly, as shown in FIG. 31, when the indicating channel 154c has a gradient shape, from a lower portion to an upper portion of the indicating channel 154c toward the center of the window 116, an inner boundary of the lower portion 154L of the indicating channel 154 may be distal from the central portion (e.g., center 152-C) of the indicating plate 152 in relation to the inner boundary of the upper portion 154U of the indicating channel 154. In some example embodiments, a gradient angle 154G of the indicating channel 154c that results in the indicating channel 154c having the gradient shape may be about 3° to about 3.5°. Thus, an upper portion of an inner surface of the indicating channel 154c having the gradient shape may be configured to make contact with an upper portion of an outer surface of the fingerprint sensor 140. Further, a lower portion of an outer surface of the indicating channel 154c may be configured to make contact with a lower portion of the upper surface 113 of the case 110. Because the fingerprint sensor 140 and the case may support the upper portion of the inner surface and the lower portion of the outer surface of the indicating channel 154c, the indicator 153 and the fingerprint sensor 140 may be accurately aligned with the center of the window 116.

In some example embodiments, the LED modules 150, 150a and 150b may be applied to the portable SSD modules having the above-mentioned structures. However, the LED modules 150, 150a and 150b may also be applied to the portable SSD modules having other structures. Further, the LED modules 150, 150a and 150b may be applied to other electronic devices requiring an emitting function in place of the portable SSD modules.

According to some example embodiments, the main bracket may be configured to support the LED module. Particularly, the slant rib of the main bracket inserted into the rear surface of the case may slidably make contact with the lower surface of the LED module. Thus, the LED module may be readily and firmly combined with the case.

Further, the indicator of the LED module may have the triangular diffusing groove so that the light from the LED may uniformly diffuse toward the whole indicator through the diffusing groove. Particularly, the light may diffuse

16

toward a corner of the indicator. As a result, the indicator may have uniform brightness.

The foregoing is illustrative of some example embodiments and is not to be construed as limiting thereof. Although some example embodiments have been described, those skilled in the art will readily appreciate that many modifications are possible in the example embodiments without materially departing from the novel teachings and advantages of the present inventive concepts. Accordingly, all such modifications are intended to be included within the scope of the present inventive concepts as defined in the claims. In the claims, means-plus-function clauses are intended to cover the structures described herein as performing the recited function and not only structural equivalents but also equivalent structures. Therefore, it is to be understood that the foregoing is illustrative of various example embodiments and is not to be construed as limited to the specific example embodiments disclosed, and that modifications to the disclosed example embodiments, as well as other example embodiments, are intended to be included within the scope of the appended claims.

What is claimed is:

1. A portable solid-state drive (SSD) module comprising:
  - a case having an open front surface, an open rear surface and a window;
  - an SSD arranged in the case;
  - a fingerprint sensor exposed through the window to recognize a fingerprint of a user for securing the SSD;
  - a main bracket inserted into the case through the open rear surface to support the fingerprint sensor; and
  - a front bracket inserted into the case through the open front surface to support connectors configured to connect the SSD with the fingerprint sensor.
2. The SSD module of claim 1, wherein the main bracket is configured to upwardly support the fingerprint sensor.
3. The SSD module of claim 2, wherein the main bracket comprises at least one rib formed on an upper surface of the main bracket, and wherein the at least one rib is downwardly inclined from the open rear surface to the open front surface of the case to slidably make contact with a lower surface of the fingerprint sensor.
4. The SSD module of claim 2, wherein the main bracket comprises:
  - a body portion positioned between the case and the SSD;
  - a pair of horizontal supporting portions horizontally extended from both portions of a front surface of the body portion to support both side surfaces of the fingerprint sensor; and
  - a vertical supporting portion arranged between the horizontal supporting portions to support a lower surface of the fingerprint sensor, wherein the vertical supporting portion comprises:
    - a central supporting portion configured to support a central portion of the lower surface of the fingerprint sensor; and
    - a pair of edge supporting portions arranged at both sides of the central supporting portion to support edge portions of the lower surface of the fingerprint sensor.
5. The SSD module of claim 1, further comprising a cushion interposed between the front bracket and the connectors.
6. The SSD module of claim 1, wherein the fingerprint sensor comprises at least one supporting groove and the front bracket comprises at least one supporting portion inserted into the supporting groove.

17

7. The SSD module of claim 1, further comprising a thermal pad interposed between the main bracket and the SSD to dissipate a heat from the SSD.

8. A portable solid-state drive (SSD) module comprising:  
a case having an open front surface, an open rear surface

and a window;

an SSD arranged in the case;  
a light-emitting device (LED) module arranged in the case to indicate an operation of the SSD through the window;

a fingerprint sensor installed adjacent to the LED module and exposed through the window to recognize a fingerprint of a user for securing the SSD;

a main bracket inserted into the case through the open rear surface to support the LED module and the fingerprint sensor; and

a front bracket inserted into the case through the open front surface to support connectors configured to connect the SSD with the LED module and the fingerprint sensor.

9. The SSD module of claim 8, wherein the main bracket comprises:

a body portion positioned between the case and the SSD;  
a pair of horizontal supporting portions horizontally extended from both portions of a front surface of the body portion to support both side surfaces of the LED module; and

a vertical supporting portion arranged between the horizontal supporting portions to support a lower surface of the LED module.

10. The SSD module of claim 9, wherein the vertical supporting portion has an upper surface lower than upper surfaces of the horizontal supporting portions to form a receiving groove for receiving the LED module and the fingerprint sensor between the vertical supporting portion and the horizontal supporting portions.

11. The SSD module of claim 9, wherein the vertical supporting portion comprises:

a central supporting portion configured to support a central portion of the lower surface of the LED module; and

a pair of edge supporting portions arranged at both sides of the central supporting portion to support edge portions of the lower surface of the LED module, wherein the vertical supporting portion further comprises one or more ribs formed on upper surfaces of the central supporting portion and the edge supporting portions, and wherein the one or more ribs are downwardly inclined from the open rear surface to the open front surface of the case to slidably make contact with the lower surface of the LED module.

12. The SSD module of claim 8, wherein the LED module comprises:

at least one LED; and  
an indicator configured to indicate a light emitted from the LED,

wherein the indicator comprises a diffusing groove configured to receive the LED and to diffuse the light emitted from the LED into the indicator, and the diffusing groove has an angular shape including at least two diffusing surfaces.

13. The SSD module of claim 12, wherein the indicator comprises:

an indicating plate including a rectangular central opening; and

18

an indicating channel arranged on an inner surface of the opening of the indicating plate to indicate the light emitted from the LED,

wherein the diffusing groove is arranged at a central portion of each of outer surfaces of the indicating plate.

14. The SSD module of claim 12, wherein the LED module comprises at least one supporting groove and the front bracket comprises at least one supporting portion inserted into the supporting groove.

15. The SSD module of claim 12, further comprising a thermal pad interposed between the main bracket and the SSD to dissipate a heat from the SSD.

16. A portable solid-state drive (SSD) module comprising:  
a case having an open front surface, an open rear surface,  
an upper surface having a window and a lower surface;

an SSD arranged on the lower surface of the case;  
an LED module including at least one LED and an indicator configured to indicate a light emitted from the LED, the indicator including a diffusing groove configured to receive the LED and to diffuse the light emitted from the LED into the indicator, and the diffusing groove having an angular shape including at least two diffusing surfaces;

a fingerprint sensor installed adjacent to the LED module and exposed through the window to recognize a fingerprint of a user for securing the SSD;

a main bracket including a body portion inserted into the case through the open rear surface and positioned between the case and the SSD, a pair of horizontal supporting portions horizontally extended from both side portions of a front surface of the body portion to support both side surfaces of the LED module, and a vertical supporting portion arranged between the horizontal supporting portions to support a lower surface of the LED module, the vertical supporting portion including at least one rib formed on an upper surface of the vertical supporting portion, and wherein the at least one rib is downwardly inclined from the rear surface to the front surface of the case to slidably make contact with the lower surface of the LED module;

a front bracket inserted into the case through the open front surface to support connectors configured to connect the SSD with the LED module and the fingerprint sensor; and

a thermal pad interposed between the main bracket and the SSD to dissipate a heat from the SSD.

17. The SSD module of claim 16, wherein the vertical supporting portion has an upper surface lower than upper surfaces of the horizontal supporting portions to form a receiving groove for receiving the LED module and the fingerprint sensor between the vertical supporting portion and the horizontal supporting portions.

18. The SSD module of claim 16, wherein the vertical supporting portion comprises:

a central supporting portion configured to support a central portion of the lower surface of the LED module; and

a pair of edge supporting portions arranged at both sides of the central supporting portion to support edge portions of the lower surface of the LED module, wherein the rib is formed on upper surfaces of the central supporting portion and the edge supporting portions.

19. The SSD module of claim 16, wherein the indicator comprises:

an indicating plate including a rectangular central opening; and

**19**

an indicating channel arranged on an inner surface of the opening of the indicating plate to indicate the light emitted from the LED,

wherein the diffusing groove is arranged at a central portion of each of outer surfaces of the indicating plate. 5

**20.** The SSD module of claim **16**, wherein the LED module comprises at least one supporting groove and the front bracket comprises at least one supporting portion inserted into the supporting groove.

\* \* \* \* \*

10

**20**