




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : G06T 15/50	A1	(11) International Publication Number: WO 99/27497 (43) International Publication Date: 3 June 1999 (03.06.99)
(21) International Application Number: PCT/US98/25061		(81) Designated States: CA, JP, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).
(22) International Filing Date: 23 November 1998 (23.11.98)		
(30) Priority Data: 08/978,984 26 November 1997 (26.11.97) US		Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>
(71) Applicant: VITAL IMAGES, INC. [US/US]; Suite 100, 3100 West Lake Street, Minneapolis, MN 55416-4510 (US).		
(72) Inventor: ARGIRO, Vincent, J.; 504 Kingman Circle, Fairfield, IA 52556 (US).		
(74) Agent: VIKSNINS, Ann, S.; Schwegman, Lundberg, Woessner & Kluth, P.O. Box 2938, Minneapolis, MN 55402 (US).		

(54) Title: VOLUME RENDERING LIGHTING USING DOT PRODUCT METHODOLOGY



(57) Abstract

Volume rendering lighting using dot product methodology is disclosed. In one embodiment of the invention, a computer includes a processor, a computer-readable medium and a computer program. The medium stores first data representing a set of voxel data representing an object, each voxel datum having a gradient that is desirably either positive or negative, and second data representing a light source having a directional vector. The computer program is executed by the processor from the medium, and displays the set of the voxel data, including illuminating each voxel datum using a dot product of the gradient of the voxel datum with the directional vector of the light source.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Republic of Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

VOLUME RENDERING LIGHTING USING DOT PRODUCT METHODOLOGY

5

FIELD OF THE INVENTION

The present invention relates generally to the display of images that are three-dimensional volume renderings, and more particularly to lighting in the display of such images using dot product methodology.

10

BACKGROUND OF THE INVENTION

Because of the increasingly fast processing power of modern-day computers, users have turned to computers to assist them in the examination and analysis of images of real-world data. For example, within the medical community, radiologists and other professionals who once examined x-rays hung on a light screen now use computers to examine images obtained via ultrasound, computed tomography (CT), magnetic resonance (MR), ultrasonography, positron emission tomography (PET), single photon emission computed tomography (SPECT), magnetic source imaging, and other imaging techniques. Countless other imaging techniques will no doubt arise as medical imaging technology evolves.

Each of the above-identified imaging procedures generates volume images, although each relies on a different technology to do so. Thus, CT requires an x-ray source to rapidly rotate around a patient to obtain up to hundreds of electronically stored pictures of the patient. Conversely, for example, MR requires that radio-frequency waves be emitted to cause hydrogen atoms in the body's water to move and release energy, which is then detected and translated into an image. Because each of these techniques penetrates the body of a patient to obtain data, and because the body is three-dimensional, this data represents a three-dimensional image, or volume. In particular, CT and MR both provide three-dimensional "slices" of the body, which can later be electronically reassembled.

Computer graphics images, such as medical images, have typically been modeled through the use of techniques such as surface rendering and other

geometric-based techniques. Because of known deficiencies of such techniques, researchers have turned to volume-rendering techniques as a more accurate way to render images based on real-world data. Volume-rendering takes a conceptually intuitive approach to rendering, by assuming that three-dimensional objects are composed of basic volumetric building blocks.

5 These volumetric building blocks are commonly referred to as voxels. Whereas, by contrast, the well known pixel is a picture element -- i.e., a tiny two-dimensional sample of a digital image have a particular location in the plane of a picture defined by two coordinates -- a voxel is a sample that exists within a

10 three-dimensional grid, positioned at coordinates x, y, and z. The voxel has a "voxel value," as that value is obtained from real-world scientific or medical instruments. The voxel value may be measured in any of a number of different units, such as hounsefield units, which are well known to those of ordinary skill within the art.

15 Using volume-rendering, any three-dimensional volume can be simply divided into a set of three-dimensional samples, or voxels. Thus, a volume containing an object of interest is dividable into small cubes, each of which contain some piece of the original object. This continuous volume representation is transformable into discrete elements by assigning to each cube a

20 voxel value that characterizes some quality of the object as contained in that cube.

The object is thus summarized by a set of point samples, such that each voxel is associated with a single digitized point in the data set. As compared to mapping boundaries in the case of geometric-based surface-rendering,

25 reconstructing a volume using volume-rendering requires much less effort and is more intuitively and conceptually clear. The original object is reconstructed by the stacking of voxels together in order, so that they accurately represent the original volume.

Although more simple on a conceptual level, and more accurate in

30 providing an image of the data, volume-rendering is nevertheless still complex. A key requisite of volume rendering is the use of the entire voxel data set to create an image. In one method of voxel rendering, called image ordering or ray

casting, the volume is positioned behind the picture plane, and a ray is projected perpendicularly from each pixel in the picture plane through the volume behind the pixel. As each ray penetrates the volume, it accumulates the properties of the voxels it passes through and adds them to the corresponding pixel. The 5 properties accumulate more quickly or more slowly depending on the transparency of the voxels.

In another method, called object-order (or compositing or splatting), the voxel values are also combined to produce image pixels for display on a computer screen. The image plane is positioned behind the volume, and each 10 pixel is assigned an initial background value. A ray is projected perpendicularly from the image plane through the volume to the viewer. As the ray encounters each successive layer of voxels, the voxel values are blended into the background, forming the image according to each voxel's interpreted opacity. The image rendered in this method as well depends on the transparency of the 15 voxels.

Typically in either method, lighting of the voxel data (i.e., providing for lighting values of the voxel data) is accomplished by conceptually placing a light source coincident with the viewer's perspective, such that each voxel is illuminated insofar as it reflects light back towards the light source (i.e., toward's 20 the viewer's perspective). In most situations, this provides for adequate lighting. However, in some instances, voxel data representing features that have surfaces facing away from the light source are desirable to illuminate, but cannot be provided with lighting insofar as they do not reflect light back towards the light source.

25 For example, a blood vessel may have an outer wall facing the light source, and an inner wall on the other side of the outer wall that does not face the light source. This inner wall may be desirable to light for clinical diagnosis, but cannot be by the method just described. A light source directed towards the outer wall, that is, provides for illumination of the outer wall because the surface 30 of the outer wall points back to the light source; however, the light source does not provide for lighting of the inner wall because the surface of the inner wall points away from the light source. This is disadvantageous in those situations

where lighting both walls is desirable for proper clinical diagnosis, however, and represents an existing shortcoming in current volume-rendering technology.

SUMMARY OF THE INVENTION

The above-identified shortcomings, problems, and disadvantages found 5 in the prior art, as well as other shortcomings, problems, and disadvantages, are addressed by the present invention. The invention relates to the lighting of volume-rendered images by using a dot product methodology. A volume-rendered image includes a set of voxel data that represents an object. Each voxel datum within the set of voxel data may have a gradient associated with it 10 representing the direction of the surface of the voxel datum. Furthermore, a light source is defined as having a vector representing the direction in which light emits from the source. Thus, a positive gradient may mean that the surface points in the same direction as does the light source (assuming the light source has a positive vector), while a negative gradient may mean that the surface points 15 in the opposite does as does the light source (again assuming that the light source has a positive vector).

In one embodiment of the invention, a computer includes a processor, a computer-readable medium and a computer program. The medium stores first 20 data representing the set of voxel data, each voxel datum having a gradient that is desirably either positive or negative, and second data representing the light source having the directional vector. The computer program is executed by the processor from the medium, and displays the set of the voxel data, including lighting each voxel datum using a dot product of the gradient of the voxel datum with the directional vector of the light source. (It is noted that for purposes this 25 application, taking the dot product of the gradient and the directional vector means more specifically taking the dot product of the vector of the gradient -- i.e., the gradient vector -- and the directional vector.)

The invention thus illuminates surfaces of the object regardless of whether the surface points towards or away from the light source, overcoming 30 disadvantages found in the prior art. For example, voxel data having positive gradients where the light source has a positive directional vector would not be lighted within the prior art, because the surface points away from the light source

such that light would not be reflected back towards the light source. However, under the invention, a dot product of the gradient and the directional vector (more specifically, the absolute value of the dot product) would yield a non-zero lighting value, such that this voxel data would be illuminated. (Note that the 5 only voxel data not lighted by the inventive approach is that which have gradients at a right angle to the lighting source, such that the absolute dot product would be zero.)

In varying embodiments of the invention, computerized system, computerized methods, and computers are disclosed. Still other and further 10 aspects, advantages and embodiments of the invention will become apparent by reading the following specification, and by reference to the drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a diagram of a typical computer in conjunction with which embodiments of the invention may be implemented;

15 FIGs. 2(a), 2(b) and 2(c) are diagrams showing the manner by which a voxel is lighted in accordance with the prior art;

FIGs. 3(a), 3(b) and 3(c) are diagrams showing the manner by which a voxel is lighted in accordance with one embodiment of the invention;

20 FIG. 4 is a flowchart of a computerized method in accordance with one embodiment of the invention.

DETAILED DESCRIPTION OF THE INVENTION

In the following detailed description of the preferred embodiments, reference is made to the accompanying drawings which form a part hereof, and in which is shown by way of illustration specific preferred embodiments in 25 which the inventions may be practiced. These embodiments are described in sufficient detail to enable those skilled in the art to practice the invention, and it is to be understood that other embodiments may be utilized and that logical, mechanical and electrical changes may be made without departing from the spirit and scope of the present invention. The following detailed description is, 30 therefore, not to be taken in a limiting sense, and the scope of the present invention is defined only by the appended claims.

The detailed description is divided into four sections. In the first section, a description of a typical computer in conjunction with which embodiments of the invention may be implemented is provided. In the second section, an overview of the invention is provided. In the third section, a description of a 5 computerized method in accordance with one embodiment of the invention is given. Finally, in the fourth section, a conclusion is presented.

Computer

In this section of the detailed description, a description of a typical computer in conjunction with which embodiments of the invention may be 10 implemented is provided. Referring to FIG. 1, the hardware shown includes computer 100, keyboard 102, pointing device 104, display device 106, and other components 107 (represented by a block diagram). Computer 100 is in one embodiment UNIX compatible. More particularly, computer 100 in one embodiment is a Silicon Graphics, Inc. (SGI) workstation running in an 15 OSF/Motif window environment, with a graphical user interface. Such SGI workstations include the SGI O2, which in one embodiment runs the SGI Irix 6.3 operating system, in which case the embodiment is based on the OpenGL graphics library, and uses the Viewkit class library. The invention is not limited, however, to any particular computer 100.

20 As shown in FIG. 1, pointing device 104 is a mouse, although the invention is not limited to any particular pointing device. For example, pointing device 104 may also be a point stick, trackball, or a touch pad. The pointing device typically has three buttons, although no embodiment of the invention is so particularly limited. As described herein, clicking, selecting, pressing, or 25 holding, etc., of a pointing device button (such as a mouse button) refers to the clicking, selecting, pressing, or holding, etc., of the left button if there is more than one button on the pointing device.

In one embodiment of the invention, an additional pointing device (viz., part of other components 107 as shown in FIG. 1) is also coupled to computer 30 100. This additional pointing device is a three-dimensional controller, which allows a user of the invention easy control of the fly through feature of embodiments of the invention. One such pointing device is the Spacetec IMC

SpaceBall 3003. Display device 106 can be any of a number of different devices, but in one embodiment of the invention is a computer monitor having a cathode ray tube (CRT). In the embodiment of the invention where computer 100 is an SGI workstation, display device 106 is a twenty-one inch monitor capable of 5 displaying twenty-four-bit color graphics, and having a resolution of 1280 x 1024 pixels. Furthermore, other components 107 may in varying embodiments of the invention include a video cassette recorder, or a printer. Computer 100 may also have the capability of hooking up to a network (such as a DICOM network), may have Internet or intranet capability, or have access to a DICOM 10 server. Each of these is well known to those skilled in the art.

Not shown in FIG. 1 is that computer 100 typically includes a central-processing unit (CPU), a random-access memory (RAM), and a read-only memory (ROM). The CPU, RAM, and ROM may be of any type; no embodiment of the invention is particularly limited. In the embodiment of the 15 invention where computer 100 is an SGI workstation, the CPU is a MIPS R10000 or an R5000, and there are typically one-hundred-twenty-eight megabytes of RAM. Also not shown in FIG. 1 is that computer 100 also usually comprises a fixed storage device such as a hard disk drive, and a removable storage device such as a tape cartridge drive or floppy disk drive. Conversely, 20 such components may be external components to computer 100, in which case they are a part of other components 107. The tape cartridge drive in one embodiment is compatible with a General Electric Genesis tape archive format. The memory (e.g., RAM and ROM) and the storage devices (e.g., hard drives, floppy disks, tapes, etc.), are types of computer-readable media.

25 The invention provides an environment in which volume data comprised of voxels is displayed. No embodiment of the invention is limited as to the programming language by which the software aspect providing this environment is implemented. However, in one embodiment, the language is the object-oriented programming language C++. Furthermore, no embodiment of the 30 invention is limited as to what the volume data comprised of voxels represents. In one embodiment of the invention, the volume data (voxel data) represents medical images of various parts of the human body, as scanned in from a

medical imaging device. One embodiment of the invention specifically relates to the viewing of volume-related medical images; however, it should be understood to and appreciated by those of ordinary skill within the art that no embodiment of the invention is so limited.

5

Overview of the Invention

In this section of the detailed description, an overview of an exemplary embodiment of the invention is described. As has been stated, a volume-rendered image includes a set of voxel data -- that is, a set of individual voxel datums or "voxels." Each voxel has a voxel value, such that the set of voxel data 10 has a range of voxel values, spanning from the lowest voxel value for any voxel within the set, to the highest voxel value for any voxel within the set.

Furthermore, each voxel has a gradient associated with it. The gradient represents the direction of the surface of the voxel. For sake of simplicity, it is assumed here that a positive gradient means that the voxel's surface direction is 15 coincident with the direction of an imaginary light source placed in front of the image -- that is, that the voxel's surface direction is the same as a directional vector of the light source -- and a negative gradient means that the voxel's surface direction is opposite to the direction of the light source. The imaginary light source is used in conjunction with the gradient of the surface of a voxel to 20 derive a lighting value for the voxel, which dictates the illumination of that voxel. Desirably, the light source is coincident with a viewer of the voxel data.

FIGs. 2(a) and 2(b) show the manner by which a lighting value is obtained for a voxel in accordance with the prior art. Specifically, FIG. 2(a) shows the situation in which a voxel has a surface having a direction pointing 25 towards the light source, such that the voxel is illuminated. Light source 200 has directional vector 202, which is defined as positive. Voxel 204 has gradient 206 pointing in the opposite direction to vector 202, and thus is negative. Voxel 204 is provided with a non-zero lighting value because light emitted by light source 200, as represented by arrow 208, is reflected by voxel 204 back towards the 30 light source, as represented by arrow 208.

Conversely, FIG. 2(b) shows the situation in which a voxel has a surface having a direction pointing away from the light source, such that the voxel is not

illuminated. Light source 250 has directional vector 252, which is defined as positive. Voxel 254 has gradient 256 pointing in the same direction as vector 252, and thus is also positive. Voxel 254 is provided with a zero lighting value because light emitted by light source 250, as represented by arrow 258, is not 5 reflected by voxel 254; the gradient of voxel 254 is not in an opposite direction to that of the directional vector of light source 250. Therefore, as shown in FIG. 2(b), a disadvantage with the prior art is that voxels having gradients pointing 10 away from the light source are not provided with lighting values.

FIG. 2(c) shows a screen shot of a blood vessel (CT data) illuminated in 10 accordance with the prior art. The interior of the blood vessel is blacked out, because the gradients of the voxels comprising the interior wall of the blood vessel point inward, away from the light source (assumed to be pointing from the outside in as well). Conversely, the exterior of the blood vessel is visible, because the gradients of the voxels comprising the exterior wall of the blood 15 vessel point outward, towards the light source.

FIGs. 3(a) and 3(b), by comparison, show the manner by which a lighting value is obtained for a voxel in accordance with one embodiment of the invention. Specifically, FIG. 3(a) shows the situation in which a voxel has a surface having a direction pointing towards the light source. Light source 300 20 has directional vector 302, which is defined as positive. Voxel 304 has gradient 306 pointing in the opposite direction to vector 302, and thus is negative. Voxel 304 is provided with a non-zero lighting value because the absolute dot product 25 of the directional vector of light source 300 and the gradient of voxel 304 is itself non-zero. Thus, as in the prior art, in the situation where a voxel has a surface having a direction pointing towards the light source, the invention provides for lighting of the voxel.

Furthermore, FIG. 3(b) shows the situation in which a voxel has a surface having a direction pointing away from the light source, but is nevertheless still illuminated. Light source 300 has directional vector 352, which is defined as 30 positive. Voxel 354 has gradient 356 pointing in the same direction as vector 352, and thus is also positive. Voxel 354 is provided with a non-zero lighting value because the absolute dot product of the directional vector of light source

350 and the gradient of voxel 354 is itself non-zero. Thus, unlike in the prior art, in the situation where a voxel has a surface having a direction pointing away from the light source, the invention nevertheless provides for lighting of the voxel. Therefore, in situations where such lighting is desirable, the invention

5 provides for an advantage over the prior art.

FIG. 3(c) shows a screen shot of a blood vessel (CT data) illuminated in accordance with the invention. The interior of the blood vessel is visible, even though the gradients of the voxels comprising the interior wall of the blood vessel point inward, away from the light source (assumed to be pointing from the 10 outside in as well). This is because the absolute dot products of the gradients and their corresponding light sources are non-zero. Similarly, the exterior of the blood vessel is visible, because the absolute dot products of the gradients of the voxels comprising the exterior wall of the blood vessel and their corresponding light sources are also non-zero.

15 In one specific implementation of an embodiment of the invention, the embodiment of the invention builds upon the Phong lighting model known in the art, and the lighting methodology described generally in Drebin, U.S. Pat. No. 4,835,721. Specifically, those skilled in the art are knowledgeable of the mathematics of lighting as described in page 191 of Jackie Neider, "OpenGL Programming Guide" (1993) (ISBN 0-201-63274-8), the chapter entitled "The Mathematics of Lighting". In the prior art, the intensity of light reflected from each voxel is proportional to the dot product of the surface normal or gradient vector and the light direction vector. When the angle between these vectors is greater than ninety degrees, this dot product is negative. In the prior art, this 20 value is clamped to zero (as shown on page 191 of the Neider reference), providing no illumination. In the specific implementation of one embodiment of the invention, conversely, illumination is proportional to the absolute value of the dot product of the surface normal or gradient vector and the light direction vector, such that two-sided lighting is realized.

25

Computerized Method

In this section of the detailed description, a computerized method according to one embodiment of the invention is shown. The method may be implemented as a computer program executed by a processor of a computer-
5 readable medium of a computer, such as a memory or a nonvolatile storage device. The medium stores first data representing a set of voxel data, each voxel datum having a gradient, desirably either positive or negative, and second data representing a light source having a directional vector. The computer program thus illuminates the voxel data (i.e., provides lighting values for the voxel data),
10 and also desirably displays the voxel data on the display device of the computer.

Referring then to FIG. 4, a flowchart of a computerized method according to one embodiment of the invention is shown. In step 400, for each voxel within the set of voxel data stored in the computer-readable medium, a dot product of the gradient of the voxel and the directional vector of the light source
15 is calculated. The dot product, as understood by those of ordinary skill within the art, is a mathematical function. Then in step 402, the voxel data may be displayed on the display device of the computer, as a lighting value has been provided for each voxel by step 400. It is noted that other operations may be performed on the voxel data prior to its being amenable to display on the display
20 device; however, these operations, as well as displaying the voxel data on the display device, are understood by those of ordinary skill in the art.

Conclusion

Volume rendering lighting using a dot product methodology has been described. Although specific embodiments have been illustrated and described
25 herein, it will be appreciated by those of ordinary skill in the art that any arrangement which is calculated to achieve the same purpose may be substituted for the specific embodiments shown. This application is intended to cover any adaptations or variations of the present invention. Therefore, it is manifestly intended that this invention be limited only by the following claims and
30 equivalents thereof.

What is claimed is:

1. A computer to assist in displaying a set of voxel data representing an object, the computer comprising:
 - 5 a processor;
 - a computer-readable medium storing
 - first data representing the set of voxel data, each voxel datum having a gradient selected from the group of gradients essentially consisting of a positive gradient and a negative gradient;
 - 10 second data representing a light source having a directional vector; and,
 - a computer program executed by the processor from the medium to display the set of voxel data, including illuminating each voxel datum using an absolute value of a dot product of the gradient of the voxel datum with the
 - 15 directional vector of the light source.
2. The computer of claim 1, wherein the light source is coincident with a viewer of the set of voxel data.
- 20 3. The computer of claim 1, wherein the positive gradient corresponds to a direction aligned with the directional vector of the light source.
4. The computer of claim 1, wherein the negative gradient corresponds to a direction opposite to the directional vector of the light source.
- 25 5. The computer of claim 1, wherein each gradient corresponds to a direction in which the surface of the voxel datum having the gradient points.
- 30 6. The computer of claim 1, wherein illuminating each voxel datum using the absolute value of the dot product of the gradient of the voxel datum with the directional vector of the light source provides for illumination of voxel data having a direction aligned with the directional vector of the light source.

7. A computerized system to assist in displaying a set of voxel data representing an object, each voxel datum with the set having a gradient selected from the group of gradients essentially consisting of a positive gradient and a negative gradient, the system comprising:

5 a display device; and,

means for illuminating each voxel datum of the set of voxel data using an absolute value of a dot product of the gradient of the voxel datum and a light source having a directional vector.

10 8. The computerized system of claim 7, wherein illuminating each voxel datum using the absolute value of the dot product of the gradient of the voxel datum with the directional vector of the light source provides for illumination of voxel data having a direction aligned with the directional vector of the light source.

15

9. A computerized method to assist in displaying a set of voxel data representing an object on a display device of a computer comprising for each voxel datum within the set:

20 determining an absolute value of a dot product of a gradient of the voxel datum selected from the group of gradients essentially consisting of a positive gradient and a negative gradient with a directional vector of a light source; and, displaying the voxel datum on the display device as determined by the absolute value of the dot product of the gradient of the voxel datum with the directional vector of the light source.

25

10. The computerized method of claim 9, wherein illuminating each voxel datum using the absolute value of the dot product of the gradient of the voxel datum with the directional vector of the light source provides for illumination of voxel data having a direction aligned with the directional vector of the light source.

30




FIG. 1




FIG. 2(a)
(PRIOR ART)




FIG. 2(b)
(PRIOR ART)



FIG. 2(c)
(Prior Art)




FIG. 3(a)




FIG. 3(b)



FIG. 3(c)

6/6




FIG. 4

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 98/25061

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 G06T15/50

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 6 G06T

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 283 837 A (WOOD CHRISTOPHER H) 1 February 1994 see column 5, line 8 - line 18 -----	1
A	FR 2 614 163 A (THOMSON CGR) 21 October 1988 see page 17, line 12 - line 30 -----	1

Further documents are listed in the continuation of box C.

Patent family members are listed in annex.

° Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance
"E" earlier document but published on or after the international filing date
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
"O" document referring to an oral disclosure, use, exhibition or other means
"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

Date of mailing of the international search report

16 March 1999

22/03/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Burgaud, C

INTERNATIONAL SEARCH REPORT

...formation on patent family members

Intern al Application No

PCT/US 98/25061

Patent document cited in search report	Publication date	Patent family member(s)			Publication date
US 5283837	A	01-02-1994			NONE
FR 2614163	A	21-10-1988	DE	3874889 A	29-10-1992
			EP	0348434 A	03-01-1990
			WO	8808169 A	20-10-1988
			JP	3500695 T	14-02-1991
			US	5245538 A	14-09-1993