



Office de la Propriété
Intellectuelle
du Canada

Un organisme
d'Industrie Canada

Canadian
Intellectual Property
Office

An agency of
Industry Canada

CA 2073708 C 2003/06/17

(11)(21) **2 073 708**

(12) **BREVET CANADIEN
CANADIAN PATENT**

(13) **C**

(22) Date de dépôt/Filing Date: 1992/07/14

(41) Mise à la disp. pub./Open to Public Insp.: 1993/01/18

(45) Date de délivrance/Issue Date: 2003/06/17

(30) Priorité/Priority: 1991/07/17 (P 41 23 603) DE

(51) Cl.Int.⁵/Int.Cl.⁵ C07C 69/96, C07C 68/00

(72) Inventeurs/Inventors:
LANDSCHEIDT, HEINZ, DE;
KLAUSENER, ALEXANDER, DE;
WOLTERS, ERICH, DE;
BLANK, HEINZ U., DE;
BIRKENSTOCK, UDO, DE

(73) Propriétaire/Owner:
BAYER AKTIENGESELLSCHAFT, DE

(74) Agent: FETHERSTONHAUGH & CO.

(54) Titre : PROCEDE POUR LA PREPARATION DE CARBONATES DE DIALKYLE

(54) Title: PROCESS FOR THE PREPARATION OF DIALKYL CARBONATES

(57) **Abrégé/Abstract:**

Dialkyl carbonates can be prepared by reaction of carbon monoxide with alkyl nitrites in continuous gas phase reaction, in which a platinum metal halide catalyst on aluminium oxides, aluminium oxide hydrates or aluminium hydroxides as support and, if desired, an additive comprising an antimony, bismuth, aluminium, copper, vanadium, niobium, tantalum, tin, iron, cobalt, nickel compound or a mixture of a plurality thereof on this catalyst are used and hydrogen halide is replaced during the course of the reaction batchwise or continuously in at least the amount which is discharged from the reactor together with the reaction mixture. This results in the formation of dialkyl carbonates in almost quantitative selectivity, while the corresponding dialkyl oxalates can not in most cases be detected. The abovementioned supports are characterised by a BET surface area of more than 1 m²/g.



Process for the preparation of dialkyl carbonates

A b s t r a c t

Dialkyl carbonates can be prepared by reaction of carbon monoxide with alkyl nitrites in continuous gas phase reaction, in which a platinum metal halide catalyst on aluminium oxides, aluminium oxide hydrates or aluminium hydroxides as support and, if desired, an additive comprising an antimony, bismuth, aluminium, copper, vanadium, niobium, tantalum, tin, iron, cobalt, nickel compound or a mixture of a plurality thereof on this catalyst are used and hydrogen halide is replaced during the course of the reaction batchwise or continuously in at least the amount which is discharged from the reactor together with the reaction mixture. This results in the formation of dialkyl carbonates in almost quantitative selectivity, while the corresponding dialkyl oxalates can not in most cases be detected. The abovementioned supports are characterised by a BET surface area of more than 1 m²/g.

23189-7366

5 Process for the preparation of dialkyl carbonates

Background of the Invention

1. Field of the Invention

10 The present invention relates to a process for the preparation of dialkyl carbonates by reaction of carbon monoxide (CO) with alkyl nitrites in the presence of a platinum group metal halide catalyst on aluminium oxides, aluminium oxide hydrates or aluminium hydroxides as support which may contain additives of compounds of further elements. The aforementioned supports are characterised by a BET surface area of
15 more than 1 m²/g.

Dialkyl carbonates are of general chemical importance. Thus, for example, diethyl carbonate is an excellent solvent in the medium boiling range. Furthermore, dialkyl carbonates are excellent carbonylating and acylating agents. Finally, they are of
20 great importance in the preparation of other carbonates, of urethanes and of ureas.

2. Description of the Related Art

The preparation of dialkyl carbonates by reactions of phosgene or alkyl chloroformates with alcohols is known. However, there is an increasing interest in
25 replacing the use of the toxic phosgene or the intermediates derived therefrom, such as the chloroformic ester, by other processes. In addition to attempts to obtain dialkyl carbonates by reaction of CO with lower alcohols, in particular those processes are important in which CO is reacted in the gas phase with alkyl nitrite over a platinum group metal catalyst. In reactions of this type, the formation of dialkyl
30 oxalate is always observed apart from the desired dialkyl carbonate. Thus, EP 425,197 discloses a process which, according to its preferred embodiment, results in dialkyl carbonates of methanol or ethanol from CO and methyl nitrite or ethyl nitrite in the gas phase over a PdCl₂ catalyst on activated carbon. The selectivities to give
35 the desired lower dialkyl carbonates reach values of up to 94% according to this EP 425,197, Table 1; however, lower dialkyl oxalates and CO₂ are always observed as by-products. Moreover, upon attempting to carry this process in practice, the high

23189-7366

selectivities mentioned could only be reproduced insufficiently. The catalysts of this EP 425,197 contain additives of chlorides of base metal; a substantial addition of hydrogen chloride in an amount of 1 to 50%, relative to the platinum group metal in the catalyst, is added to the system or a portion of the catalyst must be removed from the reactor and subjected to a treatment with hydrogen chloride.

The Journal for Catalytic Research (China), Vol. 10 (1), p. 75-78 (1989) also uses a carbon support as support for a Pd catalyst so as to obtain dimethyl carbonate from CO and methyl nitrite, in which however dimethyl oxalate is always additionally formed.

A Pd/carbon catalyst is also mentioned in Chin. Sci. Bull. 34 (1989), 875-76 for the preparation of dimethyl carbonate from CO and methyl nitrite.

This preference for a carbon support is not unexpected, since Platinum Metals Review 34 (1990), 178-180 reports with reference to the earlier literature that in the reaction of a lower alkyl nitrite with CO over a Pd catalyst different main products are obtained depending on the support; according to this reference a carbon support predominantly produces dialkyl carbonates, while an Al_2O_3 support mainly produces dialkyl oxalates.

Summary of the Invention

It has now been found that the use of aluminium oxides, aluminium oxide hydrates or aluminium hydroxides as catalyst support does not only lead unexpectedly to dialkyl carbonates when CO is reacted with alkyl nitrites, but moreover additionally also achieved a significant increase in selectivity to give the desired dialkyl carbonates to such an extent that in addition to more than 97% of selectivity, in many cases more than 99% of selectivity to give these dialkyl carbonates, in general it is not possible to detect any oxalate at all. Only a small amount of CO_2 can be observed in the reaction mixture. Moreover, the use of $\gamma\text{-Al}_2\text{O}_3$ as support, which was not considered possible, has the essential advantage of increased stability and abrasion resistance, compared with a supported catalyst based on a carbon support.

23189-7366

A process for the preparation of dialkyl carbonates of the formula



in which

5 R represents straight-chain or branched $\text{C}_1\text{-C}_4\text{-}$ alkyl,

by reaction of carbon monoxide (CO) with alkyl nitrites of the formula



10 in which

R has the meaning given,

in the presence or absence of an inert gas and in the presence or absence of the parent alcohol ROH and in the presence or absence of NO over a supported platinum group
15 metal catalyst at elevated temperature in continuous gas phase reaction has been found, which process is characterised in that the support used comprises aluminium oxides, aluminium oxide hydrates or aluminium hydroxides, the platinum group metal is in the form of a halide or a
20 halide-containing complex compound in which the platinum group metal halide or the platinum group metal halide-containing complex can be formed under the reaction conditions in situ in the process reactor from the platinum group metal or a halogen-free platinum group metal compound
25 by means of hydrogen halide, the catalyst is furthermore optionally provided with an additive comprising an antimony, bismuth, aluminium, copper, vanadium, niobium, tantalum,

23189-7366

tin, iron, cobalt, nickel compound or a mixture of a plurality thereof, and the reaction is carried out at a nitrite:CO volume ratio of 0.1-10:1, preferably 0.2-4:1, especially preferably 0.3-3:1, and a temperature of 50-
5 150°C, preferably 70-120°C, especially preferably 70-110°C, hydrogen halide being replenished batchwise or continuously in at least an amount which is suitable to replace the amount in which hydrogen halide is discharged from the reactor together with the reaction mixture.

Detailed Description of the Invention

5 The reaction in the process according to the invention proceeds according to the following equation:



10 Examples of straight-chain or branched alkyl having 1-4 C atoms are methyl, ethyl, propyl, isopropyl, butyl, isobutyl, preferably the n-alkyls mentioned, particularly preferably methyl and ethyl and very particularly preferably methyl.

15 In principle it is possible to start with a mixture of different alkyl nitrites, which however also leads to a mixture of different dialkyl carbonates and, in some cases, unsymmetrically substituted dialkyl carbonates. For a uniform reaction it is therefore preferred to start with only one alkyl nitrite.

20 While it is in principle possible to react CO with an alkyl nitrite without any further mixture component, for example if the composition of the mixture is outside the explosion limits, an inert gas is in many cases used for diluting the reactants. Examples of inert gases are noble gases, nitrogen and carbon dioxide, preferably argon, nitrogen or carbon dioxide, particularly preferably nitrogen and carbon dioxide. The amount of inert gas is 20-80% by volume, preferably 30-70% by volume, relative to the entire gas volume to be introduced into the reactor. The inert
25 gas and any unconverted residual amounts of the reactants contained therein can be recycled.

The volume ratio of the reactants nitrite and CO to one another is 0.1-10:1, preferably 0.2-4:1, particularly preferably 0.3-3:1.

30 The gas mixture to be reacted can furthermore contain small amounts of alcohol ROH, for example in an amount of 0-10% by volume, and small amounts of NO, for example in an amount of 0-10% by volume, both relative to the entire volume of the gas mixture to be used. These additions of ROH or NO can originate, for example,
35 from the preparation of the alkyl nitrite and be introduced, for example, together with the latter into the reaction gas mixture. The catalyst support according to the inventive process comprises aluminium oxide, aluminium oxide hydrate or

aluminium hydroxide or a mixture of more than one of these compounds or it has a content thereof. The content of said compounds is 1-100% by weight of the support as a whole. Values below 100% by weight are a result of standard contents of natural impurities or impurities resulting from the method of manufacture of the above compounds. Such impurities, e.g. SiO_2 , Fe_2O_3 , TiO_2 , CaO , MgO , Na_2O , K_2O , B_2O_3 or a combination of more than one of these compounds, or inorganic sulphates, carbonates and/or chlorides, are in some cases only present in trace amounts. The contents of the abovementioned aluminium oxides, aluminium oxide hydrates or aluminium hydroxides in the supports are preferably 80-100% by weight and particularly preferably 90-100% by weight. Other values below 100% by weight apply in the case of support preparations in which the abovementioned aluminium compounds are applied to other supports such as SiO_2 , TiO_2 , pumice, CaCO_3 , BaSO_4 , etc. and envelope such supports in the form of shells. In this case the contents of the abovementioned aluminium compounds are 1-60% by weight, and preferably 1-30% by weight, of the support preparation.

The BET surface area of the abovementioned aluminium compounds is higher than $1 \text{ m}^2/\text{g}$, and is preferably $10 \text{ m}^2/\text{g}$ or more, particularly preferably $50 \text{ m}^2/\text{g}$ or more, and most preferably $100 \text{ m}^2/\text{g}$ or more. The upper value for the BET surface area can be as high as up to $500 \text{ m}^2/\text{g}$ or more, and most preferably up to $400 \text{ m}^2/\text{g}$ or more. The aluminium oxides, aluminium oxide hydrates and aluminium hydroxides are defined by the general formula



in which

n denotes one of the integers 0, 1, 2 or 3 and
 m has a value from 0 to 10, preferably from 0 to 5.

The expression $m\text{H}_2\text{O}$ refers to the removable water phase, which in many cases does not take part in the formation of the crystal lattice, so that m can also have values which are not integers. On calcinating such support materials m can reach the value zero.

One important aluminium compound is $\gamma\text{-Al}_2\text{O}_3$.

23189-7366

Many of the abovementioned support materials are commercially available, such as for example SPH-501, -508, -517, -535 and -537 from Rhone-PoulencTM; CS-331/1, -331/3 and -331/5 from SüdchemieTM; GS-2261/1, -2261/2 and -2261/3
5 from KalichemieTM; Pural-S/SB 30, -S/SB 50, -S/SB 70 and TKA-168 from CondeaTM; D 10-10 from BASFTM; A 980 from Hoechst CeramTecTM and L 22 from GirdlerTM.

The reactive component of the catalyst for the process according to the invention comprises in its reactive
10 state the platinum group metal halide or a complex compound containing the platinum group metal halide. Complex compounds of this type are generally known and are, for example, alkali metal chloride complex compounds, such as lithium tetrachloropalladate or sodium tetrachloropalladate,
15 $\text{Li}_2[\text{PdCl}_4]$ or $\text{Na}_2[\text{PdCl}_4]$.

Furthermore, it has been found that the platinum group metal halide or the complex compound containing the platinum group metal halide can also be formed under the reaction conditions, i.e. in the presence of the gas mixture
20 to be reacted, in situ from metallic platinum group metal or a halogen-free platinum group metal compound by means of hydrogen halide. Accordingly, the reactor can also be filled with an otherwise comparable catalyst containing the platinum group metal initially in metallic form or prepared
25 by means of a halogen-free platinum group metal compound. Examples of suitable halogen-free platinum group metal compounds of this type are platinum group metal acetates, nitrates, propionates, butyrates, carbonates, oxides, hydroxides or others known to one skilled in the art.

23189-7366

Elements from the group of platinum metals according to the invention are Pd, Pt, Ir, Ru and Rh, preferably Pd, Ru and Rh, and particularly preferably Pd.

Halides according to the invention are fluoride, 5 chloride, bromide and iodide, preferably chloride and bromide and particularly preferably chloride.

The amount of the platinum group metal halide or the complex compound containing the platinum group metal halide is 0.01-8% by weight, preferably 0.05-4% by weight, 10 calculated as platinum group metal and based on the overall weight of the catalyst.

The catalyst for the process according to the invention is furthermore optionally provided with an additive comprising an antimony, bismuth, aluminium, copper, 15 vanadium, niobium, tantalum, tin, iron, cobalt, nickel compound or a mixture of a plurality thereof; preferably, such an additive is present. Such additives are present in salt-like or metallic form of the elements mentioned. In a manner similar to that described above for the platinum 20 group metal, the halide form, for example, of such additives if formed from the metallic form of these additives and hydrogen halide under the reaction conditions. Preferably, such additives comprise an antimony, bismuth, aluminium, vanadium, niobium, tantalum compound or a mixture of a 25 plurality thereof, particularly preferably they comprise a halide of these elements, very particularly preferably a chloride of these elements. The amount of additive is 0.1-100 times, preferably 0.2-10 times, the amount of the platinum group metal calculated as metal not only for the 30 additive but also for the platinum group metal.

23189-7366

A catalyst to be used according to the invention is prepared by methods which are generally known to one skilled in the art. Thus, the support can be impregnated or sprayed with a solution of one of the platinum group metal compounds mentioned. The same procedure is used for the additive(s) mentioned. In the case where it is desired to fix the platinum group metal as a metal or in the form of the carbonate, oxide or hydroxide on the support and only to activate it in the reactor under the reaction conditions in the manner described by means of hydrogen halide to give platinum group metal halide, the platinum group metal compound applied can be reduced to the metal by means of a suitable reducing agent in a manner known to one skilled in the art or converted into the carbonate, oxide or hydroxide by means of a suitable precipitant.

Examples of the many methods of preparing the catalysts or catalyst supports which can be used according to the invention are as follows:

1. producing mouldings from the abovementioned oxidic and hydroxyoxidic aluminium compounds,
2. incorporating the catalytically active components, such as the abovementioned platinum group metals or compounds thereof, as well as where appropriate, the abovementioned additives into the basic composition of the support prior to moulding,

23189-7366

3. subsequently loading the finished mouldings by impregnation, immersion or spraying, using salts of the platinum group metals and, where appropriate, of the additional elements,
- 5 4. rolling or spraying oxidic or hydroxyoxidic aluminium compounds onto agglomerates of any desired composition and origin,
- 10 5. rolling or spraying oxidic or hydroxyoxidic aluminium compounds already containing incorporated platinum group metals or compounds thereof, as well as, where appropriate, the abovementioned additives according to 2, onto the agglomerates according to 4, or
- 15 6. subsequently loading the supports produced according to 4 as described under 3.

Furthermore, it has been observed that in order to achieve uniformly high selectivities of dialkyl carbonate, it is advantageous to transport hydrogen halide to the catalyst while it is in use. However, it has further been observed that this amount of hydrogen halide can be significantly less than described in the literature, as mentioned above. Thus, it is only necessary to replenish the amount of hydrogen halide originating from the active form of the catalyst and discharged together with the reaction products. This amount can be determined by analysis. It is in general in the range from 50-5,000 ppm of hydrogen halide in the reactant gas mixture.

Hydrogen halide according to the invention is hydrogen fluoride, hydrogen chloride, hydrogen bromide and hydrogen iodide, preferably hydrogen chloride and hydrogen bromide, and particularly preferably hydrogen chloride.

Hydrogen halide can be metered into the reaction mixture as such in gaseous form. However, it can also be metered in dissolved in one of the substances present in the reaction mixture, thus, for example, dissolved in the alcohol on which the alkyl nitrite is based.

Catalysts of the type described have a long life (>200 h). In addition to the mechanical stability and abrasion resistance already described, they retain their activity and selectivity over an exceptionally long period.

The gas hourly space velocity (GHSV) over the catalyst mentioned can be 700-17,000 l of mixture of the gaseous reactants per l of catalyst per hour.

5

The process according to the invention is carried out at a temperature of 50-150°C, preferably 70-120°C, particularly preferably 70-110°C, and a pressure of 0.8-10 bar, preferably 1-7 bar, particularly preferably 1-6 bar.

10

The alkyl nitrites to be used according to the invention are prepared by known processes, for example from the corresponding alcohol and nitrous acid, which is formed for example in situ, from an alkali metal nitrite and a mineral acid, such as sulphuric acid. The nitrogen monoxide NO formed during the course of the process according to the invention can be regenerated continuously using oxygen and new

15

alcohol to give alkyl nitrite (German Offenlegungsschrift 3,834,065) and recycled together with unconverted reactants.

20

25

30

35

ExamplesDefinitions

5

The space-time yield (STY) in [g/lxh] and the yield of dimethyl carbonate in the examples is calculated by $\frac{n_{\text{DMC}}}{v_{\text{Cat}} \times t}$ in which n_{DMC} is the amount of dimethyl carbonate (DMC) formed, v_{Cat} is the catalyst volume and t the time.

10

The selectivity S (%) for dimethyl carbonate is calculated by

$$S = \frac{n_{\text{DMC}}}{n_{\text{DMC}} + 2x n_{\text{ODME}} + n_{\text{AME}} + n_{\text{FDA}}} \times 100$$

15

in which

- n_{DMC} is the amount of dimethyl carbonate,
 n_{ODME} is the amount of dimethyl oxalate,
 20 n_{AME} is the amount of methyl formate,
 n_{FDA} is the amount of formaldehyde dimethyl acetal.

Comparative Example 1 (vide EP 425,197)

- 25 100 ml of activated carbon granules were impregnated in a known manner with a solution of PdCl_2 and CuCl_2 in water, and the product was dried at 80°C in vacuo (20 mm Hg). The ready-to-use catalyst contained 8 g of Pd/l and 8 g of Cu/l.

Example 1

30

100 ml of an Al_2O_3 with a BET internal surface of $185 \text{ m}^2/\text{g}$ were impregnated with an aqueous Li_2PdCl_4 solution, and the product was dried at 80°C in vacuo (29 mm hg). The catalyst then contained 8 g of Pd/l.

35

Description of the process

5 In an upright glass tube, the respective catalyst was placed between a packing of Raschig rings.

10 The glass tube was heated to 90°C, and was fed with a gas mixture comprising HCl, CO₂, CH₃ONO, CO and CH₃OH. The gas leaving the reactor was cooled to 5°C, and the condensed phase obtained was analysed by gas chromatography. The uncondensed products were detected by means of IR spectroscopy and mass spectroscopy.

15

20

25

30

35

Table: Examples 2 and 3; Comparative Examples 2 and 3 (according to the description of the process)

Example	Catalyst	Reactant Gas Mixture (% by vol.)					GHSV* (h ⁻¹)	STY **	S **	STY ***	S ***
		CO	CH ₃ ONO	CH ₃ OH	CO ₂	HCl(ppm)					
Comp.Ex.2	from Comp.Ex.1	22.5	22.5	5	50	1,100	800	120	97.0	100	95.0
Example 2	from Example 1	22.5	22.5	5	50	1,100	800	330	99.8	330	99.8
Comp.Ex.3	from Comp.Ex.1	25	26	6.5	42.5	1,100	2,400	480	97.0	370	94.0
Example 3	from Example 1	25	26	6.5	42.5	1,100	2,400	1,030	99.8	1,020	99.8

* GHSV = Gaseous Hourly Space Velocity

** after 1/2 hour

*** after 10 hours

23189-7366

CLAIMS:

1. A process for the preparation of a dialkyl carbonate of the formula



5 in which

R represents straight-chain or branched C₁-C₄-alkyl,

by reaction of carbon monoxide (CO) with an alkyl nitrite of the formula

10 RONO

in which R has the meaning given,

in the presence or absence of an inert gas and in the presence or absence of a parent alcohol ROH and in the presence or absence of NO over a supported platinum group
15 metal catalyst at elevated temperature in continuous gas phase reaction, wherein the support used is an aluminum oxide, an aluminum oxide hydrate or an aluminum hydroxide having a BET internal surface of more than 1 m²/g, the platinum group metal is in the form of a halide or a halide
20 containing complex compound, in which the platinum group metal halide or the platinum group metal containing halide complex compound can be formed under the reaction conditions in situ in the process reactor from the platinum group metal or a halogen-free platinum group metal compound by means of
25 hydrogen halide, the catalyst furthermore can be provided with an additive comprising an antimony, bismuth, aluminum, copper, vanadium, niobium, tantalum, tin, iron, cobalt, nickel compound or a mixture of a plurality thereof, and the

23189-7366

reaction is carried out at a nitrite:CO volume ratio of 0.1-10:1 and a temperature of 50-150°C, hydrogen halide being replenished batchwise or continuously at least in the amount which is suitable to replace the amount in which it is
5 discharged from the reactor together with the reaction mixture.

2. The process of claim 1, wherein the reaction is carried out at 70-120°C.

3. The process of claim 1, wherein the reaction is
10 carried out at 70-110°C.

4. The process of any one of claims 1 to 3, wherein the reaction is carried out at a nitrite:CO volume ratio of 0.2-4:1.

5. The process of any one of claims 1 to 3, wherein
15 the nitrite:CO volume ratio is 0.3-3:1.

6. The process of any one of claims 1 to 5, wherein the catalyst support consists of 1-100% by weight of the total support of the oxidic or hydroxyoxidic Al compound.

7. The process of any one of claims 1 to 6, wherein
20 the BET internal surface is 10 m²/g or more.

8. The process of any one of claims 1 to 6, wherein the BET internal surface is 50 m²/g or more.

9. The process of any one of claims 1 to 6, wherein the BET internal surface is 100 m²/g or more.

25 10. The process of any one of claims 1 to 9, wherein the platinum group metal is one or more from the group of Pd, Pt, Ir, Ru and Rh.

23189-7366

11. The process of any one of claims 1 to 9, wherein the platinum group metal is one or more from the group of Pd, Ru and Rh.

12. The process of any one of claims 1 to 9, wherein
5 the platinum group metal is Pd.

13. The process of any one of claims 1 to 12, wherein the halogen in the halide and in the hydrogen halide is fluorine, chlorine, bromine or iodine.

14. The process of any one of claims 1 to 12, wherein
10 the halogen is chlorine or bromine.

15. The process of any one of claims 1 to 12, wherein the halogen is chlorine.

16. The process of any one of claims 1 to 15, wherein the replenished hydrogen halide is of an amount of 50-5,000
15 ppm, based on the reactant gas mixture.

17. The process of any one of claims 1 to 16, wherein the reaction is carried out in the presence of an inert gas, the amount of inert gas being 20-80% by volume of the overall gas volume.

20 18. The process of any one of claims 1 to 17, wherein a dimethyl carbonate or a diethyl carbonate is prepared by reaction of the CO with methyl nitrite or ethyl nitrite.

19. The process of any one of claims 1 to 17, wherein a dimethyl carbonate is prepared by reaction of the CO with
25 methyl nitrite.

20. The process of any one of claims 1 to 19, wherein the reaction is carried out at a pressure of 0.8-10 bar.