

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau



(10) International Publication Number

WO 2016/153911 A1

(43) International Publication Date

29 September 2016 (29.09.2016)

WIPO | PCT

(51) International Patent Classification:
G06T 1/00 (2006.01) *H04L 9/32* (2006.01)

(21) International Application Number:
PCT/US2016/022836

(22) International Filing Date:
17 March 2016 (17.03.2016)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
62/136,146 20 March 2015 (20.03.2015) US
14/725,399 29 May 2015 (29.05.2015) US
62/303,320 3 March 2016 (03.03.2016) US
62/308,057 14 March 2016 (14.03.2016) US

(71) Applicant: **DIGIMARC CORPORATION** [US/US];
9405 Sw Gemini Drive, Beaverton, OR 97008 (US).

(72) Inventors: **SCHULTE, Jeffrey, B.**; 466 Sw Valeria View Dr., Apt. 206, Portland, OR 97225 (US). **EVANS, Eric, D.**; 2237 Ne 9th Avenue, Portland, OR 97212 (US). **SHARMA, Ravi, K.**; 4247 Nw 125th Avenue, Portland, OR 97229 (US). **HOLUB, Vojtech**; 2020 Sw Salmon, Apt., 703, Portland, OR 97205 (US). **HAAGA, Donald**; 6523 Se 20th Avenue, Portland, OR 97202 (US).

(74) Agent: **STEWART, Steven, W.**; Digimarc Corporation, 9405 SW Gemini Drive, Beaverton, OR 97008 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

- with international search report (Art. 21(3))
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))

(54) Title: SPARSE MODULATION FOR ROBUST SIGNALING AND SYNCHRONIZATION




Fig. 1

(57) Abstract: Sparse signal modulation schemes encode a data channel on a host image in a manner that is robust, flexible to achieve perceptual quality constraints, and provides improved data capacity. The host image is printed by any of a variety of means to apply the image, with sparse signal, to an object. After image capture of the object, a decoder processes the captured image to detect and extract data modulated into the sparse signal. The sparse signal may incorporate implicit or explicit synchronization components, which are either formed from the data signal or are complementary to it.

WO 2016/153911 A1

Sparse Modulation for Robust Signaling and Synchronization

Technical Field

The invention relates to signal communication in noisy environments, and in particular to robust signal communication within host media signals, such as digital 5 watermarking.

Background and Summary

Many approaches have been developed for encoding machine readable information on objects. Perhaps the most well-known technique is the ubiquitous barcode. Over the years, various barcode types have been created, which differ 10 significantly from the name-sake pattern of dark linear bars on a lighter background. Now, the term barcode has been used to encompass machine symbols in various shapes, sizes, patterns and colors.

These types of codes were primarily developed to be reliable data carriers that could be applied with a wide array of print and marking techniques on many types of 15 objects. They were not designed, in most cases, to be aesthetically pleasing, or to be weaved into other imagery, whether it be graphical designs, text etc. on product packaging, labels, or displays. As such, in most applications, these codes occupy a dedicated location on an object, where no other information is located. This approach has worked well to reliably apply identifying information to objects, including packaging, 20 parts (“Direct Part Marking”), etc. Nevertheless, placing the code at a dedicated location limits the ability to find and read the code. When used on consumer goods, it is often located on the back or bottom of the item so as not to interfere with consumer messaging and product aesthetics. This placement of the code tends to slow down code reading or increase scanner cost by requiring additional components to capture multiple views of an 25 object. It also increases risk of injury due to the need for workers to re-position the

object to scan the code for auto-identification. Obviously, this undermines the theoretical speed and reliability advantages of auto-identification.

Data signaling techniques have been developed that have promise in addressing these drawbacks while providing additional advantages. One such technique is referred

5 to as digital watermarking. Digital watermarking provides a method of encoding information within image content or object surface topology. As such, it can be applied over the entire surface of the object within minimal cost and changes to workflow, addressing the drawbacks of barcodes while being fully compatible with them.

Additionally, the digital watermarking applies to many different types of media,

10 including analog and digital forms of images (including video) and audio. This enables enterprises to implement auto-identification and auxiliary data encoding across all of their assets, including physical and digital media.

Watermarking advantageously exploits the existing image or audio information as a carrier of additional information. This additional information is often referred to as the

15 “watermark payload,” a variable sequence of message symbols inserted per unit of host content. There are, of course, limits to the extent to which this payload can be inserted in existing image or audio (the host signal) without impacting the perceptual quality of the host. Generally speaking, host signals with more variable information provide greater opportunity to insert the payload, whereas host signals with uniform or solid tones

20 provide less opportunity for insertion of the payload. In cases where there is little host signal content, it may not be possible to encode the payload, or if it is encoded, it is done so with a greater impact on perceptual quality.

Perceptual quality relates to the extent to which a human perceives a change in an image. This is a challenging metric, as it has a significant subjective component.

25 Nevertheless, the human visual system has been modeled, and data from user tests can be used to construct a classifier that measures in a quantitative way, whether a change to an image or video will be visible or deemed objectionable. Human visual system models and classifiers based on them provide a measure of whether a change made to an image is

likely to be visible, and also, can quantify visibility in units such as Just Noticeable Difference (JND) units. For applications where images are modified to insert a data signal, the perceptual quality is a constraint on data signal design and encoding strategy. The importance of this constraint on signal design and encoding methodology varies with 5 the application. The flexibility of the watermark signal allows it to be transformed into visual elements of the object's design in various ways, and as such, provides many options for adapting the signal to satisfy perceptual quality constraints for different types of images and applications.

Literature documenting our earlier work describes various ways to deal with host 10 signal types that lack signal content compatible with data encoding. We refer to one approach as "sparse" marking as the data carrying signal is formed as a sparse array of signal elements. For visual media, the sparse array of elements works well on portions of a host image that are uniform or solid tones or appear largely blank. With greater sophistication in the signaling, it also is effective in encoding blank areas around text of a 15 document, label, visual display or package, as our signaling schemes employ robust data encoding strategies to mitigate impact of interference from the text. In one embodiment, a sparse mark is comprised of a pattern of spatial locations where ink is deposited or not. For example, the sparse signal may be comprised of ink dots on a light background, such that the signal forms a pattern of subtly darker spatial locations. The signal is designed to 20 be sparse by the spacing apart of the darker locations on the light background.

Conversely, the signal may be designed as an array of lighter "holes" on a relatively darker background. See, for example, US Patent Nos. 6,345,104, 6,993,152 and 7,340,076.

As described in US Patent Nos. 6,345,104, this strategy of forming patterns of 25 light and dark elements is consistent with our earlier digital watermarking strategies that modulate luminance. For example, a lighter element encodes a first message symbol (e.g., binary one), while a darker element encodes a second symbol (e.g., binary zero).

The sparse signal has minimal impact on visual quality due to its sparse arrangement. However, the trade-off for applications like automatic object identification is that more sophistication is required in the data signaling methodology to ensure that the data carried within the sparse signal may be reliably and efficiently recovered in many 5 different and challenging environments. The sparse nature of the signal dictates that less payload may be encoded per unit of object surface area. Further, within the sparse signal, there is a trade-off between allocating signal for payload capacity versus signal for robustness. In the latter category of robustness, the signaling scheme must support recovery in environments of geometric distortion, which occurs when the sparse signal is 10 imaged from various angles, perspectives and distances, in the presence of noise of various types that tends to interfere with the data signal.

There are various sources of geometric distortion that need to be addressed to reliably recover the payload in the sparse signal. Examples of geometric distortion include signal cropping and warping. Cropping truncates portions of the sparse signal, 15 e.g., in cases where only a portion is captured due to occlusion by other objects or incomplete capture by a scanner. Warping occurs when the surface on which the sparse signal is applied is curved (on cups or cans) or wrinkled (on bags and flexible plastic or foil pouches) and when the sparse signal is imaged from a surface at various perspectives.

The design of a signaling scheme must also account for practical challenges posed 20 by constraints on digital circuitry, processors and memory for encoding and decoding. These include computational efficiency, power consumption, memory consumption, memory bandwidth, use of network bandwidth, cost of hardware circuitry or programmable processors/circuitry, cost of designing and integrating encoders and decoders within signal transmitter and receiver, equipment, etc. For example, some 25 encoding schemes may provide optimized encoding or decoding, but may not be applicable because they are too slow for encoding or decoding in real time, e.g., as the host signal is being transmitted, received, updated, or being processed with multiple other signal processing operations concurrently.

The design must also account for practical challenges of the marking technology. The printing technology must be able to reproduce the signal reliably. This includes transformation of the data signal in the Raster Image Processor as well as application of an image to an object.

5 The design must also account for practical challenges posed by image capture and associated optics. Scanners at Point of Sale (POS), for example, tend to be tuned to detect black and white bar codes (e.g., with a spectral range that focuses on image capture around image content at a wavelength at or around 660 nm), and as such, the illumination type and sensors may have a much more limited range of spectral bands and resolutions
10 that the device can sense.

Sparse signaling is particularly challenging in that the sparse nature of the signal provides less opportunity to include signal for payload and robustness. In particular, there is less opportunity to include payload and synchronization. The strategy for synchronization may rely on an explicit synchronization (“sync”) component or an
15 implicit synchronization component. In the latter case, the encoding of the payload may be arranged in a manner that provides a pattern that facilitates detection and synchronization.

Another important consideration for some applications is compatibility and interoperability with other messaging protocols. For example, in the case of applying
20 identification over the surface of objects, the signal encoding and decoding strategy should preferably support various protocols to deal with various image types, printing technologies, and scanner technologies. This design consideration dictates that sparse signaling should be compatible with encoding and decoding other signaling, like legacy encoding schemes on older objects and dense watermark signaling strategies and
25 barcodes of various types. Preferably, the installed base of decoder technology should be able to efficiently decode signals from various signaling types, including new sparse signal arrangements.

One aspect of the disclosure is a method for inserting a sparse, variable data carrying signal into an image. This method provides a first signal component, which facilitates a synchronization function of the sparse signal. It also provides a second signal component that is modulated to carry a variable data signal. The first and second signal components have values located at coordinates within a two-dimensional block. The method combines the first signal component and the second signal component to produce the sparse, variable data carrying signal by setting sparse elements at coordinates within the two-dimensional block where the first and second component signal values provide compatible modulation of the image. The method inserts the sparse, variable data carrying signal into at least a first image layer or channel of an image design.

In this method, the sparse signal elements are set at coordinates where the signal components provide compatible modulation. Compatible modulation is where the signals of the two components comply with a consistency rule. For example, the signals have a consistent direction of modulation of an optical property at a coordinate within the two-dimensional block. One optical property is brightness or lightness and it may be modulated in a darker or lighter direction. Other examples of optical properties are chrominance and hue. Components that modulate an image in the same direction, e.g., both darker or both lighter, have a compatible modulation direction.

The consistency rule may also be determined by consistency in amount of modulation. For instance, modulation of the components is compatible if the value of signal components fall within a common range bounded by at least one threshold. In some cases, components are multi-valued, and then quantized to quantization levels or bins (multi-dimensional values falling in a bin space are quantized to a bin). This may be implemented by applying a threshold, in which values within a range are set to a particular value. Multi-valued components are converted into binary levels (e.g., 1 or 0) or more than two levels (e.g., 1, 0, -1), for example. The consistency rule is evaluated on the output of this process by comparing the values of the signal components at a coordinate and setting sparse element or not at the coordinate based on the consistency.

A logical AND operation or like comparison may be used to determine whether the signal components satisfy the consistency rule, e.g., quantize to a common quantization level or range bounded by a threshold.

The quantizing of a signal can be used to determine a distribution of sparse

5 elements in a block. In one embodiment, for example, a signal component (e.g., sync component) is quantized to provide a sparse distribution within a block. The sparse signal is then formed based on where the signal components comply with a consistency rule. The consistency rule evaluates signal components at these locations and sets a sparse element at the coordinate where they are consistent.

10 Another aspect of the disclosure is a method for inserting a sparse, variable data carrying signal into an image that employs orthogonal signal components. First and second orthogonal components are provided, with at least one of them modulated with variable data. The orthogonal components are combined to produce a sparse, variable data carrying signal by selecting a subset of the first and second orthogonal components.

15 This sparse signal is then inserted into at least a first image layer of an image design. The components may be quantized into sparse signals, and then combined. Alternatively, they may be combined and then quantized into a sparse signal.

Another aspect of the disclosure is an alternative method for inserting a sparse, variable data carrying signal into an image. In this method, a sparse pattern of elements
20 at coordinates within a two-dimensional block is provided, along with a signal component that is modulated to carry a variable data signal. The method generates a sparse, variable data carrying signal by distributing the signal component within the two-dimensional block based on the location of the sparse pattern of elements. In one such approach, the signal component is converted to a sparse, variable data carrying signal by
25 removing signal elements of the signal component at coordinates where the signal component does not coincide with coordinates of the sparse pattern. The signal component is repeated in two-dimensional blocks within the image. Different sparse patterns may be used to distribute the signal component differently in the blocks.

In this document, we detail various sparse signaling schemes, including schemes for generating signals, and encoding and decoding them in various object types and object marking technologies. We describe schemes that encode a sparse signal within host signal carrier in a manner that is robust, flexible to achieve perceptual quality 5 constraints, and provides improved data capacity.

Brief Description of the Drawings

Fig. 1 is a block diagram of a signal encoder for encoding a data signal into a host signal.

Fig. 2 is a block diagram of a signal decoder for extracting a data signal from a 10 host signal.

Fig. 3 is a flow diagram illustrating operations of a signal generator.

Fig. 4 is a diagram illustrating an example of a sparse signal generator.

Fig. 5 is a diagram illustrating a refinement of a sparse signal generator like the one in Fig. 4.

15 Fig. 6 is a histogram of a digital watermark signal component.

Fig. 7 is a histogram of another digital watermark signal component.

Fig. 8 is a histogram of a combination of the digital watermark signal components of Figs. 6 and 7, and also depicts examples of different thresholds used to generate a binary image comprising black and white pixels from an image comprised of multi-valued pixels.

20 Fig. 9 is a diagram illustrating another refinement of the sparse signal generator of Fig. 4.

Fig. 10 is a diagram illustrating application of a threshold to a watermark signal, and the resulting output for three different thresholds.

25 Fig. 11 illustrates a portion of a sparse signal.

Fig. 12 illustrates the sparse signal of Fig. 11, modified to reduce the signal using a line screen approach.

Fig. 13 is a diagram illustrating a method of decoding a watermark signal or sparse signal.

Fig. 14 illustrates one class of pattern detection methods in which a template (labeled “signal”) and the filtered spectrum of a suspect signal (labeled “measured”) are 5 transformed into a log polar (LP) coordinate system and correlated with each other to produce a LP correlation.

Fig. 15 is a diagram depicting properties of additives used to enhance detection of encoded data signals.

Fig. 16A shows a printed label. Figs. 16B and 16C show magnified excerpts from 10 Fig. 16A.

Fig. 17A shows a machine-encoded label. Figs. 17B and 17C show magnified excerpts from Fig. 17A.

Fig. 18A shows a guard band region defined around printed text. Fig. 18B shows guard band areas associated with the full label of Fig. 16A.

15 Fig. 19A shows a printed label in which machine encoding is not applied within guard band regions surrounding text. Figs. 19B and 19C show magnified excerpts from Fig. 19A.

Figs. 20A and 20B reproduce Figs. 17B and 19B, side by side.

20 Fig. 21 shows that successively larger regions may surround printed text, enabling machine marking to be applied at different levels of intensity.

Fig. 22 shows a marking element.

Fig. 23 shows an excerpt of label artwork, including different zones with machine encoding at different strengths.

25 Figs. 24A and 24B tabulate percentages of sync signal elements that have values below different thresholds, for two different embodiments.

Figs. 25A, 25B, 25C and 25D show 2x2 marking blocks.

Figs. 26A, 26B, 26C, 26D, 26E, 26F, 26G, 26H, and 26I show exemplary 3x3 marking blocks.

- 10 -

Fig. 27 shows an excerpt of label artwork, including different zones with machine encoding at different strengths.

Fig. 28A shows exemplary 3x3 marking blocks in which no darkened cell is edge-adjoining with another darkened cell.

5 Fig. 28B is like Fig. 28A, but for exemplary 4x4 marking blocks.

Figs. 29A and 29B show different conjunctions of two 3x3 marking blocks.

Fig. 30 illustrates how machine encoding markings can be a function of a linear gradient.

10 Fig. 31 shows an excerpt of label artwork, with machine encoding varying in strength in accordance with a gradient function.

Fig. 32A shows an element of a sync signal block in the spatial domain.

Fig. 32B shows a higher resolution counterpart to the sync element of Fig. 32A.

Fig. 33 details a ranking of the cells in the sync element of Fig. 32B.

15 Figs. 34A, 34B, 34C and 34D show, respectively sync element blocks in which the lowest-valued one, two, three and four cells in Fig. 32B are darkened.

Fig. 35 shows how the block of Fig. 34D can be adjusted to avoid edge-adjoining dark cells.

Fig. 36 helps explain another method for adjusting the signal element block of Fig. 34D to avoid edge-adjoining dark cells.

20 Fig. 37 shows the block of Fig. 34D after adjustment by a process involving Fig. 36.

Fig. 38 shows two adjoining sync signal element blocks.

Fig. 39 details a ranking of cells in the right-most of the sync elements of Fig. 38.

25 Fig. 40 shows how signal element blocks that – individually – lack edge-adjoining dark cells, may present edge-adjoining dark cells when juxtaposed with each other.

Fig. 41 shows the signal element blocks of Fig. 40 after adjustment to avoid edge-adjoining dark cells.

- 11 -

Fig. 42 helps explain another method for adjusting the paired element blocks of Fig. 40 to avoid edge-adjoining dark cells.

Fig. 43 shows the paired signal element blocks of Fig. 40 after adjustment by a process involving Fig. 42 to avoid edge-adjoining dark cells.

5 Fig. 44 illustrates an electronic device in which encoding and decoding may be implemented.

Detailed Description

Signal Encoder and Decoder

Fig. 1 is a block diagram of a signal encoder for encoding a sparse signal. Fig. 2
10 is a block diagram of a compatible signal decoder for extracting a payload from a sparse signal encoded on an object or within an image displayed on a video display.

Encoding and decoding is typically applied digitally, yet the signal is expected to survive digital to analog transformation and analog to digital transformation. For example, the encoder generates an image including the sparse signal that is converted to a
15 rendered form, such as a printed image, displayed image or video. We use the term “printing” to encompass a wide variety of marking technologies, including engraving, etching, stamping, etc. as there are a variety of ways to impart the image carrying the sparse signal to an object. Prior to decoding, a receiving device captures an image or stream of images of the object through its image sensor such as a camera (e.g., CMOS or
20 CCD), and converts it to an electronic signal, which is digitized and processed by signal decoding modules.

Inputs to the signal encoder include a host signal 150 and auxiliary data 152. The objectives of the encoder include encoding a robust signal with desired capacity per unit of host signal, while maintaining perceptual quality within a perceptual quality constraint.
25 In some cases, there may be very little variability or presence of a host signal, in which case, there is little host interference, on the one hand, yet little host content in which to mask the presence of the data channel visually. Some examples include a region of a

package design that is devoid of much image variability (e.g., a single, uniform color), the surface of a part, a label or receipt, or video display without natural imagery (e.g., just simple graphics, uniform or solid tones and text).

The auxiliary data 152 includes the variable data information (e.g., payload) to be

5 conveyed in the data channel, possibly along with other protocol data used to facilitate the communication.

The protocol defines the manner in which the signal is structured and encoded for robustness, perceptual quality or data capacity. For any given application, there may be a single protocol, or more than one protocol. Examples of multiple protocols include cases

10 where there are different versions of the channel, different channel types (e.g., several sparse signal layers within a host). An example is a package design or document, in which rich imagery are encoded with dense watermark signal protocols, and blank or uniform or solid tone areas are encoded with tints or sparse signal protocols. Different protocol versions may employ different robustness encoding techniques or different data

15 capacity. Protocol selector module 154 determines the protocol to be used by the encoder for generating a data signal. It may be programmed to employ a particular protocol depending on the input variables, such as user control, application specific parameters, or derivation based on analysis of the host signal.

Perceptual analyzer module 156 analyzes the input host signal to determine

20 parameters for controlling signal generation and embedding, as appropriate. It is not necessary in certain applications, while in others it may be used to select a protocol and/or modify signal generation and embedding operations. For example, when encoding in host color images that will be printed or displayed, the perceptual analyzer 156 may be used to ascertain color content and masking capability of the host image.

25 The sparse mark may be included in one of the layers or channels of the image file, e.g., corresponding to:

- a color channel of the image, e.g., Red Green Blue (RGB);
- components of a color model (Lab, HSV, HSL, etc.);

- 13 -

- inks of the printer (Cyan, Magenta, Yellow, or Black (CMYK)), a spot color layer (e.g., corresponding to a Pantone color), which are specified to be used to print the image;
- a coating (varnish, UV layer, lacquer);
- other material layer (metallic substance, e.g., metallic ink or stamped foil where the sparse signal is formed by stamping holes in the foil or removing foil to leave sparse dots of foil); etc.

The above are typically specified in a design file, and are manipulated by our

encoder. For example, our encoder is implemented as software modules of a plug-in to Adobe Photoshop image processing software. Design files in this software are specified in terms of image layers or image channels. The encoder may modify existing layers, channels or insert new ones. A plug-in can be utilized with other image processing software, e.g., Adobe Illustrator.

The perceptual analysis performed in the encoder depends on a variety of factors, including color or colors of the sparse signal, resolution of the sparse signal, dot structure and screen angle used to print image layer(s) with sparse signal, content within the layer of the sparse signal, content within layers under and over the sparse signal, etc. The perceptual analysis may lead to the selection of a color or combination of colors in which to encode the sparse signal that minimizes visual differences due to inserting the sparse signal in an ink layer or layers within the image. This selection may vary per embedding location of each sparse signal element. Likewise, the amount of signal at each location may also vary to control visual quality. The encoder can, depending on the associated print technology in which it is employed, vary sparse signal by controlling parameters such as:

- dot shape,
- signal amplitude at a dot,

- ink quantity at a dot (e.g., dilute the ink concentration to reduce percentage of ink),
- structure and arrangement of dot cluster or “bump” shape at a location of a sparse signal element or region of elements. An arrangement of ink applied to an x-by-y two dimensional array of neighboring locations can be used to form a “bump” of varying shape or signal amplitude, as explained further below.

5 The ability to control printed dot size and shape is a particularly challenging issue and varies with print technology. Dot size can vary due to an effect referred to as dot gain. The ability of a printer to reliably reproduce dots below a particular size is also a
10 constraint.

The sparse signal may also be adapted according to a blend model which indicates the effects of blending the ink of the sparse signal layer with other layers and the substrate.

15 In some cases, a designer may specify that the sparse signal be inserted into a particular layer. In other cases, the encoder may select the layer or layers in which it is encoded to achieve desired robustness and visibility (visual quality of the image in which it is inserted).

20 The output of this analysis, along with the rendering method (display or printing device) and rendered output form (e.g., ink and substrate) may be used to specify encoding channels (e.g., one or more color channels), perceptual models, and signal protocols to be used with those channels. Please see, e.g., our work on visibility and color models used in perceptual analysis in our US Application Nos. 14/616,686, 14/588,636 and 13/975,919, Patent Application Publication 20100150434, and US Patent 7,352,878.

25 The signal generator module 158 operates on the auxiliary data and generates a data signal according to the protocol. It may also employ information derived from the host signal, such as that provided by perceptual analyzer module 156, to generate the signal. For example, the selection of data code signal and pattern, the modulation

- 15 -

function, and the amount of signal to apply at a given embedding location may be adapted depending on the perceptual analysis, and in particular on the perceptual model and perceptual mask that it generates.

Embedder module 160 takes the data signal and modulates it onto a channel by

- 5 combining it with the host signal. The operation of combining may be an entirely digital signal processing operation, such as where the data signal modulates the host signal digitally, may be a mixed digital and analog process or may be purely an analog process (e.g., where rendered output images are combined). As noted, a sparse signal may occupy a separate layer or channel of the design file. This layer or channel may get
- 10 combined into an image in the Raster Image Processor (RIP) prior to printing or may be combined as the layer is printed under or over other image layers on a substrate.

There are a variety of different functions for combining the data and host in digital operations. One approach is to adjust the host signal value as a function of the corresponding data signal value at an embedding location, which is controlled according

- 15 to the perceptual model and a robustness model for that embedding location. The adjustment may alter the host channel by adding a scaled data signal or multiplying a host value by a scale factor dictated by the data signal value corresponding to the embedding location, with weights or thresholds set on the amount of the adjustment according to perceptual model, robustness model, available dynamic range, and available adjustments
- 20 to elemental ink structures (e.g., controlling halftone dot structures generated by the RIP). The adjustment may also be altering by setting or quantizing the value of a pixel to particular sparse signal element value.

As detailed further below, the signal generator produces a data signal with data elements that are mapped to embedding locations in the data channel. These data elements are modulated onto the channel at the embedding locations.

The operation of combining a sparse signal with other imagery may include one or more iterations of adjustments to optimize the modulated host for perceptual quality or robustness constraints. One approach, for example, is to modulate the host so that it

satisfies a perceptual quality metric as determined by perceptual model (e.g., visibility model) for embedding locations across the signal. Another approach is to modulate the host so that it satisfies a robustness metric across the signal. Yet another is to modulate the host according to both the robustness metric and perceptual quality metric derived for 5 each embedding location. Below, we highlight a few examples.

For color images, the perceptual analyzer generates a perceptual model that evaluates visibility of an adjustment to the host by the embedder and sets levels of controls to govern the adjustment (e.g., levels of adjustment per color direction, and per masking region). This may include evaluating the visibility of adjustments of the color at 10 an embedding location (e.g., units of noticeable perceptual difference in color direction in terms of CIE Lab values), Contrast Sensitivity Function (CSF), spatial masking model (e.g., using techniques described by Watson in US Published Patent Application No. US 2006-0165311 A1), etc. One way to approach the constraints per embedding location is to combine the data with the host at embedding locations and then analyze the difference 15 between the encoded host with the original. The rendering process may be modeled digitally to produce a modeled version of the sparse signal as it will appear when rendered. The perceptual model then specifies whether an adjustment is noticeable based on the difference between a visibility threshold function computed for an embedding location and the change due to embedding at that location. The embedder then can 20 change or limit the amount of adjustment per embedding location to satisfy the visibility threshold function. Of course, there are various ways to compute adjustments that satisfy a visibility threshold, with different sequences of operations. See, e.g., our US Applications 14/616,686, 14/588,636 and 13/975,919, Patent Application Publication 20100150434, and US Patent 7,352,878.

25 The embedder also computes a robustness model in some embodiments. The computing a robustness model may include computing a detection metric for an embedding location or region of locations. The approach is to model how well the decoder will be able to recover the data signal at the location or region. This may include

applying one or more decode operations and measurements of the decoded signal to determine how strong or reliable the extracted signal. Reliability and strength may be measured by comparing the extracted signal with the known data signal. Below, we detail several decode operations that are candidates for detection metrics within the 5 embedder. One example is an extraction filter which exploits a differential relationship between a sparse dot and neighboring content to recover the data signal in the presence of noise and host signal interference. At this stage of encoding, the host interference is derivable by applying an extraction filter to the modulated host. The extraction filter models data signal extraction from the modulated host and assesses whether a detection 10 metric is sufficient for reliable decoding. If not, the sparse signal may be re-inserted with different embedding parameters so that the detection metric is satisfied for each region within the host image where the sparse signal is applied.

Detection metrics may be evaluated such as by measuring signal strength as a measure of correlation between the modulated host and variable or fixed data components 15 in regions of the host, or measuring strength as a measure of correlation between output of an extraction filter and variable or fixed data components. Depending on the strength measure at a location or region, the embedder changes the amount and location of host signal alteration to improve the correlation measure. These changes may be particularly tailored so as to establish sufficient detection metrics for both the payload and 20 synchronization components of the sparse signal within a particular region of the host image.

The robustness model may also model distortion expected to be incurred by the modulated host, apply the distortion to the modulated host, and repeat the above process of measuring visibility and detection metrics and adjusting the amount of alterations so 25 that the data signal will withstand the distortion. See, e.g., 14/616,686, 14/588,636 and 13/975,919 for image related processing.

This modulated host is then output as an output signal 162, with an embedded data channel. The operation of combining also may occur in the analog realm where the

data signal is transformed to a rendered form, such as a layer of ink, including an overprint or under print, or a stamped, etched or engraved surface marking. In the case of video display, one example is a data signal that is combined as a graphic overlay to other video content on a video display by a display driver. Another example is a data signal 5 that is overprinted as a layer of material, engraved in, or etched onto a substrate, where it may be mixed with other signals applied to the substrate by similar or other marking methods. In these cases, the embedder employs a predictive model of distortion and host signal interference, and adjusts the data signal strength so that it will be recovered more reliably. The predictive modeling can be executed by a classifier that classifies types of 10 noise sources or classes of host signals and adapts signal strength and configuration of the data pattern to be more reliable to the classes of noise sources and host signals.

The output 162 from the embedder signal typically incurs various forms of distortion through its distribution or use. This distortion is what necessitates robust encoding and complementary decoding operations to recover the data reliably.

15 Turning to Fig. 2, a signal decoder receives a suspect host signal 200 and operates on it with one or more processing stages to detect a data signal, synchronize it, and extract data. The detector is paired with input device in which a sensor or other form of signal receiver captures an analog form of the signal and an analog to digital converter converts it to a digital form for digital signal processing. Though aspects of the detector 20 20 may be implemented as analog components, e.g., such as preprocessing filters that seek to isolate or amplify the data channel relative to noise, much of the signal decoder is implemented as digital signal processing modules.

The detector 202 is a module that detects presence of the sparse signal and other signaling layers. The incoming image is referred to as a suspect host because it may not 25 have a data channel or may be so distorted as to render the data channel undetectable. The detector is in communication with a protocol selector 204 to get the protocols it uses to detect the data channel. It may be configured to detect multiple protocols, either by detecting a protocol in the suspect signal and/or inferring the protocol based on attributes

of the host signal or other sensed context information. A portion of the data signal may have the purpose of indicating the protocol of another portion of the data signal. As such, the detector is shown as providing a protocol indicator signal back to the protocol selector 204.

5 The synchronizer module 206 synchronizes the incoming signal to enable data extraction. Synchronizing includes, for example, determining the distortion to the host signal and compensating for it. This process provides the location and arrangement of encoded data elements of a sparse signal within an image.

10 The data extractor module 208 gets this location and arrangement and the corresponding protocol and demodulates a data signal from the host. The location and arrangement provide the locations of encoded data elements. The extractor obtains estimates of the encoded data elements and performs a series of signal decoding operations.

15 As detailed in examples below, the detector, synchronizer and data extractor may share common operations, and in some cases may be combined. For example, the detector and synchronizer may be combined, as initial detection of a portion of the data signal used for synchronization indicates presence of a candidate data signal, and determination of the synchronization of that candidate data signal provides synchronization parameters that enable the data extractor to apply extraction filters at the 20 correct orientation, scale and start location. Similarly, data extraction filters used within data extractor may also be used to detect portions of the data signal within the detector or synchronizer modules. The decoder architecture may be designed with a data flow in which common operations are re-used iteratively, or may be organized in separate stages in pipelined digital logic circuits so that the host data flows efficiently through the 25 pipeline of digital signal operations with minimal need to move partially processed versions of the host data to and from a shared memory, such as a RAM memory.

Signal Generator

Fig. 3 is a flow diagram illustrating operations of a signal generator. Each of the blocks in the diagram depict processing modules that transform the input auxiliary data (e.g., the payload) into a data signal structure. For a given protocol, each block provides one or more processing stage options selected according to the protocol. In processing module 300, the auxiliary data is processed to compute error detection bits, e.g., such as a Cyclic Redundancy Check, Parity, or like error detection message symbols. Additional fixed and variable messages used in identifying the protocol and facilitating detection, such as synchronization signals may be added at this stage or subsequent stages.

5 Error correction encoding module 302 transforms the message symbols into an array of encoded message elements (e.g., binary or M-ary elements) using an error correction method. Examples include block codes, convolutional codes, etc.

10 Repetition encoding module 304 repeats the string of symbols from the prior stage to improve robustness. For example, certain message symbols may be repeated at the same or different rates by mapping them to multiple locations within a unit area of the data channel (e.g., one unit area being a tile of bit cells, bumps or “wixels,” as described further below).

15 Next, carrier modulation module 306 takes message elements of the previous stage and modulates them onto corresponding carrier signals. For example, a carrier might be an array of pseudorandom signal elements. For a sparse signal, this may include equal number of binary one and binary zero elements. These may correspond to “ink” and “no ink” elements of the sparse signal. The data elements of a sparse signal may also be multi-valued. In this case, M-ary or multi-valued encoding is possible at each sparse signal element, through use of different colors, ink quantity, dot patterns or shapes. Sparse signal application is not confined to lightening or darkening an object at a sparse element location (e.g., luminance or brightness change). Various adjustments may be made to effect a change in an optical property, like luminance. These include modulating thickness of a layer, surface shape (surface depression or peak), translucency

of a layer, etc. Other optical properties may be modified to represent the sparse element, such as chromaticity shift, change in reflectance angle, polarization angle, or other forms of optical variation. As noted, limiting factors include both the limits of the marking or rendering technology and ability of a capture device to detect changes in optical

5 properties encoded in the sparse signal. We elaborate further on signal configurations below.

Mapping module 308 maps signal elements of each modulated carrier signal to locations within the channel. In the case where a digital host signal is provided, the locations correspond to embedding locations within the host signal. The embedding 10 locations may be in one or more coordinate system domains in which the host signal is represented within a memory of the signal encoder. The locations may correspond to regions in a spatial domain, temporal domain, frequency domain, or some other transform domain. Stated another way, the locations may correspond to a vector of host signal features at which the sparse signal element is inserted.

15 Various detailed examples of protocols and processing stages of these protocols are provided in our prior work, such as our US Patents 6,614,914, 5,862,260, 6,345,104, 6,993,152 and 7,340,076, and US Patent Publication 20100150434. More background on signaling protocols, and schemes for managing compatibility among protocols, is provided in US Patent 7,412,072.

20 The above description of signal generator module options demonstrates that the form of the sparse signal used to convey the auxiliary data varies with the needs of the application. As introduced at the beginning of this document, signal design involves a balancing of required robustness, data capacity, and perceptual quality. It also involves addressing many other design considerations, including compatibility, print constraints, 25 scanner constraints, etc. We now turn to examine signal generation schemes, and in particular, schemes that employ sparse signaling, and schemes for facilitating detection, synchronization and data extraction of a data signal in a host channel.

One signaling approach, which is detailed in US Patents 6,614,914, and 5,862,260, is to map signal elements to pseudo-random locations within a channel defined by a domain of a host signal. See, e.g., Fig. 9 of 6,614,914. In particular, elements of a watermark signal are assigned to pseudo-random embedding locations 5 within an arrangement of sub-blocks within a block (referred to as a “tile”). The elements of this watermark signal correspond to error correction coded bits output from an implementation of stage 304 of Fig. 3. These bits are modulated onto a pseudo-random carrier to produce watermark signal elements (block 306 of Fig. 3), which in turn, are assigned to the pseudorandom embedding locations within the sub-blocks (block 10 308 of Fig. 3). An embedder module modulates this signal onto a host signal by adjusting host signal values at these locations for each error correction coded bit according to the values of the corresponding elements of the modulated carrier signal for that bit.

The signal decoder estimates each coded bit by accumulating evidence across the 15 pseudo-random locations obtained after non-linear filtering a suspect host image. Estimates of coded bits at the sparse signal element level are obtained by applying an extraction filter that estimates the sparse signal element at particular embedding location or region. The estimates are aggregated through de-modulating the carrier signal, performing error correction decoding, and then reconstructing the payload, which is 20 validated with error detection.

This pseudo-random arrangement spreads the data signal such that it has a uniform spectrum across the tile. However, this uniform spectrum may not be the best choice from a signal communication perspective since energy of a host image may concentrated around DC. Similarly, an auxiliary data channel in high frequency 25 components tends to be more disturbed by blur or other low pass filtering type distortion than other frequency components. We detail a variety of signal arrangements in our co-pending US Patent application no. 14/724,729, filed May 28, 2015, entitled DIFFERENTIAL MODULATION FOR ROBUST SIGNALING AND

- 23 -

SYNCHRONIZATION. This application details several signaling strategies that may be leveraged in the design of sparse signals, in conjunction with the techniques in this document. Differential encoding applies to sparse elements by encoding in the differential relationship between a sparse element and other signal, such as a background, host image, or other signal components (e.g., a sync component).

Our US Patent No. 6,345,104, building on the disclosure of US Patent No. 5,862,260, describes that an embedding location may be modulated by inserting ink droplets at the location to decrease luminance at the region, or modulating thickness or presence of line art. Additionally, increases in luminance may be made by removing ink or applying a lighter ink relative to neighboring ink. It also teaches that a synchronization pattern may act as a carrier pattern for variable data elements of a message payload. The synchronization component may be a visible design, within which a sparse or dense data signal is merged. Also, the synchronization component may be designed to be imperceptible, using the methodology disclosed in US Patent No. 5,862,260.

In this document, we further revisit the design, encoding and decoding of sparse signals in more detail. As introduced above, one consideration in the design of a sparse signal is the allocation of signal for data carrying and for synchronization. Another consideration is compatibility with other signaling schemes in terms of both encoder and decoder processing flow. With respect to the encoder, the sparse encoder should be compatible with various signaling schemes, including dense signaling, so that it each signaling scheme may be adaptively applied to different regions of an image design, as represented in an image design file, according to the characteristics of those regions. This adaptive approach enables the user of the encoder tool to select different methods for different regions and/or the encoder tool to be programmed to select automatically a signaling strategy that will provide the most robust signal, yet maintain the highest quality image, for the different regions.

One example of the advantage of this adaptive approach is in product packaging where a package design has different regions requiring different encoding strategies. One region may be blank, another blank with text, another with a graphic in solid tones, another with a particular spot color, and another with variable image content.

5 With respect to the decoder, this approach simplifies decoder deployment, as a common decoder can be deployed that decodes various types of data signals, including both dense and sparse signals.

One approach to sparse signal design is to construct the signal to have optimal allocation of payload and synchronization components, without regard to compatibility 10 with legacy dense signaling protocols. In such an approach, the signaling techniques for data and synchronization are developed to minimize interference between the variable data carrying and synchronization functions of the sparse signal. For example, if the sparse signal is being designed without needing to be compatible with a dense signaling strategy, it can be designed from the start to be comprised as an array of sparse elements, 15 with variable data and sync functions. One advantage is that there is no need to apply a threshold or quantizer to remove aspects of a signal to convert it into a sparse format.

Another approach is to design a sparse signal to be compatible with a legacy 20 signaling scheme. Within this type of an approach, one can employ techniques to convert a legacy signaling scheme into a sparse signal. In particular, in one such approach, the process of generating a sparse signal begins with a dense watermark signal, and selectively removes elements of it to produce a sparse signal, while retaining sufficient amounts of data and synchronization functionality.

As we detail further below, there are several ways to convert dense signals to 25 sparse signals. Before exploring these methods, we start by further considering properties of dense signals relative to sparse signal. In some cases, the dense signal is comprised of a multi-valued watermark tile (e.g., eight bit per pixel image approximating a continuous signal), which is a block of m by n embedding locations, where m and n are the integer coordinates of embedding locations in a tile (e.g., m = n = 128, 256, 512, etc.).

The value at each tile corresponds to an adjustment to be made to a corresponding location in a host image to encode the watermark. The tile is repeated contiguously in horizontal and vertical directions over a region of the host image, possibly the entire image. The signal is considered “dense” relative to a sparse signal, when the adjustments are densely spaced, in contrast to a sparse signal, where its signal elements are spread apart in the tile. Dense signals are preferred for host signals that are similarly dense, varying, and multi-valued, enabling embedding by adjusting the values of the host signal at the embedding locations. A dense embedding enables higher capacity embedding for both data and sync functions within a tile.

10 Converting a dense signal to a sparse signal still achieves the objective of reliable signaling due to a couple of characteristics of the signal and host. First, the signal is redundant in the tile and across repeated tiles, so removing a portion of it from each tile leaves sufficient signal for reliable and complete recovery of the payload. Signal detection is aggregated across tiles to further assist in reliable recovery, as detailed, for 15 example in US Patent No. 6,614,914. Second, sparse signaling is adaptively applied where there is less likely to be interference with host signal content, and as such, its sparse property is relatively less impacted by interference.

Some approaches to converting dense to sparse signals include, but are not limited to:

20

- Quantizing the array of multi-valued signal to produce a sparse array of elements by quantizing some sub-set of the values to zero;
- Selecting a sub-set of a dense signal, with selection being adapted to retain data signal and sync function within a tile (keeping in mind that such selection may be implemented across tile boundaries in a manner that reliable detection can be made with the aid of extraction from an area larger than that of a single tile);
- Selecting locations to retain based on a particular signal pattern, which may be variable or fixed per tile;

25

- 26 -

- Selection or locations based on a pattern of the data signal or a synchronization signal; and
- Combinations of the above, where, for example, quantizing inherently acts to select values to retain and sets the value of the sparse element.

5 These methods are not mutually exclusive and may be combined in various ways. The case of using quantization may also include applying a fixed or adaptive threshold operation to convert a multi-valued dense signal to a sparse signal. Use of a threshold operation to generate a sparse signal is described, for example, in US Patent No. 6,993,152. Below, we describe further details through examples illustrating various
10 methods.

Whether one starts with a sparse signal or generates one by converting a dense signal, it should be noted that techniques for modulating variable data into the sparse signal can vary quite a bit. Our U.S. Patent Nos. 5,862,260, 6,614,914, and 6,345,104 describe several examples of modulation for carrying variable data in image content, and
15 US Patent application no. 14/724,729, describes yet additional examples, including differential modulation methods. These documents also describe explicit and implicit synchronization signals.

As introduced above with reference to Fig. 3, there are stages of modulation/de-modulation in the encoder, so it is instructive to clarify different types of modulation.
20 One stage is where a data symbol is modulated onto an intermediate carrier signal. Another stage is where that modulated carrier is inserted into the host by modulating elements of the host. In the first case, the carrier might be pattern, e.g., a pattern in a spatial domain or a transform domain (e.g., frequency domain). The carrier may be modulated in amplitude, phase, frequency, etc. The carrier may be, as noted, a
25 pseudorandom string of 1's and 0's or multi-valued elements that is inverted or not (e.g., XOR, or flipped in sign) to carry a payload or sync symbol.

As noted in our application no. 14/724,729, carrier signals may have structures that facilitate both synchronization and variable data carrying capacity. Both functions

may be encoded by arranging signal elements in a host channel so that the data is encoded in the relationship among signal elements in the host. Application no. 14/724,729 specifically elaborates on a technique for modulating, called differential modulation. In differential modulation, data is modulated into the differential relationship among elements of the signal. In some watermarking implementations, this differential relationship is particularly advantageous because the differential relationship enables the decoder to minimize interference of the host signal by computing differences among differentially encoded elements. In sparse signaling, there may be little host interference to begin with, as the host signal may lack information at the embedding 5 location.

10

Nevertheless, differential modulation may be exploited or the scheme may be adapted to allow it to be exploited for sparse signaling. For example, sparse elements may be designed such that they have a differential relationship to other elements, either within the sparse signal (e.g. the sync component), or within the host signal (e.g., 15 neighboring background of each sparse element). A sparse element where a dot of ink is applied, for example, has a differential relationship with neighbors, where no ink is applied. Data and sync signals may be interleaved so that they have such differential relationships. A sparse signal may be encoded differentially relative to a uniform or solid tone, where some sparse elements darken the tone (e.g., darker dots), and others lighten it 20 (e.g., lighter holes).

Differential schemes may further be employed as a preliminary stage to generate a dense multi-valued signal, which in turn is converted to a sparse signal using the above described schemes for conversion. The encoder then converts this dense signal to a sparse signal, maintaining where possible, differential relationships.

25 Another form of modulating data is through selection of different carrier signals to carry distinct data symbols. One such example is a set of frequency domain peaks (e.g., impulses in the Fourier magnitude domain of the signal) or sine waves. In such an arrangement, each set carries a message symbol. Variable data is encoded by inserting

several sets of signal components corresponding to the data symbols to be encoded. The decoder extracts the message by correlating with different carrier signals or filtering the received signal with filter banks corresponding to each message carrier to ascertain which sets of message symbols are encoded at embedding locations.

5 Having now illustrated methods to modulate data into the watermark (either dense or sparse), we now turn to the issue of designing for synchronization. For the sake of explanation, we categorize synchronization as explicit or implicit. An explicit synchronization signal is one where the signal is distinct from a data signal and designed to facilitate synchronization. Signals formed from a pattern of impulse functions, 10 frequency domain peaks or sine waves is one such example. An implicit synchronization signal is one that is inherent in the structure of the data signal.

An implicit synchronization signal may be formed by arrangement of a data signal. For example, in one encoding protocol, the signal generator repeats the pattern of bit cells representing a data element. We sometimes refer to repetition of a bit cell 15 pattern as “tiling” as it connotes a contiguous repetition of elemental blocks adjacent to each other along at least one dimension in a coordinate system of an embedding domain. The repetition of a pattern of data tiles or patterns of data across tiles (e.g., the patterning of bit cells in our US Patent 5,862,260) create structure in a transform domain that forms a synchronization template. For example, redundant patterns can create peaks in a 20 frequency domain or autocorrelation domain, or some other transform domain, and those peaks constitute a template for registration. See, for example, our US Patent No. 7,152,021.

The concepts of explicit and implicit signaling readily merge as both techniques may be included in a design, and ultimately, both provide an expected signal structure 25 that the signal decoder detects to determine geometric distortion.

In one arrangement for synchronization, the synchronization signal forms a carrier for variable data. In such arrangement, the synchronization signal is modulated with variable data. Examples include sync patterns modulated with data.

Conversely, in another arrangement, that modulated data signal is arranged to form a synchronization signal. Examples include repetition of bit cell patterns or tiles.

These techniques may be further exploited in sparse signal design because the common structure for carrying a variable payload and synchronizing in the decoder is retained in the sparse design, while minimizing interference between the signal components that provide these functions. We have developed techniques in which one signal component is a carrier of the other component, and in these techniques, the process of generating a sparse signal produce a signal that performs both functions.

The variable data and sync components of the sparse signal may be chosen so as to be conveyed through orthogonal vectors. This approach limits interference between data carrying elements and sync components. In such an arrangement, the decoder correlates the received signal with the orthogonal sync component to detect the signal and determine the geometric distortion. The sync component is then filtered out. Next, the data carrying elements are sampled, e.g., by correlating with the orthogonal data carrier or filtering with a filter adapted to extract data elements from the orthogonal data carrier. Signal encoding and decoding, including decoder strategies employing correlation and filtering are described in our co-pending application 14/724,729, and these strategies may be employed to implement this approach for sparse signaling.

Additional examples of explicit and implicit synchronization signals are provided in our previously cited patents 6,614,914, and 5,862,260. In particular, one example of an explicit synchronization signal is a signal comprised of a set of sine waves, with pseudo-random phase, which appear as peaks in the Fourier domain of the suspect signal. See, e.g., 6,614,914, and 5,862,260, describing use of a synchronization signal in conjunction with a robust data signal. Also see US Patent No. 7,986,807.

Our US Publication 20120078989, provides additional methods for detecting an embedded signal with this type of structure and recovering rotation, scale and translation from these methods.

Additional examples of implicit synchronization signals, and their use, are provided in 6,614,914, 5,862,260, and Application No. 14/724,729 as well as 6,625,297 and 7,072,490.

Returning now to sparse signal design, we now provide detailed examples of sparse signaling techniques. Fig. 4 is a diagram illustrating an embodiment of a sparse signal generator. The signal generator starts with tiles of two signal components, one carrying variable data 400, and one providing a synchronization function 402. The synchronization signal is multi-valued per pixel (e.g., 0-255), and it is passed through a quantizer 404 to convert it to a signal with fewer levels per pixel. In its simplest form, the quantizer converts the multi-valued signal into a binary signal, represented as black and white pixels, by a threshold operation. The threshold operation for each pixel within a tile compares each value with a threshold. For binary signals, elements below the threshold are shown as black here, while elements above the threshold are white. As noted, this is simply representative of a modulation state of an optical property at a sparse element, such as darker or lighter relative to background, and is not particularly limited to rendering black and white pixels.

The variable data signal 400 is comprised of elements having one of two values (e.g., 1 or 0, A, -A). As explained previously, a payload signal may be transformed into a robust data signal through one or more modulation stages, e.g., error correction and modulating the error correction coded signal onto a binary carrier signal, which is the approach used in this embodiment. This modulated carrier is mapped to pixel locations within the tile to form data tile 400.

The signal generator of Fig. 4 produces a sparse signal by selectively combining elements of data tile 400 with the quantized synchronization signal 406. In the embodiment illustrated here, the signal generator performs a matrix operation 408 that selectively retains components of the data and synchronization tiles, while producing a sparse signal output 410. One particular matrix operation to generate dark sparse elements on a lighter background, as shown here, is to compute a logical AND operation

between corresponding pixel locations within the data and synchronization tiles, such that pixels that are both black at the same coordinates in each tile remain black in the output. For other inputs (white AND white, black AND white, or white AND black), the output pixel is white at that coordinate.

5 In this approach, the black pixels of the message signal are retained at all coordinates in the tile where the synchronization signal also has a black pixel. This technique distributes sparse message elements within a tile according the spatial distribution of the synchronization signal. It ensures that there sufficient signal energy to carry the payload robustly, while preserving sufficient signal energy for synchronization.

10 10 It also ensures that the sync signal does not interfere with the sparse message elements. This approach may be reversed in the case where the objective is to generate a sparse signal with light holes against a darker background, with quantization level set appropriately (see later illustrations of setting thresholds for holes in dark background).

This approach also demonstrates a signal generation method in which a multi-valued component is effectively merged with a binary component. The multi-valued synchronization tile is a spatial domain representation of synchronization template formed by peaks in the frequency domain. The binary valued payload carrying component is redundantly encoded and distributed over the tile. In particular, modulated carrier elements, with an equal number of binary 0 and 1 values are spread evenly over

20 20 the spatial locations within a tile.

The principles of the method may be applied to alternative signal component inputs. The sync and data components may both be multi-valued and selectively quantized to a binary or M-ary form prior to merging with a selective combination of the components per tile location. Alternatively, both the sync and data components may be binary valued and merged with a logic operation. Finally, the data component may be multi-valued and the sync component binary valued, with the data component being quantized prior to merging with the sync component. The matrix operation to combine elements at tile coordinates may be adapted to retain sync and data components that are

compatible (e.g., consistently valued or falling within the same quantization bin). This approach allows the generator to form sparse marks with dark elements on lighter background, lighter elements on darker background, or a combination of lighter and darker sparse elements against a mid-level tone background.

5 Quantization level (including threshold) and merging function may be set with adaptive parameters to bias the sparse signal toward data or sync elements.

Fig. 5 is a diagram illustrating a refinement of a sparse signal generator like the one in Fig. 4. In this refinement, the output of the sparse signal generator is further processed to transform the sparse signal elements. The sparse signal tile output from the 10 generator has dimensions of m by n , where m and n are integer coordinates. For the sake of illustration, we use the example of $m=n=128$. In preparation for application to an object, the tile coordinates are mapped to coordinates in a target spatial resolution, which is typically expressed in Dots Per Inch (DPI). In Fig. 5, the mapping of a tile coordinate corresponds to a 4 by 4 block, which means that the effective DPI of the tile is one-fourth 15 the DPI of the target image resolution. For example, the sparse mark tile may be generated to be 75 DPI for insertion into an image at 300 DPI, which translates to each tile coordinate (called a waxel) being a 4 by 4 block (waxel region) of pixels in the image coordinate system at 300 DPI. We refer to the region as the “bump” and ratio of target image resolution to waxel resolution as the bump size.

20 In the refinement of Fig. 5, light and dark waxels (500, 502) of the sparse tile are converted to the higher output resolution. This conversion enables additional flexibility in the shaping and location of each sparse element. Light elements 500 simply convert to 4x4 regions of light elements (504) at the waxel coordinates. In this example of dark sparse elements on light background, the flexibility is in the selection of the location of 25 the dark element. In the technique of Fig. 5 the location of the dark element is pseudo-randomly selected from among 4 locations within the center 2x2 square within the 4x4 pixel region of a waxel. These four alternative locations are depicted in blocks 506, 508, 510 and 512. The resulting converted sparse signal output is shown as output tile 514.

This conversion of the sparse input signal (e.g., at 75 DPI) to sparse output image signal at the target resolution (e.g., 300 DPI) does the following:

- It makes the sparse signal more sparse;
- It varies the location of the sparse element per embedding location so that sparse elements are not consistently falling on horizontal rows and vertical columns of the tile to make the sparse signal less visually perceptible;
- It provides some protection against errors introduced by dot gain of the printing process. Even with errors in dot size and location due to dot gain, the resulting sparse element is still located within the correct tile region.

10 As we explain further below, this sparse output signal may also be converted further in the RIP process and as applied when printed or marked onto an object surface, or rendered for display on a screen or projected image.

15 Figs. 6-8 depict histograms of signal components to help illustrate aspects of sparse signal generation from different types of signals. Fig. 6 is a histogram of a digital watermark signal component, with waxel values that are at one of two different levels (-1, 1). This is an example of a histogram of a binary antipodal watermark tile, generated by modulating symbols onto binary antipodal carriers (e.g., a chipping sequence) to create message chips which are mapped pseudo-randomly into locations across the tile.

20 Fig. 7 is a histogram of another digital watermark signal component with multi-level values. This is an example of a spatial domain conversion of a sync signal tile formed as frequency domain peaks with pseudorandom phase.

25 Fig. 8 is a histogram of a combination of the digital watermark signal components of Figs. 6 and 7, also depicting an example of a threshold operation to generate a binary image comprising black and white pixels from an image comprised of multi-valued pixels. In this example, the binary anti-podal signal elements are multiplied by a scale factor of 10 and then added to the multi-valued signal component with the distribution of Fig. 7. To create a sparse signal of darker dots on a lighter background, a threshold operation is applied, for example at the threshold level of the dashed line. Tile elements

with a value below the threshold are set to dark (“black”) and tile elements with a value above the threshold are set to light (“white”). This diagram provides a graphical depiction of the sparse signal generation process, which retains signal of both data carrying and sync components. The manner in which the payload is modulated onto

5 carriers with half positive and half negative values ensures that the complete signal can be recovered from waxels of negative values or waxels of positive values. Here, for dark on light background, the negatively valued waxels are retained. Additionally, sufficient signal energy of the sync signal is also retained.

Fig. 9 is a diagram illustrating another refinement of the sparse signal generator of
10 Fig. 4. This refinement leverages the same flexibility discussed in connection with Fig. 5 in establishing the sparse dot in a bump region. In this case, the sparse dot is located in the bump region where the sync signal level is at its lowest (for dark on light background sparse marks). A similar approach may be used for sparse holes in a darker background, with the sparse hole located where the synch signal level is highest within the bump
15 region. Because of possible dot gain errors, this approach, like the one in Fig. 5, limits the selection of dot location to the center four pixels of the bump region.

In this variant of the sparse signal generation, the multi-valued sync tile (600) is provided at the resolution of the target image (e.g., 300 DPI in the continuing example, where waxels are at resolution of 75 DPI). The low point within the center 4x4 region of
20 the waxel is at location 602. The signal generator places the sparse dot at this location 602, which is one (606) of the four candidate locations, 604, **606**, 608, 610, selectable by the signal generator. This variant provides more sync signal strength as the sparse signal is generated based on a more detailed analysis of the sync signal level within the waxel.

Fig. 10 is a diagram illustrating application of a threshold to a continuous
25 watermark signal, and the resulting output for three different thresholds. The top three plots 620, 622 and 624, illustrate histograms of a continuous watermark signal (here the sync signal), with three different threshold settings “T,” shown as the dashed lines. Waxels with values below the threshold are set to black (darker pixels), while values

above are set to white (lighter pixels). The selection of thresholds at these three different settings corresponds to the binary image signals 406a, 406b and 406c shown below each histogram. These diagrams illustrate how the threshold T may be adjusted to control the distribution (sparseness) of the quantized continuous signal (which in turn controls the

5 sparseness of the final output signal). The strongest signal output for the quantized continuous signal is where the threshold T is set to the mid-point of the continuous signal.

The combination of the binary data signal and the continuous sync signal using a logical AND operation has the effect of distributing the data signal according to the sync signal.

10 The detailed arrangement is advantageous in several respects. For example, no expression of one of the two signal components (sync and binary data) undermines the other. Wherever a dark pixel is formed, it aids representation of both signal components.

Relatedly, the sync signal is expressed without adding any noise to the binary data signal.

15 Moreover, for any given number of dark pixels, it is not possible to embed the binary data signal any stronger.

Fig. 11 illustrates a portion of a sparse signal in magnified state to show dot structure in more detail and set up our explanation of an additional transformation of the sparse signal. In this particular example, the image resolution is 300 DPI, and the black 20 squares are 2x2 black pixels at the center of the 4x4 waxel region (the “bump” region of a waxel, where waxels are at 75 DPI). In contrast to the examples of Figs. 5 and 9 where a sparse dot is selected from among the 4 pixels of the center 2x2 pixels, here all four of the 2x2 pixels are set to black.

Fig. 12 illustrates the sparse signal of Fig. 11, modified to reduce the signal using 25 a line screen approach. The sparse signal of Fig. 12 is derived from the signal of Fig. 11 by screening back the black dots from 100% to 15% with a 175 line screen. This is just one example of how the sparse signal can be made less perceptible by reducing the sparse elements. In this case, the signal is screened back. Another alternative is to reduce the

sparse elements by diluting the ink used to print it (e.g., diluting the ink to create a 15% ink dot).

While we illustrate several examples with black or dark pixels on a light background, the same approach may be applied in different color inks, including spot colors. Applying the sparse signal with Cyan ink is particularly effective where the signal is captured with a scanner that predominantly captures image signal around a 660 nm wavelength, like most commercial barcode scanners. The sparse elements may be reduced by screening, diluted ink, or other reduction techniques applied in the RIP and/or at the time of applying the sparse element to a substrate.

10 The above examples also show sparse signals are constructed from continuous or multivalued signal components and binary signal components. One component is a variable data carrier while another is a sync signal. The functions of the components may be reversed. Alternatively, both the data and sync components may be continuous signals that are selectively quantized and combined.

15 An alternative sparse signal generation process, for example, is a process that begins with sync and data components that are peaks in the frequency domain. The sync peaks are fixed to form a sync template, whereas the data peaks vary in location in frequency coordinates according to data symbols being encoded. These signal components form a continuous spatial domain signal when the combined peak signals are 20 transformed to the spatial domain. This continuous signal is then converted to a sparse signal with a threshold operation using the above-explained approach to generate sparse image signals with both data and sync components. This approach enables the frequency components for sync and data to be selected so as to minimize interference between the two components.

25 In particular, the frequencies may be chosen to be orthogonal carrier signals, with some for sync, some for data, and some for both sync and data. The carriers may be modulated with variable data, e.g., using frequency shifting, phase shifting, etc.

One benefit of the above techniques is that they are compatible with signal decoders designed for dense watermark signal counterparts to the sparse signal. For details on decoders, including synchronization methods, please see our decoders detailed in US Patents 6,614,914, 5,862,260, and 6,345,104, and synchronization methods in

5 20120078989. Synchronization methods and variable data demodulation operate in a similar fashion as in dense watermark schemes. However, as noted, the extraction filters may be adapted to be optimized for sparse mark extraction.

Binary, multi-valued and continuous watermark signal components may also be generated using various techniques describe in our co-pending application 14/724,729,

10 which describes various watermark signal arrangements, differential modulation strategies, and synchronization approaches. These binary and multi-valued signal components may then be converted to sparse signals using the techniques described in this document. Though the decoding of such sparse signals follows the dense decoding counterparts, we provide an example of the processing flow below.

15 Fig. 13 is a flow diagram illustrating a method of decoding an embedded watermark signal and compatible sparse signals. This method was particularly designed for differentiation modulation methods in application no. 14/724,729 and the following description originates in that document.

In processing module 700, the method starts by approximating initial transform parameters, which in this case, include rotation and scale. This module includes preprocessing operations on the suspect signal to prepare it for detection. These operations include transforming the signal into the domain in which the data signal is encoded and filtering the signal to reduce interference with the host and other noise. For example, if the data channel is encoded in a particular color channel or channels at a particular resolution and frequency range, module 700 transforms the signal into the channel. This may include one or more filtering stages to remove noise and host signal content outside the channel of the sparse signal being detected.

Module 700 utilizes a pattern recognition method to approximate initial rotation and scale parameters of the encoded signal structure. The encoded signal structure has an arrangement that forms a template in the signal spectrum. There are a variety of pattern matching methods that may be employed to approximate the rotation and scale of this 5 template in the suspect signal. Fig. 14 illustrates one class of such methods in which template (labeled “signal”) and the filtered spectrum of the suspect signal (labeled “measured”) are transformed into a log polar (LP) coordinate system and correlated. The maximum correlation peak in the correlation within the LP coordinate system is located. The location of this peak corresponds to the approximate rotation and scale of the 10 template.

In one embodiment for image signaling, module 700 employs the following:

1. Bilateral and Gaussian filters to remove image content while preserving the encoded data signal;
2. Grayscale conversion, mean subtraction, and 2D FFT to estimate spatial 15 frequencies;
3. Magnitude and Log-polar transform to equate 2D shift with rotation and scale; and
4. Clip magnitudes and Gaussian filter to remove processing artifacts and noise.

20

Returning to Fig. 13, signal extraction module 702 extracts an approximation of the auxiliary data signal using the initial rotation and scale estimate to compensate for rotation and scale. Module 702 includes sampling operators (e.g., interpolators) to sample embedding locations within the suspect signal, as corrected by the initial rotation 25 and scale. Module 702 also includes an extraction filter that exploits the relationships used to encode signal elements as described previously to reconstruct an estimate of the data signal.

Module 704 accesses the reconstructed data signal and determines refined rotation and scale parameters that align it with the template. Module 704 computes the spectrum from the reconstructed estimate of the data signal. From this spectrum, the module 702 obtains a more precise estimate of rotation and scale. In particular, the location of the

5 spectral peaks in the reconstructed data signal are used to determine the rotation and scale by determining the geometric transform that aligns them with the template. A variety of pattern matching techniques may be used for this process, including the log polar method above, and/or least squares approach of 20120078989, referenced earlier.

Additional refinement modules may be included to determine an estimate of
10 translation of a tile in a suspect signal, as described in 20120078989 and 6,614,914, prior to extracting data. Translation provides the coordinates of the embedding locations within a tile of the suspect signal (e.g., start of tile and location of bit cells relative to start of tile). Oversampling may also be used to recover translation.

Data extraction module 706 now extracts a data sequence from embedding
15 locations within a tile, which are sampled based on the refined geometric transformation parameters (refined rotation, scale, and translation). The data sequence extraction applies an extraction filter, again exploiting encoding relationships where appropriate, but this time with more precise determination of sparse embedding locations.

For payload extraction, the decoder employs a filter adapted to extract an estimate
20 of a data element from a relationship between a sparse data element and other signal content. The filter increases the signal to noise ratio of the data signal relative to noise by leveraging the differential relationship among the signals encoding each data element. This filter may be employed both in the synchronization process as well as the data extraction process. The shape of the filter corresponds to the area from which it samples
25 signal values and the positional relationship of the embedding locations that it evaluates to leverage relationships.

In some embodiments, the sparse signal decoder applies an extraction filter called, octaxis, to extract estimates of the sparse signal while suppressing interference. For more

on such filters, see our US Patents 7,076,082 and 8,687,839. Oct axis compares a bit cell with eight neighbors to provide a compare value (e.g., +1 for positive difference, -1 or negative difference), and sums the compare values. Different arrangements of neighbors and weights may be applied to shape the filter according to different functions. Another 5 is a cross shaped filter, in which a sample interest is compared with an average of horizontal neighbors and vertical neighbors, as described in US Patent 6,614,914.

The output of the extraction filter provides an estimate for each sparse element. The estimates are aggregated by demodulating the carrier signal. The demodulated payload is input to the error correction decoder process. For convolutional coded signals, 10 this is a Viterbi decoder. The result is the variable data payload, including error check bits, used to validate the variable data field of the payload.

The above description provides a variety of techniques from which many different signaling strategies may be developed. Below, we further describe how to derive sparse signals of various types, building on the above framework.

15 Differential modulation and sparseness

When differential modulation is used in conjunction with a sync signal component, the above approaches used for generating sparse marks from sync and message components also apply.

When differential modulation of the variable data component is used by itself to 20 provide self-sync capabilities, then there is no explicit sync component. All of the pixels carry the message signal. These pixels may be formed so as to have a binary value (-1 or +1), or multiple values (e.g., approximating a continuous signal).

In the case of binary valued pixels, a continuous sync component may be introduced to provide a means to distribute the data values within a tile.

25 In the case of multi valued pixels, a quantization (including threshold operation) may be used to generate a sparse signal from dense differential modulated input signal. Orthogonal differential modulation (see, e.g., co-pending application 14/724,729) provides a way to generate sparseness, since the message signal values can take on many

values (not just -1 or +1). Here, the thresholding approach can be used to generate sparseness.

Sparseness without explicit sync component

In some embodiments, the variable data signal may have no explicit sync 5 component and have binary valued pixels. It may be made sparse by a variety of methods, such as:

- Randomly white out (or alternatively, black out) different parts of the message;
- Use a noise distribution to play a similar role as the sync signal distribution:
 - Additional information could be conveyed through this noise distribution;
 - The noise distribution could be different for different blocks in the image (providing some randomness to the sparse pattern);
 - Which noise distribution a particular block came from can be deciphered by computing the conditional probability after detection;
 - Use knowledge of the protocol (version, error correction code, error detection code, repetition code and spreading or modulating with carrier) to determine where to place the sparse signaling components (i.e., the ink spots on a lighter background) to obtain optimal SNR for a given sparseness;
 - Perturb the message signal values at arbitrary locations and use an objective function (e.g., message correlation) to determine which perturbations to keep and which to discard.

General points about sparse signals

Recapping, we now provide additional observations and design variations. The 25 distribution of the multi-valued signal component in the spatial domain provides a control parameter (e.g., threshold) to adjust sparseness. This signal component plays a dominant

role in determining sparseness, with amount of sparseness controlled by the threshold.

The strength of this signal provides an additional parameter to control sparseness.

Sparse signals can be encoded by using multi-bit values. These could be printed using multiple inks (rather than just ink or no ink in the usual case). This can be achieved

5 using multiple thresholds or quantization levels in the histograms (e.g., histograms of Fig. 10.

For a sparse marks in a tiled configuration, the encoder can also vary the pattern of sparse elements in different tiles by choosing a slightly different threshold per tile (or introducing some randomization into pixel location optimization techniques, e.g., Fig. 5).

10 The sparse mark may be encoded in one or more ink layers. The ink layer may be a spot color already in the design file, or an ink that is added, but selected to best match inks specified in the design. See, e.g., color match optimization in 14/616,686. In other implementations, the sparse mark disclosed in this patent document can be used as the “watermark tile” in Fig. 7 of the 14/616,686 application. The sparse mark may also be

15 formed as a weighted combination of process colors, e.g., CMYK.

Sparse elements may be applied by modulating the optical property of an object at the sparse element locations according to the sparse signal element value. Above, we often noted darker or lighter modulation relative to the background, and there are many ways to make such modulation. Examples include adding or removing ink or coating, or

20 engraving or etching the substrate surface. The shape, thickness or translucency of material at a sparse element location may be modified to apply the sparse element.

Laser marking, including laser engraving, in particular is an effective way to apply a sparse mark to a wide range of object types and materials. Such marking applies to many different industries, including mobile phone parts (e.g., keypad), plastic

25 translucent parts, electronic components, integrated circuits (IC), electrical appliances, communication products, sanitary ware, tools, accessories, knives, eyeglasses and clocks, jewelry, auto parts, luggage buckle, cooking utensils, stainless steel products and other industries. It applies to a variety of substrate types including metals (including rare

metals), engineering plastics, electroplating materials, coating materials, coating materials, plastics, rubber, epoxy resin, ceramic, plastic, ABS, PVC, PES, steel, titanium, copper and other materials.

Laser marking may be applied via handheld devices such as the handheld laser 5 marking machine model BML-FH from Bodor. This is particularly useful in marking various types of objects with identifying information, which can then be read by handheld scanners, e.g., to extract a GTIN in a retail setting.

Sparse marks may be merged with display images via compositing in a display buffer of a display driver. They may be implemented as a graphic overlay and may be 10 combined with other bitmapped images via bit blit (bit-boundary block transfer) operations, which are operations for combining bitmaps using a raster operator.

Sparse marks may be generated, inserted or transformed in a halftone conversion operation. Above, we illustrated an example of applying a line screen to sparse elements. Sparse elements may be generated in the halftone conversion, or may be converted into 15 various dot structure arrangements within the halftone conversion process. Halftone conversion may be used to generate a sparse element as a cluster or pattern of dots. This conversion process may transform a sparse dot into halftone dots in a combination of colors, screen angles and dot patterns. The halftone conversion may also be adapted to insert sparse mark elements in areas of an image that are compatible with such insertion 20 (e.g., uniform or solid tone areas, light backgrounds, dark backgrounds, areas around text fonts, etc.).

Though these operations may reduce the sparse element, as in the example of Figs. 11-12, they are done in a manner in which signal is retained and captured using an image scanner compatible with the waxel resolution. In our examples, the sparse element 25 is applied at a higher resolution of image rendering (e.g., 300 DPI or higher) than the waxel resolution (e.g., 75 DPI), yet the decoder can extract the sparse signal from lower resolution images because the sparse element, though blurred at lower resolution reading,

is still recoverable because the basic encoding relationship of sparse element relative to background is intact.

Sparse marking is compatible with many printing technologies. While not practical to list them all, we list the following: flexography, gravure, offset (including dry offset), digital, ink jet, dye sublimation, thermal (including direct thermal and thermal transfer), laser, 3D printing, Intaglio and relief printing, embossing, photolithographic, lithographic, laser marking, including laser engraving, and laser etching.

Sparse marks are particularly effective for use in connection with label and receipt printers used in retail. These printers typically use thermal printing to print text on white labels or paper stock for receipts. Sparse marks may be integrated with text and printed with thermal printers on this type of print substrate. This allows variable information about fresh foods and deli items, such as the product SKU and weight to be encoded into the sparse mark or linked to an identifier encoded in the sparse mark and then printed with the thermal printer on an adhesive label or receipt for the item. This identifier may be dynamically linked to the variable information captured for the item so that the POS scanner can look up the item identifier and its variable information to assign a price at retail check out.

Mixing of the sparse signal with under and over printed layers is possible, and sparse signal insertion among other colors or inks is controlled by a blend model. Blend models may be used to achieve a desired output color for the sparse element, taking into account other inks in the package design. Please see our co-pending application 14/616,686 for more detail on blend models and use of them for watermark signal encoding. These techniques may be used for achieving desired color matching (e.g., limiting color match error) or color modification to encode sparse signal elements among other layers or channels in a design (e.g., to ensure the modification introduced by the sparse element is visible to a scanner relative to surrounding background near the sparse element).

Our sparse signal encoding may also take advantage of various spectral encoding and reading technologies, such as the ones detailed in our US Application Publication 2015-0071485, INFORMATION CODING AND DECODING IN SPECTRAL

DIFFERENCES,. Sparse signals may be encoded in spectral differences between the

5 material used to print sparse elements or holes relative to the material of the background.

Sparse elements may also be more effectively encoded and decoded when used in conjunction with multi-spectral imagers, such as those described in our PCT application, PCT/US14/66689, published as WO2015077493, entitled SENSOR-SYNCHRONIZED SPECTRALLY-STRUCTURED-LIGHT IMAGING, and coordinated illumination as

10 described in Us Application Publication 2013-0329006, and our application 14/616,686.

The latter documents describe imaging devices that employ pulsed light sources and/or spectral filtering to enable capture of different spectral bands. The sparse mark may be encoded in spectral bands that these devices are well adapted to detect, and further processing may also be used to process images in the different bands to amplify the

15 sparse signal (e.g., amplify the difference between sparse elements and its neighboring background). Sparse marks may also leverage encoding of sparse signals in plural chrominance directions, as detailed in our application publication 2010-0150434.

Sparse marks may also be applied using materials to apply the marks to objects that enhance their detection. Sparse marks may be applied in a coating or ink layer in

20 which additives, such as pigments are dyes are added to enhance the detectability of sparse elements relative to background. Such additives may be inserted in the layer used to apply sparse elements, the background or both. To illustrate, we describe an embodiment optimized for the spectral response of typical barcode scanning equipment, which is designed to detect barcodes at or in a spectral range around a wavelength of

25 660nm. This type of scanner has difficulty detecting signal encoded in colors of low absorption at 660 nm, such as light substrates, as well as objects in white, red or yellow. In addition, it was has difficulty in artwork with no reflectance at 660 nm, such as blues, greens and blacks.

The solution is to find additives that do not add objectionable visual differences, yet either absorb at or around the narrow band of the scanner, or reflect so that the scanner sees light in dark backgrounds (e.g., to mark sparse holes in a dark background). Preferably the additives used for low absorption objects appear clear (e.g., do not dirty 5 the light colors) yet have absorption in the narrow band of the scanner.

For this case, a narrow band absorption dye is added to the marking material which matches the central wavelength and width of the narrow band illumination of a scanner in the visible region. Typically, the narrow band illumination is created by LED 10 illumination (e.g., red illumination) for barcode scanners. Fig. 15 is a diagram illustrating absorption characteristics of an additive (e.g., a dye) around the narrow band of the scanner.

In the other case of artwork with low reflectivity, some spot inks like process blue or saturated colors have low reflectivity at the narrow band of the scanner. In this 15 situation, an additive can be inserted in the sparse signal marking layer or layers to produce more light under the illumination of the scanner light source. In particular, a different dye is added which absorbs at 660 nm, the illumination of the scanner, and then fluoresces at a higher wavelength as shown in Fig. 15.

Regions with dye appear lighter when printed on top of a low reflectivity region. This is well suited for applying sparse holes against a darker background. With imaging 20 barcode devices available today, this approach works by providing an additive that has a fluorescence wavelength < 900 nm.

Inks, coatings and additives with these properties may be obtained from suppliers like Gans Ink and Supply Co.

Further details on the above-described arrangements are provided in co-pending 25 application 62/263,369, filed December 4, 2015.

Further Disclosure

Fig. 16A shows a label as may be adhesively applied to deli food items, such as paper-wrapped packages of cheese or meat, or plastic tubs containing other foodstuffs.

Such labels are typically printed in-store, by a thermal label printer, onto thermally-

5 sensitive label media. An exemplary printer is the Dymo SE450. The SE450 has a horizontal linear array of elements, spaced 203 to the inch, that are selectively heated to discolor corresponding dots on a proximate label medium, as the medium is advanced in a vertical direction. Fig. 16B shows a magnified excerpt of Fig. 16A. Fig. 16C shows a magnified excerpt of Fig. 16B.

10 Artwork printed onto label of Fig. 16A can be modified to include a sparse mark of the sort described above, redundantly encoding a plural-bit message. Such a sparsely-marked label is shown in Fig. 17A. However, as shown in enlarged Figs. 17B and 17C, legibility of the label is impaired by the markings. (Such markings can also interfere with machine-decoding of the barcode shown at the lower left of Fig. 17A.)

15 In accordance with a further aspect of the present technology, a guard band is defined that surrounds text characters (and barcodes) included in the label artwork. In a simple embodiment, the sparse mark is added to the artwork only at regions outside the guard band.

20 In one particular embodiment, a dilation process is applied to a pixel representation of the text (and barcode) artwork, such as using conventional image processing software (e.g., GIMP or Adobe Photoshop). Fig. 18A is illustrative. A region-growing process is applied, starting from each pixel of each text character. This process essentially swells each glyph of the text (and barcode) – extending a guard band (safe area) 181 around the pixels that comprise such elements of the original label file.

25 No data marking is added within this enlarged guard band.

The width of the guard band depends on the application, and the desired aesthetics. The larger the guard band (up to a point), the easier the label text is to read.

In some embodiments, the text can be swollen by just a single pixel in all directions. In other embodiments, the text can be enlarged by 3, 5, or more pixels.

In some implementations, the size of the guard band will be related to the line height (h in Fig. 18A). The guard band may be less than such height (or less than half such height), although larger guard bands are sometimes used.

Regardless of the width of the guard band, any encircled regions within the text character glyphs (e.g., inside encircled parts of the “o” and “a” of Fig. 18A) are desirably included within the guard band.

It will be noted that the boundary of the guard band in Fig. 18A is non-linear; the boundary echoes contours of the letters. While the boundary has a straight portion to the left of the “N,” the boundary is non-linear along most of its extent. (In less-favored embodiments, a rectangular guard band may be used to surround an entire block of characters.)

Fig. 18B shows guard band regions for the full label of Fig. 16A.

Figs. 19A, 19B and 19C correspond to Figs. 17A, 17B and 17C, but with the Fig. 18B guard band regions protected from marking as just-described.

Figs. 20A and 20B present Figs. 17B and 19B side by side, enabling comparison of their respective legibilities.

In other embodiments, the marking is not simply applied outside the boundary, and absent within it. Rather, the marking is modulated in intensity (density). Near the text characters, the marking is more subtle. As the distance from the text characters increases, denser marking is applied.

This is conceptually illustrated in Fig. 21. In a guard band region 211, no marking is applied. In region 212 (which encloses, or surrounds, the guard band region), a subtle form of marking is applied (which may be called Strength1). In region 213, (which encloses region 212) a slightly stronger marking is applied (which may be called Strength2). In region 214 (which encloses region 213), a somewhat stronger marking is applied (which may be called Strength3). Beyond region 214, the strongest marking is

applied (which may be called Strength4). The strength of the marking thus increases along various gradients (shown by the dark arrows in Fig. 21).

Markings of different strengths can be achieved in various ways (some of which were discussed earlier).

5 One way is to vary spatial density of the markings. Fig. 22 shows a dark element 221 that can be included at each location in the label artwork where a sparse mark is to be present. With such an element (which may be a single print dot, or pixel, in the thermal printer example – or a square array of several such dark pixels, e.g., 2x2 or 3x3), markings of different strengths can be achieved by including elements 221 distributed at
10 different spatial densities.

Fig. 23 shows an excerpt of label artwork. At the top is a guard band adjacent some printed text (not shown). In this guard band, no marking element is included. Beneath, in “Zone 1,” is an area in which a marking (i.e., sparse watermark) signal is represented at Strength1, e.g., a density of about 1%. That is, about 1% of the area is
15 darkened by elements 221. Beneath that, in “Zone 2,” is an area in which the watermark signal is included at Strength2, e.g., a density of about 2.5% (i.e., about 2.5% of the area is darkened by elements 221). Beneath that is “Zone 3,” which is marked at Strength3, e.g., a density of about 4%.

Thus, one way of achieving markings of different strengths is by employing
20 uniform marks, distributed spatially across the label at differing local densities.

The marks are placed within the artwork according to the locations of sparse marks resulting from the earlier-described procedure (e.g., in connection with Figs. 4, 5, etc.). The differing densities are achieved by different thresholds T applied to the sync signal, as shown in Fig. 10.

25 Half of the sync signal elements that are selected by the threshold T will not result in printed dark marks, due to the ANDing with the binary data signal (elements of which are 50%-50% split between its two values). Thus, to achieve a marking with a 1% print density, the threshold T must select the 2% of the sync signal elements having the lowest

- 50 -

values. (Likewise, to achieve a marking with 2.5% and 4% print densities, the threshold T must be set to select 5% and 8% of the sync signal elements having the lowest values, respectively.)

As noted, the sync signal is typically a 128 x 128 element tile, and thus comprises

5 16,384 elements – each having a value of between 0 and 255. An exemplary sync signal is the sum of dozens of sine functions, causing most of the sync element values to be tightly clustered between about 90 and 160.

If the statistics of the sync function are understood (as is usually the case), the numeric thresholds beneath which, e.g., 2% of its elements are valued, can be determined 10 mathematically. But these thresholds can also be determined heuristically, by stepping a threshold through the range of 0-255 and noting the cumulative percentage of sync signal samples having values equal or lower than each such threshold. Such data collected for an exemplary 128 x 128 element sync signal tile is shown in Fig. 24A.

By reference to Fig. 24A, it can be seen that setting a threshold value of 102

15 serves to identify 1.8% of the elements in the sync signal tile (all of which have values of 102 or less). When these identified elements are set to black (as at 406a in Fig. 10) and ANDed with corresponding elements of the 128 x 128 data signal tile (as at 408 in Fig. 4), 0.9% of the 16,384 elements in the composite watermark block are thereby selected 20 for darkening. The thus-identified sparse marking elements are used for printing in Zone 1 of Fig. 23.

Similarly, by setting the sync signal threshold value to 107, 4.6% of the elements in the sync signal are selected. This results in darkening of 2.3% of the elements in the composite watermark block – suitable for printing in Zone 2 of Fig. 23.

Likewise, by setting the sync signal threshold value to 110, 7.5% of the sync 25 signal elements are identified, yielding a print density of 3.75% - suitable for printing in Zone 3 of Fig. 23.

In most embodiments, the sparse 128 x 128 composite watermark block is spatially mapped to the label by tiling, starting in the upper left corner of the label. Each

location on the label corresponds to an element of the sparse block. (Some elements of the sparse block correspond to plural locations on the label, due to tiling.)

The sync signal is typically fixed, for all labels. Accordingly, statistics of the sync signal – once understood – can be re-used in connection with generating sparse marks for different label artworks. In some embodiments, a data structure like the table in Fig. 24A is stored in software used to generate sparse marks – and serves to identify threshold values T needed to achieve different print densities.

In Fig. 23 (as in Fig. 4), the elements that express the marking are all identical. The watermark signal is expressed in a bitonal form: it is there, or it isn't.

Such a representation cannot express any variation in values of the component elements. Sometimes it is useful to express variations in the sync signal in the sparse marking. One such arrangement employs dithered marking blocks, e.g., employing 2x2 or 3x3 blocks of elements.

Fig. 25A shows four 2x2 blocks – each of which comprises one dark cell and three light cells. Fig. 25B shows six more such blocks – each of which comprises two dark cells. Fig. 25C shows four blocks comprising three dark cells (i.e., the inverse of Fig. 25A). Fig. 25D shows a block comprised of all dark cells. (The dashed lines serve simply to visually group blocks together; they do not form any part of the printed marking.)

Figs. 26A-26I show some of the blocks possible with 3x3 arrays of elements. Fig. 26A shows the nine different blocks in which a single element is darkened. Fig. 26B shows the 36 different blocks in which two elements are darkened.

Fig. 26C shows a few of the many different 3x3 blocks in which three elements are darkened. Likewise, Figs. 26D, 26E, 26F, 26G and 26H show exemplary blocks in which four, five, six, seven and eight elements, respectively are darkened. Fig. 26I shows the single 3x3 block in which all nine elements are darkened.

(It will be recognized that many of the possible blocks are simply rotational variants – or mirror images across horizontal, vertical or diagonal axes – of each other.

For example, considering Fig. 26A, it will be recognized that the first three blocks, 261, 262 and 263, are unique, but the following six blocks are just rotational variants of blocks 262 and 263.)

The use of dithered marking blocks enables the printed label to represent some of 5 the variation in values among different elements of the watermark signal. In the particular example illustrated, the data signal is bi-level, but the sync signal is continuous. Representing the sync signal with degrees of gradation – corresponding to variation among values of its components elements – can sometimes improve decodability of the resulting marking.

10 In the arrangement just-described, the sync signal elements corresponding to dark label markings typically have values ranging from about 100 to about 110. But in other embodiments, much greater variability is present. Fig. 24B shows a table like that of Fig. 24A, but corresponding to a sync signal composed of four sine waves. In such an embodiment, the sync signal elements corresponding to dark markings typically have 15 values ranging from about 28 to 64 – more than a 2:1 variation. Different markings can be used at different parts of the composite watermark signal to express some of this variation.

Fig. 27 shows a label excerpt like that depicted in Fig. 23, but using dithered representations for some of the sparse signal elements.

20 In Zone 1 of Fig. 27, a single dark mark 271 is depicted. This may be the same element 221 as in Fig. 23. (It may also be a single darkened element within a 2x2 or 3x3 block, such as block 251 in Fig. 25A or block 261 in Fig. 26A.)

25 Zone 2 includes markings of different types. Some (272b, 272c) are single elements, as were used in Zone 1. There is also a 2x2 block 272a that has two diagonal cells darkened. (This may be termed a 2/4-weighted marking block, indicating 2 cells darkened out of an array of 4 cells.) This latter marking may be used in a spatial location corresponding to the ANDing of the data signal with a particularly low-valued sync

signal (e.g., of value 30), whereas the former markings can be used in locations corresponding to higher-valued sync signals (e.g., of values 58 and 62).

Comparing Figs. 23 and 27, it will be noted that mark 232d in Fig. 23 has no counterpart in Fig. 27. Because block 272a includes two darkened cells, a darkened cell 5 may be omitted elsewhere in Zone 2 to maintain the 1% print density.

Zone 3 in Fig. 27 includes other markings of different types – here including 3x3 blocks 273a and 273b. (Block 273a may be termed a 3/9-weighted marking block, and block 273b may be termed a 2/9-weighted marking block.) Because block 273a includes three darkened elements, and block 273b includes two darkened elements, a total of three 10 darkened elements may be omitted elsewhere in Zone 3 of Fig. 27, as compared with Fig. 23. Again, dithered blocks of different weight are used to represent watermark elements corresponding to sync signal elements of differing values.

Dithered blocks can be employed for reasons other than to represent variations in watermark element values. For example, use of dithered elements can make the 15 markings on a label less conspicuous to human viewers.

Backing up, the camera systems used to discern watermark information from printed labels are commonly also designed to read barcodes. As is familiar, a barcode typically includes an array of thin and thick lines. The thin lines may be only a few thousandths of an inch in width. To discern such lines from a typical reading distance, 20 the camera system must have very high resolution.

Such high resolution imagery is not needed for watermark decoding. Indeed, most watermark decoders expect to receive depictions of watermarks at resolutions less than that produced by barcode-capable camera systems. To achieve such reduced resolution, captured imagery is typically down-sampled before watermark decoding. In 25 one illustrative embodiment, a 2:1 down-sampling is applied. Thus, an original image captured at 1600 x 1200 resolution is converted to 800 x 600 resolution. This is done by combining 2x2 neighborhoods of pixels in the original image to yield a single pixel in the down-sampled image (e.g., by averaging). Other systems may employ 3:1 down-

sampling, e.g., combining 3x3 neighborhoods of pixels in the original image to yield a single pixel in the down-sampled image.

Thus, the dithered 2x2 blocks of Fig. 25A-D may be down-sampled into a single pixel. Likewise with the 3x3 blocks of Figs. 26A-I.

5 The signal value that results from down-sampling a 2x2 or 3x3 neighborhood of elements into a single pixel, does not depend much on the particular distribution of darkened elements within the original neighborhood; only the number of darkened elements generally matters. However, the distribution of elements matters to the human eye.

10 Fig. 26C shows 53 different 3x3 blocks in which three cells are darkened (i.e., 3/9-weighted marking blocks). Still more 3/9-weighted marking blocks are not shown. While each effects the same aggregate dithered darkness (i.e., 1/3), applicant has found that blocks in which the darkened cells are not edge-adjoining are less conspicuous to human viewers. Blocks in which darkened cells are separated by white space are best in 15 terms of human aesthetics (e.g., block 264 in Fig. 26C), followed by blocks in which darkened cells adjoin only diagonally (i.e., at their corners, as in block 265 in Fig. 26C). Several such blocks are shown in Fig. 28A and Fig. 28B.

Thus, dithered blocks may be used in label markings simply for better aesthetics – regardless of whether variable information is also thereby represented.

20 (If two dithered blocks are to be placed next to each other, they are desirably selected so that darkened cells don't adjoin across a block border. For example, the conjunction shown in Fig. 29A between a 3/9-weighted marking block and a 2/9-weighted marking block, is less preferred than the conjunction of the same blocks shown in Fig. 29B, in which the right block has been rotated clockwise 90 degrees.)

25 In the preceding discussion, different zones of the label were marked with different print densities, e.g., stepping from 1% to 2.5% to 4%. In other embodiments, continuous gradients can be employed. Fig. 30 helps illustrate.

- 55 -

Fig. 30 shows an excerpt from a single row of a sync signal. The sloping dashed line is a linearly-varying gradient. Only those elements of the sync signal whose values fall below the gradient line are candidates for marking (subject to ANDing with the data signal). At other locations, no corresponding mark appears on the label.

5 If uniform elements 291 are used, the process yields a corresponding row of dark markings, as shown along arrow “A.” The amount by which the sync signal is below the threshold does not matter; all of the markings are the same.

If dithered marking blocks are used, a corresponding row of candidate markings results, as shown along arrow “B.” Here, the amount by which the sync signal is below 10 the gradient thresholds does matter. If the threshold is barely above the sync signal value, a 1/9-weighted marking block is used. For more substantial excursions, correspondingly denser markings blocks are used (e.g., 2/9-, 3/9-, 4/9- and 5/9-weighted marking blocks). By such arrangement, the same sync signal value may be represented 15 differently at different locations on the label – depending on the corresponding value of the gradient at such locations.

In an alternative arrangement, density of a marking blocks does not depend on 20 difference of a sync signal value from a threshold, but rather depends solely on the sync signal’s value. In such arrangement, the same sync signal value will always be represented by the same weight marking on the label (provided a marking is made, based on the ANDing operation).

Figure 30 also highlights the variable of print resolution. In an exemplary embodiment, a label printer with a 203 dot-per-inch resolution is employed. But, here, the corresponding watermark detector employs 3:1 down-sampling. Accordingly, each 25 element of the sparse mark desirably is made to correspond to a 3x3 dot pattern (yielding a single element after down-sampling). That is, the sparse mark is rendered at about 67 waxels per inch.

Each element of the sparse marking signal can be represented by a dark 3x3 dot block, as shown by block 291. But alternatively, each element can be represented by a

dark 2x2 dot block, or a single 1x1 dot block, as shown by blocks 292 and 293, along arrows “C” and “D.”

Fig. 31 shows a white excerpt of label artwork on which a continuous gradient watermark has been formed, employing 3x3 dithered blocks. The spatial density at which the 3x3 blocks appear (i.e., the number of such blocks per unit area) is a function of how many watermark elements fall below the threshold gradient at that part of the artwork. The weight of each dithered block (e.g., 2/9, 3/9, etc.) depends on the amount by which the threshold gradient at that part of the label exceeds the corresponding sync signal element.

The selection of a particular marking block of a desired weight, from among the (often) plural available options, can be made randomly. The result can be checked for edge-adjoining dark cells (such as depicted in Fig. 29A) and, if found, another marking block can be randomly selected (or the originally-selected marking block can be rotated or flipped to check if the Fig. 29A situation is avoided). Alternatively, a single marking block of each weight may be selected, and used consistently whenever such weighting is required. (Again, a check for the Fig. 29A situation can be made, and different orientations of the single marking block can be tried if found.)

Another approach to selection of a particular marking block of desired weight (from among multiple candidates) is to select the marking block that best mimics the finer detail of the ideal analog sync signal. If such selection is unsuitable (e.g., due to edge-adjoining black areas), then the block that second-best mimics the ideal analog signal, or third-best mimics the ideal signal, etc., can be used.

In the figures, the sync signal is generally described as a pixelated 2D signal. For example, the 2D signal has been referenced as a 128 x 128 block of 16,384 cells, each of which has a respective value. But such a representation falls short of the ideal. Such representation includes spatial areas where the signal value does not change (i.e., the spatial area of each pixel), and includes step-wise changes in signal values at pixel boundaries. Those are corruptions of the mathematical ideal.

The mathematical ideal (from which the pixelated version is derived, by spatial- and amplitude-quantization) is a signal that varies continuously in 2D. That continuous signal is the spatial domain counterpart of a signal defined in the spatial-frequency domain: namely, many (sometimes many dozen) different frequency peaks, with random phases. In the spatial domain, such signal takes the form of continuously-varying undulations in two dimensions – sort of like the (complexly-interfering) ripples that result from scattering a handful of pebbles onto a pond.

Roughly-speaking, the 2D blocks discussed above are defined by computing – at each of 128 x 128 uniformly-spaced locations in the spatial domain – the value of this continuously-varying ideal function. Each resulting sample value is then quantized (e.g., to an 8-bit value), and assigned as the value of a pixel that spans a small but certain spatial area. Such procedure generated, e.g., the value for each of the pixel areas in block 402 of Fig. 4.

Instead of computing sample values of the continuously-varying ideal on a grid of 128 x 128 points, such values may instead be computed on a grid that is 4-times as dense in both directions, i.e., 512 x 512. The computational burden is greater, but so is the fidelity of the resulting data.

Fig. 32A shows a single pixel in a 128 x 128 sync signal. It has a value of 119. This sync value resulted from summing multiple random phase peaks at known reference frequencies in the spatial-frequency domain (i.e., a continuous representation of the sync signal in the spatial-frequency domain), and then performing an inverse Fourier transform to yield a corresponding set of 128 x 128 values in the spatial domain (i.e., a quantized representation of the sync signal in the spatial domain). The 119 is one of those values.

Fig. 32B shows the same spatial area, but with the sync signal now quantized to a higher spatial resolution. Instead of performing a 128 x 128 inverse Fourier transform on the continuous representation of the sync signal in the spatial frequency domain, a 512 x 512 inverse Fourier transform is performed instead. The result is 16 values instead of one. Their average value is 119, but they vary around that average.

If a block of weight 1/16 is desired, the cell with the lowest value is darkened; all others can be left white. This is shown in Fig. 34A. Similarly, if a block of weight 2/16 or 3/16 is desired, the two or three cells with the lowest values can be darkened, as shown in Figs. 34B and 34C.

5 If a weight of 4/16 is desired, darkening the four lowest-valued cells would result in the block shown in Fig. 34D. Such arrangement is generally undesirable due to two dark cells adjoining edge-to-edge.

Various approaches can be used in this circumstances. Explanation may be aided by identifying the different cells in the block by reference letters, A, B, C..., with letters 10 assigned in order of ascending cell values. Such identification for the cells in Fig. 32B is shown in Fig. 33

One approach, in this circumstance, is to not darken the 4th lowest value (i.e., cell D, together with cells A, B and C), but instead try the 5th lowest value (cell E) to see if it avoids the dark edge-to-edge situation (i.e., cells A, B, C and E). It does, and this yields 15 the 4/16-weighted block shown in Fig. 35. If selection of cell E still resulting in edge-to-edge darkened cells, then cells F, G, etc., can be tried instead.

Rather than substitute the fifth-ranked cell for the fourth-ranked, an alternative approach is to determine whether there is a cell adjoining cell D that can be darkened without violating the dark-cells-adjoining-edge-to-edge constraint.

20 As shown in Fig. 36, cell D has a value of 94, and five cells adjoin it. The cell to the west (with value 55) is already darkened (it is cell A), so it is not available for darkening. The cell to the northwest can't be darkened without violating the constraint.

The cell to the north can be darkened, but not the cell to the northeast – as that would again violate the constraint. Finally, the cell to the east can be darkened.

25 Where, as here, there are multiple neighboring candidate cells for darkening (i.e., to the north and east), the cell of lowest value is chosen, i.e., cell H with value of 149. The resulting 4/16-weighted block, comprising darkened cells A, B, C and H, is shown in Fig. 37.

The same techniques can be extended to multiple adjoining 4x4 blocks. Fig. 38 is exemplary. On the left is the same block shown in Fig. 32B and discussed above. Adjoining, to the right, is a second block. Cells in the second block are ranked as shown in Fig. 39.

5 Referring to Fig. 40, the first approach starts by identifying cells to darken in the first block. As discussed above, this results in darkening of its cells A, B, C and E. The same procedure is separately applied to the second block, resulting in darkening of its cells A, B, E and F. (Cells C and D are disqualified for darkening due to violation of the dark-edge-to-edge constraint.) As can be seen, two dark cells edge-adjoin across the
10 block boundary: cell E in the first block, and cell A in the second block.

In such case, between the edge-adjoining dark cells, the one with the lowest value should be given priority, and remain where it is. In this case, cell E in the first block has value 108, whereas cell A in the second block has value 57. So cell E in the first block should be changed.

15 In deciding which cell in the first block to darken in lieu of cell E, either of the two approaches described above can be used. The first is to successively try next cells in the ranked ordering, i.e., starting with cell F. (Such method may be termed “trial by rank.”) Cell F is in the lower left corner, and its darkening would violate the constraint. Next to try is cell G. It, too, violates the constraint. Cell H, however, is satisfactory. The
20 adjusted pair of blocks, with cell H in the first block darkened instead of cell E, is shown in Fig. 41.

25 The other approach to resolving the violated constraint of Fig. 40 is to use the neighboring approach discussed above (which may be termed “trial by neighbor”). The cells neighboring the dark cell to be replaced are identified, as shown in Fig. 42. The lowest is first considered, to determine if it violates the constraint. Here, the lowest-valued neighboring cell is to the northwest (with value 131), but its darkening would put it edge-to-edge with the darkened cell of value 84. The next-lowest-valued neighboring cell is the cell to the north (with value 159). It can be darkened without violating the

constraint, so is selected for darkening – in lieu of originally-darkened cell E. This results in the two blocks shown in Fig. 43.

Figs. 38-43 assumed that the dark cells in the stand-alone first block and second block were initially chosen by the first approach, i.e., the trial by rank approach. In other 5 embodiments, the dark cells in the stand-alone blocks can be chosen by the second, trial by neighbor, approach (e.g., which resulted in the block shown in Fig. 37, for the first block). Again, constraint violations that arise when blocks are juxtaposed can be addressed by either the trial by rank, or trial by neighbor, approach.

As the weight of the block increases (e.g., to 6/16, 10/16, etc.), the no-edge-10 adjoining-dark-cells constraint becomes more and more difficult – and eventually impossible – to meet.

One approach is to relax the constraint as necessary. If the constraint cannot be met by the above methods, then repeat the procedure – this time allowing one violation of the constraint. If that condition cannot be met, then allow two violations of the 15 constraint, etc. The aim is to achieve a block of the desired weight, having the minimum possible number of constraint violations. Likewise for assemblages of plural blocks.

For a given block, if the weight requires one violation of the constraint, there may be several possible arrangements of dark cells that qualify. In such case, the favored block arrangement is often one in which the single constraint violation is between the pair 20 of adjoining cells whose values sum to the smallest number. (If there's to be a visually conspicuous pairing of dark cells, such transgression should – in recompense – at least faithfully depict the most important part of the sync signal – the most extreme values.)

Thus, in the block of Fig. 32B, if there is to be one violation of the constraint, it should be to darken both cells A and D in the bottom row (with values of 55 and 94). No 25 other pairing of edge-adjoining cells has a lower sum.

Likewise, if two constraint violations are required to meet a block's weight requirement, the first violation should comprise the two adjoining cells with the lowest sum, and the second violation should comprise the two cells with the second-lowest sum.

(If one cell is common to both pairings, then such approach yields a visual “L” of dark cells, filling 3 of 4 in a 2x2 cell area. In such case, the second violation may instead pair the two adjoining cells having the lowest sum – disqualifying the two cells that are already darkened by the first violation.)

5 While the constraint of primary concern is edge-adjoining dark cells, the same methods can be adapted to check for – and also redress – the secondary concern of diagonally-adjoining dark cells.

It will be recognized that the sync signal is reproduced with greatest fidelity when the lowest-valued cells are darkened – regardless of their spatial relationships with other 10 darkened cells (e.g., edge-adjoining). Conversely, aesthetics are best served by arranging the darkened cells so that a minimum number adjoin. Signal fidelity and aesthetics are thus in tension – enhancing one often degrades the other.

15 The algorithms described above tend to exalt aesthetics over signal fidelity. In some cases, these methods may be pursued to the point that signal fidelity is significantly compromised. (For example, to achieve a 8/16-weight block, the optimum pattern – from an aesthetics standpoint – is a checkerboard spatial alternation of black/white. However, there are only two such patterns that are possible, and the sync signal is usually mimicked by neither.)

20 To moderate the signal-degrading aspect of these algorithms, the number of trial adjustments can be limited to a fixed number. For example, in the trial by rank approach to darkening cells in a single block, when a cell is found to be unsuitable for darkening (by reason of edge-adjoining another dark cell), successive ones of the remaining cells are tried. For example, if cell D can’t be used with cells A, B, and C, then cells E, F, etc., are tried. These trials can be limited in number, e.g., to 2 or 4. If the constraint isn’t met 25 within that number of tries, then the original pairing of edge-adjoining dark cells is used.

Similarly, the number of cells within a block to which such methods are applied can also be limited. (As noted, if a constraint violation is to persist, it desirably involves cells of the lowest signal values, since such extreme values are generally the most

important parts of the sync signal. For this reason, if the number of cells to be processed by one of the algorithms is capped, it is generally best to start with the cells having relatively higher values. For example, to obtain a 6/16-weight block, the ideal would be to darken cells A, B, C, D, E and F. If a cap of 2 is imposed on the number of cells that 5 may be swapped for other cells, then it is generally best to start with cell F and work backwards. Any remaining constraint violation that is not addressed by the capped process will thus involve the more important sync signal values in cells A, B, etc.)

Such caps also apply to application of the algorithm to redress constrain violation across block boundaries (i.e., capping the number of relocation tries for a single cell, as 10 well as capping the number of cells for which relocation is attempted).

Limiting the application of the algorithms in such fashion preserves some measure of signal fidelity, despite its visual impact. The limit to the number of tries (e.g., the cap) can be set by the designer, in accordance with the requirements of a particular application.

15 It will be recognized that the particular arrangements detailed above are exemplary and not limiting.

For example, while the discussion contemplates darkening the lowest-valued sync signal elements, it will be recognized that in other embodiments, the highest-values sync signal elements may be darkened instead. That is, extrema of either variety may be 20 darkened.) Similarly, the element values in the variable data block (e.g., 400 in Fig. 4) that are darkened can be inverted from the arrangement described.

Similarly, while certain of the above examples concerned linear gradients, it will be recognized that non-linear gradients, e.g., following exponential and other functions, can alternatively be employed. Similarly, it will be recognized that two-dimensional 25 gradients (e.g., that vary in both horizontal and vertical directions) can also be used.

It should be understood that the term “gradient” doesn’t always refer to the direction in which density of label marking increases. The term can also be used to refer to the direction in which the density of marking decreases.

While the illustrated dithered marking features are square, this needn't be the case. Non-square features, such as rectangles or other shapes, can alternatively be used.

Speaking of squares, it will be noted that square elements with sharp corners are used in all of the figures to represent dark print markings. In actual practice, sharp-cornered squares are not produced. Instead, the printing process outputs dots of a more rounded configuration. And, as noted earlier, line screening can be applied to further reduce the visibility of the marking.

In a representative label, sparse watermark encoding of a first horizontally-printed swath, an inch wide and tall enough to span 10,000 pixels (e.g., about a quarter inch in an exemplary embodiment), may have darkened between 100 and 200 pixels – or between 1% and 2% of the swath area. Sparse watermark encoding of a second such swath on the same label may have between 225 and 350 pixels darkened. A third such swath may have between 375 and 500 pixels darkened. Different gradient functions – stepped or continuous – can be employed to achieve such differing densities of marking.

The term “watermark” is commonly used to refer to a marking that is imperceptible to human viewers. The markings discussed above are often not of this sort. For example, observers may perceive discrete printed dots, or a greyish cast, on printed labels.

The greyish cast provided by the detailed markings, and the gradient-grey markings that can also be achieved, may be among a palette of patterns from which a graphical artist can draw in composing label artwork. For example, if a blue area of artwork is to transition in luminance between a bright blue and a dark blue of the same chrominance, a gradient grey marking can be added – varying the luminance of the artwork accordingly. (So-called “signal rich art” is further detailed in applicant's published patent application 20110214044.)

Although the preferred arrangement effects thresholding of a continuous synchronization signal, followed by Boolean combination with a binary data signal, other embodiments can proceed differently. For example, some watermark signals are self-

syncing, and operate without a synchronization signal component. In this and other such cases, a continuous signal encoding the binary data can be processed as described above to yield sparse markings.

The specification's reference to "continuous" data should be understood to

5 include data represented in plural-bit quantized fashion, e.g., a synchronization signal represented as an array of 8-bit samples.

While the exemplary implementation uses a printer with 203 dots per inch resolution in horizontal and vertical directions, the technology is naturally not so limited. Thermal printers are commonly available with much higher resolutions (e.g., 300 x 600
10 dpi), and still higher resolutions are becoming available.

Moreover, the detailed arrangements are suitable for use with printing technologies other than thermal, resulting in markings other than thermally-darkened dots. For example, in alternative embodiments in which ink is deposited on a medium, a colored ink – such as red, blue, cyan or yellow – can be applied to form the detailed
15 markings. In some embodiments, the substrate may be darker, rather than lighter, than the markings, in which case the above-described arrangements can be used in inverse.

Although the discussion particularly focused on a label printed on-demand for adhesive application to an item of deli foodstuffs, the same principles are likewise applicable to labels applied to canned foodstuffs, and printed on boxed retail items.

20 In one particular such arrangement, sparse markings of the form described above are ink-printed on boxes and on paper labels for cans, by an offset printing press employing multiple printing plates. For example, one plate may lay down a patterned background flood of blue ink on certain areas of the label, three other plates may define cyan, magenta and yellow layers of photographic imagery and other artwork that are
25 printed on another area of the label. And a further plate may define a panel of nutritional information and other black-printed text. This latter plate may include the above-described sparse markings, with guard bands around the text glyphs. Alternatively, the sparse markings may be included in another of the plates, e.g., for cyan, In such latter

arrangement, guard bands derived from the text layer can be applied to the cyan plate to define safe areas in which watermark markings are omitted. (Naturally, the particular plural-bit information encoded by the detailed watermark markings is not evident to human observers of such packaging.)

5 As is familiar, machine-readable coding can serve to instruct a corresponding machine to take certain actions, such as add an item to a checkout tally, and adjust a total by a coupon amount. The actions needn't involve customer checkout; some actions concern product testing and diagnostics. For example, a scanner can be configured to respond to decoding of certain encoded markings (e.g., instructions encoded in the 10 payload of a printed sparse watermark) by initiating various self-check routines and diagnostic tests.

It will be recognized that the detailed arrangements enable machine encoding to be applied over large expanses of a label's area (e.g., commonly more than 50%, and sometimes 75%, 90%, or more), with negligible impact to the readability of label text. 15 (The guard band regions depicted in Fig. 18B leave 63% of the label area available for machine encoding.) Moreover, by spatially varying the strength of the encoding, the attention of human viewers is not drawn to stark borders at which full-strength encoding suddenly begins. Absence of such distraction further aids the viewer in quickly comprehending the printed text.

20 Because large expanses of a label's area are encoded, the decoding of such information, e.g., at a point of sale system, is made more reliable. Compared to existing barcode markings, the large area encoded with information results in a higher percentage of single-swipe reads. Barcoded items, in contrast, must more frequently be swiped past a scanner system two or more times in order for the small barcode marking to be 25 positioned appropriately for decoding. (The barcode in Fig. 16A spans about 7% of the label area. As noted, the watermark encoding spans over 60% of the label area.)

As point of sale scanners that are capable of decoding watermarked data proliferate (e.g., the Datalogic Magellan 9800i scanner and the Zebra MP6000 scanner),

barcodes on labels will become unnecessary – enabling smaller adhesive labels to be used, and reducing material costs – all with improved performance.

Operating Environment

5 The components and operations of the encoder and decoder are implemented in modules. Notwithstanding any specific discussion of the embodiments set forth herein, the term "module" may refer to software, firmware or circuitry configured to perform any of the methods, processes, functions or operations described herein. Software may be embodied as a software package, code, instructions, instruction sets or data recorded on 10 non-transitory computer readable storage mediums. Software instructions for implementing the detailed functionality can be authored by artisans without undue experimentation from the descriptions provided herein, e.g., written in C, C++, Visual Basic, Java, Python, Tcl, Perl, Scheme, Ruby, etc., in conjunction with associated data. Firmware may be embodied as code, instructions or instruction sets or data that are hard-coded (e.g., nonvolatile) in memory devices. As used herein, the term "circuitry" may 15 include, for example, singly or in any combination, hardwired circuitry, programmable circuitry such as one or more computer processors comprising one or more individual instruction processing cores, state machine circuitry, or firmware that stores instructions executed by programmable circuitry.

20 For the sake of illustration, Fig. 44 is a diagram of an electronic device in which the components of the above encoder and decoder embodiments may be implemented. It is not intended to be limiting, as the embodiments may be implemented in other device architectures or electronic circuitry.

25 Referring to Fig. 16, a system for an electronic device includes bus 100, to which many devices, modules, etc., (each of which may be generically referred as a "component") are communicatively coupled. The bus 100 may combine the functionality of a direct memory access (DMA) bus and a programmed input/output (PIO) bus. In other words, the bus 100 may facilitate both DMA transfers and direct CPU read and

write instructions. In one embodiment, the bus 100 is one of the Advanced Microcontroller Bus Architecture (AMBA) compliant data buses. Although Fig. 16 illustrates an embodiment in which all components are communicatively coupled to the bus 100, it will be appreciated that one or more sub-sets of the components may be 5 communicatively coupled to a separate bus in any suitable or beneficial manner, and that any component may be communicatively coupled to two or more buses in any suitable or beneficial manner. Although not illustrated, the electronic device can optionally include one or more bus controllers (e.g., a DMA controller, an I2C bus controller, or the like or any combination thereof), through which data can be routed between certain of the 10 components.

The electronic device also includes a CPU 102. The CPU 102 may be any microprocessor, mobile application processor, etc., known in the art (e.g., a Reduced Instruction Set Computer (RISC) from ARM Limited, the Krait CPU product-family, any X86-based microprocessor available from the Intel Corporation including those in the 15 Pentium, Xeon, Itanium, Celeron, Atom, Core i-series product families, etc.). The CPU 102 runs an operating system of the electronic device, runs application programs (e.g., mobile apps such as those available through application distribution platforms such as the Apple App Store, Google Play, etc.) and, optionally, manages the various functions of the electronic device. The CPU 102 may include or be coupled to a read-only memory 20 (ROM) (not shown), which may hold an operating system (e.g., a “high-level” operating system, a “real-time” operating system, a mobile operating system, or the like or any combination thereof) or other device firmware that runs on the electronic device. The electronic device may also include a volatile memory 104 electrically coupled to bus 100. The volatile memory 104 may include, for example, any type of random access 25 memory (RAM). Although not shown, the electronic device may further include a memory controller that controls the flow of data to and from the volatile memory 104. The electronic device may also include a storage memory 106 connected to the bus. The storage memory 106 typically includes one or more non-volatile semiconductor memory

devices such as ROM, EPROM and EEPROM, NOR or NAND flash memory, or the like or any combination thereof, and may also include any kind of electronic storage device, such as, for example, magnetic or optical disks. In embodiments of the present invention, the storage memory 106 is used to store one or more items of software. Software can

5 include system software, application software, middleware (e.g., Data Distribution Service (DDS) for Real Time Systems, MER, etc.), one or more computer files (e.g., one or more data files, configuration files, library files, archive files, etc.), one or more software components, or the like or any stack or other combination thereof.

Examples of system software include operating systems (e.g., including one or more

10 high-level operating systems, real-time operating systems, mobile operating systems, or the like or any combination thereof), one or more kernels, one or more device drivers, firmware, one or more utility programs (e.g., that help to analyze, configure, optimize, maintain, etc., one or more components of the electronic device), and the like.

Application software typically includes any application program that helps users solve

15 problems, perform tasks, render media content, retrieve (or access, present, traverse, query, create, organize, etc.) information or information resources on a network (e.g., the World Wide Web), a web server, a file system, a database, etc. Examples of software components include device drivers, software CODECs, message queues or mailboxes, databases, etc. A software component can also include any other data or parameter to be
20 provided to application software, a web application, or the like or any combination thereof. Examples of data files include image files, text files, audio files, video files, haptic signature files, and the like.

Also connected to the bus 100 is a user interface module 108. The user interface module 108 is configured to facilitate user control of the electronic device. Thus the user
25 interface module 108 may be communicatively coupled to one or more user input devices 110. A user input device 110 can, for example, include a button, knob, touch screen, trackball, mouse, microphone (e.g., an electret microphone, a MEMS microphone, or the like or any combination thereof), an IR or ultrasound-emitting stylus, an ultrasound

emitter (e.g., to detect user gestures, etc.), one or more structured light emitters (e.g., to project structured IR light to detect user gestures, etc.), one or more ultrasonic transducers, or the like or any combination thereof.

The user interface module 108 may also be configured to indicate, to the user, the

5 effect of the user's control of the electronic device, or any other information related to an operation being performed by the electronic device or function otherwise supported by the electronic device. Thus the user interface module 108 may also be communicatively coupled to one or more user output devices 112. A user output device 112 can, for example, include a display (e.g., a liquid crystal display (LCD), a light emitting diode (LED) display, an active-matrix organic light-emitting diode (AMOLED) display, an e-ink display, etc.), a light, a buzzer, a haptic actuator, a loud speaker, or the like or any combination thereof.

10

Generally, the user input devices 110 and user output devices 112 are an integral part of the electronic device; however, in alternate embodiments, any user input device 15 110 (e.g., a microphone, etc.) or user output device 112 (e.g., a loud speaker, haptic actuator, light, display, or printer) may be a physically separate device that is communicatively coupled to the electronic device (e.g., via a communications module 114). A printer encompasses many different devices for applying our encoded signals to objects, such as 2D and 3D printers, etching, engraving, embossing, laser marking, etc.

20 Although the user interface module 108 is illustrated as an individual component, it will be appreciated that the user interface module 108 (or portions thereof) may be functionally integrated into one or more other components of the electronic device (e.g., the CPU 102, the sensor interface module 130, etc.).

25 Also connected to the bus 100 is an image signal processor 116 and a graphics processing unit (GPU) 118. The image signal processor (ISP) 116 is configured to process imagery (including still-frame imagery, video imagery, or the like or any combination thereof) captured by one or more cameras 120, or by any other image sensors, thereby generating image data. General functions typically performed by the ISP

116 can include Bayer transformation, demosaicing, noise reduction, image sharpening, or the like or any combination thereof. The GPU 118 can be configured to process the image data generated by the ISP 116, thereby generating processed image data. General functions typically performed by the GPU 118 include compressing image data (e.g., into 5 a JPEG format, an MPEG format, or the like or any combination thereof), creating lighting effects, rendering 3D graphics, texture mapping, calculating geometric transformations (e.g., rotation, translation, etc.) into different coordinate systems, etc. and send the compressed video data to other components of the electronic device (e.g., the volatile memory 104) via bus 100. The GPU 118 may also be configured to perform one 10 or more video decompression or decoding processes. Image data generated by the ISP 116 or processed image data generated by the GPU 118 may be accessed by the user interface module 108, where it is converted into one or more suitable signals that may be sent to a user output device 112 such as a display, printer or speaker.

Also coupled the bus 100 is an audio I/O module 122, which is configured to 15 encode, decode and route data to and from one or more microphone(s) 124 (any of which may be considered a user input device 110) and loud speaker(s) 126 (any of which may be considered a user output device 110). For example, sound can be present within an ambient, aural environment (e.g., as one or more propagating sound waves) surrounding the electronic device. A sample of such ambient sound can be obtained by sensing the 20 propagating sound wave(s) using one or more microphones 124, and the microphone(s) 124 then convert the sensed sound into one or more corresponding analog audio signals (typically, electrical signals), thereby capturing the sensed sound. The signal(s) generated by the microphone(s) 124 can then be processed by the audio I/O module 122 (e.g., to convert the analog audio signals into digital audio signals) and thereafter output 25 the resultant digital audio signals (e.g., to an audio digital signal processor (DSP) such as audio DSP 128, to another module such as a song recognition module, a speech recognition module, a voice recognition module, etc., to the volatile memory 104, the storage memory 106, or the like or any combination thereof). The audio I/O module 122

can also receive digital audio signals from the audio DSP 128, convert each received digital audio signal into one or more corresponding analog audio signals and send the analog audio signals to one or more loudspeakers 126. In one embodiment, the audio I/O module 122 includes two communication channels (e.g., so that the audio I/O module 122

5 can transmit generated audio data and receive audio data simultaneously).

The audio DSP 128 performs various processing of digital audio signals generated by the audio I/O module 122, such as compression, decompression, equalization, mixing of audio from different sources, etc., and thereafter output the processed digital audio signals (e.g., to the audio I/O module 122, to another module such as a song recognition

10 module, a speech recognition module, a voice recognition module, etc., to the volatile memory 104, the storage memory 106, or the like or any combination thereof). Generally, the audio DSP 128 may include one or more microprocessors, digital signal processors or other microcontrollers, programmable logic devices, or the like or any combination thereof. The audio DSP 128 may also optionally include cache or other local memory

15 device (e.g., volatile memory, non-volatile memory or a combination thereof), DMA channels, one or more input buffers, one or more output buffers, and any other component facilitating the functions it supports (e.g., as described below). In one embodiment, the audio DSP 128 includes a core processor (e.g., an ARM® AudioDE™ processor, a Hexagon processor (e.g., QDSP6V5A)), as well as a data memory, program

20 memory, DMA channels, one or more input buffers, one or more output buffers, etc.

Although the audio I/O module 122 and the audio DSP 128 are illustrated as separate components, it will be appreciated that the audio I/O module 122 and the audio DSP 128 can be functionally integrated together. Further, it will be appreciated that the audio DSP 128 and other components such as the user interface module 108 may be (at least

25 partially) functionally integrated together.

The aforementioned communications module 114 includes circuitry, antennas, sensors, and any other suitable or desired technology that facilitates transmitting or receiving data (e.g., within a network) through one or more wired links (e.g., via

Ethernet, USB, FireWire, etc.), or one or more wireless links (e.g., configured according to any standard or otherwise desired or suitable wireless protocols or techniques such as Bluetooth, Bluetooth Low Energy, WiFi, WiMAX, GSM, CDMA, EDGE, cellular 3G or LTE, Li-Fi (e.g., for IR- or visible-light communication), sonic or ultrasonic

5 communication, etc.), or the like or any combination thereof. In one embodiment, the communications module 114 may include one or more microprocessors, digital signal processors or other microcontrollers, programmable logic devices, or the like or any combination thereof. Optionally, the communications module 114 includes cache or other local memory device (e.g., volatile memory, non-volatile memory or a combination 10 thereof), DMA channels, one or more input buffers, one or more output buffers, or the like or any combination thereof. In one embodiment, the communications module 114 includes a baseband processor (e.g., that performs signal processing and implements real-time radio transmission operations for the electronic device).

Also connected to the bus 100 is a sensor interface module 130 communicatively 15 coupled to one or more sensors 132. A sensor 132 can, for example, include an accelerometer (e.g., for sensing acceleration, orientation, vibration, etc.), a magnetometer (e.g., for sensing the direction of a magnetic field), a gyroscope (e.g., for tracking rotation or twist), a barometer (e.g., for sensing altitude), a moisture sensor, an ambient light sensor, an IR or UV sensor or other photodetector, a pressure sensor, a temperature 20 sensor, an acoustic vector sensor (e.g., for sensing particle velocity), a galvanic skin response (GSR) sensor, an ultrasonic sensor, a location sensor (e.g., a GPS receiver module, etc.), a gas or other chemical sensor, or the like or any combination thereof.

Although separately illustrated in Fig. 16, any camera 120 or microphone 124 can also be considered a sensor 132. Generally, a sensor 132 generates one or more signals 25 (typically, electrical signals) in the presence of some sort of stimulus (e.g., light, sound, moisture, gravitational field, magnetic field, electric field, etc.), in response to a change in applied stimulus, or the like or any combination thereof. In one embodiment, all sensors 132 coupled to the sensor interface module 130 are an integral part of the

electronic device; however, in alternate embodiments, one or more of the sensors may be physically separate devices communicatively coupled to the electronic device (e.g., via the communications module 114). To the extent that any sensor 132 can function to sense user input, then such sensor 132 can also be considered a user input device 110.

5 The sensor interface module 130 is configured to activate, deactivate or otherwise control an operation (e.g., sampling rate, sampling range, etc.) of one or more sensors 132 (e.g., in accordance with instructions stored internally, or externally in volatile memory 104 or storage memory 106, ROM, etc., in accordance with commands issued by one or more components such as the CPU 102, the user interface module 108, the audio DSP 128, the 10 cue detection module 134, or the like or any combination thereof). In one embodiment, sensor interface module 130 can encode, decode, sample, filter or otherwise process signals generated by one or more of the sensors 132. In one example, the sensor interface module 130 can integrate signals generated by multiple sensors 132 and optionally process the integrated signal(s). Signals can be routed from the sensor interface module 15 130 to one or more of the aforementioned components of the electronic device (e.g., via the bus 100). In another embodiment, however, any signal generated by a sensor 132 can be routed (e.g., to the CPU 102), the before being processed.

Generally, the sensor interface module 130 may include one or more microprocessors, digital signal processors or other microcontrollers, programmable logic 20 devices, or the like or any combination thereof. The sensor interface module 130 may also optionally include cache or other local memory device (e.g., volatile memory, non-volatile memory or a combination thereof), DMA channels, one or more input buffers, one or more output buffers, and any other component facilitating the functions it supports (e.g., as described above). In one embodiment, the sensor interface module 130 may be 25 provided as the “Sensor Core” (Sensors Processor Subsystem (SPS)) from Qualcomm, the “frizz” from Megachips, or the like or any combination thereof. Although the sensor interface module 130 is illustrated as an individual component, it will be appreciated that the sensor interface module 130 (or portions thereof) may be functionally integrated into

one or more other components (e.g., the CPU 102, the communications module 114, the audio I/O module 122, the audio DSP 128, the cue detection module 134, or the like or any combination thereof).

Review

5 A few of the inventive arrangements detailed above are reviewed in the discussion that follows.

One aspect of the present technology is a method for inserting a sparse, variable data carrying signal into a digital image. Such method includes providing a first signal component that facilitates synchronization function of the sparse, variable data carrying 10 signal, and includes first signal component values at coordinates within a two-dimensional block. A second signal component is also provided, as is modulated to carry a variable data signal. Again, this second signal includes component values at coordinates within the two-dimensional block. The first and second signal components are combined to produce the sparse, variable data carrying signal, by setting sparse 15 elements at coordinates within the two-dimensional block where the first and second component signal values provide compatible modulation of the image. The resulting sparse, variable data carrying signal is inserted into at least a first digital image layer or first digital image channel of a digital image design.

Another aspect of the technology is a method for inserting a sparse, variable data carrying signal into an image. This method includes providing a first orthogonal signal component comprising first signal component values at coordinates within a two-dimensional block. Also provided is a second orthogonal signal component, which is modulated to carry a variable data carrying signal, and comprises second signal component values at coordinates within the two-dimensional block. The first and second 25 signal components are combined to produce the sparse, variable data carrying signal by selecting a subset of the first and second orthogonal components. The resulting sparse, variable data carrying signal is then inserted into at least a first image layer or first image channel of an image design.

A further aspect of the technology is a method for inserting a sparse, variable data carrying signal into an image. Such method includes providing a sparse pattern of elements at coordinates within a two-dimensional block, and also providing a signal component that is modulated to carry a variable data signal. The sparse, variable data

5 carrying signal is generated by distributing the signal component within the two-dimensional block based on the location of the sparse pattern of elements. The resulting sparse, variable data carrying signal is then inserted into at least a first image layer or first image channel of the image.

Still another aspect of the technology is a system for inserting a sparse, variable 10 data carrying signal into a digital image. This system includes a memory for storing data representing the digital image, and one or more processors. The processor is programmed for providing a first signal component that facilitates a synchronization function of the sparse, variable data carrying signal, and includes first signal component values at coordinates within a two-dimensional block. The processor is also programmed 15 to provide a second signal component that is modulated to carry a variable data signal. Like the first, this second signal component includes component values at coordinates within the two-dimensional block. The processor is further programmed to combine the first signal component and the second signal component to produce the sparse, variable data carrying signal by setting sparse elements at coordinates within the two-dimensional 20 block where the first and second component signal values provide compatible modulation of the image. Finally, the processor inserts the sparse, variable data carrying signal into at least a first digital image layer or first digital image channel of the digital image.

Yet another aspect of the technology is an apparatus for inserting a sparse, variable data carrying signal into a digital image. This apparatus includes a memory for 25 storing data representing the digital image, including a representation of a first digital image layer or a first digital image channel. The apparatus further includes means for providing a first orthogonal signal component, which comprises first signal component values at coordinates within a two-dimensional block. The apparatus also includes means

for providing a second orthogonal signal component that is modulated to carry a variable data carrying signal, and comprises second signal component values at coordinates within the two-dimensional block. The apparatus also includes means for combining the first signal component and the second signal component to produce the sparse, variable data

5 carrying signal, by selecting a subset of the first and second orthogonal components.

Finally, the apparatus comprises means for inserting the sparse, variable data carrying signal into at least the first digital image layer or the first digital image channel.

A further aspect of the technology is an apparatus for inserting a sparse, variable data carrying signal into a digital image. This apparatus includes a memory for storing

10 data representing the digital image. It further includes: means for providing a sparse

pattern of elements at coordinates within a two-dimensional block; means for providing a signal component that is modulated to carry a variable data signal; means for generating the sparse, variable data carrying signal by distributing the signal component within the two-dimensional block based on the location of the sparse pattern of elements; means for

15 inserting the sparse, variable data carrying signal into at least a first image layer or first image channel of the digital image, thereby yielding a transformed digital image; and finally a display for displaying the transformed digital image.

In each such arrangement, signal elements can be removed from the signal component at coordinates where the signal component does not coincide with coordinates 20 of the sparse pattern.

Such arrangements can also be equipped to repeat the signal component in two-dimensional blocks within the digital image, with different sparse patterns being used to distribute the signal components in different of the two dimensional blocks.

In some embodiments, the sparse, variable data carrying signal is reduced by use 25 of a screen – such as a line screen.

In embodiments employing compatible modulation, compatible can refer to a consistent direction of modulation of an optical property at a coordinate within the two-dimensional block. It may also refer to modulation at a coordinate in which both the

value of the first and second signal components fall within a common range bounded by at least one threshold. It can also refer to modulation at a coordinate in which both the value of the first and second signal components are quantized to a common quantization value.

5 In embodiments in which the first and second signal components are provided in (or converted to) binary form, compatible modulation can be determined by applying a logical AND operation between binary values of the first and second components at a coordinate. In such case, compatible modulation corresponds to coordinates where the binary values of the first and second components agree. (Conversion to binary can be by
10 applying a threshold.)

In some embodiments, at least one of the first or second components is a multi-valued signal, and is converted to a sparse signal component by applying at least a first threshold. The combining operation can then comprise setting sparse elements at coordinates where the sparse signal component and a value of other of the first or second
15 components are consistent.

In an exemplary embodiment, the multi-valued signal component represents a synchronization template formed by a set of peaks in a transform domain.

Still another aspect of the technology starts with receiving a digital representation of product packaging artwork, comprised of pixels. A guard band region is then defined,
20 surrounding text characters included in the artwork. The artwork is then altered to redundantly encode a machine-readable plural-bit payload across different regions of the artwork. Such altering only alters the artwork outside of the guard band.

In some such embodiments, defining the guard band involves applying a dilating process to the text characters. In some embodiments, outside the guard band, a strength
25 of the machine readable encoding increases along a gradient extending away from text characters. In some embodiments, a first region encloses the guard band region, and a second region encloses the first region. By such arrangement, a strength of the machine

readable encoding has a first value in the first region, and has a second, stronger, value in the second region.

Often the guard band defines a boundary including a portion that echoes a non-linear contour of a single one of the text characters.

5 In implementations in which each of the pixels has either a first or second value, corresponding to a dark and a background color, the altering comprises toggling certain of the pixels between the first and second values.

In some embodiments, the altering involves creating plural dithered blocks in the artwork, where each of the blocks comprises a contiguous two-dimensional N-element 10 region, where $N > 2$, where M of the elements in at least some of the blocks is dark, and where $1 > M > N$.

Sometimes, along a gradient direction in the artwork, M increases, yielding a greater density of darkening alteration along the gradient direction, although the contrary arrangement is possible as well.

15 Sometimes all of the dithered blocks in the artwork are of a common size. In other arrangements, the first and second dithered blocks in the artwork are of different sizes.

The dilating process can comprise a region-growing process that extends outward from each of the pixels by N pixels, where N is 2, 3, 4 or 5.

20 Often the encoded machine-readable plural-bit payload comprises a digital watermark.

Yet another aspect of the technology again begins with receiving a digital representation of product packaging artwork. A two-dimensional data signal is generated that redundantly encodes a plural-bit message. The data signal comprises plural 25 elements, each of which has one of two values. A two-dimensional synchronization signal is received comprising plural elements, each of which has a plural-bit value. Each element of the data signal has an element of the synchronization signal corresponding thereto. The synchronization signal is quantized, including: (a) quantizing a first two-

dimensional portion of the synchronization signal with a first threshold, wherein elements of the first portion having values below the first threshold are assigned a first value, and elements of the first portion having values above the first threshold are assigned a second, different, value; and (b) quantizing a second two-dimensional portion of the

5 synchronization signal with a second threshold different than the first threshold, wherein elements of the second portion having values below the second threshold are assigned the first value, and elements of the second portion having values above the second threshold are assigned the second value. A plural-element two-dimensional marking signal is then generated, by ANDing together the value of an element of the data signal, with the value

10 of a corresponding element in the quantized synchronization signal, where each element of the marking signal corresponds to a location in the artwork. For each location in the artwork that corresponds to an element of the marking signal having a TRUE value, the luminance or chrominance is changed to a different state.

In one such embodiment, the changing of the luminance or chrominance is

15 effected by introducing a dithered pattern into the artwork. The dithered pattern comprises a two-dimensional array of N contiguous elements, where N is at least four, where M of the elements in at least some of the regions are dark, and where $1 > M > N$.

In accordance with another aspect of the technology, a digital representation of artwork is received, where the artwork has an area of uniform color. A two-dimensional

20 data signal is generated that redundantly encodes a plural-bit message. This data signal comprises plural elements, each of which has a single bit value. A two-dimensional synchronization signal is received comprising plural elements. Each of these elements has a plural-bit value. Each element of the data signal has an element of the synchronization signal corresponding thereto. The two-dimensional data signal is

25 processed with the two-dimensional synchronization signal and with a gradient function to yield a two-dimensional gradient marking signal. An ink counterpart of the gradient marking signal can then be printed on a medium with the artwork. Such printing can include printing plural dithered two-dimensional blocks of at least four contiguous

elements each, in which one or more elements of each block are printed to be dark. In such arrangement: in a first zone of the printed medium, within the area of uniform color, M elements in a first of the blocks is printed to be dark; in a second zone of the printed medium, within the area of uniform color, P elements in a second of the blocks is printed to be dark; where $P>M$, and each of the blocks corresponds to a single element of the synchronization signal.

5 The second block may be larger than the first block. For example, the first block can be a 3×3 element block and the first block can be a 2×2 element block. Or 4×4 vs. 3×3 . In most embodiments, M is at least two and P is at least three. In many 10 embodiments, M is at least three and P is at least four.

Another aspect of the technology is a can of food comprising a cylindrical metal enclosure containing foodstuffs. The cylindrical enclosure is wrapped in a paper label bearing printing. This printing comprises a first layer of ink of a first color, deposited on the label in a first pattern, and a second layer of ink of a second color, deposited on the 15 label in a second pattern. One of the inked patterns includes a marking block selected from Fig. 28A or Fig. 28B. The pattern encodes a plural-bit payload that, when imaged by a camera-equipped computer system, and decoded by such computer system, causes the computer system to respond thereto by taking a corresponding action.

In some implementations, one of the inked patterns includes plural different 3×3 20 marking blocks selected from Fig. 28A. In others, one of the inked patterns includes plural different 4×4 marking blocks elected from Fig. 28B.

Yet another aspect of the technology comprises a method of generating a 25 signaling pattern for printing on a substrate. A 2D synchronization signal is defined in a spatial-frequency domain. An $NM \times NM$ inverse Fourier transform is applied to the synchronization signal, to yield an $NM \times NM$ array of sync signal values in a spatial domain. This $NM \times NM$ array of sync signal values in the spatial domain is logically combined with an $N \times N$ array of variable data. By such arrangement, each datum of variable data corresponds to an $M \times M$ sub-block of sync signal values, yielding an $NM \times$

NM array of composite values defining a pattern. In a single MxM sub-block within the NM x NM array of composite values, a first set of P elements is identified as candidates for darkening. This identification act includes determining the P elements whose values are most extreme among the MxM sub-block from the array of composite values.

5 Finally, a pattern is produced including a second set of P elements that are darkened for printing.

Later, a label can be printed with the pattern.

In some embodiments, the first set of P elements and the second set of P elements are identical. In others, they are not. For example, the method can further include
10 determining existence of edge-adjoining elements among the first set of P elements, and identifying the second set of P elements by revising the first set of P elements to avoid edge-adjoining elements.

In an exemplary embodiment, N is 128 and M is 4. If M is 4, the pattern can include at least one block selected from Fig. 28B.

15

Concluding Remarks

Having described and illustrated the principles of the technology with reference to specific implementations, it will be recognized that the technology can be implemented in many other, different, forms.

20 The methods, processes, and systems described above may be implemented in hardware, software or a combination of hardware and software. For example, the signal processing operations described above may be implemented as instructions stored in a memory and executed in a programmable computer (including both software and firmware instructions), implemented as digital logic circuitry in a special purpose digital
25 circuit, or combination of instructions executed in one or more processors and digital logic circuit modules. The methods and processes described above may be implemented in programs executed from a system's memory (a computer readable medium, such as an electronic, optical or magnetic storage device). The methods, instructions and circuitry

operate on electronic signals, or signals in other electromagnetic forms. These signals further represent physical signals like image signals captured in image sensors, audio captured in audio sensors, as well as other physical signal types captured in sensors for that type. These electromagnetic signal representations are transformed to different states

5 as detailed above to detect signal attributes, perform pattern recognition and matching, encode and decode digital data signals, calculate relative attributes of source signals from different sources, etc.

The above methods, instructions, and hardware operate on reference and suspect signal components. As signals can be represented as a sum of signal components formed 10 by projecting the signal onto basis functions, the above methods generally apply to a variety of signal types. The Fourier transform, for example, represents a signal as a sum of the signal's projections onto a set of basis functions.

The particular combinations of elements and features in the above-detailed embodiments are exemplary only; the interchanging and substitution of these teachings 15 with other teachings in this and the above mentioned patents and applications are also contemplated.

We claim:

1. A method for inserting a sparse, variable data carrying signal into a digital image, the method comprising:

5 providing a first signal component, the first signal component facilitating a synchronization function of the sparse, variable data carrying signal, and comprising first signal component values at coordinates within a two-dimensional block;

providing a second signal component, the second signal component being modulated to carry a variable data signal, and comprising second signal component

10 values at coordinates within the two-dimensional block;

combining the first signal component and the second signal component to produce the sparse, variable data carrying signal by setting sparse elements at coordinates within the two-dimensional block where the first and second component signal values provide compatible modulation of the image; and

15 inserting the sparse, variable data carrying signal into at least a first digital image layer or first digital image channel of a digital image design.

2. The method of claim 1 wherein compatible modulation comprises a consistent direction of modulation of an optical property at a coordinate within the two-dimensional

20 block.

3. The method of claim 1 wherein compatible modulation comprises modulation at a coordinate in which both the value of the first and second signal components fall within a common range bounded by at least one threshold.

4. The method of claim 3 wherein compatible modulation comprises modulation at a coordinate in which both the value of the first and second signal components are quantized to a common quantization value.

5 5. The method of claim 1 in which the first and second signal components are provided in or converted to a binary form, and wherein compatible modulation is determined by applying a logical AND operation between binary values of the first and second components at a coordinate, and compatible modulation corresponds to coordinates where the binary values of the first and second components agree.

10

6. The method of claim 5 wherein at least one of the first or second signal components is converted to a binary form by applying a threshold.

15 7. The method of claim 1 wherein at least one of the first or second components is a multi-valued signal, and is converted to a sparse signal component by applying at least a first threshold, and the combining comprises setting sparse elements at coordinates where the sparse signal component and a value of other of the first or second components are consistent.

20 8. The method of claim 7 wherein the first component is a multi-valued signal component.

9. The method of claim 8 wherein the multi-valued signal component represents a synchronization template formed by a set of peaks in a transform domain.

10. A method for inserting a sparse, variable data carrying signal into an image, the method comprising:

providing a first orthogonal signal component, the first orthogonal signal component comprising first signal component values at coordinates within a two-dimensional block;

5 providing a second orthogonal signal component, the second orthogonal signal component being modulated to carry a variable data carrying signal, and comprising second signal component values at coordinates within the two-dimensional block;

10 combining the first signal component and the second signal component to produce the sparse, variable data carrying signal by selecting a subset of the first and second orthogonal components; and

inserting the sparse, variable data carrying signal into at least a first image layer or first image channel of an image design.

15 11. The method of claim 10 including quantizing the first and second orthogonal components to produce first and second sparse signal components, and merging the first and second sparse components.

20 12. The method of claim 11 wherein the quantizing comprises applying at least a first threshold to remove signal from the first or second orthogonal components.

13. The method of claim 10 including combining the first and second orthogonal signal components, and quantizing the combined first and second orthogonal signal components to produce the sparse, variable data carrying signal.

14. The method of claim 10 wherein the first orthogonal signal component being formed to facilitate synchronization of the sparse, variable data carrying signal.

5 15. A method for inserting a sparse, variable data carrying signal into an image, the method comprising:

 providing a sparse pattern of elements at coordinates within a two-dimensional block;

10 providing a signal component, the signal component being modulated to carry a variable data signal;

 generating the sparse, variable data carrying signal by distributing the signal component within the two-dimensional block based on the location of the sparse pattern of elements; and

15 inserting the sparse, variable data carrying signal into at least a first image layer or first image channel of the image.

16. The method of claim 15 wherein signal component is converted to a sparse, variable data carrying signal by removing signal elements of the signal component at coordinates where the signal component does not coincide with coordinates of the sparse pattern.

20 17. The method of claim 15 wherein the signal component is repeated in two-dimensional blocks within the image, and different sparse patterns are used to distribute the signal component in plural of two dimensional blocks.

18. A system for inserting a sparse, variable data carrying signal into a digital image, said system comprising:

5 memory for storing data representing the digital image; and

 one or more processors programmed for:

 providing a first signal component, the first signal component facilitating a synchronization function of the sparse, variable data carrying signal, and comprising first signal component values at coordinates within a two-dimensional
10 block;

 providing a second signal component, the second signal component being modulated to carry a variable data signal, and comprising second signal component values at coordinates within the two-dimensional block;

15 combining the first signal component and the second signal component to produce the sparse, variable data carrying signal by setting sparse elements at coordinates within the two-dimensional block where the first and second component signal values provide compatible modulation of the image; and

 inserting the sparse, variable data carrying signal into at least a first digital image layer or first digital image channel of the digital image.

20

19. The system of claim 18 wherein compatible modulation comprises a consistent direction of modulation of an optical property at a coordinate within the two-dimensional block.

20. The system of claim 18 wherein compatible modulation comprises modulation at a coordinate in which both the value of the first and second signal components fall within a common range bounded by at least one threshold.

5 21. The system of claim 20 wherein compatible modulation comprises modulation at a coordinate in which both the value of the first and second signal components are quantized to a common quantization value.

10 22. The system of claim 18 wherein at least one of the first or second components is a multi-valued signal, and is converted to a sparse signal component by applying at least a first threshold, and the combining comprises setting sparse elements at coordinates where the sparse signal component and a value of other of the first or second components are consistent.

15 23. An apparatus for inserting a sparse, variable data carrying signal into a digital image, said apparatus comprising:

memory for storing data representing the digital image, the data including a representation of a first digital image layer or a first digital image channel;

20 means for providing a first orthogonal signal component, the first orthogonal signal component comprising first signal component values at coordinates within a two-dimensional block;

25 means for providing a second orthogonal signal component, the second orthogonal signal component being modulated to carry a variable data carrying signal, and comprising second signal component values at coordinates within the two-dimensional block;

- 90 -

means for combining the first signal component and the second signal component to produce the sparse, variable data carrying signal by selecting a subset of the first and second orthogonal components; and

means for inserting the sparse, variable data carrying signal into at least the first
5 digital image layer or the first digital image channel.

24. The apparatus of claim 23 including means for quantizing the first and second orthogonal components to produce first and second sparse signal components, and means for merging the first and second sparse components.

10

25. The apparatus of claim 24 wherein the quantizing comprises applying at least a first threshold to remove signal from the first or second orthogonal components.

26. The apparatus of claim 23 including means for combining the first and
15 second orthogonal signal components, and means for quantizing the combined first and second orthogonal signal components to produce the sparse, variable data carrying signal.

27. The apparatus of claim 23 wherein the first orthogonal signal component being formed to facilitate synchronization of the sparse, variable data carrying signal.

20

28. The system of claim 18 in which said one or more processors each comprises two or more processing cores.

29. The method of claim 1, in which prior to said inserting, said method comprises reducing the sparse, variable data carrying signal with a line screen.

5 30. The method of claim 15 in which prior to said inserting, said method comprises reducing the sparse, variable data carrying signal with a line screen.

31. An apparatus for inserting a sparse, variable data carrying signal into a digital image, said apparatus comprising:

10 memory for storing data representing the digital image;

means for providing a sparse pattern of elements at coordinates within a two-dimensional block;

means for providing a signal component, the signal component being modulated to carry a variable data signal;

15 means for generating the sparse, variable data carrying signal by distributing the signal component within the two-dimensional block based on the location of the sparse pattern of elements;

means for inserting the sparse, variable data carrying signal into at least a first image layer or first image channel of the digital image, said inserting yielding a
20 transformed digital image; and

a display for displaying the transformed digital image.

32. The apparatus of claim 31 further comprising means for removing signal elements of the signal component at coordinates where the signal component does not
25 coincide with coordinates of the sparse pattern.

33. The apparatus of claim 31 further comprising means for repeating the signal component in two-dimensional blocks within the digital image, with different sparse patterns being used to distribute the signal component in plural of two dimensional

5 blocks.

34. The apparatus of claim 31 further comprising means for reducing the sparse, variable data carrying signal with a line screen.

10 35. A method comprising the acts:

receiving a digital representation of product packaging artwork, comprised of pixels;

defining a guard band region surrounding text characters included in said artwork; and

15 altering the artwork to redundantly encode a machine-readable plural-bit payload across different regions of said artwork;

wherein said altering only alters the artwork outside of said guard band.

36. The method of claim 35 in which said defining act comprises applying a 20 dilating process to said text characters.

37. The method of claim 35 in which, outside of the guard band, a strength of said machine readable encoding increases along a gradient extending away from text characters.

25

38. The method of claim 35 in which a first region encloses the guard band region, and a second region encloses the first region, wherein a strength of said machine

readable encoding has a first value in the first region, and has a second, stronger, value in the second region.

39. The method of claim 38 in which a third region encloses the second
5 region, wherein a strength of said machine readable encoding has a third value in the third region that is greater than said second value.

40. The method of claim 35 in which said guard band defines a boundary
10 including a portion that echoes a non-linear contour of a single one of said text characters.

41. The method of claim 35 in which a first of said text characters has a first height, and an outer boundary of the guard band region is spaced from said first text character by less than said first height.

15 42. The method of claim 41 the outer boundary of the guard band region is spaced from said first text character by less than half of said first height.

43. The method of claim 35 in which:
20 each of said pixels has either a first or second value, corresponding to a dark and a background color; and
said altering comprises toggling certain of said pixels between said first and second values.

25 44. The method of claim 43 in which said altering comprises creating plural dithered blocks in said artwork, each of said blocks comprising a contiguous two-dimensional N-element region, where $N > 2$, where M of the elements in at least some of said blocks is dark, and where $1 > M > N$.

45. The method of claim 44 in which, along a gradient direction in the artwork, M increases, yielding a greater density of darkening alteration along said gradient direction.

5

46. The method of claim 45 in which said dithered blocks in said artwork are all of a common size.

47. The method of claim 45 in which first and second dithered blocks in said 10 artwork are of different sizes.

48. The method of claim 43 that further includes printing the altered artwork using a thermal printing mechanism, onto a thermally-sensitive printing medium.

15 49. The method of claim 35 that includes defining the guard band region to include encircled regions of said text characters.

50. The method of claim 36 in which said dilating process comprises a region-growing process that extends outward from each of said pixels by N pixels.

20

51. The method of claim 50 in which N is 2, 3, 4 or 5.

52. The method of claim 35 in which the encoded machine-readable plural-bit payload comprises a digital watermark.

25

53. A method comprising the acts:
receiving a digital representation of product packaging artwork;

generating a two-dimensional data signal that redundantly encodes a plural-bit message, the data signal comprising plural elements, each of which has one of two values;

receiving a two-dimensional synchronization signal comprising plural elements,

5 each of which has a plural-bit value, each element of said data signal having an element of the synchronization signal corresponding thereto;

quantizing the synchronization signal, including: (a) quantizing a first two-dimensional portion of the synchronization signal with a first threshold, wherein elements of said first portion having values below the first threshold are assigned a first value, and
10 elements of said first portion having values above the first threshold are assigned a second, different, value; and (b) quantizing a second two-dimensional portion of the synchronization signal with a second threshold different than the first threshold, wherein elements of said second portion having values below the second threshold are assigned said first value, and elements of said second portion having values above the second
15 threshold are assigned the second value;

generating a plural-element two-dimensional marking signal, by ANDing together the value of an element of the data signal, with the value of a corresponding element in the quantized synchronization signal, each element of the marking signal corresponding to a location in the artwork; and

20 for each location in the artwork that corresponds to an element of the marking signal having a TRUE value, changing luminance or chrominance to a different state.

54. The method of claim 53 that includes printing a medium with the changed artwork.

25

55. The method of claim 53 that further includes:

defining a guard band region surrounding text characters included in said artwork;
and

setting, to FALSE, elements of the two-dimensional marking signal corresponding to locations in the artwork within said defined guard band, wherein the marking signal does not change luminance or chrominance within said guard band.

5 56. The method of claim 53 in which said changing act comprises introducing a dithered pattern into the artwork, the dithered pattern comprising a two-dimensional array of N contiguous elements, where N is at least four, where M of the elements in at least some of said regions are dark, and where $1 > M > N$.

10 57. A method comprising the acts:
receiving a digital representation of artwork, the artwork having an area of uniform color;
generating a two-dimensional data signal that redundantly encodes a plural-bit message, the data signal comprising plural elements, each of which has a single bit value;
15 receiving a two-dimensional synchronization signal comprising plural elements, each of which has a plural-bit value, each element of said data signal having an element of the synchronization signal corresponding thereto;
processing the two-dimensional data signal with the two-dimensional synchronization signal and with a gradient function to yield a two-dimensional gradient marking signal; and
20 printing an ink counterpart of the gradient marking signal on a medium with the artwork, said printing comprising printing plural dithered two-dimensional blocks of at least four contiguous elements each, in which one or more elements of each block are printed to be dark;

25 wherein:
in a first zone of the printed medium, within said area of uniform color, M elements in a first of said blocks is printed to be dark;

in a second zone of the printed medium, within said area of uniform color, P elements in a second of said blocks is printed to be dark;

P>M; and

each of said blocks corresponds to a single element of the synchronization signal.

5

58. The method of claim 57 in which the second block is larger than the first block.

59. The method of claim 57 in which the second block is a 3x3 element block
10 and the first block is a 2x2 element block.

60. The method of claim 57 in which the second block is a 4x4 element block
and the first block is a 3x3 element block.

15 61. The method of claim 57 in which M is at least two and P is at least three.

62. The method of claim 57 in which M is at least three and P is at least four.

63. A can of food comprising a cylindrical metal enclosure containing
20 foodstuffs, the cylindrical enclosure being wrapped in a paper label bearing printing, the
printing comprising a first layer of ink of a first color, deposited on the label in a first
pattern, and a second layer of ink of a second color, deposited on the label in a second
pattern, one of said inked patterns including a marking block selected from Fig. 28A or
Fig. 28B and encoding a plural-bit payload that, when imaged by a camera-equipped
25 computer system, and decoded by such computer system, causes the computer system to
respond thereto by taking a corresponding action.

64. The can of claim 63 wherein one of said inked patterns includes plural different 3x3 marking blocks selected from Fig. 28A.

65. The can of claim 63 wherein one of said inked patterns includes plural 5 different 4x4 marking blocks selected from Fig. 28B.

66. A method of generating a signaling pattern for printing on a substrate, the method comprising the acts:

defining a 2D synchronization signal in a spatial-frequency domain;

10 applying an NM x NM inverse Fourier transform to said signal, to yield an NM x NM array of sync signal values in a spatial domain;

logically combining said NM x NM array of sync signal values with an N x N array of variable data, wherein each datum of variable data corresponds to an M x M sub-block of sync signal values, yielding an NM x NM array of composite values defining a 15 pattern;

in an MxM sub-block within said NM x NM array of composite values, identifying a first set of P elements as candidates for darkening, wherein said identifying comprises determining the P elements whose values are most extreme among said MxM sub-block from the array of composite values; and

20 producing a pattern including a second set of P elements that are darkened for printing.

67. The method of claim 66 that further comprises printing a label with said pattern.

25

68. The method of claim 66 in which the first set of P elements and the second set of P elements are identical.

- 99 -

69. The method of claim 66 that further includes determining existence of edge-joining elements among the first set of P elements, and identifying the second set of P elements by revising the first set of P elements to avoid edge-joining elements.

5 70. The method of claim 66 in which N is 128 and M is 4.

71. The method of claim 66 in which M is 4, and said pattern includes at least one block selected from Fig. 28B.

10




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig. 12




Fig. 15




Fig. 13




Fig. 14

9/26




FIG. 16A




FIG. 16B

FIG. 16C




FIG. 17A




FIG. 17B

FIG. 17C

10/26




FIG. 18A




FIG. 18B




FIG. 19A




FIG. 19B



FIG. 19C




FIG. 20A




FIG. 20B






FIG. 21

FIG. 22**FIG. 23**

Sync Element Value	Cumulative %
0-92	nil
93	0.2%
94	0.3%
95	0.4%
96	0.6%
97	0.7%
98	0.8%
99	1.0%
100	1.2%
101	1.5%
102	1.8%
103	2.3%
104	2.7%
105	3.2%
106	3.9%
107	4.6%
108	5.4%
109	6.4%
110	7.5%
111	8.9%
112	10.3%
113	11.8%
114	13.7%
115	15.3%
116	17.3%
117	19.8%
118	21.9%
119	24.4%
120	27.1%
121	29.5%
122	32.4%
123	35.3%
124	38.3%
125	41.5%
126	44.8%
127	48.1%
128	51.5%
129	54.4%
...	...

FIG. 24A

Sync Element Value	Cumulative %
0-11	nil
12	0.21%
13	0.27%
14	0.31%
15	0.34%
16	0.38%
17	0.40%
18	0.45%
19	0.53%
20	0.58%
21	0.61%
22	0.63%
23	0.68%
24	0.73%
25	0.87%
26	0.93%
27	0.99%
28	1.12%
29	1.21%
30	1.29%
31	1.49%
32	1.59%
33	1.70%
34	1.82%
35	1.93%
36	2.03%
37	2.17%
38	2.27%
39	2.39%
40	2.53%
41	2.65%
42	2.83%
43	3.00%
44	3.18%
45	3.34%
46	3.52%
47	3.70%
48	4.00%
49	4.18%
50	4.41%
51	4.56%
52	4.75%
53	4.94%
54	5.18%
55	5.38%
56	5.58%
57	5.83%
58	6.10%
59	6.28%
60	6.59%
61	6.97%
62	7.27%
63	7.68%
64	8.04%
65	8.33%
66	8.69%
67	9.03%
68	9.51%
69	9.86%
70	10.36%

FIG. 24B







FIG. 25A**FIG. 25B****FIG. 25C****FIG. 25D**

FIG. 26A**FIG. 26B**

**FIG. 26C**



**FIG. 27**

**FIG. 28A****FIG. 29A****FIG. 29B**



**FIG. 28B**

FIG. 30






FIG. 31




FIG. 32A

179	84	131	159
189	192	193	108
81	166	189	218
130	55	94	149

FIG. 32B

A=55	I=159
B=81	J=166
C=84	K=179
D=94	L=189a
E=108	M=189b
F=130	N=192
G=131	O=193
H=149	P=218

FIG. 33




FIG. 34A




FIG. 34B




FIG. 34C




FIG. 34D




FIG. 35

179	84	131	159
189	192	149	108
81	166	189	218
130	55	94	149

FIG. 36






FIG. 37


179	84	131	159	217	85	123	95
189	192	193	108	57	138	67	74
81	166	189	218	115	166	83	176
130	55	94	149	96	174	190	164

FIG. 38

A=57	I=123
B=67	J=138
C=74	K=164
D=83	L=166
E=85	M=174
F=95	N=176
G=96	O=190
H=115	P=217

FIG. 39**FIG. 40****FIG. 41**

179	84	131	159
189	192	193	108
81	166	189	218
130	55	94	149

FIG. 42**FIG. 43**




FIG. 44

INTERNATIONAL SEARCH REPORT

International application No.

PCT/US 16/22836

A. CLASSIFICATION OF SUBJECT MATTER

IPC(8) - G06T 1/00, H04L 9/32 (2016.01)

CPC - H04N21/8358, H04L9/3281, H04N1/32144, H04N2201/3233, G11B20/00086

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC(8): G06T 1/00, H04L 9/32 (2016.01); CPC: H04N21/8358, H04L9/3281, H04N1/32144, H04N2201/3233, G11B20/00086

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched
USPC: 713/176, 382/100Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)
PatBase, ProQuest Dialog, Google Web, Google Patents (Search terms: digital watermark, signature, fingerprint, sparse, modulate, ANDing, processing cores, consistent direction, bound, threshold, quantize, binary, multi-value, synchronization, template, peak, transform domain, orthogonal, remove, line screen, etc.)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2004/0032972 A1 (Stach et al.) 19 February 2004 (19.02.2004), para. [0015], [0017]-[0018], [0020], [0022]-[0023], [0025], [0027], [0032], and [0066], and Figs. 1-2, and claim 11.	1-4, 7-27, 31-33
--		-----
Y		5-6, 28-30, 34
Y	US 2009/0040022 A1 (Finkenzeller) 12 February 2009 (12.02.2009), para. [0014].	5-6
Y	US 2014/0325656 A1 (Sallam) 30 October 2014 (30.10.2014), para. [0124], [0217], and [0221].	28
Y	US 2011/0085209 A1 (Man) 14 April 2011 (14.04.2011), para. [0009] and [0028].	29-30, 34

 Further documents are listed in the continuation of Box C.

* Special categories of cited documents:	
"A"	document defining the general state of the art which is not considered to be of particular relevance
"E"	earlier application or patent but published on or after the international filing date
"L"	document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
"O"	document referring to an oral disclosure, use, exhibition or other means
"P"	document published prior to the international filing date but later than the priority date claimed
"T"	later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"X"	document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"Y"	document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"&"	document member of the same patent family

Date of the actual completion of the international search

21 July 2016 (21.07.2016)

Date of mailing of the international search report

22 AUG 2016

Name and mailing address of the ISA/US
Mail Stop PCT, Attn: ISA/US, Commissioner for Patents
P.O. Box 1450, Alexandria, Virginia 22313-1450
Facsimile No. 571-273-8300Authorized officer:
Lee W. YoungPCT Helpdesk: 571-272-4300
PCT OSP: 571-272-7774

INTERNATIONAL SEARCH REPORT

International application No.

PCT/US 16/22836

Box No. II Observations where certain claims were found unsearchable (Continuation of item 2 of first sheet)

This international search report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. Claims Nos.: because they relate to subject matter not required to be searched by this Authority, namely:

2. Claims Nos.: because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out, specifically:

3. Claims Nos.: because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box No. III Observations where unity of invention is lacking (Continuation of item 3 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

-- see extra sheet --

1. As all required additional search fees were timely paid by the applicant, this international search report covers all searchable claims.
2. As all searchable claims could be searched without effort justifying additional fees, this Authority did not invite payment of additional fees.
3. As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims for which fees were paid, specifically claims Nos.:

4. No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.: 1-34

Remark on Protest

- The additional search fees were accompanied by the applicant's protest and, where applicable, the payment of a protest fee.
- The additional search fees were accompanied by the applicant's protest but the applicable protest fee was not paid within the time limit specified in the invitation.
- No protest accompanied the payment of additional search fees.

INTERNATIONAL SEARCH REPORT

International application No.

PCT/US 16/22836

In continuation of Box No. III Observations where unity of invention is lacking (Continuation of item 3 of first sheet)

This application contains the following inventions or groups of inventions which are not so linked as to form a single general inventive concept under PCT Rule 13.1.

Group I: Claims 1-34, directed to a method and system for inserting a sparse, variable data carrying signal into an image.

Group II: Claims 35-52, directed to receiving a digital representation of product packaging artwork, defining a guard band region surrounding text characters included in said artwork, and altering the artwork to redundantly encode a machine-readable plural-bit payload across different regions of said artwork.

Group III: Claim 53-56, directed to receiving a digital representation of product packaging artwork, generating a two-dimensional data signal that redundantly encodes a plural-bit message, receiving a two-dimensional synchronization signal, quantizing the synchronization signal, generating a plural-element two-dimensional marking signal, and for each location in the artwork that corresponds to an element of the marking signal having a TRUE value, changing luminance or chrominance to a different state.

Group IV: Claim 57-62, directed to receiving a digital representation of artwork, the artwork having an area of uniform color; generating a two-dimensional data signal that redundantly encodes a plural-bit message, receiving a two-dimensional synchronization signal, processing the two-dimensional data signal with the two-dimensional synchronization signal and with a gradient function to yield a two-dimensional gradient marking signal, and printing an ink counterpart of the gradient marking signal on a medium with the artwork.

Group V: Claim 63-65, directed to a can of food comprising a cylindrical metal enclosure containing foodstuffs, the cylindrical enclosure being wrapped in a paper label bearing printing including a marking block encoding a plural-bit payload that, when imaged by a camera-equipped computer system, and decoded by such computer system, causes the computer system to respond thereto by taking a corresponding action.

Group VI: Claim 66-71, directed to a method for generating a signaling pattern for printing on a substrate.

The groups of inventions listed above do not relate to a single general inventive concept under PCT Rule 13.1 because, under PCT Rule 13.2, they lack the same or corresponding special technical features for the following reasons:

The special technical feature of the Group I invention is providing a signal component, the signal component facilitating a synchronization function of the sparse, variable data carrying signal, and comprising signal component values at coordinates within a two-dimensional block, providing a signal component being modulated to carry a variable data signal, and comprising signal component values at coordinates within the two-dimensional block, combining signal components to produce the sparse, variable data carrying signal by setting sparse elements at coordinates within the two-dimensional block where the component signal values provide compatible modulation of the image, and inserting the sparse, variable data carrying signal into at least a first digital image layer or first digital image channel of a digital image design, not required by Group II-VI. (See Figs. 3-5 for example).

The special technical feature of the Group II invention is altering the artwork to redundantly encode a machine-readable plural-bit payload across different regions of said artwork, wherein said altering only alters the artwork outside of said guard band, not required by Group I or III-VI. (See Fig. 18A for example).

The special technical feature of the Group III invention is generating a plural-element two-dimensional marking signal, by ANDing together the value of an element of the data signal, with the value of a corresponding element in the quantized synchronization signal, each element of the marking signal corresponding to a location in the artwork, and for each location in the artwork that corresponds to an element of the marking signal having a TRUE value, changing luminance or chrominance to a different state, not required by Group I-II or IV-VI. (See Fig. 10 for example).

The special technical feature of the Group IV invention is printing an ink counterpart of the gradient marking signal on a medium with the artwork, said printing comprising printing plural dithered two-dimensional blocks of at least four contiguous elements each, in which one or more elements of each block are printed to be dark, wherein: in a first zone of the printed medium, within said area of uniform color, M elements in a first of said blocks is printed to be dark, in a second zone of the printed medium, within said area of uniform color, P elements in a second of said blocks is printed to be dark, $P > M$, and each of said blocks corresponds to a single element of the synchronization signal, not required by Group I-III or V-VI. (See Fig. 23 for example).

The special technical feature of the Group V invention is a can of food comprising a cylindrical metal enclosure containing foodstuffs, the cylindrical enclosure being wrapped in a paper label bearing printing, the printing comprising a first layer of ink of a first color, deposited on the label in a first pattern, and a second layer of ink of a second color, deposited on the label in a second pattern, one of said inked patterns including a marking block selected from Fig. 28A or Fig. 28B and encoding a plural-bit payload that, when imaged by a camera-equipped computer system, and decoded by such computer system, causes the computer system to respond thereto by taking a corresponding action, not required by Group I-IV or VI. (See Fig. 28A & Fig. 28B for example).

(See next extra sheet)

INTERNATIONAL SEARCH REPORT

International application No.

PCT/US 16/22836

In continuation of previous extra sheet:

The special technical feature of the Group VI invention is defining a 2D synchronization signal in a spatial-frequency domain, applying an NM x NM inverse Fourier transform to said signal, to yield an NM x NM array of sync signal values in a spatial domain, logically combining said NM x NM array of sync signal values with an N x N array of variable data, wherein each datum of variable data corresponds to an M x M subblock of sync signal values, yielding an NM x NM array of composite values defining a pattern, in an MxM sub-block within said NM x NM array of composite values, identifying a first set of P elements as candidates for darkening, wherein said identifying comprises determining the P elements whose values are most extreme among said MxM sub-block from the array of composite values, and producing a pattern including a second set of P elements that are darkened for printing, not required by Group I-V. (See Figs. 32A & 32B for example).

Groups II-III share the technical features of, in various combination, receiving a digital representation of product packaging artwork.

However, these shared technical features fail to represent a contribution over the prior art of US 2014/0304122 A1 to Rhoads et al. (hereinafter 'Rhoads'), which discloses receiving a digital representation of product packaging artwork (para [0006], [0181] - "capturing imagery depicting package artwork from a 3D package of consumer goods, by resting the package on a turntable and rotating the turntable so that imagery from plural different viewpoints is captured. This captured imagery is processed (e.g., by a hardware processor) to discern locations and payloads of tiled steganographic watermarks encoded in the package artwork").

Groups II-IV share the technical features of, in various combination, receiving a digital representation of artwork, and redundantly encoding a plural-bit message.

However, these shared technical features fail to represent a contribution over the prior art of US 2015/0016688 A1 (Aller), which discloses receiving a digital representation of artwork (para [0288]-[0290] - "the smartphone is imaging part of a cereal box--the artwork"), and redundantly encoding (para [0155], [0312] - "Redundant encoding of certain barcodes") a plural-bit message (para [0333] - "the smartphone applies imagery captured by its camera to a watermark detector, which extracts plural-bit data encoded into the artwork of the product packaging").

Groups III-IV share the technical features of, in various combination, receiving a digital representation of artwork, generating a two-dimensional data signal that redundantly encodes a plural-bit message, the data signal comprising plural elements, receiving a two-dimensional synchronization signal comprising plural elements, each of which has a plural-bit value, each element of said data signal having an element of the synchronization signal corresponding thereto.

However, these shared technical features fail to represent a contribution over the prior art of Aller, which discloses receiving a digital representation of artwork (para [0288]-[0290]), generating a two-dimensional data signal that redundantly encodes (para [0155], [0312]) a plural-bit message (para [0333]), the data signal comprising plural elements, receiving a two-dimensional synchronization signal comprising plural elements, each of which has a plural-bit value, each element of said data signal having an element of the synchronization signal corresponding thereto (para [0610]-[0619] - "Software in the smartphone determines the pose of the camera relative to the first image. With this information, the software geometrically warps the second (background) image, so that it has a scale, and perspective, as if viewed from the same pose. The phone then composites the two images--the phone-captured imagery of the four Beatles, and the background--warped to provide the original backdrop of the image. The two images complement each other to present a unified image that appears like the original album cover").

Groups I, & III-IV share the technical features of, in various combination, utilizing two-dimensional data/signals.

However, these shared technical features fail to represent a contribution over the prior art of US 2014/0052555 A1 (MacIntosh), which discloses utilizing two-dimensional data/signals (para [0210], [0464] - "a two-dimensional exhaustive search is done--varying both the assumed location of the edge of the cylinder"; "a two dimensional surface of the available colors").

Groups I, III-IV & VI share the technical features of, in various combination, utilizing two-dimensional data/signals and synchronization.

However, these shared technical features fail to represent a contribution over the prior art of US 2007/0181685 A1 to Zhu et al. (hereinafter 'Zhu'), which discloses utilizing two-dimensional data/signals (para [0011], claim 43 - "two-dimensional image contour tracing methods are used to extract package dimension data") and synchronization (para [0073] - "a synchronized amplitude-modulated laser beam is automatically produced and scanned across the width of a conveyor belt structure and, during each scan there across, detects and processes the reflected laser beam in order to capture a row of raw range (and optionally reflection-intensity) information").

Groups II-III & V share the technical features of, in various combination, utilizing product packaging/wrapping/labels.

However, these shared technical features fail to represent a contribution over the prior art of Zhu, which discloses utilizing product packaging/wrapping/labels (para [0395] - "the tunnel scanning systems can read bar code symbols on the package products when the bar code symbol label is placed under diaphanous materials").

Thus, the inventions listed as Groups I-VI lack unity of invention because they do not share a same or corresponding special technical feature providing a contribution over the prior art.