



US007117669B2

(12) **United States Patent**
Kaboord et al.

(10) **Patent No.:** **US 7,117,669 B2**
(45) **Date of Patent:** **Oct. 10, 2006**

(54) **TEMPERATURE SWING ADSORPTION AND
SELECTIVE CATALYTIC REDUCTION NOX
REMOVAL SYSTEM**

(75) Inventors: **Wayne Scott Kaboord**, Mequon, WI
(US); **Dawn Marie Becher**, Random
Lake, WI (US); **Fred Joseph Begale**,
Oconomowoc, WI (US); **Daniel**
Woodrow Fellers, Milwaukee, WI
(US); **John Albert Kovacich**,
Waukesha, WI (US); **Steven M.**
Kuznicki, Edmonton (CA)

(73) Assignee: **Eaton Corporation**, Cleveland, OH
(US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 120 days.

(21) Appl. No.: **10/839,397**

(22) Filed: **May 5, 2004**

(65) **Prior Publication Data**

US 2005/0247049 A1 Nov. 10, 2005

(51) **Int. Cl.**
F01N 3/00 (2006.01)

(52) **U.S. Cl.** **60/288**; 60/274; 60/286;
60/298; 60/300; 60/301

(58) **Field of Classification Search** 60/274,
60/286, 287, 288, 295, 300, 301, 298
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,125,231 A 6/1992 Patil et al.
5,388,406 A 2/1995 Takeshima et al.
5,457,958 A * 10/1995 Boegner et al. 60/279
5,587,137 A 12/1996 Swaroop et al.
5,727,385 A * 3/1998 Hepburn 60/297
5,910,097 A 6/1999 Boegner et al.
6,113,870 A 9/2000 Haslbeck et al.

6,119,452 A 9/2000 Kinugasa et al.
6,170,259 B1 * 1/2001 Boegner et al. 60/286
6,176,079 B1 1/2001 Konrad et al.
6,274,106 B1 8/2001 Held
6,334,986 B1 1/2002 Gieshoff et al.
6,338,244 B1 1/2002 Guenther et al.
6,354,079 B1 3/2002 Choi et al.
6,422,007 B1 * 7/2002 Hartick 60/298
6,560,958 B1 5/2003 Bromberg et al.
6,713,030 B1 3/2004 Chandler et al.
6,735,940 B1 5/2004 Stroia et al.
6,779,339 B1 * 8/2004 Laroo et al. 60/297

(Continued)

FOREIGN PATENT DOCUMENTS

EP 0 540 280 A1 5/1993

(Continued)

Primary Examiner—Thomas Denion


Assistant Examiner—Diem Tran

(74) *Attorney, Agent, or Firm*—Paul V. Keller, LLC

(57) **ABSTRACT**

The invention relates to systems for removing NOx from exhaust. In one aspect of the invention, after adsorption, an NOx adsorber is isolated from the main exhaust flow and desorption induced by raising the temperature. The desorbed NOx is combined with a reductant and reduced over a catalyst. Preferably, the reductant is syn gas produced in an on-board reformer. The catalyst need never be exposed to the main exhaust flow, which is particularly advantageous for catalysts sensitive to water, oxygen, or sulfur. In another aspect of the invention, a recirculating flow is induced through an NOx adsorber during a regeneration cycle. Recirculation can induce greater desorption at a given temperature, provide a source of heat for the adsorber, and allow a higher conversion rate with a fixed amount of catalyst. A further aspect of the invention relates to a vehicle-mounted adsorbers with provisions for heating.

18 Claims, 7 Drawing Sheets



US 7,117,669 B2

Page 2

U.S. PATENT DOCUMENTS


6,832,473 B1 * 12/2004 Kupe et al. 60/286
6,868,668 B1 * 3/2005 Suzuki 60/286
2002/0081254 A1 6/2002 Boger
2002/0194835 A1 12/2002 Bromberg et al.
2003/0074888 A1 4/2003 Jobson et al.
2003/0074893 A1 4/2003 Webb et al.
2003/0177763 A1 9/2003 Twigg et al.
2003/0226350 A1 12/2003 Liu
2004/0018132 A1 1/2004 Bartley et al.
2004/0040287 A1 3/2004 Beu et al.
2004/0050037 A1 3/2004 Betta et al.

2004/0052693 A1 3/2004 Crane, Jr. et al.
2004/0076565 A1 4/2004 Gandhi et al.
2004/0076566 A1 4/2004 Unger et al.

FOREIGN PATENT DOCUMENTS

EP 0 702 134 A2 9/1995
EP 1 027 919 A2 8/2000
EP 1 281 842 A2 2/2003
JP 55-5785 * 1/1980
WO WO 0151178 * 7/2005

* cited by examiner

**Fig. 1**




Fig. 2






Fig. 3






Fig. 6




Fig. 7




Fig. 8








Fig. 10





1

TEMPERATURE SWING ADSORPTION AND SELECTIVE CATALYTIC REDUCTION NO_x REMOVAL SYSTEM

FIELD OF THE INVENTION

The present invention relates to the field of pollution control devices for internal combustion engines.

BACKGROUND OF THE INVENTION

NO_x emissions from vehicles with internal combustion engines are an environmental problem recognized worldwide. Several countries, including the United States, have long had regulations pending that will limit NO_x emissions from vehicles. Manufacturers and researchers have put considerable effort toward meeting those regulations. In conventional gasoline powered vehicles that use stoichiometric fuel-air mixtures, three-way catalysts have been shown to control NO_x emissions. In diesel powered vehicles and vehicles with lean-burn gasoline engines, however, the exhaust is too oxygen-rich for three-way catalysts to be effective.

Several solutions have been posed for controlling NO_x emissions from diesel powered vehicles and lean-burn gasoline engines. One set of approaches focuses on the engine. Techniques such as exhaust gas recirculation, homogenizing fuel-air mixtures, and inducing sparkless ignition can reduce NO_x emissions. These techniques alone, however, will not eliminate NO_x emissions. Another set of approaches remove NO_x from the vehicle exhaust. These include the use of lean-burn NO_x catalysts, NO_x adsorber-catalysts, and selective catalytic reduction (SCR).

Lean-burn NO_x catalysts promote the reduction of NO_x under oxygen-rich conditions. Reduction of NO_x in an oxidizing atmosphere is difficult. It has proved challenging to find a lean-burn NO_x catalyst that has the required activity, durability, and operating temperature range. Lean-burn NO_x catalysts also tend to be hydrothermally unstable. A noticeable loss of activity occurs after relatively little use. Lean burn NO_x catalysts typically employ a zeolite wash coat, which is thought to provide a reducing microenvironment. The introduction of a reductant, such as diesel fuel, into the exhaust is generally required and introduces a fuel economy penalty of 3% or more. Currently, peak NO_x conversion efficiency with lean-burn catalysts is unacceptably low.

NO_x adsorber-catalysts alternately adsorb NO_x and catalytically reduce it. The adsorber can be taken offline during regeneration and a reducing atmosphere provided. The adsorbant is generally an alkaline earth oxide adsorbant, such as BaCO₃ and the catalyst can be a precious metal, such as Ru. A drawback of this system is that the precious metal catalysts and the adsorbant may be poisoned by sulfur.

SCR involves using ammonia as the reductant. The NO_x can be temporarily stored in an adsorbant or ammonia can be fed continuously into the exhaust. SCR can achieve NO_x reductions in excess of 90%, however, there is concern over the lack of infrastructure for distributing ammonia or a suitable precursor. SCR also raises concerns relating to the possible release of ammonia into the environment.

U.S. Pat. No. 6,560,958 describes an adsorber-catalyst system in which hydrogen-rich synthesis gas (syn gas), including H₂ and CO, is used as a reductant to regenerate the adsorber. The syn gas is produced from diesel fuel in a plasma converter. Periodically, the adsorber is taken offline from the exhaust system and supplied with the syn gas. The adsorber contains a catalyst for SCR of NO₂ with syn gas.

2

U.S. Pat. No. 5,587,137 describes an exhaust system with a zeolite adsorber and a catalyst placed in line. The system is intended for a stoichiometrically fed engine. The adsorber is meant to be active during cold start. After the adsorber and catalyst heat up desorption is induced by making the exhaust stream rich in oxygen. Desorbed products are asserted to undergo conversion over the downstream catalyst in spite of the oxygen-rich conditions. A preferred adsorbant is a Y, Beta, or ZSM-5 zeolite with an SiO₂ to Al₂O₃ mole ratio of about 3 to about 20, ion exchanged with a rare earth metal, chromium, or a combination thereof.

There continues to be a long felt need for reliable, affordable, and effective systems for removing NO_x from the exhaust of diesel and lean-burn gasoline engines.

SUMMARY OF THE INVENTION

The following presents a simplified summary in order to provide a basic understanding of some aspects of the invention. This summary is not an extensive overview of the invention. It is intended neither to identify key or critical elements of the invention nor to delineate the scope of the invention. Rather, the primary purpose of this summary is to present some concepts of the invention in a simplified form as a prelude to the more detailed description that is presented later.

One aspect of the invention relates to a system and method for removing NO_x from a vehicle exhaust. The exhaust is first passed over an NO_x adsorber. The NO_x adsorber is then isolated from the main exhaust flow. While the adsorber is isolated, desorption is induced, preferably by raising the temperature of the adsorber. The desorbed NO_x is combined with a reductant and reduced over a catalyst. Preferably, the reductant is syn gas produced by an on-board reformer. According to the invention, the catalyst need never be exposed to the main exhaust flow, which is particularly advantageous for catalysts sensitive to water, oxygen, or sulfur. One catalyst bed can be shared by several adsorbers. The adsorber and the catalyst bed can be independently optimized for their respective functions. To the extent that poisoning of the adsorber is unavoidable, the adsorber can be a simpler and more cheaply replaced unit than a combined adsorber-catalyst.

Another aspect of the invention also relates to a system and method of treating vehicle exhaust with a NO_x adsorber. During a regeneration phase, a recirculating flow is induced through the adsorber. A reductant is injected into the flow and reduction of NO_x occurs either in the adsorber or in a separate catalyst bed. A fan can be used to drive the flow. Recirculation can serve one of several purposes. One purpose would be to induce greater desorption from the adsorber at a given temperature. Another purpose would be to heat the adsorber using the recirculating flow. A further purpose would be to achieve a higher conversion rate for NO_x with a fixed amount of catalyst.

A further aspect of the invention relates to an NO_x adsorber for a vehicle exhaust system. According to this aspect of the invention, the NO_x adsorber is provided with a heating system, which can be an electrical resistance heater or a fluid heat exchanger. The NO_x adsorber facilitates the use of temperature swing adsorption in treating vehicle exhaust.

To the accomplishment of the foregoing and related ends, the following description and associated drawings set forth in detail certain illustrative aspects and implementations of the invention. These are indicative of but a few of the various ways in which the principles of the invention may be

3

employed. Other aspects, advantages and novel features of the invention will become apparent from the following detailed description of the invention when considered in conjunction with the drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is schematic illustration of a vehicle in accordance with one aspect of the present invention;

FIG. 2 is an illustration of an adsorber comprising a porous-walled monolith;

FIG. 3 is an illustration of an adsorber comprising a cohesive mass of adsorbant pellets;

FIG. 4 is an illustration of an adsorber comprising a stack of coated screens;

FIG. 5 is a cross-sectional view of the adsorber of FIG. 4;

FIG. 6 is an illustration of an adsorber comprising an annular monolith adsorbant bed and a central channel for heat exchange;

FIG. 7 is a cross-sectional view of the adsorber of FIG. 6;

FIG. 8 is another cross-sectional view of the adsorber of FIG. 6;

FIG. 9 is an illustration of an adsorber comprising a rolled, coated screen adsorbant bed surrounding a central channel for heat exchange;

FIG. 10 is a cross-sectional view of the adsorber of FIG. 9;

FIG. 11 is an illustration of an adsorber comprising coated screens radially arrayed around a central channel;

FIG. 12 is a cross-sectional view of the adsorber of FIG. 11;

FIG. 13 is a schematic illustration of vehicle according to another aspect of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

FIG. 1 is a schematic illustration of an exemplary vehicle 10 according to one aspect of the present invention. The vehicle 10 includes an internal combustion engine 11, NOx adsorbers 12 and 13, a reductant source 20, and a catalyst bed 22. The internal combustion engine 11 provides a motive force for the vehicle 10 and produces an exhaust containing NOx. The adsorbers 12 and 13 absorb NOx from the exhaust. While one of the adsorbers is treating the main exhaust flow, the other adsorber can be isolated from the main exhaust flow and regenerated. Regeneration involves inducing desorption of NOx and combining the desorbed NOx with a reductant supplied by reductant source 20. The reductant and NOx react over the catalyst bed 22 to reduce NOx to N₂.

The various flows are managed with valve and conduits. Valves 14 and 15, in cooperation with valves 18 and 19, selectively direct the main exhaust flow to one or the other of the adsorbers. In FIG. 1, the valve 15 is closed while the valve 14 is open, whereby the main exhaust flow is through the adsorber 12. Valves 16 and 17 selectively place one or the adsorber in communication with the catalyst bed 22. In FIG. 1, valve 16 is close while valve 17 is open, whereby gas desorbed from the adsorber 13 is channeled to the catalyst bed 22. Valve 21 controls the flow of reductant from the reductant source 20.

The invention is specifically applicable to vehicles and other mobile applications. Mobile applications create restriction on weight, dimensions, and durability. For example, an adsorber or a catalyst bed for a mobile application must be reasonably resistant to degradation under the

4

vibrations encountered during vehicle motion. The vehicle 10 is typically powered by a fossil fuel such as diesel, gasoline, natural gas, or propane. The invention is applicable to any vehicle that burns fuel and generates an exhaust comprising NOx.

The adsorbers 12 and 13 comprise an adsorbant for NOx and are physically structured to facilitate mass transfer between the main exhaust flow and the adsorbant while limiting back-pressure on the internal combustion engine 11. NO_x includes, without limitation, NO, NO₂, N₂O, and N₂O₂. From time to time, one or another of these specific compounds may be used as a point of reference for the sake of specificity. Adsorption is the preferential partitioning of a substance from the gas phase to the surface of a solid. Adsorption can be chemical or physical.

The adsorbant preferably has a large capacity for adsorbing NOx at typical adsorption temperatures and exhaust NOx partial pressures. Preferably, the adsorbant can adsorb at least about 3% of an NOx species by weight adsorbant at a typical adsorption temperature and 1 torr partial pressure of the NOx species, more preferably at least about 5% by weight adsorbant, and still more preferably at least about 7% by weight adsorbant. The weight of adsorbant does not include the weight of any binders or inert substrates.

The weight of adsorbant can be significant. To minimize total weight, the adsorbant preferably accounts for at least 40% of the adsorber weight, more preferably at least about 60%, and still more preferably at least about 80%. Preferably, the adsorbers as a group can adsorb at least 250 gm of an NOx species at a typical adsorption temperature and 1 torr partial pressure of the NOx species, more preferably at least about 500 gm, still more preferably at least about 1000 gm.

The vehicle 10 has two adsorbers, however, three or more adsorbers can be used. To the extent that smaller adsorbers can be cycled more quickly, the use of larger numbers of smaller adsorbers can reduce the total amount of adsorbant required. At any given time, more than one adsorber can be treating the main exhaust flow. Also, more than one adsorber can be undergoing regeneration. A system could also be designed with only one adsorber, but the main exhaust flow would go untreated during the regeneration cycle.

A typical adsorption temperature depends on the embodiment of the present invention. In one embodiment, the adsorbers 12 and 13 are cooled with engine coolant and the typical adsorption temperature is 65° C. In another embodiment, the adsorbers 12 and 13 are cooled with engine coolant or ambient air, but the exhaust is kept above the condensation temperature of water. In such a case, the typical adsorption temperature is 120° C. In a further embodiment, the adsorbers 12 and 13 are cooled to about an average exhaust gas temperature, and a typical adsorption temperature is 350° C. Lower temperature operating regimes have the advantage that a greater degree of NOx desorption can be achieved with a smaller change in the adsorbant temperature.

The heat (energy) of adsorption is a critical factor in determining the temperature increase that will induce desorption. Solid adsorbants generally have a plurality of types of binding sites with a range of heats of adsorption, but an average or approximate value can be determined by analyzing changes in partial pressure with temperature. A larger heat of adsorption means a more rapid increase in partial pressure of adsorbants with temperature. Preferably, the heat of adsorption for NO on the adsorbant is at least about 50 kJ/mol, more preferably at least about 70 kJ/mol, still more preferably at least about 90 kJ/mol.

5

Any suitable adsorbant material can be used. Examples of adsorbants are molecular sieves, such as zeolites, alumina, silica, and activated carbon. Further examples are oxides, carbonates, and hydroxides of alkaline earth metals such as Mg, Ca, Sr, and Be or alkali metals such as K or Ce. Still further examples include metal phosphates, such as phosphates of titanium and zirconium.

Molecular sieves are materials having a crystalline structure that defines internal cavities and interconnecting pores of regular size. Zeolites are the most common example. Zeolites have crystalline structures generally based on atoms tetrahedrally bonded to each other with oxygen bridges. The atoms are most commonly aluminum and silicon (giving aluminosilicates), but P, Ga, Ge, B, Be, and other atoms can also make up the tetrahedral framework. The properties of a zeolite may be modified by ion exchange, for example with a rare earth metal or chromium. While the selection of an adsorbant depends on such factors as the desired adsorption temperature and the desorption method, preferred zeolites generally include rare earth zeolites and Thomsonite. Rare earth zeolites are zeolites that have been extensively (i.e., at least about 50%) or fully ion exchanged with a rare earth metal, such as lanthanum.

Desorption from the adsorbers 12 and 13 is preferably induced by raising the temperature of the adsorbant bed, however, other methods, such as pressure swing adsorption, and combinations of methods can be used. Depending on the adsorbant, another material such as a hydrocarbon, an oxygenated hydrocarbon, H₂, or CO may induce desorption. Where the reductant induces adsorption, it may be desirable to connect the reductant source 20 to the catalyst bed 22 via the adsorbers 12 and 13, whereby the reductant passes through one or more of the adsorbers 12 and 13 in reaching the catalyst bed 22.

An adsorbant material that adsorbs NO_x in an oxidizing atmosphere and desorbs NO_x in a reducing atmosphere can be an alkaline metal or an alkaline earth metal oxide loaded with a precious metal. An alkali metal and copper-doped hydrous zirconium oxide can also exhibit this property. Producing a reducing atmosphere can involve exposing the adsorbant to a reductant such as a hydrocarbon, an oxygenated hydrocarbon, H₂, or CO.

The adsorbant is typically combined with a binder and either formed into a self-supporting structure or applied as a coating over an inert substrate. A binder can be, for example, a clay, a silicate, or a cement. Portland cement can be used to bind molecular sieve crystals. Generally, the adsorbant is most effective when a minimum of binder is used. Preferably, the adsorbant bed contains from about 3 to about 20% binder, more preferably from about 3 to about 12%, most preferably from about 3 to about 8%.

The adsorbers 12 and 13 can have any suitable structure. Suitable structures can include monoliths, layered structures having two-dimensional passages, as between sheets or screens, and packed beds. Monolith passages can have any suitable cross section, including, for example, round, hexagonal, or triangular passages. Sheets or screens can be layered in any suitable fashion including, for example, stacking, rolling, or arraying about a central axis. Packed beds can be formed with pellets of the adsorbant, preferably held together with a binder or sintered to form a cohesive mass.

Optionally, the adsorbers 12 and 13 can be provided with a suitable mechanism for heating or cooling. For example, the adsorbers can be permeated with heat-exchange passages in fluid isolation from the passages provided for exhaust flow. A hot or cold fluid is circulated through the heat-exchange passages to heat or cool the adsorber. A cooling

6

fluid could be, for example, engine coolant or ambient air. A heating fluid could be, for example, hot exhaust or a fluid that draws heat from hot exhaust or a heat-producing device such as an ammonia synthesis reactor, a catalytic reformer, or an adsorber.

In one embodiment the adsorbers each have a small number of heat-exchange passages, for example less than five, and preferably just one. A single channel can pass through the center of each adsorber. A central channel is typically rather large, having for example a cross-sectional area of at least about 1 square inch. The channels can be provided with heat exchanger fins. Advantages of heat exchange through a single central passage include simplicity and low pressure drop. The design takes advantage of the fact that larger variations in temperature are generally permissible in adsorption beds according to the invention than in catalyst beds.

The adsorber 12 and 13 can include a provision for electrical heating. Where the adsorber includes a metal substrate, the metal substrate can be used as an electrical resistance heater. As discussed more fully below, the adsorbers 12 and 13 can be heated and/or cooled by circulating hot or cold gases through the same passages through which the vehicle exhaust flows. If the adsorbers 12 and 13 are provided with an oxidation catalyst, they can be heated by supplying them with fuel and oxygen. An oxidation catalyst may also be useful in the adsorbers 12 and 13 to convert NO to NO₂ for purposes discussed below. The adsorbers 12 and 13 can be provided with temperature sensors to control heating and/or cooling.

Adsorbants with narrow pores, especially molecular sieves, work better with certain adsorber structures. Generally, when considering a design such as a monolith for an exhaust application, smaller passages are considered desirable because they provide better contact between the gas stream and a coating on the walls. Small passages are also desirable for NO_x adsorbers, up to the point where pressure drop becomes problematic, however, even with very narrow passages the utilization of a molecular sieve adsorbant may be poor. The gases may not effectively diffuse through the narrow pores of the molecular sieve into the depths of the walls and only the outer surface of the walls may be effective for adsorption.

FIG. 2 illustrates an adsorber 30 with a design for improving the utilization of a molecular sieve adsorbant. The substrate 30 comprises a monolith 31 within a housing 32. The monolith 31 is preferably a self-supporting structure without an inert substrate. The monolith can be cast or extruded. Casting may be accomplished by pressing a coarse mixture into a mold followed by curing or filling the mold with small pellets and sintering them into a cohesive mass. Extrusion can be carried out in a similar fashion with heat applied at the point of extrusion to cure the binder or sinter the pellets. The walls 33 of the substrate 30 have a macroporous structure, whereby the diffusion path length from the macro-pores to the centers of the pellets is substantially less than the diffusion path length from the channels to the centers of the walls. Because the monolith 31 lacks an inert substrate, it comprises a large fraction of adsorbant by weight. Preferably, the walls of the monolith, exclusive of the channel volume and exclusive of any pores having an effective diameter less than 100 nm (an effective diameter being defined with reference to mercury porosimetry) have a void volume fraction of at least about 0.2, more preferably at least about 0.3, still more preferably at least about 0.4.

Preferably, an adsorbant bed comprises at least about 50% adsorbant by weight, more preferably at least about 70%,

7

still more preferably at least about 90%. For the adsorber **30**, the adsorbent bed is the monolith. The weight of an adsorbent bed includes any inert substrate and any binders, but does not include any housing.

FIG. **3** illustrates an adsorber **35** comprising a cohesive mass of pellets **36** in a housing **37**. Loose pellets in a packed bed have a tendency to erode when mounted on a vehicle. The adsorber **35** mitigates this problem by forming the pellets into a cohesive mass, either by sintering the pellets together or mixing them with a binder. The individual pellets are preferably themselves made up of smaller particles held together by a binder or a sintering process. The spaces between the pellets correspond to the channels of the adsorber **30** and the voids in the pellets correspond to the voids in the walls of the adsorber **30**. The comments regarding preferred composition and void sizes for the adsorber **30** apply to the adsorber **35**. The adsorber **35** is provided in a pancake design. A pancake design gives a large cross-sectional area in the direction of flow and thereby reduces the pressure drop for a given bed volume.

FIGS. **4** and **5** illustrates a substrate **40** in the form of a stack **41** of coated metal screens **42** in a housing **43**. The adsorbent, which can be a molecular sieve, forms a coating over the screens **42**. Exhaust flows between the screens **42**. The spacing between the screens is controlled by spacers **44**. The openings in the screens **42** provide additional surface area for the adsorbent. Electrical leads **45** are connected to the screens along either side of the adsorbent bed. By connecting a power source to the electrical leads **45**, the adsorber **40** can be heated.

FIGS. **6** to **8** illustrate an adsorber **50** comprising an annular monolith **51** enclosed in a housing **52** and surrounding a central channel **53**. The central channel **53** is in fluid isolation from the monolith **51**, but can be used to heat or cool the monolith. For example, the monolith can be heated by passing hot exhaust through the central channel **51** and cooled by driving ambient air through the central channel **51**. The monolith itself can have any suitable structure. In one embodiment, the monolith is made up of metal foil coated with an adsorbent. A metal foil substrate can be used for electrical resistance heating.

FIGS. **9** and **10** illustrate an adsorber **60** that has a housing **63** and a central channel **64**. The adsorbent bed **61** comprises a metal screen coated with adsorbent and rolled into a hollow cylinder to form roughly annular passages. The widths of the passages are controlled by spacers **62**. The housing **63** is different from the housing **53** of the adsorber **50** in that the central passage vents out the ends rather than the sides. These housings can be interchanged.



FIGS. **11** and **12** illustrate adsorber **70** using the housing **52** and the central channel **53**. The adsorber **70** comprises an adsorbent bed **71** made of metal screens **72** coated with adsorbent, attached edgewise, and arrayed radially about the central channel **53**. Attaching the screens **72** edgewise to the central channel **53** may facilitate heat transfer between the adsorbent bed **71** and the central channel **53**. Optionally, the central channel **53** includes heat-exchanger fins extending from the edges of the channel towards its interior. The screens **72** curve as they extend away from the central channel **53**. The curvature limits or eliminates the tendency for the spacing between screens **72** to increase with distance from the central channel **53**. The curvature also makes the adsorber **70** more compact and may further facilitate heat exchange with a fluid in the central channel **53**. The spacing between screens is controlled with spacers **73**.

Gas desorbed from the adsorbers **12** and **13** is combined with a reductant from reductant source **20** and reacted over

8

the catalyst bed **22**. Examples of suitable reductants include ammonia, synthesis gas (syn gas) products, hydrocarbons, and oxygenated hydrocarbons. Ammonia can be supplied in any suitable form, including for example urea, ammonium bicarbonate, or ammonium carbamate. Syn gas products include H₂ and CO. A group consisting of syn gas products includes H₂ and CO individually as well as mixtures of the two.

The catalyst bed **18** comprises a catalyst for a reaction that reduces NO to N₂. The reaction can be, for example, one or more of the following:



Catalysts for these reaction will also reduce other species of NOx.

Examples of catalysts for reactions with ammonia include oxides of metals such as Cu, Zn, V, Cr, Al, Ti, Mn, Co, Fe, Ni, Pd, Pt, Rh, Rd, Mo, W, and Ce, zeolites, such as ZSM-5 or ZSM-11, substitutes with metal ions such as cations of Cu, Co, Ag, Zn, or Pt, and activated carbon. Reaction can be obtained at relatively low temperatures, for example, temperatures in the range from about 230 to about 450° C.

Examples of catalysts for reactions with syn gas products, hydrocarbons, or oxygenated hydrocarbons include, without limitation, precious metals, such as Au, Ag, and Cu, group VIII metals, such as Pt, Pd, Ru, Ni, and Co, Cr, Mo, or K. The catalysts can be combined, for example Au with Pt, Pd, or Ru. The catalyst can be supported on a zeolite, such as Y zeolite, beta zeolite, mordenite, and ZSM-5, or a metal oxide, such as Fe₂O₃, Al₂O₃, ZnO, ZrO₂, TiO₂, MnO₂, and CeO₂. A preferred catalyst, giving high conversions at low temperatures, is Au on a metal oxide support, especially an Fe₂O₃ or Al₂O₃ support. High conversions can be obtained in the temperature range from about 150 to about 300° C.

Any of the substrates and structures described with reference to the NOx adsorbers **12** and **13** can be used for the catalyst bed **22** however, the design considerations are different and in any particular application different structures may be used. For example, a ceramic monolith with a wash coat containing the catalyst would be an appropriate choice for the catalyst bed **22**, but would generally not be used for the adsorbers **12** and **13**. In this regard, it should be noted that the adsorbers **12** and **13** are generally alternately heated and cooled and a small thermal mass is preferable to both conserve energy and reduce cycle time, whereas thermal mass is a much smaller concern for the catalyst bed **22**.

The catalyst bed **22** can be heated by any of the mechanisms described with reference to the NOx adsorbers **12** and **13**. The reduction reactions are endothermic and some heat must generally be supplied. The heat can be supplied by the feed gases. Alternatively, the catalyst bed **22** can be heated electrically or by heat exchange with a fluid.

The reductant source **20** can be any appropriate system for supplying the reductant. Hydrocarbons and oxygenated hydrocarbons can be stored in reservoirs and supplied as needed. Where ammonia is the reductant, the reductant source can be, for example, a reservoir of ammonia, ammonium carbamate, or urea. Ammonia can be generated on the vehicle by an ammonia plant that forms ammonia from H₂ and N₂ or from H₂ and NO. N₂ can be obtained from air and NO can be obtained from the adsorbers **12** and **13**. H₂ can be produced by a reformer. Ammonia, whatever its source, can

also be stored in adsorption beds, such as a molecular sieve adsorption beds, and desorbed as needed.

In one embodiment, the reductant is syn gas and the reductant source is a reformer together with purifiers and storage devices as appropriate. A reformer can convert fuel for the vehicle **10**, such as diesel, into syn gas. A reformer can be a catalytic reformer or a plasma reformer. A reformer can use oxygen and/or steam. The reformer can be vehicle mounted. The reformer output is generally hot, and can be channeled through the adsorbant beds to facilitate desorption.

It is preferably to use feedback control to determine the rate at which the reductant is supplied. A control system senses the concentration of NO_x, or some proxy therefore, downstream of the catalyst bed **22**. A temperature sensor for the catalyst bed **22** is also preferred. In one example, the temperature of the catalyst bed is initially sensed. If it is within its operating range, the reductant feed is increased until a point is reached where the NO_x concentration is at a target level or until a point where further increases in the reductant feed rate no longer reduce the NO_x concentration. Alternatively, the reductant concentration may be detected downstream of the catalyst bed **22** and the reductant feed rate increased until break-through of the reductant is detected or until the concentration of the reductant reaches a targeted level. More precise control schemes can be formulated based on measuring concentrations for both the reductant and NO_x.

The valves and associated conduits control the flow of exhaust and desorbed gases through adsorption and regeneration cycles. Conduits are inclusive of pipes and manifolds. The valves are generally actuated electronically under the control of a central processing unit. The central processing unit may serve other functions on the vehicle **10**.

The cycling of the adsorbers **12** and **13** can be controlled in any suitable fashion. In one example, an adsorber is put into a regeneration cycle based on detecting a maximum allowed concentration of NO_x in the exhaust downstream of the adsorber. In another example, the amount of NO_x adsorbed is estimated based on information regarding vehicle operating conditions such as speed, engine temperature, and torque. From such data, a reasonable estimate of the amount of NO_x emitted can be determined. Allowing a margin of error, the central processing unit can determine when it is time to regenerate an adsorber.

The provision of the catalyst bed **22** separate from the adsorbers **12** and **13** has advantages over systems in which reduction of NO_x takes place in the adsorption bed. One advantage is that a single catalyst charge can serve a plurality of NO_x adsorption beds. Another advantage is that the catalyst bed can be isolated from components of the exhaust that might deactivate or inhibit the catalyst. This permits the use of catalysts that are sensitive to water, oxygen, or sulfur, for example.

A further advantage of the invention is that the adsorbers can be operated at lower temperatures than adsorber-catalysts and other systems where the catalyst is in the main exhaust stream. In such systems, the adsorbers are kept warm to maintain catalyst activity. Lower temperature operation of the adsorbers is advantageous in that a greater loading of NO_x for a given adsorber mass can typically be obtained. As a result, the adsorbers can be smaller and less expensive. In one embodiment, either the exhaust is cooled or the adsorber is cooled whereby even when the vehicle is operating at steady state under load, the temperature at which the adsorbers routinely operate to remove NO_x is

about 200° C. or less, in another embodiment, about 150° C. or less, in a further embodiment about 100° C. or less.

One embodiment of the invention contemplates that the adsorbers will be replaced periodically due to poisoning, especially sulfur poisoning. In this embodiment, it is significant that replacing an adsorber is less expensive than replacing an adsorber-catalyst. In one embodiment, the adsorber is designed for replacement after driving a distance that is no more than about 60,000 miles, in another embodiment it is designed for replacement after driving a distance that is no more than about 40,000 miles, in a further embodiment it is designed for replacement after driving a distance that is no more than about 20,000 miles.

For the vehicle **10**, the temperature of the adsorbers **12** and **13** must be increased until the sum of the partial pressures of the adsorbates is sufficiently high to induce flow from the adsorbers **12** and **13** to the catalyst bed **22**. This generally means the sum of the partial pressures must exceed at least about one atmosphere, although a vacuum pump can be provided to draw the desorption product off the adsorbers **12** and **13**. The desorption partial pressure can also be reduced by channeling the reductant and/or a small amount of exhaust gas through the adsorbers.

FIG. **13** is a schematic illustration of a vehicle **100** in which desorption can occur at much lower partial pressures, permitting temperatures swings to be smaller and possibly eliminated altogether. The vehicle **100** includes adsorbers **101**, **102**, and **103**. Each of these adsorbers can be selectively placed in a recirculating loop that includes a catalyst bed **104**. Desorption will occur whenever the partial pressure in equilibrium with the adsorbant at its current loading level is lower than the partial pressure of the adsorbant in the recirculating gas.

Valves **105–110** control which of the adsorbers **101–103** is in a recirculating loop with the catalyst bed **104**. In FIG. **13**, valves **105–108** are closed and valves **100–110** are open, whereby only the adsorber **103** is in the recirculating loop. A fan **111** drives recirculation within the loop. Valve **112** is partially open and allows a fraction of the loop contents to be drawn off. Optionally, a vacuum pump can be installed downstream of valve **112** to enable the loop to operate below atmospheric pressure. Valve **113** controls the flow of a reductant from reductant source **114** into the loop.

The recirculating gas is optionally used to heat the adsorbers **101–103** to induce desorption. The gas can be heated anywhere in the recirculating stream. In the present example, the gas is heated by the catalyst bed **104**, which is in turn heated by hot exhaust. The conduits in the recirculating loop can be insulated to conserve heat.

The exhaust is produced by internal combustion engine **115** and flows through oxidation catalyst **116** before entering heat exchange with the catalyst bed **104**. The oxidation catalyst **116** is optional. An oxidation catalyst can serve to oxidize unburned hydrocarbons and CO and to convert NO to NO₂. NO₂ may be adsorbed more easily and may be reduced more easily, depending in part on the operation of the adsorbers **101–103** and the catalyst bed **104**. An oxidation catalyst may also increase the temperature of the exhaust, making it a better source of heat. In another embodiment, the oxidation catalyst **116** is replaced by a catalyst-free ceramic monolith or other low pressure-drop device that gives thermal inertia to the exhaust stream. Such a device can smooth out fluctuations in the exhaust gas temperature and make the exhaust gas a more stable source of heat.

After heating the catalyst bed **104**, the exhaust can be cooled in optional heat exchanger **117**. The heat exchanger

11

117 can use any cool fluid, including, for example, engine coolant or ambient air. Valves 118–120, in cooperation with valves 121–123, selectively admit the optionally cooled exhaust to the adsorbers 101–103. In FIG. 13, valve 121 is open while valves 122 and 123 are closed, whereby the main exhaust flow only enters the adsorber 101.

If the exhaust gas is sufficiently cool, and the adsorbers 101–103 are already cool at the beginning of the adsorption cycle, the adsorbers 101–103 may not need any additional cooling during adsorption. In the vehicle 100, the adsorbers are cooled with ambient air following desorption. Fan 121 drives ambient air, which is selectively admitted to the adsorbers 101–103 by valves 122–124. In FIG. 13, valve 123 is open while valves 122 and 124 are closed, whereby ambient air is driven into adsorber 102 only. The valve 122 is also open, whereby the ambient air leaves the adsorber and combines with treated exhaust. In the vehicle 100, ambient air used for cooling flows through the same passages as exhaust. Optionally, the adsorbers 101–103 can be configured with separate passages for heat exchange. The design in FIG. 13, however, has the advantage that the adsorbers require no separate provision for heat exchange other than valving, permitting the adsorbers to have a very simple design.

The recirculating loops of FIG. 13 are also applicable to combined adsorber-catalyst systems. In addition to providing a simple means of heating and cooling the adsorber-catalysts, the recirculating system allows greater conversion of NOx to be achieved with a given amount of catalyst. In one embodiment, the ratio between the recirculating flow rate and the flow rate of release from the recirculating system is at least about 2:1, preferably it is at least about 5:1, and more preferably it is at least about 10:1.

The invention has been shown and described with respect to certain aspects, examples, and embodiments. While a particular feature of the invention may have been disclosed with respect to only one of several aspects, examples, or embodiments, the feature may be combined with one or more other features of the other aspects, examples, or embodiments as may be advantageous for any given or particular application.

The invention claimed is:

1. A vehicle, comprising:

an internal combustion engine;

an NOx adsorber configured to receive exhaust from the internal combustion engine;

a catalyst bed configured to receive gas desorbed from the NOx adsorber, the catalyst bed comprising a catalyst for a reaction between NO and a reductant selected from the group consisting of synthesis gas products, ammonia, hydrocarbons, and oxygenated hydrocarbons, wherein the reaction reduces NO to give N₂; and valves and conduits configured to selectively channel exhaust from the internal combustion engine through the NOx adsorber and out of the vehicle while bypassing the catalyst bed and being further configured to selectively interrupt the flow of exhaust from the internal combustion engine to the NOx adsorber while channeling the gas desorbed from the NOx adsorber to the catalyst bed.

2. The vehicle of claim 1, wherein the vehicle comprises a plurality of NOx adsorbers and the valves and conduits are configured to selectively channel the exhaust to each of the NOx adsorbers and selectively channel gas desorbed from each of the NOx adsorbers to the catalyst bed.

3. The vehicle of claim 1, further comprising a reformer configured to reform a fuel suitable for the internal com-

12

bustion engine into synthesis gas, wherein the vehicle is configured to provide the synthesis gas, or a product thereof, to the catalyst bed.

4. The vehicle of claim 1, wherein the catalyst comprises an effective amount of gold on a metal oxide support.

5. The vehicle of claim 1, wherein the NOx adsorber comprises an adsorption bed and a heating system selected from the group consisting of an electrical resistance heater and one or more heating fluid conduits in functional thermal communication but fluid isolation from the adsorption bed.

6. The vehicle of claim 1, wherein the NOx adsorber comprises a functional amount of a molecular sieve.

7. The vehicle of claim 1, further comprising an oxidation catalyst positioned to oxidize NO in the exhaust to NO₂ prior to the exhaust entering the NOx adsorber.

8. The vehicle of claim 1, further comprising valves and conduits configured to selectively channel ambient air through the NOx adsorber to cool the NOx adsorber.

9. The vehicle of claim 1, further comprising a heat exchanger configured to cool the exhaust to about 200° C. or less prior to entering the NOx adsorber.

10. The vehicle of claim 1, wherein the NOx adsorber is configured to maintain an operating temperature for adsorption at or below about 200° C. through fluid heat exchange.

11. The vehicle of claim 1, further comprising a vacuum pump configured to selectively draw a vacuum on the NOx adsorber.

12. The vehicle of claim 1, wherein the catalyst bed is configured for heating by the exhaust.

13. The vehicle of claim 1, further comprising valves and conduits configured to selectively recirculate gas between the NOx adsorber and the catalyst bed.

14. The vehicle of claim 13, further comprising a fan to drive the recirculation.

15. The vehicle of claim 13, further comprising a heating system configured to heat recirculating gas, the heating system having a structure selected from the group consisting of electrical resistance heaters and fluid heat exchangers, the heating system being located outside the NOx adsorber and functional to heat the NOx adsorber through the medium of the recirculating gas.

16. A vehicle, comprising:

an internal combustion engine producing exhaust during operation;

an NOx adsorber having channels for the exhaust and configured to receive the exhaust from the internal combustion engine;

valves and conduits being configured to channel exhaust from the internal combustion engine through the NOx adsorber and out of the vehicle during an adsorption cycle and being further configured to interrupt the flow of exhaust from the internal combustion engine to the NOx adsorber and, in conjunction with a fan, recirculate gas through the NOx adsorber during a regeneration cycle;

valves and conduits configured to selectively channel ambient air through the NOx adsorber during a cooling cycle.

17. A vehicle, comprising:

an internal combustion engine producing exhaust during operation;

an NOx adsorber having channels for the exhaust and configured to receive the exhaust from the internal combustion engine;

valves and conduits being configured to channel exhaust from the internal combustion engine through the NOx adsorber and out of the vehicle during an adsorption

13

cycle and being further configured to interrupt the flow of exhaust from the internal combustion engine to the NOx adsorber and, in conjunction with a fan, recirculate gas through the NOx adsorber during a regeneration cycle;

a heating system configured to heat recirculating gas, the heating system having a structure selected from the group consisting of electrical resistance heaters and fluid heat exchangers, the heating system being located outside the NOx adsorber and functional to heat the NOx adsorber through the medium of the recirculating gas.

18. A method of reducing the amount of NOx in the exhaust of a vehicle, comprising:

14

passing the exhaust over a first NOx adsorption bed; substantially isolating the bed from the exhaust; heating the adsorption bed to desorb NOx;

combining the desorbed NOx with a reductant selected from the group consisting of synthesis gas products, ammonia, hydrocarbons, and oxygenated hydrocarbons to form a gas mixture;

passing the gas mixture over a catalyst to induce a reaction that reduces NOx to N₂

further comprising cooling the first NOx adsorption bed following desorption by flowing ambient air through the bed.

* * * * *