



US010267390B2

(12) **United States Patent**
Morrow et al.

(10) **Patent No.:** **US 10,267,390 B2**

(45) **Date of Patent:** **Apr. 23, 2019**

(54) **MULTI-MODE ELECTROMECHANICAL VARIABLE TRANSMISSION**

(58) **Field of Classification Search**

None

See application file for complete search history.

(71) Applicant: **Oshkosh Corporation**, Oshkosh, WI (US)

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,411,171 A 10/1983 Fiala
4,719,361 A 1/1988 Brubaker
(Continued)

FOREIGN PATENT DOCUMENTS

CN 101323243 A 12/2008
CN 107405990 11/2017
(Continued)

OTHER PUBLICATIONS

Diesel Locomotive Technology, <http://www.railway-technical.com/diesel.shtml>, available by Jan. 24, 2012, 15 pages.

(Continued)

Primary Examiner — Jacob S. Scott

(74) *Attorney, Agent, or Firm* — Foley & Lardner LLP

(57)

ABSTRACT

A drive system includes a first gear set and a second gear set, each including a sun gear, a ring gear, a plurality of planetary gears coupling the sun gear to the ring gear, and a carrier rotationally supporting the plurality of planetary gears, a first electrical machine coupled to the sun gear of the first gear set, a second electrical machine coupled to the sun gear of the second gear set, a connecting shaft coupled to the ring gear of the first gear set, a driveshaft that transports power from the electrical machines to a tractive element, a first clutch selectively rotationally coupling the first carrier and the second carrier to the driveshaft, and at least one of a second clutch selectively rotationally coupling the second electrical machine to the connecting shaft and a third clutch selectively rotationally coupling the second gear set to the driveshaft.

21 Claims, 10 Drawing Sheets

(73) Assignee: **Oshkosh Corporation**, Oshkosh, WI (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **15/978,994**

(22) Filed: **May 14, 2018**

(65) **Prior Publication Data**

US 2018/0259042 A1 Sep. 13, 2018

Related U.S. Application Data

(63) Continuation of application No. 15/595,443, filed on May 15, 2017, now Pat. No. 9,970,515, which is a (Continued)

(51) **Int. Cl.**

B60K 6/38 (2007.10)


F16H 3/72 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC **F16H 3/727** (2013.01); **B60K 6/365** (2013.01); **B60K 6/387** (2013.01); **B60K 6/442** (2013.01);

(Continued)



Related U.S. Application Data

continuation of application No. 14/624,285, filed on
Feb. 17, 2015, now Pat. No. 9,651,120.

(51) Int. Cl.

B60K 6/365 (2007.10)
B60K 6/445 (2007.10)
F16H 37/02 (2006.01)
F16H 37/08 (2006.01)
B60K 6/442 (2007.10)
B60K 6/387 (2007.10)

(52) U.S. Cl.

CPC **B60K 6/445** (2013.01); **F16H 3/728**
(2013.01); **B60K 2006/381** (2013.01); **F16H**
37/02 (2013.01); **F16H 37/084** (2013.01);
F16H 2037/0866 (2013.01); **F16H 2037/0873**
(2013.01); **F16H 2200/20** (2013.01); **F16H**
2200/2002 (2013.01); **F16H 2200/203**
(2013.01); **F16H 2200/2007** (2013.01); **F16H**
2200/2043 (2013.01); **Y02T 10/6239**
(2013.01); **Y10S 903/917** (2013.01)

(56)**References Cited**

U.S. PATENT DOCUMENTS

5,120,282	A	6/1992	Fjaellstroem	7,204,776	B2	4/2007	Minagawa et al.
5,498,208	A	3/1996	Braun	7,217,211	B2	5/2007	Klemen et al.
5,501,567	A	3/1996	Lanzdorf et al.	7,219,756	B2	5/2007	Bischoff
5,607,028	A	3/1997	Braun et al.	7,223,200	B2	5/2007	Kojima et al.
5,669,842	A	9/1997	Schmidt	7,246,672	B2	7/2007	Shirai et al.
5,722,502	A	3/1998	Kubo	7,258,194	B2	8/2007	Braun et al.
5,786,640	A	7/1998	Sakai et al.	7,276,007	B2	10/2007	Takami et al.
5,789,882	A	8/1998	Ibaraki et al.	7,277,782	B2	10/2007	Yakes et al.
5,820,150	A	10/1998	Archer et al.	7,322,896	B2	1/2008	Minagawa
5,820,258	A	10/1998	Braun	7,338,401	B2	3/2008	Klemen et al.
5,895,333	A	4/1999	Morisawa et al.	7,357,203	B2	4/2008	Morrow et al.
5,927,417	A	7/1999	Brunner et al.	7,367,415	B2	5/2008	Oliver et al.
5,934,395	A	8/1999	Koide et al.	7,419,021	B2	9/2008	Morrow et al.
6,086,074	A	7/2000	Braun	7,448,460	B2	11/2008	Morrow et al.
6,105,984	A	8/2000	Schmitz et al.	7,467,678	B2	12/2008	Tanaka et al.
6,356,817	B1	3/2002	Abe	7,479,080	B2	1/2009	Usono
6,371,878	B1	4/2002	Bowen	7,520,354	B2	4/2009	Morrow et al.
6,478,705	B1	11/2002	Holmes et al.	7,527,573	B2	5/2009	Lang et al.
6,516,914	B1	2/2003	Andersen et al.	7,572,201	B2	8/2009	Supina et al.
6,553,287	B1	4/2003	Supina et al.	7,597,164	B2	10/2009	Severinsky et al.
6,561,718	B1	5/2003	Archer et al.	7,601,093	B2	10/2009	Tabata et al.
6,575,866	B2	6/2003	Bowen	7,635,039	B2	12/2009	Fujiwara et al.
6,607,466	B2	8/2003	Bordini	7,678,014	B2	3/2010	Nohara et al.
6,702,709	B2	3/2004	Bowen	7,689,332	B2	3/2010	Yakes et al.
6,726,592	B2	4/2004	Kotani	7,711,460	B2	5/2010	Yakes et al.
6,757,597	B2	6/2004	Yakes et al.	7,749,131	B2	7/2010	Imamura et al.
6,764,085	B1	7/2004	Anderson	7,811,191	B2	10/2010	Iwase et al.
6,793,600	B2	9/2004	Hiraiwa	7,824,293	B2	11/2010	Schimke
6,819,985	B2	11/2004	Minagawa et al.	7,874,373	B2	1/2011	Morrow et al.
6,846,257	B2	1/2005	Baker et al.	7,878,750	B2	2/2011	Zhou et al.
6,852,053	B2	2/2005	Nakano et al.	7,888,894	B2	2/2011	Sugawara et al.
6,852,054	B2	2/2005	Tumback et al.	7,908,063	B2	3/2011	Sah
6,885,920	B2	4/2005	Yakes et al.	7,927,250	B2	4/2011	Imamura et al.
6,886,647	B1	5/2005	Gotta	7,931,103	B2	4/2011	Morrow et al.
6,991,054	B2	1/2006	Takaoka et al.	7,935,021	B2	5/2011	Tabata et al.
6,994,646	B2	2/2006	Ai	7,935,022	B2	5/2011	Iwase et al.
7,000,717	B2	2/2006	Ai et al.	7,941,259	B2	5/2011	Tabata et al.
7,004,868	B2	2/2006	Oshidari et al.	7,972,237	B2	7/2011	Ota
7,053,566	B2	5/2006	Aizawa et al.	8,007,402	B2	8/2011	Tabata et al.
7,073,620	B2	7/2006	Braun et al.	8,038,572	B2	10/2011	Matsubara et al.
7,073,847	B2	7/2006	Morrow et al.	8,062,172	B2	11/2011	Supina et al.
7,076,356	B2	7/2006	Hubbard et al.	8,091,662	B2	1/2012	Tolksdorf
7,140,461	B2	11/2006	Morrow	8,123,645	B2	2/2012	Schimke
7,154,236	B1	12/2006	Heap	8,231,491	B2	7/2012	Oba et al.
7,164,977	B2	1/2007	Yakes et al.	8,337,352	B2	12/2012	Morrow et al.
7,179,187	B2	2/2007	Raghavan et al.	8,561,735	B2	10/2013	Morrow et al.
7,192,373	B2	3/2007	Bucknor et al.	8,801,318	B2	8/2014	Knoble et al.
7,196,430	B2	3/2007	Yang	8,864,613	B2	10/2014	Morrow et al.
				9,114,699	B2	8/2015	Takei et al.
				9,114,804	B1	8/2015	Shukla et al.
				9,132,736	B1	9/2015	Shukla et al.
				9,428,042	B2	8/2016	Morrow et al.
				9,452,750	B2	9/2016	Shukla et al.
				9,492,695	B2	11/2016	Betz et al.
				9,580,962	B2	2/2017	Betz et al.
				9,650,032	B2	5/2017	Kotlowski et al.
				9,651,120	B2	5/2017	Morrow et al.
				9,656,659	B2	5/2017	Shukla et al.
				9,677,334	B2	6/2017	Aiken et al.
				9,908,520	B2	3/2018	Shukla et al.
				9,970,515	B2	5/2018	Morrow et al.
				10,029,555	B2	7/2018	Kotloski et al.
				2005/0234622	A1	10/2005	Pillar et al.
				2006/0223663	A1	10/2006	Bucknor et al.
				2006/0276288	A1	12/2006	Iwanaka et al.
				2007/0105678	A1	5/2007	Bucknor et al.
				2008/0150350	A1	6/2008	Morrow et al.
				2009/0194347	A1	8/2009	Morrow et al.
				2009/0209381	A1	8/2009	Ai et al.
				2009/0221390	A1	9/2009	Houle
				2009/0227409	A1	9/2009	Ito et al.
				2009/0227417	A1	9/2009	Imamura et al.
				2009/0275437	A1	11/2009	Kersting
				2010/0051361	A1	3/2010	Katsuta et al.
				2010/0051367	A1	3/2010	Yamada et al.
				2010/0120579	A1	5/2010	Kawasaki
				2010/0138086	A1	6/2010	Imamura et al.
				2010/0145589	A1	6/2010	Kobayashi
				2010/0227722	A1	9/2010	Conlon

(56)

References Cited

U.S. PATENT DOCUMENTS

2010/0261565	A1	10/2010	Ai et al.
2010/0301668	A1	12/2010	Yakes et al.
2010/0326752	A1	12/2010	Lamperth
2011/0319211	A1	12/2011	Si
2012/0022737	A1	1/2012	Kumazaki et al.
2013/0196806	A1	8/2013	Morrow et al.
2013/0260936	A1	10/2013	Takei et al.
2014/0269145	A1	9/2014	Fasana et al.
2014/0350803	A1	11/2014	Ye et al.
2015/0246331	A1	9/2015	Broker et al.
2015/0283894	A1	10/2015	Morrow et al.
2016/0133557	A1	5/2016	Mortensen et al.
2016/0288780	A1	10/2016	Shukla et al.
2016/0311253	A1	10/2016	Palmer et al.
2016/0361987	A1	12/2016	Morrow et al.
2017/0008507	A1	1/2017	Shukla et al.
2017/0108085	A1	4/2017	Morrow et al.
2017/0246946	A1	8/2017	Morrow et al.
2017/0246947	A1	8/2017	Kotloski et al.
2017/0253229	A1	9/2017	Shukla et al.
2017/0370446	A1	12/2017	Steinberger et al.
2018/0023671	A1	1/2018	Watt et al.
2018/0023672	A1	1/2018	Watt et al.
2018/0031085	A1	2/2018	Steinberger et al.

FOREIGN PATENT DOCUMENTS

DE	10 2011 109 352	2/2013
EP	1 229 636 A2	8/2002
GB	2 400 588	1/2005

GB	2 400 589	2/2005
GB	2 400 590	3/2005
JP	2010-070008 A	4/2010
WO	WO-03/055714 A1	7/2003
WO	WO-03/093046 A2	11/2003
WO	WO-2004/083081	9/2004
WO	WO-2004/110849	12/2004
WO	WO-2006/028452	3/2006
WO	WO-2006/037041	4/2006
WO	WO-2006/037098	4/2006
WO	WO-2006/037099	4/2006
WO	WO-2007/108805	9/2007
WO	WO-2011/041549	4/2011
WO	WO-2011/163135	12/2011
WO	WO-2016/133557	8/2016
WO	WO-2016/172250	10/2016
WO	WO-2017/007599	1/2017
WO	WO-2017/007600	1/2017
WO	WO-2017/070388	4/2017
WO	WO-2017/106410 A1	6/2017

OTHER PUBLICATIONS

Miller, Hybrid Electric Vehicle Propulsion System Architectures of the e-CVT Type, IEEE Transactions on Power Electronics, vol. 21, No. 3, May 2006, 12 pages.

International Search Report and Written Opinion Received for PCT Application No. PCT/US2018/053983, Oshkosh Corporation, Jan. 3, 2019, 18 pages.

International Search Report and Written Opinion, Oshkosh Corporation, PCT/US2018/049158, Dec. 13, 2018, 138 pages.

International Search Report and Written Opinion, Oshkosh Corporation, PCT/US2018/049550, Dec. 13, 2018, 116 pages.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 7




FIG. 8




FIG. 9




FIG. 10

MULTI-MODE ELECTROMECHANICAL VARIABLE TRANSMISSION

CROSS-REFERENCE TO RELATED PATENT APPLICATIONS

This application is a continuation of U.S. application Ser. No. 15/595,443, filed May 15, 2017, which is a continuation of U.S. application Ser. No. 14/624,285, filed Feb. 17, 2015, now U.S. Pat. No. 9,651,120, both of which are incorporated herein by reference in their entireties.

BACKGROUND

Internal combustion engine vehicles, hybrid vehicles, and electric vehicles, among other types of vehicles, include transmissions. Traditional vehicle transmissions use gears and gear trains to provide speed and torque conversions from a rotating power source (e.g., an engine, a motor, etc.) to another device (e.g., a drive shaft, wheels of a vehicle, etc.). Transmissions include multiple gear ratios selectively coupled to the rotating power source with a mechanism that may also selectively couple an output to the various gear ratios.

SUMMARY

One exemplary embodiment relates to a drive system for a vehicle. The drive system includes a first gear set including a first sun gear, a first ring gear, a first plurality of planetary gears coupling the first sun gear to the first ring gear, and a first carrier rotationally supporting the first plurality of planetary gears and a second gear set including a second sun gear, a second ring gear, a second plurality of planetary gears coupling the second sun gear to the second ring gear, and a second carrier rotationally supporting the second plurality of planetary gears. The first carrier is directly coupled to the second carrier. The drive system further includes a first electrical machine directly coupled to the first sun gear of the first gear set, a second electrical machine directly coupled to the second sun gear of the second gear set, a connecting shaft coupled to the first ring gear of the first gear set, a driveshaft configured to transport power from the first electrical machine and the second electrical machine to a tractive element of the vehicle, a first clutch selectively rotationally coupling the first carrier and the second carrier to the driveshaft when engaged, and at least one of a second clutch selectively rotationally coupling the second electrical machine to the connecting shaft when engaged and a third clutch selectively rotationally coupling the second gear set to the driveshaft when engaged.

Another exemplary embodiment relates to a drive system for a vehicle. The drive system includes a first planetary gear set, a second planetary gear set directly coupled to the first planetary gear set, a connecting shaft coupled to the first planetary gear set, a first electromagnetic device coupled to the first planetary gear set and including a first shaft, a second electromagnetic device coupled to the second planetary gear set, selectively rotationally engaged with the connecting shaft, and including a second shaft, and an output selectively coupled to the first planetary gear set and the second planetary gear set. The first planetary gear set, the second planetary gear set, and the connecting shaft are radially aligned. The first shaft and the second shaft are radially aligned with the first planetary gear set, the second planetary gear set, and the connecting shaft. The connecting shaft extends through the second electromagnetic device and

through the second planetary gear set to the first planetary gear set. The output is radially offset from the first planetary gear set, the second planetary gear set, and the connecting shaft.

Another exemplary embodiment relates to a vehicle including a multi-mode transmission. The multi-mode transmission includes a first gear set having a first planetary gear carrier, a second gear set having a second planetary gear carrier, a first motor/generator coupled to the first gear set, and a second motor/generator coupled to the second gear set. The first planetary gear carrier and the second planetary gear carrier are rotatably coupled. A connecting shaft is selectively coupled to the second gear set, and a drive axle is selectively coupled to the multi-mode transmission. During a first mode of the multi-mode transmission the connecting shaft is coupled to the second motor/generator and decoupled from the drive axle. During a second mode of the multi-mode transmission the connecting shaft is decoupled from the second motor/generator, the second motor/generator is selectively coupled to the drive axle, and the connecting shaft is coupled to the first motor/generator.

The invention is capable of other embodiments and of being carried out in various ways. Alternative exemplary embodiments relate to other features and combinations of features as may be recited herein.

BRIEF DESCRIPTION OF THE DRAWINGS

The disclosure will become more fully understood from the following detailed description, taken in conjunction with the accompanying figures, wherein like reference numerals refer to like elements, in which:

FIG. 1 is a schematic view of a drive train for a vehicle, according to an exemplary embodiment;

FIG. 2 is a detailed schematic view of the drive train of FIG. 1, according to an exemplary embodiment;

FIG. 3 is a schematic diagram of a control system for the drive train of FIG. 1, according to an exemplary embodiment.

FIG. 4 is a detailed schematic view of a drive train configured in a neutral startup mode of operation, according to an exemplary embodiment;

FIG. 5 is a detailed schematic view of a drive train configured in a power generation mode of operation, according to an exemplary embodiment;

FIG. 6 is a detailed schematic view of a drive train configured in a low range mode of operation, according to an exemplary embodiment;

FIG. 7 is a detailed schematic view of a drive train configured in a mid range mode of operation, according to an exemplary embodiment;

FIG. 8 is a detailed schematic view of a drive train configured in a high range mode of operation, according to an exemplary embodiment;

FIG. 9 is a detailed schematic view of a drive train configured in a low speed reverse mode of operation, according to an exemplary embodiment; and

FIG. 10 is a detailed schematic view of a drive train configured in a high speed reverse mode of operation, according to an exemplary embodiment.

DETAILED DESCRIPTION

Before turning to the figures, which illustrate the exemplary embodiments in detail, it should be understood that the present application is not limited to the details or methodology set forth in the description or illustrated in the figures.

It should also be understood that the terminology is for the purpose of description only and should not be regarded as limiting.

According to an exemplary embodiment, a multi-mode electromechanical variable transmission is provided as part of a vehicle and is selectively reconfigurable into one of a plurality of operating modes. The vehicle may also include an engine, a first electromagnetic device, and second electromagnetic device. In one embodiment, at least one of the first electromagnetic device and the second electromagnetic device provides rotational mechanical energy to start the engine. In another embodiment, the engine provides a rotational mechanical energy input to both the first and second electromagnetic devices such that each operates as a generator to generate electrical energy. In still other embodiments, one of the first electromagnetic device and the second electromagnetic device are configured to receive a rotational mechanical energy output from at least one of the engine and the multi-mode electromechanical variable transmission and provide an electrical energy output to power a control system and/or the other electromagnetic device.

According to the exemplary embodiment shown in FIGS. 1-2, a vehicle 10 includes an engine 20 coupled to a transmission, shown as transmission 30. In one embodiment, engine 20 is configured to combust fuel and provide a mechanical energy input to transmission 30. By way of example, engine 20 may be configured to provide a rotational mechanical energy input to transmission 30. As shown in FIGS. 1-2, a first electrical machine, electromagnetic device and/or motor/generator, shown as first electromagnetic device 40, and a second electrical machine, electromagnetic device and/or motor/generator, shown as second electromagnetic device 50, are coupled to transmission 30.

Referring again to the exemplary embodiment shown in FIG. 1, vehicle 10 includes a front axle, shown as front axle 60, and a rear axle, shown as rear axle 70. As shown in FIG. 1, front axle 60 includes a pair of tractive elements, shown as tires 62, coupled to a front differential, shown as front differential 64. Rear axle 70 includes a pair of tractive elements, shown as tires 72, coupled to a rear differential, shown as rear differential 74, according to an exemplary embodiment. According to the exemplary embodiment shown in FIG. 1, front differential 64 is coupled to transmission 30 with a front axle driveshaft 66 and rear differential 74 is coupled to transmission 30 with a rear axle driveshaft 76. While shown as coupled to tires 62 and tires 72, front differential 64 and rear differential 74 may be coupled to various other types of tractive elements (e.g., tracks, etc.), according to alternative embodiments. As shown in FIG. 1, front axle driveshaft 66 and rear axle driveshaft 76 are configured to transport power from first electromagnetic device 40, second electromagnetic device 50, and engine 20 to tires 62 and tires 72, respectively. Vehicle 10 may include a plurality of front differentials 64 that may be coupled or a plurality of rear differentials 74 that may be coupled, according to various alternative embodiments.

Engine 20 may be any source of rotational mechanical energy that is derived from a stored energy source. The stored energy source is disposed onboard vehicle 10, according to an exemplary embodiment. The stored energy source may include a liquid fuel or a gaseous fuel, among other alternatives. In one embodiment, engine 20 includes an internal combustion engine configured to be powered by at least one of gasoline, natural gas, and diesel fuel. According to various alternative embodiments, engine 20 includes at least one of a turbine, a fuel cell, an electric motor or still

another device. According to one exemplary embodiment, engine 20 includes a twelve liter diesel engine capable of providing between approximately 400 horsepower and approximately 600 horsepower and between approximately 400 foot pounds of torque and approximately 2000 foot pounds of torque. In one embodiment, engine 20 has a rotational speed (e.g., a rotational operational range, etc.) of between 0 and 2,100 revolutions per minute. Engine 20 may be operated at a relatively constant speed (e.g., 1,600 revolutions per minute, etc.). In one embodiment, the relatively constant speed is selected based on an operating condition of engine 20 (e.g., an operating speed relating to a point of increased fuel efficiency, etc.).

In one embodiment, at least one of first electromagnetic device 40 and second electromagnetic device 50 provide a mechanical energy input to transmission 30. By way of example, at least one of first electromagnetic device 40 and second electromagnetic device 50 may be configured to provide a rotational mechanical energy input to transmission 30 (i.e., at least one of first electromagnetic device 40 and second electromagnetic device 50 may operate as a motor, etc.). At least one of first electromagnetic device 40 and second electromagnetic device 50 may receive a mechanical energy output from at least one of engine 20 and transmission 30. By way of example, at least one of first electromagnetic device 40 and second electromagnetic device 50 may be configured to receive a rotational mechanical energy output from at least one of engine 20 and transmission 30 and provide an electrical energy output (i.e., at least one of first electromagnetic device 40 and second electromagnetic device 50 may operate as a generator, etc.). According to an exemplary embodiment, first electromagnetic device 40 and second electromagnetic device 50 are capable of both providing mechanical energy and converting a mechanical energy input into an electrical energy output (i.e., operate as a motor and a generator, etc.). The operational condition of first electromagnetic device 40 and second electromagnetic device 50 (e.g., as a motor, as a generator, etc.) may vary based on a mode of operation associated with transmission 30.

According to the exemplary embodiment shown in FIG. 2, a drive system for a vehicle, shown as drive system 100, includes engine 20, transmission 30, first electromagnetic device 40, second electromagnetic device 50, front axle driveshaft 66, and rear axle driveshaft 76. As shown in FIG. 2, transmission 30 includes a first gear set, shown as power split planetary 110, and a second gear set, shown as output planetary 120. In one embodiment, power split planetary 110 and output planetary 120 are disposed between first electromagnetic device 40 and second electromagnetic device 50. In an alternative embodiment, one or both of power split planetary 110 and output planetary 120 are positioned outside of (i.e., not between, etc.) first electromagnetic device 40 and second electromagnetic device 50. As shown in FIG. 2, power split planetary 110 is directly coupled to engine 20.

Referring to the exemplary embodiment shown in FIG. 2, power split planetary 110 is a planetary gear set that includes a sun gear 112, a ring gear 114, and a plurality of planetary gears 116. The plurality of planetary gears 116 couple sun gear 112 to ring gear 114, according to an exemplary embodiment. As shown in FIG. 2, a carrier 118 rotationally supports the plurality of planetary gears 116. In one embodiment, first electromagnetic device 40 is directly coupled to sun gear 112 such that power split planetary 110 is coupled to first electromagnetic device 40. By way of example, first

electromagnetic device **40** may include a shaft (e.g., a first shaft, an input shaft, an output shaft, etc.) directly coupled to sun gear **112**.

Referring still to the exemplary embodiment shown in FIG. 2, output planetary **120** is a planetary gear set that includes a sun gear **122**, a ring gear **124**, and a plurality of planetary gears **126**. The plurality of planetary gears **126** couple sun gear **122** to ring gear **124**, according to an exemplary embodiment. As shown in FIG. 2, a carrier **128** rotationally supports the plurality of planetary gears **126**. In one embodiment, second electromagnetic device **50** is directly coupled to sun gear **122** such that output planetary **120** is coupled to second electromagnetic device **50**. By way of example, second electromagnetic device **50** may include a shaft (e.g., a second shaft, an input shaft, an output shaft, etc.) directly coupled to sun gear **122**. Carrier **118** is directly coupled to carrier **128**, thereby coupling power split planetary **110** to output planetary **120**, according to the exemplary embodiment shown in FIG. 2. In one embodiment, directly coupling carrier **118** to carrier **128** synchronizes rotational speeds of carrier **118** and carrier **128**.

According to an exemplary embodiment, transmission **30** includes a first clutch, shown as power split coupled clutch **130**. In one embodiment, power split coupled clutch **130** is positioned downstream of power split planetary **110** (e.g., between power split planetary **110** and front axle driveshaft **66** or rear axle driveshaft **76**, etc.). In an alternative embodiment, power split coupled clutch **130** is directly coupled to engine **20**. As shown in FIG. 2, power split coupled clutch **130** is positioned to selectively couple power split planetary **110** and output planetary **120** with a shaft, shown as output shaft **32**. In one embodiment, power split coupled clutch **130** allows a vehicle to be towed without spinning the gears within transmission **30** (e.g., power split planetary **110**, output planetary **120**, etc.). Output shaft **32** may be coupled to rear axle driveshaft **76** and selectively coupled to front axle driveshaft with a declutch assembly, shown as front declutch collar shift **34**. Front declutch collar shift **34** may be engaged and disengaged to selectively couple front axle driveshaft **66** to output shaft **32** of transmission **30** (e.g., to facilitate operation of a vehicle in a rear-wheel-drive-only mode, an all-wheel-drive mode, a four-wheel-drive mode, etc.).

As shown in FIG. 2, transmission **30** includes a second clutch, shown as input coupled clutch **140**. Input coupled clutch **140** is positioned to selectively couple second electromagnetic device **50** with engine **20**, according to an exemplary embodiment. Input coupled clutch **140** may thereby selectively couple engine **20** to output planetary **120**. As shown in FIG. 2, transmission **30** includes a shaft, shown as connecting shaft **36**. According to an exemplary embodiment, connecting shaft **36** extends from engine **20**, through second electromagnetic device **50**, and through output planetary **120** to power split planetary **110**. Connecting shaft **36** couples engine **20** with power split planetary **110**, according to the exemplary embodiment shown in FIG. 2. In one embodiment, connecting shaft **36** directly couples engine **20** with ring gear **114** of power split planetary **110**. Input coupled clutch **140** may selectively couple second electromagnetic device **50** with connecting shaft **36**. According to an exemplary embodiment, the shaft (e.g., input/output shaft, etc.) of first electromagnetic device **40** and the shaft (e.g., input/output shaft, etc.) of second electromagnetic device **50** are radially aligned with power split planetary **110**, output planetary **120**, and connecting shaft **36** (e.g., centerlines thereof are aligned, etc.). As shown in FIG. 2, transmission **30** includes a third clutch, shown as output

coupled clutch **150**. Output coupled clutch **150** is positioned to selectively couple output planetary **120** with output shaft **32**, according to an exemplary embodiment. In one embodiment, output shaft **32** is radially offset from power split planetary **110**, output planetary **120**, and connecting shaft **36** (e.g., radially offset from centerlines thereof, etc.).

Referring again to the exemplary embodiment shown in FIG. 2, transmission **30** includes a first brake, shown as power split brake **160**. As shown in FIG. 2, power split brake **160** is positioned to selectively inhibit the movement of at least a portion of power split planetary **110** (e.g., planetary gears **116**, carrier **118**, etc.) and output planetary **120** (e.g., planetary gears **126**, carrier **128**, etc.). In other embodiments, transmission **30** does not include power split brake **160**. Power split brake **160** may thereby be an optional component of transmission **30**. According to an exemplary embodiment, transmission **30** includes a second brake (or a first brake in embodiments where transmission **30** does not include power split brake **160**), shown as output brake **170**. Output brake **170** is positioned to selectively inhibit the movement of at least a portion of output planetary **120** (e.g., ring gear **124**, etc.), according to an exemplary embodiment. In one embodiment, at least one of power split brake **160** and output brake **170** are biased into an engaged position (e.g., with a spring, etc.) and selectively disengaged (e.g., with application of pressurized hydraulic fluid, etc.). In other embodiments, power split brake **160** and output brake **170** are hydraulically-biased and spring released. In still other embodiments, the components of transmission **30** are still otherwise engaged and disengaged (e.g., pneumatically, etc.). By way of example, output brake **170** and output coupled clutch **150** may be engaged simultaneously to function as a driveline brake (e.g., a braking mechanism to slow down a vehicle, etc.). By way of another example, power split brake **160** and power split coupled clutch **130** may be engaged simultaneously to function as a driveline brake.

As shown in FIG. 2, transmission **30** includes a gear set **180** that couples carrier **118** and carrier **128** to output shaft **32**. In one embodiment, gear set **180** includes a first gear, shown as gear **182**, in meshing engagement with a second gear, shown as gear **184**. As shown in FIG. 2, gear **182** is rotatably coupled to carrier **118** and carrier **128**. By way of example, gear **182** may be fixed to a component (e.g., shaft, tube, etc.) that couples carrier **118** and carrier **128**. As shown in FIG. 2, power split coupled clutch **130** is positioned to selectively couple gear **184** with output shaft **32** when engaged. With power split coupled clutch **130** disengaged, relative movement (e.g., rotation, etc.) may occur between gear **184** and output shaft **32**. Power split brake **160** may be positioned to selectively limit the movement of gear **184** when engaged to thereby limit the movement of gear **182**, carrier **118**, and carrier **128**.

According to an exemplary embodiment, transmission **30** includes a gear set, shown as gear set **190**, that couples output planetary **120** to output shaft **32**. As shown in FIG. 2, gear set **190** includes a first gear, shown as gear **192**, coupled to ring gear **124** of output planetary **120**. Gear **192** is in meshing engagement with a second gear, shown as gear **194**, according to an exemplary embodiment. As shown in FIG. 2, gear **194** is coupled to a third gear, shown as gear **196**. In other embodiments, gear **192** is directly coupled with gear **196**. By way of example, gear set **190** may not include gear **194**, and gear **192** may be directly coupled to (e.g., in meshing engagement with, etc.) gear **196**. As shown in FIG. 2, output coupled clutch **150** is positioned to selectively couple gear **196** with output shaft **32** when engaged. With

output coupled clutch 150 disengaged, relative movement (e.g., rotation, etc.) may occur between gear 196 and output shaft 32. By way of example, output coupled clutch 150 may be engaged to couple ring gear 124 to output shaft 32. Output brake 170 is positioned to selectively limit the movement of gear 192 when engaged to thereby also limit the movement of ring gear 124, gear 194, and gear 196.

According to the exemplary embodiment shown in FIG. 3, a control system 200 for a vehicle includes a controller 210. In one embodiment, controller 210 is configured to selectively engage, selectively disengage, or otherwise communicate with components of the vehicle according to various modes of operation. As shown in FIG. 3, controller 210 is coupled to engine 20. In one embodiment, controller 210 is configured to selectively engage engine 20 (e.g., interface with a throttle of, etc.) such that an output of engine 20 spins at a target rate. Controller 210 is coupled to first electromagnetic device 40 and second electromagnetic device 50, according to an exemplary embodiment, and may send and receive signals therewith. By way of example, controller 210 may send command signals relating to at least one of a target rotational speed and a target rotation direction for first electromagnetic device 40 and second electromagnetic device 50. As shown in FIG. 3, first electromagnetic device 40 and second electromagnetic device 50 are electrically coupled. By way of example, power generated by first electromagnetic device 40 may be utilized by second electromagnetic device 50 (e.g., to provide an output torque as a motor, etc.), or power generated by second electromagnetic device 50 may be utilized by first electromagnetic device 40 (e.g., to provide an output torque as a motor, etc.).

According to the exemplary embodiment shown in FIG. 3, control system 200 includes a user interface 220 that is coupled to controller 210. In one embodiment, user interface 220 includes a display and an operator input. The display may be configured to display a graphical user interface, an image, an icon, or still other information. In one embodiment, the display includes a graphical user interface configured to provide general information about the vehicle (e.g., vehicle speed, fuel level, warning lights, etc.). The graphical user interface may also be configured to display a current mode of operation, various potential modes of operation, or still other information relating to transmission 30 or drive system 100. By way of example, the graphical user interface may be configured to provide specific information regarding the operation of drive system 100 (e.g., whether power split coupled clutch 130, input coupled clutch 140, output coupled clutch 150, power split brake 160, and output brake 170 are engaged or disengaged, a fault condition where at least one of power split coupled clutch 130, input coupled clutch 140, output coupled clutch 150, power split brake 160, and output brake 170 fail to engage or disengage in response to a command signal, etc.).

The operator input may be used by an operator to provide commands to at least one of engine 20, transmission 30, first electromagnetic device 40, second electromagnetic device 50, and drive system 100 or still another component of the vehicle. The operator input may include one or more buttons, knobs, touchscreens, switches, levers, or handles. In one embodiment, an operator may press a button to change the mode of operation for at least one of transmission 30, and drive system 100, and the vehicle. The operator may be able to manually control some or all aspects of the operation of transmission 30 using the display and the operator input. It should be understood that any type of display or input controls may be implemented with the systems and methods described herein.

Controller 210 may be implemented as a general-purpose processor, an application specific integrated circuit (ASIC), one or more field programmable gate arrays (FPGAs), a digital-signal-processor (DSP), circuits containing one or more processing components, circuitry for supporting a microprocessor, a group of processing components, or other suitable electronic processing components. According to the exemplary embodiment shown in FIG. 3, controller 210 includes a processing circuit 212 and a memory 214. Processing circuit 212 may include an ASIC, one or more FPGAs, a DSP, circuits containing one or more processing components, circuitry for supporting a microprocessor, a group of processing components, or other suitable electronic processing components. In some embodiments, processing circuit 212 is configured to execute computer code stored in memory 214 to facilitate the activities described herein. Memory 214 may be any volatile or non-volatile computer-readable storage medium capable of storing data or computer code relating to the activities described herein. According to an exemplary embodiment, memory 214 includes computer code modules (e.g., executable code, object code, source code, script code, machine code, etc.) configured for execution by processing circuit 212. Memory 214 includes various actuation profiles corresponding to modes of operation (e.g., for transmission 30, for drive system 100, for a vehicle, etc.), according to an exemplary embodiment. In some embodiments, controller 210 may represent a collection of processing devices (e.g., servers, data centers, etc.). In such cases, processing circuit 212 represents the collective processors of the devices, and memory 214 represents the collective storage devices of the devices.

Referring next to the exemplary embodiments shown in FIGS. 4-10, transmission 30 is configured to operate according to a plurality of modes of operation. Various modes of operation for transmission 30 are identified below in Table 1. In other embodiments, a vehicle having transmission 30 is configured to operate according to the various modes of operation shown in FIGS. 4-10 and identified below in Table 1.

TABLE 1

Mode of Operation	Power Split Brake	Power Split Coupled Clutch	Output Coupled Clutch	Output Brake	Input Coupled Clutch
	160	130	150	170	140
High Speed		X		X	
Reverse					
Low Speed		X	X		
Reverse					
Power	X				X
Generation Neutral/ Vehicle Start					
Low Range		X	X		
Mid Range		X		X	
High Range		X			X

As shown in Table 1, an “X” represents a component of drive system 100 (e.g., power split brake 160, power split coupled clutch 130, etc.) that is engaged or closed during the respective modes of operation. In other embodiments, power split brake 160 may be engaged during a neutral startup mode.

As shown in FIG. 4, transmission 30 is selectively reconfigured into a neutral startup mode. In one embodiment, rotation of first electromagnetic device 40 rotates connecting shaft 36 to start engine 20. An energy storage device (e.g., a capacitor, a battery, etc.) configured to store energy (e.g.,

electrical energy, chemical energy, etc.) may be associated with drive system 100. By way of example, first electromagnetic device 40 may be configured to use the stored energy to start engine 20 by providing a rotational mechanical energy input (e.g., a torque, etc.) to engine 20 via connecting shaft 36. In an alternative embodiment, engine 20 includes a traditional starting mechanism (e.g., a starter motor, etc.) configured to start engine 20. Engine 20 may provide a rotational mechanical energy input to at least one of first electromagnetic device 40 and/or second electromagnetic device 50. The first electromagnetic device 40 and second electromagnetic device 50 may be brought up to a threshold (e.g., a threshold speed, a threshold speed for a target period of time, a threshold power generation, a threshold power generation for a target period of time, etc.) that establishes a requisite DC bus voltage. Both first electromagnetic device 40 and second electromagnetic device 50 may thereafter be activated and controlled within and/or to desired states. The power electronics of control system 200 that control the motor-to-motor functions may be brought online during the neutral startup mode.

In one embodiment, transmission 30 includes power split brake 160, and power split brake 160 is engaged when transmission 30 is configured in the neutral startup mode. According to an exemplary embodiment, engaging power split brake 160 selectively limits the rotational movement of portions of both power split planetary 110 and output planetary 120. By way of example, engaging power split brake 160 may inhibit the rotational movement of gear 182, gear 184, and carrier 118 such that each remains rotationally fixed. Accordingly, carrier 128 also remains rotationally fixed because carrier 118 and carrier 128 are directly coupled. According to an exemplary embodiment, an energy flow path in the neutral startup mode includes: first electromagnetic device 40 providing a rotational mechanical energy input to sun gear 112 that is received by the plurality of planetary gears 116; the plurality of planetary gears 116 rotating about central axes thereof (e.g., planetary gears 116 may or may not rotate about sun gear 112 because carrier 118 may or may not be rotationally fixed, etc.); the plurality of planetary gears 116 conveying the rotational mechanical energy to ring gear 114; ring gear 114 transferring the rotational mechanical energy to connecting shaft 36 such that the rotational mechanical energy provided by first electromagnetic device 40 starts engine 20. Another energy flow path in the neutral startup mode may include engine 20 providing a rotational mechanical energy input to ring gear 114 that is received by the plurality of planetary gears 116; the plurality of planetary gears 116 rotating about central axes thereof (e.g., planetary gears 116 may or may not rotate about sun gear 112 because carrier 118 may or may not be rotationally fixed, etc.); the plurality of planetary gears 116 conveying the rotational mechanical energy to sun gear 112; and sun gear 112 conveying the rotational mechanical energy to first electromagnetic device 40 to bring first electromagnetic device 40 up to the threshold for establishing a requisite DC bus voltage and controlling first electromagnetic device 40 and/or second electromagnetic device 50 in a desired state.

Power split brake 160 may be used to isolate engine 20, first electromagnetic device 40, and second electromagnetic device 50 from output shaft 32 in the neutral startup mode. Such isolation may substantially eliminate a forward lurch potential of the vehicle (e.g., transmission 30 does not provide an output torque to tires 62 and/or tires 72, etc.). By way of example, the neutral startup mode utilizing power split brake 160 may be used to start engine 20, establish a

requisite DC bus voltage, or otherwise export power without relying on controller 210 to engage first electromagnetic device 40 and/or second electromagnetic device 50.

As shown in FIG. 5, transmission 30 is selectively reconfigured into a power generation mode such that rotation of connecting shaft 36 rotates first electromagnetic device 40 and second electromagnetic device 50 to generate electrical power. In one embodiment, the electrical power is stored for future use. In another embodiment, the electrical power is used to power internal devices (e.g., control system 200, components of the vehicle, etc.) and/or external devices. As shown in FIG. 5 and Table 1, power split brake 160 and input coupled clutch 140 are engaged when transmission 30 is configured in the power generation mode. As shown in FIG. 5, both power split coupled clutch 130 and output coupled clutch 150 are not engaged such that engine 20 is isolated from output shaft 32. Engine 20 does not provide rotational mechanical energy to tires 62 or tires 72 during the power generation mode.

According to an exemplary embodiment, engine 20 provides a rotational mechanical energy input to connecting shaft 36, which drives both first electromagnetic device 40 and second electromagnetic device 50. As shown in FIG. 5, second electromagnetic device 50 is rotationally coupled to engine 20 via the engagement of input coupled clutch 140 with connecting shaft 36 such that second electromagnetic device 50 generates electrical power. The rotational mechanical energy of connecting shaft 36 is also provided to ring gear 114 of power split planetary 110. Engaging power split brake 160 inhibits the rotational movement of gear 182, gear 184, and carrier 118. Ring gear 114 conveys the rotational mechanical energy from connecting shaft 36 to the plurality of planetary gears 116. The plurality of planetary gears 116 rotate about central axes thereof, while remaining rotationally fixed relative to sun gear 112 such that the rotational mechanical energy is transferred to sun gear 112. Sun gear 112 provides the rotational mechanical energy from engine 20 to first electromagnetic device 40 via the shaft of first electromagnetic device 40 such that first electromagnetic device 40 generates electrical power.

As shown in FIG. 6, transmission 30 is selectively reconfigured into a low range mode of operation such that transmission 30 allows for a low output speed operation with a high output torque. The low range mode increases a vehicle's gradability (e.g., facilitates the vehicle maintaining speed on a grade, etc.). In one embodiment, engine 20 provides a rotational mechanical energy input to transmission 30 such that first electromagnetic device 40 generates electrical power and second electromagnetic device 50 uses the generated electrical power to provide a rotational mechanical energy input to transmission 30. As such, engine 20 and second electromagnetic device 50 provide a rotational mechanical energy input to drive at least one of tires 62 and tires 72. In an alternative embodiment, first electromagnetic device 40 operates as a motor and second electromagnetic device 50 operates as a generator when transmission 30 is configured in the low range mode.

As shown in FIG. 6 and Table 1, power split coupled clutch 130 and output coupled clutch 150 are engaged when transmission 30 is configured in the low range mode. As shown in FIG. 6, power split coupled clutch 130 and output coupled clutch 150 couple gear set 180 and gear set 190 to output shaft 32, respectively. Accordingly, when engine 20 provides a rotational mechanical energy input to transmission 30, both power split planetary 110 and output planetary 120 drive output shaft 32 via gear set 180 and gear set 190, respectively. According to the exemplary embodiment

11

shown in FIG. 6, an energy flow path for the low range includes: engine 20 providing a rotational mechanical energy input to connecting shaft 36; connecting shaft 36 conveying the rotational mechanical energy to ring gear 114; ring gear 114 causing the plurality of planetary gears 116 to rotate about central axes thereof, as well as about sun gear 112 such that both carrier 118 and sun gear 112 rotate; and the rotation of sun gear 112 driving first electromagnetic device 40 such that it operates as a generator (e.g., generates electrical energy, etc.).

Referring still to FIG. 6, the rotation of carrier 118 drives both carrier 128 and gear set 180. Carrier 128 drives the plurality of planetary gears 126 to rotate about sun gear 122 and about central axes thereof. In one embodiment, second electromagnetic device 50 receives electrical energy generated by first electromagnetic device 40. Accordingly, second electromagnetic device 50 operates as a motor, providing a rotational mechanical energy input to sun gear 122. The sun gear 122 conveys the rotational mechanical energy to the plurality of planetary gears 126 such that each further rotates about the central axis thereof. The plurality of planetary gears 126 drive ring gear 124, and the rotation of ring gear 124 drives gear set 190. According to the exemplary embodiment shown in FIG. 6, gear set 180 and gear set 190 transfer a torque to and from output shaft 32 with power split coupled clutch 130 and output coupled clutch 150 engaged. As such, engine 20 and second electromagnetic device 50 move a vehicle at a low speed with a high output torque.

As shown in FIG. 7, transmission 30 is selectively reconfigured into a mid range mode of operation such that transmission 30 allows for a mid range output speed operation. The mid range mode may improve low output speed torque and high output speed power. In one embodiment, engine 20 provides a rotational mechanical energy input such that first electromagnetic device 40 generates electrical power, and second electromagnetic device 50 uses the generated electrical power to provide a rotational mechanical energy input to transmission 30. As such, second electromagnetic device 50 provides a rotational mechanical energy input to drive at least one of tires 62 and tires 72. In an alternative embodiment, second electromagnetic device 50 operates as a generator and first electromagnetic device 40 operates as a motor when transmission 30 is configured in the mid range mode. In still another alternative embodiment, both first electromagnetic device 40 and second electromagnetic device 50 operate as a generator in the mid range mode.

As shown in FIG. 7 and Table 1, power split coupled clutch 130 and output brake 170 are engaged when transmission 30 is configured in the mid range mode. As shown in FIG. 7, output brake 170 inhibits the rotation of gear set 190 (e.g., gear 192, gear 194, gear 196, etc.). Output brake 170 thereby rotationally fixes ring gear 124. In one embodiment, engaging output brake 170 substantially eliminates a power dip between output and input modes of transmission 30. According to the exemplary embodiment shown in FIG. 7, an energy flow path for the mid range mode includes: engine 20 providing a rotational mechanical energy input to connecting shaft 36 that is conveyed to ring gear 114; and ring gear 114 driving the plurality of planetary gears 116 to rotate about central axes thereof, as well as about sun gear 112 such that both carrier 118 and sun gear 112 rotate.

Referring still to FIG. 7, the rotation of carrier 118 drives carrier 128, which rotates the plurality planetary gears 126 about central axes thereof, as well as about sun gear 122. With ring gear 124 fixed by output brake 170, second electromagnetic device 50 may operate as a motor. In one

12

embodiment, second electromagnetic device 50 receives electrical energy generated by first electromagnetic device 40. Accordingly, first electromagnetic device 40 operates as a generator, removing a rotational mechanical energy from sun gear 112. The sun gear 122 conveys the rotational mechanical torque to the plurality of planetary gears 126 such that each further rotates about sun gear 122 (e.g., at an increased rotational speed, etc.). The rotation of the plurality of planetary gears 126 (e.g., effected by sun gear 122, etc.) drives carrier 128 and thereby gear set 180. As shown in FIG. 7, power split coupled clutch 130 couples gear set 180 to output shaft 32 such that the rotational mechanical energy of gear set 180, received from second electromagnetic device 50, drives output shaft 32 at a mid range output speed and may thereby drive a vehicle at a mid range output speed.

As shown in FIG. 8, transmission 30 is selectively reconfigured into a high range mode of operation such that transmission 30 allows for a high output speed operation. In one embodiment, engine 20 provides a rotational mechanical energy input such that second electromagnetic device 50 generates electrical power and first electromagnetic device 40 uses the generated electrical power to provide a rotational mechanical energy input to transmission 30. As such, engine 20 and first electromagnetic device 40 provide a rotational mechanical energy input to drive at least one of tires 62 and tires 72. In an alternative embodiment, first electromagnetic device 40 operates as a generator and second electromagnetic device 50 operates as a motor when transmission 30 is configured in the medium range mode.

As shown in FIG. 8 and Table 1, power split coupled clutch 130 and input coupled clutch 140 are engaged when transmission 30 is configured in the high range mode. As shown in FIG. 8, the engagement of input coupled clutch 140 with connecting shaft 36 rotationally couples engine 20 and second electromagnetic device 50. By way of example, engine 20 may provide a rotational mechanical energy input to connecting shaft 36 such that second electromagnetic device 50 generates electrical energy. In one embodiment, first electromagnetic device 40 receives the electrical energy generated by second electromagnetic device 50. Accordingly, first electromagnetic device 40 operates as a motor, providing a rotational mechanical energy input to sun gear 112 that drives the plurality of planetary gears 116.

Referring still to FIG. 8, the power from engine 20 is transferred to ring gear 114 and the plurality of planetary gears 116. The plurality of planetary gears 116 are driven by both engine 20 (e.g., via ring gear 114, etc.) and first electromagnetic device 40 (e.g., via sun gear 112, etc.). Carrier 118 rotates, which drives gear set 180. As shown in FIG. 8, power split coupled clutch 130 couples gear set 180 to output shaft 32 such that the rotational mechanical energy provided by engine 20 and first electromagnetic device 40 drives a vehicle at a high range speed.

As shown in FIG. 9, transmission 30 is selectively reconfigured into a low speed reverse mode of operation. In one embodiment, engine 20 provides a rotational mechanical energy input to transmission 30 such that first electromagnetic device 40 generates electrical power and second electromagnetic device 50 uses the generated electrical power to provide a rotational mechanical energy input to transmission 30. As such, engine 20 and second electromagnetic device 50 provide a rotational mechanical energy input to drive at least one of tires 62 and tires 72 in a reverse direction (e.g., backwards, etc.). In an alternative embodiment, first electromagnetic device 40 operates as a motor and second electromagnetic device 50 operates as a generator when transmission 30 is configured in the low speed reverse mode.

13

As shown in FIG. 9 and Table 1, power split coupled clutch 130 and output coupled clutch 150 are engaged when transmission 30 is configured in the low speed reverse mode. As shown in FIG. 9, the low speed reverse mode is substantially similar to the low range mode of FIG. 6 in that power split coupled clutch 130 and output coupled clutch 150 couple both gear set 180 and gear set 190 to output shaft 32. In the low speed reverse mode, second electromagnetic device 50 may provide a rotational mechanical energy input to transmission 30 in an opposite direction as compared to the low range mode of FIG. 6.

As shown in FIG. 10, transmission 30 is selectively reconfigured into a high speed reverse mode of operation such that transmission 30 allows for a high reverse output speed operation. In one embodiment, engine 20 provides a rotational mechanical energy input such that first electromagnetic device 40 generates electrical power, and second electromagnetic device 50 uses the generated electrical power to provide a rotational mechanical energy input to transmission 30. As such, second electromagnetic device 50 provides a rotational mechanical energy input to drive at least one of tires 62 and tires 72. In an alternative embodiment, second electromagnetic device 50 operates as a generator and first electromagnetic device 40 operates as a motor when transmission 30 is configured in the high speed reverse mode. In still another alternative embodiment, both first electromagnetic device 40 and second electromagnetic device 50 operate as a generator in the high speed reverse mode.

As shown in FIG. 10 and Table 1, power split coupled clutch 130 and output brake 170 are engaged when transmission 30 is configured in the high speed reverse mode. As shown in FIG. 10, output brake 170 inhibits the rotation of gear set 190 (e.g., gear 192, gear 194, gear 196, etc.). Output brake 170 thereby rotationally fixes ring gear 124. According to the exemplary embodiment shown in FIG. 10, an energy flow path for the high speed reverse mode includes: engine 20 providing a rotational mechanical energy input to connecting shaft 36 that is conveyed to ring gear 114; and ring gear 114 driving the plurality of planetary gears 116 to rotate about central axes thereof, as well as about sun gear 112 such that both carrier 118 and sun gear 112 rotate.

Referring still to FIG. 10, the rotation of carrier 118 drives carrier 128, which rotates the plurality planetary gears 126 about central axes thereof, as well as about sun gear 122. With ring gear 124 fixed by output brake 170, second electromagnetic device 50 may operate as a motor. In one embodiment, second electromagnetic device 50 receives electrical energy generated by first electromagnetic device 40. Accordingly, first electromagnetic device 40 operates as a generator, removing a rotational mechanical energy from sun gear 112. The sun gear 122 conveys the rotational mechanical torque to the plurality of planetary gears 126 such that each further rotates about sun gear 122 (e.g., at an increased rotational speed, etc.). The rotation of the plurality of planetary gears 126 (e.g., effected by sun gear 122, etc.) drives carrier 128 and thereby gear set 180. As shown in FIG. 10, power split coupled clutch 130 couples gear set 180 to output shaft 32 such that the rotational mechanical energy of gear set 180, received from second electromagnetic device 50, drives output shaft 32 at a high reverse output speed and may thereby drive a vehicle at a high reverse output speed.

According to an alternative embodiment, transmission 30 is selectively reconfigured into a high speed reverse mode of operation (e.g., a series electric mode, etc.) whereby output coupled clutch 150 and the optional power split brake 160

14

are engaged. In such a high speed reverse mode, engine 20 may be coupled to first electromagnetic device 40 such that rotation of first electromagnetic device 40 by engine 20 generates electric power to operate second electromagnetic device 50 as a motor. According to an exemplary embodiment, power split brake 160 increases the reverse range (e.g., potential speed range while in reverse, etc.) without increasing the gear speeds of transmission 30 to substantial levels. Output coupled clutch 150 may couple output planetary 120 and gear set 190 to output shaft 32 such that second electromagnetic device 50 provides a mechanical output to output shaft 32.

Power split brake 160 may inhibit the rotational movement of gear 182, gear 184, and carrier 118 such that each remains rotationally fixed. Accordingly, carrier 128 remains rotationally fixed. Engine 20 may provide a rotational mechanical energy input to connecting shaft 36. Connecting shaft 36 conveys the rotational mechanical energy to ring gear 114, which drives the plurality of planetary gears 116 to rotate about central axes thereof, in turn rotating sun gear 112. First electromagnetic device 40 receives the rotational mechanical energy from engine 20 to generate electrical power. In one embodiment, the electrical power is used by second electromagnetic device 50 to drive sun gear 122. Sun gear 122 causes the plurality of planetary gears 126 to rotate about central axes thereof to drive ring gear 124. Ring gear 124 drives gear set 190 such that the rotational mechanical energy provided by second electromagnetic device 50 drives output shaft 32 and thereby a vehicle at a high speed in a reverse direction.

According to an alternative embodiment, engine 20 does not provide a rotational mechanical energy input to drive a vehicle. By way of example, first electromagnetic device 40, second electromagnetic device 50, and/or another device may store energy during the above mentioned modes of operation. When sufficient energy is stored (e.g., above a threshold level, etc.), at least one of first electromagnetic device 40 and second electromagnetic device 50 may provide a rotational mechanical energy input to transmission 30 such that the vehicle is driven without an input from engine 20 (e.g., an electric mode, etc.).

Although the figures may show a specific order of method steps, the order of the steps may differ from what is depicted. Also two or more steps may be performed concurrently or with partial concurrence. Such variation will depend on the software and hardware systems chosen and on designer choice. All such variations are within the scope of the disclosure. Likewise, software implementations could be accomplished with standard programming techniques with rule-based logic and other logic to accomplish the various connection steps, processing steps, comparison steps, and decision steps. contrariwise

As utilized herein, the terms “approximately”, “about”, “substantially”, and similar terms are intended to have a broad meaning in harmony with the common and accepted usage by those of ordinary skill in the art to which the subject matter of this disclosure pertains. It should be understood by those of skill in the art who review this disclosure that these terms are intended to allow a description of certain features described and claimed without restricting the scope of these features to the precise numerical ranges provided. Accordingly, these terms should be interpreted as indicating that insubstantial or inconsequential modifications or alterations of the subject matter described and claimed are considered to be within the scope of the invention as recited in the appended claims.

It should be noted that the term “exemplary” as used herein to describe various embodiments is intended to indicate that such embodiments are possible examples, representations, and/or illustrations of possible embodiments (and such term is not intended to connote that such 5 embodiments are necessarily extraordinary or superlative examples).

The terms “coupled,” “connected,” and the like, as used herein, mean the joining of two members directly or indirectly to one another. Such joining may be stationary (e.g., permanent, etc.) or moveable (e.g., removable, releasable, etc.). Such joining may be achieved with the two members or the two members and any additional intermediate members being integrally formed as a single unitary body with one another or with the two members or the two members 15 and any additional intermediate members being attached to one another.

References herein to the positions of elements (e.g., “top,” “bottom,” “above,” “below,” “between,” etc.) are merely used to describe the orientation of various elements in the figures. It should be noted that the orientation of various elements may differ according to other exemplary embodiments, and that such variations are intended to be encompassed by the present disclosure. 20

It is important to note that the construction and arrangement of the electromechanical variable transmission as shown in the exemplary embodiments is illustrative only. Although only a few embodiments of the present disclosure have been described in detail, those skilled in the art who review this disclosure will readily appreciate that many modifications are possible (e.g., variations in sizes, dimensions, structures, shapes and proportions of the various elements, values of parameters, mounting arrangements, use of materials, colors, orientations, etc.) without materially departing from the novel teachings and advantages of the subject matter recited. For example, elements shown as integrally formed may be constructed of multiple parts or elements. It should be noted that the elements and/or assemblies of the components described herein may be constructed from any of a wide variety of materials that provide sufficient strength or durability, in any of a wide variety of colors, textures, and combinations. Accordingly, all such modifications are intended to be included within the scope of the present inventions. Other substitutions, modifications, changes, and omissions may be made in the design, operating conditions, and arrangement of the preferred and other exemplary embodiments without departing from scope of the present disclosure or from the spirit of the appended claims. 35

What is claimed is:

1. A drive system for a vehicle, comprising:

- a first gear set including a first sun gear, a first ring gear, a first plurality of planetary gears coupling the first sun gear to the first ring gear, and a first carrier rotationally supporting the first plurality of planetary gears;
- a second gear set including a second sun gear, a second ring gear, a second plurality of planetary gears coupling the second sun gear to the second ring gear, and a second carrier rotationally supporting the second plurality of planetary gears, wherein the first carrier is directly coupled to the second carrier;
- a first electrical machine directly coupled to the first sun gear of the first gear set;
- a second electrical machine directly coupled to the second sun gear of the second gear set;
- a connecting shaft coupled to the first ring gear of the first gear set;

a driveshaft configured to transport power from the first electrical machine and the second electrical machine to a tractive element of the vehicle;

a first clutch selectively rotationally coupling the first carrier and the second carrier to the driveshaft when engaged;

a second clutch selectively rotationally coupling the second electrical machine to the connecting shaft when engaged; and

a third clutch selectively rotationally coupling the second gear set to the driveshaft when engaged.

2. The drive system of claim 1, wherein the drive system is selectively reconfigurable into a first mode whereby the first clutch and the third clutch are engaged, and wherein the drive system is selectively reconfigurable into a second mode whereby the first clutch and the second clutch are engaged. 15

3. The drive system of claim 1, further comprising a brake positioned to selectively limit a rotational movement of the second ring gear, wherein the drive system is selectively reconfigurable into a mode whereby the first clutch and the brake are engaged. 20

4. The drive system of claim 1, further comprising a brake positioned to selectively limit a rotation of the first carrier and the second carrier, wherein the drive system is selectively reconfigurable into a mode whereby the brake and the second clutch are engaged.

5. The drive system of claim 4, wherein the drive system is selectively reconfigurable into a second mode whereby the brake and the third clutch are engaged. 30

6. The drive system of claim 5, further comprising a second brake positioned to selectively limit a rotational movement of the second ring gear.

7. A drive system for a vehicle, comprising:

a first planetary gear set;

a second planetary gear set directly coupled to the first planetary gear set;

a connecting shaft coupled to the first planetary gear set, wherein the first planetary gear set, the second planetary gear set, and the connecting shaft are radially aligned;

a first electromagnetic device coupled to the first planetary gear set, wherein the first electromagnetic device includes a first shaft;

a second electromagnetic device coupled to the second planetary gear set and selectively rotationally engaged with the connecting shaft, wherein the second electromagnetic device includes a second shaft, wherein the first shaft and the second shaft are radially aligned with the first planetary gear set, the second planetary gear set, and the connecting shaft, and wherein the connecting shaft extends through the second electromagnetic device and through the second planetary gear set to the first planetary gear set; and

an output selectively coupled to the first planetary gear set and the second planetary gear set, wherein the output is radially offset from the first planetary gear set, the second planetary gear set, and the connecting shaft.

8. The drive system of claim 7, further comprising a brake positioned to selectively limit a rotational movement of the second planetary gear set. 60

9. The drive system of claim 7, wherein the drive system is selectively reconfigurable into a first mode whereby the output is coupled to the first planetary gear set and the second planetary gear set, wherein the drive system is selectively reconfigurable into a second mode whereby the output is coupled to the first planetary gear set and a 65

17

rotational movement of the second planetary gear set is limited, and wherein the drive system is selectively reconfigurable into a third mode whereby the output is coupled to the first planetary gear set and the second electromagnetic device is rotationally engaged with the connecting shaft.

10. The drive system of claim 7, wherein the first planetary gear set and the second planetary gear set are disposed between the first electromagnetic device and the second electromagnetic device.

11. The drive system of claim 7, further comprising a brake positioned to selectively limit a rotational movement of the first planetary gear set when engaged.

12. The drive system of claim 11, wherein the drive system is selectively reconfigurable into a mode whereby the brake is engaged and the second electromagnetic device is rotationally engaged with the connecting shaft.

13. The drive system of claim 7, wherein the drive system is selectively reconfigurable into a mode whereby the output is coupled to the first planetary gear set and the second electromagnetic device is rotationally engaged with the connecting shaft.

14. A vehicle, comprising:

a multi-mode transmission including:

a first gear set having a first planetary gear carrier and a second gear set having a second planetary gear carrier, wherein the first planetary gear carrier and the second planetary gear carrier are rotatably coupled;

a first motor/generator coupled to the first gear set; and a second motor/generator coupled to the second gear set;

a connecting shaft selectively coupled to the second gear set; and

a drive axle selectively coupled to the multi-mode transmission;

wherein during a first mode of the multi-mode transmission the connecting shaft is coupled to the second motor/generator and decoupled from the drive axle, and

wherein during a second mode of the multi-mode transmission the connecting shaft is decoupled from the second motor/generator, the second motor/generator is selectively coupled to the drive axle, and the connecting shaft is coupled to the first motor/generator.

15. The vehicle of claim 14, further comprising a first clutch positioned to selectively couple the first planetary gear carrier and the second planetary gear carrier to the drive axle.

16. The vehicle of claim 15, further comprising a brake positioned to selectively limit movement of the first planetary gear carrier and the second planetary gear carrier when engaged.

17. The vehicle of claim 16, further comprising a second brake positioned to selectively limit movement of a ring gear of the second gear set.

18. The vehicle of claim 17, further comprising a second clutch positioned to selectively couple the second motor/generator to the connecting shaft, wherein during a third mode of the multi-mode transmission the first clutch and the second brake are engaged, and wherein during a fourth mode of operation the first clutch and the second clutch are engaged.

19. The vehicle of claim 18, further comprising a third clutch positioned to selectively couple the second gear set to the drive axle, wherein during a fifth mode of the multi-mode transmission the first clutch and the third clutch are engaged.

18

20. A drive system for a vehicle, comprising:

a first gear set including a first sun gear, a first ring gear, a first plurality of planetary gears coupling the first sun gear to the first ring gear, and a first carrier rotationally supporting the first plurality of planetary gears;

a second gear set including a second sun gear, a second ring gear, a second plurality of planetary gears coupling the second sun gear to the second ring gear, and a second carrier rotationally supporting the second plurality of planetary gears, wherein the first carrier is directly coupled to the second carrier;

a first electrical machine directly coupled to the first sun gear of the first gear set;

a second electrical machine directly coupled to the second sun gear of the second gear set;

a connecting shaft coupled to the first ring gear of the first gear set;

a driveshaft configured to transport power from the first electrical machine and the second electrical machine to a tractive element of the vehicle;

a first clutch selectively rotationally coupling the first carrier and the second carrier to the driveshaft when engaged;

at least one of:

a second clutch selectively rotationally coupling the second electrical machine to the connecting shaft when engaged; and

a third clutch selectively rotationally coupling the second gear set to the driveshaft when engaged; and

a brake positioned to selectively limit a rotational movement of the second ring gear, wherein the drive system is selectively reconfigurable into a mode whereby the first clutch and the brake are engaged.

21. A drive system for a vehicle, comprising:

a first gear set including a first sun gear, a first ring gear, a first plurality of planetary gears coupling the first sun gear to the first ring gear, and a first carrier rotationally supporting the first plurality of planetary gears;

a second gear set including a second sun gear, a second ring gear, a second plurality of planetary gears coupling the second sun gear to the second ring gear, and a second carrier rotationally supporting the second plurality of planetary gears, wherein the first carrier is directly coupled to the second carrier;

a first electrical machine directly coupled to the first sun gear of the first gear set;

a second electrical machine directly coupled to the second sun gear of the second gear set;

a connecting shaft coupled to the first ring gear of the first gear set;

a driveshaft configured to transport power from the first electrical machine and the second electrical machine to a tractive element of the vehicle;

a first clutch selectively rotationally coupling the first carrier and the second carrier to the driveshaft when engaged;

at least one of:

a second clutch selectively rotationally coupling the second electrical machine to the connecting shaft when engaged; and

a third clutch selectively rotationally coupling the second gear set to the driveshaft when engaged; and

a brake positioned to selectively limit a rotation of the first carrier and the second carrier, wherein the drive system is selectively reconfigurable into a mode whereby the brake and the second clutch are engaged.