

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
16 April 2009 (16.04.2009)

PCT

(10) International Publication Number
WO 2009/047273 A1

(51) International Patent Classification:
H04N 7/52 (2006.01) *H04N 7/24* (2006.01)

(74) Agent: **BERTHIER, Karine**; Thomson, 46, Quai A. Le Gallo, F-92648 Boulogne Cedex (FR).

(21) International Application Number:
PCT/EP2008/063487

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(22) International Filing Date: 8 October 2008 (08.10.2008)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
07301453.2 11 October 2007 (11.10.2007) EP

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MT, NL, NO, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant (*for all designated States except US*): **THOMSON LICENSING** [FR/FR]; Thomson Licensing, 46 Quai A. Le Gallo, F-92100 Boulogne-billancourt (FR).

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **HENRY, Jean-Baptiste** [FR/FR]; 6 square du Tregor, F-35520 Melesse (FR).
HERISSE, Alexandre [FR/FR]; 14 rue St-Denis, F-86000 Poitiers (FR).

Published:
— with international search report

(54) Title: SYSTEM AND METHOD FOR AN EARLY START OF AUDIO-VIDEO RENDERING




FIG. 2

(57) Abstract: The present invention relates to a method at a receiver for playing a stream comprising a set of discrete samples adapted to be rendered at a standard rendering speed, comprising at the receiver the steps of starting the reception of the stream, starting the rendering of the discrete samples at a speed slower than the standard rendering speed and accelerating the rendering speed up to the standard rendering speed. The invention also concerns methods for an early rendering of continuous samples, when the stream comprises a set of continuous samples, wherein the continuous and discrete samples being adapted to be rendered at a standard rendering speed in a synchronized manner.

WO 2009/047273 A1

SYSTEM AND METHOD FOR AN EARLY START OF AUDIO-VIDEO RENDERING

The present invention relates generally to audio-video rendering
5 and in particular to a method for an early start of audio-video rendering.

This section is intended to introduce the reader to various aspects
of art, which may be related to various aspects of the present invention that
are described and/or claimed below. This discussion is believed to be helpful
10 in providing the reader with background information to facilitate a better
understanding of the various aspects of the present invention. Accordingly, it
should be understood that these statements are to be read in this light, and
not as admissions of prior art.

15 Changes in Television broadcast technologies have lead to a
longer zapping time. With analogical broadcast television, zapping was
immediate. With digital television, zapping requires more time. This is
illustrated as follows. Video distribution through broadband networks uses
standard compression systems such as MPEG-2 or JVT/H.264/MPEG AVC.
20 MPEG standards define the group of pictures (GoP). The GoP defines
successive pictures sequence I, P, B. These pictures are defined in MPEG
standards. The I picture is encoded without any reference to the other
pictures. The P picture refers to the previous I or P pictures. The B picture
refers to the previous and following I or P pictures. When a receiver receives
25 a new program, it waits for the reception of an I picture to start decoding the
program. A delay appears between the reception of the stream and the
rendering of the stream on a video screen.

Mechanisms used to reduce the digital television bandwidth use
less and less I pictures. The decoder requires then more time to find and
30 decode the I picture. This can take up to half a second. Moreover, with
television transport over the Internet Protocol networks, an additional buffer is
needed at the decoder to compensate the network delivery unreliability. This

increases the time between the reception of the program and the transmission of the television stream to the decoder. It can require more than two seconds between the reception and the rendering of the new program picture on the screen.

5 Some technologies have appeared to decrease this zapping time. WO2005112465A1 describes additional streams that are quickly decoded for zapping, such as rapid I picture finding. EP1523190 patent application describes a unicast burst push method to fill the decoder. These methods
10 require sending an additional stream to the decoders specifically for the zapping process.

The present invention concerns a method for an early start of audio-video rendering. It provides a simple method at an audio-video receiver without any impact at the audio-video sender.

15

To this end the invention concerns a method at a receiver for playing a stream, the stream comprising a set of discrete samples adapted to be rendered at a standard rendering speed, comprising at the receiver the steps of starting the reception of the stream, starting the rendering of the
20 discrete samples at a speed slower than the standard rendering speed and accelerating the rendering speed up to the standard rendering speed.

The stream is received from another device. The receiver starts the reception of the stream.

25 Instead of starting the rendering of the discrete samples at the standard rendering speed, the receiver of the invention starts the rendering at a lower speed. This is a slow start rendering. And the rendering speed is slowly and continuously increased to the standard rendering speed. This permits to render the discrete samples earlier.

30 According to an embodiment of the invention, the stream comprises a set of continuous samples, the continuous and discrete samples being adapted to be rendered at a standard rendering speed in a

synchronized manner, and the method further comprises the step of rendering the continuous samples at the standard rendering speed and not synchronized with the discrete samples when the discrete samples are rendered at a speed lower than the normal speed and rendering the
5 continuous samples at the standard rendering speed and synchronized with the discrete samples when the discrete samples are rendered at the standard rendering speed.

Rendering the continuous samples with the slow start method would conduct to an inconvenient rendering to the end user. Waiting for the
10 time when the synchronized continuous samples rendering would be acceptable to the end user might be long to the end user. The continuous samples rendering of the invention is desynchronized from the discrete samples rendering. The method permits to provide early continuous samples rendering that is acceptable to the end user.

15

According to an embodiment of the invention, the step of rendering the continuous samples synchronized with the discrete samples starts with the discrete sample rendering being adjusted to the continuous sample rendering.

20

The synchronization start is then transparent to the end user.

According to an embodiment of the invention, the step of rendering the continuous samples not synchronized with the discrete samples starts at a time corresponding to the time when the discrete sample would be
25 rendered at the standard rendering speed.

According to a variant embodiment of the invention, the stream comprises a set of continuous samples, the continuous and discrete samples being adapted to be rendered at a standard rendering speed in a
30 synchronized manner, and the method further comprises the steps of, when the discrete samples are rendered at a speed lower than the normal speed, and when the continuous samples rendering speed reaches a threshold,

rendering the continuous samples synchronized with the discrete samples and at a speed lower than the normal speed, wherein the speed is continuously accelerated up to the standard rendering speed.

5 It may be possible to render continuous samples at a speed lower than the standard rendering speed, where the rendering is acceptable to an end user. The method permits to start the rendering earlier, synchronized to the discrete samples rendering, as soon as the continuous samples rendering speed is convenient.

10 According to an embodiment of the invention, prior to the step of receiving a stream, the method comprises the step of zapping to a new program.

The method of the invention permits to reduce the zapping time.

15 According to an embodiment of the invention, the discrete sample is a video sample and the continuous sample is an audio sample.

According to an embodiment of the invention, the stream is an MPEG-2 stream.

20 According to an embodiment of the invention, the discrete samples rendering time depends on the delay between the reception of continuous and discrete samples of a same rendering time.

25 Increasing the discrete samples rendering time permits to enable synchronization with the continuous samples rendering, when the delay between the reception of continuous and discrete samples corresponding to a same rendering time is too high.

30 Certain aspects commensurate in scope with the disclosed embodiments are set forth below. It should be understood that these aspects are presented merely to provide the reader with a brief summary of certain forms the invention might take and that these aspects are not intended to

limit the scope of the invention. Indeed, the invention may encompass a variety of aspects that may not be set forth below.

5 The invention will be better understood and illustrated by means of the following embodiment and execution examples, in no way limitative, with reference to the appended figures on which:

- Figure 1 is a block diagram of a system compliant with the embodiments;
- 10 - Figure 2 is a block diagram of a receiver according to the embodiments;
- Figure 3 illustrates the slow start video rendering process according to the embodiment;
- Figure 4 illustrates the slow start audio rendering process according to a first embodiment;
- 15 - Figure 5 illustrates the slow start audio rendering process according to a second embodiment;
- Figure 6 illustrates the slow start audio rendering process according to a third embodiment;
- 20 - Figure 7 illustrates the reception of audio video streams;
- Figure 8 illustrates the audio and video presentation according to the audio and video reception; and
- Figure 9 also illustrates the audio and video presentation according to the audio and video reception.

25

In Figures 1 and 2, the represented blocks are purely functional entities, which do not necessarily correspond to physically separate entities. Namely, they could be developed in the form of software, or be implemented in one or several integrated circuits or a combination of both.

30

The system according to the embodiment is represented in figure 1. It comprises devices such as a server 6, a receiver 4, and a video screen

5. The server comprises a video source module 1 and a video encoder module 2. Of course the video source module and a video encoder module might be comprised in separate devices. The server encodes the audio-video stream and sends the audio-video stream to the receiver through the Internet
5 Protocol network 3. Of course the audio-video stream might be transmitted through any network type enabling sending audio-video streams from a server to a receiver. In particular the network might be a local area network. The various components of the audio-video might also be transmitted through a plurality of different networks; wherein the components would then
10 have a way to synchronize themselves at the receiver. The video receiver is a set-top box. Of course it might be any device comprising functions such as the ones comprised in the set-top box for the video decoding. The video stream is received by the set-top box, decoded and rendered at the video screen.

15

A receiver according to the embodiments is illustrated in the figure
2. The receiver comprises communicating module 21 for receiving audio video data from a server on the network. It comprises a storing module 23 for storing audio data and video data. It comprises audio video decoding module
20 25 for decoding the audio streams and the video streams. It comprises user interface 24 for allowing a user to control the receiver. The user interface permits to activate or deactivate the zapping methods. The various embodiments describes hereinafter might be all implemented in a same receiver, and the user interface permits to select one of the methods for
25 zapping. A processing module 22 is adapted to execute the methods according to the embodiments. Data circulates in the device through an internal bus 26.

The slow start video rendering process according to the
30 embodiment is illustrated in figure 3. It comprises the reception buffer filling level diagram and the video rendering speed diagram in function of the time. The stream is transported at a standard speed. It allows the receiver to

render the stream at a standard speed. At step S1, the stream is received at the receiver. No image is stored nor rendered. At step S2 an I picture is found in the stream. The phase 1 start, wherein the I picture is displayed on the screen. The receiver then starts filling in the reception buffer. The buffer
5 fills at the rate of the reception since only the received I picture is rendered and no other image is consumed. At step S3 the reception buffer reaches a level where the rendering starts. The level corresponds to an amount of data received that permits to suitably render the video. That level value might be modifiable so that the rendering may be started more or less early. If very
10 early, the rendering is a succession of still pictures. If less early the rendering looks like a slow motion video. At this step, rendering is performed at a speed slower than the standard rendering speed. This is the beginning of the phase 2. The buffer is still filled at receiving speed, but emptied at a speed slower than the standard speed that corresponds to the rendering speed. That
15 emptying speed accelerates slowly to enable rendering at the standard speed. Consequently, the buffer level still fills up but slower and slower as the rendering speed approaches the standard speed. The rendering speed then accelerates up to the time when the reception buffer is full at step S4. This corresponds to the phase 3 where the video is rendered at standard
20 speed.

The emptying speed accelerates as follows. The video buffer is filled at N%. The speed is then set to the value $100 / (1 + (100 - N) * \text{coeff} / 100)$. The coeff value is by default set to 1. For example, if the video buffer is filled at 60%, the speed is 71.4% of the standard speed.

25 The coeff value may be set to any value other than 1. A coeff value lower than 1 enables to quickly have an acceptable rendering speed, but requires longer time to fill the buffer and so to reach the standard speed. A coeff value higher than 1 enables to quickly fill the buffer, but the rendering speed is lower at the beginning. The coeff value might also be dynamically
30 modified according to the buffer size.

As the buffer filling increases, the speed then also increases to reach the standard speed.

The slow start rendering process is convenient for video, which is a succession of still pictures, also called discrete samples. A discrete sample of content, when displayed during a period of time, represents the same content during the whole period of time. A discrete sample is rendered totally once during a specific amount of time. A video is a succession of discrete samples, i.e. still pictures, rendered more or less quickly. Typically in MPEG-2, a video displays at a frequency of a picture every 40ms for a Phase Alternating Line encoding system (PAL), which means 25 pictures per second. This is acceptable for the end user if the frequency is higher than 40ms.

The slow start rendering process may not be acceptable for continuous samples such as an audio stream. A continuous sample of content, when displayed during a period of time, continuously represents the whole content during the period of time. A continuous sample is gradually represented during a period of time. Typically in MPEG-1 layer II or layer III, an audio stream is encoded into fixed size samples, for example a sample every 24ms, which corresponds to 48kHz sampling. Rendering this sample at a rate lower or higher than normal rate typically modifies the pitch of the sound. The modification is already noticeable when the rendering speed is increased or decreased by 5%.

A first embodiment of an early audio rendering uses a slow start mechanism, as illustrated in figure 4. The figure 4 comprises an audio reception buffer diagram and an audio rendering speed diagram according to the time. The audio rendering speed diagram matches to the video rendering speed diagram as indicated in figure 3. In the first embodiment, the audio is rendered synchronized to the video rendered in a slow start manner.

The receiver uses an algorithm that allows modifying the sample duration while reprocessing the sample so as not to change the pitch. Such algorithms are well known to the skilled person in the art. With such algorithm, called hereinafter pitch algorithm, it is possible to increase or

decrease the rendering speed by 25% without strong noticeable effect for the end user. Therefore, the receiver may transparently render the audio when the reception buffer is 75% full. Of course the threshold may be higher or lower than 75%; it may depend on the type of sound that is processed and on
5 the algorithm itself.

The receiver receives the audio at the same time as the video. The audio is stored in the audio reception buffer, this is the phase 1', which corresponds to the phase 1 of figure 3. When the video rendering starts at S'2 (corresponding to S3 in figure 3), audio samples are consumed in a
10 synchronized manner but are not rendered. This is phase 1.5'. When the audio rendering speed reaches 75%, the audio rendering start, at step S'3, in phase 2'. The audio is synchronized to the video rendering. During the phases 1.5' and 2' the audio reception buffer is slowly entirely filled. When the audio reception buffer is full, the phase 3' starts, at step S'4. The audio
15 and video are rendered at standard speed. Phase 3' matches the phase 3 of figure 3.

Some implementations cannot provide such pitch algorithms to process the audio for rendering at low speed. With those implementations,
20 only a standard speed can be used for the audio. With the previous method, the audio would be rendered only at the end of phase 2, when entering the phase 3, which may be quite long.

The early audio rendering according to the second embodiment is
25 illustrated in figure 5. This is a desynchronized method where the receiver does not comprise any pitch algorithm. The figure 5 comprises an audio reception buffer diagram and an audio rendering speed diagram according to the time. The audio rendering speed diagram matches the video rendering speed diagram indicated in figure 3. In particular the start of phase 1 matches
30 the start of phase 1bis and the phase 3 matches the phase 3bis. According to the embodiment, the receiver receives the audio stream and fills in the audio reception buffer. When the buffer is full, at the end of phase 1bis, it renders

the audio at standard speed, step S3bis and phase 2bis. The audio rendering is therefore not synchronized with the video rendering during phase 2bis. Audio is rendered later than the start of slow speed video rendering. It is synchronized to the video when the video is rendered at standard speed, at
5 step S5bis.

According to a third embodiment, the method using a pitch algorithm is combined to the desynchronized method, as illustrated in figure 6. The receiver comprises means for running a pitch algorithm. At the phase
10 1ter, the receiver receives the audio and fills in the audio reception buffer at the same speed as the video buffer. When video rendering starts, audio rendering does not start; the audio threshold has not been reached and rendering the audio would be unacceptable for the end user. When the audio buffer reaches a threshold, the pitch algorithm permits to render the audio at
15 a reduced speed, here 85%, at step S''3. This is the start of the phase 1'ter. The audio is not synchronized to the video rendering.

The audio buffer filling level is higher than the video buffer filling level. As soon as the audio buffer filling level reaches the video buffer filling level, the audio is synchronized to the video, step S''5. This is the start of the
20 phase 2ter. The synchronized audio-video rendering speed then slowly increases to reach the standard speed as indicated in the first embodiment, step S''4 and phase 3ter.

When the audio and the video do not match exactly at the time
25 where they should be synchronized (for example at the end of phase 2 with the desynchronized method), it is easier to adjust the video component to the audio component rather than the audio component to the video component. The video picture that is rendered at that time is then rendered more or less time than its original duration so that it catches up with the corresponding
30 audio samples. Adjusting the audio component is not as easy as adjusting the video component, and for system without pitch algorithm, this would result in a sound impact for the end-user, small silence or scratch.

Audio and video buffering sizes depend on the reception time of audio and video samples. They may be received simultaneously or at different times, as illustrated in figure 7. The PTS is the presentation time stamp compliant with an MPEG-2 transport stream. The transport plane illustrates the value of the PTS in the packet that are received, and shows the difference of the reception time of the PTS. In the figures, for illustrative purpose, the PTS are representing samples that are equivalent in duration, which technically is not true for MPEG systems. The buffering plane indicates the minimum reception buffer size required depending on the difference of the reception time. The rendering plane indicates when the audio and video are rendered in a synchronized manner.

When received at the same time, both audio and video samples have the same PTS when they are received. Audio and video buffers are filled simultaneously. Consequently the audio and video buffers have the same size in time unit.

When audio and video components are not synchronized at the transport level, they are not received at the same time. In 702 video is received before audio, with a difference of 2 PTS, represented with Δ value set to 2. In 703 video is received after audio, with a difference of 2 PTS, represented with Δ value set to - 2.

Buffer adjustment is then necessary at the receiver. In 702 the video buffer size in the buffer plane is 2 PTS larger in time. In 703 the audio buffer size in the buffer plane is 2 PTS larger in time. The audio and video are then rendered at the same PTS in the rendering plane.

With the desynchronized method, it is however possible to have an audio rendering very early in the zapping phase.

Figure 8 and 9 illustrate the audio and video presentation according to the audio and video reception, when audio and video are not received at the same time. As illustrated in figure 8, the audio component is received late compared to the video component. It is not necessary to

increase the video buffer size; the video buffer size is sufficiently large to allow synchronization after phase 2. The desynchronized audio starts when it reaches the virtual video line, which is defined hereinafter.

As illustrated in figure 9, when the audio component is received very late compared to the video component at the transport level, video buffering size is increased to a new video buffer size. This is necessary because the default video buffer size is not sufficient to enable synchronization to the audio after phase 2. The virtual video line is calculated according to the new video buffer size. The desynchronized audio starts when it reaches the virtual video line.

The point in time when to render the desynchronized audio is determined by the meeting point with a virtual video line. This virtual video line is calculated with the final video buffer size and by extrapolating the video PTS that would be rendered if the video was rendered at standard speed without zapping. With an accurate computation, audio and video are synchronized at the end of phase 2. In order to compute the final video buffer size, the video component bit rate is required, because the final video buffer size is expressed in time unit.

The virtual video line is calculated taking into account the minimum video buffer size, the PTS difference at reception between the audio and the video and the video bitrate. The reception bit rate is continuously calculated with the packets reception flow. The minimum video buffer size is `buffer_default`. The difference between the audio and the video in the reception flow is observed, this is the `delta_audio_video`.

This provides the targeted video buffer, which is the `buffer_real`:
$$\text{buffer_real} = \max(\text{buffer_default}, \text{delta_audio_video} \times \text{bit_rate})$$

The virtual video PTS is continuously calculated:
$$\text{virtual_video_PTS} = \text{current_video_PTS} - (\text{buffer_real} - \text{current_buffer_level}) / \text{bit_rate}$$

As soon as the real audio PTS reaches the virtual_video_PTS, the audio is rendered at standard speed. The audio buffer size is set to the value of the audio buffer filling level at that moment.

5 The embodiments as indicated hereinabove preferably fit to small buffers, wherein a small buffer corresponds to a maximum of five seconds.

When the buffer is much larger, the zapping method comprises another phase, between phase 2 and phase 3, where the content is rendered at a speed close to the standard speed for a long duration. The nominal level
10 is reached linearly. During the phase 3, the receiver usually sets up corrective mechanisms to support transport jitter variations, wherein the nominal buffer filling level is continuously updated. Corrective mechanisms are also set up during this phase, wherein the virtual buffer level which is the ideal line of progressive buffer fill is continuously updated.

15 For example for a 30 seconds buffer, the phase 2 ends at a buffer filling level of 2 seconds. Then during the new phase the video is rendered at a speed set to 95% of the standard speed.

References disclosed in the description, the claims and the
20 drawings may be provided independently or in any appropriate combination. Features may, where appropriate, be implemented in hardware, software, or a combination of the two.

Reference herein to "one embodiment" or "an embodiment" means that a particular feature, structure, or characteristic described in
25 connection with the embodiment can be included in at least one implementation of the invention. The appearances of the phrase "in one embodiment" in various places in the specification are not necessarily all referring to the same embodiment, nor are separate or alternative embodiments necessarily mutually exclusive of other embodiments.

30 Reference numerals appearing in the claims are by way of illustration only and shall have no limiting effect on the scope of the claims.

CLAIMS

1. Method at a receiver for early playing a stream, said stream
5 comprising a set of discrete samples adapted to be rendered at a standard rendering speed, and a set of continuous samples, said continuous samples and said discrete samples being adapted to be rendered at a standard rendering speed in a synchronized manner, comprising at the receiver the steps of:
- 10 - Starting the reception of said stream;
 - Starting the rendering of said discrete samples at a speed slower than the standard rendering speed and not synchronized with the continuous samples rendered at the standard rendering speed;
 - Accelerating the rendering speed of said discrete samples up to
15 the standard rendering speed and
 - Rendering the discrete samples at the standard rendering speed and synchronized with the continuous samples rendered at the standard rendering speed.
- 20 2. Method according to claim 1, characterized in that the step of rendering the continuous samples at the standard rendering speed and synchronized with the discrete samples starts with the discrete sample rendering being adjusted to the continuous sample rendering.
- 25 3. Method according to claim 1 or 2, characterized in that the step of rendering the continuous samples at the standard rendering speed and not synchronized with the discrete samples starts at a time corresponding to the time when the discrete sample is rendered at the standard rendering speed.
- 30 4. Method according to claim 1, characterized in that said method further comprises the steps of, when the discrete samples are rendered at a speed lower than the standard speed, and when the continuous samples

rendering speed reaches a threshold, rendering the continuous samples synchronized with the discrete samples and at a speed lower than the standard speed, wherein the speed is continuously accelerated up to the standard rendering speed.

5

5. Method according to any one of the preceding claims, characterized in that it prior to the step of receiving a stream, it comprises the step of zapping to a new program.

10

6. Method according to any one of the preceding claims, characterized in that the discrete sample is a video sample and the continuous sample is an audio sample.

7. Method according to any one of the preceding claims, characterized in that the stream is an MPEG-2 stream.

15

8. Method according to any one of the preceding claims, characterized in that the discrete samples rendering time depends on the delay between the reception of continuous and discrete samples of a same rendering time.

20

9. Method at a receiver for early playing a stream, said stream comprising a set of discrete samples adapted to be rendered at a standard rendering speed, and a set of continuous samples, said continuous samples and said discrete samples being adapted to be rendered at a standard rendering speed in a synchronized manner, comprising at the receiver the steps of:

25

- Starting the reception of said stream;
- Starting the rendering of said continuous samples at a speed slower than the standard rendering speed and not synchronized with the discrete samples rendered at the standard rendering speed;

30

- Accelerating the rendering speed of said continuous samples up to the standard rendering speed and
 - Rendering the continuous samples at the standard rendering speed and synchronized with the discrete samples rendered at the standard rendering speed.
- 5

10. Method according to claim 9, characterized in that said method further comprises the steps of, when the continuous samples are rendered at a speed lower than the standard speed, and when the discrete samples rendering speed reaches a threshold, rendering the discrete samples synchronized with the continuous samples and at a speed lower than the standard speed, wherein the speed is continuously accelerated up to the standard rendering speed.

10

1/9




FIG. 1

2/9




FIG. 2

3/9




FIG. 3

4/9




FIG. 4

5/9




FIG. 5

6/9




FIG. 6

7/9




FIG. 7

8/9




FIG. 8

9/9




FIG. 9

INTERNATIONAL SEARCH REPORT

International application No

PCT/EP2008/063487

A. CLASSIFICATION OF SUBJECT MATTER

INV. H04N7/52

ADD. H04N7/24

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

H04N

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EP0-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 2004/062291 A (KONINKL PHILIPS ELECTRONICS NV [NL]; SALOMONS EDUARD W [IE]) 22 July 2004 (2004-07-22) page 12; line 25 - page 13, line 7 page 20 - page 24 figures 6,9	1-10
A	US 6 665 751 B1 (CHEN JEANE SHU-CHUN [US] ET AL) 16 December 2003 (2003-12-16) column 4 - column 5 figure 4	1-10



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance.
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *Z* document member of the same patent family

Date of the actual completion of the international search

19 November 2008

Date of mailing of the international search report

27/11/2008

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040.
Fax: (+31-70) 340-3016

Authorized officer

Richard, Romain

INTERNATIONAL SEARCH REPORT

International application No

PCT/EP2008/063487

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	STEINBACH E: "ADAPTIVE ABSPIELTECHNIKEN FUER INTERNET-MEDIASTREAMING" FKT FERNSEH UND KINOTECHNIK, FACHVERLAG SCHIELE & SCHON GMBH., BERLIN, DE, vol. 57, no. 1/02, 1 January 2003 (2003-01-01), pages 22-25, XP001220605 ISSN: 1430-9947 the whole document	1-10
A	STEINBACH E ET AL: "Adaptive playout for low latency video streaming" PROCEEDINGS 2001 INTERNATIONAL CONFERENCE ON IMAGE PROCESSING. ICIP 2001. THESSALONIKI, GREECE, OCT. 7 - 10, 2001; [INTERNATIONAL CONFERENCE ON IMAGE PROCESSING], NEW YORK, NY : IEEE, US, vol. 1, 7 October 2001 (2001-10-07), pages 962-965, XP010565021 ISBN: 978-0-7803-6725-8 the whole document	1-10
A	GIROD B ET AL: "Advances in channel-adaptive video streaming" PROCEEDINGS 2002 INTERNATIONAL CONFERENCE ON IMAGE PROCESSING. ICIP 2002. ROCHESTER, NY, SEPT. 22 - 25, 2002; [INTERNATIONAL CONFERENCE ON IMAGE PROCESSING], NEW YORK, NY : IEEE, US, vol. 1, 22 September 2002 (2002-09-22), pages 9-12, XP010607247 ISBN: 978-0-7803-7622-9 the whole document	1-10
A	US 6 247 072 B1 (FIRESTONE SCOTT [US]) 12 June 2001 (2001-06-12) column 4, line 1 - column 4, line 11 column 6, line 43 - column 7, line 22 figure 3	1-10

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/EP2008/063487

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 2004062291	A	22-07-2004	AU 2003285676 A1	29-07-2004
			CN 1736106 A	15-02-2006
			EP 1584192 A1	12-10-2005
			JP 2006513608 T	20-04-2006
			KR 20050090448 A	13-09-2005
			US 2007143800 A1	21-06-2007
US 6665751	B1	16-12-2003	NONE	
US 6247072	B1	12-06-2001	NONE	