

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
12 August 2004 (12.08.2004)

PCT

(10) International Publication Number
WO 2004/066751 A1

(51) International Patent Classification⁷: **A23L 1/01**, 1/36,
A23F 5/04, A23N 12/08, A21D 8/06, A23G 1/02

(74) Agent: **PRINS, A.W.**; Nieuwe Parklaan 97, NL-2587 BN
Den Haag (NL).

(21) International Application Number:
PCT/NL2004/000070

(81) Designated States (*unless otherwise indicated, for every
kind of national protection available*): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(22) International Filing Date: 30 January 2004 (30.01.2004)

(25) Filing Language: Dutch

(26) Publication Language: English

(30) Priority Data:
1022547 31 January 2003 (31.01.2003) NL

(84) Designated States (*unless otherwise indicated, for every
kind of regional protection available*): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), Euro-
pean (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR,
GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK,
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
ML, MR, NE, SN, TD, TG).

(71) Applicant (*for all designated States except US*): **NED-
ERLANDSE ORGANISATIE VOOR TOEGEPAST-
NATUURWE TENSCHAPPELIJK ONDERZOEK
TNO** [NL/NL]; Schoemakerstraat 97, NL-2628 VK Delft
(NL).

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **VAN DER MEER,
Henricus, Johannes, Jozef** [NL/NL]; Dorpsstraat 201,
NL-1566 AH Assendelft (NL). **BUSSMANN, Paulus,
Josephus, Jozef** [NL/NL]; Het Schip 239, NL-7325 NM
Apeldoorn (NL). **HEIJMANS, Rudy, Mathias, Henricus**
[NL/NL]; De Janswei 16, NL-6932 MT Westervoort (NL).
AKKERMAN, Jan, Coen [NL/NL]; Geertjesweg 104,
NL-6706 EE Wageningen (NL).

Published:

- with international search report
- before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments

*For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.*

(54) Title: PROCESS FOR THERMALLY TREATING A PRODUCT WITH STEAM

(57) Abstract: A method for thermally treating a product in order to have the product obtain the desired product properties, comprising the following steps: (a) determining the water activity value which, for carrying out the thermal treatment, is required to have the product obtain the desired properties; (b) contacting the product with water vapour, at an increased temperature and an associated saturated vapour pressure (p^*), while the temperature on the surface of the product is 80 - 260°C; (c) setting a vapour pressure (p) in step (b) such that p/p^* is equal to the water activity value determined in step (a); and (d) maintaining for a time duration (t) the process conditions mentioned in steps (b) and (c) for obtaining the product with the desired product properties.



WO 2004/066751 A1

PROCESS FOR THERMALLY TREATING A PRODUCT WITH STEAM

The invention relates to a method for thermally treating a product, for instance a food.

Roasting, baking, frying and sterilising are known thermal treatments to which products such as foods can be subjected. As a rule, such thermal treatments are aimed at improving the quality and the storage life of products. Roasting is for instance understood to mean a heat treatment of a food in which by means of Maillard-reactions the flavour and odour of the treated food are improved. It can also be possible to improve the colour of the food in this manner. Roasting foods is done both in continuous and batch systems, while heating takes place through direct contact with warm process air or indirectly via a heated wall. The development of flavour and odour through roasting is an extremely complicated chemical process. Reactions occur between the reducing sugars present and free amino acids, the so-called Maillard-reactions or non-enzymatic browning. The process is continued by Amadori conversion reactions and Strecker degradations. This series of different reactions may lead to a number of highly differing flavour profiles and aromas and the occurrence of undesired additional effects. In addition, in known thermal treatments of foods, eventual products are obtained whose quality and storage life often leave to be desired.

Surprisingly, it has now been found that products with extraordinary quality and preservability can be obtained when the thermal treatments takes place in the presence of water vapour and under specific conditions.

Therefore, the invention relates to a method for thermally treating a product in order to have the product obtain the desired product properties, comprising the following steps:

(a) determining the water activity value which is required for carrying out the thermal treatment for having the products obtain the desired properties;

(b) contacting the product with water vapour, at an increased temperature and associated saturated vapour pressure (p^*), while the temperature on the surface of the product is 80 - 260°C;

- (c) setting a vapour pressure (p) in step (b) such that p/p^* is essentially equal
5 to the water activity value determined in step (a); and
(d) maintaining the process conditions mentioned in the steps (b) and (c) for a time duration (d) for obtaining the product with the desired product properties.

As is customary, the water activity value (a_w -value) is defined as the water vapour pressure above the food in equilibrium with its surroundings at a
10 particular temperature divided by the saturated vapour pressure of water at that particular temperature.

With the method according to the present invention, products can be roasted, baked, fried or sterilised. The products to be treated can be foods or other products, such as, for instance, manure or silt which have to be
15 sterilised.

The a_w -value to be determined corresponds to the desired product properties. When foods are concerned, for killing bacterial spores, the a_w -value during the thermal treatment is preferably 0.5-1; for killing vegetative cells the a_w -value during the thermal treatment is preferably smaller than 0.7 or
20 greater than 0.8; for promoting Maillard-reactions the a_w -value during the thermal treatment is preferably 0.4-0.8; for the prevention of enzymatic activity the a_w -value during the thermal treatment is preferably 0-0.2; and for prevention of formation of acrylamide the a_w -value during the thermal treatment will, as a rule, have to be 0.1-1. The skilled person will know from
25 experience which a_w -value is required during the thermal treatment because, as a rule, this is closely connected to the product properties of the product to be obtained.

In a preferred embodiment of the invention, the method is carried out such that the temperature on the surface of the product is 80-260°C, and the
30 p/p^* has a value of 0.15-0.95.

Therefore, the invention also relates to a method for thermally treating a product in the presence of water vapour, wherein the temperature on the surface of the product is 80-260°C, and the ratio of the vapour pressure used and the saturated vapour pressure (p/p^*) has a value of 0.15-0.95.

5 In a suitable embodiment of the method according to the invention, the temperature on the surface of the product is 80-220°C, whereupon the thermal treatment is stopped and the product is cooled.

Preferably, the method is carried out in the presence of water vapour and in absence of oxygen. The temperature of the water vapour is, suitably,
10 90-270°C, and preferably 90-230°C. Preferably, the water vapour contains superheated steam.

The foods to be treated with the method of the invention can be foods of varying nature. Suitable foods are cocoa beans, cocoa nibs, coffee beans, peanuts, nuts, soy products, (powder-form) herbs such as, for instance, basil
15 leaves or paprika powder, (powder-form) spices such as for instance pepper, potato, starch and cereal products such as, for instance, fries and crisps, and bread, cake, meat, snack and fish products.

It will be clear to the skilled person that cocoa nibs, coffee beans, peanuts, nuts, soy products will be roasted, whereas the other products can be
20 baked and/or fried.

Preferably, cocoa beans, cocoa nibs, coffee beans, nuts or peanuts are roasted while using the method of the invention, and more preferably cocoa beans or cocoa nibs. Bread, cake, meat, snack and fish products can be baked in an attractive manner with the method according to the invention.

25 Preferably, the baking is carried out such that a temperature on the surface of the food is 150-250°C.

Bread - and in particular cake products can be baked in a particularly favorable manner with the method according to the invention. The fact is that, with the invention, the content of carcinogenic acrylamides can be reduced to a
30 particular extent. This holds in particular when baking and preparing cake

products, in particular gingercakes. These favorable results can be attributed to the aw-value to be obtained which is the result of the temperature and vapour pressure to be used and the presence of water vapour. By contrast, loaves of bread and cakes are baked in known processes in the presence of dry air, that is, absence of water vapour.

Therefore, the invention also relates to a method for baking a bread or cake product in which, respectively, a bread or cake product, in the presence of water vapour, is subjected to a thermal treatment, wherein the temperature on the surface of the bread or cake product is 80-260°C, and the p/p^* (the ratio of the vapour pressure used and the saturated vapour pressure) has a value of 0.15-0.8, preferably 0.2-0.8, and more preferably 0.4-0.8. Therefore, during the thermal treatment, the bread or cake product has an aw-value of 0.15-0.8, preferably 0.2-0.8 and more preferably 0.4-0.8. The skilled person will understand that the bread or cake product which is subjected to the thermal treatment will, as a rule, be a bread or cake dough. Preferably, the baking is carried out such that the temperature on the surface of the bread or cake product is 150-250°C. Preferably, frying foods is, according to the invention, also carried out such that the temperature on the surface of the food is 150-250°C.

Different products such as manure, silt, (powder-form) herbs and/ or (powder-form) spices can be sterilised with the method according to the invention in a particularly attractive manner.

Therefore, the invention also relates to a method for sterilising a product wherein the product in the presence of water vapour is subjected to a thermal treatment, the temperature on the surface of the product being 80-260°C and a ratio of the vapour pressure and the saturated vapour pressure (p/p^*) having a value of 0.8-0.95, preferably 0.85-0.95. Therefore, the thus sterilised products have an aw-value of 0.8-0.95, preferably 0.85-0.95. Manure and silt as well as foods can be sterilised well in this manner. In particular (powder-form) herbs and/or (powder-form) spices can be sterilised particularly

attractively in this manner. Preferably, sterilising is carried out such that the temperature on the surface of the product is 110-130°C.

During roasting, baking or frying the different foods, the value of the ratio of the vapour pressure and the saturated vapour pressure (p/p^*) is, very suitably, 0.3-0.8, preferably 0.4-0.8, and more preferably 0.5-0.8. The temperature on the surface of the food depends on the type of food, and the time duration the food is heated. Therefore, without problems, the skilled person can regulate the conditions such that the food, during the thermal treatment, has the desired temperature and aw-value.

As already stated, the temperature to be used on the surface of the food will depend on the type of food to be treated. For instance, the temperature of nuts or peanuts is preferably 140-180°C, that of coffee is preferably 180-220°C, and that of cocoa preferably 80-140°C.

As a rule, the temperature of the water vapour will at least be 1°C higher than the temperature on the surface of the foods.

Depending on the food to be treated, the thermal treatment can be selected from the group of roasting, baking and frying.

The method of the invention can be carried out while using a batch system or a continuous system.

When the method takes place in a batch system, preferably, a pressure lower than 12 bara is used. For foods that can be thermally treated at relatively low temperatures, such as cocoa beans, cocoa nibs, nuts and peanuts, the pressure of the water vapour in a batch system is, preferably, below 3 bara, more preferably atmospheric. For foods that usually can be thermally treated at higher temperatures, such as coffee, in a batch system, preferably, a pressure of over 3 bara is used, and more preferably a pressure of over 5 bara but below 12 bara.

In batch systems, as a rule, the food is contacted with the water vapour for 1.5 to 120 minutes.

The method according to the invention can particularly suitably be used in a continuous system, in which the food and the water vapour (steam), preferably superheated water vapour (steam), flow in the same direction or in the opposite direction.

5 In a suitable embodiment, the continuous system comprises a vertical shaft in which, due to gravity, the food flows downwards and is contacted with the water vapour, preferably superheated water vapour, which is blown upwards into the shaft in counter flow. In a suitable embodiment, the vertical shaft has a length of 0.5 - 2 metres. The shaft can be insulated or provided
10 with a heated casing for preventing the formation of condensation on the inner wall of the shaft.

In a different suitable embodiment, the continuous system comprises a double walled tube transport within which the food with the water vapour, preferably steam, and more preferably superheated steam, as a transport
15 medium flow in the same direction within one single tube or a series of connected tubes. The tubes are provided with a heating medium, for instance thermal oil or steam. The required energy for roasting the food is, in principle, obtained from the heating medium in the double wall and not from the transport medium directly blown in, for instance steam. The tube transport
20 can have a length of some tens to some hundreds of metres depending on the desired final temperature of the food, the desired product properties, and a heating medium to be used.

If a continuous system is used, the time of treatment, that is the time duration of the contact between the food and the water vapour, can vary
25 between 10 seconds and 30 minutes. This is determined by the type of continuous system that is used in the method. For instance, the roasting time can be 10-30 minutes when a vertical shaft is used within which the food and the water vapour are contacted with each other in counter flow. When, by contrast, a double walled tube transport is used within which the water vapour
30 and the food proceed at high speed in the same direction, the roasting time

can, for instance, be 10-30 seconds. The pressure used in a continuous system depends on the aw-value to be reached but is preferably below 5 bara, and more preferably below 2 bara.

In a suitable embodiment of the invention, the foods are granular or powder-form foods.

The foods which are obtained with the method according to the invention have unique product qualities. They exhibit extraordinary flavour and odour profiles, and contain particularly low contents of thermophilic spore forming bacteria. Further, they contain surprisingly low contents of carcinogenic acrylamides. Therefore, the invention also relates to a food which can be obtained with the method according to the invention. The method according to the invention also has the advantage that the risk of a fire occurring is reduced, and the odour and dust problems towards the surroundings of the process are better controlled.

The temperature on the surface of the cocoa beans or cocoa nibs is, suitably, 80-140°C, preferably 85-135°C. The temperature on the surface of pure cocoa is preferably 80-110°C and still more preferably 85-105°C. The temperature on the surface of the cocoa beans or cocoa nibs to be used in dairy products to be sterilised is, preferably, 110-140°C, and still more preferably 115-135°C. The aw-values of the cocoa beans or cocoa nibs during roasting is preferably 0.3-0.8, more preferably 0.5-0.8, still more preferably 0.5-0.6.

Cocoa beans or cocoa nibs which have been roasted with the method according to the invention are unprecedented as to flavour profiles and aromas, while off-flavours that are naturally present can be discerned less prominently. Further, they contain a particularly low content of thermophilic spore forming bacteria. This is of importance for UHT sterilised dairy products in which cocoa has been used. It occurs that heat resistant spores from the cocoa survive the UHT treatment in the dairy industry, which, eventually, results in food decay of a dairy product intended to be preservable. As regards pure cocoa, in which the highly volatile odour and flavour components

disappear in customary roasting processes, now, with a brief roasting time and at a low temperature of for instance 90°C, an optimal product can be obtained with lower germ counts and certainly free of undesired microorganisms, such as E. coli and Salmonella. Pure cocoa which can be obtained with the method according to the invention can have a germ count of below 5,000/g while the germ count of traditionally roasted cocoa, customarily, is approximately 100,000/g. Further, the cocoa beans or cocoa nibs which can be obtained with the method according to the invention contain a surprisingly low content of carcinogenic acrylamides. While cocoa roasted in the traditional manner contains, as a rule, 350 ppb or more of acrylamides, the cocoa foods according to the invention contain less than 250 ppb of acrylamides, preferably less than 200 and more preferably less than 150 ppb of acrylamides. This same phenomenon occurs, as has already been indicated hereinabove, when baking cake products, in particular gingercakes.

15

Example 1

In a first experiment, cocoa nibs were continuously supplied to a vertical pipe (one metre long, 0.4 metre diameter, and a content of 125 litres), while the pipe was provided with a regulating valve at the underside. In counter flow, superheated steam at a pressure of 1.08 bara and a temperature of 165°C was blown into the pipe from below. The roasting temperature of the cocoa nibs was 130°C, the aw-value of the cocoa nibs during roasting was 0.4 and the roasting capacity was 88 kg/hour. The roasted product had a moisture content of 1.6%, a germ count smaller than 10/g and contained no thermophilic spore formers.

25

Example 2

An experiment was carried out in the same manner as described in Example 1 except that the roasting temperature of the cocoa nibs during roasting was 110°C, the cocoa nibs had an aw-value of 0.8 and the roasting capacity was 120

30

kg/hour. The roasted product had a moisture content of 3.36%, a germ count of 10/g and contained no thermophilic spore formers.

Example 3

- 5 Cocoa nibs of the same type were roasted while using a continuous system comprising a double walled tube (150 metres long, and a cross-section of 150 millimetres). With steam as transport medium, the cocoa nibs were blown through the tube. The steam was blown into the tube at a pressure of 2 bara while the steam temperature was 120°C. The double wall was heated by steam
- 10 at a pressure of 6 bara (160°C). The roasting temperature of the cocoa nibs was 120°C, the aw-value of the nibs was 0.8 and the roasting capacity was 3,000 kg/hour. The roasted product had a moisture content of 3.8%, a germ count of 270/g and it contained 140 ppb of acrylamides.

Example 4

- 15 Cocoa nibs of the same type were roasted in a batch drum of the Barth 7500-type. During the process, steam was blown into the drum to prevent the presence of air. The roasting temperature of the nibs was 115°C, the aw-value of the nibs during roasting was 0.6 and the batch size 3,500 kg/40 minutes.
- 20 The roasted product had a moisture content of 4.8%, a germ count smaller than 10 per gram, it contained no detectable thermophilic spore formers and contained 155 ppb of acrylamides.

- From the results shown hereinabove it will be clear that with the method
- 25 according to the invention, cocoa nibs can be obtained of an extraordinarily good quality. Further, the products obtained exhibited an extraordinary flavour and aroma profile.

Example 5

An amount of paprika powder (approximately 60 g) or an amount of basil (approximately 25 g) are placed batch-wise on a sieve plate and sterilised with superheated steam of 125°C for 5 minutes and a pressure of, successively, 1 and 2.4 bara; leading, at equilibrium, to an aw-value of 0.43 and 0.82. The results relative to the initial contamination have been summarised in the table.

Product	Temperature	aw-value	Killing off
	°C		(log)
Basil	125	0.43	1
	125	0.82	3
Paprika powder	125	0.43	2
	125	0.82	4

10

Example 6

200 g of peanuts were batch-wise placed on a sieve plate and, for five minutes, flowed through from above with superheated steam at a temperature of 160°C at a pressure of 1 bara; leading, at equilibrium, to an aw-value of the peanuts of 0.16. As to colour and flavour, the roasted peanuts could not be distinguished from traditionally roasted peanuts (reference). An acrylamide concentration of 0.05 mg/kg was found against a content of 0.18 mg/kg of the reference product.

20

Example 7

Gingercake (700 g of dough) was baked for 50 minutes in an atmosphere of superheated steam at a temperature of 155°C and a pressure of 3 bara;

leading, at equilibrium, to an aw-value of 0.54. The baked gingercake was slightly darker than the bread traditionally baked in air (reference). A concentration of acrylamide was measured of 0.200 mg/kg, while the average literature value is 0.315 mg/kg, with a maximum of 3.190 mg/kg.

5

Example 8

220 grams of oven fries were placed batch-wise on a sieve plate and flowed through from above with superheated steam with a temperature of 175°C at a pressure of 1 bara; leading, at equilibrium, to an aw-value of the oven fries of
10 0.11. As to colour and flavour, the fried oven fries could not be distinguished from traditionally air-fried oven fries (reference). A concentration of acrylamide was found of 0.26 mg/kg with a content of a 0.10 mg/kg of the starting product.

15 From the results of, in particular, Examples 6 – 8 it will be clear that also with the method according to the invention, in a particularly attractive manner, foods can be baked, fried or sterilised.

Claims

1. A method for thermally treating a product in order to have the product obtain the desired product properties, comprising the following steps:
 - (a) determining the water activity value which, for carrying out the thermal treatment, is required to have the product obtain the desired properties;
 - 5 (b) contacting the product with water vapour, at an increased temperature and an associated saturated vapour pressure (p^*), while the temperature on the surface of the product is 80 - 260°C;
 - (c) setting a vapour pressure (p) in step (b) such that p/p^* is equal to the water activity value determined in step (a); and
 - 10 (d) maintaining for a time duration (t) the process conditions mentioned in steps (b) and (c) for obtaining the product with the desired product properties.
2. A method for thermally treating a product in the presence of water vapour, wherein the temperature on the surface of the product is 80 - 260°C and the ratio of the vapour pressure and the saturated vapour pressure used
15 has a value of the 0.15 – 0.95.
3. A method according to claim 1 or 2, wherein the temperature of the surface of the product is 80 - 220°C.
4. A method according to any one of claims 1 - 3, wherein the p/p^* has a value of 0.3-0.8.
- 20 5. A method according to any one of claims 1 - 4, wherein the p/p^* has a value of 0.4-0.8.
6. A method according to any one of claims 1 - 5, wherein the p/p^* has a value of 0.5-0.8.
7. A method according to any one of claims 1 – 6, wherein the product
25 is a food and the food is roasted, baked, fried or sterilised.
8. A method according to any one of claims 1 - 7, wherein the food is sterilised and the p/p^* has a value of 0.8-0.95.

9. A method according to any one of claims 1 – 8, wherein the food is baked and the p/p^* has a value of 0.15-0.8.
10. A method according to any one of claims 1 - 9, wherein the food is treated for 10 seconds - 30 minutes.
- 5 11. A method according to any one of claims 1 – 10, which is carried out in a continuous system in which the product and the water vapour flow in the same direction or in opposite directions.
12. A method according to claim 11, which is carried out in a continuous system comprising a vertical shaft within which, due to gravity, the product
- 10 flows downwards and is contacted with water vapour which is blown upwards in the shaft in counter flow.
13. A method according to claim 11, which is carried out in a continuous system comprising a double walled tube transport within which the water vapour and the product flow in the same direction, and the double wall
- 15 comprises a heating medium.
14. A method according to any one of claims 1 - 10, which is carried out in a batch system within which the pressure is below 12 Bara.
15. A method according to any one of claims 1 - 14, wherein the water vapour comprises superheated steam.
- 20 16. A method according to any one of claims 1 – 15, wherein the product is a food which is selected from the group of cocoa beans, cocoa nibs, coffee beans, nuts, peanuts, soy products, (powder-form) herbs, (powder-form) spices, potato, starch and cereal products, and bread, cake, meat, snack and fish products.
- 25 17. A method according to claim 16, wherein the food is roasted and is selected from the group of cocoa beans, cocoa nibs, coffee beans, peanuts and nuts.
18. A method according to claim 17, wherein the food is cocoa beans or cocoa nibs.

19. A method according to claim 16, in which the food is baked and is selected from the group of the bread or cake products.

20. A method according to any one of claims 16 to 19, wherein the temperature on the surface of the food is 80 - 140°C.

5 21. A method according to claim 18 or 19, wherein the food has an aw-value of 0.4-0.8.

22. A food obtainable with the method according to any one of claims 16 - 20.

23. A food according to claim 21 comprising cocoa beans and/cocoa nibs.

INTERNATIONAL SEARCH REPORT

PCT/NL2004/000070

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 A23L1/01 A23L1/36 A23F5/04 A23N12/08 A21D8/06
A23G1/02

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A23L A23F A23N A21D A23G

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, FSTA, PAJ, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	DEVENTER VAN H ET AL: "STOOM DROOGT MEER DAN BIETENPULP" VOEDINGSMIDDELEN TECHNOLOGIE, NOORDERVLIET B.V. ZEIST, NL, vol. 34, no. 9, 27 April 2001 (2001-04-27), pages 11-13, XP001011663 ISSN: 0042-7934 the whole document	1-23
X	FR 2 792 810 A (LENFANT JEAN PIERRE) 3 November 2000 (2000-11-03) page 2, line 3 - line 24 page 4, lines 5-15 page 15, line 10 - page 17, line 16 ----- -/--	1-4, 7, 9, 10, 14-16, 22

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

19 May 2004

Date of mailing of the international search report

02/06/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+31-70) 340-3016

Authorized officer

Vuillamy, V

INTERNATIONAL SEARCH REPORT

PCT/NL2004/000070

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 308 003 A (PROCTER & GAMBLE) 22 March 1989 (1989-03-22) claims column 4, lines 9-35 column 5, lines 23-44 column 8, lines 1-30 -----	1-8,10, 11,13, 15,16, 20,22
X	FR 2 788 336 A (REVTECH) 13 July 2000 (2000-07-13) page 3, line 17 - page 4, line 31 page 6, lines 5-16 -----	1-13, 15-17,22
X	WO 87/06799 A (DANSKE SUKKERFAB) 19 November 1987 (1987-11-19) page 1, line 21 - page 2, line 21 examples -----	1-4,7,9, 10, 14-16, 20,22
X	GB 2 221 830 A (DUDEK DANIEL HENRY) 21 February 1990 (1990-02-21) page 10; table -----	1-10, 14-16, 20,22
X	US 5 075 121 A (DESAGE ROBERT ET AL) 24 December 1991 (1991-12-24) column 2, line 63. - column 4, line 9 claims -----	1-7,9, 10, 14-16, 19-22
X	GB 754 510 A (VICT TH ENGWALL M CO KOMMANDIT) 8 August 1956 (1956-08-08) page 5, lines 115-122 examples -----	1-5,9, 10, 14-16, 19,21,22
X	DATABASE FSTA 'Online! INTERNATIONAL FOOD INFORMATION SERVICE (IFIS), FRANKFURT-MAIN, DE; erilization 1984, AKAO T ET AL: "Sterilization of powdery food by superheated steam" XP002256792 Database accession no. 86-4-04-e0072 abstract & ENGINEERING AND FOOD, vol. 2, 1984, pages 595-600, JAPAN -----	1-9,11, 15-18, 20-23
	----- -/--	

INTERNATIONAL SEARCH REPORT

PCT/NL2004/000070

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 061 305 A (KIKKOMAN CORP) 29 September 1982 (1982-09-29) page 6, line 1 - page 7, line 9 figures; examples -----	1-7, 9-11,15, 16,20,22
X	WO 95/20325 A (AJINOMOTO GENERAL FOODS INC ; MAKI YOSHIKI (JP); HARUYAMA TSUTOMU (JP) 3 August 1995 (1995-08-03) claims; table I -----	1-7,9, 10, 14-17,22
X	PATENT ABSTRACTS OF JAPAN vol. 0171, no. 35 (C-1037), 19 March 1993 (1993-03-19) & JP 4 311352 A (FUJI OIL CO LTD), 4 November 1992 (1992-11-04) abstract -----	1-3, 14-18, 20-23
X	US 4 456 625 A (DURST JACK R) 26 June 1984 (1984-06-26) claims; examples -----	22
A	PATENT ABSTRACTS OF JAPAN vol. 0101, no. 12 (C-342), 25 April 1986 (1986-04-25) & JP 60 241859 A (KIKKOMAN KK), 30 November 1985 (1985-11-30) abstract; figure -----	12

INTERNATIONAL SEARCH REPORT

PCT/NL2004/000070

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
FR 2792810	A	03-11-2000	FR 2792810 A1 AU 4306500 A WO 0065931 A1	03-11-2000 17-11-2000 09-11-2000
EP 0308003	A	22-03-1989	US 4911889 A AT 86504 T AU 2233088 A CA 1319617 C DE 3879057 D1 DE 3879057 T2 EP 0308003 A2 ES 2038741 T3 GR 3007297 T3 US 5229117 A	27-03-1990 15-03-1993 16-03-1989 29-06-1993 15-04-1993 22-07-1993 22-03-1989 01-08-1993 30-07-1993 20-07-1993
FR 2788336	A	13-07-2000	FR 2788336 A1	13-07-2000
WO 8706799	A	19-11-1987	WO 8706799 A1	19-11-1987
GB 2221830	A	21-02-1990	AT 141465 T AU 613515 B2 AU 4056589 A BR 8903785 A BR 8907041 A CA 1339928 C CN 1041003 A ,B DE 68926998 D1 DE 68926998 T2 EP 0382835 A1 ES 2014825 A6 GR 89100481 A ,B HK 71493 A IN 170212 A1 JP 2840351 B2 JP 3500723 T PT 91301 A ,B SG 125192 G WO 9000865 A1	15-09-1996 01-08-1991 19-02-1990 20-03-1990 02-01-1991 30-06-1998 04-04-1990 26-09-1996 06-03-1997 22-08-1990 16-07-1990 27-06-1990 30-07-1993 29-02-1992 24-12-1998 21-02-1991 08-02-1990 25-06-1993 08-02-1990
US 5075121	A	24-12-1991	FR 2629569 A1 AT 106689 T CA 1339848 C DE 68915845 D1 DE 68915845 T2 EP 0335796 A1 ES 2057158 T3 US 5215000 A	06-10-1989 15-06-1994 28-04-1998 14-07-1994 26-01-1995 04-10-1989 16-10-1994 01-06-1993
GB 754510	A	08-08-1956	NONE	
EP 0061305	A	29-09-1982	JP 57153654 A JP 1599474 C JP 57152863 A JP 63050984 B DE 3261422 D1 EP 0061305 A1	22-09-1982 31-01-1991 21-09-1982 12-10-1988 17-01-1985 29-09-1982
WO 9520325	A	03-08-1995	JP 2535123 B2	18-09-1996

INTERNATIONAL SEARCH REPORT

Information on patent family members

PCT/NL2004/000070

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9520325	A	JP 6046755 A	22-02-1994
		WO 9520325 A1	03-08-1995
		AU 5891594 A	15-08-1995
		CA 2180840 A1	03-08-1995
		DE 69406805 D1	18-12-1997
		DE 69406805 T2	19-03-1998
		DK 732880 T3	27-07-1998
		EP 0732880 A1	25-09-1996
		GR 3025963 T3	30-04-1998
		HU 74957 A2	28-03-1997
		LV 11662 A ,B	20-02-1997
		PL 315556 A1	12-11-1996
		SK 94596 A3	05-03-1997
		US 5681607 A	28-10-1997
JP 4311352	A	04-11-1992	NONE
US 4456625	A	26-06-1984	
		AU 561557 B2	14-05-1987
		AU 1560783 A	22-12-1983
		BR 8303157 A	31-01-1984
		CA 1190429 A1	16-07-1985
		DE 3365854 D1	09-10-1986
		DE 97038 T1	02-08-1984
		DK 272283 A	15-12-1983
		EP 0097038 A1	28-12-1983
		ES 8406171 A1	01-11-1984
		IE 54629 B1	20-12-1989
		JP 59059136 A	04-04-1984
		MX 7588 E	19-12-1989
		NO 832114 A ,B;	15-12-1983
		US 4511585 A	16-04-1985
JP 60241859	A	30-11-1985	
		JP 1390561 C	23-07-1987
		JP 61052657 B	14-11-1986