



US00RE47358E

(19) **United States**  
(12) **Reissued Patent**  
**Jeon**

(10) **Patent Number:** **US RE47,358 E**  
(45) **Date of Reissued Patent:** **Apr. 16, 2019**

(54) **METHOD FOR PREDICTING A BI-PREDICTIVE BLOCK OF A MOVING PICTURE**

(71) Applicant: **LG ELECTRONICS INC.**, Seoul (KR)

(72) Inventor: **Byeong Moon Jeon**, Seoul (KR)

(73) Assignee: **LG ELECTRONICS INC.**, Seoul (KR)

(21) Appl. No.: **14/669,487**

(22) Filed: **Mar. 26, 2015**

**Related U.S. Patent Documents**

Reissue of:

(64) Patent No.: **8,548,053**  
Issued: **Oct. 1, 2013**  
Appl. No.: **10/335,331**  
Filed: **Dec. 31, 2002**

(30) **Foreign Application Priority Data**

Apr. 9, 2002 (KR) ..... 10-2002-0019262  
Nov. 21, 2002 (KR) ..... 10-2002-0072862

(51) **Int. Cl.**

**H04N 7/12** (2006.01)  
**H04N 11/02** (2006.01)  
**H04N 11/04** (2006.01)  
**H04N 19/137** (2014.01)  
**H04N 19/503** (2014.01)

(Continued)

(52) **U.S. Cl.**

CPC ..... **H04N 19/137** (2014.11); **H04N 19/00** (2013.01); **H04N 19/139** (2014.11); **H04N 19/503** (2014.11); **H04N 19/51** (2014.11); **H04N 19/513** (2014.11); **H04N 19/52** (2014.11); **H04N 19/573** (2014.11); **H04N 19/577** (2014.11); **H04N 19/58** (2014.11); **H04N 19/61** (2014.11)

(58) **Field of Classification Search**

CPC .... H04N 19/00; H04N 19/503; H04N 19/139; H04N 19/51; H04N 19/61; H04N 19/573; H04N 19/58; H04N 19/577; H04N 19/137; H04N 19/513; H04N 19/52  
USPC ..... 375/240.15  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

5,838,872 A 11/1998 Kawara  
5,991,447 A \* 11/1999 Eifrig et al. .... 382/236  
(Continued)

**FOREIGN PATENT DOCUMENTS**

CN 1302510 A 7/2001  
CN 1526204 9/2004  
(Continued)

**OTHER PUBLICATIONS**

Flierl et al., "Generalized B Pictures and the Draft H.26L Video Compression Standard", pp. 1-11, IEEE Transactions on Circuits and Systems for Video Technology.

(Continued)


*Primary Examiner* — Christina Y. Leung

(74) *Attorney, Agent, or Firm* — Dentons US LLP

(57) **ABSTRACT**

In the method for predicting a bi-predictive block of a moving picture, first and second distinct motion-compensated blocks are obtained using first and second motion vectors respectively. The bi-predictive block of the moving picture is predicted using first and second variable weight factors associated with the first and second distinct motion-compensated blocks, respectively.

**2 Claims, 2 Drawing Sheets**



- (51) **Int. Cl.**  
*H04N 19/139* (2014.01)  
*H04N 19/51* (2014.01)  
*H04N 19/61* (2014.01)  
*H04N 19/52* (2014.01)  
*H04N 19/58* (2014.01)  
*H04N 19/577* (2014.01)  
*H04N 19/513* (2014.01)  
*H04N 19/00* (2014.01)  
*H04N 19/573* (2014.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,658,056 B1	12/2003	Duruoz et al.	
6,816,552 B2 *	11/2004	Demos .....	375/240.15
7,720,152 B2 *	5/2010	Boyce .....	H04N 19/577 375/240.12

FOREIGN PATENT DOCUMENTS

EP	0 863 674 A2	9/1998
EP	0 863 674 A3	12/2002
JP	2-192378	7/1990
JP	2-285816	11/1990
JP	9-163376	6/1997
JP	2004-088722	3/2004
JP	2006-501761	1/2006
JP	2006-501761 A	1/2006
WO	98/44743 A1	10/1998
WO	WO 98/44743	10/1998
WO	01/33864 A1	5/2001
WO	WO 01/33864	5/2001
WO	02/43399 A2	5/2002
WO	03/007119 A2	1/2003
WO	2004/032506 A1	4/2004
WO	WO 2004/032506	4/2004

OTHER PUBLICATIONS

M.-K. Kim and J.-K. Kim, "Efficient motion estimation algorithm for bi-directional prediction scheme", pp. 632-633, IEE Electronics Letters, published Apr. 14, 1994, vol. 30 No. 8. E.

Kondo, Satoshi et al. "Proposal of Minor Changes to Multi-Frame Buffering Syntax for Improving Coding Efficiency of B-pictures." Joint Video Team (JVT) of ISO/IEC MPEG & ITU-T VCEG (ISO/IEC JTC1/SC29/WG11 and ITU-T SG16 Q.6); 2nd Meeting: Geneva, CH, Jan. 29-Feb. 1, 2002.

Japanese Office Action dated Jul. 5, 2005.

Tsuhuan Chen et al., "A New Frame Interpolation Scheme for Talking Head Sequences", Proceedings of the International Conference on Image Processing. (ICIP). Washington, Oct. 23-26, 1995, Los Alamitos, IEEE Comp. Soc. Press, US, vol. 3, Oct. 23, 1995 (Oct. 23, 1995), pp. 591-594, XP010197038 ISBN: 0-7803-3122-2, paragraph [0002].

Office Action by Japanese Patent Office, dated Jul. 6, 2010, for Appl. No. 2006-000627.

Office Action by German Patent Office dated Jun. 15, 2010, for Appl. No. 103 62 305.1-55.

Japanese Office Action dated Sep. 28, 2010, dated Oct. 5, 2010; issued in Application No. JP 2008-053958.

Office Action by Japanese Patent Office, dated Apr. 20, 2010, for Appl. No. 2008-053845.

Office Action by Japanese Patent Office dated Apr. 20, 2010, for Appl. No. 2008-053934.

Office Action by Japanese Patent Office, dated Apr. 20, 2010, for Appl. No. 2008-053982.

Office Action by Japanese Patent Office, dated Apr. 20, 2010, for Appl. No. 2008-053850.

U.S. Office Action dated Oct. 2, 2012 for U.S. Appl. No. 11/042,083.

U.S. Office Action dated Sep. 14, 2012 for U.S. Appl. No. 11/042,051.

ITU—Telecommunications Sector, Video Coding Experts Group, Improved Direct mode for B pictures in TML, Aug. 8, 2000, Study Group 16, Question 15, pp. 1-2.\*

Joint video team of ISO/IEC MPEG and ITU-T VCEG, Working Draft No. 2 Revision 2, Mar. 15, 2002, pp. 13, 18-28, 33-34, and 60-68.\*

Kondo, Satoshi et al. "New Prediction Method to Improve B-picture Coding Efficiency." ITU—Telecommunications Standardization Sector; Study Group 16 Question 6, Video Coding Experts Group (VCEG). 15<sup>th</sup> Meeting, Pattaya: Thailand, Dec. 4-6, 2001.

European Combined Search and Examination Report, Apr. 1, 2005. Thomas Wiegand; "Joint Model No. 1, Revision 1(JM-IRL)"; Itu Study Group 16—Video Coding Experts Group; Dec. 3, 2001; pp. 1, 3-75; XP-001086627.

European Search Report dated Jan. 31, 2008.

Document Q15-K-44, ITU—Telecommunications Standardization Sector, Study Group 16, Video Coding Experts Group (Question 15), Eleventh Meeting, Portland, Oregon, USA, Aug. 22-25, 2000.

Document JVT-B057, Joint Video Team (JVT) of ISO/IEC MPEG & ITU-T VCEG, 2<sup>nd</sup> Meeting: Geneva, CH, Jan. 29-Feb. 1, 2002.

U.S. Office Action mailed Oct. 2, 2012 for U.S. Appl. No. 11/042,083.

U.S. Office Action mailed Sep. 14, 2012 for U.S. Appl. No. 11/042,051.

Office Action for corresponding Japanese Application No. 091565 dated Jul. 28, 2011.

Lillevoid, K. "Improved Direct Mode for B Pictures in TML" Aug. 22, 2000, ITU—Telecommunications Standardization Sector Study Group 16, Video Coding Experts Group, Eleventh Meeting, document Q15-K-44, 3 pages.

MPEG-4, Sep. 30, 1998, 6 pages.

Sullivan, G. "Announcement of the Eleventh Meeting of Experts Group for ITU-T Q15/SG16—Advanced Video Coding, Portland, Oregon, Aug. 22-25, 2000", 12 pages.

List of Meeting Attendees for the ITU Work on Advance Video Coding, Q15/16, 3 pages.

Eleventh Meeting of ITU-T Q.15/SG16 Advanced Video Coding Experts Group, Aug. 21-14, 2000, Meeting Plan, 5 pages.

List of Documents for the Eleventh Meeting ITU-T Q.15/SG16 Video Coding Experts Group, 6 pages.

Transfer of ftp://standards.pictel.com to ITU, 3 pages.

Ishtiaq, F. et al., "A Rate Control Method for H.263 Temporal Scalability," Department of Electrical and Computer Engineering, Northwestern University, 1999.

Joint Video Team (JVT) of ISO/IEC MPEG and ITU-T VCEG, Draft International Standard, May 6-10, 2002, pp. 1-131.

\* cited by examiner

FIG. 1  
CONVENTIONAL ART




FIG. 2




FIG. 3





FIG. 4



**METHOD FOR PREDICTING A  
BI-PREDICTIVE BLOCK OF A MOVING  
PICTURE**

**Matter enclosed in heavy brackets [ ] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue; a claim printed with strikethrough indicates that the claim was canceled, disclaimed, or held invalid by a prior post-patent action or proceeding.**

FOREIGN PRIORITY INFORMATION

The present invention *is a continuation reissue of U.S. patent application Ser. No. 10/335,331 (now U.S. Pat. No. 8,548,053), issued on Oct. 1, 2013, and claims priority under 35 U.S.C. 119 on Korean Application No. 10-2002-0019262 filed Apr. 9, 2002 and Korean Application No. 10-2002-0072862 filed Nov. 21, 2002; the contents of which are hereby incorporated by reference in their entirety.*

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a moving picture coding system.

2. Description of the Background Art

A moving picture coding system is able to have higher coding efficiency with a B picture (a predicted image that may be based on the motion vectors) than the coding efficiency when using only P pictures (a predicted image based on one motion vector).

For the B picture, the block prediction method for a direct mode involves calculating a forward motion vector and a backward motion vector as scaled versions of a motion vector of a co-located block in a backward reference picture for direct mode, to then obtain two distinct motion-compensated blocks using the forward and backward motion vectors, respectively. A predicted block is then obtained by averaging the two motion-compensated blocks.

The block prediction method for the direct mode as described above will be described in more detail with reference to FIG. 1.

FIG. 1 is a view showing a picture pattern for describing the block prediction method for the direct mode according to the conventional art. The picture pattern comprises an I-picture (not shown) coded using prediction only from decoded samples within the same picture (e.g., intra prediction), P pictures P1, P4, and P7 coded by inter prediction using at most one motion vector from previously-decoded reference pictures, and B-pictures B2, B3, B5 and B6 coded by two inter prediction blocks from previously-decoded reference pictures.

Also, parameters shown in FIG. 1 will first be described first for the sake of convenience.  $TR_D$  represents a temporal distance between a forward reference picture for direct mode (P1) and a backward reference picture for direct mode (P7),  $TR_B$  represents a temporal distance between the forward reference picture for direct mode (P1) and a current B picture (B5),  $MV$  represents a motion vector of a co-located block in the backward reference picture for direct mode (P7),  $MV_f$  represents a forward motion vector of direct mode pointing to the forward reference picture for direct mode, and  $MV_b$  represents a backward motion vector of direct mode pointing to the backward reference picture for direct mode. Herein, the forward reference picture for direct mode

is a reference picture pointed by the motion vector of the co-located block in the backward reference picture for direct mode.

The block prediction method for direct mode will be described using the above parameters as follows.

First, the forward motion vector of direct mode ( $MV_f$ ) is obtained from a motion vector ( $MV$ ) of a co-located block  $B_s$  in the backward reference picture for direct mode (P7) by applying following equation (1).

$$MV_f = \frac{TR_B \times MV}{TR_D} \quad (1)$$

In addition, the backward motion vector of direct mode ( $MV_b$ ) is obtained from a motion vector ( $MV$ ) of the co-located block  $B_s$  in the backward reference picture for direct mode (P7) by applying following equation (2).

$$MV_b = (TR_B - TR_D) \times \frac{MV}{TR_D} \quad (2)$$

Therefore, blocks  $B_f$  and  $B_b$  are motion-compensated using the motion vectors  $MV_f$  and  $MV_b$  calculated from equations (1) and (2), and after that, the two blocks are averaged to get a prediction value  $B'_c$  of a current block  $B_c$  in the B picture as following equation (3).

$$B'_c = \frac{B_f + B_b}{2} \quad (3)$$

However, according to the block prediction method for the direct mode of the conventional art, the forward motion vector of direct mode is obtained from the motion vector of the co-located block in the backward reference picture for direct mode, and therefore, the obtained value is just an approximated value, not a precise motion vector of the current block of the B picture.

Also, according to the block prediction method for direct mode of the conventional art, even though the reference picture temporally close to the B picture has higher similarity with the B picture, the block prediction is made using the average of two distinct motion-compensated blocks without considering temporal distance between the reference pictures. Therefore, the accuracy of predicted block is lowered.

Especially, in a sequence having a fading scene, since brightness of continuous B pictures can be gradually darkened or gradually lightened, the prediction value obtained by simply averaging two motion-compensated blocks can differ significantly from the original value, and thereby the coding efficiency of the entire system is greatly lowered.

SUMMARY OF THE INVENTION

The present invention provides a method for predicting a bi-predictive block of a moving picture.

In one embodiment, first and second distinct motion-compensated blocks are obtained using first and second motion vectors respectively. The bi-predictive block of the moving picture is predicted using first and second variable weight factors associated with the first and second distinct motion-compensated blocks, respectively.

In an embodiment, each of the first and second variable weight factors is dependant on a temporal distance between the moving picture and a reference picture pertaining to one of the first and second distinct motion-compensated blocks. The temporal distance may be derived using display order information allocated to the moving picture and the reference picture.

In another embodiment, the bi-predictive block is predicted using a equation that includes a sum of a first value multiplied by the first variable weight factor and a second value multiplied by the second variable weight factor. In the equation, the first and second values represent the first and second distinct motion-compensated blocks, respectively.

### BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this specification, illustrate embodiments of the invention and together with the description serve to explain the principles of the invention.

In the drawings:

FIG. 1 is a view showing a picture pattern for describing a block prediction method for direct mode according to the conventional art;

FIG. 2 is a view showing a picture pattern for describing a block prediction method according to the present invention;

FIG. 3 is a view showing a picture pattern for describing an interpolative prediction method according to an embodiment of the present invention; and

FIG. 4 is a view showing a picture pattern for describing an interpolative prediction method according to another embodiment of the present invention.

### DETAILED DESCRIPTION OF THE EXAMPLE EMBODIMENTS

Reference will now be made in detail to the example embodiments of the present invention, examples of which are illustrated in the accompanying drawings.

In a block prediction method, for example in a direct mode, according to the present invention, a forward motion vector and a backward motion vector of a direct mode may be calculated from a motion vector of a co-located block in a backward reference picture for direct mode. Then, two motion-compensated blocks are obtained using the above motion vectors, and a predicted block is obtained by interpolation using the two motion-compensated blocks.

Also, in the block prediction method according to the present invention, the backward motion vector may be calculated from the backward reference picture for direct mode, a forward motion vector of direct mode may be calculated from the reference picture closest to the current B picture among the forward reference pictures, motion-compensated blocks may be obtained from the above motion vectors, and a predicted block may be obtained by interpolation using the two motion-compensated blocks.

Hereinafter, embodiments of the present invention will be described with reference to accompanying Figures as follows.

FIG. 2 shows a picture pattern for describing the block prediction method for direct mode according to the present invention. The picture pattern comprises an I-picture (not shown) coded using prediction only from decoded samples within the same picture, P pictures P1, P4, and P7 coded by inter prediction using at most one motion vector from

previously-decoded reference pictures, and B-pictures B2, B3, B5 and B6 coded by two inter prediction blocks from previously-decoded reference pictures.

Parameters shown in FIG. 2 will be described first for the sake of convenience.  $TR_D$  represents a temporal distance between a forward reference picture for direct mode (P1) and a backward reference picture for direct mode (P7),  $TR_B$  represents a temporal distance between the forward reference picture for direct mode (P1) and a current B picture (B5),  $TR_N$  represents a temporal distance between the reference picture (P4) closest to the current B picture and the current B picture (B5),  $MV$  represents a motion vector of a co-located block in the backward reference picture for direct mode (P7),  $MV_f'$  represents a forward motion vector of direct mode pointing to the reference picture (P4) closest to the current B picture, and  $MV_B$  represents a backward motion vector of direct mode pointing to the backward reference picture for direct mode (P7).

The motion vector ( $MV$ ) of the co-located block  $B_s$  in the backward reference picture for direct mode (P7) is established in the process of coding (or decoding) the backward reference picture for direct mode before the current B picture is coded (or decoded).

The block prediction method for direct mode as constructed above according to the present invention will be described as follows.

The forward motion vector ( $MV_f'$ ), which points to the reference picture (P4) having the closest temporal distance among the forward reference pictures, is obtained from following equation (4).

$$MV_f' = \frac{TR_N \times MV}{TR_D} \quad (4)$$

In addition, the backward motion vector ( $MV_b$ ), which points to the backward reference picture for direct mode (P7), is obtained according to the conventional art using equation (2) reproduced below.

$$MV_b = (TR_B - TR_D) \times \frac{MV}{TR_D} \quad (2)$$

Accordingly, motion-compensated blocks  $B_f$  and  $B_b$  are obtained using the motion vectors  $MV_f'$  and  $MV_b$  calculated in the convention manner, but using the motion vectors from equations (2) and (4).

However, the block prediction method according to the present invention may be applied to the example situations in either FIG. 1 or FIG. 2. Therefore, the reference picture in which the motion-compensated block  $B_f$  exists may be the forward reference picture for direct mode (for example, P1 picture in FIG. 1) or the reference picture closest to the B picture (for example, P4 picture in FIG. 2). It will be appreciated that these are only two example situations, and that the present invention is not limited to these two examples.

The block prediction method according to the present invention performs interpolative prediction considering the temporal distance between the current B picture and the reference picture in which the motion-compensated block  $B_f$  exists (that is, the forward reference picture for direct mode or the reference picture closest to the B picture in the two example situations of FIGS. 1 and 2), and considering the

5

temporal distance between the current B picture and the backward reference picture for direct mode.

As shown in FIG. 3, if the forward motion vector of direct mode is obtained using the conventional art, the motion-compensated block  $B_f$  exists in the forward reference picture for direct mode (P1) and the motion-compensated block  $B_b$  exists in the backward reference picture for direct mode (P7). The interpolative prediction is performed according to equation (5) below. Herein,  $TR_D$  is the temporal distance between the forward reference picture for direct mode (P1) and the backward reference picture for direct mode (P7), and  $TR_B$  is the temporal distance between the forward reference picture for direct mode (P1) and the current B picture (B5). As shown in Equation (5), the interpolative predictive method involves taking a weighted average of the two motion-compensated blocks  $B_f$  and  $B_b$ . The weighting of the motion-compensated block  $B_f$  is based on the temporal difference between the current picture (B5) and the reference picture (P7), which is related to the motion-compensated block  $B_b$ . The weighting of the motion-compensated block  $B_b$  is based on the temporal difference between the current picture (B5) and the reference picture (P1), which is related to the motion-compensated block  $B_f$ . Also, as will be appreciated from equation (5), each weight may be expressed as a function of the other weight.

$$B'_C = B_f \times \frac{(TR_D - TR_B)}{TR_D} + B_b \times \frac{TR_B}{TR_D} \quad (5)$$

Also, FIG. 4 shows the case that the forward motion vector of direct mode is obtained according to the embodiment of the present invention where the motion-compensated block  $B_f$  exists in the reference picture (P4) closest to the current B picture and the motion-compensated block  $B_b$  exists in the backward reference picture for direct mode (P7). Therefore, the interpolative prediction is performed as shown in equation (6) below. Herein,  $TR_D$  is the temporal distance between the forward reference picture for direct mode (P1) and the backward reference picture for direct mode (P7), and  $TR_B$  is the temporal distance between the forward reference picture for direct mode (P1) and the current B picture, and  $TR_N$  is the temporal distance between the reference picture (P4) closest to the current B picture and the current B picture.

$$B'_C = B_f \times \frac{(TR_D - TR_B)}{(TR_N + TR_D - TR_B)} + B_b \times \frac{TR_N}{(TR_N + TR_D - TR_B)} \quad (6)$$

Again, as shown in equation (6), the interpolative predictive method involves taking a weighted average of the two motion-compensated blocks  $B_f$  and  $B_b$ . The weighting of the motion-compensated block  $B_f$  is based on the temporal difference between the current picture (B5) and the reference picture (P7), which is related to the motion-compensated block  $B_b$ . The weighting of the motion-compensated block  $B_b$  is based on the temporal difference between the current picture (B5) and the reference picture (P4), which is related to the motion-compensated block  $B_f$ . Also, as will be appreciated from equation (6), each weight may be expressed as a function of the other weight.

The respective pictures may also be represented or referenced using display order information such as a picture order count. Here, equations (5) and (6) may be represented as equation (7) below using the picture order count values,

6

which are display order information of the respective pictures. Herein,  $T_c$  is a picture order count value, that is, the display order information allocated to the current B picture;  $T_f$  is a picture order count value, that is, the display order information allocated to the forward reference picture for direct mode or a picture order count value, that is, the display order information allocated to the reference picture closest to the B picture in case that the forward motion vector is calculated by the equation (4); and  $T_b$  is a picture order count value, that is, the display order information allocated to the backward reference picture for direct mode.

$$B'_C = B_f \times \frac{(T_b - T_c)}{(T_b - T_f)} + B_b \times \frac{(T_c - T_f)}{(T_b - T_f)} \quad (7)$$

In this example, equation (7) shows that the interpolative prediction method involves taking a weighted average of the two motion-compensated blocks  $B_f$  and  $B_b$ . Here, the weighting of the motion-compensated block  $B_f$  is based on the picture order count difference between the picture order count of the current block (B5) and the picture order count of the reference picture (P7) related to the motion-compensated block  $B_b$ ; and the weighting of the motion-compensated block  $B_b$  is based on the picture count difference between the picture order count of the current block (B5) and the picture order count of the reference picture (P1) or (P4) related to the motion compensated block  $B_f$ . Also, as will be appreciated from equation (7), each weight may be expressed as a function of the other weight.

As described above, according to the present invention, the forward motion vector for direct mode is obtained from the motion vector of the co-located block in the backward reference picture for direct mode, and a predicted block of the B picture, which is about to be coded, is obtained by applying interpolative prediction to the motion-compensated block values. Therefore, the coding efficiency is improved.

Also, according to the present invention, the forward motion vector of direct mode may be obtained from the reference picture closest to the B picture which is about to be coded (or decoded) presently and having higher similarity with the B picture. The predicted block of the B picture may then be obtained by applying the interpolative prediction to the blocks which are motion-compensated from the above forward motion vector and backward motion vector. Therefore, the accuracy of the predicted block can be improved and the coding efficiency can be improved.

As the present invention may be embodied in several forms without departing from the spirit or essential characteristics thereof, it should also be understood that the above-described embodiments are not limited by any of the details of the foregoing description, unless otherwise specified, but rather should be construed broadly within its spirit and scope, and therefore all changes and modifications, or equivalences are therefore intended to be embraced by the invention.

What is claimed is:

1. A method for a [decoding device] *moving picture coding system* to predict a bi-predictive block of a current picture, the method comprising:

deriving[, by the decoding device,] a first picture order count allocated to a first picture wherein the first picture is a reference picture of the current picture;

deriving[, by the decoding device,] a second picture order count allocated to the current picture;

deriving[, by the decoding device,] a third picture order count allocated to a second picture;

deriving[, by the decoding device,] a fourth picture order count allocated to a third picture, wherein the second picture is a reference picture of the third picture; 5

scaling[, by the decoding device,] a motion vector of a block in the third picture based on the first, second, third and fourth picture order counts to [calculate] obtain a first motion vector for the bi-predictive block;

determining[, by the decoding device,] a first motion-compensated block in the first picture by using the first motion vector; and

predicting[, by the decoding device,] the bi-predictive block by using the first motion-compensated block[, respectively]. 15

wherein the first picture order count, the second picture order count, the third picture order count, and the fourth picture order count are values counted in display order.

2. *The method of claim 1, wherein the first picture is a closest reference picture of the current picture.* 20

\* \* \* \* \*