



- (51) **International Patent Classification:**
A61B 10/00 (2006.01) *A61F 6/08* (2006.01)
- (21) **International Application Number:**
PCT/EP2014/070710
- (22) **International Filing Date:**
26 September 2014 (26.09.2014)
- (25) **Filing Language:** English
- (26) **Publication Language:** English
- (30) **Priority Data:**
1317149.1 26 September 2013 (26.09.2013) GB
- (71) **Applicant:** VIVOSENSMEDICAL GMBH [DE/DE];
Ferdinand-Rhode-Str. 20, 04107 Leipzig (DE).
- (72) **Inventors:** KERSKEN, Tim; Datenspiel, Ferdin-
and-Rhode-Str. 20, 04107 Leipzig (DE). ALEXANDER,
Henry; Kurt Huber Weg 4, 04299 Leipzig (DE).
- (74) **Agent:** SCHREITER, Christoph; Schreiter-IP, Stauden-
rauchstr. 19, 80939 Munich (DE).
- (81) **Designated States** (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY,

BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM,
DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT,
HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR,
KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG,
MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM,
PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC,
SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN,
TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

- (84) **Designated States** (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ,
TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU,
TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE,
DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU,
LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK,
SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, KM, ML, MR, NE, SN, TD, TG).

Published:

- with international search report (Art. 21(3))
- before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments (Rule 48.2(h))

(54) **Title:** OVULATION DETERMINATION




Fig. 5

(57) **Abstract:** The present disclosure relates to a method and a system for determining the fertility status of a female. The method comprises the steps of determining and recording a continuous series of temperature data points relating to a body temperature of the female, identifying if the series of temperature data points comprises at least one pre-determined feature in the series of temperature data points and, if a pre-determined feature has been identified, determining a point in time of ovulation for the series of temperatures based on a pre-determined relation of the pre-determined feature and ovulation.

DescriptionTitle: Ovulation Determination

The present application claim priority to GB 131 71 49.1, filed on 26 September 2013, the
5 entire content of which is incorporated by reference herewith.

Field of the invention

[0001] The present invention relates to a method and a system for determining the
fertility status of a female based on body temperatures.

10

Introduction

[0002] Fertility is one of the most important health care aspects in the society. Fertility
and fecundity are associated with several factors such as psychological, environmental
and chemical factors. The increasing influence of environmental factors and knowledge
15 about the associated risks to such factors are leading to a growing need for methods by
which the fertility of the population can be assessed without significant encroachment of
the personal circumstances of test persons. The lack of available methods for fertility
screening for women is discussed in Reproduction Toxicology (1990), Vol. 4, Pages 1-2.
Measurement methods for the evaluation of the menstrual cycle and fertility of women
20 are much needed that will not encroach on their daily routines.

[0003] Determining fertility either for family planning or for contraception is a critical
approach of the female health care system and precise determination of ovulation is
required. So far, some indirect methods to determine the ovulation in women are based
25 on serum hormone levels or measurement of the basal body temperature. The method
using serum hormone levels is reliable but the wide employment of laboratory diagnostic
methods that are required for these measurements in urine leads to substantial costs.
Otherwise, a postovulatory rise in the temperature of about 0.5°C (+/- 0.1 °C) has been
documented in the evaluation of the course of the menstrual cycle. This temperature rise
30 is due to the circadian variations of the body core temperature amount to ± 0.5 °C.

[0004] Conventional methods are based on the estimation of a basal temperature, the lowest temperature during a day. This usually is in the morning after wake up and involves an inconvenient temperature measurement right after waking up. A change in this basal temperature is used as an indication for ovulation. This method is not very reliable.

[0005] There is a need to provide a reliable forecast for ovulation in a female and to determine the actual fertility status of the woman or female.

10 Summary of the invention

[0006] The present disclosure suggests a method and a system for determining the fertility status of a female as outlined in the independent claims. Optional additional features are presented in the dependent claims.

15

[0007] In one aspect, the method comprises the steps of determining and recording a continuous series of temperature data points relating to a body temperature of the female, identifying if the series of temperature data points comprises at least one pre-determined feature in the series of temperature data points and, if a pre-determined feature has been identified, determining a point in time of ovulation for the series of temperatures based on a pre-determined relation of the pre-determined feature and ovulation.

20

[0008] In another alternative or additional aspect, the method comprises the steps of determining and recording a plurality of temperature curves over a menstrual cycle of the female, the temperature curve relating to a body temperature of the female, analysing the homogeneity of each one of the plurality of temperature curves and determining if the homogeneity has a break, determining a point in time of the break in the menstrual cycle of the female, and estimating a point of time of ovulation in the menstrual cycle of the female and out-putting the estimated point of time of ovulation.

30

[0009] In another aspect, the system comprises a temperature measurement device for determining and recording a series of temperature data points relating to a body temperature of the female and an analysing tool for analysing the series of temperature data points. The series of temperature data points are transferred from the temperature measurement device to the analysing tool. The analysing tool performs the steps of identifying if the series of temperature data points comprises at least one pre-determined feature in the series of temperature data points and, if a pre-determined feature has been identified, determining a point in time of ovulation for the series of temperature data points based on a pre-determined relation of the pre-determined feature and ovulation.

[0010] In yet another aspect, the analysing tool performs the steps of analysing the homogeneity of each one of the plurality of temperature curves and determining if the homogeneity has a break, determining a point in time of the break in the menstrual cycle of the female, and estimating a point of time of ovulation in the menstrual cycle of the female and outputting the estimated point of time of ovulation.

[0011] The methods and systems of the present disclosure improve prognosis of ovulation and thus the termination of the fertility status of the female.

20

Description of the figures

[0012] The invention may be better understood when reading the detailed description of examples of the present disclosure which is given with respect to the accompanying figures in which:

25

Figs. 1 shows a pessary that may be used with the present disclosure

Figs. 2a and 2b show examples of temperature curves that may be determined with the analysing system of Fig. 1;

Fig. 3 illustrates a method for determining the point of ovulation based on homogeneity analysis;

30

Figs 4a and 4b show the temperature curves of Figures 2a and 2b, with and without analysed break, respectively;

Fig. 5 shows examples of features that may be used with pattern or feature analysis;

Fig. 6 shows further examples of a pattern analysis; and

5 Fig. 7 illustrates a method for determining the point of ovulation based on pattern analysis.

Detailed description

10 [0013] Examples of the present disclosure will now be described in more detail. It is to be understood that the described examples and the examples shown in the figures are purely illustrative and a person skilled in the art will amend the examples according to specific requirements. It is not necessary to implement all features shown in the examples and a person skilled in the art will combine features shown or described with respect to
15 one figure with examples shown in other figures or described elsewhere in the present disclosure.

[0014] Determining fertility either for family planning or for contraception is a critical approach of the female health care system and precise determination of ovulation is
20 required. The present disclosure seeks to provide a woman a prognosis of the “fertility window” when the ovulation may occur.

[0015] The present disclosure relates to a method and a system for determining a fertility status of a female by measuring a body core temperature and for determining a prognosis
25 for ovulation.

[0016] The present invention provides a method for determining the fertility status of the female by using data determined by a temperature sensor placed in the vaginal channel of the female. An example of a temperature sensor that may be used with the present
30 disclosure is shown in Figs 1a to 1c and described in US 2013/0237771 (EP 2567680), the content of which is incorporated herein by reference. The temperature sensor 10 may

have the form of a pessary or may be attached to a pessary 20 placed in the vaginal channel of the female. The temperature sensor 10 can measure the actual temperature of the body core of the user inside the vaginal channel. The measured temperatures may therefore be termed body core temperature. The temperature sensor is able to measure
5 and record circamensual (30 days and more) a series of body core temperature data points.

[0017] The body core temperature is the most reliable temperature measurement of a human or animal and is by far more precise than measurements on other places, where
10 they are often influenced by external or environmental conditions.

[0018] The series of body core temperature data points may be determined continuously, for example every 5 minutes over 24 hours a day, 7 days a week resulting in about 288 temperature data points per day. The time interval may be greater or less than five
15 minutes, for example every minute or every 10 or 15 minutes resulting in more or less temperature data points per day. It is advantageous, however, to monitor the temperature continuously over the whole day, during night and day, and if possible over the entire menstrual cycle of the female. A continuous temperature data curve can be
20 evaluated from these temperature data points representing the actual body core temperature of the female. Examples for continuous temperature data curves are shown in Figures 2a and 2b, where 288 temperature data points per day were measured and recorded continuously every 5 minutes over a menstrual cycle (about 30 days or more).

[0019] Conventional approaches, for example, measure the temperature data only during
25 sleep phases, i.e. during the nights and the temperature sensor is removed for read out in the morning. These approaches try to estimate a basal temperature based on the lowest temperatures measured during the sleep phase. Other conventional approaches involve a measurement right after waking up. These methods aim to determine a basal temperature which is often not well defined and the method is not very reliable. In
30 addition, these methods are also influenced by the behaviour and the conditions of the

user. Not every night and sleep phase is the same and variations in the life style, the amount and time of sleep may have a strong influence on the measured values.

[0020] The present disclosure suggest the use of a continuous series of temperature data points of the body core temperature measured in the vaginal channel of the female which are determined and recorded continuously over days, weeks or circamensual to determine temperature curves of the body core temperature over long periods. Depending on the application, the sensor may remain in the vagina for the entire menstrual cycle and the recorded data may be read out at the end of the menstrual cycle. Alternatively, the recorded temperature data may be read out regularly, for example once or twice a day. The measurement and read-out of the actual temperature data makes an "real-time" prediction of ovulation possible.

[0021] These recorded temperature curves may be analysed and/or evaluated to determine a prognosis or prediction of future ovulation. It is to be understood that a prediction of a point in time of ovulation is given by probabilities for ovulation. There are different methods that can be applied to determine probabilities and to predict ovulation and/or a fertility window from one or more series of temperature data point and/or from temperature curve recorded over one or more menstrual cycles. Different methods are outlined below. One or more of these methods may be combined to enhance the reliability of the prediction.

Homogeneity Analysis

[0022] A temperature curve of a menstrual cycle may be analysed after the measurement of the entire menstrual cycle has been recorded. The temperature curve or the individual temperature data points of this menstrual cycle may be analysed for homogeneity. An example for a method for analysing homogeneity is illustrated in Figure 3.

[0023] A menstrual cycle can be classified as bi-phasic or as mono-phasic cycle depending on whether a break in the homogeneity of the temperature curve can be found. The break separates the temperature curve of a bi-phasic cycle in a first cycle phase, termed luteal phase before the break and a second cycle phase, termed follicular phase after the

break. A break in homogeneity can be defined as a break in the measured temperature curve of at least 0.2° Celsius. If this break in temperature is positive, i.e. the break involves an increase in temperature and if the second cycle phase lasts for at least ten days or more, the cycle may be considered as bi-phasic. If the second phase after a break
5 is less than ten days and/or if the break is negative, i.e. involves a decrease in temperature, or less than about 0.2° Celsius, the cycle may be considered as mono-phasic.

[0024] Fig. 4a shows the temperature curve of Fig. 2a, analysed for homogeneity. A break
10 in homogeneity with an increase of temperature of more than 0.3°C and with the second phase extending over 12 days could be found. This temperature curve has been determined as bi-phasic.

[0025] Fig. 4b shows the temperature curve of Fig. 2b, analysed for homogeneity. A
15 negative break towards lower temperatures was determined with a delta of less than 0.2°C. This break does not meet criteria for a break in homogeneity. This cycle is therefore considered as mono-phasic.

[0026] The point in time of ovulation is considered to be 24 hours before the break. If
20 three or more menstrual cycles of the same female are determined as bi-phasic, they may be classified by the increase in temperature, length of the cycle, length of the luteal phase and length of the follicular phase. Based on these data, a probability for ovulation on every day of the cycle can be calculated for this female. This information may be presented or output to a user on a display, such as a screen of computer, or other
25 electronic device. The output may comprise the day of the menstrual cycle with the highest probability of ovulation and the days before or after this day with still high probability for ovulation. For example, the day with the highest probability of ovulation is output, and five days before and three days after that day, if for each of these day, the probability is above a pre-determined value. This can depend on the variance of the
30 determined break in the acquired temperature curves. This determination can be used as

a prediction for the ovulation and/or a fertility window of the next menstrual cycle of that female.

[0027] The above prognosis or prediction based on homogeneity test may be used alone
5 or in combination with the method described below. Combining the above homogeneity
based prognosis with a pattern based determination of ovulation described below may
lead to an increase in reliability of the determination of ovulation at a point in time before
the actual ovulation occurs.

10 Pattern Analysis

[0028] Pattern analysis may be used for determination or prediction of ovulation in the
present menstrual cycle of the female. In this application, the temperature data points
are measured, recorded and read out during the menstrual cycle. The reader may be
15 connected to a computer and the temperature data points may be analysed and
evaluated with a computer program running on this computer. It is also possible to use an
internet based analysis tool and to transfer the temperature data points via the internet
to the analysis tool either directly from the reader or via an internet access device, such
as a computer, smartphone tablet or the like.

20

[0029] A time series of temperature data points can be read out and evaluated at any
time during the menstrual cycle. For example, the temperature data points may be read
out or transmitted to a reader or analysis device once every 24 hours or twice a day. The
temperature curve corresponds then to the present menstrual cycle of the female up to
25 the last temperature measurement before read-out, i.e. before the pessary was removed
from the vagina. The time series of temperature data points is thus in this case not a
complete menstrual cycle but only a first portion. A prediction of ovulation can be made
in real-time during the menstrual cycle.

30

[0030] The time series of temperature data points may now be analysed for pre-
determined features or patterns. Principles of pattern analysis have been described in

mathematical theories. The present disclosure suggests the use of such a pattern analysis for analysing temperature curves of body core temperatures in a female.

[0031] Figs. 5 and 6 show sections of two temperature curves taken from a series of temperature data point in which patterns are identified. These examples are purely illustrative and by no means intended to a specific pattern. Every series of data points may be different and different shapes and types of features or patterns may be identified as relevant for ovulation.

10 Example 1

[0032] Fig. 5 shows a first example of features or pattern analysed in a section or subset of a series or temperature data points taken from a woman. The pre-determined feature or pattern may be an increase or a decrease in temperature or a certain sequence of peaks as illustrated by patterns 51, 52, and 53 in Figure 5. For example, a first feature 51 may be a decrease in temperature followed by a second feature 52 of two subsequent peaks at a higher temperature value than the first feature 51. A pre-determined feature may be each one of the first feature or second feature separately or a combination of the first feature 51 and the second feature, for example within a time interval t_1 . The pre-determined feature or pattern may also be the combination of the first feature 51 and the second feature 52 with a third feature 53 that all occur within a time interval Δt_g . An alternative or additional requirement may be that the third feature is found within a time interval t_2 and/or at a certain temperature. These and/or other features can be combined to determine and define the pre-determined feature.

25

[0033] The pre-determined pattern or feature may more generally relate to an increase, a decrease, specific peak temperatures, temperature difference, time intervals, peak frequencies and any combination thereof.

30

[0034] The pre-determined feature or pattern may be a pattern identified in previous cycles of the same female or may be a pattern present in the menstrual cycle of a specific group or of all females or any combination thereof. For example, a feature may be

considered, if it has been observed in about 70 % or more of all considered bi-phasic cycles of all users detected and analysed with the present method.

Example 2

5

[0035] Fig. 6 shows another example of a section of a temperature curve in which a pattern is analysed by pattern recognition. In a first step, a measured series of temperature data points may be subdivided in a plurality of subsets of the temperature data points. Each subset of temperature data points may correspond to a day in the menstrual cycle but other time intervals can be used as well. A specific indicator, termed PuK-indicator, may be determined for each subset of temperature data points. Based on the PuK indicator, each subset of the temperature data points may be assigned to a first phase before ovulation (L1-phase) or a second phase after ovulation (L2 phase) in the menstrual cycle. Other additional phases may be added if considered necessary. In addition to the PuK indicator, the temperature median of the subset of temperature data points may be used for the assignment of the subset of temperature data points to the first phase before ovulation (L1-phase) or to the second phase after ovulation (L2 phase).

10

15

[0036] The PuK indicator is an indicator for temperature stress and may also be termed temperature-stress-indicator. An example of the determination of the PuK-indicator is shown with respect to a single subset of temperature data points in Figure 6. Figure 6a shows the subset of temperature data points in a temperature curve as measured for example with the temperature sensor described with respect to Figure 1. Temperature measurements were taken every 5 minutes in this example.

20

25

[0037] The PuK-indicator determines and evaluates in this example the peaks of the respective subset of temperature data points. The peaks are usually irregular and can not be determined or predicted in any way. Furthermore, the number of peaks depends on different situations, for example peaks can be caused by sports activities, every day activities, diseases or hormones to give just a few examples. The present example aims to identify and analyse peaks or patterns of peaks caused by hormones or hormonal changes. The female body emits high numbers of the hormone progesterone prior to ovulation

30

which has an influence on the body temperature, as known in the art. Peaks caused by hormones can be determined with a certain probability by evaluating based on the length, intensity and frequency of peaks which can be termed a feature of temperature curve or the PuK- or temperature-stress indicator.

5

[0038] To analyse the feature or pattern of a subset of temperature data points as illustrated in Figure 6a, first, peaks have to be identified. Identification of a peak may vary for different persons or different time scales. In some cases peaks can be easily recognized, while other peaks may be more difficult to determine, for example if two or
10 more peaks are very close together or if temperature variation is very little.

[0039] Identified peaks can then be classified as “wide” peaks shown within the squares in Fig. 6b and “acute” peaks shown in square in Fig. 6c. A peak may be classified as “wide” peak if the peak has, for example, a certain length, magnitude or slope, or any
15 combination thereof. Peak criteria for acute peaks may be identified by at least one peak characteristics that may be selected from magnitude, slope or length, wherein the length is shorter than the length of a wide peak. Known mathematical method for pattern analysis can be used for the determination and for the adaption of the peak. A high number and/or a high frequency of acute peaks may be an indicator for high temperature
20 stress.

[0040] The pattern of the acute peaks and/or the pattern of the wide peaks may be considered a feature of the series or subset of the series of temperature data points. The pattern of the acute peaks and/or the pattern of the wide peaks may be compared to
25 data base patterns that may be recorded from the same women and the corresponding subset of the series of data points may be classified as belonging to phase L1 or phase L2. In this way, each subset of the series of data point can be classified. If the subset corresponds for example to the day at which the analysis is made, a real time estimation can be given, if the woman is in phase L1 or L2. Thus every day of the menstrual cycle can
30 be classified as belonging to phase L1 or phase L2.

[0041] The method has been tested and showed with more than 94% reliability the correct phase of the menstrual cycle.

[0042] The example above determines the PuK indicator based on the peaks in the series of temperature data points. Alternative examples may use other characteristics of the data points such as minima, slope or other features of the series of temperature data points.

[0043] All examples shown above may be further improved by a cycle start and/or a cycle end determination. This cycle start determination determines based on the series of temperature data points the start of the menstrual cycle. This can make the determination of ovulation more precise and improves prediction quality when the woman has strongly varying and/or long menstrual cycles.

[0044] The temperature curves may be used as biomarker for hormone events. This is based on the finding that hormone levels have an influence on the body core temperature. The luteinizing hormone (LH) or other hormones such as estradiol and progesterone that effect the implantation of an embryo in the uterus have an direct or indirect influence on the body temperature. This effect is sometimes termed thermal depressive effect. However, there is not direct correlation between the hormone level and the temperature curve and the temperature cure itself does not correspond to ore represent the hormone level. The present disclosure suggests a method and a system for monitoring the body core temperature in real-time which enables to detect changed in the hormone levels in real time.

[0045] Fig. 7 illustrates and example of how ovulation of the fertility window may be predicted. If the pre-determined pattern or feature is identified in the present series of temperature data points, it is verified that the feature was measured in the expected time window. If the time window is accepted, a relation of the feature to the point of time of ovulation is made and a prognosis for ovulation can be given. For example, if the feature occurs 48 hours before ovulation, a prediction of ovulation can be calculated for a point in

time 48 hours after the occurrence of the feature in the time series of temperature data points. In this way, it is possible to make a prediction of ovulation based on the actual menstrual cycle of the female.

- 5 [0046] It is also possible, to combine the prediction based in pattern analysis with the homogeneity method described above. In this case the probability of ovulation may be increased or decreased depending on whether both methods predict the same or a similar time of ovulation or of a fertility window or if they are contradicting.
- 10 [0047] The above disclosure has been given with respect to the determination of the fertility status of a human female. The method and the system, however, are equally applicable with any mammalian female where a continuous temperature measurement is possible.

Claims

1. A for determining the fertility status of a female, the method comprising:
 - determining and recording a continuous series of temperature data points relating to a body temperature of the female;
 - identifying if the series of temperature data points comprises at least one pre-determined feature in the series of temperature data points;
 - and
 - if a pre-determined feature has been identified, determining a point in time of ovulation for the series of temperatures based on a pre-determined relation of the pre-determined feature and ovulation.
2. The method of claim 1, wherein the body temperature is a body core temperature measured in the vaginal channel of the female and the continuous series of temperature data points relate to the body core temperature.
3. The method of claim 1 or 2, wherein the determining and recording the continuous series of temperature data points comprises measuring a temperature data in intervals of every 10 minutes or less and storing data relating to the temperature value in a memory.
4. The method of claim 3, wherein the determining and recording the continuous series of temperature data points comprises measuring the temperature data in intervals of every 10 minutes or less continuously over at least 24 hours.
5. The method of any one of the preceding claims, wherein the determining and recording the series of temperature data points comprises measuring temperature data temperature with a temperature sensor and a data memory in a pessary (placed in the vaginal channel of the female).

6. The method of any one of the preceding claims, wherein the pre-determined feature is present in a plurality of previously recorded menstrual cycles of the female.

5

7. The method of any one of the preceding claims, wherein the pre-determined feature is present in a plurality menstrual cycles of a plurality of females.

10

8. The method of any one of the preceding claims, wherein the pre-determined feature is present in a follicular phase of a plurality menstrual cycles.

9. The method of any one of the preceding claims, further comprising:

- determining the homogeneity of a plurality of temperature curves and determining if the homogeneity has a break in the homogeneity,
- if a break in the homogeneity has been determined, identifying a probability for ovulation and determining how the probability for ovulation corresponds to the determined point in time of ovulation.

15

10. The method of claim 9, wherein the plurality of temperature curves is recorded from the female.

20

11. A system for determining the fertility status of a female, the system comprising

a temperature measurement device for determining and recording a series of temperature data points relating to a body temperature of the female;
an analysing tool for analysing the series of temperature data points, wherein the series of temperature data points is transferred from the temperature

25

measurement device to the analysing tool; the analysing tool performing the steps of:

- identifying if the series of temperature data points comprises at least one pre-determined feature in the series of temperature data points;

and

- if a pre-determined feature has been identified, determining a point in time of ovulation for the series of temperatures based on a pre-determined relation of the pre-determined feature and ovulation.

5

12. The system of claim 11, wherein the temperature measurement device is a pessary and wherein the series of temperature values is determined in the vaginal channel of the female.

10

13. The system of claim 11 or 12, further comprising a reader for reading the series of temperature data points recorded in the temperature measurement device.

14. The system of claim of any one of claims 11 to 13, wherein the analyzing tool is an internet based tool.

15. A method for determining the fertility status of a female, the method comprising

15

- determining and recording a plurality of temperature curves over a menstrual cycle of the female, the temperature curve relating to a body temperature of the female;

- analysing the homogeneity of each one of the plurality of temperature curves and determining if the homogeneity has a break;

20

- determining a point in time of the break in the menstrual cycle of the female; and

- estimating a point of time of ovulation in the menstrual cycle of the female and out-putting the estimated point of time of ovulation.

25

16. The method of claim 15, wherein the plurality of temperature curves represent body core temperatures of the female.

17. The method of claim 15 or 16, wherein the determining and recording a plurality of temperature curves over a complete menstrual cycle of the female comprises

measuring body core temperatures with a temperature sensor arranged in a pessary which is placed in the vaginal channel of the female.

18. The method of any one of claims 15 to 17, wherein the plurality of temperature curves comprises a series of temperature data points measured in intervals of every 10 minutes or less and storing data relating to the temperature value in a memory.
19. The method of any one of claims 15 to 18, wherein the determining if the homogeneity has a break comprises determining if the break includes an increase in temperature.
20. The method of any one of claims 15 to 19, wherein the determining if the homogeneity has a break comprises determining if the break is at least about 0.2° Celsius.
21. The method of any one of claims 15 to 20, further comprising
- determining and recording a continuous series of temperature data points relating to a body temperature of the female;
 - identifying if the series of temperature data points comprises at least one pre-determined feature in the series of temperature data points;
- and
- if a pre-determined feature has been identified, determining a point of time of ovulation for the series of temperatures based on a pre-determined relation of the pre-determined feature and ovulation and
 - determining if the point of time of ovulation corresponds to the estimated point of time of ovulation in the menstrual cycle of the female.
22. A system for determining the fertility status of a female, the system comprising a temperature measurement device for determining a series of temperature data points relating to a body temperature of the female;

transferring the series of temperature values from the a temperature measurement device to an analysing tool; the analysing tool performing the steps of:

- analysing the homogeneity of each one of the plurality of temperature curves and determining if the homogeneity has a break;

- determining a point in time of the break in the menstrual cycle of the female; and

- estimating a point of time of ovulation in the menstrual cycle of the female and out-putting the estimated point of time of ovulation.

5

10

15




Fig. 1




Fig. 2a




Fig. 2b




Fig. 3




Fig. 4a




Fig. 4b




Fig. 5

6/7




Fig. 6




Fig. 7

INTERNATIONAL SEARCH REPORT

International application No
PCT/EP2014/070710

A. CLASSIFICATION OF SUBJECT MATTER
INV. A61B10/00 A61F6/08
ADD.
According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED
Minimum documentation searched (classification system followed by classification symbols)
A61B A61F
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)
EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 2008/029130 A2 (FERTILITY FOCUS LTD [GB]; JAMES MICHAEL HOWARD [GB]; KNOWLES TOBY GRAH) 13 March 2008 (2008-03-13) page 28, line 22 - page 37, line 17; claims 1, 2, 9, 11, 23-25, 36, 44-45; figures 1-4	1-14
X	US 4 151 831 A (LESTER ROBERT W [US]) 1 May 1979 (1979-05-01) column 2, line 46 - column 3, line 28; claims 1-14; figures 1-11	1,2,5,6, 11-13
	----- -/--	

Further documents are listed in the continuation of Box C.

See patent family annex.

* Special categories of cited documents :

<p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier application or patent but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p>	<p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</p> <p>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art</p> <p>"&" document member of the same patent family</p>
---	---

Date of the actual completion of the international search 30 October 2014	Date of mailing of the international search report 21/01/2015
---	---

Name and mailing address of the ISA/ European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Fax: (+31-70) 340-3016	Authorized officer Jansson Godoy, Nina
--	--

INTERNATIONAL SEARCH REPORT

International application No
PCT/EP2014/070710

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2012/016258 A1 (WEBSTER WADE W [US] ET AL) 19 January 2012 (2012-01-19) paragraph [0005] paragraph [0025] paragraph [0031] paragraph [0046] paragraph [0051] - paragraph [0053]; figures 1-9 -----	1-6, 11-13
X	US 2013/137940 A1 (SCHAFER DEBORAH LAWRENCE [US]) 30 May 2013 (2013-05-30) paragraph [0045] paragraph [0087] paragraph [0140] - paragraph [0162]; claims 1, 10-12, 26, 34-35; figures 1-10 -----	1,2,6, 11,13,14

INTERNATIONAL SEARCH REPORT

International application No.
PCT/EP2014/070710

Box No. II Observations where certain claims were found unsearchable (Continuation of item 2 of first sheet)

This international search report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. Claims Nos.:
because they relate to subject matter not required to be searched by this Authority, namely:

2. Claims Nos.:
because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out, specifically:

3. Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box No. III Observations where unity of invention is lacking (Continuation of item 3 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

see additional sheet

1. As all required additional search fees were timely paid by the applicant, this international search report covers all searchable claims.

2. As all searchable claims could be searched without effort justifying an additional fees, this Authority did not invite payment of additional fees.

3. As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims for which fees were paid, specifically claims Nos.:

4. No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

1-14

Remark on Protest

- The additional search fees were accompanied by the applicant's protest and, where applicable, the payment of a protest fee.
- The additional search fees were accompanied by the applicant's protest but the applicable protest fee was not paid within the time limit specified in the invitation.
- No protest accompanied the payment of additional search fees.

FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

This International Searching Authority found multiple (groups of) inventions in this international application, as follows:

1. claims: 1-14

A system/method comprising identifying if the series of temperature data points comprises at least one pre-determined feature in the series of temperature data points and if a pre-determined feature has been identified, determining a point in time of ovulation for the series of temperatures based on a pre-determined relation of the pre-determined feature and ovulation.

2. claims: 15-22

A system/method comprising determining and recording a plurality of temperature curves over a menstrual cycle of the female, analysing the homogeneity of each one of the plurality of temperature curves and determining if the homogeneity has a break, determining a point in time of the break in the menstrual cycle of the female and estimating a point of time of ovulation in the menstrual cycle of the female and out-putting the estimated point of time of ovulation.

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/EP2014/070710

Patent document cited in search report	Publication date	Patent family member(s)	Publication date	
WO 2008029130	A2	13-03-2008	AT 509580 T	15-06-2011
			AU 2007293287 A1	13-03-2008
			CN 101528138 A	09-09-2009
			EP 2061380 A2	27-05-2009
			ES 2366929 T3	26-10-2011
			JP 2010502338 A	28-01-2010
			US 2009326410 A1	31-12-2009
			US 2013296735 A1	07-11-2013
			US 2013310704 A1	21-11-2013
			WO 2008029130 A2	13-03-2008

US 4151831	A	01-05-1979	NONE	

US 2012016258	A1	19-01-2012	US 2012016258 A1	19-01-2012
			US 2014213927 A1	31-07-2014

US 2013137940	A1	30-05-2013	US 2013137940 A1	30-05-2013
			US 2014378863 A1	25-12-2014
