

(19) AUSTRALIAN PATENT OFFICE

(54) Title
Snappingly assembled surf fins

(51)⁶ International Patent Classification(s)
B63B 35/79 (2006.01) 20060101AFI20060101
B63B 35/79 BHAU

(21) Application No: **2004242515**

(22) Application Date: **2004 .12 .24**

(43) Publication Date : **2006 .07 .13**

(43) Publication Journal Date : **2006 .07 .13**

(71) Applicant(s)
Keng-Hsun Hsieh

(72) Inventor(s)
Hsieh, Keng-Hsun

(74) Agent/Attorney
Callinan Lawrie, 711 High Street, Kew, VIC, 3101

ABSTRACT OF THE DISCLOSURE

Disclosed is a device disposed in one of a plurality of holes on a body of a surfboard for fixing one of a plurality of fins therein, each fin including an elongated tab extended downwardly, horizontally from a base thereof, the tab
5 including a plurality of spaced protrusions on its either side. The device comprises a central, lengthwise slot including a plurality of spaced projections on its either side above its bottom, wherein responsive to inserting the tab into the slot, the tab is adapted to move rearward by snappingly pushing until the tab is stopped by a rear end of the slot with upper surfaces of the protrusions
10 engaged with lower surfaces of the projections. Either assembly of the fins without sacrificing its fastening or disassembly thereof can be made easy.







FIG. 1
PRIOR ART



2004242515 24 Dec 2004

FIG. 3





F I G . 4

F I G . 5




FIG. 6




FIG. 7




FIG. 8





FIG. 9



2004242515 24 Dec 2004

P/00/011
Regulation 3.2

AUSTRALIA

Patents Act 1990

COMPLETE SPECIFICATION

FOR A STANDARD PATENT

ORIGINAL

TO BE COMPLETED BY APPLICANT

Name of Applicant: KENG-HSUN HSIEH.

Actual Inventors: KENG-HSUN HSIEH

Address for Service: CALLINAN LAWRIE, 711 High Street,
Kew, Victoria 3101, Australia

Invention Title: SNAPPINGLY ASSEMBLED SURF FINS

The following statement is a full description of this invention, including the best method of performing it known to us:-

SNAPPINGLY ASSEMBLED SURF FINS

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to surf fin fixing arrangements, and more particularly to such an arrangement in which one or more fins are securely mounted at a rear of a surfboard by snapping such that either assembly of the fins without sacrificing its fastening or disassembly thereof can be made easy.

2. Description of Related Art

For stability, one or more fins 2, most commonly three, are fixed to a surfboard 1 at its rear as shown in FIG. 1. A prior approach of fixing the fins 2 to the surfboard 1 is disclosed in U.S. Pat. No. 5,464,359 as shown in FIG. 2. A plurality of holes (one is shown) 11 are formed on a rear of the surfboard 1. Each hole 11 is adapted to neatly receive a fixing plug 3. The plug 3 comprises a rectangular slot 31 and two obliquely drilled tapped holes 32 extending from a face and intersecting the slot 31. The fin 2 comprises a pair of tabs 21 extended downwardly from a base thereof. The tabs 21 are inserted into the slots 31. Each of two grub screws 16 is driven home by means of a tool (e.g., screw driver) to fasten the tab 21. This finishes the assembly of the fins 2 on the surfboard 1. For disassembly, simply unfasten the screws 16 by means of a screw driver and then pull the tabs 21 out of the slots 31.

While the cited patent is advantageous for its reliable fixing, its assembly or disassembly is a labor-intensive process. This is not desired. Moreover, the fin 2 tends to break in its joining portion (i.e., V-shaped grooves) with the tab 21. Thus, the need for improvement still exists.

25 SUMMARY OF THE INVENTION

It is an object of the present invention to provide a surf fin fixing arrangement in which one or more fins are securely mounted at a rear of a

surfboard by snapping such that either assembly of the fins without sacrificing its fastening or disassembly thereof can be made easy.

The advantages of the present invention are realized by providing a device disposed in one of a plurality of holes on a body of a surfboard for fixing one of
5 a plurality of fins therein, each fin including an elongated tab extended downwardly, horizontally from a base thereof, the tab including a plurality of spaced protrusions on its either side, comprising a central, lengthwise slot including a plurality of spaced projections on its either side above its bottom, wherein responsive to inserting the tab into the slot, the tab is adapted to move
10 rearward by snappingly pushing until the tab is stopped by a rear end of the slot with upper surfaces of the protrusions engaged with lower surfaces of the projections.

The above and other objects, features and advantages of the present invention will become apparent from the following detailed description taken
15 with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of a surfboard equipped with three fins;

FIG. 2 is a fragmentary sectional view showing the fixing of a fin and a plug in a surfboard disclosed in U.S. Pat. No. 5,464,359;

20 FIG. 3 is an exploded view of three fins to be mounted at a rear of a surfboard according to a fixing system of the invention;

FIG. 4 is an enlarged perspective view of the base of the fin and the plug of FIG. 3;

FIG. 5 shows in cross-section the tab of the fin inserted into the slot prior to
25 fastening;

FIG. 6 shows in another cross-section the components of FIG. 5;

FIG. 7 shows in cross-section the tab of the fin fastened in the slot by

pushing rearward (i.e., assembled);

FIG. 8 shows in another cross-section the components of FIG. 7; and

FIG. 9 is a view similar to FIG. 5 where the tab of the fin has moved to an unfastened position prior to pulling out of the slot (i.e., disassembled).

5 DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring to FIGS. 3 and 4, a surf fin fixing structure in accordance with a preferred embodiment of the invention is illustrated. A plurality of holes 51 of bar-bell shape are formed on a rear of a surfboard 5. The holes 51 are arranged as a shape of triangle. A plurality of fixing plugs 6 having the same number and
10 shape as the holes 51 are inserted into the holes 51 and are fastened therein by means of an adhesive chosen for compatibility with the materials of the surfboard 5 and the plugs 6. Preferably, each mounted plug 6 has its top face flush with the surface of the surfboard 5. The elongated plug 6 comprises a central, lengthwise slot 61 having three pairs of opposite projections 62 and 63
15 along its both sides above its bottom and proximate its top. A plurality of fins (three are shown) 7 each comprises an elongated tab 71 extended downwardly, horizontally from a base thereof. The tab 71 has a length smaller than that of the slot 61. On either side of the tab 71 there are provided three spaced protrusions 72 or 73. Each protrusion 72 on one side and a corresponding
20 protrusion 73 on the other side form a pair and each pair has a length and a width to enable itself to neatly fit in one of three enlarged portions of the slot 61 as detailed later.

Referring to FIGS. 5 and 6, it is shown that three pairs of protrusions 72 and 73 are inserted into the slot 61. At this position, a top face of the protrusion
25 72 or 73 has substantially the same elevation as a bottom face of the projection 62 or 63. Also, an internal space in a rearmost portion of the slot 61 is dimensioned to receive the rearmost pair of the protrusions 72 and 73. As such,

the pairs of protrusions 72 and 73 are adapted to move rearward by snappangly pushing as indicated by arrow as detailed later.

Referring to FIGS. 7 and 8, it is shown that the pairs of protrusions 72 and 73 have moved rearward in the slot 61 by pushing until being stopped by a rear end of an inner wall of the slot 61. At this position, the pairs of protrusions 72 and 73 are fastened since their upward movements are stopped by the bottom faces of the projections 62 and 63. Also, the pairs of protrusions 72 and 73 are concealed in the slot 61. This has finished the assembly of fins 7 in the surfboard 5. In view of the above, it is clear that the assembly of fins 7 can be made by an easy insertion and snapping operation. There is no need to worry the disengagement of the fins 7 from the surfboard 5 since the fastening is reliable. Also, the fastening can be enhanced while surfing since water substantially flows in a direction opposing the movement of the surfboard 5. Moreover, the fastening is totally done by the hand rather than any tool. As such, the assembly can be made quickly.

15

Referring to FIG. 9, for disassembling the fins 7, the steps discussed with reference to FIGS. 5 to 8 are traversed in the opposite direction. That is, push the fins 7 forwardly until being stopped a forward end of the inner wall of the slot 61. At this position, the fins 7 are unfastened. Next, pull the fins 7 upwardly to disengage from the slot 61. It is also clear that the unfastening is totally done by the hand rather than any tool. As such, the disassembly can be made quickly.

20

While the invention herein disclosed has been described by means of specific embodiments, numerous modifications and variations could be made thereto by those skilled in the art without departing from the scope and spirit of the invention set forth in the claims.

25

Where the terms "comprise", "comprises", "comprised" or "comprising" are used in this specification, they are to be interpreted as specifying the presence of the stated features, integers, steps or components referred to, but not to preclude the presence or addition of one or more other feature, integer, step, component or group thereof.

30

WHAT IS CLAIMED IS:


1. A device disposed in one of a plurality of holes on a body of a surfboard for fixing one of a plurality of fins therein, each fin including an elongated tab extended downwardly, horizontally from a base thereof, the tab including a
5 plurality of spaced protrusions on its either side, comprising:
a central, lengthwise slot including a plurality of spaced projections on its either side above its bottom,
wherein responsive to inserting the tab into the slot, the tab is adapted to move rearward by snappingly pushing until the tab is stopped by a rear end of
10 the slot with upper surfaces of the protrusions engaged with lower surfaces of the projections.
2. The device of claim 1, wherein the number of the projections on either side is three and the number of the protrusions on either side is three.
3. The device of claim 1, wherein the projection on one side and a
15 corresponding projection on the other side form a pair.
4. The device of claim 3, wherein upper surfaces of the projections are disposed proximate a top of the slot.
5. The device of claim 1, wherein each protrusion on one side and a corresponding protrusion on the other side form a pair.
- 20 6. The device of claim 1, wherein the upper surface of each protrusion has substantially the same elevation as the lower surface of the projection after the tab has inserted into the slot.

Dated this 23rd day of December 2004

KENG-HSUN HSIEH

By their Patent Attorneys:

CALLINAN LAWRIE









FIG. 1
PRIOR ART



2004242515 24 Dec 2004

FIG. 3





F I G . 4

F I G . 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9

