



US 20170160630A1

(19) **United States**(12) **Patent Application Publication**
Risher(10) **Pub. No.: US 2017/0160630 A1**(43) **Pub. Date: Jun. 8, 2017**(54) **TENSIONED PROJECTION SCREEN**
APPARATUS(71) Applicant: **Draper, Inc.**, Spiceland, IN (US)(72) Inventor: **Kenneth M. Risher**, Warren Park, IN
(US)(21) Appl. No.: **15/209,075**(22) Filed: **Jul. 13, 2016****Related U.S. Application Data**

(63) Continuation of application No. 14/463,097, filed on Aug. 19, 2014, now Pat. No. 9,395,615, which is a continuation of application No. 13/739,339, filed on Jan. 11, 2013, now Pat. No. 8,810,909, which is a continuation of application No. 12/897,484, filed on Oct. 4, 2010, now Pat. No. 8,358,464, which is a continuation of application No. 12/115,351, filed on May 5, 2008, now Pat. No. 7,808,702, which is a


continuation of application No. 11/526,951, filed on Sep. 26, 2006, now Pat. No. 7,369,310, which is a continuation-in-part of application No. 10/930,255, filed on Aug. 31, 2004, now Pat. No. 7,113,332, which is a continuation of application No. 10/327,421, filed on Dec. 20, 2002, now Pat. No. 6,785,047.

Publication Classification(51) **Int. Cl.****G03B 21/56** (2006.01)**F16M 13/02** (2006.01)(52) **U.S. Cl.**CPC **G03B 21/56** (2013.01); **G03B 21/565**
(2013.01); **F16M 13/02** (2013.01)

(57)

ABSTRACT

A projection screen apparatus is disclosed for displaying an image projected by a projector. The projection screen apparatus includes a frame and a screen. The frame includes a plurality of frame members and corner members.






FIG. 1





FIG. 2



மேல்





FIG. 4











FIG. 7




FIG. 8




FIG. 9




FIG. 10

TENSIONED PROJECTION SCREEN APPARATUS

BACKGROUND AND SUMMARY OF THE INVENTION

[0001] This application is a continuation of U.S. patent application Ser. No. 14/463,097, filed Aug. 19, 2014, which is a continuation of U.S. patent application Ser. No. 13/739,339, filed Jan. 11, 2013, now U.S. Pat. No. 8,810,909, which is a continuation of U.S. patent application Ser. No. 12/897,484, filed Oct. 4, 2010, now U.S. Pat. No. 8,358,464, which is a continuation of U.S. patent application Ser. No. 12/115,351, filed May 5, 2008, now U.S. Pat. No. 7,808,702, which is a continuation of U.S. patent application Ser. No. 11/526,951, filed Sep. 26, 2006, now U.S. Pat. No. 7,369,310, which is a continuation-in-part of U.S. patent application Ser. No. 10/930,255, filed Aug. 31, 2004, now U.S. Pat. No. 7,113,332, which is a continuation of U.S. patent application Ser. No. 10/327,421, filed Dec. 20, 2002, now U.S. Pat. No. 6,785,047, the disclosures of which are expressly incorporated by reference herein.

[0002] The present invention relates to projection screens. More particularly, the present invention relates to tensioned projection screens.

[0003] According to one aspect of an exemplary embodiment of the present disclosure, a projection screen apparatus for use with a projector is provided that is configured to project an image to be watched by a viewer. The projection screen apparatus includes a projection screen having a viewing surface configured to display the image to the viewer. The projection screen includes a plurality of truncated corners. The projection screen apparatus further includes a frame supporting the projection screen and including a plurality of frame members. The projection screen apparatus further includes a coupler coupling the projection screen to the frame.

[0004] According to another aspect of an exemplary embodiment of the present disclosure, a projection screen apparatus for use with a projector is provided that is configured to project an image to be watched by a viewer. The projection screen apparatus includes a projection screen having a viewing surface configured to display the image to the viewer. The projection screen includes a first perimeter edge, a second perimeter edge perpendicular to the first perimeter edge, and a corner perimeter edge angled between the first and second perimeter edges. The projection screen apparatus further includes a frame supporting the projection screen and including a plurality of frame members. The projection screen apparatus further includes a coupler coupling the projection screen to the frame.

[0005] According to yet another aspect of an exemplary embodiment of the present disclosure, a projection screen apparatus for use with a projector is provided that is configured to project an image to be watched by a viewer. The projection screen apparatus includes a projection screen having a viewing surface configured to display the image to the viewer. The projection screen defines a plurality of edges and has a length and a width. First and second edges of the projection screen have lengths less than the length of the projection screen. Third and fourth edges of the projection screen have lengths less than the width of the projection screen. The projection screen apparatus further includes a frame supporting the projection screen and including a

plurality of frame members. The projection screen apparatus further includes a coupler coupling the projection screen to the frame.

[0006] Additional features of the present invention will become apparent to those skilled in the art upon consideration of the following detailed description of an illustrated embodiment exemplifying the best mode of carrying out the invention as presently perceived.

BRIEF DESCRIPTION OF THE DRAWINGS

[0007] A detailed description particularly refers to the accompanying figures in which:

[0008] FIG. 1 is a perspective view of a room showing a projector projecting an image on a projection screen apparatus according to the present disclosure;

[0009] FIG. 2 is a perspective view of four corners of the projection screen apparatus of FIG. 1;

[0010] FIG. 3 is an exploded perspective view of a frame of the projection screen apparatus of FIG. 1;

[0011] FIG. 4 is another exploded perspective view of the frame of the projection screen apparatus of FIG. 1;

[0012] FIG. 5 is an exploded perspective view of a projection screen and four couplers configured to couple the screen to the frame;

[0013] FIG. 6 is a perspective view of a portion of the projection screen apparatus showing two extended frame members coupled to a corner member and the projection screen aligned to be coupled to the frame and corner members by two screen couplers;

[0014] FIG. 7 is a cross-sectional view taken along line 7-7 of FIG. 1 showing the coupler in a first location relative to the frame member;

[0015] FIG. 8 is a cross-sectional view taken along line 8-8 of FIG. 1 showing the coupler in a second location relative to the frame member;

[0016] FIG. 9 is a view similar to FIG. 8 showing the coupler being moved to a third position when a user pushes on the coupler with a tool (in phantom); and

[0017] FIG. 10 is a cross-sectional view of the frame member and coupler showing the coupler positioned within a channel of the frame member for shipping.

DETAILED DESCRIPTION OF THE DRAWINGS

[0018] According to the present disclosure, a projection screen apparatus 10 is provided to display images projected by a projector 12. Typically, projection screen apparatus 10 is mounted to a wall 14 of a structure, such as an entertainment room of a residence or conference room of a business. As shown in FIG. 1, projector 12 is positioned on the audience side of projection screen apparatus 10 to reflect back the images projected by projector 12 to an audience. According to alternative installations, projector 12 is positioned for a rear projection application on the back side of projection screen apparatus 10 so that images projected by projector 12 are displayed through projection screen apparatus 10 to the audience. In some installations, speakers (not shown) are positioned behind the projection screen apparatus 10 so that the sound is transmitted through projection screen apparatus 10.

[0019] As shown in FIG. 2, projection screen apparatus 10 includes a perimeter frame 16 and a projection screen 18 tensioned on frame 16. As shown in FIG. 5, projection screen apparatus 10 further includes a plurality of couplers

20 that couple projection screen **18** to frame **16** as shown in FIG. 7. According to the preferred embodiment, each coupler **20** can be positioned at one of a number of locations on frame **16**. Depending on the location at which coupler **20** is positioned on frame **16**, the level of tension in screen **18** is greater or lesser.

[0020] Frame **16** includes four corner members **22** and four extended frame members **24** extending between corner members **22** and forming a junction **88**, as shown in FIG. 6. Junction **88** includes a pair of tubular channels **26, 28** and a pair of posts **30, 32**. Each frame member **24** is made of extruded aluminum and includes the pair of channels **26, 28**. The lengths of frame members **24** are dependent upon the size of screen **18**.

[0021] Each corner member **22** is made of ABS plastic and includes the pair of posts **30, 32** sized to fit within respective channels **26, 28** of respective channels **26, 28** of respective frame members **24**. During assembly, posts **30, 32** are slid into respective channels **26, 28** of each respective frame member **24** to define a rectangular perimeter. Additional disclosure of a suitable projection screen apparatus is provided in U.S. Provisional Patent Application No. 60/840,583, entitled "Tensioned Projection Screen," filed Aug. 28, 2006, to Steven E. Enochs, the disclosure of which is herein incorporated by reference in its entirety.

[0022] Each frame member **24** further includes a fastener-receiving channel **34** sized to receive a fastener **36**, such as a screw. Each corner member **22** includes a pair of fastener-receiving apertures **38** also sized to receive fastener **36**. After posts **30, 32** are positioned in channels **26, 28**, fastener **36** are inserted into apertures **38** and screwed into channels **34** to securely couple corner members **22** to respective frame members **24**.

[0023] Depending upon the length of frame members **24**, an aluminum brace **40** is provided that extends between opposite frame members **24**. Each frame member **24** includes an open channel **42** and opposite ends of brace **40** are positioned in channels **42**. Preferably, brace **40** is under slight compression. According to alternative embodiments, fasteners are provided to secure brace **40** on frame members **24**.

[0024] Before or after frame **16** is assembled, couplers **20** are coupled to projection screen **18**. Preferably before shipment of projection screen apparatus **10**, edges **44** of screen **18** are folded over and sewn as shown in FIG. 5 to define permanent loops **46** in screen **18**.

[0025] Screen **18** may be made of a number of materials suitable for projection screen applications. Preferably, screen **18** has a reflectivity gain from about 0.4 to about 2.5. Front projection screens are preferably white or light gray in appearance. Rear projection screens are preferably light gray in color and translucent to permit the projected image to transmit through the screen and be displayed to the audience. Some of the screens are acoustically transparent, like speaker cover fabric, to permit sound to be transmitted through the screen.

[0026] According to one embodiment, the screen includes a woven fiberglass backing with a vinyl reflective surface laminated to the fiberglass (gain of approximately 1.0). According to one embodiment, microscopic glass beads are provided on the viewing surface (gain from about 0.5 to about 2.5 depending on the viewing angle). According to another embodiment, the screen is made of a white (gain of about 1.0 or from about 0.4 to about 2.2 depending on the

viewing angle) or light gray (gain of about 0.6 to 0.9 depending on the viewing angle) vinyl material without a backing. Other suitable projection screens known to those of ordinary skill in the art may also be provided. Preferably the screen is substantially blank so that it is substantially free of printing or other markings that noticeably detract from the images projected on the screen. According to one embodiment, the substantially blank screen is provided with black borders that frame the screen for "wide screen" or other projection formats.

[0027] Couplers **20** are made of extruded, rigid PVC and include a first end **48** having an interactive member **50** and a second end **52** having an open channel **54** sized to receive loops **46** of screen **18**. Preferably at the site of installation, each loop **46** is positioned to extend down an open channel **54** of a respective coupler **20**. A retention rod **56** that is slightly longer than coupler **20** is slid through an open end of each loop **46**. This prevents the withdrawal of the respective loop **46** from the respective screen coupler **20** to couple each screen coupler **20** to an edge **44** of screen **18**. Preferably, retention rods **56** are hollow and made of HDPE plastic. Because loops **46** are permanent, the position of couplers **20** relative to screen **18** is fixed by the manufacturer and not dependent upon the skill of the installer.

[0028] After screen couplers **20** are coupled to screen **18**, they are coupled to frame **16** to tension screen **18** on frame **16**. Each interactive member **50** of couplers **20** includes a rib **58** that defines an undercut groove **60** with a body **62** of coupler **20**. Each frame member **24** includes three spaced-apart interactive members **64, 66, 68** including ribs **70, 72, 74** that define undercut grooves **76, 78, 80**. Interactive member **50** of screen coupler **20** mates with one of interactive members **64, 66, 68** to couple coupler **20** to frame member **24**. Each corner member **22** includes two sets of corresponding interactive members **82, 84, 86** that align with respective interactive members **64, 66, 68** of adjacent frame members **24** to define continuous interactive members and grooves that extend across junctions **88** defined between respective corner and frame members **22, 24**.

[0029] Each respective coupler **20**, loop **46**, and retention rod **56** is longer than the distance between each exposed end of frame member **24** so that each coupler **20**, loop **46**, and rod **56** extends over the respective junction **88** between corners **22** and frame members **24** when couplers **20** are coupled to frame **16**. Thus, continuous coupling is provided along the entire length of frame members **24** and extends over to corners **22**.

[0030] After screen **18** is coupled to frame **16**, frame **16** is mounted to wall **14**. As shown in FIGS. 3, 4, and 8, projection screen apparatus **10** includes a pair of wall couplers **90** that are coupled to wall **14** and frame **16** to support perimeter frame **16** on wall **14**. Wall coupler **90** is made of extruded aluminum and includes a first flange **92** including a plurality of fastener-receiving apertures **94** and a second flange **96**.

[0031] During installation, one or more wall couplers **90** are coupled to wall **14** with second flange **96** extending upwardly. Preferably, wall couplers **90** are positioned at the same level so that perimeter frame **16** will be level and then fasteners **95**, such as screws, are inserted through apertures **94** into wall **14**. Second flange **96** and a flange **98** of frame members **24** defines channel **40** each have a ramped edge that facilitates insertion of flange **98** over second flange **96**. As flange **98** of frame member **24** slides down flange **96** of

wall coupler 90, frame 16 is drawn closer to wall 14. If necessary to center frame 16, frame 16 can be slid right or left on wall couplers 90 to a centered position without having to remove frame 16 from wall 14. To remove frame 16 for adjustment of the tension in screen 18 or otherwise, frame 16 is raised up and removed from wall 14.

[0032] FIGS. 7 and 8 illustrate screen 18 coupled to frame 16. Preferably, frame member 24 has a width 100 that is 4 inches wide. These figures and the others are proportional. Thus, one of ordinary skill in the art can derive dimensions for the other components from the figures based on the known width 100 of frame 24. According to alternative embodiments other widths are provided, such as 2, 3, or 5 inches.

[0033] When coupled to frame 16, perimeter portions 110 of screen 18 overlap respective walk 112 of frame members 24 and corresponding walk 114 of corner members 22. A substantially flat display portion 116 of screen 18 is surrounded by perimeter portions 110 and provides a display surface 118 on one side of display portion 116 on which images projected on screen 18 by projector 12 (either front or rear projection) are viewed by the audience seated in front of projection screen apparatus 10. Display surface 118 defines a plane 120 that has a first audience side 122 and an opposite second side 124. As shown in FIG. 8, screen coupler 20 is positioned on audience side 122 of plane 120 and wall coupler 90 is positioned on opposite side 124.

[0034] Wall 112 includes a first corner 126 on its inner edge that causes screen 18 to turn or bend and divides screen 18 into perimeter and display portions 110, 116 as shown in FIG. 8. Wall 112 also includes a second bend 128 that turns and divides perimeter portion 110 of screen 18 into first and second segments 130, 132. Corner 126 and bend 128 assist in suppressing puckering or creasing of screen caused by coupler 20 so that most, if not all, puckering or creasing is removed from screen 18 before reaching display portion 116 so that little or no distortion is caused in display surface 118.

[0035] Second segment 132 of perimeter portion 110 defines a plane 134 having a first side 136 and a second side 138. When screen 18 is coupled to frame 16, interactive member 50 of coupler 20 is positioned on first side 136 along with interactive members 64, 66, 68 of frame member 24 and interactive members 82, 84, 86 of corner members 22.

[0036] As shown in FIG. 8, frame 16 includes a front side 140 facing the audience and an opposite back side 142. Front side 140 is preferably painted or otherwise colored black and includes a face 144, an outer wall 146, and an inner side wall 148. When screen 18 is coupled to frame 16, display portion 116 of screen 18 defines an angle 150 of 91° to suppress images from “washing” onto face 144. Furthermore, face 144 and inner side wall 148 have a relatively large radius of 0.25 inches therebetween that further suppresses washing.

[0037] In a typical installation, frame 16 is first assembled as described above. Screen 18 and screen couplers 20 are coupled together as described above either before or after frame 16 is assembled. Screen 18 is then coupled to frame 16 with screen couplers 20. A tool 152, such as a plastic putty knife, is provided to assist in coupling couplers 20 to frame 16. Each coupler 20 includes a rib 154 positioned opposite rib 58 that is configured to receive a front edge 156 of tool 152.

[0038] Initially, screen coupler 20 is positioned adjacent to wall 112 of the respective frame member 24. By pressing on

rib 154 with tool 152, rib 58 is forced along wall 112 until it snaps into one of grooves 76, 78, 80. When one end of rib 58 is positioned in groove 76, tool 152 is slid along the length of coupler 20 forcing the entire length of rib 58 into groove 76. Preferably, screen 18 is sized so that when ribs 58 of couplers 20 are positioned in first grooves 76, screen 18 is properly tensioned so that display portion 116 of screen 18 is properly tensioned and substantially flat. Depending on factors, such as manufacturing tolerances, temperature, or humidity, one or more of ribs 58 of couplers 20 may need to be moved further outward to second or third grooves 78, 80 to obtain the proper tension.

[0039] After a period time passes from the initial installation, screen 18 may stretch and develop a sag that noticeably distorts the quality of the images displayed on screen 18. To remove this sag, one or more couplers 20 is moved further out to the next respective groove 78, 80 until the sag in screen 18 is removed. Because couplers 20 are inaccessible from the front of projection screen apparatus 10, it must first be removed from wall 14 before the adjustment can be made.

[0040] As shown in FIG. 10, channel 26 is sized to receive coupler 26 and rod 56. Before shipping, coupler 26 and rod 56 are placed in channel 26. This help avoids damage to coupler 26 and rod 56 during shipping and also reduces the shipping space required.

[0041] Preferably, instructions for the assembly, installation, and/or use of projection screen apparatus 10 are provided with projection screen apparatus 10 or otherwise communicated to permit a person or machine to assemble, install and/or use projection screen apparatus 10. Such instructions may include a description of any or all portions of projection screen apparatus 10 and/or any or all of the above-described assembly, installation, and use of projection screen apparatus 10 or components of projection screen apparatus 10. The instructions may be provided on separate papers and/or on the packaging in which projection screen apparatus 10 is sold or shipped. These instructions may also be provided over the Internet or other communication system. Furthermore, the instructions may be embodied as text, pictures, audio, video, or any other medium or method of communicating instructions known to those of ordinary skill in the art.

[0042] Although the present invention has been described in detail with reference to preferred embodiments, variations and modifications exist within the scope and spirit of the present invention as described and defined in the following claims.

1-20. (canceled)

21. A projection screen apparatus for use with a projector configured to project an image to be watched by a viewer, the projection screen apparatus including:

- a projection screen having a viewing surface configured to display the image to the viewer;
- a frame supporting the projection screen and including a plurality of frame members, the plurality of frame members including a top frame member extending along a top edge of the projection screen, the top frame member being a unitary extruded member including:
 - a front wall having a first side facing the viewer and a second side opposite the first side,
 - an upper portion including a first channel extending the length of the top frame member,

a lower portion including a second channel extending the length of the top frame member, and
a plurality of ribs extending from the second side, each rib defining an undercut groove, a first rib of the plurality of ribs forming a top wall of the second channel, and a second rib of the plurality of ribs being positioned between the first channel and the second channel; and
at least coupler coupling the projection screen to the frame, a first coupler of the at least one coupler coupling the top edge of the projection screen to the top frame member with the top edge of the projection screen being positioned rearward of the front wall of the top frame member, the first coupler being a unitary extruded member including:
a central body;
a lower circular portion extending from the central body, the lower circular portion having an open end and a channel extending the length of the first coupler, the top edge of the projection screen being located in the channel extending the length of the

first coupler and the projection screen extends downward through the open end of the lower circular portion; and

an upper portion including a first rib and a second rib, the first rib extending from the central body in a first direction towards the first side of the front wall of the top frame member, the first rib defining with the central body an undercut groove, the second rib extending from the central body in a second direction away from the first side of the front wall of the top frame member,

wherein the first rib of the first coupler is positioned on top of a rib of the plurality of ribs of the top frame member to couple the projection screen to the top frame member, the undercut groove of the first rib of the first coupler receiving the rib of the plurality of ribs of the top frame member, the first channel of the top frame member being sized and shaped to receive the first coupler for storage of the first coupler when uncoupled from the projection screen.

* * * * *