



US 20090065505A1

(19) **United States**(12) **Patent Application Publication**  
**LAI**(10) **Pub. No.: US 2009/0065505 A1**(43) **Pub. Date: Mar. 12, 2009**(54) **COLLAPSIBLE AND DISPOSABLE  
CONTAINER****Publication Classification**(51) **Int. Cl.****B65D 6/16** (2006.01)**B65D 25/38** (2006.01)**B65D 41/04** (2006.01)(52) **U.S. Cl. .... 220/288; 220/623; 220/666; 220/707;  
220/677**(75) **Inventor: Teng-Shun LAI, Taipei (TW)**


Correspondence Address:

**PATENTTM.US****P. O. BOX 82788****PORTLAND, OR 97282-0788 (US)**(73) **Assignees: Teng-Shun LAI, Taipei (TW);  
Shun-Wei HUANG, Taipei (TW)**(21) **Appl. No.: 12/203,755**(22) **Filed: Sep. 3, 2008**(30) **Foreign Application Priority Data**

Sep. 10, 2007 (TW) ..... 096133698

**ABSTRACT**

A container has a body constructed by a front panel, a rear panel, a top panel, two side panels and a bottom panel. An opening is defined in the top panel and is closed by a cap. Each one of the front, rear and top panels has a thickness larger than that of each one of the side and bottom panels. The top panel has a top folding groove defined in the top panel along a direction perpendicular to the side panels. The bottom panel has a bottom reinforced rib having a bottom folding groove defined in the bottom reinforced rib and parallel with the top folding groove in the top panel. Accordingly, the container that is easily collapsible and recycled.






FIG.1A

FIG.1B




FIG.2A

FIG.2B




FIG.3




FIG.4




FIG.5




FIG.6




FIG. 7




FIG. 8

## COLLAPSIBLE AND DISPOSABLE CONTAINER

### BACKGROUND OF THE INVENTION

#### [0001] 1. Field of the Invention

[0002] The present invention relates to a container, and more particularly to a collapsible and disposable container for beverages or the like.

#### [0003] 2. Description of Related Art

[0004] Tetra Pak packages are widely used containers for beverages or food. However, the Tetra Pak packages are difficult for recycling because a Tetra Pak package comprises multiple layers of aluminum films, papers and plastic films. In addition, a conventional Tetra Pak package has to be torn off before being folded for reducing spaces for recycling or reclaiming process. However, some parts of the conventional Tetra Pak package are bent and connected by glue or adhesive, to tear of the conventional package is difficult and time-consuming.

[0005] To overcome the shortcomings, the present invention tends to provide a container to mitigate or obviate the aforementioned problems.

### SUMMARY OF THE INVENTION

[0006] The main objective of the invention is to provide a container that is easily collapsible. The container has a body constructed by a front panel, a rear panel, a top panel, two side panels and a bottom panel. An opening is defined in the top panel and is closed by a cap. Each one of the front, rear and top panels has a thickness larger than that of each one of the side and bottom panels. The top panel has a top folding groove defined in the top panel along a direction perpendicular to the side panels. The bottom panel has a bottom reinforced rib having a bottom folding groove defined in the bottom reinforced rib and parallel with the top folding groove in the top panel.

[0007] Other objects, advantages and novel features of the invention will become more apparent from the following detailed description when taken in conjunction with the accompanying drawings.

### BRIEF DESCRIPTION OF THE DRAWINGS

[0008] FIG. 1A is a perspective view of a first embodiment of a container in accordance with the present invention;

[0009] FIG. 1B is an enlarged perspective view of a side reinforced rib of the container in FIG. 1A;

[0010] FIG. 2A is a bottom perspective view of the first embodiment of the container in FIG. 1A;

[0011] FIG. 2B is an enlarged perspective view of a bottom reinforced rib of the container in FIG. 2A;

[0012] FIG. 3 is a cross sectional top view of a side panel of the container in FIG. 1A;

[0013] FIG. 4 is a cross sectional side view of a bottom panel of the container in FIG. 1A;

[0014] FIG. 5 is operational cross sectional side views of a nozzle of the container in FIG. 1A;

[0015] FIG. 6 is an operational perspective view of the container in FIG. 1A showing that the container is folded;

[0016] FIG. 7 is a perspective view of a second embodiment of a container in accordance with the present invention; and

[0017] FIG. 8 is a bottom perspective view of the container in FIG. 7.

### DETAILED DESCRIPTION OF PREFERRED EMBODIMENT

[0018] With reference to FIGS. 1, 2, 7 and 8, a beverage container in accordance with the present invention comprises a body. The body is hollow is constructed by a front panel (30,30A), a rear panel (40,40A), a top panel (50,50A), two side panels (10,10A) and a bottom panel (20,20A).

[0019] The front panel (30,30A) has a top connected to one end of the top panel (50,50A), and the rear panel (40,40A) has a top connected to the other end of the top panel (50,50A). The top panel (50,50A) may be curved as shown. The side panels (10,10A) are mounted between the front, rear and the top panels (30,30A,40,40A,50,50A). The bottom panel (20,20A) is mounted between the front, rear and side panels (10,10A, 30,30A,40,40A) to form a hollow body with a chamber for containing beverage, food or the like.

[0020] With further reference to FIGS. 3 and 4, the front, rear and top panels (30,30A,40,40A,50,50A) may be made of hard plastic material and each has a thickness larger than that of each one of the side and bottom panels (10,10A,20,20A).

[0021] The top panel (50,50A) has a top folding groove (51,51A) defined in the top panel (50,50A) along a direction perpendicular to the side panels (10,10A). In a preferred embodiment, the top folding groove (51,51A) is defined in the top of the top panel (50,50A). In an alternative embodiment, the top folding groove (51,51A) can be defined in the bottom of the top panel (50,50A).

[0022] The top panel (50,50A) has an opening defined through the top panel (50,50A) and communicating with the chamber. The opening is provided with a cap (65,80) to close the opening. With reference to FIG. 5, the opening is defined through the top of the top panel (50,50A) and may be defined at a position lower than a topmost position of the curved top panel (50). In a second embodiment as shown in FIGS. 7 and 8, the opening is defined the topmost position of the curved top panel (50A).

[0023] In the first embodiment, with reference to FIG. 5, a nozzle (60) is attached to the top panel (50) to close the opening in the top panel (50) and is provided with the cap (65). The nozzle (60) communicates with the chamber in the body and has an outer thread (62) formed around a free end of the nozzle (60). The cap (65) is attached to the nozzle (60) and has an inner thread screwed with the outer thread (62) on the free end of the nozzle (60). The nozzle (60) may be extendable to a position where the free end of the nozzle (60) is higher than the topmost position of the curved top panel (50). Consequently, the chamber of the body can be filled with beverage as full as possible to improve the use of the container.

[0024] In the second embodiment, the cap (80) is attached directly to the opening in the top panel (50A) to close the opening.

[0025] The bottom panel (20,20A) may be implemented by two plastic films connected with each other and has a bottom reinforced rib (75,75A). The bottom reinforced rib (75,75A) is embedded between the plastic films of the bottom panel (20,20A) and is X-shaped.

[0026] The bottom reinforced rib (75,75A) has a bottom folding groove (751) defined in the bottom reinforced rib (75,75A) and parallel with the top folding groove (51,51A) in the top panel (50,50A). In a preferred embodiment, the bot-

tom folding groove (751) is defined in a top of the bottom reinforced rib (75,75A) on the bottom panel (20,20A). Alternatively, the bottom folding groove (751) may be defined in a top of the bottom reinforced rib (75,75A) on the bottom panel (50,50A). In addition, the bottom folding groove (751) is in alignment with the top folding groove (51,51A) and is located at a surface that is perpendicular to the side panels (10,10A) and is parallel with the front and rear panels (30,30A,40,40A).

[0027] With reference to FIG. 1 to 3, each side panel (10,10A) is implemented by two plastic films connected with each other and may further have a side reinforced rib (70). The side reinforced rib (70) of each side panel (10) is embedded in the plastic films of the side panel (10), is X-shaped and has a side folding groove (71) defined along a direction parallel with the front panel (30). In a preferable embodiment, the side folding grooves (71) in the side panels (10) are located at the surface at which the top and bottom folding grooves (51,751) are located.

[0028] With the reinforced ribs (70,75) on the side and bottom panels (10,20,20A), the structural strength of the side and bottom panels (10,20,20A) implemented by plastic films can be reinforced. Thus, the volume of beverage that the container can hold can be increased. In addition, for small volume usage, the side reinforced ribs (70) can be kept free from the side panels (10A) as the container shown in FIGS. 7 and 8.

[0029] To fold the container, with reference to FIGS. 1, 2 and 6, the top, side and bottom panels (10,10A,20,20A,30,30A) can be folded with the folding grooves (51,51A,71,751). Because the thickness of the side and bottom panels (10,10A,20,20A) are smaller than that of the front, top and rear panels (30,30A,40,40A,50,50A), the container can be easily collapsed to reduce the space for recycling or reclaiming the container. Furthermore, because the panels (10,10A,20,20A,30,30A,40,40A,50,50A) are formed by plastic material, the container is sorted to plastic for a recycling or reclaiming process. To recycle or reclaim the container in accordance with the present invention is easy and convenient.

[0030] Even though numerous characteristics and advantages of the present invention have been set forth in the foregoing description, together with details of the structure and function of the invention, the disclosure is illustrative only, and changes may be made in detail, especially in matters of shape, size, and arrangement of parts within the principles of the invention to the full extent indicated by the broad general meaning of the terms in which the appended claims are expressed.

What is claimed is:

1. A container comprising:

a hollow body constructed by a front panel, a rear panel, a top panel, two side panels and a bottom panel; and an opening defined in the top panel and being closed by a cap, wherein

each one of the front, rear and top panels has a thickness larger than that of each one of the side and bottom panels;

the top panel has a top folding groove defined in the top panel along a direction perpendicular to the side panels; and

the bottom panel has a bottom reinforced rib having a bottom folding groove defined in the bottom reinforced rib and parallel with the top folding groove in the top panel.

2. The container as claimed in claim 1, wherein the top folding groove is defined in a top of the top panel;

the bottom folding groove is defined in a top of the bottom reinforced rib on the bottom panel; and

the bottom folding groove is in alignment with the top folding groove and is located at a surface that is perpendicular to the side panels and is parallel with the front and rear panels.

3. The container as claimed in claim 2, wherein each side panel further has a side reinforced rib having a side folding groove defined in the side reinforced rib along a direction parallel with the front panel; and

the side folding grooves in the side panels are located at the surface at which the top and bottom folding grooves are located.

4. The container as claimed in claim 3, wherein

the top panel is curved and the opening is defined at a position lower than a topmost position of the curved top panel;

the top panel further has a nozzle attached to the opening in the top panel, being extendable and having an outer thread formed around a free end of the nozzle; and

the cap has an inner thread screwed with the outer thread on the free end of the nozzle.

5. The container as claimed in claim 4, wherein

the bottom panel is implemented by two plastic films connected with each other; and

the bottom reinforced rib is embedded between the plastic films of the bottom panel and is X-shaped.

6. The container as claimed in claim 5, wherein

each side panel is implemented by two plastic films connected with each other; and

the side reinforced rib of each side panel is embedded in the plastic films of the side panel and is X-shaped.

7. The container as claimed in claim 1, wherein each side panel further has a side reinforced rib having a side folding groove defined in the side reinforced rib; and

the side folding grooves in the side panels are located at the surface at which the top and bottom folding grooves are located.

8. The container as claimed in claim 7, wherein

each side panel is implemented by two plastic films connected with each other; and

the side reinforced rib of each side panel is embedded in the plastic films of the side panel and is X-shaped.

9. The container as claimed in claim 1, wherein

the top panel is curved and the opening is defined at a position lower than a topmost position of the curved top panel;

the top panel further has a nozzle attached to the opening in the top panel, being extendable and having an outer thread formed around a free end of the nozzle; and

the cap has an inner thread screwed with the outer thread on the free end of the nozzle.

10. The container as claimed in claim 1, wherein

the bottom panel is implemented by two plastic films connected with each other; and

the bottom reinforced rib is embedded between the plastic films of the bottom panel and is X-shaped.