

(12) STANDARD PATENT
(19) AUSTRALIAN PATENT OFFICE

(11) Application No. AU 2015265932 B2

(54) Title
Method of governing the elevation, attitude and structural integrity of a pressure-containing vessel such as an undersea pipeline in a body of liquid

(51) International Patent Classification(s)
B63C 7/08 (2006.01) **F16L 1/12** (2006.01)
B63G 8/14 (2006.01) **F16L 1/24** (2006.01)
B63G 8/22 (2006.01)

(21) Application No: **2015265932** (22) Date of Filing: **2015.05.28**

(87) WIPO No: **WO15/181314**

(30) Priority Data

(31) Number **14/290,660** (32) Date **2014.05.29** (33) Country **US**

(43) Publication Date: **2015.12.03**
(44) Accepted Journal Date: **2018.10.04**

(71) Applicant(s)
Michael William Neil Wilson

(72) Inventor(s)
Wilson, Michael W. N.

(74) Agent / Attorney
Spruson & Ferguson, GPO Box 3898, Sydney, NSW, 2001, AU

(56) Related Art
WO 2003/002848 A1
US 6354764 B1
US 2012/0120759 A1
US 8136470 B1

(43) International Publication Date
3 December 2015 (03.12.2015)

(51) International Patent Classification:
B63C 7/08 (2006.01) *B63G 8/14* (2006.01)
B63G 8/22 (2006.01) *F16L 1/24* (2006.01)
F16L 1/12 (2006.01)

(21) International Application Number:
PCT/EP2015/061886

(22) International Filing Date:
28 May 2015 (28.05.2015)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
14/290,660 29 May 2014 (29.05.2014) US

(71) Applicant: ECOSSE SUBSEA SYSTEMS LTD.
[GB/GB]; Brathens Eco-Business Park, Banchory Aberdeenshire AB31 4BW (GB).

(72) Inventor: WILSON, Michael, W., N; Burnfoot, Upper Lochton, Banchory Aberdeenshire AB31 4ES (GB).

(74) Agent: CAMERON INTELLECTUAL PROPERTY LTD.; 69 St Vincent Street, Glasgow G2 5TF (GB).


(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK,

[Continued on next page]

(54) Title: METHOD OF GOVERNING THE ELEVATION, ATTITUDE AND STRUCTURAL INTEGRITY OF A PRESSURE-CONTAINING VESSEL SUCH AS AN UNDERSEA PIPELINE IN A BODY OF LIQUID

(57) Abstract: A method for governing the elevation, attitude and structural integrity of a pressure-containing vessel (V) in a body of liquid (L) counterbalances flotation (MF) and incompressible (MB) ballast mediums against each other in separate serial compartments (CF, CB). Varying the quantity of incompressible ballast medium (MB) allows control of the elevation and attitude of the vessel (V). If the flotation medium (MF) is compressible, varying the quantity of flotation medium (MF) allows control of the ambient pressure of the vessel (V). The method facilitates floating and towing and laying of an undersea pipeline on, to and at a deep water site.

**Fig. 2A**



SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

— *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))*

Declarations under Rule 4.17:

— *as to the identity of the inventor (Rule 4.17(i))*

Published:

— *with international search report (Art. 21(3))*

METHOD OF GOVERNING THE ELEVATION, ATTITUDE AND STRUCTURAL INTEGRITY OF A PRESSURE-CONTAINING VESSEL SUCH AS AN UNDERSEA PIPELINE IN A BODY OF LIQUID

5

Background of the Invention:

This invention relates generally to the use of pressure-containing vessels to control the elevation and attitude of objects submerged in a body of liquid, especially in environments where hydrostatic crush is of significant concern. The objects may be connected to one or more pressure containing vessels, such as subsea jackets used to support wind turbines or oil rig platforms. The objects may be the pressure-containing vessels, such as pipelines.

In a presently known method of moving an object from one subsea location to another or raising and lowering an object between the surface and the seabed, small glass microspheres containing air or other gas are dispersed in a body of liquid to form a buoyant fluid. The fluid can be injected into or evacuated from a bladder which is disposed inside of a rigid housing. A valve allows seawater to be injected into or evacuated from a void in the housing and around the bladder. If the void is water filled, as the bladder is expanded or contracted by the addition or evacuation of fluid, water will be evacuated from or admitted into the void in the housing.

The depths at which the microsphere/bladder system can effectively operate are limited. The fluid is a dispersion of the gas-containing microspheres in a liquid and is, therefore, incompressible. The gas contained in the microspheres is the predominant source of system buoyancy. The wall thickness of each microsphere must be sufficient to withstand the proportionate-to-depth internal anti-hydrostatic pressure of the housing. Therefore, the operating depth is limited by the competing

interests of pressure-withstanding microsphere wall thickness and the volume of buoyancy-providing gas in the microspheres.

The attitude of the housing of the microsphere/bladder system in the water cannot be controlled. When the bladder is not fully expanded, its shape, and 5 therefore the distribution of gas in the housing, is unpredictable. Even if the bladder is fully expanded, there is no external structure guaranteeing that its position in the housing is constant. And, even if the bladder does initially assume its intended shape and location in the housing, if the distribution of gas in the bladder is uneven, the housing will experience unpredictable changes in shape and 10 location during operation. The purpose of the glass microspheres is to assure that the buoyant gas they contain is evenly distributed in the liquid that is used to fill the bladder. Regardless of the orientation of the bladder in the housing, if sufficient microspheres are damaged or destroyed, perhaps by depth increases as 15 explained above, their gas is freely dispersed into the liquid, and the stability of the system is compromised.

The ratios of buoyant fluid to water is not known throughout the operation of the microsphere/bladder system. The bladder changes its shape as the liquid containing the microspheres is added to or evacuated from the bladder, but the void between the bladder and the housing may never be fully evacuated of air or water. 20 Therefore, while the amount of the liquid in the bladder may be controlled, the ratio of housing-contained liquid to water is not precisely known. Furthermore, because the microsphere/bladder system requires the bladder to expand to a substantial part of the total housing, use of an elongated housing, such as a pipeline, is impractical. 25

In present shallow water pipeline laying practices, buoyant primary pipelines are capped and floated to the laying site and, by controlled flooding with seawater, are submerged to the seabed while non-buoyant primary pipelines, perhaps

containing one or more cables and/or other pipelines, have piggybacked secondary pipelines which are capped and provide sufficient buoyancy to float the combination. The primary pipeline, or primary and piggybacked secondary pipelines together, are floated to the laying site where the primary, or primary and/or secondary pipelines, can be control-flooded to provide the necessary ballast to submerge the primary pipeline.

The present applications of known shallow water pipeline laying practice are illustrated in Figure 1. Each block of Figure 1 shows the primary pipeline P_P in its floated condition prior to controlled flooding with water to cause the primary pipeline P_P to sink. Block 1 shows an empty primary pipeline P_P which is filled with air A. Block 2 shows an empty primary pipeline P_P which is filled with air A and is piggybacked to a secondary pipeline P_S which is also filled with air A. Block 3 shows a primary pipeline P_P which is filled with air A and contains a cable/other pipeline Z. Block 4 shows a primary pipeline P_P which is filled with air A and contains a cable/other pipeline Z and is piggybacked to a secondary pipeline P_S which is also filled with air A.

None of these Figure 1 applications are useful in deep water applications. Without a piggybacked secondary pipeline P_S , a primary pipeline P_P heavy enough to sink to deep water levels cannot be floated. On the other hand, a secondary piggybacked pipeline P_S satisfactory to provide flotation for a non-buoyant primary pipeline P_P must have such thin walls that the secondary piggybacked pipeline P_S will be destroyed by hydrostatic crush before deep water levels are reached. Therefore, the presently known shallow water flotation practices are effective to submerge pipelines only to depths in a range of 60 to 70 meters. If primary pipelines are intended to contain one or more cables and/or other pipelines, the weight of their contents must also be overcome, likely reducing the maximum depth that can be reached to less than 60 or 70 meters. If the air contained by the

secondary pipeline were compressed, it might be possible to reach a depth of approximately 100 meters before hydrostatic crush occurs, but 100 meters is still relatively shallow for offshore pipelines.

In laying pipelines at greater depths, delivery is presently, and has for about 5 a half century been, accomplished in one of two ways. In some applications, sticks of pipe are transported to a laying-site welding platform the pipeline is assembled offshore. In other applications, the pipeline is assembled on shore and plastically coiled onto a reel. The reel of coiled pipeline is transported to the laying site. The 10 offshore-assembled or reel delivered pipeline is then laid on the seabed by known J-lay or S-lay techniques.

When delivering sticks of pipe to the site, the size of the delivery vessel is generally dictated by a comparison of its size and cost with the time and expense of the total number of trips required between the shore and the site to deliver all the sticks needed to construct the pipeline. When delivering reels of pipeline to the 15 site, the number of trips is greatly reduced but the cost of the vessel increases exponentially.

Whether by pipeline flotation or reeled pipeline delivery, the cost of laying, for example, a 30" diameter pipeline 1,500 meters in length in deep water typically ranges from \$10,000,000 to \$30,000,000. If the product pipeline is intended to 20 contain one or more cables and/or other pipelines, the time and costs associated with the construction and/or the delivery of the pipeline off-shore are further exacerbated.

In sum, there are known object handling practices with depth and control 25 limitations, known pipeline laying practices which can use crafts as small as tugboats but are limited to very shallow water applications and known pipeline laying practices for deep water applications which involve much larger ships

and/or great time and expense and are still fraught with hydrostatic crush complications.

It is, therefore, a primary object of this invention to provide a method for controlling the elevation and attitude of pressure-containing vessels in a body of liquid. Alternatively, an object of this invention is to provide a method for controlling the elevation and attitude of objects connected to pressure-containing vessels in a body of liquid. Alternatively, an object of this invention is to provide a method of delivering pipelines to and laying pipelines at offshore deep-water laying sites which is less costly and less time-consuming than known methods and which facilitates the present method of controlling the elevation and attitude of pressure controlling vessels and of objects connected to pressure-containing vessels. Alternatively, an object of this invention is to provide a method for controlling the elevation and attitude of pressure controlling vessels and of objects connected to pressure-containing vessels which counteracts the varying forces of hydrostatic crush over great changes in depth.

Summary of the Invention:

In accordance with the invention, a method is provided for governing the elevation, attitude and structural integrity of a pressure-containing vessel in a body of liquid.

As used herein, a flotation medium is one which is capable of increasing the buoyancy of the vessel. An incompressible ballast medium is one which is capable of decreasing the buoyancy of the vessel. According to the method, flotation and ballast mediums are selected for such capabilities as applied to the vessel and to the vessel and an object to be attached to the vessel and/or the load capability of any external device used to control the depth and attitude of the vessel in the body of liquid. The vessel is divided into reciprocal serial hydraulically discrete compartments, one for containing the selected flotation medium and the other for containing the selected incompressible ballast medium. As used herein, the compartments of the vessel are reciprocal in that their separate volumes taken together are constant, serial in that they are sequential within the vessel and hydraulically discrete in that they each contain only their corresponding medium. The selected flotation medium in the flotation medium compartment is counterbalanced against the selected incompressible ballast medium in the ballast medium compartment. Counterbalanced as used in this sense means that each compartment of the vessel is filled with its corresponding medium. The quantity of incompressible ballast medium in the ballast medium compartment is then varied to control the elevation of the pressure-containing vessel in the body of liquid.

Dividing the vessel can be accomplished by positioning a pig held in confinement by the inner walls of the vessel between the flotation and incompressible ballast mediums or by selecting flotation and incompressible

ballast mediums which, when abutting, create an impermeable interface therebetween.

Varying the quantity of incompressible ballast medium in the ballast medium compartment can be accomplished by (a) adding at least sufficient 5 incompressible ballast medium to the ballast medium compartment to cause the vessel to descend in the body of liquid; (b) evacuating at least sufficient incompressible ballast medium from the ballast medium compartment to cause the vessel to rise in the body of liquid; or (c) either adding or evacuating sufficient incompressible ballast medium from the ballast medium compartment to cause the 10 vessel to maintain a constant elevation in the body of liquid.

Varying the quantity of incompressible ballast medium in the ballast medium compartment can be further accomplished by adding incompressible ballast medium to the ballast medium compartment to cause the vessel to (a) descend more rapidly in the body of liquid; (b) rise more slowly in the body of 15 liquid; or (c) maintain a constant elevation in the body of liquid. Varying the quantity of incompressible ballast medium in the ballast medium compartment can also be further accomplished by evacuating incompressible ballast medium from the ballast medium compartment to cause the vessel to (d) descend more slowly in the body of liquid; (e) rise more rapidly in the body of liquid; or (f) maintain a 20 constant elevation in the body of liquid.

In addition to causing the vessel to descend, ascend or maintain constant elevation, varying the quantity of incompressible ballast medium can also be used for other specific purposes. If the vessel is caused to rest on the bed of the body of liquid, additional incompressible ballast medium can be added into the ballast 25 medium compartment until the vessel is filled with the incompressible ballast medium and the flotation medium is evacuated from the vessel. The compartments can then be closed to their respective sources of the flotation and ballast mediums.

If the vessel is caused to rest on the surface of the body of liquid, additional flotation medium can be added into the flotation medium compartment until the vessel is filled with the flotation medium and the incompressible ballast medium is evacuated from the vessel. The compartments can then be closed to their 5 respective sources of the flotation and incompressible ballast mediums.

If the selected flotation medium is incompressible, whether a liquid or a gel, both mediums are incompressible. In this case, counterbalancing the mediums can be accomplished by initially filling the vessel with either the flotation or the ballast medium and then exchanging a portion of that medium with a portion of the other 10 medium. Once the mediums are counterbalanced, varying the quantity of incompressible ballast medium contained in the ballast compartment can then be accomplished by exchanging a quantity of either one of the mediums in its respective compartment for a quantity of the other medium in its respective compartment.

15 If the flotation medium is compressible, whether composed of one or more gases, the quantity of the flotation medium contained in the flotation medium compartment and/or the incompressible ballast medium contained in the ballast medium compartment can be varied to cause the internal pressure of the pressure-containing vessel to be within a counterbalancing range of the pressure-containing 20 vessel against ambient pressure. Varying only the flotation medium quantity will control the pressure without significant impact on buoyancy while varying the ballast medium quantity will impact both pressure and buoyancy.

If the flotation medium is compressible, counterbalancing of the flotation and ballast mediums may be accomplished by filling the vessel with either the 25 flotation or the ballast medium and then exchanging a portion of that medium with a portion of the other medium. Once the mediums are counterbalanced, varying the quantity of incompressible ballast medium in the ballast medium compartment

can be accomplished by (a) adding at least sufficient incompressible ballast medium to the ballast medium compartment to cause the vessel to descend in the body of liquid;

5 (b) evacuating at least sufficient incompressible ballast medium from the ballast medium compartment to cause the vessel to rise in the body of liquid; or (c) either adding or evacuating sufficient incompressible ballast medium from the ballast medium compartment to cause the vessel to maintain a constant elevation in the body of liquid.

Varying the quantity of incompressible ballast medium in the ballast medium compartment can also be further accomplished by adding incompressible ballast medium to the ballast medium compartment to cause the vessel to (a) descend more rapidly in the body of liquid; (b) rise more slowly in the body of liquid; or (c) maintain a constant elevation in the body of liquid or evacuating incompressible ballast medium from the ballast medium compartment to cause the vessel to (d) descend more slowly in the body of liquid; (e) rise more rapidly in the body of liquid; or (f) maintain a constant elevation in the body of liquid.

The method may further include selecting a vessel with vertical and/or horizontal axes of symmetry, such as a hollow body with circular or polygonal cross-sections transverse to one of the axes of symmetry, a pipe wound in a loop, a spiral or a helix about one of the axes of symmetry or a linear pipe aligned on one of the axes of symmetry.

Furthermore, the shape and attitude of the vessel can be coordinated with the shape and attitude of an object connected to the vessel and the center of buoyancy of the vessel and the center of buoyancy of the object coordinated in the body of liquid so that not only the elevation but also attitude of the object in the body of liquid can be controlled by the vessel.

The method may also include the selection of multiple vessels and the coordination of the shapes and attitudes of each vessel with the shape and orientation of the object connected to the vessels so that the elevation and attitude of the object in the body of liquid can be controlled by applying the method to 5 control each of the vessels. In a multi-vessel object-manipulating application, if the flotation medium is compressible, as earlier discussed the method can further include the step of varying the quantity of the flotation medium contained in the flotation medium compartments of each vessel and/or the incompressible ballast medium contained in the ballast medium compartments of each vessel to cause the 10 internal pressure of the pressure-containing vessels to be within a counterbalancing range of their respective ambient pressure capabilities.

The method is very useful in laying offshore pipelines, including those laid at exceedingly great depths. To do this, the method is applied as hereinbefore discussed, but only after the pipeline is first floated and towed to the laying site.

15 Using a liquid or a light gel as a flotation medium the primary pipeline is floated by association with the flotation medium and then towed with the associated flotation medium to the pipe laying site. In some applications, the primary pipeline may be the pressure-containing vessel, in which case association with the flotation medium is accomplished by pumping sufficient flotation medium 20 into the primary pipeline to cause the primary pipeline to float. In other applications, the vessel may be a secondary pipeline, in which case association with the flotation medium is accomplished by piggybacking the secondary pipeline to the primary pipeline and pumping sufficient flotation medium into the secondary pipeline to cause the primary pipeline to float. In still other applications, the 25 primary and secondary pipelines will both be pressure containing vessels, in which case association with the flotation medium is accomplished by piggybacking the secondary pipeline to the primary pipeline and pumping sufficient flotation

medium into the primary pipeline and the secondary pipeline to cause the primary pipeline to float.

Using a gas or combination of gases as a flotation medium, the vessel may be a secondary pipeline, in which case floating the primary pipeline by association 5 with the flotation medium is accomplished by piggybacking the secondary pipeline to the primary pipeline and pumping sufficient flotation medium into the secondary pipeline to cause the primary pipeline to float.

In each and all of the above pipeline applications, the method may also include installing at least one cable and/or other pipeline throughout the length of 10 the primary pipeline prior to the step of floating the primary pipeline by association with the flotation medium. In such cases, sufficient flotation medium will be pumped into the primary and/or secondary pipelines to cause the primary and/or secondary pipelines and the installed cables and/or other pipelines to float.

Brief Description of the Drawings:

Other objects and advantages of the invention will become apparent upon reading the following detailed description and upon reference to the drawings in which:

5 Figure 1 is a block diagram illustration of the applications of the known air-assisted shallow water pipeline laying method;

Figures 2A-2B are block diagrams illustrating first and second embodiments of the method in accordance with this invention of governing the elevation, attitude and structural integrity of a pressure containing vessel in a body of liquid;

10 Figures 3A-3D are block diagrams illustrating the steps of preparing a two compartment pressure-containing vessel for use in the present method;

Figures 3E-3G are block diagrams illustrating the steps of preparing a three compartment pressure-containing vessel for use in the present method;

15 Figures 4A-4D are block diagrams illustrating the steps of the present method using a compressible flotation medium and a ballast medium derived from the host liquid in a vertically oriented cylindrical pressure-containing vessel;

Figures 5A-5D are block diagrams illustrating the steps of the present method using an incompressible flotation medium and an independent source ballast medium in a vertically oriented cylindrical pressure-containing vessel;

20 Figures 6A-6D are block diagrams illustrating the steps of the present method using a compressible flotation medium and an independent source ballast medium in a horizontally oriented cylindrical pressure-containing vessel;

25 Figures 7A-7D are block diagrams illustrating the steps of the present method using a compressible flotation medium and an independent source ballast medium in horizontally oriented coiled pipe pressure-containing vessel;

Figure 8 is a one line diagram illustrating the method applied to multiple vessels to control the elevation and attitude of an object in a liquid;

Figure 9 is a block diagram illustrating twelve applications of the present method in laying deep water pipelines;

Figure 10 is a top plan block diagram illustrating the transition of a pipeline being towed across the shoreline toward a laying site in accordance with the deep-
5 water pipeline laying applications of Figure 9;

Figure 11 is a diametric cross-sectional illustration of the descent of the pipeline as seen in Figure 10 from the surface to the seabed; and

Figure 12 is a longitudinal elevational illustration of the descent of the pipeline as seen in Figure 10 from the surface to the seabed.

10 While the invention will be described in connection with preferred embodiments thereof, it will be understood that it is not intended to limit the invention to those embodiments or to the details of the construction or arrangement of parts illustrated in the accompanying drawings.

Detailed Description:***Pressure-Containing Vessels***

The structure and shape of a pressure-containing vessel intended to control the elevation and attitude of an object submerged in a body of liquid will primarily 5 be determined by the shape and center of buoyancy of the object to be controlled by the vessel, by the attitudes the object is to assume in the body of liquid and the depths which the vessel is expected to reach during its operation.

Usually, the chosen vessel will be symmetric, such as a spherical, cylindrical, conical or cubic container. Pipelines may be treated as cylindrical 10 vessels and, in pipeline laying applications, the pipeline may be the vessel and the object to be controlled. When pipe is involved, the length of the pipe or pipeline may be straight and/or curved and may be, or may include, one or more loops, spirals or helical coils. Some vessels may be partly or entirely asymmetric. 15 Multiple vessels of varying types and shapes may be used in combination without departing from the principles of the invention.

Insofar as this disclosure is concerned, various relevant forces should be accounted for in controlling the elevation and attitude of the vessel in the body of liquid. As to the vessel, these forces include the weight of the vessel, the weight of any object to be attached to the vessel and the load capability of any external 20 device used to control the depth and attitude of the vessel in the body of liquid. As to the ambient environment of the vessel, these forces include the hydrostatic crush that will be applied to the vessel at various depths in the body of liquid and the buoyancy applied by the host liquid to the vessel. All of these forces are determinable by known methods before implementation of the invention.

Vessel Buoyancy Control

Looking at Figures 2A and 2B, a cylindrical tank is chosen as the vessel V for the purpose of explaining the general principles of the present invention. As shown, the vessel V is divided into two reciprocal serial hydraulically discrete compartments C_F and C_B . As used herein, the compartments C_F and C_B of the vessel V are reciprocal in that their separate volumes taken together are constant, serial in that they are sequential within the vessel V and hydraulically discrete in that, during the operation of the vessel V, they each contain only their corresponding selected flotation medium M_F or incompressible ballast medium M_B .

As used herein, a flotation medium M_F is one which is capable of increasing the buoyancy of the vessel in the host liquid L. A ballast medium M_B is one which is capable of decreasing the buoyancy of the vessel in the host liquid. According to the method, flotation and ballast mediums M_F and M_B are selected for such buoyancy capabilities in relation to the vessel V or, when applicable, to the vessel V and an object to be attached to the vessel V. As used herein, unless otherwise specified, a selected flotation medium M_F may be a gas, a liquid or a gel. A selected ballast medium M_B may be a liquid or a gel.

Looking at the example of Figures 2A and 2B, by controlling the volume of incompressible ballast medium M_B in its respective compartment C_B , the volume of the other compartment C_F is also controlled and known. In this example, the body of liquid L and the incompressible ballast medium M_B are chosen to be one and the same. However, this will not always be the case.

As seen in Figure 2A, the division of the vessel V into the compartments C_F and C_B is illustrated as a surface of separation S which is the natural result of an interface of the opposing mediums M_F and M_B if the mediums are impervious to each other. If they are not, as seen in Figure 2B, the division of the vessel V into

compartments C_F and C_B will be accomplished by the use in the vessel V of one or more liquid or amorphous jelly pigs P . Of course, the pig P may also be used even if the mediums M_F and M_B are mutually impermeable.

In Figure 2A, as incompressible medium M_B is evacuated from or admitted 5 to the vessel V through its respective valve B , the surface of separation S is reciprocated accordingly. Simultaneously, the flotation medium M_F is admitted to or evacuated from the vessel V through its respective valve F or allowed to expand or compress in the vessel V . Simultaneous admission and expansion or evacuation and compression of the flotation medium M_F are also permissible. In Figure 2B, 10 when a pig P is used, it will move in similar fashion as the surface of separation S between the mediums M_F and M_B with its perimeter sealed against the inside walls of the vessel V . Vessels of greater internal volume require less sophisticated valves.

Pigs P may be liquid or amorphous jelly pigs. Liquid pigs are formed in a 15 vessel by the confinement of the pig liquid in the vessel between the opposing surfaces of mediums which are impervious to the pig liquid but not necessarily impervious to each other. An amorphous jelly pig has a predetermined shape contoured to normally span and seal against the greatest possible cross-section of the vessel V and a memory biasing the pig P to that shape. However, the pig P will 20 conform to the restrictive forces applied to it by the rigid walls of the vessel V and by the pressure applied by the mediums M_F and M_B to the opposed surfaces S_F and S_B of the pig P which are not in contact with the vessel V . In applications in which 25 one or more cables and/or other pipelines Z are contained within a pipeline, pigs are able to conform to the inside wall of the vessel V and the outside walls of the contents Z . Thus, for liquid and jelly pigs, as the volume of the incompressible medium M_B in one of the compartments C_B is varied, the pig P will move along the walls of the vessel V , assuming any shape permitted by the forces of the vessel

walls, the surfaces of the opposed mediums M_F and M_B and the outside walls of any contents Z to reach a condition of equilibrium in the vessel V . Jelly pigs suitable for the purposes of this disclosure are available from the Aubin Group of Ellon, Aberdeenshire, Scotland.

5 Whether by an impermeable interface S or by use of a pig P , the vessel V is divided into two or more hydraulically discrete compartments C_F and C_B . Each hydraulically discrete compartment is defined by the walls of the vessel V and the surface of separation S afforded by an interface of opposed mutually impermeable mediums as seen in Figure 2A or by the end surfaces of a pig P as seen in Figure 10 2B. As noted above in reference to a pig P , the surface of separation is actually two surfaces S_F and S_B , one on the flotation end and the other on the ballast end, respectively, of the pig P . However, it being the purpose of the pig P to structurally provide opposite wall surfaces reciprocating in unison, they are herein 15 referred to as one surface S . In either case, the volumes of the compartments C_F and C_B are always complementary and their total is always the volume of the vessel V less the volume filled by the pig P , if a pig P is used.

Continuing to look at Figures 2A and 2B, assuming the vessel V had a known volume of incompressible ballast medium M_B , the volume of incompressible ballast medium M_B remaining in the vessel V at any time can 20 always be known if the volume of incompressible ballast medium M_B which thereafter flows out of or into the vessel V , respectively, is known. Furthermore, if the inner cross-sectional area of the vessel V is, as shown, linearly constant, the remaining volume of ballast medium M_B will be directly proportional to the distance between the surface of separation S and the ballast end of the vessel V . 25 Thus, the volume of ballast medium M_B in the vessel V can be determined if the flow of ballast medium M_B is metered and/or the location of the interface or pig P in the vessel V is known.

In some applications of the method, for example when horizontally oriented vessels are used, it may be necessary to not only to control the buoyancy of the vessel in the host liquid but also to control the distribution of buoyancy forces within the vessel. Rigging can be used to maintain the vessel in its horizontal 5 orientation regardless of buoyancy applied forces. Multiple compartments can be serially arranged in a single vessel, for example a flotation compartment between two ballast compartments, to balance the buoyancy applied forces. Then too, multiple vessels can be used with each vessel cooperating with others to cancel their unbalanced buoyancy applied forces.

10 ***Vessel Internal Pressure Control***

Further considering Figures 2A and 2B, if the selected flotation medium M_F is also incompressible, as the flotation and ballast mediums M_F and M_B are exchanged, the internal pressure of the vessel V will remain constant. If the ballast 15 medium M_B is the same as the host liquid L , then the ballast valve B can be left open and flotation medium M_F can be used to vary buoyancy.

If, however, the flotation medium M_F is compressible, then flotation medium M_F and/or ballast medium M_B can be added to or evacuated from its vessel compartment C_F and/or C_B without evacuating and/or adding the other medium M_B and/or M_F from or to its vessel compartment C_B and/or C_F , thus increasing or 20 decreasing the internal pressure of the vessel V , respectively. The internal pressure in the flotation compartment C_F can be monitored to provide real time data indicative of the pressure level of the vessel V *vis a vis* the hydrostatic crush applied to the vessel V at its varying depths in the liquid L .

The introduction of a compressible flotation medium M_F and, if necessary, a 25 pig P into the vessel V does not defeat the ability to meter the amount of ballast medium M_B evacuated from or admitted into the vessel V . The total volume of the vessel V is a given. The volume occupied by the pig P , if any, is a given. If the

vessel V is initially filled with ballast medium M_B , the initial volume of ballast medium M_B will be the volume of the vessel V less the volume of the pig P, if any. If the vessel V is initially filled with flotation medium M_F , the vessel V contains no ballast medium M_B . Since the total volume of both compartments C_F and C_B is a 5 constant, the metered transfer of ballast medium M_B determines the volume of both flotation and ballast mediums M_F and M_B in the vessel V at all times. Therefore, the internal pressure of the vessel V can be controlled directly in response to a pressure reading and/or in response to the metered or otherwise determined flow of ballast medium M_B into or out of the vessel V.

10 The method of controlling any one or more of the elevation, attitude and ambient pressure can be automated by controlling the flotation, ballast and flow meter valves F, B and Y in response to, for example, one or more of the flow of ballast medium M_B into and out of the ballast compartment C_B and the internal pressure and depth of each vessel V used in a given application with additional 15 connections to supplies of ballast and floatation mediums M_B and M_F .

Initial Conditions for Applying the Method

Turning to Figure 3A, preparation of the vessel V for use in the method can, for example, be accomplished by first injecting a pig P, if necessary and as shown, into the vessel V at the ballast valve B. Then, as seen in Figure 3B, as 20 incompressible ballast medium M_B is added to the vessel V through the ballast valve B, the interface, or as shown the pig P, will sweep across the vessel V toward the float valve F. Looking at Figure 3C, the vessel V is filled with the incompressible ballast medium M_B when the interface, or as shown the pig P, reaches the float valve F. As seen in Figure 3D, the float and ballast valves F and 25 B can then be closed and a ballast flow meter X and flow meter valve Y serially connected to the ballast valve B. The pig P, if necessary, can be introduced at either valve F or B of the vessel V and then caused by the flotation or ballast

medium M_F or M_B associated with that valve F or B to sweep toward the other valve B or F of the vessel V. This is a preferred, but not only, way of preparing the vessel V for use in the present method. It is only important that a vessel V of known total volume is ultimately filled with a known volume of incompressible ballast medium M_B in one compartment C_B and a remaining volume of flotation medium M_F in the other compartment C_F and, if necessary, a pig P.

Figures 3E, 3F and 3G illustrate an application in which more than two compartments are used. In this example, in a horizontal vessel V_H a flotation compartment C_F is sandwiched between two ballast compartments C_{B1} and C_{B2} . Flotation medium M_F can be admitted and evacuated via a float valve F at the center of the vessel V_H and ballast medium M_B evacuated and admitted via ballast valves B_1 and B_2 , one at each end. Two pigs P_{B1} and P_{B2} divide the vessel V_H into three compartments C_F , C_{B1} and C_{B2} . One way to prepare such a vessel is to admit the two pigs P_{B1} and P_{B2} , one at each of the ballast ends of the vessel V_H as seen in Figure 3E and then admit equal quantities of ballast medium M_B through ballast valves B_1 and B_2 at each end of the vessel V_H to drive the pigs P_{B1} and P_{B2} toward a centered float valve F to evacuate the non-ballast contents of the vessel V_H through the float valve F and bring the pigs P_{B1} and P_{B2} together, as seen in Figure 3F. Then, as seen in Figure 3G, flotation medium M_F can be admitted at the float valve F as ballast medium M_B is evacuated through flow meters X_1 and X_2 and flow meter valves Y_1 and Y_2 in equal quantities from the vessel V_H . The principles of the method are the same.

The Method For All Flotation Mediums

Returning to Figures 2A and 2B, whether the flotation medium is compressible or incompressible, the present method of governing the elevation of a pressure-containing vessel in a body of liquid is the same. Flotation and ballast mediums M_F and M_B are selected in accordance with the buoyancy criteria as

hereinbefore discussed. The vessel V is divided into reciprocal serial hydraulically discrete compartments C_F and C_B , one for containing the selected flotation medium M_F and the other for containing the selected incompressible ballast medium M_B . The selected flotation medium M_F in the flotation medium compartment C_F is 5 counterbalanced against the selected incompressible ballast medium M_B in the ballast medium compartment C_B . The mediums M_F and M_B are deemed to be counterbalanced when both compartments C_F and C_B are filled with their own respective medium M_F or M_B and the compartment volumes are in a state of equilibrium. In this condition, the quantity of incompressible ballast medium M_B 10 in the ballast medium compartment C_B can be varied to control the elevation of the pressure-containing vessel V in the body of liquid L.

The quantity of incompressible ballast medium M_B in the ballast medium compartment C_B can be varied to cause the vessel V to descend, ascend or maintain 15 a constant elevation in the body of liquid L. Descent can be caused by adding incompressible ballast medium M_B to the ballast medium compartment C_B until the vessel V begins to descend. Ascent can be caused by evacuating incompressible ballast medium M_B from the ballast medium compartment C_B until the vessel V begins to ascend. A constant elevation can be maintained by either adding or 20 evacuating incompressible ballast medium M_B to or from the ballast medium compartment C_M until the vessel V is neither descending nor ascending.

The quantity of incompressible ballast medium M_B in the ballast medium compartment C_B can be further varied by adding incompressible ballast medium M_B to the ballast medium compartment C_B to cause a descending vessel V to descend more rapidly or to cause an ascending vessel V to ascend more slowly or 25 to maintain a constant elevation in the body of liquid L. Similarly, the quantity of incompressible ballast medium M_B in the ballast medium compartment C_B can be further varied by evacuating incompressible ballast medium M_B from the ballast

medium compartment C_B to cause an ascending vessel V to ascend more rapidly or to cause a descending vessel V to descend more slowly or to maintain a constant elevation in the body of liquid L . If, for example, the vessel V is descending to the bed of the liquid L , the quantity of ballast medium M_B can be reduced so as to slow 5 its descent and allow the vessel V to land softly on the bottom.

If the vessel V is caused to rest on the bed of the body of liquid L , additional incompressible ballast medium M_B can be added into the ballast medium compartment C_B until the vessel V is filled with the incompressible ballast medium M_B and the flotation medium M_F is evacuated from the vessel V . The 10 compartments C_F and C_B can then be closed to their respective sources of the flotation and ballast mediums M_F and M_B . If the vessel V is caused to float on the surface of the body of liquid L , additional flotation medium M_F can be added into the flotation medium compartment C_F until the vessel V is filled with the flotation medium M_F and the incompressible ballast medium M_B is evacuated from the 15 vessel V . The compartments C_F and C_B can then be closed to their respective sources of the flotation and incompressible ballast mediums M_F and M_B .

If a pig P is used, it can be left in the vessel V if the vessel V is not to be recovered or if it will be reused in the vessel V during its recovery. If it is desirable to recover the pig P from the vessel V , it can be extruded through one of 20 the valves F or B of the vessel V or through other valves already or newly made part of the vessel V .

Incompressible Flotation Mediums

If the flotation medium M_F is incompressible, either an incompressible gas or a liquid or a gel, both mediums M_F and M_B are incompressible. Therefore, 25 counterbalancing the mediums M_F and M_B will require an exchange in which a quantity of one medium M_F or M_B is added to its respective compartment C_F or C_B while the same quantity of the other medium M_B or M_F is simultaneously

evacuated from its respective compartment C_B or C_F . Once the mediums M_F and M_B are counterbalanced, varying the quantity of incompressible ballast medium M_B contained in the ballast compartment C_B requires further simultaneous exchange of a quantity of either one of the mediums M_F or M_B in its respective compartment C_F or C_B for the same quantity of the other medium M_B or M_F in its respective compartment C_B or C_F .

Compressible Flotation Mediums--Ambient Pressure Control

If the flotation medium M_F is compressible, that is composed of one or more compressible gases, the quantity of the flotation medium M_F contained in the flotation medium compartment C_F and/or the incompressible ballast medium M_B contained in the ballast medium compartment C_B can be varied to cause the internal pressure of the pressure-containing vessel V to be within the counterbalancing range of the pressure-containing vessel V against ambient pressure. If only the quantity of flotation medium M_F is varied, the internal pressure of the vessel V will be varied without significant impact on buoyancy of the vessel V . If the quantity of the ballast medium M_B is varied, both the internal pressure and the buoyancy of the vessel V will be impacted.

For the compressible flotation medium M_F , counterbalancing may still be accomplished by filling the vessel V with either the flotation or the ballast medium M_F or M_B and then exchanging a quantity of that medium M_F or M_B with a quantity of the other medium M_B or M_F . Once the mediums M_F and M_B are counterbalanced, a quantity of incompressible ballast medium M_B can be added in the ballast medium compartment C_B to cause the vessel V to descend in the body of liquid L , evacuated from the ballast medium compartment C_B to cause the vessel V to ascend in the body of liquid L or added or evacuated to or from the ballast medium compartment C_B to cause the vessel V to maintain a constant elevation in the body of liquid L .

Another quantity of incompressible ballast medium M_B can be added to the ballast medium compartment C_B to cause the vessel V to descend more rapidly in the body of liquid L , ascend more slowly in the body of liquid L or maintain a constant elevation in the body of liquid L . Similarly, another quantity of 5 incompressible ballast medium M_B can be evacuated from the ballast medium compartment C_B to cause the vessel V to descend more slowly in the body of liquid L , to ascend more rapidly in the body of liquid L or to maintain a constant elevation in the body of liquid L .

10 *A Vertically Oriented Cylindrical Vessel using
A Compressible Gas Flotation Medium and
the Host Liquid As An Incompressible Ballast Medium*

Turning to Figures 4A-4D, the method is applied to control the depth of, and 15 the internal pressure in, a pressure-containing cylindrical vessel 10 vertically oriented in a body of liquid, in this instance seawater W . A compressible flotation medium accessible from a source isolated from the seawater W is counterbalanced 20 against a ballast medium taken from the seawater W .

This application of the method begins with the assumption that, as seen in 25 Figure 4A, the vessel 10 is prepared for use as described above in relation to Figure 3D and is submerged in and filled with the seawater W . The cylindrical inner walls 11 of the vessel 10 are shown aligned on a vertical center axis 15. The vessel 10 has ports controlled by a float valve 17 and a ballast valve 19, respectively. As shown, the float valve 17 has been closed and connected by a conduit 21 to a source (not shown) of compressible gas 23. Also as shown, the ballast valve 19 has been closed and connected through a ballast flow meter 25 and a flow meter valve 29, which is closed, to the body of seawater W .

Looking at Figure 4B, all three valves 17, 19 and 29 have been opened and 30 compressible gas 23 is being pumped through the float valve 17 into the vessel 10,

causing evacuation of the water W from the vessel 10 through the ballast valve 19 in a quantity measured by the ballast flow meter 25. Since the water W is incompressible, the vessel 10 is divided at the interface 31 into two compartments 33 and 35 of variably complementary volume. The quantity of water W remaining 5 in the ballast compartment 35 is the total quantity of water W which filled the vessel 10 in Figure 4A less the quantity of evacuated water W measured by the ballast flow meter 25.

As seen in Figure 4C, the ballast valve 19 has been closed, a predetermined amount of water W having been evacuated from the vessel 10 so as to cause the 10 vessel 10 to descend toward its desired depth in the water W. Since the ballast valve 19 is closed, continued pumping of the compressible gas 23 through the flotation valve 17 into the vessel 10 increases the internal pressure of the vessel 10 without any significant change in the buoyancy of the vessel 10.

Moving on to Figure 4D, the density of the compressible gas 23 has been 15 increased sufficiently to bring the vessel internal pressure to a desired level to counteract the hydrostatic ambient pressure that is applied to the vessel 10. The flotation valve 17 has been closed, at least temporarily, to maintain the desired internal pressure of the vessel 10. This internal pressure can be monitored and increased or decreased by injecting or evacuating compressible gas 23 through the 20 float valve 17 as the changing depth of the vessel 10 may require without changing the buoyancy of the vessel 10. If a change in quantity of ballast medium W in the vessel 10 is required, whether to slow or speed up the rate of descent of the vessel 10, the ballast and flow meter valves 19 and 29 can be opened to admit or evacuate a metered amount of ballast medium W.

25 By appropriate further manipulation of the float and/or ballast valves 17 and 19 and 29, the location of the interface 37 in the vessel 10 can be reciprocally varied to raise or lower the vessel 10 in the water W while simultaneously, if

desired, changing the density of the compressible flotation medium 23. Thus, changes in hydrostatic crush applied to the vessel 10 over a wide range of depths can be accommodated.

This application of the method is explained in specific relation to controlling 5 a vertically oriented cylindrical vessel 10 in seawater W, but applies to all shapes of vessels, compressible gas flotation mediums and bodies of liquid. This application is also explained in relation to an impermeable surface of separation S, as discussed in relation Figure 2A, which divides the vessel 10 into hydrostatically discrete compartments 33 and 35, in this case the interface 37 of mutually 10 impermeable mediums 23 and W, as discussed above. However, this application is also useful if the vessel 10 is divided into compartments by one or more pigs, also as discussed above.

***15 A Vertically Oriented Cylindrical Vessel Using
A Compressible Gas Flotation Medium Source and
An Incompressible Ballast Medium Source Independent of the Host Liquid***

Turning to Figures 5A-5D, the method is applied to control the depth of, and the internal pressure in, a cylindrical pressure-containing vessel 40 vertically oriented in a body of liquid L. A compressible flotation medium accessible from a 20 source isolated from the body of liquid L is counterbalanced against and an incompressible ballast medium taken from another source isolated from the body of liquid L.

This application of the method begins with the assumption that, as seen in Figure 5A, a pig 67 has been introduced at the ballast valve 49 into the vessel 40 and that the vessel 40 has been prepared for use in the manner described above in 25 relation to Figure 3A and is submerged in the body of liquid L. The cylindrical inner walls 41 of the vessel 40 are shown aligned on a vertical center axis 45. The vessel 40 has ports controlled by a float valve 47 and a ballast valve 49,

respectively. As shown, the float valve 47 has been closed and connected by a conduit 51 to a source (not shown) of compressible gas 53. The ballast valve 49 has been connected through a ballast flow meter 55, a flow meter valve 59 and a conduit 61 to a source (not shown) of incompressible ballast medium 57. The 5 vessel 40 has been filled with incompressible ballast medium 57. The pig 67 has been driven by the incompressible ballast medium to the float valve 47 of the vessel 40. The ballast valve 49 has been closed.

Looking at Figure 5B, all three valves 47, 49 and 59 have been opened and compressible gas 53 is being pumped through the float valve 47 into the vessel 40, 10 causing evacuation of the ballast medium 57 from the vessel 40 through the ballast valve 49 in a quantity measured by the ballast flow meter 55. Since the ballast medium 57 is incompressible, the vessel 40 is divided by the pig 67 into two compartments 63 and 65 of variably complementary volume. The quantity of 15 ballast medium 57 remaining in the ballast compartment 55 is the total quantity of ballast medium 57 which filled the vessel 40 in Figure 5A less the quantity of evacuated ballast medium 57 measured by the ballast flow meter 55.

As seen in Figure 5C, the ballast valve 49 has been closed, a predetermined amount of ballast medium 57 having been evacuated from the vessel 40 so as to cause the vessel 40 to descend toward its desired depth in the body of liquid L. 20 Since the ballast valve 49 is closed, continued pumping of the compressible gas 53 through the float valve 47 into the vessel 40 increases the internal pressure of the vessel 40 without any significant change in the buoyancy of the vessel 40.

Moving on to Figure 5D, the density of the compressible gas 53 has been increased sufficiently to bring the vessel internal pressure to a desired level to 25 counteract the hydrostatic ambient pressure that is applied to the vessel 40. The float valve 47 has been closed, at least temporarily, to maintain the desired internal pressure of the vessel 40. This internal pressure can be monitored and increased or

decreased by injecting or evacuating compressible gas 53 through the float valve 47 as the changing depth of the vessel 70 may require without changing the buoyancy of the vessel 40. If a change in quantity of ballast medium 57 in the vessel 40 is required, the ballast and flow meter valves 49 and 59 can be opened to 5 admit or evacuate a metered amount of ballast medium 57.

By appropriate further manipulation of the float and/or ballast and flow meter valves 47 and 49 and 59, the location of the pig 67 in the vessel 40 can be reciprocally varied to raise or lower the vessel 40 in the body of liquid L while simultaneously, if desired, changing the density of the compressible flotation 10 medium 53. Thus, changes in hydrostatic crush applied to the vessel 40 over a wide range of depths can be accommodated.

This application of the method is explained in specific relation to controlling a vertically oriented cylindrical vessel 40 in a body of liquid L, but applies to all shapes of vessels, compressible gas flotation mediums, incompressible ballast 15 mediums and host liquids. This illustration is also explained in relation to the use of a pig 67 to separate the vessel 40 into hydraulically discrete compartments 63 and 65, as discussed above. However, this application is also useful if the vessel 40 is divided by mutually impermeable flotation and ballast mediums, also as discussed above.

20 *A Horizontally Oriented Cylindrical Vessel with
A Compressible Gas Flotation Medium Source and
An Incompressible Ballast Medium Source Independent of the Host Liquid*

Turning to Figures 6A-6D, the method is applied to control the depth of, and 25 the internal pressure in, a cylindrical pressure-containing vessel 70 horizontally oriented in a body of liquid L. A compressible flotation medium accessible from a source isolated from the body of liquid L is counterbalanced against and an

incompressible ballast medium taken from another source isolated from the body of liquid L.

In the case of a horizontally oriented vessel, as shown a cylindrical vessel 70 with its center axis aligned a horizontal axis 75, the attitude or buoyancy balance of 5 the vessel 70 can be maintained in any one or combinations of several ways as hereinbefore discussed. In this application, it is assumed that the rigging method is used for buoyancy balance control.

In this application it is also assumed that, as seen in Figure 6A, a pig 97 has been introduced at the ballast valve 49 into the vessel 70 and that the vessel 70 has 10 been prepared for use in the manner described above in relation to Figure 3D, except that the vessel 70 is horizontally oriented by the rigging, and is submerged in the body of liquid L. The cylindrical inner walls 71 of the vessel 70 are shown aligned on a horizontal center axis 75. The vessel 70 has ports controlled by a float valve 77 and a ballast valve 79, respectively. As shown, the float valve 77 has 15 been connected by a conduit 81 to a source (not shown) of compressible gas 83 and the ballast valve 79 has been connected through a ballast flow meter 85, a flow meter valve 89 and a conduit 91 to a source of incompressible ballast medium 87. The vessel 70 is filled with incompressible ballast medium 87 and the pig 97 has been driven by the incompressible ballast medium 87 to the float valve 77 of the 20 vessel 70. As shown, the valves 77, 79 and 89 have been closed.

Looking at Figure 6B, all three valves 77, 79 and 89 have been opened and compressible gas 83 is being pumped through the float valve 77 into the vessel 70, causing evacuation of the ballast medium 87 from the vessel 70 through the ballast valve 79 in a quantity measured by the ballast flow meter 85. Since the ballast medium 87 is incompressible, the vessel 70 is divided by the pig 97 into two compartments 93 and 95 of variably complementary volume. The quantity of ballast medium 87 remaining in the ballast compartment 85 is the total quantity of

ballast medium 87 which filled the vessel 70 in Figure 6A less the quantity of evacuated ballast medium 87 measured by the ballast flow meter 85.

As seen in Figure 6C, the ballast valve 79 has been closed, a predetermined amount of ballast medium 87 having been evacuated from the vessel 70 so as to 5 cause the vessel 70 to descend toward its desired depth in the body of liquid L. Since the ballast valve 79 is closed, continued pumping of the compressible gas 83 through the float valve 77 into the vessel 70 increases the internal pressure of the vessel 70 without any significant change in the buoyancy of the vessel 70.

Moving on to Figure 6D, the density of the compressible gas 83 has been 10 increased sufficiently to bring the vessel internal pressure to a desired level to counteract the hydrostatic ambient pressure that is applied to the vessel 70. The float valve 77 has been closed, at least temporarily, to maintain the desired internal pressure of the vessel 70. This internal pressure can be monitored and increased or decreased by admitting or evacuating compressible gas 83 through the float valve 15 77 as the changing depth of the vessel 70 may require without changing the buoyancy of the vessel 70. If a change in quantity of ballast medium 87 in the vessel 70 is required, the ballast and flow meter valves 79 and 89 can be opened to admit or evacuate a metered amount of ballast medium 87.

By appropriate further manipulation of the float and/or ballast and flow 20 meter valves 77 and 79 and 89, the location of the pig 97 in the vessel 70 can be reciprocally varied to raise or lower the vessel 70 in the body of liquid L while simultaneously, if desired, changing the density of the compressible flotation medium 83. Thus, changes in hydrostatic crush applied to the vessel 70 over a wide range of depths can be accommodated.

25 This application of the method is explained in specific relation to controlling a horizontally oriented cylindrical vessel 70 in a body of liquid L, but applies to all shapes of vessels, compressible gas flotation mediums, incompressible ballast

mediums and host liquids. This illustration is also explained in relation to the use of a pig 97 to separate the vessel 70 into hydraulically discrete compartments 93 and 95, as discussed above. However, this application is also useful if the vessel 70 is divided by mutually impermeable flotation and ballast mediums, also as 5 discussed above.

***A Horizontally Oriented Helically Coiled Pipe Vessel with
A Compressible Gas Flotation Medium Source and
An Incompressible Ballast Medium Source Independent of the Host Liquid***

10 Turning to Figures 7A-7D, the method is applied to control the depth of, and the internal pressure in, a pressure-containing helically coiled pipe vessel 100 horizontally oriented in a body of liquid L. A compressible flotation medium accessible from a source isolated from the body of liquid L is counterbalanced against and an incompressible ballast medium taken from another source isolated 15 from the body of liquid L.

15 In the case of a horizontally oriented vessel, as shown a helically coiled pipe with its center axis aligned a horizontal axis 105, the attitude or buoyancy balance of the vessel 100 can be maintained in any one or combinations of several ways as hereinbefore discussed. In this application, it is assumed that the rigging method is 20 used for buoyancy balance control.

20 This application of the method begins with the assumption that, as seen in Figure 7A, a pig 127 has been introduced at the ballast valve 109 into the vessel 100 and that the vessel 100 has been prepared for use in the manner described above in relation to Figure 3D, except that the vessel 100 is a horizontally oriented 25 helically coiled pipe, and is submerged in the body of liquid L. The coils 101 of the vessel 100 are shown aligned on a horizontal center axis 105. The vessel 100 has ports controlled by a float valve 107 and a ballast valve 109, respectively. As shown, the float valve 107 has been connected by a conduit 111 to a source (not

shown) of compressible gas 113 and the ballast valve 109 has been connected through a ballast flow meter 115, a flow meter valve 119 and a conduit 121 to a source of incompressible ballast medium 117. The vessel 100 has been filled with incompressible ballast medium 117 and the pig 127 has been driven by the 5 incompressible ballast medium 117 through the coils 101 of the coiled pipe vessel 100 to the float valve 107 of the vessel 100. The valves 107, 109 and 119 have been closed.

Looking at Figure 7B, all three valves 107, 109 and 119 have been opened and compressible gas 113 is being pumped through the float valve 107 into the 10 vessel 100, causing evacuation of the ballast medium 117 from the vessel 100 through the ballast valve 109 in a quantity measured by the ballast flow meter 115. Since the ballast medium 117 is incompressible, the vessel 100 is divided by the 15 pig 127 into two compartments 123 and 125 of variably complementary volume. The quantity of ballast medium 117 remaining in the ballast compartment 115 is the total quantity of ballast medium 117 which filled the vessel 100 in Figure 7A less the quantity of evacuated ballast medium 117 measured by the ballast flow 20 meter 115.

As seen in Figure 7C, the ballast valve 109 has been closed, a predetermined amount of ballast medium 117 having been evacuated from the vessel 100 so as to 25 cause the vessel 100 to descend toward its desired depth in the body of liquid L. Since the ballast valve 109 is closed, continued pumping of the compressible gas 113 through the float valve 107 into the vessel 100 increases the internal pressure of the vessel 100 without any significant change in the buoyancy of the vessel 100.

Moving on to Figure 7D, the density of the compressible gas 113 has been 20 increased sufficiently to bring the vessel internal pressure to a desired level to counteract the hydrostatic ambient pressure that is applied to the vessel 100. The float valve 107 has been closed, at least temporarily, to maintain the desired

internal pressure of the vessel 100. This internal pressure can be monitored and increased or decreased by injecting or evacuating compressible gas 83 through the float valve 107 as the changing depth of the vessel 100 may require without changing the buoyancy of the vessel 100. If a change in quantity of ballast 5 medium 117 in the vessel 100 is required, the ballast and flow meter valves 109 and 119 can be opened to admit or evacuate a metered amount of ballast medium 117.

By appropriate further manipulation of the float and/or ballast and flow meter valves 107 and 109 and 119, the location of the pig 127 in the vessel 100 can 10 be reciprocally varied to raise or lower the vessel 100 in the body of liquid L while simultaneously, if desired, changing the density of the compressible flotation medium 113. Thus, changes in hydrostatic crush applied to the vessel 100 over a wide range of depths can be accommodated.

This application of the method is explained in specific relation to controlling 15 a horizontally oriented coiled pipe vessel 100 in a body of liquid L, but applies to all shapes of vessels, compressible gas flotation mediums, incompressible ballast mediums and host liquids. This illustration is also explained in relation to the use of a pig 127 to separate the vessel 100 into hydraulically discrete compartments 123 and 125, as discussed above. However, this application is also useful if the 20 vessel 100 is divided by mutually impermeable flotation and ballast mediums, also as discussed above.

Vessels With or Without Attached Objects

As earlier discussed, the shape and orientation of the vessel V can be 25 coordinated with the shape and orientation of an object O to be raised and lowered by the vessel V. For example, the vessel V can be designed with vertical and/or horizontal axes of symmetry, such as a hollow body with circular or polygonal

cross-sections transverse to one of the axes of symmetry, one or more pipes wound in one or more loops, spirals or helixes about one of the axes of symmetry or a linear pipe aligned on one of the axes of symmetry. The center of buoyancy of the vessel V and the center of buoyancy of the object O can be coordinated, perhaps 5 vertically aligned, so that not only the elevation but also the attitude of the object O in the body of liquid L can be controlled by controlling the elevation and attitude of the vessel V.

In an object manipulating application, the flotation and ballast mediums M_F and M_B would be selected so that, when the vessel V was filled with only one of 10 the mediums M_F or M_B , the vessel V would be capable of causing both the vessel V and the attached object O to ascend and descend, respectively, in the body of liquid L.

In some object manipulating applications, multiple vessels V can be attached to the same object O, the shapes and orientations of each vessel V being 15 coordinated with the shape and orientation of the object O so that the elevation and attitude of the object O in the body of liquid L can be controlled by applying the present method to control each of the vessels V. In such a multi-vessel object-manipulating application, flotation and ballast mediums M_F and M_B would be selected which, when filling the vessels V, would be capable of causing the vessels 20 V and the attached object O to ascend and descend, respectively, in the body of liquid L. Also, in a multi-vessel application, if the flotation medium M_F is compressible, the quantity of the flotation medium M_F contained in the flotation medium compartments C_F of each vessel V and/or the incompressible ballast medium M_B contained in the ballast medium compartments C_B of each vessel V 25 can be varied to cause the internal pressure of the pressure-containing vessels V to be within a counterbalancing range of their respective ambient pressure capabilities. In a multi-vessel object-manipulating application, the mediums M_F

and M_B need not be the same in each vessel V . Furthermore, the vessels V may be independently caused to ascend or descend, and to do either at different rates, so as to apply rotation-producing moments to the object O .

For example, looking at Figure 8, a box shaped object 150 with a height 151, 5 a width 153 and a depth 155 of three different lengths is connected to three helically cylindrical pressure-containing vessels 161, 163 and 165, respectively. As shown, the vessels 161, 163 and 165 are rigidly connected to the object 150 by arms 171, 173 and 175, respectively, to the center points of the top, front and side faces 181, 183 and 185, respectively, of the object 150. Using the present method 10 to control the elevation of each of the vessels 161, 163 and 165, the elevation and attitude of the object O in the host liquid L can be varied. As suggested by the axial coordinates 191, 193 and 195, the connection points can be positioned anywhere on the surfaces of an object O . The object O could be of any shape, the vessels V of any number and shape and the connection points located at any 15 positions on the surface of the object O depending on the center of buoyancy of the object O and the attitudes that the object O is intended to take in the liquid L .

Primary and Secondary Pipelines as Vessels

Turning to Figure 9, the method is very useful in laying offshore pipelines, especially those to be laid at exceedingly great depths. In laying pipeline, the 20 method is applied as hereinbefore discussed after the pipeline to be laid has been floated and towed to the laying site by association of the pipeline with a flotation medium, either air A or a liquid or gel M_F .

If the primary pipeline P_P is the pressure-containing vessel V , association 25 with the flotation medium is accomplished by pumping sufficient flotation medium into the primary pipeline P_P, V to cause the primary pipeline P_P to float. If the secondary pipeline P_S is the vessel V , association with the flotation medium is accomplished by piggybacking the secondary pipeline P_S to the primary pipeline P_P

and pumping sufficient flotation medium into the secondary pipeline P_S, V to cause the primary pipeline P_P to float. It is also possible, though not discussed in relation to Figure 9, that the primary and secondary pipelines P_P and P_S will both be pressure containing vessels V , in which case association with the flotation medium 5 is accomplished by piggybacking the secondary pipeline P_S to the primary pipeline P_P and pumping sufficient flotation medium into either or both pipelines P_P and/or P_S to cause the primary pipeline P_P to float.

Looking at Figure 9, each block **9/1-9/12** shows the pipeline to be laid as the primary pipeline P_P in a different floated condition. Blocks **9/1-9/6** illustrate an 10 empty primary pipeline P_P while blocks **9/7-9/12** illustrate a primary pipeline P_P containing one or more cables and/or other pipelines Z . In each of the blocks **9/1-9/12**, the primary pipeline P_P contains a flotation medium, either air A or a liquid 15 or gel M_F . Gels, which are dispersions of solids in liquids, are preferred. In blocks **9/1** and **9/7**, the primary pipeline P_P is the vessel V of the present method and the flotation medium, a liquid or gel M_F , of the method is contained in the vessel V . In blocks **9/2-9/6** and **9/8-9/12**, a secondary pipeline P_S is piggybacked to the primary 20 pipeline P_P . In blocks **9/2**, **9/3**, **9/5** and **9/6** and blocks **9/8**, **9/9**, **9/11** and **9/12** the secondary pipeline P_S is the vessel V of the method and contains the liquid or gel flotation medium M_F of the method. In blocks **9/4** and **9/10** the secondary pipeline P_S is the vessel V of the method and contains air A as the flotation medium of the method.

In block **9/1**, the primary pipeline P_P, V would sink if it did not contain sufficient flotation medium M_F to float. The floated primary pipeline P_P, V can be sunk by gradually displacing flotation medium M_F from the primary pipeline P_P, V 25 with sufficient ballast medium M_B , perhaps seawater, to allow the combination to sink. In block **9/7**, the same primary pipeline P_P, V contains a cable and/or other pipeline Z . Therefore, greater initial buoyancy is necessary to float the primary

pipeline P_p, V and its contents Z . Still, the floated primary pipeline P_p, V can be sunk by gradually displacing flotation medium M_f from the primary pipeline P_p, V with sufficient ballast medium M_b , perhaps seawater, to allow the primary pipeline P_p, V with its contents Z to sink.

5 In block 9/2, the primary pipeline P_p contains air A but would still sink if it were not piggybacked to the secondary pipeline P_s, V which contains sufficient flotation medium M_f to float the combination. The floated primary pipeline P_p can be sunk by detaching the primary pipeline P_p from the secondary pipeline P_s, V or by gradually displacing flotation medium M_f from the secondary pipeline P_s, V 10 with sufficient ballast medium M_b , perhaps seawater, to allow the combination to sink. In block 9/8, in the same combination of pipelines P_p and P_s, V , the primary pipeline P_p contains a cable and/or other pipeline Z . Therefore, greater initial buoyancy is necessary to float the combination and its contents Z . Still, the floated primary pipeline P_p can be sunk by detaching the primary pipeline P_p from the 15 secondary pipeline P_s, V or by gradually displacing flotation medium M_f from the secondary pipeline P_s, V with sufficient ballast medium M_b , perhaps seawater, to allow the combination with the contents Z to sink.

20 In block 9/3, the primary pipeline P_p contains flotation liquid M_l but would still sink if it were not piggybacked to a secondary pipeline P_s, V which contains sufficient additional flotation medium M_f to float the combination. The floated primary pipeline P_p can be sunk by detaching the primary pipeline P_p from the secondary pipeline P_s, V or by gradually displacing flotation medium M_f in the 25 secondary pipeline P_s, V with sufficient ballast medium M_b , perhaps seawater, to allow the combination to sink. In block 9/9, in the same combination of pipelines P_p and P_s, V , the primary pipeline P_p contains a cable and/or other pipeline Z . Therefore, greater initial buoyancy is necessary to float the combination and its contents Z . Still, the floated primary pipeline P_p can be sunk by detaching the

primary pipeline P_P from the secondary pipeline $P_{S,V}$ or by gradually displacing flotation medium M_F from the secondary pipeline $P_{S,V}$ with sufficient ballast medium M_B , perhaps seawater, to allow the combination with the contents Z to sink.

5 In block 9/4, the primary pipeline P_P contains air A and would float, and is piggybacked to a secondary pipeline $P_{S,V}$ which is also filled with air A and would also float. The floated primary pipeline P_P can be sunk by gradually displacing air A in the secondary pipeline $P_{S,V}$ with sufficient ballast medium M_B to cause the combination to sink. In block 9/10, in the same combination of primary and
10 secondary pipelines P_P and $P_{S,V}$, the primary pipeline P_P contains a cable and/or other pipeline Z . Still, the floated primary pipeline P_P can be sunk by gradually displacing air A in the secondary pipeline $P_{S,V}$ with sufficient ballast medium M_B to cause the combination with its contents Z to sink.

15 In block 9/5, the primary pipeline P_P contains air A but would still sink if it were not piggybacked to a secondary pipeline $P_{S,V}$ filled with sufficient flotation medium M_F to float the combination. The floated primary pipeline P_P can be sunk by gradually displacing flotation medium M_F in the secondary pipeline $P_{S,V}$ with sufficient ballast medium M_B to allow the combination to sink. In block 9/11, in the same combination of pipelines P_P and $P_{S,V}$, the primary pipeline P_P contains a
20 cable and/or other pipeline Z . Therefore, greater initial buoyancy is necessary to float the combination and the contents Z . Still, the floated primary pipeline P_P can be sunk by gradually displacing flotation medium M_F in the secondary pipeline $P_{S,V}$ with sufficient ballast medium M_B to allow the combination with its contents Z to sink.

25 In block 9/6, the primary pipeline P_P contains flotation medium M_F but would still sink if it were not piggybacked to a secondary pipeline $P_{S,V}$ filled with sufficient additional flotation medium M_F to float the combination. The floated

primary pipeline P_P can be sunk by gradually displacing flotation medium M_F in the secondary pipeline P_S, V with sufficient ballast medium M_B to allow the combination to sink. In block 9/12, in the same combination of pipelines P_P and P_S , the primary pipeline P_P contains a cable and/or other pipeline Z . Therefore, 5 greater initial buoyancy is necessary to float the combination and the contents Z . Still, the floated primary pipeline P_P can be sunk by gradually displacing flotation medium M_F in the secondary pipeline P_S, V with sufficient ballast medium M_B to allow the combination with its contents Z to sink.

As seen in Figures 10-12, the primary pipeline P_P is floated and towed to the 10 pipeline laying site in one of the conditions described above in relation to Figure 9. Looking at Figure 10, the primary pipeline P_P , together with any piggybacked secondary pipeline P_S and contents Z as seen in Figure 9, is being towed by a tugboat T or other relatively small boat to an offshore pipeline laying site (not shown). As seen in Figures 11 and 12, the piggybacked secondary pipeline P_S can 15 have been attached to the primary pipeline P_P in any manner known in the art. The on-shore portion P_1 of the towed pipelines can ride on any suitable delivery system known in the art, a preferred delivery system being disclosed in United States Patent No. 7,927,040. As the on-shore portion transitions into an off-shore position, the offshore portion P_2 of the towed pipelines is floated as explained in 20 reference to Figure 9. Once the primary pipeline P_P and any associated secondary pipeline P_S , contents Z and flotation medium A or M_F have been towed to the laying site, the primary pipeline P_P can be sunk by detachment of the secondary pipeline P_S from the primary pipeline P_P , as seen in Figure 11, or by applying the present method as disclosed in relation to Figure 9. As seen in Figures 10 and 11, 25 the sinking of the primary pipeline P_P with any piggybacked secondary pipeline P_S and contents Z , if applicable, is gradual. As flotation medium A or M_F is exchanged with ballast medium M_B , the heavier ballast medium M_B will cause the

ballast end E_B of the pipelines to descend as the flotation end E_F of the pipelines remains substantially at a constant elevation at or near the surface of the water W . The transitioning portion of the pipelines between ballast and flotation ends E_B and E_F takes on a gradual S configuration, best seen in Figure 12. As seen in Figure 11, 5 when the primary pipeline P_P has settled on the seabed, it can be filled with ballast medium M_B to secure and protect the pipeline P_P and its contents Z , if any.

Given that water has a specific gravity of 1.0, and recognizing that foams and gels have a specific gravity approximating 0.5, if plastic pipe is used as a vessel in the present method the specific gravity of a lift system can be reduced to less than 0 0.1, making it possible that collapsible air bags used by divers, which are subject to Boyle's law, can be replaced by rigid vessels, which are not.

Thus, it is apparent that there has been provided, in accordance with the invention, a method for controlling the elevation, attitude and ambient pressure of pressure-containing vessels that fully satisfies the objects and advantages set forth 5 above. While the invention has been described in conjunction with specific embodiments thereof, it is evident that many alternatives, modifications and variations will be apparent to those skilled in the art and in light of the foregoing description. Accordingly, it is intended to embrace all such alternatives, modifications and variations as fall within the spirit of the appended claims.

20 In the present specification and claims, the word 'comprising' and its derivatives including 'comprises' and 'comprise' include each of the stated integers but does not exclude the inclusion of one or more further integers.

The reference to any prior art in this specification is not, and should not be taken as an acknowledgement or any form of suggestion that the prior art forms part 25 of the common general knowledge.

A definition of a specific embodiment of the invention as claimed herein follows.

According to an embodiment of the invention, there is provided a method of governing the elevation, attitude and structural integrity of a pressure-containing vessel in a body of liquid, the method comprising the steps of:

5 selecting a flotation medium which is capable of increasing the buoyancy of the vessel;

selecting an incompressible ballast medium which is capable of decreasing the buoyancy of the vessel;

0 dividing the vessel into reciprocal serial hydraulically discrete compartments, one compartment for containing the selected flotation medium and the other compartment for containing the selected incompressible ballast medium;

counterbalancing the selected flotation medium in the flotation medium compartment against the selected incompressible ballast medium in the ballast medium compartment;

5 varying the quantity of incompressible ballast medium in the ballast medium compartment to control the elevation of the pressure-containing vessel in the body of liquid; and

measuring the quantity of incompressible ballast medium injected into and exhausted from the ballast medium compartment during said step of varying the quantity of incompressible ballast medium in the ballast medium compartment.

IN THE CLAIMS:

1. A method of governing the elevation, attitude and structural integrity of a pressure-containing vessel in a body of liquid, the method comprising the steps of:

5 selecting a flotation medium which is capable of increasing the buoyancy of the vessel;

selecting an incompressible ballast medium which is capable of decreasing the buoyancy of the vessel;

dividing the vessel into reciprocal serial hydraulically discrete compartments, 0 one compartment for containing the selected flotation medium and the other compartment for containing the selected incompressible ballast medium;

counterbalancing the selected flotation medium in the flotation medium compartment against the selected incompressible ballast medium in the ballast medium compartment;

.5 varying the quantity of incompressible ballast medium in the ballast medium compartment to control the elevation of the pressure-containing vessel in the body of liquid; and

measuring the quantity of incompressible ballast medium injected into and exhausted from the ballast medium compartment during said step of varying the 20 quantity of incompressible ballast medium in the ballast medium compartment.

2. A method according to claim 1, said step of dividing the vessel comprising positioning a pig held in confinement by inner walls of the vessel between the flotation and incompressible ballast mediums.

3. A method according to claim 1, said step of dividing the vessel comprising selecting flotation and incompressible ballast mediums which, when abutting, create an impermeable interface therebetween.

5 4. A method according to claim 1, said step of varying the quantity of incompressible ballast medium in the ballast medium compartment comprising one of:

0 adding at least sufficient incompressible ballast medium to the ballast medium compartment to cause the vessel to descend in the body of liquid;

0 evacuating at least sufficient incompressible ballast medium from the ballast medium compartment to cause the vessel to ascend in the body of liquid; and

5 one of adding and evacuating sufficient incompressible ballast medium from the ballast medium compartment to cause the vessel to maintain a constant elevation in the body of liquid.

5 5. A method according to claim 4, said step of varying the quantity of incompressible ballast medium in the ballast medium compartment further comprising adding incompressible ballast medium to the ballast medium compartment to cause the vessel to one of:

20 descend more rapidly in the body of liquid;

ascend more slowly in the body of liquid; and

maintain a constant elevation in the body of liquid.

6. A method according to claim 4, said step of varying the quantity of incompressible ballast medium in the ballast medium compartment further comprising evacuating incompressible ballast medium from the ballast medium compartment to cause the vessel to one of:

descend more slowly in the body of liquid;
ascend more rapidly in the body of liquid; and
maintain a constant elevation in the body of liquid.

5 7. A method according to claim 1 further comprising the step of, with the vessel resting on a bed of the body of liquid, adding additional incompressible ballast medium into the ballast medium compartment until the vessel is filled with the incompressible ballast medium and the flotation medium is evacuated from the vessel.

0 8. A method according to claim 7 further comprising the step of closing the compartments to sources of the flotation and ballast mediums.

5 9. A method according to claim 1 further comprising the step of, with the vessel floating on a surface of the liquid, adding additional flotation medium into the flotation medium compartment until the vessel is filled with the flotation medium and the incompressible ballast medium is evacuated from the vessel.

20 10. A method according to claim 9 further comprising the step of closing the compartments to sources of the flotation and incompressible ballast mediums.

11. A method according to claim 1, the flotation medium being one of a liquid and a gel.

25 12. A method according to claim 11, said step of counterbalancing comprising the sub-steps of:

filling the vessel with one of the flotation and incompressible ballast mediums; and

exchanging a portion of the one of the flotation and incompressible ballast mediums with the other of the flotation and incompressible ballast mediums.

13. A method according to claim 12, said step of varying the quantity of incompressible ballast medium contained in the ballast compartment comprising exchanging a quantity of one of the mediums in its respective compartment for a quantity of the other medium in its respective compartment.

14. A method according to claim 1, the flotation medium being a gas, the method further comprising the step of varying the quantity of at least one of the flotation medium contained in the flotation medium compartment and the incompressible ballast medium contained in the ballast medium compartment to cause the internal pressure of the pressure-containing vessel to be within a counterbalancing range of the pressure-containing vessel against ambient pressure.

15. A method according to claim 14, said step of counterbalancing comprising the sub-steps of:

20 filling the vessel with one of the flotation and incompressible ballast mediums; and

exchanging a portion of the one of the flotation and incompressible ballast mediums with the other of the flotation and incompressible ballast mediums.

25 16. A method according to claim 15, said step of varying the quantity of incompressible ballast medium in the ballast medium compartment comprising one of:

adding at least sufficient incompressible ballast medium to the ballast medium compartment to cause the vessel to descend in the body of liquid;

evacuating at least sufficient incompressible ballast medium from the ballast medium compartment to cause the vessel to rise in the body of liquid; and

5 one of adding and evacuating sufficient incompressible ballast medium from the ballast medium compartment to cause the vessel to maintain a constant elevation in the body of liquid.

17. A method according to claim 16, said step of varying the quantity of
0 incompressible ballast medium in the ballast medium compartment further comprising adding incompressible ballast medium to the ballast medium compartment to cause the vessel to one of:

descend more rapidly in the body of liquid;

rise more slowly in the body of liquid; and

5 maintain a constant elevation in the body of liquid.

18. A method according to claim 16, said step of varying the quantity of incompressible ballast medium in the ballast medium compartment further comprising evacuating incompressible ballast medium from the ballast medium compartment to cause the vessel to one of:

descend more slowly in the body of liquid;

rise more rapidly in the body of liquid; and

maintain a constant elevation in the body of liquid.

25 19. A method according to claim 1 further comprising the step of selecting a vessel having at least one of a vertical and a horizontal axis of symmetry, the vessel being one of:

a hollow body having one of circular and polygonal cross-sections transverse to one of the vertical and horizontal axes of symmetry;

a pipe wound in one of a loop, a spiral and a helix about one of the vertical and horizontal axes of symmetry; and

5 a linear pipe aligned on one of the vertical and horizontal axes of symmetry.

20. A method according to claim 19 further comprising the step of coordinating a shape and orientation of the vessel with a shape and orientation of an object connected to the vessel with the center of buoyancy of the vessel and the 0 center of buoyancy of the object vertically aligned in the body of liquid, whereby the elevation and attitude of the object in the body of liquid is controlled by the vessel.

21. A method according to claim 20 further comprising the steps of:

5 selecting at least one other vessel according to claim 19;

coordinating a shape and orientation of each at least one other vessel with the shape and orientation of the object connected to the vessel according to claim 20;

whereby the elevation and attitude of the object in the body of liquid is controlled by the vessel and at least one other vessel.

20

22. A method according to claim 21 further comprising the steps of applying the method of claim 1 to the vessel and to each at least one other vessel to control the elevation of the vessel and each at least one other vessel and the elevation and attitude of the object in the body of liquid.

25

23. A method according to claim 22, the flotation medium being a gas, the method further comprising the steps of varying the quantity of at least one of the

flotation medium contained in the flotation medium compartment and the incompressible ballast medium contained in the ballast medium compartment of the vessel and the at least at one other vessel to cause the internal pressure of the vessel and the at least one other vessel to be within its respective counterbalancing range
5 against ambient pressure.

24. A method according to claim 1, the flotation medium being one of a liquid and a light gel and the method being used to lay a primary pipeline, the step of dividing the vessel into reciprocal serial hydraulically discrete compartments being
0 preceded by the steps of:

floating the primary pipeline by association with the flotation medium; and
towing the floated primary pipeline and the associated flotation medium to a
pipe laying site.

25. A method according to claim 24, the vessel being the primary pipeline and said step of floating the primary pipeline by association with the flotation medium comprising pumping sufficient flotation medium into the primary pipeline to cause the primary pipeline to float.

26. A method according to claim 24, the vessel being a secondary pipeline and said step of floating the primary pipeline by association with the flotation medium comprising the sub-steps of:

piggybacking the secondary pipeline to the primary pipeline; and
pumping sufficient flotation medium into the secondary pipeline to cause the
25 primary pipeline to float.

27. A method according to claim 24, the vessel being the primary pipeline and a secondary pipeline and said step of floating the primary pipeline by association with the flotation medium comprising the sub-steps of:

piggybacking the secondary pipeline to the primary pipeline; and

pumping sufficient flotation medium into the primary pipeline and the secondary pipeline to cause the primary pipeline to float.

28. A method according to claim 24, the flotation medium being a gas, the said being a secondary pipeline and said step of floating the primary pipeline by association with the flotation medium comprising the sub-steps of:

piggybacking the secondary pipeline to the primary pipeline; and

pumping sufficient flotation medium into the secondary pipeline to cause the primary pipeline to float.

29. A method according to claim 24 further comprising the step of installing at least one cable/other pipeline throughout the length of the primary pipeline prior to the step of floating the primary pipeline by association with the flotation medium.

30. A method according to claim 29, said step of floating the primary pipeline
20 by association with the flotation medium comprising pumping sufficient flotation
medium into the primary pipeline to cause the primary pipeline and the at least one
cable/other pipeline to float.

31. A method according to claim 29, said step of floating the primary pipeline
25 by association with the flotation medium comprising the sub-steps of:
piggybacking a secondary pipeline to the primary pipeline; and

pumping sufficient flotation medium into the secondary pipeline to cause the primary pipeline and the at least one cable/other pipeline to float.

32. A method according to claim 29, said step of floating the primary pipeline by association with the flotation medium comprising the sub-steps of:

5 piggybacking a secondary pipeline to the primary pipeline; and

pumping sufficient flotation medium into the secondary pipeline and the primary pipeline to cause the primary pipeline and the at least one cable/other pipeline to float.

0 33. A method according to claim 29, the flotation medium being a gas, the vessel being a secondary pipeline and said step of floating the primary pipeline by association with the flotation medium comprising the sub-steps of:

5 piggybacking the secondary pipeline to the primary pipeline; and

pumping sufficient flotation medium into the secondary pipeline to cause the primary pipeline to float.

Date: 6 September 2018

Fig. 1
PRIOR ART











Fig. 9






2/10

LLFig. 2AFig. 2B





3/10





Fig. 3AFig. 3BFig. 3CFig 3D

4/10

**Fig. 3E****Fig. 3F****Fig. 3G**

5/10

Fig. 4AFig. 4BFig. 4CFig. 4D

Fig. 5AFig 5BFig. 5CFig 5D

7/10




Fig. 6A




Fig. 6B




Fig. 6C




Fig. 6D





Fig. 7C

Fig. 7D

9/10







Fig. 8

10/10

Fig. 10Fig. 11Fig. 12