



AU9463314

(12) PATENT ABRIDGMENT (11) Document No. AU-B-63314/94
(19) AUSTRALIAN PATENT OFFICE (10) Acceptance No. 665309

- (54) Title
IMPROVEMENTS TO FILTRATION DEVICES FOR TREATMENT OF LIQUIDS SUCH AS WATER
- International Patent Classification(s)
(51)^s **B01D 024/22 B01D 024/24 B01D 024/46**
- (21) Application No. : **63314/94** (22) Application Date : **25.05.94**
- (30) Priority Data
- (31) Number (32) Date (33) Country
93 06479 28.05.93 FR FRANCE
- (43) Publication Date : **01.12.94**
- (44) Publication Date of Accepted Application : **21.12.95**
- (71) Applicant(s)
DEGREMONT
- (72) Inventor(s)
BERNARD CAPON
- (74) Attorney or Agent
DAVIES COLLISON CAVE , 1 Little Collins Street, MELBOURNE VIC 3000
- (56) Prior Art Documents
**US 5032294
EP 036793**
- (57) Claim

1. A filtering device for the clarification of liquids, especially industrial or waste waters, said device comprising an open tank provided with a floor possessing nozzles and supporting a filtering bed, side channels for admitting untreated water into said tank, a removal conduit for removing filtered water, means for enabling washing of the material of the filtering bed and an axial channel for removal of washing waters, said device being characterised in that a bottom portion of the filtering device, below the floor, is separated along its longitudinal axis by a watertight partition defining two independent cells.

665309

AUSTRALIA
PATENTS ACT 1990
COMPLETE SPECIFICATION

NAME OF APPLICANT(S):

Degremont

ADDRESS FOR SERVICE:

DAVIES COLLISON CAVE

Patent Attorneys

1 Little Collins Street, Melbourne, 3000.

INVENTION TITLE:

Improvements to filtration devices for treatment of liquids such as water

The following statement is a full description of this invention, including the best method of performing it known to me/us:-

The present invention relates to improvements made to filtering devices for the clarification of liquids, especially industrial or waste waters.

The present proprietor has developed open filters named "AQUAZUR", which are described in particular in the "Memento Technique de l'Eau" (Technical Review of Water) - page 772 - 783 - Vol. 2 - 9th Edition - published by the company DEGREMONT - 1989 - (Editions Lavoisier) to which the reader may refer.

This type of filtering device comprises an open tank made of concrete, comprising a floor which is also generally made of concrete and fitted with nozzles, on which the bed of filtering material is arranged, untreated water being supplied via supply channels arranged laterally along the tank, the filtered water being removed below the floor via an axial, longitudinal conduit. In this type of known filter, the particles of the filtering bed are washed by admitting washing water and air below the floor possessing nozzles, the washing waters being removed via a longitudinal channel arranged along the axis of the tank.

These filtering installations are satisfactory. However, embodiments of the present invention propose to make improvements thereto which make it possible, in particular, to limit the instantaneous rinsing flow rate on filters with large surface area, given that the limit on producing large filters of this type is currently the instantaneous rinsing flow rate. Moreover, embodiments of the invention propose to improve the supplying of such large filters with water to be filtered, by producing equal distribution of this supply over the entire length of the filter.

According to the present invention there is provided a filtering device for the clarification of liquids, especially industrial or waste waters, said device comprising an open tank provided with a floor possessing nozzles and supporting a filtering bed, side channels for admitting untreated water into said tank, a removal conduit for removing filtered water, means for enabling washing of the material of the filtering bed and an axial channel for removal of washing



waters, said device being characterised in that a bottom portion of the filtering device, below the floor, is separated along its longitudinal axis by a watertight partition defining two independent cells.

Preferably, each cell of the filtering device comprises an inlet for the washing water, a washing air inlet and a regulating valve.

Preferably, the side channels for supplying water to be filtered are arranged laterally along the tank of the filtering device and are designed so as to fulfil a double function, said double function being

- equal distribution of the water to be treated over the entire length of each cell of the filtering device during a filtering phase, and

- equal distribution of the cleaning water used during a phase of washing of the material of the filtering bed.

Embodiments of the invention will now be described by way of example only with reference to the accompanying drawings in which:-

- Figure 1 is a cross-section, through a vertical plane, of a filtering device according to an embodiment of the present



invention, represented in the filtering phase and;

- Figure 2 is a similar view to Figure 1 representing the filtering device in the washing and cleansing phase of one of its cells.

5 Referring to the drawings, and more particularly to Figure 1, a filter¹⁵ ~~according to the present invention~~ ~~has been~~ shown which, as stated hereinabove, constitutes an improvement to the "AQUAZUR" filter designed by the present proprietor.

10 This is therefore an open filter intended for industrial or waste water clarification installations with a high flow rate and which can be washed simultaneously or successively with air and with water. As is seen in Figure 1, such a filter is in the form of a tank
15 made of concrete comprising a filter floor 12, generally made of concrete and of the type with nozzles. This floor supports the layer of filtering material 14,14', generally consisting of sand. The untreated water to be filtered is supplied via side channels 18,18'. The
20 washing water and air are introduced, in the phase of washing the filter, below the filtering floor, the washing waters being removed using a conduit 24 placed at the lower part of an axial longitudinal channel 17 defined by two longitudinal partitions 16,16'. These
25 arrangements are described in the work mentioned hereinabove, to which the reader is invited to refer.

In order to limit the instantaneous rinsing flow rate on a filter of the type described hereinabove, of large size, the present invention provides a watertight
30 separating partition 20 below the floor 12 of the filter, making it possible to define two independent filtering cells. In the example considered, each of these cells therefore comprises a filtering bed, 14,14' respectively, an enclosure for collecting the filtered water 15,15'
35 respectively, and a conduit 22,22' respectively for removing the filtered water and for supplying washing air and water.

Clearly, the fact that each cell of the filter is made separate leads to the provision of two inlets for



the washing water and two inlets for the washing air, as well as two regulating valves slaved to the same level. However, this does not constitute a drawback, in view of the fact that these regulating valves are smaller and hence less expensive than a single valve which would be necessary on a conventional filtering device with a single cell and with a large size.

In the filtering device ~~which forms the subject of the present invention~~, the channels 18, 18' provided on the tank for supplying untreated water which is to be treated are designed so as to produce, on the one hand, equal distribution of the untreated water over the entire length of the filter during the filtering phase and, on the other hand, equal distribution of the cleansing water during the phase of washing the material 14, 14' of the filter.

This arrangement makes it possible to avoid the drawbacks which are observed on filtering devices currently produced, which drawbacks result from time lapses between the supply of the untreated water at one of the ends of the filter and its arrival at the opposite end, which time lapses may be detrimental to the filtration, in particular in the case of coagulation on the filter. The imbalances thus observed may be substantial and the development in the nature of the flocculation may lead to different filtering speeds at different places on the filter.

Thus, ~~according to the present invention~~, each of the channels 18, 18' comprises a lower wall 26, 26' respectively, which is inclined towards the inside of the tank and comprises calibrated orifices 27 and 27' respectively, each of these lower walls being extended upwards by a vertical wall 28 and 28' respectively, also provided with orifices 29, 29' respectively.

The filter ~~according to the invention~~ has been represented in Figure 1 during the filtering phase. It is seen that the untreated water delivered by the channels 18 and 18' is introduced into the tank via the orifices 26, 26', 29, 29', the vertical partitions 28, 28' not



being immersed, which makes it possible to obtain a regular supply of the tank of the filter, over the entire length of the tank, which eliminates the drawbacks, mentioned hereinabove, of conventional installations of this type. The water which is filtered by passing over the filtering material 14, 14' of each cell is removed via the independent conduits 22, 22' from each cell.

This type of supply may also be applied to filtering settled water coming from highly loaded untreated water. In this case, the flocculation escaping from the settler still has a high sedimentation speed and preferential settling may be observed towards the supply region. By virtue of the equal distribution of the water, obtained by the above described design of the channels 18, 18' according to the invention, such a phenomenon may be eliminated or at last very substantially reduced.

Figure 2 represents the filter during the washing phase of one of its cells, (left-hand side when looking at the figure). The washing water 15 and/or the washing air is introduced below the floor of the filter via the conduit 22 and passes through the filtering bed 14, it is swept along by untreated water introduced through the orifices 27 made in the inclined wall 26 of the channel 18 and it is removed over the partition 16 into the axial channel 17 and through the removal conduit 24. This figure clearly shows the feature of the invention according to which each of the cells of the filter can be washed independently of the other.

The arrangements ^{described herein} ~~which form the subject of the present invention~~ may be applied in particular:

-to sand filters with a high layer height, in which, at the end of the blowing period, sometimes excessive air retention is observed, due to the use of certain reactants (especially cationic polymers);

- to granular activated-charcoal filters; for removing the charcoal from the filters it is necessary to fluidize it and the invention makes it possible, by fluidizing only one cell at a time, to economize on water;



- to bilayer filters; the rinsing flow rates normally applied on this type of filter vary from 40 to 60 m/h, which leads to extremely high instantaneous flow rates for filters
5 with a large surface area (for example 12,000 m³/h for a filter for 200 m²). Washing by individual cell makes it possible to divide these flow rates by two, with the result which this has not only on the washing pumps, the manifolds, etc., but also on the conduits and the washing water removal
10 network.

Throughout this specification, unless the context requires otherwise, the word "comprise", or variations such as "comprises" or "comprising", will be understood to imply the inclusion of a stated element or integer or group of
15 elements or integers but not the exclusion of any other element or integer or group of elements or integers.



THE CLAIMS DEFINING THE INVENTION ARE AS FOLLOWS:

1. A filtering device for the clarification of liquids, especially industrial or waste waters, said device comprising an open tank provided with a floor possessing nozzles and supporting a filtering bed, side channels for admitting untreated water into said tank, a removal conduit for removing filtered water, means for enabling washing of the material of the filtering bed and an axial channel for removal of washing waters, said device being characterised in that a bottom portion of the filtering device, below the floor, is separated along its longitudinal axis by a watertight partition defining two independent cells.

2. A device according to claim 1, characterised in that each cell of the filtering device comprises an inlet for the washing water, a washing air inlet and a regulating valve.

3. A device according to either one of the preceding claims, comprising a single washing pump, said pump being provided with a valve for distributing the washing water between the two cells of the filter.

4. A device according to any one of the preceding claims, characterised in that the side channels for supplying water to be filtered are arranged laterally along the tank of the filtering device and are designed so as to fulfil a double function, said double function being

- equal distribution of the water to be treated over the entire length of each cell of the filtering device during a filtering phase, and

- equal distribution of the cleaning water used during a phase of washing of the material of the filtering bed.



5. A device according to claim 4, characterised in that each side channel comprises a lower wall inclined towards the inside of the tank having calibrated orifices, said wall being extended upwards by a vertical wall having further calibrated orifices with the untreated water to be filtered being introduced through the calibrated orifices of the inclined and vertical walls, whereas the cleaning water is introduced, during washing of the cell in question, via the calibrated orifices provided in the lower walls.

6. A filtering device substantially as hereinbefore described with reference to the drawings.

DATED this 24th day of October, 1995

DEGREMONT

By Its Patent Attorneys

DAVIES COLLISON CAVE



ABSTRACT

Filtering device for the clarification of liquids, especially industrial or waste waters, is of the type which includes an open tank (10) provided with a floor (12) possessing nozzles and supporting the filtering bed, side channels for arrival of the untreated water, a removal conduit for the filtered water, means for washing the material of the filter and an axial channel for removal of the washing waters. The bottom of the filter, below the floor (12), is separated along its longitudinal axis by a watertight partition (20) defining two independent cells (14, 15 - 14' - 15') in the filter.

