



US011980810B2

(12) **United States Patent**
Yamano et al.

(10) **Patent No.:** **US 11,980,810 B2**

(45) **Date of Patent:** ***May 14, 2024**

(54) **INFORMATION PROCESSING SYSTEM,
OPERATION DEVICE, AND OPERATION
DEVICE CONTROL METHOD**

(71) Applicant: **Sony Interactive Entertainment Inc.,**
Tokyo (JP)

(72) Inventors: **Ikuo Yamano,** Tokyo (JP); **Yusuke
Nakagawa,** Kanagawa (JP); **Shinichi
Hirata,** Kanagawa (JP); **Yuichi
Machida,** Kanagawa (JP); **Yoichi
Nishimaki,** Kanagawa (JP)

(73) Assignee: **Sony Interactive Entertainment Inc.,**
Tokyo (JP)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

This patent is subject to a terminal dis-
claimer.

(21) Appl. No.: **17/725,863**

(22) Filed: **Apr. 21, 2022**

(65) **Prior Publication Data**

US 2022/0241684 A1 Aug. 4, 2022

Related U.S. Application Data

(63) Continuation of application No. 16/311,778, filed as
application No. PCT/JP2017/017909 on May 11,
2017, now Pat. No. 11,344,797.

(30) **Foreign Application Priority Data**

Jul. 26, 2016 (JP) 2016-146604

(51) **Int. Cl.**

G06F 3/01 (2006.01)
A63F 13/20 (2014.01)

(Continued)

(52) **U.S. Cl.**

CPC **A63F 13/285** (2014.09); **A63F 13/23**
(2014.09); **A63F 13/24** (2014.09); **G06F 3/01**
(2013.01); **G06F 3/016** (2013.01)

(58) **Field of Classification Search**

CPC **A63F 13/28**; **A63F 13/285**; **A63F**
2300/1037; **A63F 2300/302**; **G06F 3/01**;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,555,894 A 9/1996 Doyama
5,734,373 A 3/1998 Rosenberg
(Continued)

FOREIGN PATENT DOCUMENTS

CN 101610877 A 12/2009
CN 104043246 A 9/2014
(Continued)

OTHER PUBLICATIONS

International Search Report for related PCT Application No. PCT/
JP2017/004763, 2 pages, dated Apr. 18, 2017.

(Continued)


Primary Examiner — Lawrence S Galka

(74) *Attorney, Agent, or Firm* — Matthew B. Dernier,
Esq.

(57) **ABSTRACT**

An operation device has a movable portion movable
between a first position and a second position. The movable
portion is operated by a user while the operation device is
gripped by the user. The operation device receives informa-
tion identifying a control mode and control information
defined for each control mode as an instruction related to
control of a tactile force sense, and controls the tactile force
sense presented to the movable portion by using the received
control information in the control mode identified by the
received information.

7 Claims, 7 Drawing Sheets



(56)

References Cited

FOREIGN PATENT DOCUMENTS

WO	9712357	A1	4/1997
WO	2005116802	A1	12/2005
WO	2013099742	A1	7/2013
WO	2015092966	A1	6/2015
WO	2016051986	A1	4/2016
WO	2016105496	A1	6/2016
WO	2016114269	A1	7/2016
WO	2017150128	A1	9/2017
WO	2017150129	A1	9/2017

OTHER PUBLICATIONS

International Preliminary Report on Patentability and Written Opinion for related PCT Application No. PCT/JP2017/004763, 11 pages, dated Sep. 13, 2018.

International Search Report for related PCT Application No. PCT/JP2017/017909, 7 pages, dated Jul. 18, 2017.

International Search Report for related PCT Application No. PCT/2017/004978, 4 pages, dated Mar. 14, 2017.

International Search Report for related PCT Application No. PCT/JP2017/018914, 2 pages, dated Aug. 22, 2017.

International Preliminary Report on Patentability and Written Opinion for related PCT Application No. PCT/JP2017/017909, 17 pages, dated Feb. 7, 2019.

International Preliminary Report on Patentability and Written Opinion for related PCT Application No. PCT/JP2017/018914, 13 pages, dated Feb. 7, 2019.

International Preliminary Report on Patentability and Written Opinion for related PCT Application No. PCT/PCT/2017/004978, 13 pages, dated Jan. 31, 2019.

Notification of Reasons for Refusal for related JP Application No. 2018-528391, 9 pages, dated Apr. 23, 2019.

Extended European Search Report for related EP Application No. 17833789.5, 10 pages, dated May 23, 2019.

Supplementary Search Report for related European Search Report for corresponding Application No. 17833805, 12 pages, dated Jul. 19, 2019.

Decision of Refusal for related Japanese Patent Application No. 2018-528391, 10 pages, dated Jul. 9, 2019.

Extended European Search Report for related European Application No. 17759599.8, 7 pages, dated Sep. 9, 2019.

Korean Office Action for related Application No. 1020197002594, 11 pages, dated Sep. 18, 2019.

Extended European Search Report for corresponding Application No. 17833805.9, 14 pages, dated Nov. 6, 2019.

Notification of Reasons for Refusal for corresponding Application No. JP2018-529371, 9 pages, dated Oct. 29, 2019.

International Search Report for corresponding PCT Application No. PCT/JP2017/035570, 8 pages, dated Dec. 26, 2017.

Office Action for corresponding Korean Application No. 10-2019-7002594, 10 pages, dated Mar. 26, 2020.

International Search report for related application PCT/JP2017/038937, 4 pages, dated Jan. 30, 2018.

International Preliminary Report on Patentability and Written Opinion for related PCT Application No. PCT/JP2017/035570, 20 pages, dated Apr. 9, 2020.

International Preliminary Report on Patentability and Written Opinion for related PCT Application No. PCT/JP2017/038937, 14 pages, dated May 7, 2020.

Notice of Reason for Refusal for corresponding JP Application No. 2019-214619, 6 pages, dated Sep. 2, 2020.

Notice of Reason for Refusal for corresponding JP Application No. 2019-184529, 10 pages, dated Sep. 2, 2020.

Notice of Reason for Refusal for corresponding JP Application No. 2019-221160, 6 pages, dated Sep. 18, 2020.

Notice of Reasons for Refusal for related application JP Application No. 2020104664, 10 pages, dated Mar. 29, 2021.

Notice of Reasons for Refusal for related application JP Application No. 2019549971, 8 pages, dated Apr. 20, 2021.

Extended European Search Report application EP Application No. 21159343.9, 11 pages, dated May 21, 2021.

The First Office Action for related CN Application No. 201780044599.0, 20 pages, dated Jun. 4, 2021.

First Office Action for corresponding CN Application No. 201780044603.3, 21 pages, dated Jun. 29, 2021.

Office Action for related JP Application No. 2021-099339, 8 pages, dated Jun. 16, 2022.

* cited by examiner

FIG. 1




FIG. 2




FIG. 3






FIG. 4



224

FIG. 5
(A)



(B)




FIG. 6



FIG. 7





FIG. 8
(A)



(B)





FIG. 9



1

INFORMATION PROCESSING SYSTEM, OPERATION DEVICE, AND OPERATION DEVICE CONTROL METHOD

CROSS REFERENCE TO RELATED APPLICATIONS

This is a continuation application of U.S. patent application Ser. No. 16/311,778, accorded a filing date of Dec. 20, 2018, allowed, which is a national phase application of International Application No. PCT/JP2017/017909, filed May 11, 2017, which claims priority to Japanese Application No. JP 2016-146604, filed Jul. 26, 2016, the entire disclosures of which are hereby incorporated by reference.

TECHNICAL FIELD

The present invention relates to an information processing system, an operation device, and a control method for the operation device.

BACKGROUND ART

An operation device in a game machine for home use or the like detects an operation performed by a user, such as depression of a button, a shake of the operation device, or the like, and sends out information indicating the detected operation of the user to a main unit of the game machine or the like. In addition, such operation devices include an operation device that presents a tactile force sense to the user by using an actuator or the like.

SUMMARY

Technical Problem

However, the above-described conventional operation device having a tactile force sense presenting function presents a tactile force sense according to an instruction from the main unit of the game machine or the like. Thus, when a tactile force sense is to be presented in response to an operation of the user, the content of the operation of the user is sent out to the main unit, a parameter necessary to control the tactile force sense is obtained by calculation on the main unit side, the parameter is sent out from the main unit to the operation device, and the operation device performs an operation of presenting the tactile force sense on the basis of the parameter. It therefore takes time to present the tactile force sense after the operation is performed. Tactile force senses that can be presented are thus limited.

The present invention has been made in view of the above-described actual situation. It is an object of the present invention to provide an operation device capable of presenting tactile force senses in various modes and a control method for the operation device.

Solution to Problem

According to one mode of the present invention for solving the problem of the foregoing conventional example, there is provided an operation device having a movable portion movable between a first position and a second position, the movable portion being operated by a user while the operation device is gripped by the user, the operation device including: receiving means for receiving information identifying a control mode and control information deter-

2

mined for each control mode as an instruction related to control of a tactile force sense; and control means for controlling the tactile force sense presented to the movable portion by using the received control information in the control mode identified by the received information.

Advantageous Effect of Invention

According to the present invention, it becomes possible to present tactile force senses in various modes.

BRIEF DESCRIPTION OF DRAWINGS

FIG. 1 is a perspective view of an operation device according to an embodiment of the present invention as viewed from a front side.

FIG. 2 is a perspective view of the operation device according to the embodiment of the present invention as viewed from a back side.

FIG. 3 is a block diagram depicting an example of a configuration of the operation device according to the embodiment of the present invention.

FIG. 4 is a schematic diagram depicting an example of a movable portion of the operation device according to the embodiment of the present invention.

FIG. 5 is an explanatory diagram conceptually depicting relation between an arm and a button cover according to the embodiment of the present invention.

FIG. 6 is a functional block diagram depicting an example of the operation device according to the embodiment of the present invention.

FIG. 7 is an explanatory diagram depicting an example of the content of a packet transmitted and received in an information processing system according to the embodiment of the present invention.

FIG. 8 is an explanatory diagram depicting an example of setting information used by the operation device according to the embodiment of the present invention.

FIG. 9 is a flowchart depicting an example of operation of the information processing system according to the embodiment of the present invention.

DESCRIPTION OF EMBODIMENT

An embodiment of the present invention will be described with reference to the drawings. It is to be noted that the size, ratio, arrangement, and the like of each part in the following description are an example, and that the example of the present embodiment is not limited to sizes, ratios, and arrangements depicted in the figures and the like. As illustrated in FIG. 1, an information processing system according to the embodiment of the present invention includes an operation device 10 and a main device 20 such as a game machine for home use or the like, the main device 20 being connected to the operation device 10 by radio or wire. The operation device 10 outputs the content of an instruction operation received from a user to the main device 20. In addition, the operation device 10 receives instructions input from the main device 20, and controls various parts. Detailed operation of the operation device 10 will be described later.

In the example of the present embodiment, the operation device 10 is set as an operation device to be fitted to either the left hand or right hand of the user. An example of the operation device 10 is as illustrated in FIG. 1 and FIG. 2. FIG. 1 is a perspective view of the operation device 10 as

viewed from a front side. FIG. 2 is a perspective view of the operation device 10 as viewed from a back side.

The operation device 10 includes a gripping portion 21 gripped by the user and an operating portion 22. The gripping portion 21 forms substantially the shape of a polygonal column. The operating portion 22 is formed continuously from the gripping portion 21. In the example of FIGS. 1 and 2, the operating portion 22 includes, on a front side, a sensor portion 221 and a button operating portion 222, and includes, on a back side, a finger sensor 223 and a rocking button 224 corresponding to a movable portion according to the present invention. As illustrated in FIG. 3, the operation device 10 also includes a circuit unit 100 within a main body of the operation device 10. The circuit unit 100 includes a control unit 11, a storage unit 12, an interface unit 13, and a communicating unit 14.

The control unit 11 is a program control device such as a microcomputer or the like. The control unit 11 operates according to a program stored in the storage unit 12. In the present embodiment, the control unit 11 receives, from the main device 20, information identifying a control mode and control information defined for each control mode as an instruction related to control for presenting a tactile force sense via the rocking button 224 as the movable portion. The control unit 11 then controls the tactile force sense to be presented to the user in response to a moving operation by the user of the rocking button 224, by using the received control information in the control mode identified by the received information. Operation of the control unit 11 will be described later. The storage unit 12 is a memory device. The storage unit 12 retains the program executed by the control unit 11. The storage unit 12 also operates as a work memory for the control unit 11.

The interface unit 13 is connected to various parts of the operating portion 22. The interface unit 13 receives various kinds of signals such as signals indicating user instructions input from the sensor portion 221, the button operating portion 222, and the like, and outputs the signals to the control unit 11. The interface unit 13 also outputs instructions input from the control unit 11 to various parts of the operating portion 22.

The communicating unit 14 includes, for example, a radio communication interface for Bluetooth (registered trademark) or the like or a wire communication interface for universal serial bus (USB), a wired local area network (LAN), or the like. The communicating unit 14 is connected to the main device 20, and sends and receives various signals to and from the main device 20.

In the present embodiment, a fixture is fixed to one side of either a left side surface or a right side surface of the operation device 10. The fixture is, for example, an annularly formed flexible belt. The user operating the operation device 10 in the present example uses the operation device 10 in a state in which the index to little fingers of the user himself/herself are passed through the fixture, and the main body of the operation device 10 is fixed at a position abutting against the base of the thumb of the user. In the example of FIGS. 1 and 2, a state is depicted in which the operation device 10 is fixed with the right side surface side of the operation device 10 pressed against the palm of a hand of the user. In addition, suppose that the size of the operation device 10 is approximately a size such that when the user wearing the operation device 10 after passing the fingers through the fixture naturally grips the operation device 10, the distal joint of the thumb of the user reaches the button operating portion 222 on the front side of the operation device 10. That is, in the present embodiment, at least a part

of the buttons or the like of the operating portion 22 including the rocking button 224 are arranged in a range reached by the digit of the user when the user grips the gripping portion 21.

Specifically, when the user wearing the operation device 10 naturally grips the operation device 10, the index finger of the user is at a position touching the rocking button 224 of the operation device 10, and the user grips the gripping portion 21 with the palm of the hand, the middle finger, the third finger, and the little finger. Needless to say, even when the user opens the hand from this state, the operation device 10 does not fall because the operation device 10 is fixed to the hand of the user by the fixture.

The sensor portion 221 is disposed at a position slightly below a position that the distal joint side of the thumb of the user reaches, that is, a position to which the proximal joint side of the thumb of the user is in proximity, when the user naturally grips a device main body 210, for example. The finger sensor portion 221 detects the thumb of the user in a detectable range, the detectable range being a relatively wide angle range from the left side surface side to the right side surface side of the front of the operation device 10, and the detectable range being centered about a direction normal to the surface of the operation device 10 on the front side of the operation device 10. Then, a position at which the thumb is detected (an angle within the above-described angle range) and a distance from the finger sensor portion 221 to the thumb of the user are detected, and detection result information including these pieces of information is output to the control unit 11. The finger sensor portion 221 may be any sensor portion such as a camera, an optical sensor, a pyroelectric sensor, an electrostatic capacitive sensor, or the like.

The button operating portion 222 includes at least one button. When the user performs an operation of depressing the button, the button operating portion 222 outputs information identifying the depressed button to the control unit 11. The finger sensor 223 detects whether or not the middle to little fingers of the user are in proximity to (or touching) the gripping portion 21 of the operation device 10. Then, information indicating a result of the detection is output to the control unit 11.

The rocking button 224 corresponds to the movable portion according to the present invention, and is a button capable of rotational movement with respect to the main body of the operation device 10 between a first position where the rocking button 224 projects to the back side of the operation device 10 and a second position where the rocking button 224 is pressed in to the main body side of the operation device 10. The rocking button 224 is pressed in to the second position by the index finger or the like of the user, and is biased by an elastic body or the like to return to the first position when the user releases the finger.

The operation device 10 according to the present embodiment expresses the texture of a virtual object that the user virtually holds, by presenting a tactile force sense to the finger of the user by the rocking button 224. Specifically, the tactile force sense is presented to the user by changing a movable range of the rocking button 224, and presenting a reaction force in response to an operation of the user (a force resisting a force with which the user presses in the rocking button 224). It is to be noted that the present embodiment is not limited to the present example. The disposition and mode of the movable portion are not limited to those illustrated here as long as a tactile force sense can be presented to a part of a hand of the user by, for example, changing the movable portion to a member disposed in the vicinity of the palm of a hand of the user instead of the

rocking button **224**, and presenting a tactile force sense to the palm of the hand of the user.

Specifically, in the present embodiment of this example, as illustrated in FIG. 4, the rocking button **224** includes a button cover **224b** as a movable member, a button cover supporting portion **30**, a position sensor **31** detecting the position of the rocking button **224**, and a regulating portion **32** regulating the movable range of the button cover **224b** to a specified range.

Here, the position sensor **31** is a potentiometer or the like attached to a hinge as a rotational center of an arm **323**. The position sensor **31** outputs information on the rotational angle of the arm **323**. Alternatively, the position sensor **31** may be a potentiometer or the like attached to a hinge as a rotational center of the rocking button **224** rather than the arm **323**. In this case, the position sensor **31** outputs information on the rotational angle of the rocking button **224**. In addition, the regulating portion **32** includes, for example, a motor **321** as an actuator, a control circuit **322** for the motor **321**, and the arm **323** as a regulating member driven by the actuator.

The button cover **224b** has a surface pressed by the finger of the user. The button cover supporting portion **30** has a hinge fixed to the main body side of the operation device **10**. The button cover supporting portion **30** supports the button cover **224b** in a state of being rotatable in a predetermined angle range (between the first position and the second position described above) about the hinge. In addition, the button cover supporting portion **30** biases the button cover **224b** toward the first position by an elastic body such as a spring or the like. Thus, in a state in which the user is not pressing, the button cover **224b** moves to the first position.

The button cover **224b** can be pressed in to a position abutting against the arm **323** to be described later (which position will be referred to as an abutment position) between the first position at which the button cover **224b** projects to the back side of the operation device **10** and the second position at which the button cover **224b** is pressed in to the main body side of the operation device **10**. Accordingly, when the user grips the main body of the operation device **10**, and presses the button cover **224b** with the index finger, the button cover **224b** moves to the abutment position without the user feeling any particular resisting force (by merely resisting only the biasing force of the button cover supporting portion **30**). A tactile force sense of touching a hard object is presented when the button cover **224b** abuts against the arm **323** at the abutment position.

When the user further grips with force and thereby increases the pressing force against the button cover **224b**, and when the motor **321** is rotated so as to retreat the arm **323** to the main body side of the operation device **10**, a tactile force sense can be presented to the user as if the object were deformed by the gripping force. At this time, a difference in hardness can be presented at the same time by changing the rotational speed of the motor **321** according to the pressing force against the button cover **224b** by the user.

The motor **321** of the regulating portion **32** is a motor capable of controlling the rotational angle, the motor being a servomotor, a stepping motor, or the like. The motor **321** may be a so-called geared motor integrated with a gear head. The motor **321** performs rotating operation according to a current input from the control circuit **322**.

The control circuit **322** for the motor **321** receives input of a torque control value τ and information D on a rotational direction from the control unit **11**. The control circuit **322** then supplies the motor **321** with a current whose magnitude is in accordance with the torque control value τ and whose

direction corresponds to the information D on the rotational direction. The motor **321** rotates in the specified rotational direction with a torque corresponding to the current. Specifically, when the rotational direction is "up," a tip end (abutting part) of the arm **323** is rotated in a direction of moving to the button cover **224b** side. In addition, when the rotational direction is "down," the tip end (abutting part) of the arm **323** is rotated in a direction of moving to the main body side of the operation device **10**.

When the rotational direction is "up," the tip end (abutting part) of the arm **323** is rotated in a direction of moving to the button cover **224b** side, the torque produced by the motor **321** and the pressing force against the button cover **224b** by the user (which pressing force is transmitted by the arm **323** as a rotational force in an opposite direction from the rotational direction of the motor **321**) cancel each other, and the button cover **224b** moves toward the second position at a speed corresponding to an amount by which the pressing force exceeds the torque. In addition, when the pressing force and the torque balance out, the button cover **224b** is in an immobile state at a position at the time point of the balancing out.

In addition, the control circuit **322** may receive input of a rotational angle θ in place of the torque control value τ from the control unit **11**. In this case, the control circuit **322** rotates the tip end (abutting part) of the arm **323** in a direction of moving to the button cover **224b** side by controlling rotation of the motor **321** to the input rotational angle θ . Incidentally, control that rotates the motor to a determined rotational angle and stops the motor is widely known, and therefore detailed description thereof will be omitted here.

In yet another example, the control circuit **322** may receive input of a current value or a voltage value in place of the torque control value τ from the control unit **11**. In this case, the control circuit **322** supplies a current having a magnitude corresponding to the input value to the motor **321**, or applies a voltage having a magnitude corresponding to the input value to the motor **321**.

The arm **323** is attached to a rotating shaft of the motor **321**, and regulates the movable range of the button cover **224b** according to the rotational angle θ of the motor **321**. Specifically, in the example of the present embodiment, as illustrated in FIG. 4, the arm **323** is disposed on the back side of the button cover **224b**, that is, the main body side of the operation device **10** (on the movement trajectory of the button cover **224b**). The arm **323** includes an arm member **323a** and a disk-shaped arm main body **323c**. In the example of FIG. 4, the center of the disk-shaped arm main body **323c** is fixed to the rotating shaft of the motor **321**. The arm member **323a** is formed integrally with the arm main body **323c**, and is a projecting portion projecting from the arm main body **323c** in a direction tangential to the circumference of the arm main body **323c**.

According to the arm **323** in the example of FIG. 4, the position of the tip end (abutting portion) of the arm member **323a** moves within the movable range of the button cover **224b** according to the rotational angle of the motor **321**. Thus, the button cover **224b** can move to the abutment position abutting against the abutting portion of the arm member **323a**.

FIG. 5 is a diagram conceptually depicting relation between the arm **323** and the button cover **224b** in the example of FIG. 4. As conceptually depicted in FIG. 5, when an angle (φ in FIG. 5(B)) formed between the longitudinal direction (projecting direction) of the arm member **323a** and the moving direction of the button cover **224b** is equal to or

more than a predetermined value (for example, 90 degrees), the button cover **224b** can move freely between the first position (X in FIG. 5(A)) and the second position (Y in FIG. 5(A)) without the moving range of the button cover **224b** being regulated (by merely resisting only the biasing force of the button cover supporting portion **30**). In the example of FIG. 5(A), the rotational angle of the arm **323** is assumed to be "0," and φ is assumed to be 90 degrees.

On the other hand, when the arm **323** is rotated by the rotational angle θ by the motor **321**, and the angle φ formed between the longitudinal direction (projecting direction) of the arm member **323a** and the moving direction of the button cover **224b** becomes less than the predetermined value (for example, 90 degrees), the tip end of the arm member **323a** is located within the movement trajectory of the button cover **224b**. Incidentally, in this case, the position of an angle determined by a counterclockwise rotation by an angle γ in the drawing from an initial position of the arm **323** is set as a maximum position θ_{max} (set in advance), the maximum position is set as a reference, and the rotational angle θ of the arm **323** is defined as an angle θ by which the arm **323** returns in the direction of the initial position from the reference angle. That is, in the present example, Rotational Angle $\theta = \gamma$ at the initial position, and $\theta = 0$ when a maximum rotational angle is formed. Then, the smaller the rotational angle θ of the arm **323** becomes, that is, the closer to "0" the formed angle φ becomes, the more the abutment position (position of Y' in FIG. 5(B)) of the arm member **323a** and the button cover **224b** approaches the first position (X in FIG. 5(B)) of the button cover **224b**. Thus, an amount by which the button cover **224b** can be pressed in (movable range) is regulated.

Incidentally, the regulating portion **32** is not limited to the example of the motor **321** and the arm **323** as illustrated in FIG. 4. As in a case of a linear actuator and a solenoid as a regulating member moved by the linear actuator, for example, when the regulating member can regulate the moving range of the button cover **224b** to a specified range, the regulating member may regulate the moving range of the button cover **224b** by linearly moving in the moving direction of the button cover **224b** and having one end side of the regulating member abut against the button cover **224b**.

The main device **20**, for example, includes a camera and images the user. In each predetermined timing, the main device **20** detects the position of the hand of the user within a real space, and obtains, by calculation, a virtual position of the hand of the user within a game space, the virtual position corresponding to the detected position within the real space. Then, a tactile force sense to be presented to the hand of the user is determined as game processing on the basis of information on the obtained virtual position. As an example, when the main device **20** detects that the user is holding a gun in a game, and pulling a trigger, the main device **20** outputs, to the operation device **10**, an instruction to perform control so as to present a tactile force sense when the trigger of the gun is pulled.

Description will next be made of operation of the control unit **11** of the operation device **10** according to the embodiment of the present invention. In the present embodiment, as illustrated in FIG. 6, the control unit **11** includes: a receiving unit **51** that receives an instruction related to control of a tactile force sense; a tactile force sense control unit **52** that generates an instruction for controlling the tactile force sense to be presented to the user in response to an operation of the rocking button **224** by the user on the basis of the received instruction; and an output unit **53** that outputs the generated instruction.

The receiving unit **51** receives the instruction related to control of the tactile force sense from the main device **20**. In the present embodiment, this instruction is transmitted in a state of being included in an instruction data packet transmitted repeatedly in each predetermined timing from the main device **20**. Here, the transmission timing of the instruction data packet may be approximately timing of 10 to 100 Hz (timing of 10 to 100 times per second). In addition, as illustrated in FIG. 7, the instruction data packet includes a header part H including a packet identifier (N), a tactile force sense instruction part F, and an other data part D. In addition, the tactile force sense instruction part F includes information (M) identifying a control mode and control information (P) defined for each control mode.

The receiving unit **51** receives the information (M) identifying the control mode and control information (P) defined for each control mode by receiving the packet. A concrete example of these pieces of information will be described later.

The tactile force sense control unit **52** controls the tactile force sense presented in response to a moving operation of the rocking button **224** as the movable portion by using the control information received together with the information identifying the control mode in the control mode identified by the information received in the receiving unit **51**. In the example of the present embodiment, the tactile force sense control unit **52** controls the tactile force sense presented to the user by controlling the motor **321** as an actuator. This operation of the tactile force sense control unit **52** will be described later in detail.

The output unit **53** outputs a control instruction (a torque control value, a current value, a voltage value, or the like) input from the tactile force sense control unit **52** to the control circuit **322** for the motor **321**.

The operation of the tactile force sense control unit **52** will be described in the following by using concrete examples. In an example of the present embodiment, control modes specified by instructions from the main device **20** include:

- (1) a first control mode that controls the actuator by specifying a target position of the actuator and information of a control gain,
- (2) a second control mode that controls the actuator by specifying the voltage value of a voltage supplied to the actuator or the current value of a current supplied to the actuator, and
- (3) a third control mode that instructs the operation device **10** side to control the actuator by specifying which setting information to use among a plurality of pieces of setting information in which control information for positional ranges of the actuator or the movable portion is set.

(Example of Specifying Target Position and Gain)

First, in the case of (1) specifying the target position of the actuator and the information of the control gain (first control mode), the information of the control gain which information is received from the main device **20** includes a gain (p gain p) for a position error and a gain (d gain d) for a speed. In this case, the tactile force sense control unit **52** receives, as positional information of the actuator from the position sensor **31**, information on the rotational angle θ of the arm **323** rotated by pressing in the rocking button **224**. In the example here, the target position of the actuator which target position is included in control information is specified as the rotational angle θ_t of the arm **323**.

Then, letting G be a gain constant, the tactile force sense control unit **52** defines the torque control value τ output to the control circuit **322** of the motor **321** as the actuator as

$$\tau = (p \times |\theta - \theta_t| + d \times \Delta\theta) / Gk$$

where $\Delta\theta$ is a difference between a value θ_p input from the position sensor **31** last time and a value θ input from the position sensor **31** this time, that is,

$$\Delta\theta = \theta - \theta_p$$

$|x|$ denotes calculation of an absolute value of x . The tactile force sense control unit **52** outputs the torque control value τ calculated here to the output unit **53**.

Further, in the case of the present example, on the basis of a difference $\theta - \theta_t$ between an actual angle of the arm **323** and a target position, the tactile force sense control unit **52** outputs, to the output unit **53**, the rotational direction of the motor **321** as “up” when $\theta - \theta_t > 0$ or as “down” otherwise. Incidentally, the determination of “up” or “down” may be made on the basis of the sign of the torque control value τ without using $\theta - \theta_t$, and “up” may be output to the output unit **53** when $\tau > 0$ or “down” may be output to the output unit **53** otherwise. This takes into consideration a fact that, depending on a control method, the rotational direction of the motor **321** can be “down” even when $\theta - \theta_t > 0$.

Incidentally, the tactile force sense control unit **52** in the present example may set the torque control value τ to “0” and output the torque control value τ to the output unit **53** when $|\theta - \theta_t|$ is less than a predetermined value.

In addition, the target position of the actuator may be specified as information on the position of the rocking button **224** as the movable portion (rotational angle). In this case, the position sensor **31** outputs information on the rotational angle of the rocking button **224** rather than that of the arm **323**.

(Example of Specifying Voltage Value or Current Value)

In addition, in the case of (2) specifying the voltage value of a voltage supplied to the actuator or the current value of a current supplied to the actuator (second control mode), the tactile force sense control unit **52** outputs the current value received or the voltage value received to the output unit **53** as it is. In the present example, receiving the input of the current value or the voltage value via the output unit **53**, the control circuit **322** supplies the current value or the voltage value to the motor **321**. The receiving unit **51** in the present example receives information indicating a rotational direction (information indicating “up” or “down”) from the main device **20** together with the current value or the voltage value. The tactile force sense control unit **52** then outputs the information indicating the rotational direction to the output unit **53** as it is.

(Example of Specifying Duration)

In the example of specifying the voltage value or the current value, the receiving unit **51** may receive, from the main device **20**, information identifying the second control mode and information related to a duration of control together with the current value or the voltage value.

In this case, the tactile force sense control unit **52** clocks an elapsed time from a time point of outputting the current value or the voltage value to the control circuit **322** by using clocking means not depicted (which clocking means may be publicly known clocking means that can be implemented by a clock signal generating unit and a counter, for example), and instructs the control circuit **322** to stop the operation of the motor **321** (for example, outputs “0” as the current value) when the duration specified by the received information has passed. According to this, even when information related to control of the actuator is not newly received from the main device **20**, it is possible to end processing at a point in time that the specified time has passed, and present a tactile force

sense intended by the processing performed on the main device **20** side even when communication with the main device **20** is interrupted.

(Example of Specifying Control Pattern)

Description will next be made of an example of (3) instructing the operation device **10** side to control the actuator by specifying which setting information to use among a plurality of pieces of setting information in which control information for positional ranges of the actuator or the movable portion is set (third control mode).

Incidentally, the positional range of the actuator in the present embodiment actually represents the range of the rotational angle of the arm **323**. However, the range of the angle may be the range of the rotational angle of the rotating shaft of the actuator itself, or may be otherwise (a case where the arm **323** is connected via a reduction gear or the like). In the latter case, the position on an output side of the reduction gear corresponds to the position of the actuator.

In the present example, the storage unit **12** of the operation device **10** stores, in advance, setting information including at least one set of a positional range of the actuator or the movable portion and control information. As illustrated in FIG. **8**, which represents an example of shooting a gun in a game, for example, this information includes a set of information θ_{1min} indicating a lower limit of the positional range as information indicating the positional range of the actuator, a target position $\theta_{t1} = 40$ as the control information, and control gains p_1 and d_1 , or a set of information θ_{2min} indicating a lower limit of the positional range as information indicating the positional range of the actuator and information CV on the voltage value (or information CI on the current value) as the control information. Incidentally, an example of using the positional range of the actuator is illustrated in FIG. **8** and the following description. However, in a case of using the positional range of the movable portion, it suffices to use information indicating the positional range of the movable portion in place of the positional range of the actuator in FIG. **8** and the following description.

The tactile force sense control unit **52** in the present example receives information on the rotational angle θ of the arm **323** or the rocking button **224** as the movable portion, and refers to the control information associated with the information on the positional range including the received rotational angle θ in the specified setting information. When the control information is a set of the target position and the control gains, the tactile force sense control unit **52** controls the actuator by processing similar to that of the first control mode. In addition, when the referred-to control information is the voltage value or the current value, the tactile force sense control unit **52** controls the actuator by processing similar to that of the second control mode.

Specifically, in the example of FIG. **8**, when the positional range becomes less than θ_{2min} (for example, 40), an “up mode” is set, and control is performed with the target position θ_{t1} and the control gains p_1 and d_1 (the rotational direction is up, though not depicted) in an interval from $\theta_{1min} = 20$ to $\theta_{2min} = 40$ as a lower limit of a next positional range. In addition, during this “up mode,” control is performed such that the voltage value CV is 200 in an interval from $\theta_{2min} = 40$ to $\theta_{3min} = 80$ as a lower limit of a next positional range, and control is performed such that the voltage value CV is -30 in an interval from $\theta_{3min} = 80$ to $\theta_{4min} = 125$ as a lower limit of a next positional range (FIG. **8(A)**, where a positive voltage value CV indicates control in an up rotational direction, and a negative voltage value CV indicates control in a down rotational direction).

In addition, when the positional range becomes equal to or more than $\theta_{4\min}$ ($\theta_{4\min}$ is, for example, 125 in a case where $\theta=130$ is a maximum angle), a “down mode” is set, and control is performed with the target position $\theta t_2=20$ and control gains p_2 and d_2 as the control information (FIG. 8(B), where the rotational direction is down in this case). Thus, the control information related to the first control mode and the control information related to the second control mode may be mixed in the setting information.

According to the present example, as illustrated in FIG. 8(A), when the user presses in the rocking button 224 from the initial position (the rotational angle θ of the arm 323 is zero at the time of the initial position), the user presses in the rocking button 224 without receiving any resistance at all (while merely resisting the biasing force attempting to return the rocking button 224 to the initial position) until the position of the arm 323 becomes $\theta=20$. The user receives a presentation of a tactile force sense such that the resistance gradually increases while the position of the arm 323 is in a range from $\theta=20$ to $\theta=40$. A tactile force sense of a relatively strong reaction force (force attempting to push back) is presented while the position of the arm 323 is in a range from $\theta=40$ to $\theta=80$. When the user presses in the rocking button 224 until the position of the arm 323 becomes $\theta=80$, the user receives a tactile force sense as if the reaction force disappeared suddenly.

This precisely corresponds to a state in which a tactile force sense corresponding to a kickback feeling of a gun, as it were, is presented, that is, corresponds to a sequence in which there is play at first when the trigger of a pistol or the like is pulled, there is a slight reaction force until a hammer is pulled, a strong force thereafter becomes necessary to return the hammer, a bullet is fired when the hammer then returns, and the trigger is set free.

In addition, the tactile force sense control unit 52 may estimate a speed or a force and change a gain on the basis of a change speed of the positional information of the arm 323, that is, on the basis of movement of a finger of the user. Specifically, the control gain is made to differ between a case where the movement of the finger of the user (change speed of the positional information of the arm 323) is less than a threshold value determined in advance and a case where the movement of the finger of the user exceeds the threshold value. For example, the control gain may be set stronger (so as to present a stronger reaction force) in the case where the movement of the finger of the user (change speed of the positional information of the arm 323) exceeds the threshold value determined in advance than in the case where the movement of the finger of the user is less than the threshold value.

(Vibration Presentation)

In the present embodiment, a vibration may also be presented to the user by vibrating the rocking button 224. Specifically, the main device 20 gives an instruction to vibrate the rocking button 224 between the first position on the upper side and the second position on the lower side.

Then, when the control unit 11 of the operation device 10 receives the instruction to present the vibration, the control unit 11 switches, in each predetermined timing, between the first control mode in which the target position of the actuator is set at the first position and the second control mode in which information setting the rotational direction to “down” is output together with the current value or the voltage value.

When the vibration is presented by the method of thus alternately switching between the first control mode and the second control mode, the position of a vibration limit on the upper side (first position) can be controlled. In addition,

according to this method, also for the second position, a distance by which the arm 323 moves (which distance is equal to a distance by which the rocking button 224 moves when the user is pressing in the rocking button 224) depends on the length of a time during which control in the second control mode is performed. When switching from the second control mode to the first control mode is performed in each fixed time, the second position is substantially constant irrespective of the magnitude of a force with which the user presses in the rocking button 224. Therefore the second position can be controlled by changing the timing of switching between the first control mode and the second control mode.

Incidentally, in the above-described case, in place of the method of alternately switching between the first control mode and the second control mode, the control unit 11 may switch the target position between the first position on the upper side and the second position on the lower side in each predetermined time in the first control mode. In addition, the second control mode may be used, and switching may be performed alternately between the rotational directions “up” and “down” in each predetermined time.

In addition, as for the timing of switching between the first control mode and the second control mode, the control unit 11 may, for example, detect the relative positions of the rocking button 224 and the arm 323 during driving in the “up” direction, perform driving in the first control mode until the arm 323 and the rocking button 224 come into contact with each other, and perform driving in the second control mode after the arm 323 and the rocking button 224 come into contact with each other.

(Control Based on Actual Vibration Range)

In addition, in the control of the vibration presentation, the following control may be performed on the basis of information on the range of the position detected by the position sensor 31. Specifically, for example, when information on the specified first and second (upper limit side and lower limit side) positions represents 20 degrees and 60 degrees, but information on the position detected by the position sensor 31 represents 20 degrees between 40 degrees and 60 degrees due to an effect of a force with which the user presses in the rocking arm, the control unit 11 controls the upper limit side or the lower limit side (for example, the second position as the lower limit side) so that the width of the vibration becomes an intended width of the vibration, that is, controls the upper limit side and the lower limit side to 40 degrees and 80 degrees, for example. Incidentally, the upper limit side may also be controlled at this time.

(Another Example: Rapid-Fire Gun)

In addition, in the example of FIG. 8, when the positional range is equal to or more than $\theta_{4\min}$ (supposing that $\theta=130$ is a maximum angle), control may be performed with the target position $\theta t_2=125$ and the control gains p_2 and d_2 as the control information (supposing that the rotational direction is up in this case). According to the present example, slightly returning the trigger when fully pulling the trigger and then fully pulling the trigger is repeated. In the other example, a tactile force sense can be presented as if the gun were blazing.

In addition, a method of presenting a rapid-fire feeling of a gun is not limited to the present example, but may be as follows, for example. When the positional range of the arm 323 or the rocking button 224 exceeds a predetermined value (start condition value) (when $\theta=100$ is a maximum angle, for example, the start condition value is $\theta=50$, which is $\frac{1}{2}$ of the maximum angle), for example, the operation device 10 makes a transition to a “rapid-fire mode,” and

presents a vibration by switching the actuator between the up and down directions in each predetermined timing.

Specifically, when the actuator is set in the up direction, the target position $\theta_t=5$ is set as the control information, and when the actuator is set in the down direction, the target position $\theta_t=95$ is set as the control information (values obtained by providing a predetermined margin to a minimum value and a maximum value are set in consideration of a case where control tends to act in an overshooting manner).

In addition, in the present example, the operation device **10** ends the “rapid-fire mode” and stops controlling the actuator when the positional range of the arm **323** or the rocking button **224** becomes less than a predetermined value (stop condition value). Here, the stop condition value may be the same as the start condition value, or may be different from the start condition value. For example, the stop condition value may be on a side in closer proximity to the first position than the start condition value, or may be, for example, $\theta=30$.

Further, it is assumed that the target position is set at a time of control of the actuator in this case. However, without limitation to this, when the actuator is set in the up direction, the voltage value CV of the voltage supplied to the actuator may be set to a negative value CV1 determined in advance, or when the actuator is set in the down direction, the voltage value CV of the voltage supplied to the actuator may be set to a positive value CV2 determined in advance (it is assumed in this case that a negative voltage value CV indicates control in the up rotational direction and that a positive voltage value CV indicates control in the down rotational direction), and the voltage value CV may be alternately set to CV1 and CV2 in each predetermined timing to present a vibration. The presentation of this vibration may adopt a method of alternately performing first control and second control, as described earlier, instead of alternately setting the voltage value.

Incidentally, the start condition value and the end condition value described above may be provided with hysteresis. Specifically, when the positional range of the arm or the rocking button **224** before the “rapid-fire mode” is set (before a start of determination processing of the start condition value) exceeds the start condition value, control may be performed so as not to make a transition to the “rapid-fire mode” until the positional range of the arm or the rocking button **224** once falls below the start condition value and thereafter exceeds the start condition value again.

In addition, during the “rapid-fire mode,” in consideration of a case where control tends to act in an overshooting manner, control may be performed so as to end the “rapid-fire mode” when a time during which the positional range of the arm **323** or the rocking button **224** is less than the stop condition value exceeds a threshold value determined in advance, rather than ending the “rapid-fire mode” immediately when the positional range of the arm **323** or the rocking button **224** falls below the stop condition value. When control is thus performed as if filtering is performed, a natural rapid-fire feeling can be presented. Incidentally, this filtering may be performed by a low-pass filter such as uses a moving average.

(Control by Game Program)

Further, the main device **20** may output an instruction to set the control gain as game processing. In a case of a game in which rapid fire of a gun is performed, for example, the control gain may be controlled to be changed according to the number of remaining bullets.

In addition, the main device **20** may perform control that reduces the gain according to a predetermined condition. Specifically, the control gain may be controlled (for example, control may be performed which reduces the control gain) on the basis of a total play time (sum of play time in each round), the number of times of game play, a time from a start of play in each round (play time), or an elapsed time from a start of a predetermined operation as this condition. For example, in a case where an operation of continuing firing a machine gun is performed, control is performed so as to decrease the control gain according to an elapsed time from a start of an operation of firing the machine gun. This prevents a strong vibration from being presented continuously, while providing a feeling of performing rapid fire of the machine gun. Operability is thereby improved.

(Another Example of Presenting Force Sense)

Further, when a force of pressing the rocking button **224** by the user is larger than the force of the actuator, the rocking button **224** cannot be raised against the force of the user, and a force sense felt as if to hit an object and be repelled by the object cannot be presented.

Accordingly, in a certain example of the present embodiment, when the positional information of the arm **323** which positional information is indicated by information input from the position sensor **31** is θ , and θ_t ($\theta_t > \theta$) is given as a target of the rotational angle of the arm **323** from the main device **20**, the tactile force sense control unit **52** controls the arm **323** to rotate to the rotational angle θ_t by driving the actuator. At this time, the tactile force sense control unit **52** repeats, each predetermined timing, determining the positional information θ of the arm **323** which positional information is indicated by the information input from the position sensor **31**, and determining whether or not the state of $\theta_t > \theta$ is unchanged for a time determined in advance (whether or not the rocking button **224** is immovable for a predetermined time). When determining here that the rocking button **224** is immovable for the predetermined time, the tactile force sense control unit **52** may set anew the target θ_t of the rotational angle of the arm **323** to $\theta_t = \theta - \Delta\theta$ (where $\Delta\theta > 0$), and control the actuator.

In the present example, the rocking button **224** is pulled in instead of being raised. However, because the rocking button **224** is temporarily pulled in, the force applied to the rocking button **224** by the user is temporarily weakened. Applying a force of pushing back again in response to the weakening of the force applied to the rocking button **224** by the user causes the user to feel the force of pushing back more strongly. In addition, because of an inertial force caused by pushing back from the pulled-in position, the force of pushing back is applied more strongly. Thus, as compared with a case where no change is provided at all, a feeling similar to that of being repelled is given.

Incidentally, in the case where this control is performed, the tactile force sense control unit **52** may correct the target value to $\theta_t - \Delta\theta$ and perform control in advance when the target value θ_t of the rotational angle of the arm **323** is given. Thus, the arm **323** is rotated by an extra $\Delta\theta$ in advance, and the regulated range of the rocking button **224** is set to a position at which the rocking button **224** is raised by a corresponding amount. This enables control of pulling in by $\Delta\theta$ to be performed at any time afterward.

In addition, when the force with which the user presses the rocking button **224** is relatively large, an amount of change $\delta\theta$ in the positional information θ of the arm **323** which positional information is indicated by the information input from the position sensor **31**, the amount of change $\delta\theta$

being obtained per unit time while the tactile force sense control unit 52 is performing control that rotates the motor 321 in the “up” direction, for example, may be less than a predetermined threshold value $\delta\theta t$.

When such a state occurs, the tactile force sense control unit 52 may provide a period of stopping rotational control of the arm 323. Specifically, when the tactile force sense control unit 52 intends to perform control with the target of the rotational angle of the arm 323 set at θt , the tactile force sense control unit 52 may perform control in N (integer $N>1$) divided stages instead of performing control with the target of the rotational angle of the arm 323 set at θt as the final target. That is, $\Delta\theta t=(\theta t-\theta)/N$ is set (where θ denotes the rotational angle of the arm 323 at a point in time of a start of this control), and control is performed which effects movement in steps of $\Delta\theta t$ at time intervals ΔT determined in advance from the rotational angle θ of the arm 323 at the point in time of the start.

Similarly, also in the case where control is performed by the voltage value supplied to the motor 321, instead of performing control by the voltage value CV to be specified, a predetermined voltage value CV' is supplied to the motor 321 at time intervals ΔT determined in advance for only an infinitesimal time τ that can be different from ΔT (suppose that the rotational direction is a direction in which the original control is performed).

Here, the predetermined voltage value CV' may be a maximum voltage CV_{max} that can be supplied to the motor 321, or a voltage value higher than the voltage value CV to be specified may be calculated as the predetermined voltage value CV' by a predetermined method. For example, it suffices to perform multiplication by a predetermined value larger than one, or perform addition of a predetermined value larger than zero. In either case, a setting is made such that $CV'=CV_{max}$ when a result of the calculation exceeds the maximum voltage CV_{max} that can be supplied to the motor 321.

Thus controlling the rotational angle of the arm 323 stepwise, or discretely, as it were, instead of controlling the rotational angle of the arm 323 linearly until the target rotational angle is achieved can effectively provide the user with a feeling that the rocking button 224 is being raised.

Further, when the tactile force sense control unit 52 is given θt as the target of the rotational angle of the arm 323 from the main device 20, the tactile force sense control unit 52 compares this θt with the positional information θ of the arm 323 which positional information is indicated by the information input from the position sensor 31, and obtains $\sigma(\theta t-\theta)$. Here, $\sigma(X)$ denotes the positive or negative sign of X . Suppose that $\sigma(X)=-1$ when $X<0$, that $\sigma(X)=1$ when $X>0$, and that $\sigma(X)=0$ when $X=0$.

Then, the tactile force sense control unit 52 sets the target of the rotational angle of the arm 323 to $\theta t'=\theta-\sigma(\theta t-\theta)\times\Delta\theta$ ($\Delta\theta$ is an infinitesimal angle determined in advance), and controls the actuator for only a time τ (this τ is an infinitesimal time determined in advance) so as to set the arm 323 at the rotational angle $\theta t'$. After the time τ thereafter passes, the tactile force sense control unit 52 sets the target of the rotational angle of the arm 323 to the target angle θt specified from the main device 20, and starts controlling the actuator so as to set the arm 323 at the rotational angle θt .

According to the present example, the arm 323 is controlled so as to move temporarily in an opposite direction from the specified moving direction (preparatory operation), and thereafter the arm 323 is controlled so as to move in the specified direction (main operation). When the preparatory operation is thus performed before the main operation,

movement of the main operation is emphasized, and the user feels the movement at a time of the main operation more strongly.

Incidentally, the arm 323 may be rotatable to the outside of an initial movable range (whole of a movable range not regulated by the arm 323) of the rocking button 224 to make this operation more effective. That is, in the example of FIG. 5(A), when the button cover 224b of the rocking button 224 can be pressed in to the position Y, the arm 323 may be rotatable until the rotational angle θ becomes a negative rotational angle. At this time, the button cover 224b may be regulated by another member so as not to be able to move below the position Y, and may be in a state of not abutting against the arm 323. However, the arm 323 can be pulled in in an opposite direction from the original rotational direction.

Incidentally, this control can be applied also to the case where the voltage value of the voltage supplied to the actuator or the current value of the current supplied to the actuator is specified (second control mode). Specifically, when the tactile force sense control unit 52 receives, from the main device 20, information indicating the rotational direction (information indicating “up” or “down”) together with the current value or the voltage value, the tactile force sense control unit 52 instructs the output unit 53 to set the rotational direction to an opposite direction from the direction received from the main device 20, and set the current or voltage to be supplied to the actuator to a predetermined current value or a predetermined voltage value (which may be a current value or a voltage value determined in advance, or may be the input value itself). Then, when a time τ (suppose that this τ is an infinitesimal time determined in advance as in the foregoing) thereafter passes, the tactile force sense control unit 52 outputs the information indicating the rotational direction and the information indicating the current value or the voltage value, which information is received from the main device 20, to the output unit 53 as they are.

Thus, the arm 323 is controlled so as to move temporarily in an opposite direction from the specified moving direction (preparatory operation), and the arm 323 is thereafter controlled so as to move in the specified direction (main operation).

In addition, the operations of these various force sense presentations may be used in combination with each other. For example, when the main operation is performed after the preparatory operation, the rotational control of the arm 323 may be performed discretely, as it were, while a period of stopping the rotational control is provided. (Prevention of Chattering)

Incidentally, in an example of the present embodiment, the main device 20 may detect a speed at which the user moves the operation device 10, and make an actuator control parameter sent out to the operation device 10 differ according to the detected speed. Here, the speed at which the user moves the operation device 10 may be detected on the basis of an image obtained by imaging the user by a camera or the like connected to the main device 20. In a case where the operation device 10 has an acceleration sensor (not depicted), and sends out the value of acceleration detected by the acceleration sensor, the speed may be detected on the basis of an integrated value (accumulated value) of the acceleration detected by the acceleration sensor.

Specifically, this parameter is a cutoff frequency of a low-pass filter. The output unit 53 of the control unit 11 of the operation device 10 calculates an average of input values (torque control values, current values, or the like) from the

tactile force sense control unit **52** for immediately preceding M times corresponding to the cutoff frequency (the value of M changes according to the cutoff frequency) (that is, calculates a moving average for the immediately preceding M times), and outputs a result of the calculation to the control circuit **322**. The faster the movement of the operation device **10** by the user, the lower the cutoff frequency set by the main device **20**.

Thus, in a case where the main device **20** presents a tactile force sense when the position of the hand of the user in the virtual space of a game touches an object disposed within the virtual space, for example, the movement of the actuator becomes slower as the user moves the hand faster (the operation device **10** fitted to the hand is moving faster). As the user moves the hand more slowly (in a case where the hand is moved slowly along the surface of an object within the virtual space, for example), on the one hand, the actuator is driven along the shape of the object within the virtual space, and a corresponding tactile force sense is presented.

Consequently, the actuator is prevented from being controlled so as to vibrate finely (such that chattering occurs) according to the position of the object within the virtual space when the user is moving the hand fast.

Further, in a case where a vibrating device such as a vibrator or the like is fixed within the gripping portion **21**, this control may be performed for the vibrating device, and the main device **20** may detect the speed at which the user moves the operation device **10**, and make a vibrating device control parameter sent out to the operation device **10** differ according to the detected speed. That is, the main device **20** sets the cutoff frequency of the low-pass filter for the vibrating device lower as the user moves the operation device **10** faster.

(Operation)

The information processing system according to the embodiment of the present invention has the above configuration, and operates as in the following example. In each predetermined timing (for example, timing of each frame), the main device **20** detects the position of the hand of the user, and determines the content of a tactile force sense to be presented to the hand of the user according to game processing or the like on the basis of the detected position of the hand. In the present embodiment, the tactile force sense to be presented to the hand of the user is replaced by presenting the tactile force sense to a finger of the user. The user receives the presentation of the tactile force sense only by the finger. However, the user feels as if the tactile force sense were presented to the whole of the hand.

In the present embodiment, as illustrated in FIG. **9**, in each predetermined timing described above, the main device **20** generates a packet (referred to as an instruction packet) including information specifying a control mode and control information or setting information as the content of a tactile force sense to be presented to the hand of the user (S1), and sends out the packet to the operation device **10** (S2). Specifically, suppose here that a packet is sent out which includes information specifying the third control mode as the control mode and information specifying the setting information illustrated in FIG. **7**.

The operation device **10** obtains, by the position sensor **31**, information on the rotational angle θ of the arm **323** (or the rocking button **224**) as the positional information of the actuator (S3). Then, the specified setting information is referred to, and a control value corresponding to the rotational angle obtained in processing S3 is obtained (S4). Specifically, when the obtained rotational angle is $\theta=30$, the target position θ_1 and the control gains p_1 and d_1 , which are

a control value between $\theta_{1\min}=20$ and $\theta_{2\min}=40$ as the lower limit of a next positional range, are obtained as the control value. Then, letting G be a gain constant, the torque control value τ output to the control circuit **322** for the motor **321** as the actuator is defined as

$$\tau=(p \times |\theta-\theta_1|+d \times \Delta \theta) / G k$$

The calculated torque control value τ is output to the control circuit **322**, and rotational control of the motor **321** is performed (S5).

The operation device **10** repeats the processing of S3 to S5 until a new instruction packet is received from the main device **20**. The timing of this repetition is, for example, a cycle of approximately 1 kHz. Meanwhile, rotational control of the motor **321** is performed according to the rotational angle of the arm **323** (or the rocking button **224**) on the basis of the control value set in the setting information.

Thus, in the present embodiment, until a next instruction packet is received from the main device **20**, the operation device **10** autonomously performs the operation of presenting a tactile force sense on the basis of the content of the instruction packet received previously. It is therefore possible to perform the presentation of a tactile force sense in accordance with operation timing, and present tactile force senses in various modes.

(Example of Presenting Bow Drawing Feeling)

In addition, the main device **20** may not only determine a tactile force sense to be presented on the basis of the position of one of a left hand and a right hand to which hand to present the tactile force sense (hand to which the operation device **10** is fitted in a case where the operation device **10** is fitted to one hand) but also determine a tactile force sense to be presented on the basis of the positions of the left and right hands. For example, the main device **20** may set the second control mode as the control mode of a tactile force sense to be presented, and increase the current value as a distance between the hands is increased (suppose that the rotational direction is up). According to the present example, when an operation of drawing a bow is performed, for example, a tactile force sense can be presented so as to make a finger of the hand of the user wearing the operation device **10** feel a force such as pushes out to the outside (such as opposes a drawing force) as the distance between the left and right hands is increased (as a bow is drawn more strongly).

When such a third control mode is provided, a desired force sense presentation can be made to be performed by merely specifying one of the pieces of setting information stored on the operation device **10** side in advance without a developer of a game program or the like on the main device **20** side specifying fine control.

(Modifications)

Needless to say, in the third control mode, instead of the main device **20** transmitting an instruction to select one of the pieces of setting information stored by the operation device **10** in advance, a developer of a game program or the like on the main device **20** side may specify fine control. Specifically, the main device **20** may send out information indicating the content of setting information (information including at least one set of the positional range of the actuator and control information) together with an instruction for the third control mode, and the operation device **10** may perform operation as the third control mode using the information as setting information.

In the present example, the operation device **10** may be further enabled to accumulate and store, in the storage unit **12**, the information indicating the content of the setting information which information is received from the main

device 20, and thereafter receive a specification. In this case, the main device 20 also sends out information (identification information) identifying the setting information to the operation device 10, and the operation device 10 stores the information indicating the content of the setting information in association with the identification information. It is therefore possible to receive a specification of the setting information later by using the identification information from the main device 20.

Incidentally, the operation device 10 according to the present embodiment may not only present a tactile force sense in response to a moving operation of the movable portion such as the rocking button 224 or the like, but also present a tactile force sense even when the movable portion is not moved.

In addition, in the example thus far, description has been made supposing that the button cover 224b and the arm 323 are not interlocked with each other. However, the button cover 224b and the arm 323 may be configured to be coupled to each other and interlocked with each other.

Also in the present example, the arm 323 is attached to the rotating shaft of the motor 321, and regulates the movable range of the button cover 224b according to the rotational angle θr of the motor 321. Then, the motor 321 performs a rotating operation by being supplied with a current from the control circuit 322 that supplies the motor 321 with the current having a magnitude corresponding to the torque control value τ input from the control unit 11.

In the present example of the present embodiment, suppose that the button cover 224b coupled to the arm 323 moves to the first position when the rotational angle θ of the motor 321 (angle on the output side of a reduction gear when the reduction gear is attached; the same applies hereinafter) is $\theta 0$, and that the button cover 224b moves to the second position when the rotational angle θ of the motor 321 is $\theta 1$ ($\theta 0 \neq \theta 1$).

Then, in the present example, while the torque control value τ is input from the control unit 11, the control circuit 322 supplies the motor 321 with a current having a magnitude corresponding to the torque control value τ . In addition, while the torque control value τ is not input from the control unit 11, whether or not the rotational angle θr of the motor 321 is equal to $\theta 0$ is determined. When the rotational angle θr of the motor 321 is not equal to $\theta 0$, a current having a magnitude determined in advance is supplied to the motor 321 to perform rotational control of the motor 321 toward the rotational angle $\theta 0$. It suffices to determine an amount of current supplied in this case experimentally as an amount of current of such a degree as to present a force of such a degree as to move the button cover 224b as a force corresponding to the biasing force that moves the button cover 224b to the first position when the button cover 224b is not pressed in the example in which the button cover 224b and the arm 323 are not coupled to each other.

(Control of Left and Right Devices)

In addition, in the present embodiment, in a case where both the left hand and the right hand of the user are fitted with operation devices 10, the main device 20 sends out an instruction related to control for presenting a tactile force sense to each of the operation devices 10 via rocking buttons 224.

The main device 20 determines, by a predetermined method, which of a tactile force sense presented by the operation device 10 fitted to the left hand and a tactile force sense presented by the operation device 10 fitted to the right hand is a main tactile force sense. This determination may be made on the basis of a specification in accordance with an

application program such as a game or the like, or it may be determined that the tactile force sense presented by one of the left and right operation devices 10 on a side where the presentation of the tactile force sense is specified last is the main tactile force sense. Further, the tactile force sense presented on a side where the magnitude (for example, the magnitude of amplitude or the like) of the presented tactile force sense is larger may be determined to be the main tactile force sense.

The main device 20 weakens control on the side of one of the left and right operation devices 10 on which side the main tactile force sense is not presented. For example, when determining that the operation device 10 on the right side is presenting the main tactile force sense, the main device 20 reduces the control value (for example, the torque control value) of the tactile force sense output to the operation device 10 on the left side, and thereby reduces power consumption.

REFERENCE SIGNS LIST

10 Operation device, 11 Control unit, 12 Storage unit, 13 Interface unit, 14 Communicating unit, 15 Power supply unit, 20 Main device, 21 Gripping portion, 22 Operating portion, 30 Button cover supporting portion, 31 Position sensor, 32 Regulating portion, 51 Receiving unit, 52 Tactile force sense control unit, 53 Output unit, 100 Circuit unit, 210 Device main body, 221 Sensor portion, 222 Button operating portion, 223 Finger sensor, 224 Rocking button, 224b Button cover, 321 Motor, 322 Control circuit, 323 Arm, 323a Arm member, 323c Arm main body

The invention claimed is:

1. An operation device, comprising:

a movable portion, movable between a first position and a second position via direct contact pressure by a user while the operation device is gripped by the user;
a receiving circuit for receiving information identifying a control mode, among a plurality of control modes, and control information determined for such control mode as an instruction related to control of a tactile force sense; and

a controller for controlling the tactile force sense presented to the movable portion by using the received control information in the control mode identified by the received information, wherein:

the receiving circuit receives setting information taken from one or more pre-stored profiles,

the control mode establishes which of the one or more pre-stored profiles is selected for use by the controller, the controller controls the tactile force sense presented to the movable portion in response to the selected one of the pre-stored profiles,

the movable portion includes an actuator, where the actuator is not movable via the direct contact pressure by the user,

when the receiving circuit receives, as the instruction related to the control of the tactile force sense, information including information identifying a first control mode, a target position as control information determined in advance for the first control mode, and a control gain of the actuator, and

the controller controls the tactile force sense presented to the movable portion by performing control of the actuator on a basis of a difference between a position of the actuator and the target position and the information of the control gain.

21

2. An information processing system, comprising:
an operation device having a movable portion, movable
between a first position and a second position via direct
contact pressure by a user while the operation device is
gripped by the user; and
a main device configured to communicate with the operation
device, and output an instruction related to control
of a tactile force sense provided to the user;
the operation device including
a receiving circuit for receiving information identifying a
control mode, among a plurality of control modes, and
control information defined for such control mode as an
instruction related to control of the tactile force sense
from the main device, and
a controller for controlling the tactile force sense presented
to the movable portion by using the received
control information in the control mode identified by
the received information, wherein:
the receiving circuit receives setting information taken
from one or more pre-stored profiles,
the control mode establishes which of the one or more
pre-stored profiles is selected for use by the controller,
the controller controls the tactile force sense presented to
the movable portion in response to the selected one of
the pre-stored profiles,
the movable portion includes an actuator, where the
actuator is not movable via the direct contact pressure
by the user,
when the receiving circuit receives, as the instruction
related to the control of the tactile force sense, information
including information identifying a first control
mode, a target position as control information determined
in advance for the first control mode, and a control
gain of the actuator, and
the controller controls the tactile force sense presented to
the movable portion by performing control of the
actuator on a basis of a difference between a position of
the actuator and the target position and the information
of the control gain.

3. The information processing system of claim 2, wherein
the at least one pre-stored profile contains at least one of: (i)
parametric data representing a plurality of possible positions
of the movable member between the first position and the
second position, inclusive, (ii) parametric data representing
a plurality of possible tactile forces presented to the movable
portion, and (iii) a functional relationship between the
plurality of possible tactile forces as a dependent variable
and the plurality of possible positions of the movable
member as an independent variable.

4. The information processing system of claim 2, wherein
when the receiving circuit receives, as the instruction
related to the control of the tactile force sense, information
identifying a second control mode and information of a control
voltage value or a control current value of the actuator as
control information determined in advance for the second
control mode,
the controller controls the tactile force sense presented to
the movable portion by performing control of the
actuator by controlling a voltage or a current supplied
to the actuator on a basis of the received control voltage
value or the received control current value.

22

5. The information processing system of claim 4, wherein
the receiving circuit further receives information related
to a duration of control together with the information
identifying the second control mode, and
the controller performs control of the actuator for only the
received duration.

6. The information processing system of claim 4, further
comprising:
a storing medium for storing setting information including
at least one set of information identifying a positional
range of the actuator or the movable portion and
control information, wherein
when the receiving circuit receives, as the instruction
related to the control of the tactile force sense, information
identifying a third control mode and information
identifying one piece of setting information in the
setting information stored by the storing medium,
the controller reads, from the storing medium, the set of
the information identifying the positional range of the
actuator or the movable portion and the control information,
the set being included in the identified setting
information, and controls the tactile force sense presented
to the movable portion by performing control of the
actuator on a basis of the control information
corresponding to the positional range of the actuator or
the movable portion, the positional range including a
position of the actuator or the movable portion.

7. A control method for an operation device, the operation
device having a movable portion movable between a first
position and a second position via direct contact pressure
by a user while the operation device is gripped by the user,
the control method comprising:
receiving information identifying a control mode, among
a plurality of control modes, and control information
determined for such control mode as an instruction
related to control of a tactile force sense, and
controlling the tactile force sense presented to the movable
portion by using the received control information
in the control mode identified by the received information,
wherein:
the receiving includes receiving setting information taken
from one or more pre-stored profiles,
the control mode establishes which of the one or more
pre-stored profiles is selected for use by the controller,
and
the controlling includes controlling the tactile force sense
presented to the movable portion in response to the
selected one of the pre-stored profiles,
the movable portion includes an actuator, where the
actuator is not movable via the direct contact pressure
by the user,
when the receiving includes receiving, as the instruction
related to the control of the tactile force sense, information
including information identifying a first control
mode, a target position as control information determined
in advance for the first control mode, and a control
gain of the actuator, and
the controlling includes controlling the tactile force sense
presented to the movable portion by performing control
of the actuator on a basis of a difference between a
position of the actuator and the target position and the
information of the control gain.