PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : A61B 5/00	A1	(11) International Publication Number:	WO 97/24059
		(43) International Publication Date:	10 July 1997 (10.07.97
(21) International Application Number: PCT/US9 (22) International Filing Date: 20 December 1996 (2)		DK, ES, FI, FR, GB, GR, IE, IT	
(30) Priority Data: 08/580,212 28 December 1995 (28.12.95	5) L	Published With international search report.	
(71) Applicant: CYGNUS, INC. [US/US]; 400 Penobsco Redwood City, CA 94063 (US).	ot Driv	е,	
(72) Inventors: KURNIK, Ronald, T.; 961 Haddock Stree City, CA 94404 (US). TAMADA, Janet; 1622 Avenue, Belmont, CA 94002 (US). TIERNEY, I 368 N. 6th Street, San Jose, CA 95112 (US). Russell, Owen; 76 Uranus Terrace, San Francis 94114 (US).	Ralsto Michae POTT	n l; S,	
(74) Agents: BOZICEVIC, Karl et al.; Fish & Richardse Suite 100, 2200 Sand Hill Road, Menlo Park, CA (US).		· 1	
(54) Title: CONTINUOUS MONITORING OF PHYSIOL	OGIC	AL ANALYTE	

(57) Abstract

A method for continual monitoring of a physiologic analyte in a subject includes steps of contacting the subject with a collection reservoir such that the analyte can move from the subject into the collection reservoir, the contents of the collection reservoir being in operative communication with a detector, collecting the analyte in the collection reservoir, using the detector to detect the analyte in the collection reservoir, and, once the analyte has been detected, rendering the analyte undetectable by the detector. Also, apparatus for continual monitoring of a physiologic analyte in a subject includes a collection reservoir for receiving the analyte from the subject, the contents of the collection reservoir being in operative relationship with a detector that detects the analyte in the reservoir, and means for rendering the analyte, once detected, undetectable by the reservoir.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
		IT	Italy	PL	Poland
BG	Bulgaria	JP	Japan	PT	Portugal
BJ	Benin Brazil	KE	Kenya	RO	Romania
BR	Belarus	KG	Kyrgystan	RU	Russian Federation
BY		KP	Democratic People's Republic	SD	Sudan
CA	Canada	Kı	of Korea	SE	Sweden
CF	Central African Republic	KR	Republic of Korea	SG	Singapore
CG	Congo	KZ	Kazakhstan	SI	Slovenia
CH	Switzerland	KŁ Li	Liechtenstein	SK	Slovakia
CI	Côte d'Ivoire		Sri Lanka	SN	Senegal
CM	Cameroon	LK		SZ	Swaziland
CN	China	LR	Liberia	TD	Chad
CS	Czechoslovakia	LT	Lithuania	TG	Togo
CZ	Czech Republic	LU	Luxembourg	-	_
DE	Germany	LV	Latvia	TJ	Tajikistan
DK	Denmark	MC	Monaco	TT	Trinidad and Tobago
EE	Estonia	MD	Republic of Moldova	UA	Ukraine
ES	Spain	MG	Madagascar	UG	Uganda
FI	Finland	ML	Mali	US	United States of America
FR	France	MN	Mongolia	UZ	Uzbekistan
GA	Gabon	MR	Mauritania	VN	Viet Nam

CONTINUOUS MONITORING OF PHYSIOLOGICAL ANALYTE Field of the Invention

This invention relates to continual measurement of indicia of the physiological state of a subject, and particularly to continual measurement of analytes in tissues and body fluids of a subject.

Background of the Invention

The physiologic state of a subject can by monitored by measurement of certain indicia.

Some such indicia, including the familiar "vital signs" such as the subject's body temperature, heart rate, respiratory rate, and the like can be measured

15 directly either without resort to instrumentation, or by use of simple instruments placed onto a body surface or within a body cavity. Body temperature measurement, for example, can be made directly by use of a thermometer or

- thermistor placed on the skin or within a body cavity.

 Other indicia of physiologic state that can be measured directly require the use of more complex instrumentation. Such indicia include electrocardiography and electroencephalography, for example, and the instrumentation for measuring such indicia may include
- apparatus affixed to the subject's skin or implanted within the body. Biochemical indicia of a subject's physiologic state can provide highly useful information. Such biochemical indicia include the presence and amounts in the subject's tissue or body fluids of certain
- 30 chemical species; by way of example, such chemical species may be or may have been ingested by or administered to the subject, or they may be metabolic products or byproducts or metabolic precursors, or they

- 2 -

may constitute parts of the subject's metabolic apparatus, such as enzymes and hormones and the like. Thus, the presence or amount of a drug or drug metabolite, for example in a sample of a subject's blood or urine, can provide an indication of the subject's history of use of the drug, or can provide an assurance that a dosage or route of administration is providing a suitable therapeutic level in the subject's tissues. And, as a well-known example, a measure of the amount of glucose in a subject's blood, or of ketones in the subject's urine, can provide useful information for management of hypoglycemia and hyperglycemia, particularly in diabetics.

Such biochemical indicia can be measured, for

example, in a sample of a fluid or tissue removed from
the subject's body; blood work and urinalysis, routine or
more complete, for example, can provide information
regarding such indicia. Where the subject's physiologic
state may change significantly over short periods of
time, samples for analysis of biochemical indicia may be
taken more frequently.

For some physiologic conditions the time scale for changes in the physiologic state can be short, so that removal and analysis of the appropriate sample at a preferred frequency is impractical. It is generally understood, for example, that more frequent sampling and analysis of a diabetic person's blood glucose, together with careful management of the person's sugar and insulin, can provide an improvement in quality of life and the lifespan of the diabetic; but removal of the blood sample is painful, and the apparatus surrounding the analysis of the sample is cumbersome and inconvenient to use. For some types of biochemical indicia, then, there is a need for methods for "continual" monitoring, that is to say, for measuring the biochemical indicia

- 3 -

over extended monitoring time periods (for example, around the clock; or 24 hours per day throughout the week; etc.) substantially without interruption, or in a continuing series of measurements at appropriately spaced intervals.

In some instances detectors may be available to directly detect the biochemical indicia in the range of concentrations that are pertinent to monitoring the physiologic state of the subject. In these instances, the detector may be implanted and left to reside within the tissue or internal body space, where the detector measures the biochemical analyte as it comes within detectable range of the detector, and records or transmits the resulting data for further use.

In other instances the biochemical indicia may not be directly detectable by known detectors. In these instances some treatment of the analyte is required as a step preliminary to detection. Such treatment may, for example, result in the analyte (or the analyte together with some other substance involved in the treatment) having a particular spectrum of radiation absorption (detectable for example colorimetrically) or of radiation (detectable for example by fluorescence detection). Or, the treatment may entail a specific chemical reaction (as for example by a substrate-specific catalyst such as an enzyme) that results in generation of a chemical species (for example an ion) that is directly detectable using a known detector.

Where some treatment of the analyte is required, a reservoir may be employed for collecting the analyte and carrying out the treatment. Such a reservoir can be held in operational proximity to (in some instances in contact with) the detector and within or in contact with a tissue or surface of the body of the subject to be monitored.

35 Conveniently, the reservoir can for example be placed on

- 4 -

the subject's skin; in this instance the analyte passes into the reservoir through the skin surface (the movement can be facilitated by a potential gradient), where it undergoes the treatment and is then detected.

Irrespective of the technique of detection, where the analyte is continually collected, it can accumulate in the reservoir, resulting in a progressively higher measurement over time, resulting in decreased reliability in subsequent measurements over the monitoring period.

5

10

Summary of the Invention

In one general aspect the invention features a method for continual monitoring of a physiologic analyte in a subject, by contacting the subject with a collection reservoir such that the analyte can move from the subject into the collection reservoir, the collection reservoir being in contact with a detector, collecting the analyte in the collection reservoir, using the detector to detect the analyte in the collection reservoir, and, once detection of the analyte is accomplished, rendering the analyte undetectable by the detector.

In some embodiments the analyte itself is not directly detected by the detector, but is instead processed through a detection cascade, the final step of which occurs at the detector. In such embodiments the step of using the detector to detect the analyte includes steps of treating the analyte to generate a detectable signal or a detectable chemical species that is detected by the detector. In some embodiments the step of treating the analyte includes contacting the analyte with a catalyst, such as an enzyme, that reacts with the analyte to produce a detectable chemical species; in preferred such embodiments the reaction of the catalyst and the enzyme further results in conversion of the analyte to a reaction product that is not detected by the detector

- 5 ~

(that is, the reaction product is removed from the
 detection cascade); and in preferred such embodiments the
 detection of the detectable chemical species by the
 detector results in conversion of the detectable chemical
 species to a reaction product that is not detected by the
 detector.

As a result, whether the analyte is detected directly by the detector, or is instead detected indirectly by being treated in a cascade of reactions 10 resulting in a detectable signal or detectable chemical species which is detected by the detector, the potential for detection of each analyte molecule is extinguished once detection occurs. As a significant consequence, there is no accumulation, over the monitoring time 15 period, of detectable signal or of detectable chemical species or of the analyte itself once detection has occurred. For any measurement at any time during the monitoring time, only that detectable analyte or detectable signal which has entered the collection 20 reservoir since the previous measurement, or that detectable signal or detectable chemical species that has been produced since the previous measurement, is The detector itself can therefore operate over measured. a narrower dynamic range than would be required if 25 detectable analyte or signal or detectable chemical species were permitted to accumulate over time. Significantly, there is no need for a differential measurement; that is, there is no accumulated measure to subtract from the instant measurement, and thus potential 30 compounding of error, notoriously problematic where differential measurements are required, is avoided. Moreover, saturation of the collection/detection system with the analyte is avoided by conversion of the analyte.

In some embodiments the collection reservoir is contacted with a surface of the subject's skin, and the

- 6 -

analyte moves from the subject through the skin surface into the collection reservoir, in most instances under the influence of a potential gradient such as an osmotic or ionic gradient, or an electrical or magnetic gradient, or a hydrostatic pressure gradient, for example; in some such embodiments the analyte moves passively through the skin surface, or its movement is enhanced by application of electrical energy (for example, by electroosmosis or by electrophoresis) or ultrasound energy (by sonophoresis), or the permeability of the skin to its movement is enhanced by applying to the skin surface a sweat inducing substance (such as, for example, pilocarpine) or a skin permeation enhancer.

In another general aspect the invention features

15 apparatus for continual monitoring of a physiologic
analyte in a subject, the apparatus including a
collection reservoir for receiving the analyte from the
subject, the contents of the collection reservoir being
in operative communication with a detector that detects

20 the analyte in the reservoir, and means for rendering the
analyte undetectable by the reservoir.

In some embodiments the analyte itself is not directly detected by the detector, and the reservoir contains analyte interacting means, which upon contact with the analyte results in production of a detectable signal or a detectable chemical species that is detected by the detector. In some such embodiments the analyte and the analyte contacting means associate to create a binding couple, and the detectable signal is generated by the association. In other such embodiments the analyte contacting means is a catalyst, such as an enzyme, which upon contact with the analyte produces the detectable signal or detectable chemical species; in preferred such embodiments the catalyst or enzyme reacts with the analyte itself, and the result is conversion of the

- 7 -

analyte to a reaction product that is undetectable by the detector as well as production of the detectable signal or detectable chemical species. Because each molecule of the analyte can effectively react only once with the catalyst, the undetectable reaction product passes out of the detection cascade.

In a particularly preferred embodiment, for continual measurement of blood glucose, the analyte is glucose, and the analyte contacting means is an enzyme 10 (for example, a glucose oxidase) that acts upon the glucose to substantially irreversibly produce a detectable chemical species (for example, hydrogen peroxide) and an undetectable reaction product (for example, gluconic acid); and the detector is an electrode 15 that senses the detectable chemical species by a substantially irreversible electrochemical redox reaction (for example, conversion of hydrogen peroxide to water and liberating oxygen).

Description of Preferred Embodiments

Before the method and apparatus of the invention is described and disclosed it is to be understood that this invention is not limited to the particular components or compositions described as such may, of course, vary. It is also to be understood that the terminology used herein is for the purpose of describing particular embodiments only, and is not intended to be limited, as the scope of the invention will be limited only by the appended claims.

It must be noted that as used in this

specification and the appended claims, the singular forms
"a", "an" and "the" include plural referents unless the
context clearly dictates otherwise. Thus, for example,
reference to "a molecule" includes a plurality of
molecules and different types of molecules.

- 8 -

Unless defined otherwise all technical and scientific terms used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this invention belongs. Although any materials or methods similar or equivalent to those described herein can be used in the practice or testing of the present invention, the preferred methods and materials are now described. All publications mentioned herein are incorporated herein by reference for the purpose of describing and disclosing the particular information for which the publication was cited in connection with.

In a preferred embodiment of the invention, for continual monitoring of glucose, the collection reservoir is applicable to the subject's skin, it contains an 15 electrolyte and a glucose oxidase, which in a coupled reaction in the presence of oxygen converts glucose to gluconic acid, generating hydrogen peroxide. The detector is an electrode that detects hydrogen peroxide in a redox reaction. Such a collection and detection scheme, and 20 apparatus for carrying it out, is disclosed for example in copending patent applications U.S. Serial Nos. 08/373,931; 08/501,664; 08/526,732, pertinent parts of which are hereby incorporated herein by reference. Here, the analyte (glucose), which is not directly detected by 25 the detector, passes from the subject transdermally into the collection reservoir, where it contacts the enzyme (glucose oxidase), which reacts with the analyte to produce a detectable chemical species (hydrogen peroxide) and in the same reaction converts the analyte to a 30 reaction product (gluconic acid) that is not detected by the detector; when activated, the detector (electrode sensor) detects the detectable chemical species and, in the same (redox) reaction, converts it to an undetectable chemical species. As a result, each molecule of glucose 35 that enters the reservoir and is processed through the

- 9 -

detection cascade is detected only once.

In this example, as in others, the detector needn't be activated throughout the collection period; copending patent applications U.S. Serial Nos. 5 08/265,844; 08/265,048; 08/373,931 disclose, among other matters, various schemes in which collection cycles alternate with detection cycles throughout the monitoring time In these particular examples, suppressing (or not activating) detection during collection provides for a 10 short time interval in which the analyte (glucose) enters the collection reservoir and is there converted by reaction with a catalyst (glucose oxidase) to a nondetectable chemical species (gluconic acid) and to a detectable chemical species (hydrogen peroxide): during 15 this short collection interval the detectable species (hydrogen peroxide) accumulates. Then the detector is activated, and the accumulated detectable species (hydrogen peroxide) is simultaneously detected and converted (by the redox reaction) into a nondetectable 20 chemical species. An advantage of this scheme can be that it provides for availability of a higher quantity of hydrogen peroxide to the sensing electrode during the measurement cycle, so that the electrode need not be as sensitive as would be required if the electrode remained 25 activated throughout the collection cycle, and measuring hydrogen as it evolved from the detection cascade. While this can be an advantage in some circumstances, it is not necessarily a requirement, as the sensitivity of the electrode can be increased, or the detectable signal may 30 be elevated by other techniques.

Further in the examples described in U.S. Serial Nos. 08/265,844; 08/265,048; 08/373,931, the method further includes a step of applying an electrical (iontophoretic) current to the skin, to assist by electroosmosis the transdermal movement of the glucose

- 10 -

into the collection reservoir. A further motivation for suppressing (or not activating) the detector during the collection phase is avoidance of possible conflict between the iontophoretic current and the detection current produced at the sensor. Such considerations would not pertain where an electric current is not applied; and any such conflicts can be avoided by other techniques.

Thus, whether detection is suppressed (or not activated) during collection, providing for a short

10 accumulation period before measurement, or not, it can be advantageous according to the present invention to render the analyte (and any detectable signals or species) undetectable, once detection of the analyte has been accomplished either directly or indirectly.

15 The instant invention is shown and described herein in what is considered to be the most practical, and preferred embodiments. It is recognized, however, that departures may be made therefrom which are within the scope of the invention, and that modifications will occur to one skilled in the art upon reading this disclosure.

- 11 -

What is claimed is:

1. A method for continual monitoring of a physiologic analyte in a subject, comprising steps of:

contacting the subject with a collection reservoir such that the analyte can move from the subject into said collection reservoir, the contents of the collection reservoir being in operative relationship with a detector,

collecting the analyte in the collection 10 reservoir,

using the detector to detect the analyte in the collection reservoir, and

once the analyte has been detected, rendering the analyte undetectable by the detector.

- 2. The method of claim 1 wherein the step of using the detector to detect the analyte includes steps of treating the analyte to generate a detectable signal or a detectable chemical species that is detected by the detector.
- 3. The method of claim 2 wherein the step of treating the analyte includes contacting the analyte with a catalyst that reacts with the analyte to produce a detectable chemical species
- 4. The method of claim 3 wherein the step of treating the analyte includes contacting the analyte with an enzyme.
- 5. The method of claim 3 wherein the reaction of the catalyst and the catalyst further results in conversion of the analyte to a reaction product that is 30 not detected by the detector

- 12 -

- 6. The method of claim 2 wherein the detection of the detectable chemical species by the detector results in conversion of the detectable chemical species to a reaction product that is not detected by the 5 detector.
- 7. The method of claim 1 wherein the step of contacting the subject with a collection reservoir comprises contacting said collection reservoir with a surface of the subject's skin, such that the analyte moves from the subject through the skin surface into the collection reservoir.
 - 8. The method of claim 7 wherein the analyte is permitted to move passively through the skin surface.
- 9. The method of claim 7, further including the 15 step of applying electrical energy to the skin surface.
 - 10. The method of claim 7, further including the step of applying ultrasound energy to the skin surface.
- 11. The method of claim 7, further including the step of applying to the skin surface a sweat inducing 20 substance.
 - 12. The method of claim 7, further including the step of applying to the skin surface a skin permeation enhancer.
- 13. The method of claim 4, being a method for
 25 continual monitoring of glucose in the subject, wherein
 the steps of treating the analyte and of rendering the
 analyte undetectable comprise contacting the analyte with
 an enzyme that acts upon the glucose to substantially

- 13 -

irreversibly produce a detectable chemical species and an undetectable reaction product.

14. Apparatus for continual monitoring of a physiologic analyte in a subject, the apparatus including a collection reservoir for receiving the analyte from the subject, the contents of the collection reservoir being in operative contact with a detector that detects the analyte in the reservoir, and means for rendering the analyte, once detected, undetectable by the reservoir.

INTERNATIONAL SEARCH REPORT

International application No. PCT/US96/20591

A. CLA IPC(6)	ASSIFICATION OF SUBJECT MATTER :A61B 5/00			
US CL	:128/632, 636, 760, 771			
	to International Patent Classification (IPC) or to bo	th national classification and IPC		
	DS STARCHED			
	documentation searched (classification system follow	ved by classification symbols)		
U.S. :	128/632, 633, 636, 637, 760, 771			
Documenta	tion searched other than minimum documentation to t	he extent that such documents are included	in the fields searched	
Electronic o	data have consulted during the international recent	name of data have and sub-section of the	•	
<i>Licensine</i> (data base consulted during the international search (name of data base and, where practicable	, scarch terms used)	
C. DOC	CUMENTS CONSIDERED TO BE RELEVANT			
Category*	Citation of document, with indication, where	announciate of the relevant passages	Relevant to claim No.	
X	US 5,050,604 A (RESHEF et al) : document.	24 September 1991, entire	1-4, 7, 8, 14	
Y	US 5,458,140 A (EPPSTEIN et al) 17 October 1995, entire 1-4, 7-12, 14 document.			
	document.			
		ĺ		
İ				
				
	er documents are listed in the continuation of Box (
•	cial categories of cited documents: ument defining the general state of the art which is not considered	"T" later document published after the inter date and not in conflict with the applica	tion but cited to understand the	
to b	e of particular relevance	principle or theory underlying the inve "X" document of particular relevance; the		
	ier document published on or after the international filing date ument which may throw doubts on priority claim(s) or which is	considered novel or cannot be consider when the document is taken alone	ed to involve an inventive step	
cite	d to establish the publication date of another citation or other cial reason (as specified)	"Y" document of particular relevance; the	claimed invention cannot be	
O* docs	ument referring to an oral disclosure, use, exhibition or other	considered to involve an inventive combined with one or more other such being obvious to a person skilled in the	documents, such combination	
P* docs	ument published prior to the international filing date but later than priority date claimed	"&" document member of the same patent f		
	actual completion of the international search	Date of mailing of the international sear	ch report	
26 FEBRU	ARY 1997	18 MAR 1997		
	ailing address of the ISA/US er of Patents and Trademarks	Authorized officer	0 .	
Box PCT	D.C. 2023	RYAN CARTER Stalia	Sinuik	
acsimile No		Telephone No. (703) 308-2990	for	
orm PCT/IS	A/210 (second sheet)(July 1992)*		/	