(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau

(43) International Publication Date
10 May 2013 (10.05.2013)

WIPO | PCT

(10) International Publication Number
WO 2013/064817 A1

(51) International Patent Classification:
A61F 2/34 (2006.01)

(21) International Application Number:
PCT/GB2012/052701

(22) International Filing Date:
31 October 2012 (31.10.2012)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
1119017.0 3 November 2011 (03.11.2011) GB

(71) Applicant: **BIOMET UK HEALTHCARE LIMITED** [GB/GB]; Waterton Industrial Estate, Bridgend South Wales CF31 3XA (GB).

(72) Inventors: **BIGSBY, Robert John Andrew**; 15 Plassey Street, Penarth, Glamorgan South Wales CF64 1EJ (GB). **KHAN (Dr), Mohammed Imran**; 11 Liverpool Road, Reading Berkshire RG1 3PP (GB).

(74) Agent: **GILES, Ashley Simon**; HASELTINE LAKE LLP, 5th Floor, Lincoln House, 300 High Holborn, London Greater London WC1V 7JH (GB).

(81) Designated States *(unless otherwise indicated, for every kind of national protection available)*: AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States *(unless otherwise indicated, for every kind of regional protection available)*: ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— *with international search report (Art. 21(3))*

— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))*

(54) Title: PROSTHESIS COMPONENT




FIG. 2

(57) Abstract: A prosthesis component 2 is disclosed, the component comprising a shell (2) formed form a carbon fibre reinforced polymer material and having an inner bearing surface (10); and a liner (6) formed from a ceramic material and having an outer bearing surface(12); wherein the liner (6) is received in an articulating manner within the shell (4). A hip replacement prosthesis is also disclosed, the hip replacement prosthesis comprising a prosthesis component (2) as disclosed and a femoral head prosthesis component (24), the femoral head prosthesis component being formed from a ceramic material.

WO 2013/064817 A1

PROSTHESIS COMPONENT

The present invention relates to a prosthesis component, and particularly to a prosthesis component having a shell and articulating liner.

Background

It is known to replace some or all of a natural bone joint that has become damaged or diseased with prosthetic components. For example, a natural hip joint that has become degraded may be replaced with an artificial joint comprising a prosthetic acetabular component which is implanted into the patient's acetabulum, and a prosthetic femoral head component which is implanted into the patient's femur and articulates with the acetabular component. A prosthetic joint of this type is known as a total hp replacement (THR).

Various types of THR exist and are well known in the art. The different types of prosthesis take different approaches to balancing the competing requirements of reducing wear in the joint, maintaining stability of the joint, increasing patient range of motion, and many other factors. Reducing wear on the prosthesis components can be achieved by reducing as far as possible the surface area over which the components articulate. This leads to the use of smaller diameter femoral head components, which have favourable wear characteristics but suffer from a limited range of motion. In contrast, in order to promote joint stability it is desirable to use a large diameter femoral head component, which has the additional benefit of a better range of patient motion but results in an increase in the articulating surface area, and hence risk of wear damage. One type of prosthetic hip joint that seeks to combine advantages of reduced wear with increased stability and range of motion is the so called "double mobility" total hip prosthesis. In a double mobility THR, a prosthetic femoral head of relatively small diameter is received within a polyethylene "liner" within which the head articulates. This articulation is the primary mobility of the joint, and benefits from the reduced wear associated with a smaller articulating surface. The second mobility of the joint arises from the movement of the polyethylene liner within an exterior metallic shell. This second articulation benefits from increased stability, owing to the relatively large external diameter of the liner. The large diameter of the second articulation, in addition to being highly stable, also offers a greater range of motion than the smaller first articulation. The second articulation only comes into operation at the extremes of

motion of the joint, when the smaller primary articulation has reached its limit. The majority of motion within the joint thus takes place at the lower wearing primary articulation between the femoral head and the liner. By combining large and small diameter articulations in the same prosthesis, dual mobility prostheses offer some of the greatest ranges of motion available in THRs, as well as being some of the most stable of the prosthesis options available. In order to increase stability still further, it is known to use an additional circular clip, or circlip, to engage around the femoral neck and cooperate with the polyethylene liner and shell to maintain the femoral head within the liner. It is also known to provide the exterior metal shell with an additional superior lip, in order to support the polyethylene liner and prevent any possible creep deformation which may impede performance of the device.

While the double mobility type hip prosthesis has experienced good results, there remain some disadvantages to the system. The larger articulation of polyethylene liner against metal shell is excellent for stability, but it does not provide the best wear characteristics. Some prostheses have experimented with alternative metal alloys and material coatings for the shell to address the wear characteristics, but in the main this issue has been ignored in existing devices as the articulation is only engaged at extremes of motion and the wear performance of the articulation has not been considered a priority.

Fixation is another area where difficulties can arise with a double mobility prosthesis. The conventional means of fixation for the external metallic shell is to impact the shell into the prepared acetabulum, with the additional use of bone cement if required. This is acceptable in many cases but does not offer alternatives for patients with a high level of degradation of the acetabular bone tissue. In conventional single mobility hip prostheses, additional fixation may be provided by bone screws which pass through the outer shell and engage deeply into the patient's bone tissue to hold the shell in place. A static liner is then fitted into the shell, over the screw heads to provide the articulating surface for the femoral head. In the case of a double mobility prosthesis the liner must articulate against the shell, and so the inclusion of bone screws can only be achieved by increasing the degree of modularity within the device, adding an extra liner between the shell and the articulating liner. Such an additional stationary liner can be inserted to cover the screw heads and provide the articulating surface for the mobile liner. However, the inclusion of the extra liner reduces the space available for the femoral head, meaning the extra fixation comes at the expense of a reduced range of motion.

The present invention seeks to address some or all of the above mentioned issues.

Summary of Invention

According a first aspect of the present invention, there is provided a prosthesis component comprising: a shell formed form a fibre reinforced polymer material and having an inner bearing surface; and a liner having an outer bearing surface formed from a ceramic material; wherein the liner is received in an articulating manner within the shell.

The shell may further comprise one or more openings on the inner bearing surface.

The one or more openings may extend through the thickness of the shell to open on an outer surface of the shell.

The openings may be suitable to receive one or more attachment means operable to secure the prosthesis component in place.

The prosthesis component may further comprise one or more attachment means, which may be operable to extend through the openings to secure the prosthesis component in place.

The attachment means may be formed from a fibre reinforced polymer material and may be formed from the same fibre reinforced polymer material as the shell.

The shell may be formed from a carbon fibre reinforced polymer material and may be formed from carbon fibre reinforced polyether ether ketone (CFR-PEEK).

A hydroxyapatite (HA) coating may be formed on an outer surface of the shell. Alternatively, or in addition, a porous metal coating may be formed on an outer surface of the shell.

The prosthesis component may be an acetabular prosthesis component.

The liner may be formed from a ceramic material.

The liner may further comprise an inner bearing surface which may be operable to receive a femoral head prosthesis component.

The prosthesis component may further comprise a retaining element, which may be operable to cooperate with the liner and the shell to retain a femoral head prosthesis component in engagement with the inner bearing surface of the liner.

The retaining element may be formed from a fibre reinforced polymer material, and may be formed from the same fibre reinforced polymer material as the shell. The material may be a carbon fibre reinforced polymer material.

The retaining element may comprise a circular clip, or circlip.

According to another aspect of the present invention, there is provided a hip replacement prosthesis comprising a prosthesis component according to the first aspect of the present invention and a femoral head prosthesis component.

The femoral head prosthesis component may be formed from a ceramic material or may be formed from a coated metallic material.

According to another aspect of the present invention, there is provided a kit of parts for a hip replacement prosthesis comprising: an acetabular shell formed from a fibre reinforced polymer material and comprising an inner bearing surface; an acetabular liner having an outer bearing surface formed from a ceramic material and operable to articulate with the inner bearing surface of the shell and an inner bearing surface; and a femoral head prosthesis having a bearing surface formed from a ceramic material and operable to articulate with the inner bearing surface of the liner.

The acetabular liner may be formed from a ceramic material, the acetabular shell may be formed from a carbon fibre reinforced polymer material and the femoral head prosthesis may be formed from a ceramic material.

The kit may further comprise a plurality of attachment means formed from a fibre reinforced polymer material. The material may be a carbon fibre reinforced polymer material.

The kit may further comprise a circular clip, or circlip, which may be operable to cooperate with the liner and the shell to retain the femoral head prosthesis in engagement with the inner bearing surface of the liner. The circlip may be formed from a carbon fibre reinforced polymer material.

According to another aspect of the present invention, there is provided a prosthesis comprising a shell, a liner received in an articulating manner within the shell to form a first bearing couple, and a head received in an articulating manner within the liner to form a second bearing couple, wherein the bearing surfaces of the second bearing couple, and a bearing surface of the first bearing couple, are relatively harder than the other bearing surface of the first bearing couple.

For the purposes of the present specification, the phrase "bearing couple" refers to a pair of bearing surfaces that engage each other. According to certain embodiments of the invention, the first bearing couple may operate under boundary lubrication. The bearing surfaces of the second bearing couple and a bearing surface of the first bearing couple may be formed from a ceramic material. The other bearing surface of the first bearing couple may be formed form a fibre reinforced polymer material, which may be a carbon fibre reinforced polymer material such as carbon fibre reinforced polyether ether ketone (CFR-PEEK). The shell may comprise fixation openings extending there through.

Brief Description of the Drawings

For a better understanding of the present invention, and to show more clearly how it may be carried into effect, reference will now be made by way of example to the following drawings, in which:

Figure 1 is a perspective view of a liner, circlip and femoral head in an assembled and disassembled condition;

Figure 2 is a perspective view of an acetabular prosthesis component and femoral head prosthesis component;

Figure 3 is a sectional illustration of an acetabular shell; and

Figure 4 is a perspective view illustrating assembly of a hip prosthesis.

Detailed Description of Embodiments

The present invention relates to a double mobility acetabular prosthesis component and cooperating femoral head prosthesis component that together provide a hip prosthesis having ceramic on ceramic and ceramic on carbon fibre reinforced polymer articulations.

With reference to Figures 1 and 2, an acetabular prosthesis component 2 in accordance with an embodiment of the present invention comprises a shell 4 and a liner 6. The shell 4 is substantially hemispherical and is formed from a carbon fibre reinforced polymer material. According to the embodiment of the invention described below, the shell 4 is formed from carbon fibre reinforced polyether ether ketone (CFR-PEEK), however it will be appreciated that other fibre reinforced polymer materials may be considered. A carbon fibre reinforced polymer material such as CFR-PEEK provides a low wear bearing surface, as well as offering an alternative to metal bearing surfaces, concerns over which have been expressed in the literature owing to possible detrimental effects of metal ions released into the body from such surfaces.

The shell 4 is machined from bar or preferably injection moulded and comprises an outer surface 8, operable to engage with bone tissue when implanted into a patient, and an inner bearing surface 10. The inner bearing surface 10 is operable to receive the liner 6 in an articulating manner. The outer surface 8 may be provided with a hydroxyapatite (HA) coating 20 and/or a porous metal coating to stimulate bone in growth for additional fixation. The hydroxyapatite (HA) coating may be achieved by using thermal spraying (for example, using plasma spraying, arc spraying, flame spraying or using a high velocity oxyfuel), cold gas spraying or electrochemically assisted deposition. The porous coating may be achieved by using thermal spraying or cold gas spraying.

The liner 6 is also substantially hemispherical in shape and is formed from a ceramic material such as Alumina or Zirconia toughened Alumina. The liner comprises an outer bearing surface 12 that is operable to articulate with the inner bearing surface 10 of the shell. The liner also comprises an inner bearing surface 14, shaped to receive a femoral head prosthesis component, as described in further detail below. It will be appreciated that as the liner 6 is formed from a ceramic material, it is not necessary to form a lip on the shell 4 in order to support the liner 6 or to prevent creep deformation.

With additional reference to Figure 3, the shell 4 further comprises a plurality of openings 16 formed on the inner bearing surface 10 and extending through the thickness of the shell 4 to open onto the outer surface 8. The openings 16 may be clustered together or may be spaced across the bearing surface 10 as illustrated in the Figure. In one embodiment, the openings 16 comprise a series of substantially circular holes, sized to admit the passage of individual attachment means 18. One or more individual attachment means 18 is also provided as part of the prosthesis component. The attachment means pass through the openings 16 in the shell 4 and attach the shell 4 to a patient acetabulum, as described in further detail below. The attachment means may take the form of screws, pins, spikes, barbs or any other suitable attachment device. In the illustrated embodiment, the attachment means 18 take the form of screws but it will be appreciated that alternative attachment means may also be considered. The screws 18 are formed from a carbon fibre reinforced polymer material and in the present embodiment are formed from the same CFR-PEEK material as the shell 4, for example with a continuous fibre orientation. As the shell 4 and screws 18 are formed from the same CFR-PEEK material, the shell 4 presents a continuous inner bearing surface 10 and the presence of the screws 18 does not risk damaging the outer bearing surface 12 of the liner 6. In addition, CFR-PEEK operates under boundary lubrication, meaning the presence of the attachment means 18 does not affect the wear performance of the bearing. The articulation between the ceramic liner 6 and CFR-PEEK shell 4 is extremely low wear and hence desirable. In addition, the articulation contains no exposed metal, meaning that the production of metal ions is avoided.

Referring again to Figure 1, the prosthesis component 2 further comprises a circular clip, or circlip, 22 which is also formed from a carbon fibre reinforced polymer material, and in the present embodiment is formed from CFR-PEEK. The circlip 22 is of annular form and includes a split 23 to allow the component to be snapped into place over the

femoral neck and engaging a distal portion of the femoral head, as described in further detail below. The circlip 22 is dimensioned to be received against an annular surface 25 of the liner 6, within the confines of the shell 4, as illustrated for example on Figure 1. The circlip 22 and liner 6 may comprise cooperating formations to enable the circlip 22 to be locked in place against the liner 6 once the femoral head is in position articulating against the inner bearing surface 14 of the liner 6.

Referring again to Figure 1, a prosthesis according to an embodiment of the present invention comprises the acetabular prosthesis component 2 described above and a femoral head prosthesis component 24. The femoral head prosthesis component 24 is a modular component, designed to cooperate with a stem and femoral neck prosthesis components in a known manner. For example the femoral head prosthesis component may comprise a recess 27 that forms one part of a Morse taper fixation arrangement, the recess being shaped to be received on a trunnion part of a femoral neck prosthesis component. The head 24 has a highly polished outer bearing surface designed to be received in an articulating manner against the inner bearing surface 14 of the liner 6. The head is formed from a ceramic material and according to the present embodiment is formed from the same ceramic material as the liner, which may for example be Alumina or Zirconia toughened Alumina. The hip prosthesis of the present invention thus provides a ceramic on ceramic articulation at the primary articulation of the joint, ceramic on ceramic being the lowest wearing material combination available.

Implantation and operation of the prosthesis will now be described with reference to the Figures. It will be understood that the details of the operative technique used may vary, including the order in which the femoral and acetabular prosthesis components are prepared and implanted. The following explanation is merely exemplary in nature, focussing on the issues specific to the prosthesis of the present invention.

Considering first the acetabular component, once the bone surface has been fully prepared, the shell 4 is implanted into the acetabulum of a patient. The level of fixation required in order to securely implant the shell 4 will vary according to the condition of the patient bone tissue. In some patients, there may be sufficient healthy bone tissue remaining in the acetabulum for the shell 4 to be implanted using simply a friction fit, or with the assistance of bone cement. In such cases, the openings 16 on the shell 4 and cooperating attachment means 18 may not be used. In order to maintain the physical continuity of the bearing surface of the shell 4, the openings 16 may be plugged using

caps (not shown) formed from the same carbon fibre reinforced polymer material as the shell. Alternatively, the openings may be left uncovered in the implanted shell 4.

In patients experiencing significant degradation of acetabular bone tissue, there may not be sufficient healthy bone tissue available to enable a secure fixation using only friction and bone cement. In these cases, additional fixation is provided by the attachment screws 18, which are passed through the attachment openings 16 and into the surrounding bone tissue.

Once the shell is implanted into the patient acetabulum, the liner 6 may be inserted into the shell 4. As discussed above, the liner 6 and shell 4 articulate under boundary lubrication, which is not impacted by the presence of the CFR-PEEK screws.

The femoral prosthesis components, including stem, femoral neck and the femoral head 24 are prepared and assembled in a known manner, and a series of trial reductions may be carried out to ensure correct sizing and placement of components. Once the correct femoral head component 24 is correctly seated on the femoral neck and stem components, the head 24 is introduced into the liner 6, until the femoral head bearing surface articulates against the inner bearing surface 14 of the liner 6. The circlip 22 is then snapped around the femoral neck and into engagement with the liner 6 and shell 4 to hold the femoral head in place in engagement with the inner bearing surface 14 of the liner 6 (see Figure 4).

Once implanted, the principal articulation of the prosthesis is between the ceramic femoral head component 24 and the ceramic liner 6. At extremes of motion, the articulation between the ceramic liner 6 and the CFR-PEEK shell 4 is engaged. During articulation, the circlip 22 prevents micro separation or dislocation of the femoral head 24, as well as acting as a “bumper” to cushion the components.

The prosthesis of the present invention may be provided as a kit of parts, comprising shell 4, liner 6, circlip 22, attachment means 18 and femoral head 24 in a range of sizes, allowing a surgeon to select the most appropriate sizing combinations for a particular patient.

CLAIMS

1. A prosthesis component comprising: a shell formed form a fibre reinforced polymer material and having an inner bearing surface; and a liner having an outer bearing surface formed from a ceramic material; wherein the liner is received in an articulating manner within the shell.

2. A prosthesis component as claimed in claim 1, wherein the shell further comprises one or more openings on the inner bearing surface.

3. A prosthesis component as claimed in claim 2, wherein the one or more openings extend through the thickness of the shell to open on an outer surface of the shell.

4. A prosthesis component as claimed in claim 2 or 3, wherein the openings are suitable to receive one or more attachment means operable to secure the prosthesis component in place.

5. A prosthesis as claimed in any one of claims 2 to 4, further comprising one or more attachment means, operable to extend through the openings to secure the prosthesis component in place.

6. A prosthesis component as claimed in claim 5, wherein the attachment means are formed from a fibre reinforced polymer material.

7. A prosthesis component as claimed in any one of the preceding claims, wherein the shell is formed from a carbon fibre reinforced polymer material.

8. A prosthesis component as claimed in any one of the preceding claims, wherein the shell is formed from carbon fibre reinforced polyether ether ketone (CFR-PEEK).

9. A prosthesis component as claimed in any one of the preceding claims, wherein a hydroxyapatite (HA) coating is formed on an outer surface of the shell.

10. A prosthesis component as claimed in any one of the preceding claims, wherein a porous metal coating is formed on an outer surface of the shell.

11. A prosthesis component as claimed in any one of the preceding claims, wherein the prosthesis component is an acetabular prosthesis component.

12. A prosthesis component as claimed in any one of the preceding claims, wherein the liner is formed from a ceramic material.

13. A prosthesis component as claimed in any one of the preceding claims, wherein the liner further comprises an inner bearing surface operable to receive a femoral head prosthesis component.

14. A prosthesis component as claimed in claim 13, wherein the component further comprises a retaining element, operable to cooperate with the liner and the shell to retain a femoral head prosthesis component in engagement with the inner bearing surface of the liner.

15. A prosthesis component as claimed in claim 14, wherein the retaining element is formed from a carbon fibre reinforced polymer material.

16. A prosthesis component as claimed in claim 14 or 15, wherein the retaining element comprises a circlip.

17. A hip replacement prosthesis comprising a prosthesis component as claimed in any one of the preceding claims and a femoral head prosthesis component.

18. A hip replacement prosthesis as claimed in claim 17, wherein the femoral head prosthesis component is formed from a ceramic material.

19. A hip replacement prosthesis as claimed in claim 17, wherein the femoral head prosthesis component is formed from a coated metallic material.

20. A kit of parts for a hip replacement prosthesis comprising: an acetabular shell formed from a fibre reinforced polymer material and comprising an inner bearing surface; an acetabular liner and having an outer bearing surface formed from a ceramic material and operable to articulate with the inner bearing surface of the shell and an inner bearing surface; and a femoral head prosthesis having a bearing surface formed

from a ceramic material and operable to articulate with the inner bearing surface of the liner.

21. A kit of parts as claimed in claim 20, wherein the acetabular liner is formed from a ceramic material.

22. A kit of parts as claimed in claim 20 or 21, wherein the acetabular shell is formed from a carbon fibre reinforced polymer material.

23. A kit of parts as claimed in any one of claims 20 to 22, wherein the femoral head prosthesis is formed from a ceramic material.

24. A kit of parts as claimed in any one of claims 20 to 23, further comprising a plurality of attachment means formed from a fibre reinforced polymer material.

25. A prosthesis component substantially as described herein with reference to and as shown in the accompanying drawings.




FIG. 1




FIG. 2




FIG. 3




FIG. 4

INTERNATIONAL SEARCH REPORT

International application No
PCT/GB2012/052701

A. CLASSIFICATION OF SUBJECT MATTER
INV. A61F2/34
ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
A61F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)
EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 6 042 612 A (VOYDEVILLE GILLES [FR]) 28 March 2000 (2000-03-28) figure single column 3, line 1 - line 29 -----	1-25
Y	FR 2 795 302 A1 (RECH S ET DE FABRICATION S E R [FR]) 29 December 2000 (2000-12-29) figures 1,2 page 3, line 1 - line 17 -----	1-25
Y	EP 1 442 727 A2 (CERAMTEC AG [DE]; CERAMCONCEPT WORLDWIDE L L C [US]) 4 August 2004 (2004-08-04) figure 6 paragraphs [0018], [0022], [0025] ----- -/--	1-25

[X] Further documents are listed in the continuation of Box C.

[X] See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search	Date of mailing of the international search report
18 February 2013	27/02/2013

Name and mailing address of the ISA/	Authorized officer
European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Fax: (+31-70) 340-3016	Josten, Stefan

1

Form PCT/ISA/210 (second sheet) (April 2005)

INTERNATIONAL SEARCH REPORT

International application No
PCT/GB2012/052701

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	WO 2011/008752 A1 (BIOMET MFG CORP [US]; MERIDEW JASON D [US]) 20 January 2011 (2011-01-20) figures 1-3 paragraphs [0005], [0006], [0021]	1-25
Y	WO 96/22746 A1 (ZAHEDI AMIR [DE]) 1 August 1996 (1996-08-01) figures 1-3 page 6, line 1 - line 11 page 7, line 21 - line 31	2-5,24
Y	EP 0 461 019 A1 (BOUVET JEAN CLAUDE [FR]) 11 December 1991 (1991-12-11) column 4, line 1 - line 5	9
Y	US 2011/251698 A1 (GUPTA GAUTAM [US] ET AL) 13 October 2011 (2011-10-13) paragraph [0041]	10

1

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No
PCT/GB2012/052701

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 6042612 A	28-03-2000	CA 2245249 A1	07-08-1997
		DE 69725966 D1	11-12-2003
		EP 0879031 A1	25-11-1998
		FR 2744357 A1	08-08-1997
		JP 2000503871 A	04-04-2000
		US 6042612 A	28-03-2000
		WO 9727827 A1	07-08-1997
FR 2795302 A1	29-12-2000	NONE	
EP 1442727 A2	04-08-2004	DE 10304102 A1	12-08-2004
		EP 1442727 A2	04-08-2004
		JP 4242301 B2	25-03-2009
		JP 2004230175 A	19-08-2004
		US 2004225370 A1	11-11-2004
WO 2011008752 A1	20-01-2011	US 2011015752 A1	20-01-2011
		WO 2011008752 A1	20-01-2011
WO 9622746 A1	01-08-1996	DE 19502503 C1	26-09-1996
		WO 9622746 A1	01-08-1996
EP 0461019 A1	11-12-1991	DE 69114050 D1	30-11-1995
		DE 69114050 T2	27-06-1996
		EP 0461019 A1	11-12-1991
		ES 2080270 T3	01-02-1996
		FR 2662930 A1	13-12-1991
US 2011251698 A1	13-10-2011	US 2011251698 A1	13-10-2011
		WO 2011130169 A1	20-10-2011