



(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:  
**24.03.2021 Bulletin 2021/12**

(51) Int Cl.:  
**A24F 47/00 (2020.01)**

(21) Application number: **20204713.0**

(22) Date of filing: **15.07.2013**

(84) Designated Contracting States:  
**AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR**

(72) Inventor: **Lord, Christopher**  
**London, GB WC2R 3LA (GB)**

(74) Representative: **D Young & Co LLP**  
**120 Holborn**  
**London EC1N 2DY (GB)**

(30) Priority: **16.07.2012 GB 201212603**

(62) Document number(s) of the earlier application(s) in accordance with Art. 76 EPC:  
**16189742.6 / 3 167 729**  
**13741696.2 / 2 871 986**

Remarks:


This application was filed on 29-10-2020 as a divisional application to the application mentioned under INID code 62.

(71) Applicant: **Nicoventures Holdings Limited**  
**London WC2R 3LA (GB)**

(54) **ELECTRONIC VAPOUR PROVISION DEVICE**

(57) An electronic vapour provision device 1 comprising a power cell 9 and a vaporiser 7, where the vaporiser 7 comprises a heating element 21 and a heating

element support 20, wherein the heating element 21 is on the inside of the heating element support 20.



**FIG. 2**

**Description****Technical Field**

**[0001]** The specification relates to electronic vapour provision devices. 5

**Background**

**[0002]** Electronic vapour provision devices, such as electronic cigarettes, are typically cigarette-sized and typically function by allowing a user to inhale a nicotine vapour from a liquid store by applying a suction force to a mouthpiece. Some electronic vapour provision devices have an airflow sensor that activates when a user applies the suction force and causes a heater coil to heat up and vaporise the liquid. 10 15

**Summary**

**[0003]** In an embodiment there is provided an electronic vapour provision device comprising a power cell and a vaporiser, where the vaporiser comprises a heating element and a heating element support, wherein the heating element is on the inside of the heating element support. One or more gaps may be provided between the heating element and the heating element support. Moreover, the electronic vapour provision device may have a mouthpiece section and the vaporiser may be part of the mouthpiece section. The heating element support may substantially fill the mouthpiece section. 20 25 30

**[0004]** In another embodiment there is provided a vaporiser for use in the vapour provision device, that comprises a heating element and a heating element support, wherein the heating element is on the inside of the heating element support. 35

**[0005]** In another embodiment there is provided an electronic vapour provision device comprising a liquid store; a wicking element configured to wick liquid from the liquid store to a heating element for vaporising the liquid; an air outlet for vaporised liquid from the heating element; and a heating element support, wherein the heating element is on the inside of the heating element support. The heating element support may be the wicking element. Moreover, the electronic vapour provision device may include a power cell for powering the heating element. 40 45

**Brief Description of the Drawings**

**[0006]** For a better understanding of the disclosure, and to show how example embodiments may be carried into effect, reference will now be made to the accompanying drawings in which: 50

Figure 1 is a side perspective view of an electronic cigarette;

Figure 2 is a schematic sectional view of an electronic cigarette having a parallel coil;

Figure 3 is a side perspective view of a heating element coil;

Figure 4 is a side perspective view of an outer heating element support;

Figure 5 is a side perspective view of a heating element coil within an outer heating element support;

Figure 6 is a side sectional view of a heating element coil within an outer heating element support;

Figure 7 is an end view of a heating element coil within an outer heating element support, where a central channel has a square cross-section;

Figure 8 is an end view of a heating element coil within an outer heating element support, where a central channel has a circular cross-section; 20

Figure 9 is an end view of a heating element coil within an outer heating element support, where a central channel has an octagonal cross-section; 25

Figure 10 is an end view of a heating element coil within an outer heating element support having an outer square cross-section, where a central channel has a square cross-section; 30

Figure 11 is an end view of a heating element coil within an outer heating support having two sections; 35

Figure 12 is an end view of a heating element coil within a side channel of a heating element support;

Figure 13 is an end view of a heating element coil within a side channel of a heating element support, with a second support section; 40

Figure 14 is an end view of a heating element coil within a side channel of a heating element support having a rectangular cross-section; and 45

Figure 15 is an end view of a heating element coil within a side channel of a heating element support having a rectangular cross-section, with a second support section. 50

**Detailed Description**

**[0007]** In an embodiment there is provided an electronic vapour provision device comprising a power cell and a vaporiser, where the vaporiser comprises a heating element and a heating element support, wherein the heating element is on the inside of the heating element 55

support. The electronic vapour provision device may be an electronic cigarette.

**[0008]** Having a separate heating element and support allows a finer heating element to be constructed. This is advantageous because a finer heating element can be more efficiently heated. Having the heating element on the inside of the support means that a much smaller and narrower heating element can be used since space is not needed inside the heating element to house a support. This enables a much larger and therefore stronger support to be used.

**[0009]** The heating element may not be supported on its inside. Having a heating element that is not supported on its inside means that a support does not interfere with the heating element on its inner region. This provides a greater heating element surface area which thereby increases the vaporisation efficiency.

**[0010]** The heating element support may be a liquid store. A combined support and liquid store has the advantage that liquid can be easily transferred from the liquid store to the heating element supported by the liquid store. Also, by eliminating the need for a separate support, the device can be made smaller or a larger liquid store can be utilised for increased capacity.

**[0011]** One or more gaps may be provided between the heating element and the heating element support. Providing a gap between the heating element and the heating element support allows liquid to gather, and thereby be stored, in the gap region for vaporisation. The gap can also act to wick liquid onto the heating element. Also, providing a gap between the heating element and support means that a greater surface area of the heating element is exposed thereby giving a greater surface area for heating and vaporisation.

**[0012]** The heating element may be in contact with the heating element support at two or more locations. Moreover, the heating element may be in contact with the heating element support at points along the length of the support.

**[0013]** The heating element support may be a rigid and/or a solid support. Furthermore, the heating element support may be porous. For example, the heating element support may be formed of porous ceramic material.

**[0014]** The heating element support may be elongated in a lengthwise direction. Moreover, the heating element support may have a support channel and the heating element may be located in the support channel. Furthermore, the support channel may run in a lengthwise direction of the heating element support.

**[0015]** The support channel may be an internal support channel. Moreover, the support channel may be a central support channel. Alternatively, the support channel may be a side support channel, located on a side of the heating element support.

**[0016]** The support channel may be substantially cylindrical. Moreover, the cross-sectional shape of the support channel may be circular. Alternatively, the cross-sectional shape of the support channel may be a polygon.

Furthermore, the cross-sectional shape of the support channel may have 4 sides, 6 sides or 8 sides. Cross-sections are sections perpendicular to the elongated lengthwise direction. These various shapes of support channel provide natural gaps between the support and a heating element coil within the support channel. These gaps lead to increased wicking, liquid storage and vaporisation.

**[0017]** The heating element support may comprise a first support section and a second support section. Moreover, the heating element may be supported by the first support section and the second support section. For example, the heating element may be supported between the first support section and the second support section. Furthermore, the support channel may be provided between the first support section and the second support section and the heating element may be in the support channel. The first support section may provide a first side of the support channel and the second support section may provide a second side of the support channel.

**[0018]** Providing a support that comprises two separate sections provides an easier method of assembly. It also enables a more accurate and consistent positioning of the heating element relative to the support.

**[0019]** The heating element may run along the length of the support channel. Moreover, the heating element may be in contact with the support channel at points along the length of the support channel. The heating element may be in contact with the surface of the support channel along the length of the support channel.

**[0020]** The heating element may be a heating coil, such as a wire coil. The heating coil may be coiled so as to be supported along its length by the heating element support. The turns of the heating coil may be supported by the heating element support. The turns of the heating coil may be in contact with the heating element support. A gap may be provided between the heating coil and the heating element support. Moreover, the gap may be between a coil turn and heating element support. Furthermore, gaps may be between coil turns and the heating element support.

**[0021]** By providing a gap between a coil turn and the support, liquid can be wicked into the gap and held in the gap for vaporisation. In particular, liquid can be wicked by the spaces between coil turns and into the gap between a coil turn and the support.

**[0022]** The vaporiser may have a vaporisation cavity configured such that in use the vaporisation cavity is a negative pressure region. At least part of the heating element may be inside the vaporisation cavity, or the heating element may be entirely inside the vaporisation cavity. For example, the vaporisation cavity may be inside the heating element support. Moreover, the vaporisation cavity may be inside a channel of the heating element support. At least part of the vaporisation cavity may be inside the heating element.

**[0023]** By having the heating element in the vaporisation cavity, which in turn is a negative pressure region

when a user inhales through the electronic vapour provision device, the liquid is directly vaporised and inhaled by the user.

**[0024]** The electronic vapour provision device may further include a mouthpiece section and the vaporiser may be part of the mouthpiece section. Moreover, the heating element support may substantially fill the mouthpiece section.

**[0025]** The liquid store may not comprise an outer liquid store container.

**[0026]** Since the support is on the outside of the coil and can act as a liquid store, a liquid store container is not needed in addition to the liquid store, and the heating element support can fill the mouthpiece section to give greater storage capacity and a more efficient device.

**[0027]** The electronic vapour provision device may further include a heating element connecting wire and the heating element support may include a heating element connecting wire support section.

**[0028]** The heating element support may be substantially cylindrical. The outer cross-sectional shape of the heating element support may be a circle. Alternatively, the outer cross-sectional shape of the heating element support may be a polygon. The outer cross-sectional shape of the heating element support may have 4 sides.

**[0029]** Referring to Figure 1 there is shown an embodiment of the electronic vapour provision device 1 in the form of an electronic cigarette 1 comprising a mouthpiece 2 and a body 3. The electronic cigarette 1 is shaped like a conventional cigarette having a cylindrical shape. The mouthpiece 2 has an air outlet 4 and the electronic cigarette 1 is operated when a user places the mouthpiece 2 of the electronic cigarette 1 in their mouth and inhales, drawing air through the air outlet 4. Both the mouthpiece 2 and body 3 are cylindrical and are configured to connect to each other coaxially so as to form the conventional cigarette shape.

**[0030]** Figure 2 shows an example of the electronic cigarette 1 of Figure 1. The body 3 is referred to herein as a battery assembly 5, and the mouthpiece 2 includes a liquid store 6 and a vaporiser 7. The electronic cigarette 1 is shown in its assembled state, wherein the detachable parts 2, 5 are connected. Liquid wicks from the liquid store 6 to the vaporiser 7. The battery assembly 5 provides electrical power to the vaporiser 7 via mutual electrical contacts of the battery assembly 5 and the mouthpiece 2. The vaporiser 7 vaporises the wicked liquid and the vapour passes out of the air outlet 4. The liquid may for example comprise a nicotine solution.

**[0031]** The battery assembly 5 comprises a battery assembly casing 8, a power cell 9, electrical contacts 10 and a control circuit 11.

**[0032]** The battery assembly casing 8 comprises a hollow cylinder which is open at a first end 12. For example, the battery assembly casing 8 may be plastic. The electrical contacts 10 are located at the first end 12 of the casing 8, and the power cell 9 and control circuit 11 are located within the hollow of the casing 8. The power cell

9 may for example be a Lithium Cell.

**[0033]** The control circuit 11 includes an air pressure sensor 13 and a controller 14 and is powered by the power cell 9. The controller 14 is configured to interface with the air pressure sensor 13 and to control provision of electrical power from the power cell 9 to the vaporiser 7, via the electrical contacts 10.

**[0034]** The mouthpiece 2 further includes a mouthpiece casing 15 and electrical contacts 26. The mouthpiece casing 15 comprises a hollow cylinder which is open at a first end 16, with the air outlet 4 comprising a hole in the second end 17 of the casing 15. The mouthpiece casing 15 also comprises an air inlet 27, comprising a hole near the first end 16 of the casing 15. For example, the mouthpiece casing may be formed of aluminium.

**[0035]** The electrical contacts 26 are located at the first end of the casing 15. Moreover, the first end 16 of the mouthpiece casing 15 is releasably connected to the first end 12 of the battery assembly casing 8, such that the electrical contacts 26 of the mouthpiece 2 are electrically connected to the electrical contacts 10 of the battery assembly 5. For example, the device 1 may be configured such that the mouthpiece casing 15 connects to the battery assembly casing 8 by a threaded connection.

**[0036]** The liquid store 6 is situated within the hollow mouthpiece casing 15 towards the second end 17 of the casing 15. The liquid store 6 comprises a cylindrical tube of porous material saturated in liquid. The outer circumference of the liquid store 6 matches the inner circumference of the mouthpiece casing 15. The hollow of the liquid store 6 provides an air passageway 18. For example, the porous material of the liquid store 6 may comprise foam, wherein the foam is substantially saturated in the liquid intended for vaporisation.

**[0037]** The vaporiser 7 comprises a vaporisation cavity 19, a heating element support 20 and a heating element 21.

**[0038]** The vaporisation cavity 19 comprises a region within the hollow of the mouthpiece casing 15 in which liquid is vaporised. The heating element 21 and a portion 22 of the support 20 are situated within the vaporisation cavity 19.

**[0039]** The heating element support 20 is configured to support the heating element 21 and to facilitate vaporisation of liquid by the heating element 21. The heating element support 20 is an outer support and is illustrated in Figures 4 to 7. The support 20 comprises a hollow cylinder of rigid, porous material and is situated within the mouthpiece casing 15, towards the first end 16 of the casing 15, such that it abuts the liquid store 6. The outer circumference of the support 20 matches the inner circumference of the mouthpiece casing 15. The hollow of the support comprises a longitudinal, central channel 23 through the length of the support 20. The channel 23 has a square cross-sectional shape, the cross-section being perpendicular to the longitudinal axis of the support.

**[0040]** The support 20 acts as a wicking element, as it is configured to wick liquid in the direction W from the

liquid store 6 of the mouthpiece 2 to the heating element 21. For example, the porous material of the support 20 may be nickel foam, wherein the porosity of the foam is such that the described wicking occurs. Once liquid wicks W from the liquid store 6 to the support 20, it is stored in the porous material of the support 20. Thus, the support 20 is an extension of the liquid store 6.

**[0041]** The heating element 21 is formed of a single wire and comprises a heating element coil 24 and two leads 25, as is illustrated in Figures 3, 5, 6 and 7. For example, the heating element 21 may be formed of Ni-chrome. The coil 24 comprises a section of the wire where the wire is formed into a helix about an axis A. At either end of the coil 24, the wire departs from its helical form to provide the leads 25. The leads 25 are connected to the electrical contacts 26 and are thereby configured to route electrical power, provided by the power cell 9, to the coil 24.

**[0042]** The wire of the coil 24 is approximately 0.12 mm in diameter. The coil is approximately 25 mm in length, has an internal diameter of approximately 1 mm and a helix pitch of approximately 420 micrometers. The void between the successive turns of the coil 24 is therefore approximately 300 micrometers.

**[0043]** The coil 24 of the heating element 21 is located coaxially within the channel 23 of the support. The heating element coil 24 is thus coiled within the channel 23 of the heating element support 20. Moreover, the axis A of the coil 24 is thus parallel to the cylindrical axis B of the mouthpiece casing 15 and the longitudinal axis C of the electronic cigarette 1. Moreover, the device 1 is configured such that the axis A of the coil 24 is substantially parallel to airflow F through the device when a user sucks on the device. Use of the device 1 by a user is later described in more detail.

**[0044]** The coil 24 is the same length as the support 20, such that the ends of the coil 24 are flush with the ends of the support 20. The outer diameter of the helix of the coil 24 is similar to the cross-sectional width of the channel 23. As a result, the wire of the coil 24 is in contact with the surface 28 of the channel 23 and is thereby supported, facilitating maintenance of the shape of the coil 24. Each turn of the coil is in contact with the surface 28 of the channel 23 at a contact point 29 on each of the four walls 28 of the channel 23. The combination of the coil 24 and the support 20 provides a heating rod 30, as illustrated in Figures 5, 6 and 7. The heating rod 30 is later described in more detail with reference to Figures 5, 6 and 7.

**[0045]** The inner surface 28 of the support 20 provides a surface for liquid to wick onto the coil 24 at the points 29 of contact between the coil 24 and the channel 23 walls 28. The inner surface 28 of the support 20 also provides surface area for exposing wicked liquid to the heat of the heating element 21.

**[0046]** There exists a continuous inner cavity 31 within the electronic cigarette 1 formed by the adjacent hollow interiors' of the mouthpiece casing 15 and the battery

assembly casing 8.

**[0047]** In use, a user sucks on the second end 17 of the mouthpiece casing 15. This causes a drop in the air pressure throughout the inner cavity 31 of the electronic cigarette 1, particularly at the air outlet 4.

**[0048]** The pressure drop within the inner cavity 31 is detected by the pressure sensor 13. In response to detection of the pressure drop by the pressure sensor 13, the controller 14 triggers the provision of power from the power cell 9 to the heating element 21 via the electrical contacts 10, 26. The coil of the heating element 21 therefore heats up. Once the coil 17 heats up, liquid in the vaporisation cavity 19 is vaporised. In more detail, liquid on the coil 24 is vaporised, liquid on the inner surface 28 of the heating element support 20 is vaporised and liquid in the portions 22 of the support 20 which are in the immediate vicinity of the heating element 21 may be vaporised.

**[0049]** The pressure drop within the inner cavity 31 also causes air from outside of the electronic cigarette 1 to be drawn, along route F, through the inner cavity from the air inlet 27 to the air outlet 4. As air is drawn along route F, it passes through the vaporisation cavity 19, picking up vaporised liquid, and the air passageway 18. The vaporised liquid is therefore conveyed along the air passageway 18 and out of the air outlet 4 to be inhaled by the user.

**[0050]** As the air containing the vaporised liquid is conveyed to the air outlet 4, some of the vapour may condense, producing a fine suspension of liquid droplets in the airflow. Moreover, movement of air through the vaporiser 7 as the user sucks on the mouthpiece 2 can lift fine droplets of liquid off of the heating element 21 and/or the heating element support 20. The air passing out of the air outlet 4 may therefore comprise an aerosol of fine liquid droplets as well as vaporised liquid.

**[0051]** With reference to Figures 5, 6 and 7, due to the cross-sectional shape of the channel, gaps 35 are formed between the inner surface 28 of the heating element support 20 and the coil 24. In more detail, where the wire of the coil 24 passes between contact points 29, a gap 35 is provided between the wire and the area of the inner surface 28 closest to the wire due to the wire substantially maintaining its helical form. The distance between the wire and the surface 28 at each gap 35 is in the range of 10 micrometers to 500 micrometers. The gaps 35 are configured to facilitate the wicking of liquid onto the coil 24 through capillary action at the gaps 35. The gaps 35 also provide areas in which liquid can gather prior to vaporisation, and thereby provide areas for liquid to be stored prior to vaporisation. The gaps 35 also expose more of the coil 24 for increased vaporisation in these areas.

**[0052]** Many alternatives and variations are possible. For example, in embodiments, the electronic vapour provision device 1 may be configured such that the coil 24 is mounted perpendicular to a longitudinal axis C of the device. Moreover, Figures 8 to 15 show examples of dif-

ferent heating rod 30 configurations.

**[0053]** Figure 8 shows another example heating element support 20. This is similar to the example above with the exception that the internal channel 23 has a circular cross-section rather than a square one. The coil 24 fits inside the channel 23 such that the coil turns are in contact with the channel walls 28. There is greater contact between the coil 24 and the channel walls 28 than the example above, with the entire coil 24 generally in contact with the channel walls 28 rather than contact at given points 29.

**[0054]** This increase in contact area means that more liquid can be transferred to the full length of the coil rather than particular points 29. However, since the coil 24 is generally in constant contact with the heating element support 20, less of the coil surface area is exposed. So in use, when the coil 24 heats up, there will be less vaporisation surface.

**[0055]** These two examples show that a balance can be achieved between the amount of liquid on the coil 24 and the amount of vaporisation surface exposed. This balance is varied by changing the amount of contact between the coil 24 and the channel 23 of the heating element support 20.

**[0056]** Figure 9 shows an example where the amount of contact between the coil 24 and the channel 23 walls 28 lies between the examples shown in Figures 7 and 8. In this example, the channel 23 has an octagonal cross-section rather than a circle or a square. As such, the coil 24 has coil turns which are generally in contact with the channel 23 of the heating element support 20 at 8 points 29 of contact. More gaps 35 are provided by the configuration of Figure 9 than the configuration of Figures 3 to 7. Moreover, the provided gaps 35 are smaller, leading to greater capillary action at the gaps.

**[0057]** When compared to the channel 23 with the square cross-section, the increased contact, greater number of gaps 35 and smaller gap sizes all facilitate increased liquid transfer onto the coil 24. The increased exposed coil 24 surface compared to the channel 23 with the circular cross-section allows for more exposed vaporisation surface for increased vaporisation.

**[0058]** In this way it can be seen that providing a heating element support 20 with an internal channel 23 having a regular polygon cross-section can be used to modify the amount of liquid transfer and the degree of vaporisation by selecting the number of polygon sides. Thus, an optimum channel 23 cross-section can be selected.

**[0059]** In the examples above, the heating element support 20 has a cylindrical shape and therefore the outer surface cross-sectional shape is circular. This shape is advantageous because the mouthpiece 2 section is also cylindrical so the heating element support 20 can be efficiently fitted into the mouthpiece 2 to minimize wasted space.

**[0060]** Other outer surface cross-sectional shapes may for example be configured as shown in Figure 10 having a heating element support 20 with a square outer

cross-sectional shape.

**[0061]** Figure 11 shows a heating element support 20 comprising a first support section 36 and a second support section 37. The heating element support 20 is generally cylindrical in shape and the first support section 36 and second support section 37 are half cylinders, with generally semi-circular cross-sections, which are joined together to form the cylindrical shape of the heating element support 20.

**[0062]** The first support section 36 and second support section 37 each comprise a side channel 38, or groove 38, running along their respective lengths, along the middle of their otherwise flat longitudinal faces. When the first support section 36 is joined to the second support section 37 to form the heating element support 20, their respective side channels 38 together form the heating elements support 20 internal channel 23.

**[0063]** In this example, the combined side channels 28 form an internal channel 23 having a square cross-sectional shape. Thus, the side channels 28 are each rectangular in cross-section. As in the examples above, the coil 24 is situated within the heating element support 20 internal channel 23. Having a heating element support 20 that comprises two separate parts 36, 37 facilitates manufacture of this component. During manufacturing, the coil 24 can be fitted into the side channel 28 of the first support section 36, and the second support section 37 can be placed on top to form the completed heating element support 20.

**[0064]** Other arrangements can also be considered to aid the construction of the heating element support 20 and coil 24 combination. Figure 12 shows an example having a generally cylindrical heating element support 20 similar to that shown in Figure 7. However, the internal channel 23 is comprises a side channel 38 and the coil is thus not completely enclosed. The coil 24 can therefore be easily fitted into the open side channel 23, 38. Because the channel 23, 38 is open, the coil 24 has coil turns that are in contact with the channel walls 28 at three points 29 of contact rather than four.

**[0065]** Figure 13 shows an example similar to that shown in Figure 12 where the heating element support 20 of Figure 12 is a first support section 36 and a second support section 37 is arranged such that it runs along the open channel 23, 38, plugging the open channel 38 and thereby closing it, and providing a combined arrangement similar to that shown in Figure 7. Thus the coil 24 is enclosed inside an internal combined channel 23 and the coil turns are in contact with the channel 23 at four points 29 of contact, three points 29 of contact with the first support section 36 and one point 29 of contact with the second support section 36.

**[0066]** Figure 14 shows an example similar to that shown in Figure 12 with the exception that the heating element support 20 has an outer rectangular cross-sectional shape. The coil 24 has coil turns having three points 29 of contact with the heating element support 20 channel 23.

**[0067]** Figure 15 shows an example similar to that shown in Figure 13 where a first support section 36 has an open side channel 38 and the coil 24 is fitted in this side channel. A second support section 37 is placed next to the first support section so that the coil 24 is enclosed between the support sections providing an arrangement similar to that shown in Figure 10. The coil 24 has coil turns with four points 29 of contact with the heating element support 20 channel 23, 38, three with the first support section 36 and one with the second support section 37. Once the first support section 36 and the second support section 37 are joined to form the support 20, the formed support is substantially rectangular.

**[0068]** The wire of the coil 24 is described above as being approximately 0.12 mm thick. However, other wire diameters are possible. For example, the diameter of the coil 24 wire may be in the range of 0.05 mm to 0.2 mm. Moreover, the coil 24 length may be different to that described above. For example, the coil 24 length may be in the range of 20 mm to 40 mm.

**[0069]** The internal diameter of the coil 24 may be different to that described above. For example, the internal diameter of the coil 24 may be in the range of 0.5 mm to 2 mm.

**[0070]** The pitch of the helical coil 24 may be different to that described above. For example, the pitch may be between 120 micrometers and 600 micrometers.

**[0071]** Furthermore, although the distance of the voids between turns of the coil is described above as being approximately 300, different void distances are possible. For example, the void may be between 20 micrometers and 500 micrometers.

**[0072]** The size of the gaps 35 may be different to that described above.

**[0073]** In embodiments, the support 20 may be located partially or entirely within liquid store 6. For example, the support 20 may be located coaxially within the tube of the liquid store 6.

**[0074]** An air pressure sensor 13 is described herein. In embodiments, an airflow sensor may be used to detect that a user is sucking on the device 1.

**[0075]** The heating element 21 is not restricted to having a uniform coil 24. Moreover, in embodiments the coil 24 is described as being the same length as the support 20. However, the coil 24 may be shorter in length than the support 20 and may therefore reside entirely within the bounds of the support 20. Alternatively, the coil 24 may be longer than the support 20.

**[0076]** An electronic vapour provision device 1 comprising an electronic cigarette 1 is described herein. However, other types of electronic vapour provision device 1 are possible.

**[0077]** Liquid may not be wicked and/or stored by the support 20 and could instead be wicked from the liquid store 6 to the coil and/or the inner surface 28 of the support 20 by a separate wicking element. In this case, the support 20 may not be porous.

**[0078]** Internal support channels 23 with cross-section

tional shapes other than those described could be used.

**[0079]** The electronic vapour provision device 1 is not restricted to the sequence of components described and other sequences could be used such as the control circuit 11 being in the tip of the device 1 or the liquid store 6 being in the body 3 rather than the mouthpiece 2.

**[0080]** The electronic vapour provision device 1 of Figure 2 is described as comprising two detachable parts, the mouthpiece 2 and the body 3, comprising the battery assembly 5. Alternatively, the device 1 may be configured such these parts 2, 5 are combined into a single integrated unit. In other words, the mouthpiece 2 and the body 3 may not be detachable.

**[0081]** Reference herein to a vaporisation cavity 19 may be replaced by reference to a vaporisation region.

**[0082]** Although examples have been shown and described it will be appreciated by those skilled in the art that various changes and modifications might be made without departing from the scope of the invention.

**[0083]** In order to address various issues and advance the art, the entirety of this disclosure shows by way of illustration various embodiments in which the claimed invention(s) may be practiced and provide for superior electronic vapour provision. The advantages and features of the disclosure are of a representative sample of embodiments only, and are not exhaustive and/or exclusive. They are presented only to assist in understanding and teach the claimed features. It is to be understood that advantages, embodiments, examples, functions, features, structures, and/or other aspects of the disclosure are not to be considered limitations on the disclosure as defined by the claims or limitations on equivalents to the claims, and that other embodiments may be utilised and modifications may be made without departing from the scope and/or spirit of the disclosure. Various embodiments may suitably comprise, consist of, or consist essentially of, various combinations of the disclosed elements, components, features, parts, steps, means, etc. In addition, the disclosure includes other inventions not presently claimed, but which may be claimed in future. Any feature of any embodiment can be used independently of, or in combination with, any other feature.

**[0084]** Further embodiments of the invention are defined in the following numbered clauses:

1. An electronic vapour provision device comprising a power cell and a vaporiser, where the vaporiser comprises a heating element and a heating element support, wherein the heating element is on the inside of the heating element support.
2. The electronic vapour provision device of clause 1, wherein the electronic vapour provision device is an electronic cigarette.
3. The electronic vapour provision device of clauses 1 or 2, wherein the heating element is not supported on its inside.

4. The electronic vapour provision device of any preceding clause, wherein the heating element support is a liquid store.

5. The electronic vapour provision device of any preceding clause, wherein one or more gaps are provided between the heating element and the inner surface of the heating element support. 5

6. The electronic vapour provision device of any preceding clause, wherein the heating element is in contact with the heating element support at two or more locations. 10

7. The electronic vapour provision device of any preceding clause, wherein the heating element support is a rigid support. 15

8. The electronic vapour provision device of any preceding clause, wherein the heating element support is porous. 20

9. The electronic vapour provision device of clause 8, wherein the heating element support is porous ceramic material. 25

10. The electronic vapour provision device of any preceding clause, wherein the heating element support is elongated in a lengthwise direction. 30

11. The electronic vapour provision device of any preceding clause, wherein the heating element support comprises a support channel and the heating element is located in the support channel. 35

12. The electronic vapour provision device of clause 11 dependent on claim 10, wherein the support channel runs parallel to the lengthwise direction of the heating element support. 40

13. The electronic vapour provision device of clauses 11 or 12, wherein the support channel is a central support channel.

14. The electronic vapour provision device of clauses 11 or 12, wherein the support channel is a side support channel, located on a side of the heating element support. 45

15. The electronic vapour provision device of any one of clauses 11 to 14, wherein the support channel is substantially cylindrical. 50

16. The electronic vapour provision device of any one of clauses 11 to 15, wherein the cross-sectional shape of the support channel is circular. 55

17. The electronic vapour provision device of any

one of clauses 11 to 14, wherein the cross-sectional shape of the support channel is a polygon.

18. The electronic vapour provision device of clause 17, wherein the cross-sectional shape of the support channel has 4 sides, 6 sides or 8 sides.

19. The electronic vapour provision device of any preceding clause, wherein the heating element support comprises a first support section and a second support section.

20. The electronic vapour provision device of clause 19, wherein the heating element is supported by the first support section and the second support section.

21. The electronic vapour provision device of clauses 19 or 20, wherein the heating element is supported between the first support section and the second support section.

22. The electronic vapour provision device of any one of clauses 19 to 21, wherein a support channel according to any one of clauses 11 to 18 is provided between the first support section and the second support section and the heating element is in the support channel.

23. The electronic vapour provision device of clause 22, wherein the first support section provides a first side of the support channel and the second support section provides a second side of the support channel.

24. The electronic vapour provision device of clauses 22 or 23, wherein the heating element runs along the length of the support channel.

25. The electronic vapour provision device of any one of clauses 22 to 24, wherein the heating element is in contact with the support channel at points along the length of the support channel.

26. The electronic vapour provision device of any preceding clause, wherein the heating element is a heating coil.

27. The electronic vapour provision device of clause 26, wherein the heating coil is coiled so as to be supported along its length by the heating element support.

28. The electronic vapour provision device of clauses 26 or 27, wherein the turns of the heating coil are in contact with the heating element support.

29. The electronic vapour provision device of any one of clauses 26 to 28, wherein one or more gaps

are provided between the heating coil and the inner surface of the heating element support.

30. The electronic vapour provision device of any preceding clause, wherein the vaporiser further comprises a vaporisation cavity configured such that in use the vaporisation cavity is a negative pressure region.

31. The electronic vapour provision device of clause 30, wherein at least part of the heating element is inside the vaporisation cavity.

32. The electronic vapour provision device of clauses 30 or 31, wherein the vaporisation cavity is inside the heating element support.

33. The electronic vapour provision device of clause 32, wherein the vaporisation cavity is inside a support channel of the heating element support.

34. The electronic vapour provision device of any one of clauses 30 to 33, wherein at least part of the vaporisation cavity is inside the heating element.

35. The electronic vapour provision device of any preceding clause, wherein the electronic vapour provision device further comprises a mouthpiece section and the vaporiser is part of the mouthpiece section.

36. The electronic vapour provision device of clause 35, wherein the heating element support substantially fills the mouthpiece section.

37. The electronic vapour provision device of any preceding clause, wherein the electronic vapour provision device further comprises a heating element connecting wire and the heating element support comprises a heating element connecting wire support section.

38. The electronic vapour provision device of any preceding clause, wherein the heating element support is substantially cylindrical.

39. The electronic vapour provision device of any preceding clause, wherein the outer cross-sectional shape of the heating element support is a circle.

40. The electronic vapour provision device of any one of clauses 1 to 38, wherein the outer cross-sectional shape of the heating element support is a polygon.

41. The electronic vapour provision device of clause 40, wherein the polygon has 4 sides.

42. The vaporiser of any preceding clause.

43. An electronic vapour provision device comprising a liquid store;  
a wicking element configured to wick liquid from the liquid store to a heating element for vaporising the liquid;  
an air outlet for vaporised liquid from the heating element;  
and a heating element support, wherein the heating element is on the inside of the heating element support.

44. An electronic vapour provision device according to clause 43, wherein the heating element support is the wicking element.

45. An electronic vapour provision device comprising a liquid store;  
a wicking element configured to wick liquid from the liquid store to a heating element for vaporising the liquid;  
a power cell for powering the heating element;  
an air outlet for vaporised liquid from the heating element;  
and a heating element support, wherein the heating element is on the inside of the heating element support.

46. An electronic vapour provision device according to clause 45, wherein the heating element support is the wicking element.

47. An electronic vapour provision device, substantially as described herein with reference to the accompanying drawings.

48. A vaporiser, substantially as described herein with reference to the accompanying drawings.

## Claims

1. An electronic vapour provision device comprising a power cell and a vaporiser, where the vaporiser comprises a heating element and a heating element support, wherein the heating element is on the inside of the heating element support.
2. The electronic vapour provision device of claim 1, wherein the heating element support comprises a first support section and a second support section.
3. The electronic vapour provision device of claim 2, wherein the heating element is supported by the first support section and the second support section.
4. The electronic vapour provision device of claims 2

or 3, wherein the heating element is supported between the first support section and the second support section.

5. A vaporiser comprising a heating element and a heating element support, wherein the heating element is on the inside of the heating element support, wherein the heating element support comprises a first support section and a second support section, wherein the heating element is supported between the first support section and the second support section. 5  
10
6. The electronic vapour provision device or vaporiser of any preceding claim, wherein the heating element is in contact with the heating element support at two or more locations. 15
7. The electronic vapour provision device or vaporiser of any preceding claim, wherein the heating element support is porous. 20
8. The electronic vapour provision device or vaporiser of any preceding claim, wherein the heating element support is elongated in a lengthwise direction. 25
9. The electronic vapour provision device or vaporiser of any preceding claim, wherein the heating element support comprises a support channel and the heating element is located in the support channel. 30
10. The electronic vapour provision device or vaporiser of claim 9 dependent on claim 8, wherein the support channel runs parallel to the lengthwise direction of the heating element support. 35
11. The electronic vapour provision device or vaporiser of claim 9 or claim 10, wherein the cross-sectional shape of the support channel is circular. 40
12. The electronic vapour provision device or vaporiser of any preceding claim, wherein the heating element support is substantially cylindrical. 45
13. The electronic vapour provision device or vaporiser of any preceding claim, wherein the outer cross-sectional shape of the heating element support is a circle. 50
14. The electronic vapour provision device or vaporiser of any preceding claim, wherein the heater is the same length as the support. 55
15. The electronic vapour provision device or vaporiser of any preceding claim, wherein the vaporiser forms part of a mouthpiece.











FIG. 1



2  
G  
L








FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15



## EUROPEAN SEARCH REPORT

 Application Number  
 EP 20 20 4713

5

10

15

20

25

30

35

40

45

50

55

| DOCUMENTS CONSIDERED TO BE RELEVANT                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                                                                                                                                                          |                                                            |                                         |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------|-----------------------------------------|
| Category                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | Citation of document with indication, where appropriate, of relevant passages                                                                            | Relevant to claim                                          | CLASSIFICATION OF THE APPLICATION (IPC) |
| X,P                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | WO 2013/083634 A1 (PHILIP MORRIS PROD [CH]) 13 June 2013 (2013-06-13)<br>* page 11 - page 19; figures 1,5 *                                              | 1-10,15                                                    | INV.<br>A24F47/00                       |
| X                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | EP 2 404 515 A1 (HON LIK [CN] RUYAN INVEST HOLDINGS LTD [CN])<br>11 January 2012 (2012-01-11)<br>* paragraph [0025] - paragraph [0035];<br>figures 1-4 * | 1,11-14                                                    |                                         |
| A                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | EP 2 022 349 A1 (HAN LI [HK])<br>11 February 2009 (2009-02-11)<br>* the whole document *                                                                 | 1-15                                                       |                                         |
| A                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | DE 10 2006 004484 A1 (SCHMIDT KARSTEN [DE]) 9 August 2007 (2007-08-09)<br>* the whole document *                                                         | 1-15                                                       |                                         |
| A                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | DE 297 13 866 U1 (BAESLER PETER [DE])<br>2 October 1997 (1997-10-02)<br>* the whole document *                                                           | 1-15                                                       |                                         |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |                                                                                                                                                          |                                                            | TECHNICAL FIELDS SEARCHED (IPC)         |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |                                                                                                                                                          |                                                            | A24F                                    |
| The present search report has been drawn up for all claims                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                          |                                                            |                                         |
| Place of search<br><b>Munich</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                                                                                                                                          | Date of completion of the search<br><b>1 February 2021</b> | Examiner<br><b>Schwertfeger, C</b>      |
| CATEGORY OF CITED DOCUMENTS<br>X : particularly relevant if taken alone<br>Y : particularly relevant if combined with another document of the same category<br>A : technological background<br>O : non-written disclosure<br>P : intermediate document<br>T : theory or principle underlying the invention<br>E : earlier patent document, but published on, or after the filing date<br>D : document cited in the application<br>L : document cited for other reasons<br>& : member of the same patent family, corresponding document |                                                                                                                                                          |                                                            |                                         |

 1  
 EPO FORM 1503 03.82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 20 20 4713

5 This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.  
The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

01-02-2021

| Patent document<br>cited in search report | Publication<br>date | Patent family<br>member(s) | Publication<br>date |
|-------------------------------------------|---------------------|----------------------------|---------------------|
| WO 2013083634 A1                          | 13-06-2013          | AR 089588 A1               | 03-09-2014          |
|                                           |                     | AR 113360 A2               | 22-04-2020          |
|                                           |                     | AU 2012347290 A1           | 24-07-2014          |
|                                           |                     | AU 2016253576 A1           | 17-11-2016          |
|                                           |                     | BR 112014013755 A2         | 13-06-2017          |
|                                           |                     | CA 2857989 A1              | 13-06-2013          |
|                                           |                     | CN 104039184 A             | 10-09-2014          |
|                                           |                     | CN 106213585 A             | 14-12-2016          |
|                                           |                     | DK 2787847 T3              | 30-05-2016          |
|                                           |                     | DK 3072407 T3              | 22-05-2018          |
|                                           |                     | EP 2787847 A1              | 15-10-2014          |
|                                           |                     | EP 3072407 A1              | 28-09-2016          |
|                                           |                     | EP 3357357 A1              | 08-08-2018          |
|                                           |                     | EP 3763407 A1              | 13-01-2021          |
|                                           |                     | ES 2668948 T3              | 23-05-2018          |
|                                           |                     | HK 1197867 A1              | 27-02-2015          |
|                                           |                     | HK 1255350 A1              | 16-08-2019          |
|                                           |                     | HU E027566 T2              | 28-10-2016          |
|                                           |                     | HU E037923 T2              | 28-09-2018          |
|                                           |                     | IL 232792 A                | 28-02-2018          |
|                                           |                     | JP 6038948 B2              | 07-12-2016          |
|                                           |                     | JP 6619319 B2              | 11-12-2019          |
|                                           |                     | JP 2015500025 A            | 05-01-2015          |
|                                           |                     | JP 2017018146 A            | 26-01-2017          |
|                                           |                     | JP 2019170396 A            | 10-10-2019          |
|                                           |                     | KR 20140110855 A           | 17-09-2014          |
|                                           |                     | KR 20190103464 A           | 04-09-2019          |
|                                           |                     | LT 3072407 T               | 10-05-2018          |
|                                           |                     | MX 345610 B                | 07-02-2017          |
|                                           |                     | NO 3072407 T3              | 08-09-2018          |
|                                           |                     | NZ 625808 A                | 27-05-2016          |
|                                           |                     | PH 12014501189 A1          | 08-09-2014          |
|                                           |                     | PL 2787847 T3              | 31-10-2016          |
|                                           |                     | PL 3072407 T3              | 28-09-2018          |
|                                           |                     | PT 3072407 T               | 23-07-2018          |
|                                           |                     | RU 2014127719 A            | 10-02-2016          |
|                                           |                     | RU 2017111212 A            | 24-01-2019          |
|                                           |                     | SG 11201402916T A          | 27-02-2015          |
|                                           |                     | SI 3072407 T1              | 29-06-2018          |
|                                           |                     | TW 201325481 A             | 01-07-2013          |
|                                           |                     | UA 112883 C2               | 10-11-2016          |
|                                           |                     | US 2014346689 A1           | 27-11-2014          |
|                                           |                     | US 2016255880 A1           | 08-09-2016          |
|                                           |                     | WO 2013083634 A1           | 13-06-2013          |
|                                           |                     | ZA 201403918 B             | 30-09-2015          |
| -----                                     |                     |                            |                     |

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 20 20 4713

5 This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.  
The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

01-02-2021

| Patent document<br>cited in search report | Publication<br>date | Patent family<br>member(s) | Publication<br>date |
|-------------------------------------------|---------------------|----------------------------|---------------------|
| EP 2404515                                | A1                  | 11-01-2012                 |                     |
|                                           |                     | AU 2010213270 A1           | 06-10-2011          |
|                                           |                     | BR P11008569 A2            | 08-03-2016          |
|                                           |                     | CA 2752255 A1              | 19-08-2010          |
|                                           |                     | CA 2884987 A1              | 19-08-2010          |
|                                           |                     | CN 102387719 A             | 21-03-2012          |
|                                           |                     | CN 201379072 Y             | 13-01-2010          |
|                                           |                     | DK 2404515 T3              | 14-12-2015          |
|                                           |                     | EA 201171031 A1            | 30-01-2012          |
|                                           |                     | EA 201690438 A2            | 29-12-2017          |
|                                           |                     | EA 202091010 A2            | 30-11-2020          |
|                                           |                     | EG 26588 A                 | 17-03-2014          |
|                                           |                     | EP 2404515 A1              | 11-01-2012          |
|                                           |                     | EP 2772149 A2              | 03-09-2014          |
|                                           |                     | EP 3677131 A1              | 08-07-2020          |
|                                           |                     | ES 2551779 T3              | 23-11-2015          |
|                                           |                     | HU E028292 T2              | 28-12-2016          |
|                                           |                     | JP 5877066 B2              | 02-03-2016          |
|                                           |                     | JP 6146788 B2              | 14-06-2017          |
|                                           |                     | JP 2012517229 A            | 02-08-2012          |
|                                           |                     | JP 2016073316 A            | 12-05-2016          |
|                                           |                     | JP 2017153483 A            | 07-09-2017          |
|                                           |                     | JP 2020072730 A            | 14-05-2020          |
|                                           |                     | KR 20120012961 A           | 13-02-2012          |
|                                           |                     | KR 20160017667 A           | 16-02-2016          |
|                                           |                     | KR 20170070269 A           | 21-06-2017          |
|                                           |                     | KR 20180000347 A           | 02-01-2018          |
|                                           |                     | KR 20190132577 A           | 27-11-2019          |
|                                           |                     | MX 337342 B                | 26-02-2016          |
|                                           |                     | NZ 595117 A                | 20-12-2013          |
|                                           |                     | PL 2404515 T3              | 29-02-2016          |
|                                           |                     | PL 2772149 T3              | 10-08-2020          |
|                                           |                     | SG 174233 A1               | 28-10-2011          |
|                                           |                     | SG 2014008262 A            | 30-03-2015          |
|                                           |                     | US 2012111347 A1           | 10-05-2012          |
|                                           |                     | US 2012279512 A1           | 08-11-2012          |
|                                           |                     | US 2014305453 A1           | 16-10-2014          |
|                                           |                     | US 2016213067 A1           | 28-07-2016          |
|                                           |                     | US 2017172213 A1           | 22-06-2017          |
|                                           |                     | US 2018184719 A1           | 05-07-2018          |
|                                           |                     | US 2020146348 A1           | 14-05-2020          |
|                                           |                     | WO 2010091593 A1           | 19-08-2010          |
|                                           |                     | ZA 201106325 B             | 28-11-2012          |
|                                           |                     | ZA 201206458 B             | 29-05-2013          |
| -----                                     |                     |                            |                     |
| EP 2022349                                | A1                  | 11-02-2009                 |                     |
|                                           |                     | AU 2007250367 A1           | 22-11-2007          |
|                                           |                     | AU 2007250368 A1           | 22-11-2007          |

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 20 20 4713

5 This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.  
The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

01-02-2021

| Patent document<br>cited in search report | Publication<br>date | Patent family<br>member(s) | Publication<br>date |
|-------------------------------------------|---------------------|----------------------------|---------------------|
|                                           |                     | BR PI0711395 A2            | 01-11-2011          |
|                                           |                     | BR PI0711401 A2            | 01-11-2011          |
|                                           |                     | CA 2647212 A1              | 22-11-2007          |
|                                           |                     | CA 2647234 A1              | 22-11-2007          |
|                                           |                     | CA 2768122 A1              | 22-11-2007          |
|                                           |                     | CN 201067079 Y             | 04-06-2008          |
|                                           |                     | CN 201079011 Y             | 02-07-2008          |
|                                           |                     | DK 2022349 T3              | 08-09-2014          |
|                                           |                     | DK 2789250 T3              | 15-04-2019          |
|                                           |                     | DK 2878215 T3              | 15-08-2016          |
|                                           |                     | EA 200802045 A1            | 27-02-2009          |
|                                           |                     | EA 200802046 A1            | 27-02-2009          |
|                                           |                     | EP 2022349 A1              | 11-02-2009          |
|                                           |                     | EP 2022350 A1              | 11-02-2009          |
|                                           |                     | EP 2359705 A1              | 24-08-2011          |
|                                           |                     | EP 2789250 A2              | 15-10-2014          |
|                                           |                     | EP 2878215 A1              | 03-06-2015          |
|                                           |                     | EP 3061359 A1              | 31-08-2016          |
|                                           |                     | ES 2520018 T3              | 11-11-2014          |
|                                           |                     | ES 2584860 T3              | 29-09-2016          |
|                                           |                     | ES 2701325 T3              | 21-02-2019          |
|                                           |                     | ES 2717717 T3              | 24-06-2019          |
|                                           |                     | HK 1203127 A1              | 23-10-2015          |
|                                           |                     | HK 1210919 A1              | 13-05-2016          |
|                                           |                     | HU E029721 T2              | 28-03-2017          |
|                                           |                     | HU E043160 T2              | 29-07-2019          |
|                                           |                     | JP 5103561 B2              | 19-12-2012          |
|                                           |                     | JP 5385418 B2              | 08-01-2014          |
|                                           |                     | JP 5648111 B2              | 07-01-2015          |
|                                           |                     | JP 2009537119 A            | 29-10-2009          |
|                                           |                     | JP 2009537120 A            | 29-10-2009          |
|                                           |                     | JP 2012223190 A            | 15-11-2012          |
|                                           |                     | JP 2014039553 A            | 06-03-2014          |
|                                           |                     | KR 20090005139 A           | 12-01-2009          |
|                                           |                     | KR 20090018039 A           | 19-02-2009          |
|                                           |                     | KR 20110131320 A           | 06-12-2011          |
|                                           |                     | KR 20120002555 A           | 05-01-2012          |
|                                           |                     | MX 349386 B                | 24-07-2017          |
|                                           |                     | NZ 572309 A                | 29-04-2011          |
|                                           |                     | NZ 572310 A                | 29-10-2010          |
|                                           |                     | PL 2022349 T3              | 30-04-2015          |
|                                           |                     | PL 2789250 T3              | 30-09-2019          |
|                                           |                     | PL 2878215 T3              | 28-02-2017          |
|                                           |                     | PL 3061359 T3              | 28-06-2019          |
|                                           |                     | TR 201904176 T4            | 22-04-2019          |
|                                           |                     | US 2009095311 A1           | 16-04-2009          |

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 20 20 4713

5 This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.  
The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

01-02-2021

| Patent document<br>cited in search report | Publication<br>date | Patent family<br>member(s) | Publication<br>date |
|-------------------------------------------|---------------------|----------------------------|---------------------|
|                                           |                     | US 2009126745 A1           | 21-05-2009          |
|                                           |                     | US 2011209717 A1           | 01-09-2011          |
|                                           |                     | US 2013125906 A1           | 23-05-2013          |
|                                           |                     | US 2013139833 A1           | 06-06-2013          |
|                                           |                     | US 2013276798 A1           | 24-10-2013          |
|                                           |                     | US 2014209110 A1           | 31-07-2014          |
|                                           |                     | US 2015250230 A1           | 10-09-2015          |
|                                           |                     | US 2015250231 A1           | 10-09-2015          |
|                                           |                     | US 2015250232 A1           | 10-09-2015          |
|                                           |                     | US 2016262458 A1           | 15-09-2016          |
|                                           |                     | US 2016270448 A1           | 22-09-2016          |
|                                           |                     | US 2016270449 A1           | 22-09-2016          |
|                                           |                     | US 2017290373 A1           | 12-10-2017          |
|                                           |                     | US 2018184720 A1           | 05-07-2018          |
|                                           |                     | US 2018184721 A1           | 05-07-2018          |
|                                           |                     | US 2018279684 A1           | 04-10-2018          |
|                                           |                     | US 2019090551 A1           | 28-03-2019          |
|                                           |                     | US 2020236996 A1           | 30-07-2020          |
|                                           |                     | US 2020253277 A1           | 13-08-2020          |
|                                           |                     | WO 2007131449 A1           | 22-11-2007          |
|                                           |                     | WO 2007131450 A1           | 22-11-2007          |
|                                           |                     | ZA 200809062 B             | 25-11-2009          |
|                                           |                     | ZA 200809063 B             | 25-11-2009          |
| -----                                     |                     |                            |                     |
| DE 102006004484 A1                        | 09-08-2007          | NONE                       |                     |
| -----                                     |                     |                            |                     |
| DE 29713866 U1                            | 02-10-1997          | NONE                       |                     |
| -----                                     |                     |                            |                     |

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82