



(86) Date de dépôt PCT/PCT Filing Date: 2008/08/29
(87) Date publication PCT/PCT Publication Date: 2009/03/12
(45) Date de délivrance/Issue Date: 2012/10/30
(85) Entrée phase nationale/National Entry: 2009/09/01
(86) N° demande PCT/PCT Application No.: US 2008/074719
(87) N° publication PCT/PCT Publication No.: 2009/032786
(30) Priorité/Priority: 2007/09/05 (US11/850,476)


(51) Cl.Int./Int.Cl. *A45D 19/06* (2006.01),
A47G 19/12 (2006.01), *A47J 47/18* (2006.01)

(72) Inventeurs/Inventors:
MCGINLEY, MICHAEL L., US;
LAU, BRIAN, US

(73) Propriétaires/Owners:
MCGINLEY, MICHAEL L., US;
LAU, BRIAN, US

(74) Agent: MOFFAT & CO.

(54) Titre : CRUCHE A PANNEAU SOUPLE AVEC DIVISEUR INCURVE
(54) Title: FLEXIBLE PANEL PITCHER WITH CURVED DIVIDER



(57) Abrégé/Abstract:

A container or pitcher is provided having a flexible side wall portion and rim portion of the container which can conform to the shape of an object to which the pitcher is applied to thereby direct fluid flow from the pitcher over a broader area and to prevent fluid from flowing from the pitcher and underneath the rim of the pitcher and onto portions of the object to which it is not desirable to apply the fluid.



ABSTRACT

A container or pitcher is provided having a flexible side wall portion and rim portion of the container which can conform to the shape of an object to which the pitcher is applied to thereby direct fluid flow from the pitcher over a broader area and to prevent fluid from flowing from the pitcher and underneath the rim of the pitcher and onto portions of the object to which it is not desirable to apply the fluid.

FLEXIBLE PANEL PITCHER WITH CURVED DIVIDER

Field of the Invention

The present invention relates to containers, specifically containers used to hold fluids and, in particular, a container having a flexible side wall portion and rim portion which is capable of conforming to the shape of an object to which the pitcher is applied to more particularly direct the flow of fluid from the pitcher and to prevent the flow of fluid from the pitcher and onto areas to which application of the fluid is not intended.

Background of the Invention

When using pitchers to pour fluids, it is frequently desired to pour a stream of the fluid into a specific location, such as a glass or other container. Alternatively, it may be useful to use a container or a pitcher that does not provide an actual spout, but rather, simply has a rim when it is desired to pour a greater amount of fluid or broader stream of fluid onto an object such as when rinsing a floor or an automobile. However, both of these types of containers and pouring operations present specific drawbacks to particular applications. For example, when using a pitcher having a spout, the fluid that is poured from the pitcher can only be applied to a particular area, specifically, that area determined by the stream of fluid as it exits the spout. While this is useful for pouring water into a glass, another container or a specific area, it is not useful for applying the fluid to a larger area. Also, the use of a spout while narrowing the stream of water, nevertheless, provides a narrow column-like stream of water which, when it contacts the object or container toward which it is directed, will flow in all directions.

The other case of pouring a fluid from a container - that is the case of a bucket or other broad-rimmed container - also presents limitations with respect to the pouring of a fluid. In the case of a bucket or a pitcher having no spout, the water will flow from the pitcher over the rim or edge of the pitcher and create a broad stream of fluid flowing from the pitcher which will be related to the angle of the longitudinal axis of the pitcher as it moves from vertical to horizontal. To state the obvious, when the longitudinal axis of the pitcher (that is the axis passing through the bottom of the pitcher and the top of

5 the pitcher) is parallel to vertical, no fluid will flow from the pitcher. As the longitudinal axis is tilted increasingly toward a horizontal plane, more and more fluid will flow over the rim of the pitcher, and the stream flowing from the pitcher will be increasingly wide. While such a spoutless pitcher, such as a bucket, provides a wide stream of fluid which is useful in, for example, rinsing an area, there is still no control over the distribution of
10 that stream over the object on which it is poured. Specifically, if a stream of water is poured from a bucket, when the stream of water contacts the object on which it is poured, the water will flow in all directions and will not be limited to a single direction of flow. Even if the rim of the pitcher is pressed directly against the object onto which the fluid is to flow, the fluid will flow back toward the pitcher and underneath the pitcher and
15 onto portions of the object which are near the side wall of the pitcher.

In the specific case of rinsing shampoo and other hair treatments from the head of a child, this "backflow" from a pitcher can provide compelling support for the Victorian premise that children should be seen and not heard. Specifically, the backflow of rinse water from a pitcher that is used to dip bath water and to lift it to rinse the head of a
20 child can cause shampoo and other hair and scalp treatments to flow down the forehead of the child and into the eyes and face of the child. This will cause the child to notify the parent of the situation through loud screams, tears and arm movements. The prospect of rinsing soap suds into the eyes and mouth and nose of a child is not pleasant for either the parent or the child and can lead to difficulties as bath time
25 approaches. Usually it is the case that the best of attempts to try to limit this problem are unsuccessful. Asking the child to close his or her eyes tightly while the rinsing is proceeding will be only partially successful. The child, for one reason or another, may open their eyes during the rinsing procedure whereupon the soapy water contacts and stings their eyes. Alternatively, the child may improperly time the closing of their eyes
30 with the application of the rinse water and receive a stinging realization of their incapacity to coordinate their eyelid movements. Even should the parent attempt to assist the situation by placing a hand across the forehead of the child, some soapy water will inevitably trickle down the forehead of the child and into the child's eyes, mouth or nose.

35 Therefore, it would be a great benefit if a rinse container or pitcher could be provided which would prevent the flow of rinse water from a rinse pitcher or container and back underneath the rim of the container thereby providing specific, directional application of rinse water to an object such as a child's head.

Yet another benefit would be obtained from a pitcher or rinse container which could provide a broad flow of rinse water to an object to more efficiently rinse the object and while providing means for directing the flow of the rinse water from the pitcher and onto the object while preventing the backflow of rinse water onto areas of the object to which rinse water is not intended to be applied.

It would still be a further benefit if such a pitcher or rinsing container could conform to the shape of the object to which the rinse water in the pitcher was to be applied thereby restricting the portions of the object which will receive rinse water from those portions of the object which will not receive rinse water. These objects and benefits and more are provided by the present invention which is more completely described hereinafter.

Summary of the Invention

The present invention solves the preceding problems and improves the state of the art by providing a pitcher for holding solutions such as rinse water or shampoo or other liquids to allow application of those liquids to a localized portion of the body such as the head. The present invention provides a flexible panel and/or flexible rim portion of the container which conforms to the shape of the an object, such as the head of an individual, to allow application of the fluid to the body and to prevent misapplication of the fluid by preventing fluid from flowing underneath the rim and onto body parts to which it is not desired to apply the fluid.

In one embodiment, the invention provides a flexible panel which can conform to the shape of the child's head or other object to effectively seal off passage of fluids back under the flexible rim thereby allowing application of the fluid, such as rinse water, to the child's hair while preventing the flow of rinse water and a rinse water-shampoo mixture down into the child's face and eyes.

In another embodiment a divider panel is provided within the container to provide a second source of fluid flow onto the object to which the container is applied to provide a source of flow that is not partially deflected from the object by the deflection of the flexible panel as it conforms to the shape of the child's head or other object to which the flexible panel is applied.

In a broad aspect, the present invention provides a container comprising: a generally rigid continuous side wall terminating in an upper side wall end and a lower side wall end and defining an inward space bounded by said continuous sidewall, a bottom closing said lower side wall end with said upper side wall end being generally open, and an inwardly flexible panel forming a portion of said side wall and extending to form at least a portion of said upper side wall end, said flexible panel having a generally smooth inward surface for unobstructed fluid flow out of said open upper side wall end, and, a divider spanning said interior and contacting said bottom to define first and second fluid-holding portions of said interior, said divider being oriented generally parallel to said flexible panel, said first and second fluid-holding portions operating to approximately concurrently pour a fluid onto the object pressed against said flexing.

In another broad aspect, the present invention provides a container comprising: a generally rigid continuous side wall having an upper side wall end and a lower side wall end and defining an inward space bounded by said continuous sidewall, a bottom attached to said lower side wall end with said upper side wall end being generally open, a rim connected to said upper side wall end, a portion of said rim being sufficiently inwardly flexible to conform to the shape of an object to which said rim is pressed against, an inwardly flexible panel forming a portion of said side wall and connection with said inwardly flexible rim portion, said inwardly flexible panel having a generally smooth inward surface for unobstructed fluid flow out of said open upper side wall end, and a divider spanning said interior and contacting said bottom to define first and second fluid-holding portions of said interior, said divider being oriented generally parallel to said flexible panel, said first and second fluid-holding portions operating to approximately concurrently pour a fluid onto the object pressed against said flexing panel.

These other objects are intended to be illustrative of the invention and are not meant in a limiting sense. Many possible embodiments of the invention may be made and will be evident upon a study of the following specification and accompanying drawings. Various features and subcombinations of invention may be employed

5 without reference to other features and subcombinations. Other objects and advantages of this invention will become apparent from the following description and drawings, wherein is set forth by way of illustration and example, an embodiment of this invention.

10 Description of the Drawings

Preferred embodiments of the invention, illustrative of the best modes in which the applicant has contemplated applying the principles, are set forth in the following description and are shown in the drawings and are particularly and distinctly pointed out and set forth in the appended claims.

15 Fig. 1 is a top and side perspective view of the pitcher of the present invention showing the flexible panel which comprises a portion of the side wall of the container and the top edge of the side wall of the container;

Fig. 2 is a top and interior perspective view of the embodiment of Fig. 1 and showing the flexible wall opposite the handle;

20 Fig. 3 shows the application of an embodiment of the invention to the head of a child to allow water to flow over the child's hair and back of the head while the flexible panel and flexible rim conform to the shape of the child's head and prevents water from flowing down the front of the child's head and into the child's eyes and face;

Fig. 4 shows the embodiment of Fig. 4 having a flexible panel and flexible rim and showing the panel and rim in a depressed position and showing the panel and rim in phantom lines in a relaxed or undepressed position,

Fig. 5 shows an embodiment of the invention having a divider placed within the container to provide a second source of fluid flow; and

30 Fig. 6 shows the embodiment of Fig. 5 applied to the head of a child to allow water to flow over the child's hair and back of the head and having a divider panel within the container to provide a second source of fluid flow that is not affected by the deflection of the flexible panel.

Fig. 7 shows an alternate embodiment having a curved divider panel 50 which separates container 10 into first and second fluid holding compartments;

35 Fig. 8 shows an alternate embodiment of the embodiment of Fig. 7 showing fluid directing ridges 52 provided on the inside surface of flexible panel 28; and

Fig. 9 is a top front and right side perspective view of the embodiments of Figs. 7 and 8 showing the flexing of flexible panel 28 inwardly along the direction indicated by

- 5 Arrow **A** and toward curved divider panel **50** which is curved toward flexible panel **28** and in the direction indicated by Arrow **B**.

Description of the Preferred Embodiment

As required, detailed embodiments of the present inventions are disclosed
10 herein; however, it is to be understood that the disclosed embodiments are merely exemplary of the invention, which may be embodied in various forms. Therefore, is specific structural and functional details disclosed herein are not to be interpreted as limiting, but merely as a basis for the claims and as a representative basis for teaching one skilled in the art to variously employ the present invention in virtually any
15 appropriately detailed structure.

Referring now to Fig. 1, an embodiment of the inventive container **10** is shown which is comprised of generally continuous side wall **12** which can be of any convenient shape, spanning shapes from square to circular to polygonal. Continuous side wall **12** terminates at either end in upper side wall end **14**, and lower side wall end. Continuous
20 side wall **12** can be formed of rubber or plastic or metal or wood or any material which will serve to hold a fluid within continuous side wall **12**. Connected to a lower side wall end **16** is bottom or bottom panel **18** (Fig. 2) which serves to close lower side wall end **16** thereby allowing a fluid to be held within continuous side wall **12** and to bottom **18**. It will be appreciated that, depending on the material used for the construction of side
25 wall **12**, bottom **18** could be constructed with the forming of side wall **12** thus forming a unitary construction of side wall **12** and bottom **18**. As shown in Fig. 1, upper side wall end **14**, depending on the material used for the construction of side wall **12**, can form in and of itself a side wall rim **20**, or an additional structure **20** (Fig. 3) can be attached to upper side wall end **14** to form a discreet side wall rim **20** (Fig. 3). Generally, side wall
30 rim **20** will take the shape of upper side wall end **14**, however, alternatively, decorative materials could be used to modify the shaping of side wall rim **20**. For further convenience, and depending on the size of container **10**, a handle **22** can be attached to side wall **12** to assist in the manipulation of container **10**.

Side wall rim **20**, in a preferred embodiment is comprised of side wall portion **24**,
35 which is a generally flat portion of side wall rim **20**, and which may, therefore, differ, generally, in its shape as compared to the remainder of side wall rim **12** and side wall **20**. For example, if side wall **12**, in its construction, comprises a cylindrical container, then side wall rim **20** will be comprised of a generally circular side wall rim portion **26** and a generally flat side wall rim portion or side wall segment or rim segment **24**. The

5 utility and benefits of generally flat rim segment **24** will be described hereinafter. In a preferred embodiment, and in the vicinity of generally flat side wall rim portion **24**, is flexible panel **28** which extends from side wall **12** toward generally flat side wall rim segment **24** to connect side wall **12** with rim segment **24**. It will be appreciated by those skilled in the art that flexible panel **28** and rim segment **24** can be comprised of
10 the to same materials or of different materials depending on the choice of construction. For example, flexible panel **28** may be thin flexible plastic, or a flexible rubber panel, or a waterproof canvas which is attached to side wall **12** and which extends upwardly toward upper side wall end **14** to connect with or form side wall rim segment **24**. In such a construction, rim segment **24** could be of a different material which connects
15 with flexible panel **28** or, for example, if a waterproof canvas were used, the canvas could be wrapped over a flexible cord or wire which would form rim segment **24**. Therefore, it will be appreciated by those skilled in the art that one of the objects of a preferred embodiment of the present invention is to provide a flexible, shapeable wall segment **30** of either side wall **12** or rim **20**, or both rim **20** and side wall **12** which can
20 conform to the shape of an object against which this flexible portion of container **10** is pressed.

Referring now to Fig. 4, the flexibility and construction of the novel flexible side wall portion and rim portion of container **10** will be further described. As is shown in Fig. 4, flexible panel **28** and rim segment **24** are deformable and can be pressed
25 inwardly from the position shown in phantom lines and toward the interior of container **10**. The benefits of this flexibility or malleability of flexible panel **28** and rim segment **24** are that the pouring portion of side wall rim **20**, which is generally rim segment **24**, can be formed, by compression of container **10** against the object on which fluid is to be poured, to the shape of the object which is to receive the fluid which is within container
30 **10**. Referring to both Figs. 3 and 4, it is shown that flexible panel **28** and side wall rim **24** are capable of deformation inwardly. This feature of container **10** allows container **10** to be placed against an object, in this case, the forehead of a child (Fig. 3) to have flexible panel **28** and side wall rim **24** registerably mate with the head of the child to provide a wide pouring spout and wide volume of fluid therefor which can be evacuated
35 from container **10** and poured onto the head of the child to rinse the hair of the child.

It will further be appreciated that it is the flexible character of panel **28** and side wall rim **24** which allow for the registerable mating of the flexible portion of container **10**. Flexible wall portion **30** (Fig. 1 and 4), made up of flexible panel **28** and side wall rim segment **24**, conforms to the shape of the object or, in this case, the head of a child

5 onto which fluid is to be poured from container **10**, and thus, reducing or preventing the
flow of fluid from container **10** and back under side wall rim **24** and panel **28**. This
benefit is particularly useful with respect to rinsing shampoo or other hair products from
the hair of a child. The prevention of rinse fluid from draining underneath the side wall
rim of a container to allow the rinse fluids and shampoo to run down the forehead of a
10 child and into the eyes, nose and mouth prevent the unpleasantness of eyes stinging
from the shampoo or other product being rinsed from the child's hair. The construction
of flexible wall portion **30** can be continuous between panel **28** and rim segment **24**
(Figs. 1 and 2), or flex panel **28** and rim **24** can be separate constructions which join
together Figs. 3 and 4 to provide a flexible rim segment and side wall portion of
15 container **10**. For example, flex panel **28** could be formed from a flexible plastic, or a
rubber panel or a waterproof cloth panel which connects with a rim segment **24** which is
constructed of a flexible wire covered with sponge or covered with rubber or covered
with a waterproof fabric. Alternatively, rim segment **24** could be a piece of rubber or
piece of sponge which is placed across a rigid portion of side wall **12** which comprises
20 any portion of side wall rim **20**. In this construction, only the malleable or flexible rim
segment **24** would conform to the shape of the object against which container **10** is
pressed. In this embodiment only rim segment **24** is flexible and no flex panel is
provided to connect between side wall **12** and rim segment **24**. In such an
embodiment, side wall **12** continues to join rim segment **24**, and the flexible, malleable
25 aspect is contained solely within side wall rim segment **24**.

As has been described, the benefits of the present invention are achieved by a
container having a flexible side wall segment and/or a flexible rim segment which allow
close contact of the container with an object or the head of a child to prevent the wash
back or flow of fluid from the container underneath the rim and side wall of the
30 container, and which, thereby when rinsing the head of a child, prevents soapy water
from getting into the eyes and face of the child. Further, the present invention, as
previously described, allows the flexible portion of the container to mold to a shape
against which it is pressed and to allow large volumes of fluid to be passed from the
container onto the object by virtue of the generally flat rim segment which may contain
35 a rubber cushion to ease contact with the head. It will further be appreciated that in an
alternative embodiment of this invention, the side wall could be provided with a
concave portion which would generally conform to the curvature of a child's head and
the side wall would be provided with a malleable rim segment on the concave side wall
portion. The malleable rim segment portion would more closely register with the child's

WO 2009/032786

PCT/US2008/074719

5 head than with the concave side wall segment thereby directing the flow of water over the child's head and preventing the flow of water back underneath the side wall of the container.

Referring now to Fig. 5, an alternative embodiment of the present invention is shown wherein a divider panel **40** is formed or inserted within container **10** to divide the interior space defined by continuous **12** into a first compartment **42** and a second compartment **44**. As has previously been described, an important aspect of the present invention is the provision of a flexible panel **28**, or, alternatively, a malleable rim segment **24** which can conform to the shape of the objects against which container **10** is pressed. It will be appreciated that as flexible panel **28** is depressed inwardly to conform to the shape of the object against which container **10** is pressed that there can be a tendency for the water contained in container **10** to be diverted to one side or the other (i.e., the lower outside edges of flexible panel **28**) as the middle portion of flex panel **28** is depressed inwardly, and therefore, becomes a high point which can shed water towards the outside edges as shown in Fig. 3. The alternative embodiment shown in Figs. 5 and 6 provides a means for providing a secondary water supply which is captured within the second compartment **44**. As container **10** is pressed against an object and tipped upwardly as is shown in Fig. 6, water contained in second compartment **44** will flow along divider panel **40** and will flow outwardly evenly across the width of divider panel **40** and onto the object against which container **10** is depressed. At the same time, water contained within first compartment **42** will, depending upon the degree of inward depression formed in flex panel **28** by the pressure flex panel **28** against an object, will tend to divert a greater portion of the fluid contained in first compartment **42** toward the outer, lower edges of flex panel **28** and away from the higher portion of flex panel **28** presented by the compression of flex panel **28** against an object. In this manner, the alternate embodiment of the present invention containing divider panel **40** provides increase flow of fluid across the area of the object that is causing the greater deflection of flex panel **28** by providing two separate sources of fluid. The first source of fluid being contained in first compartment **42** which flows outwardly across flex panel **28** and is susceptible to a degree of diversion depending upon the degree of flexing of flex panel **28** and a second component of fluid contained in second compartment **44** which will flow independently of the amount of depression or flexion of flex panel **28** as it flows outwardly from second compartment **44** across the surface of divider panel **40** to flow onto the object against which container **10** is compressed.

5 It will be appreciated by those skilled in the art that divider panel **40** may be either fixed in place within container **10**, or panel **40** may be insertable and removable within container **10** through the use of a frictional fit of divider panel **40** within container **10**, or by the use of support tracks formed into side wall **12** and/or bottom **18** of container **10**.

10 Referring now to Fig. 7, an alternate embodiment of the present invention is shown in which container **10** is provided with a generally curved divider panel **50** which separates container **10** into two fluid holding compartments. A first fluid holding compartment **44** and a second fluid holding compartment **42** are separated by curved divider panel **50**. It will be appreciated that first compartment **44** and second
15 compartment **42** typically will both hold the same fluid although different fluids might be placed into each. As shown in the embodiment of Fig. 7, curved divider panel **50** is provided with a curvature in which the panel **50** is curved toward flexible panel **28**. This curvature of panel **50** provides a fluid directing feature to the shape of curved divider panel **50**. The curvature of panel **50** generally directs the flow of water held within
20 second compartment **44** into the center of curved divider panel **50** as it flows out of container **10** and onto the head of a child or other person against whom flexible panel **28** has been pressed. It will be appreciated that the curvature of panel **50** thereby directs the fluid contained in second compartment **44** generally onto the center of the head of the child and avoids even distribution of the water across the width of curved
25 divider panel **50** as the water is being poured out of second compartment **44**. The benefit of the curvature of divider panel **50** is that the majority of the rinse fluid contained within compartment **44** is placed onto the center of the child's head and is not wasted by pouring down either side of the child's head nor does it contribute to an increased probability of shampoo suds being washed into the eyes of the child. As
30 previously described for other embodiments, flexible panel **28** of the embodiment shown in Fig. 7 becomes inwardly flexed toward curved divider panel **50** when container **10** is pressed against the forehead of a child while rinsing shampoo from the child's head. It also will be appreciated that during the course of flexing, flexible panel **28**, as it is pressed against the head of a child, a certain amount of fluid will be directed
35 to the lower portions of flexible panel **28** which are designated in Fig. 7 as **S1** and **S2**. By providing curvature to curved panel **50**, to increase the water flow towards the center of the child's head, curve divider panel **50** helps compensate for any increase in water flow from first compartment **42** which is directed to the areas **S1**, **S2** due to the

upward or inward flexing of flexible panel **28** as it is pressed against the forehead of a child.

Referring now to Fig. 8, an embodiment is shown in which fluid directing ridges **52** are included on the inside surface of flexible panel **28**. Ridges **52** are included to assist in reducing the amount of water which flows out the side areas **S1**, **S2** of flexible panel **28** as it flexed against the head of a child. It will be appreciated that ridges **52** are, in a preferred embodiment, molded of the same material which flexible panel **28** is constructed. Alternatively, ridges **52** could be separately constructed and affixed to flexible panel **28**, however, it is desirable that ridges **52** do not obstruct the flexibility of panel **28** as it should be readily shapeable or moldable against the contours of the forehead of a child. It will be appreciated by those skilled in the art that fluid directing ridges **52** will assist in reducing the amount of fluid which is directed along a path at either side of flexible panel **28** as indicated by arrows **S1** and **S2** of Fig. 8. In this manner, ridges **52**, in conjunction with the curvature of panel **50**, will generally increase the amount of water flow from compartments **42**, **44** which is directed towards the center of the head of a child.

Referring now to Fig. 9, the exterior of the embodiments of Figs. 7 and 8 is shown with flexible panel **28** being presented slightly inwardly flexed along the direction indicated by Arrow **A**, and with Arrow **B**. Fig. 9 shows the general direction of the depression or curvature provided in curved divider panel **50**. The embodiment of Fig. 9 shows flexible panel **28** as being directly connected or molded onto container sidewall **12** with the upper edge **52** of flexible panel **28** providing the flexible rim segment **24** of the sidewall rim **20** of sidewall **12**.

In the foregoing description, certain terms have been used for brevity, clearness and understanding; but no unnecessary limitations are to be implied therefrom beyond the requirements of the prior art, because such terms are used for descriptive purposes and are intended to be broadly construed.

CLAIMS

What is claimed is:

1. A container comprising:

a generally rigid continuous side wall terminating in an upper side wall end and a lower side wall end and defining an inward space bounded by said continuous sidewall,

a bottom closing said lower side wall end with said upper side wall end being generally open, and

an inwardly flexible panel forming a portion of said side wall and extending to form at least a portion of said upper side wall end, said flexible panel having a generally smooth inward surface for unobstructed fluid flow out of said open upper side wall end, and,

a divider spanning said interior and contacting said bottom to define first and second fluid-holding portions of said interior, said divider being oriented generally parallel to said flexible panel, said first and second fluid-holding portions operating to approximately concurrently pour a fluid onto the object pressed against said flexing.

2. The container as claimed in claim 1 further comprising a rim attached to said upper side wall end.

3. The container as claimed in claim 2 wherein said rim is comprised of a sponge material.

4. The container as claimed in claim 2 wherein said rim is comprised of rubber.

5. The container as claimed in claim 2 wherein said rim is comprised of cloth.

6. The container as claimed in claim 1 further comprising a handle.

7. A container comprising:

a generally rigid continuous side wall having an upper side wall end and a lower side wall end and defining an inward space bounded by said continuous sidewall,

a bottom attached to said lower side wall end with said upper side wall end being generally open,

a rim connected to said upper side wall end,

a portion of said rim being sufficiently inwardly flexible to conform to the shape of an object to which said rim is pressed against,

an inwardly flexible panel forming a portion of said side wall and connection with said inwardly flexible rim portion, said inwardly flexible panel having a generally smooth inward surface for unobstructed fluid flow out of said open upper side wall end, and

a divider spanning said interior and contacting said bottom to define first and second fluid-holding portions of said interior, said divider being oriented generally parallel to said flexible panel, said first and second fluid-holding portions operating to approximately concurrently pour a fluid onto the object pressed against said flexing panel.

8. The container as claimed in claim 7 at least a portion of said side wall is concave, said concave side wall portion having a rim portion of flexible material.



9. The container as claimed in claim 8 wherein said rim is comprised of a sponge material.

10. The container as claimed in claim 8 wherein said rim is comprises of rubber.

11. The container as claimed in claim 8 wherein the rim is comprised of cloth.

12. The container as claimed in claim 7 further comprising a handle.

1/5

*Fig. 1.**Fig. 2.*




Fig. 3.






Fig. 4.



+

+

*Fig. 6**Fig. 5*


4/5

+



+

+

*Fig. 9*

+

