

(12) STANDARD PATENT
(19) AUSTRALIAN PATENT OFFICE

(11) Application No. **AU 2006296410 B2**

(54) Title
Vertebral fixing system

(51) International Patent Classification(s)
A61B 17/70 (2006.01)

(21) Application No: **2006296410** (22) Date of Filing: **2006.09.18**

(87) WIPO No: **WO07/036657**

(30) Priority Data

(31) Number	(32) Date	(33) Country
0650609	2006.02.22	FR
0509570	2005.09.20	FR

(43) Publication Date: **2007.04.05**

(44) Accepted Journal Date: **2012.03.08**

(71) Applicant(s)
Zimmer Spine

(72) Inventor(s)
Belliard, Karl P.;Mazda, Keyvan;Baccelli, Christian

(74) Agent / Attorney
Spruson & Ferguson, Level 35 St Martins Tower 31 Market Street, Sydney, NSW, 2000

(56) Related Art
WO 2004/010881
JP 2001299770
US 6514255

(12) DEMANDE INTERNATIONALE PUBLIÉE EN VERTU DU TRAITÉ DE COOPÉRATION
EN MATIÈRE DE BREVETS (PCT)

(19) Organisation Mondiale de la Propriété
Intellectuelle
Bureau international



(43) Date de la publication internationale
5 avril 2007 (05.04.2007)

PCT

(10) Numéro de publication internationale
WO 2007/036657 A1

(51) Classification internationale des brevets :
A61B 17/70 (2006.01)

(21) Numéro de la demande internationale :
PCT/FR2006/050898

(22) Date de dépôt international :
18 septembre 2006 (18.09.2006)

(25) Langue de dépôt : français

(26) Langue de publication : français

(30) Données relatives à la priorité :
0509570 20 septembre 2005 (20.09.2005) FR
0650609 22 février 2006 (22.02.2006) FR

(71) Déposant (pour tous les États désignés sauf US) : **ABBOTT SPINE** [FR/FR]; Cité Mondiale, 23 Parvis des Chartrons, F-33000 Bordeaux (FR).

(72) Inventeurs; et

(75) Inventeurs/Déposants (pour US seulement) : **BACCELLI, Christian** [FR/FR]; Lieu-dit "La Couye", F-33650 Saucats (FR). **BELLIARD, Karl, P.** [FR/FR]; 29 Route du Plessis Macé, F-49770 La Membrolle sur Longuenée (FR). **MAZDA, Keyvan** [FR/FR]; 17 Rue Houdart, F-75020 Paris (FR).


(74) Mandataires : **DRONNE, Guy** etc.; Cabinet Beau de Lomenie, 158 Rue de l'Université, F-75340 Paris Cedex 07 (FR).

(81) États désignés (sauf indication contraire, pour tout titre de protection nationale disponible) : AE, AG, AL, AM, AT,

[Suite sur la page suivante]

(54) Title: VERTEBRAL FIXING SYSTEM

(54) Titre : SYSTEME DE FIXATION VERTEBRALE



(57) Abstract: The invention relates to a vertebral fixing system mountable on a spinal vertebra for connecting said vertebra to a rod (18) comprising a connection part (20, 22) connectable to said rod, an elongated flexible link (14) connecting said connection part to at least one part of the vertebra posterior arc and/or to a transverse process and/or to a rib, wherein said link comprises two free ends (50, 52), and adjustable locking means (26) mounted on said connection part, which defines at least one through path (46) for said link in such a way that two distinct segments (42, 44) thereof are engageable into said through path in such a way that said two segments of the link define the first link part forming a loop (48) and extending from the first side of the connection part and the link second and third parts extending from the other side thereof.

(57) Abrégé : L'invention concerne un système de fixation vertébrale susceptible d'être monté sur une vertèbre du rachis pour la relier à une tige (18) comprenant : - une pièce de liaison (20, 22), susceptible d'être reliée à ladite tige, - un lien flexible (14) de forme allongée susceptible de relier ensemble ladite pièce de liaison et au moins une partie de l'arc postérieur d'une vertèbre et/ou une apophyse transverse et/ou une cote, ledit lien présentant deux extrémités libres (50, 52) ; et - des moyens de blocage réglables (26) montés sur ladite pièce de liaison, - ladite pièce de liaison définissant au moins un chemin de passage (46) pour ledit lien de telle manière que deux portions distinctes (42, 44) dudit lien puissent être engagées dans ledit chemin de passage de telle manière que lesdites deux portions de lien

définissent une première partie de lien formant une boucle (48) s'étendant d'un premier côté de ladite pièce de liaison et des deuxième et troisième parties de lien s'étendant de

[Suite sur la page suivante]

WO 2007/036657 A1



AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LV, LY, MA, MD, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Publiée :

- avec rapport de recherche internationale
- avant l'expiration du délai prévu pour la modification des revendications, sera republiée si des modifications sont reçues

(84) États désignés (sauf indication contraire, pour tout titre de protection régionale disponible) : ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), eurasien (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), européen (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,

En ce qui concerne les codes à deux lettres et autres abréviations, se référer aux "Notes explicatives relatives aux codes et abréviations" figurant au début de chaque numéro ordinaire de la Gazette du PCT.

A VERTEBRAL FIXING SYSTEM

The present invention relates to vertebral fixing system suitable for being mounted on a vertebra.

5 An intended field of application is particularly, but not exclusively, the treatment of scoliosis, or more generally correcting abnormal curvatures of the spine.

The spine is constituted by superposed vertebrae that are normally in alignment along a vertical axis, going from the lumbar vertebrae to the cervical
10 vertebrae, each vertebra presenting a posterior wall from which there projects a spinous process and two sides having walls from which there project the ribs and/or transverse processes. When the spine of an individual presents abnormal curvature, the vertebrae are inclined
15 relative to one another and relative to said vertebral axis. The sides of the vertebrae situated on one side are thus moved closer together forming a concave side, whereas the sides of the vertebrae on the other side are spaced apart from one another and form a convex side.

20 In order to straighten the spinal column, the sides of the vertebrae on the concave side are spaced apart from one another and moved relative to one another to distances that are substantially equivalent to those between the sides of the vertebrae on the other side. In
25 order to keep the vertebrae in that relative positioning, known devices have screws that are inserted in the vertebrae or hooks that are inserted along the inside wall of the vertebral canal, and rods that are for interconnecting the screws or the hooks.

30 The hooks are generally inserted in pairs into each vertebra and on either side close to the pedicles, with their heads projecting from the posterior wall of the vertebra, one on either side of the spinous process. By way of example, the heads form a socket suitable for
35 receiving a rod that is held in place by means of a nut screwed onto the head so as to press against the rod. The rows constituted by the heads of the hooks situated

on either side of the spinous processes are interconnected and held in a fixed position by two rods that are parallel to each other and to the axis of the spine.

5 Nevertheless, it is difficult to use such hooks since the operator must under no circumstances interfere with the spinal cord that extends along the center of the vertebral canal, since otherwise there is a danger of paralyzing the patient.

10 The use of screws makes it possible to diminish the risks of the operation. The screws likewise have socket-forming heads and they are inserted in pairs into the posterior walls of the vertebrae in the pedicles on either side of the spinous process. Thus, the screws
15 constitute points for fixing the vertebrae so as to hold them relative to one another. Nevertheless, they are necessarily introduced into the pedicles of the vertebrae, and under certain circumstances such pedicles can be small in size or damaged.

20 The problem that arises and that the present invention seeks to solve is how to establish fixing points when it is not possible to introduce screws into the vertebrae in the curved portion of the spine and when the use of hooks is too dangerous. PCT patent
25 application WO 2004/010881 in the name of the Applicant describes a vertebral fixing system that enables the problem to be solved.

 That vertebral fixing system adapted to be mounted on a vertebra of the spine to connect it to a rod
30 comprises:

- a connecting part placed facing said rib and/or said transverse process and suitable for being connected to said rod;
- an elongate flexible ligature suitable for
35 connecting together said connecting part and at least one rib and/or one transverse process; and

adjustable locking means fastened to said connecting part, said ligature having a first end secured to said connecting part and a free second end suitable for sliding in said connecting part to form a loop, said locking means being suitable for holding in a fixed position both said connecting part relative to said rod, and a length of said ligature
5 between said ends that is suitable for being prevented from moving in translation relative to said connecting part by said adjustable locking means, whereby the loop presents a length that is determined so as to prevent relative displacement of said rod and said vertebra in opposite directions.

That system is satisfactory, but under certain circumstances it can present the
10 following drawback. When the surgeon exerts traction on the free end of the flexible ligature, the ligature can be jammed by friction against the bottom face of the process. Under such circumstances, it will be understood that although the length of the ligature between the bottom face of the process and the zone where traction is applied to the ligature is indeed under tension, the length that extends between the end of the ligature
15 that is secured to the elongate passageway and the bottom face of the process is not under tension. Thus, overall, the ligature does not perform its function of fastening to the vertebra in appropriate manner.

Object of the Invention

20 It is the object of the present invention to substantially overcome or ameliorate one or more of the disadvantages of the prior art.

Summary of the Invention

The present invention provides a vertebral fixing system suitable for being
25 mounted on a vertebra of the spine in order to connect it to a rod, the system comprising:

a connecting part presenting first and second sides and suitable for being connected to said rod;

a flexible ligature of elongate shape suitable for connecting together said connecting part and at least one rib and/or a transverse process and/or a portion of the
30 posterior arc of a vertebra; and

adjustable locking means mounted on said connecting part;

wherein

said ligature presents two free ends;

said connecting part defines at least one passageway for passing said ligature in
35 such a manner that two distinct strands of said ligature can be engaged in said

passageway(s) so that said two ligature strands define a first ligature portion forming a loop that extends from a first side of said connecting part, and second and third ligature portions extending from the other side of said connecting part between respective ones of said ligature strands and said free ends; and

5 said locking means are distinct from the connecting part and co-operate therewith by screw-fastening, said locking means being capable of taking a first position relative to the connecting part in which the two ligature strands are free in said strand-passing passageway(s), a second position relative to the connecting part in which the two ligature strands are prevented from moving in translation relative to the connecting part,
10 and intermediate positions in which a coefficient of friction is created between said ligature strands and said connecting part.

 It will be understood that because the two ligature strands that are on either side of the transverse process are both placed in one or more passageways, when the locking means are brought into their locking position, both ligature strands can be used to exert
15 the tension needed for fixing to the vertebra by means of a rib and/or a portion of the posterior arc of a vertebra and/or a transverse process.

In addition, since the locking means co-operate with the connecting part by screw-fastening, the "dimensions" of the passageways can be defined accurately during the various stages of clamping and then locking the ligature.

5 Preferably, the connecting part defines a single passageway and both ligature strands are engaged in the single passageway.

Also preferably, the single passageway is defined firstly by the outside surface of the portion of the rod that is engaged in the connecting part and secondly by a wall of the connecting part, and the locking means are suitable for modifying the section of the passageway.

When the locking means are in their second position, this ensures effective clamping of the two ligature strands, thereby preventing them from moving.

15 In a first embodiment, the connecting part comprises two longitudinal elements having first ends that are hinged together, each of said longitudinal elements presenting a recess suitable for receiving a portion of a section of said rod, a wall of said recess co-operating with the side surface of said rod to define said passageway for passing said ligature strands, said locking means being mounted at the two second ends of said longitudinal elements.

25 In a second embodiment, the connecting part comprises a part that is generally U-shaped, suitable for receiving said rod, and having the outer ends of the limbs of the U-shape threaded, and the adjustable locking means comprise a tapped ring suitable for co-operating with the thread on the U-shaped part, tightening the ring causing the limbs of the part to be clamped against the rod.

35 Preferably, said passageway(s) is/are constituted by the space between the inside wall of the recess formed in said connecting part and the side wall of said rod.

Other characteristics and advantages of the invention appear better on reading the following

description of embodiments of the invention given by way of non-limiting example. The description refers to the accompanying figures, in which:

- 5 · Figure 1 is a perspective view of a first embodiment of a vertebral fixing system;
- Figures 2A, 2B, and 2C are vertical section views of the fixing system showing the use of said system as shown in Figure 1;
- 10 · Figure 3 is a face view showing the Figure 1 fixing system put into place on a vertebra;
- Figure 4 is a perspective view of a second embodiment of the fixing system, the ligature not being shown;
- 15 · Figure 5 is an exploded view of the connection device of Figure 4;
- Figure 6 is a plan view of a portion of the Figure 1 connection device;
- Figure 6A is a section view on line AA of Figure 6;
- 20 · Figure 7 is a face view of the fixing system of the second embodiment; and
- Figures 7A and 7B are section views on line VII-VII of Figure 7 showing two ways in which the flexible ligature can be put into place.
- 25 As shown in Figure 1, in the first embodiment, the vertebral fixing system comprises a connecting part 12, a flexible ligature 14, and adjustable locking means 16. The flexible ligature 14 is of elongate shape and is capable of matching the outline of the parts it is to
- 30 connect together. In this figure, there can also be seen the rod 18 that is to be secured to the vertebra by means of the vertebral fixing system. In the first embodiment, the connecting part 12 is constituted by two longitudinal elements given respective references 20 and 22, each
- 35 having a first end 22a, 20a and a second end 22b, 20b.

As can be seen better in Figure 2A, the longitudinal elements 20 and 22 are hinged to each other at their second ends 20b, 22b about a pivot pin 24.

In the embodiment described, the locking means are
5 constituted by a screw 26 having a head 26a that is engaged in a bore 28 formed in the first end 22a of the longitudinal element 22. The first end 20a of the longitudinal element 20 is pierced by a tapped bore 28 for co-operating with the threaded shank 26b of the screw
10 26. Each longitudinal element 20, 22 has an outside face 20c, 22c and an inside face 20d, 22d. The longitudinal elements 20 and 22 are mounted in such a manner that the inside faces 20d, 22d of the longitudinal elements face each other. The inside faces 20d, 22d of the
15 longitudinal elements 20 and 22 have respective mutually-facing recesses 30 and 32, each of substantially semicylindrical shape. The recesses 30 and 32 define walls 34 and 36 which are ruled surfaces having generator lines parallel to the pivot axis 24. Finally, slots 38
20 and 40 cause the bottoms of the recesses 30 and 32 to communicate with the outside faces 20c and 22c of the longitudinal elements 20 and 22. As explained in greater detail below, the recesses 30 and 32 are for receiving the rod 18 together with a strand of the ligature 14, the
25 slots 38 and 40 serving to pass the ligature 14.

With reference to Figures 2A to 2C, there follows an explanation of how the fixing system is used.

In Figure 2A, there can be seen the longitudinal elements 20 and 22 in the spaced-apart position, a
30 position in which the locking means 16 are naturally not active, the threaded shank 26b of the screw 26 not being engaged in the bore 28. The ligature 14 is engaged in the slots 38 and 40 of the longitudinal elements against one portion of the inside wall 34, 36 of the recesses 30
35 and 32. The rod 18 is then introduced into the recess 30 of the longitudinal element 20 so that the two strands 42 and 44 of the ligature 14 are disposed between the inside

wall of the recesses 30 and 32 and the side face 18a of the rod 18. These two surfaces define a passageway 46 for passing the ligature 14 and having the strands 42 and 44 of the ligature 14 placed therein.

5 As shown better in Figure 2B, the strands 42 and 44 of the ligature define a portion of the ligature 14 that forms a loop 48 that extends beyond the outside face 20c of the longitudinal element 20, and also two free portions 50 and 52 that extend beyond the outside face
10 22c of the longitudinal element 22. When the longitudinal elements 20 and 22 are spaced apart as shown in Figure 2B, the ligature 14 can slide freely along the passageway 46. Once the portion 48 of the ligature 14 forming the loop is placed around the transverse process
15 or a rib or indeed a portion of the posterior arc of a vertebra, the surgeon engages the threaded shank 26b of the screw 26 in the tapped bore 28, causing the longitudinal element 22 to come progressively closer to the longitudinal element 20. This approach
20 simultaneously reduces the section of the passageway 46 in which the strands 42 and 44 of the ligature are engaged and simultaneously introduces a certain coefficient of friction between the ligature and
25 respectively the rod 18 and the walls of the recesses 30 and 32. Nevertheless, it is still possible for the surgeon to extract traction on the free ends 50 and 52 of the ligature 14 until sufficient tension is obtained in the ligature around the vertebral process. Once the tension in the ligature is sufficient for providing
30 appropriate fastening, the surgeon finishes off tightening the screw 26 in the tapped bore 28, thus locking the longitudinal elements 20 and 22 together. Simultaneously, it will readily be understood that the strands 42 and 44 of the ligature are pinched between the
35 rod 18 and the wall of the recesses 30 and 32.

 In this locking position, the rod 18 is thus secured to the ligature 14 via the connecting part 12.

It will also be understood that because the surgeon exerts traction only on the free ends 50 and 52 of the ligature 14, there is no risk of jamming between the ligature 14 and the bottom face of the transverse process or of the rib, thus guaranteeing that effective fastening is provided with the transverse process or the rib or indeed a portion of the posterior arc of a vertebra.

This is shown in Figure 3, where reference AT identifies the transverse process.

In the above description, both of the strands 42 and 44 of the ligature are disposed in the recesses 30 and 32 on the same side of the rod 18. This disposition serves to obtain an optimum result. Nevertheless, it would not go beyond the invention if the strands 42 and 44 of the ligature 14 were to be placed on opposite sides of the rod 18. Under such circumstances, it should be considered that the outside face 18a of the rod 18 and the inside walls of the recesses 30 and 32 define two passageways, respectively for passing each of the strands 42 and 44 of the ligature 14.

Figures 4 to 7B show a second embodiment of the fixing system.

In these figures, there can be seen the rod 18, the connecting part now referenced 12', and the flexible ligature 14.

In this embodiment, the connecting part 12' is constituted by a part 50 that is generally U-shaped. The inside wall of this part is constituted by a bottom 52 of substantially semicylindrical shape and by two substantially plane portions 54 and 56 that correspond to the two limbs of the part 50. The width ℓ of the recess 58 formed in the part 50 is substantially equal to the diameter d of the rod 18. On its outside face 50a which is circularly symmetrical about a longitudinal axis of the part 50, there is provided a thread 60 occupying its upper portion. The thread 60 is located entirely above the rod 18 when it is put into place in the recess 58.

The thread 60 is designed to co-operate with a clamping ring 62 that constitutes the adjustable locking means. This ring has a slightly frustoconical bore 64 with an inside face 66 that carries tapping 68.

5 It can thus be understood that when the ring 62 is screwed tight on the threaded portion 60 of the part 50, it deforms the limbs of the part 50 elastically, thereby pinching and clamping strands of the ligature 14 between the rod 18 and the inside wall(s) of the recess 58, in a
10 manner explained below.

As shown better in Figures 6 and 6A, the part 50 includes in its bottom 70 a passage 72 for passing the ligature 14 in a manner explained below.

15 With reference to Figures 7, 7A, and 7B, there follows a description of two different ways of putting the flexible ligature 14 into place inside the connecting part 12' in the second embodiment. The side wall of the rod 18 and the inside wall of the recess 58 of the part 50 potentially define two passageways 74 and 76 for
20 passing the middle strands of the flexible ligature 14. In the configuration shown in Figure 7A, only the passageway 74 is used. Thus, both intermediate strands 42 and 44 of the flexible ligature 14 are disposed in the passage 74. This disposition presents all of the
25 advantages described with reference to the first embodiment.

30 In the configuration shown in Figure 7B, the middle strands 42 and 44 of the flexible ligature 14 are disposed respectively one in each of the passageways 76 and 78, i.e. on either side of the rod 18. This configuration likewise presents all of the advantages described with reference to the first embodiment of the device since the free ends 50 and 52 of the ligature 14 are accessible for exerting the desired traction in order
35 to obtain suitable clamping on the spinous process prior to locking the clamping ring 62 on the part 52.

This second embodiment presents the advantage of being simpler in design since it serves in particular to avoid making two longitudinal parts constituting a kind of clamp hinged on the pin 24.

- 5 It will be understood that in both embodiments, the locking means are constituted by an element that is distinct from the connecting part and that is removable therefrom. In addition, in both cases, the locking means co-operate with the connecting part by screw engagement.
- 10 It is thus possible to adjust accurately the dimensions of the ligature-passing passageway(s) as defined by the connecting part and the rod. In an initial stage, the coefficient of friction between the coefficient of the ligature and secondly the rod and the connecting part can
- 15 be adjusted. In the final stage, very effective clamping of the ligature is obtained between the rod and the locking part.

The claims defining the invention are as follows:

1. A vertebral fixing system suitable for being mounted on a vertebra of the spine in order to connect it to a rod, the system comprising:

5 a connecting part presenting first and second sides and suitable for being connected to said rod;

a flexible ligature of elongate shape suitable for connecting together said connecting part and at least one rib and/or a transverse process and/or a portion of the posterior arc of a vertebra; and

10 adjustable locking means mounted on said connecting part;

wherein

said ligature presents two free ends;

said connecting part defines at least one passageway for passing said ligature in such a manner that two distinct strands of said ligature can be engaged in said
15 passageway(s) so that said two ligature strands define a first ligature portion forming a loop that extends from a first side of said connecting part, and second and third ligature portions extending from the other side of said connecting part between respective ones of said ligature strands and said free ends; and

said locking means are distinct from the connecting part and co-operate
20 therewith by screw-fastening, said locking means being capable of taking a first position relative to the connecting part in which the two ligature strands are free in said strand-passing passageway(s), a second position relative to the connecting part in which the two ligature strands are prevented from moving in translation relative to the connecting part, and intermediate positions in which a coefficient of friction is created between said
25 ligature strands and said connecting part.

2. A vertebral fixing system according to claim 1, wherein said connecting part defines a single passageway and wherein ligature strands are engaged in the single passageway.

3. A vertebral fixing system according to claim 1 or claim 2, wherein said
30 passageway(s) is/are defined firstly by the outside surface of the portion of the rod that is engaged in the connecting part and secondly by a wall of the connecting part, and wherein said locking means are suitable for modifying the section of said passageway.

4. A vertebral fixing system according to claim 3, wherein said connecting part comprises two longitudinal elements having first ends that are hinged together, each
35 of said longitudinal elements presenting a recess suitable for receiving a portion of a

section of said rod, a wall of said recess co-operating with the side surface of said rod to define said passageway for passing said ligature strands, said locking means being mounted at the two second ends of said longitudinal elements.

5 5. A vertebral fixing system according to claim 4, wherein each longitudinal element has a longitudinal face, said longitudinal faces facing each other, and wherein each recess comprises a cavity of substantially semicylindrical shape opening out into said longitudinal face and a slot putting said cavity into communication with the opposite face of the longitudinal element.


10 6. A vertebral fixing system according to claim 3, wherein it comprises a part that is generally U-shaped, suitable for receiving said rod, and having the outer ends of the limbs of the U-shape threaded, and wherein the adjustable locking means comprise a tapped ring suitable for co-operating with the thread on the U-shaped part, tightening the ring causing the limbs of the part to be clamped against the rod.

15 7. A vertebral fixing system according to claim 6, wherein said passageway(s) is/are constituted by the space between the inside wall of the recess formed in said connecting part and the side wall of said rod.

 8. A vertebral fixing system substantially as hereinbefore described with reference to the accompanying drawings.

20

Dated 3 February 2012**Zimmer Spine****Patent Attorneys for the Applicant/Nominated Person****SPRUSON & FERGUSON**






FIG. 2A




FIG. 2B




FIG. 2C




FIG.3

4/5

