



US011537357B2

(12) **United States Patent**  
**Falcon**

(10) **Patent No.:** **US 11,537,357 B2**

(45) **Date of Patent:** **Dec. 27, 2022**

(54) **MEDIA CONTEXT SWITCHING BETWEEN DEVICES USING WIRELESS COMMUNICATIONS CHANNELS**

(58) **Field of Classification Search**  
CPC . G06F 3/165; H04L 65/1083; H04L 65/4015; H04W 4/80; H04W 12/084  
See application file for complete search history.

(71) Applicant: **Spotify AB**, Stockholm (SE)

(56) **References Cited**

(72) Inventor: **Jose Falcon**, Brooklyn, NY (US)

U.S. PATENT DOCUMENTS

(73) Assignee: **Spotify AB**, Stockholm (SE)

9,432,429 B1 \* 8/2016 Ho ..... H04L 65/604  
2008/0209021 A1 8/2008 Shamma  
2009/0215435 A1 8/2009 de Leon et al.  
2013/0054697 A1 2/2013 Cha  
(Continued)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **17/112,819**

OTHER PUBLICATIONS

(22) Filed: **Dec. 4, 2020**

Chloe Albanesius, Google Buys Bump App for Easy Sharing, Sep. 16, 2013, PCMag, 3 pages.

(65) **Prior Publication Data**

US 2021/0149622 A1 May 20, 2021

(Continued)

**Related U.S. Application Data**

*Primary Examiner* — Nicholas R Taylor

*Assistant Examiner* — Sanjoy K Roy

(63) Continuation of application No. 16/506,925, filed on Jul. 9, 2019, now Pat. No. 10,884,697, which is a continuation of application No. 14/983,317, filed on Dec. 29, 2015, now Pat. No. 10,348,790.

(74) *Attorney, Agent, or Firm* — Morgan, Lewis & Bockius LLP

(60) Provisional application No. 62/271,181, filed on Dec. 22, 2015.

(57) **ABSTRACT**

Methods, systems, and/or devices for media context switching among electronic devices are described herein. In one aspect, a method is performed at a first electronic device. A first media item is played. While playing the first media item, a near-field-communication (NFC) channel is established with a second electronic device while the second electronic device is playing a second media item. First contextual data of the first electronic device is transferred via the NFC channel to the second electronic device, wherein the first contextual data corresponds to the first media item. A playback command for the second media item is received. In response to receiving the playback command for the second media item, the first electronic device plays the second media item.

(51) **Int. Cl.**


**G06F 3/16** (2006.01)  
**H04W 4/80** (2018.01)  
**H04L 65/1083** (2022.01)  
**H04L 65/401** (2022.01)  
**H04W 12/084** (2021.01)

(52) **U.S. Cl.**

CPC ..... **G06F 3/165** (2013.01); **H04L 65/1083** (2013.01); **H04L 65/4015** (2013.01); **H04W 4/80** (2018.02); **H04W 12/084** (2021.01)

**21 Claims, 9 Drawing Sheets**

Media Content Delivery System 100



(56)

References Cited

U.S. PATENT DOCUMENTS

2013/0073584 A1 3/2013 Kuper et al.  
2013/0268593 A1\* 10/2013 Parekh ..... G06Q 30/0631  
709/204  
2013/0346478 A1 12/2013 Rodriguez et al.  
2014/0105561 A1 4/2014 Chen et al.  
2015/0094834 A1 4/2015 Vega et al.  
2015/0355878 A1\* 12/2015 Corbin ..... G06F 16/64  
700/94  
2016/0087928 A1\* 3/2016 Soldner ..... H04L 51/10  
709/206  
2016/0162252 A1\* 6/2016 Di Censo ..... G11B 27/11  
700/94  
2016/0174180 A1\* 6/2016 Daley ..... H04W 56/0015  
455/3.06  
2017/0093943 A1 3/2017 Alsina et al.  
2017/0273044 A1\* 9/2017 Alsina ..... H04L 65/60

OTHER PUBLICATIONS

Falcon, Office Action, U.S. Appl. No. 14/983,317, dated Dec. 18, 2017, 23 pgs.  
Falcon, Final Office Action, U.S. Appl. No. 14/983,317, dated Jul. 17, 2018, 22 pgs.  
Falcon, Office Action, U.S. Appl. No. 14/983,317, dated Nov. 2, 2018, 22 pgs.  
Falcon, Notice of Allowance, U.S. Appl. No. 14/983,317, dated Feb. 21, 2019, 9 pgs.  
Sarah Perez, With Its Latest Update, Bump's Mobile App Replaces USB Flash Drives, Feb. 14, 2013, Tech Crunch, 7 pages.  
Daniel Terdiman, With Bump Pay, sending money is easier than ever, Mar. 29, 2012, CNET, 4 pages.  
Falcon, Office Action, U.S. Appl. No. 16/506,925, dated Jun. 1, 2020, 23 pgs.  
Falcon, Notice of Allowance, U.S. Appl. No. 16/506,925, dated Sep. 10, 2020, 7 pgs.

\* cited by examiner




Figure 1




Figure 2

Media Content Server 104




Figure 3




Figure 4A




Figure 4B





Figure 4C






Figure 4E




Figure 5

## MEDIA CONTEXT SWITCHING BETWEEN DEVICES USING WIRELESS COMMUNICATIONS CHANNELS

### RELATED APPLICATION

This application is a continuation of U.S. Non-Provisional application Ser. No. 16/506,925, filed Jul. 9, 2019, which is a continuation of U.S. Non-Provisional application Ser. No. 14/983,317, filed Dec. 29, 2015, and claims priority and benefit to U.S. Provisional Application No. 62/271,181, filed Dec. 22, 2015, each of which is hereby incorporated by reference in its entirety.

### TECHNICAL FIELD

The disclosed implementations relate generally to media playback, and, in particular, to using wireless communications channels for media context switching between devices.

### BACKGROUND

Given the expansive and ever-growing amount of media available to consumers, users may wish to share and exchange media content with each other. While the details of media content may be verbally or visually exchanged between users, multiple steps are typically required in order for users to access and experience shared media content. For example, in order to listen to a recommended music track, a user would typically need to enter details of the music track in a search engine. Assuming the content is available, the user would then need to select the track in order to listen. The process is further encumbered if the user wishes to listen only to a specific portion of the music track that was recommended, as the user might need to skip over parts of the track until the relevant portion is accessed.

### SUMMARY

Accordingly, there is a need for devices, systems, and methods for switching playback contexts between electronic devices in order to share media content playing on the electronic devices. Using a near-field-communications (NFC) channel or other wireless channel, contextual data may be transferred between electronic devices, specifying media items, such as music tracks, being played on respective electronic devices. Thereafter, each of the electronic devices receive playback commands based on the contextual data of the other, causing each of the electronic devices to play a media item that was previously playing on the other electronic device before the contextual data was transferred. Users are therefore able to more efficiently, effectively, and securely share media content with other users. Such devices, systems, and methods optionally complement or replace conventional methods for sharing media content.

In accordance with some implementations, a method is performed at a first electronic device (e.g., a first smart phone) having one or more processors and memory storing instructions for execution by the one or more processors. The method includes playing a first media item. While playing the first media item, a near-field-communication (NFC) channel is established with a second electronic device (e.g., a second smart phone) while the second electronic device is playing a second media item. First contextual data of the first electronic device is transferred via the NFC channel to the second electronic device, wherein the first contextual data corresponds to the first media item. A

playback command for the second media item is received. In response to receiving the playback command for the second media item, the first electronic device plays the second media item.

5 In accordance with some implementations, a method is performed at a first electronic device (e.g., a first smart phone) having one or more processors and memory storing instructions for execution by the one or more processors. The method includes the first electronic device playing a first media item, wherein first contextual data of the first electronic device specifies the first media item. While playing the first media item, an NFC channel is established with a second electronic device (e.g., a second smart phone) while the second electronic device is playing a second media item, wherein second contextual data of the second electronic device corresponds to the second media item. The first electronic device receives the second contextual data via the NFC channel from the second electronic device. After receiving the second contextual data, the first electronic device receives a playback command for the second media item. In response to receiving the playback command for the second media item, the first electronic device plays the second media item.

15 In accordance with some implementations, a method is performed at a remote server system (e.g., a media content server) having one or more processors and memory storing instructions for execution by the one or more processors. The remote server system receives, from a first electronic device (e.g., a first smart phone), first contextual data of the first electronic device and second contextual data of a second electronic device (e.g., a second smart phone). The first contextual data specifies a first media item playing on the first electronic device and the second contextual data specifies a second media item playing on the second electronic device. The remote server system sends a first playback command for the second media item to the first electronic device in accordance with the second contextual data, and sends a second playback command for the first media item to the second electronic device in accordance with the first contextual data.

25 In accordance with some implementations, an electronic device includes one or more processors and memory storing one or more programs configured to be executed by the one or more processors. The one or more programs include instructions for performing the operations of any of the methods described above. In accordance with some implementations, a non-transitory computer-readable storage medium has stored therein instructions that, when executed by the electronic device, cause the electronic device to perform the operations of any of the methods described above.

30 Thus, devices are provided with efficient methods for sharing media content among one another, thereby increasing the effectiveness, efficiency, and user satisfaction with such devices.

### BRIEF DESCRIPTION OF THE DRAWINGS

The implementations disclosed herein are illustrated by way of example, and not by way of limitation, in the figures of the accompanying drawings. Like reference numerals refer to corresponding parts throughout the drawings.

FIG. 1 is a block diagram illustrating an exemplary media content delivery system in accordance with some implementations.

FIG. 2 is a block diagram illustrating an exemplary client device in accordance with some implementations.

FIG. 3 is a block diagram illustrating an exemplary media content server in accordance with some implementations.

FIGS. 4A-4E illustrate an interaction between electronic devices in which media context switching is performed, in accordance with some implementations.

FIG. 5 is a flow diagram illustrating a method of media context switching among electronic devices, in accordance with some implementations.

#### DETAILED DESCRIPTION

Reference will now be made to implementations, examples of which are illustrated in the accompanying drawings. In the following description, numerous specific details are set forth in order to provide an understanding of the various described implementations. However, it will be apparent to one of ordinary skill in the art that the various described implementations may be practiced without these specific details. In other instances, well-known methods, procedures, components, circuits, and networks have not been described in detail so as not to unnecessarily obscure aspects of the implementations.

It will also be understood that, although the terms first, second, etc. are, in some instances, used herein to describe various elements, these elements should not be limited by these terms. These terms are used only to distinguish one element from another. For example, a first electronic device could be termed a second electronic device, and, similarly, a second electronic device could be termed a first electronic device, without departing from the scope of the various described implementations. The first electronic device and the second electronic device are both electronic devices, but they are not the same electronic device.

The terminology used in the description of the various implementations described herein is for the purpose of describing particular implementations only and is not intended to be limiting. As used in the description of the various described implementations and the appended claims, the singular forms “a,” “an,” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will also be understood that the term “and/or” as used herein refers to and encompasses any and all possible combinations of one or more of the associated listed items. It will be further understood that the terms “includes,” “including,” “comprises,” and/or “comprising,” when used in this specification, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof.

As used herein, the term “if” is, optionally, construed to mean “when” or “upon” or “in response to determining” or “in response to detecting” or “in accordance with a determination that,” depending on the context. Similarly, the phrase “if it is determined” or “if [a stated condition or event] is detected” is, optionally, construed to mean “upon determining” or “in response to determining” or “upon detecting [the stated condition or event]” or “in response to detecting [the stated condition or event]” or “in accordance with a determination that [a stated condition or event] is detected,” depending on the context.

As used herein, the term “exemplary” is used in the sense of “serving as an example, instance, or illustration” and not in the sense of “representing the best of its kind.”

FIG. 1 is a block diagram illustrating an exemplary media content delivery system 100 in accordance with some implementations. The media content delivery system 100 includes

one or more client devices 102 (e.g., client device 102-1 and client device 102-2), one or more media content servers (e.g., media content server 104), and one or more media presentation systems (e.g., media presentation systems 108, which may include a speaker, television (TV), digital versatile disk (DVD), and/or other media presentation system). One or more networks (e.g., network(s) 112) communicably connect each component of the media content delivery system 100 with other components of the media content delivery system 100. In some implementations, the one or more networks 112 include public communication networks, private communication networks, or a combination of both public and private communication networks. For example, the one or more networks 112 can be any network (or combination of networks) such as the Internet, other wide area networks (WAN), local area networks (LAN), virtual private networks (VPN), metropolitan area networks (MAN), peer-to-peer networks, and/or ad-hoc connections.

In some implementations, a client device (e.g. client device 102-1 or client device 102-2) is a representative electronic device associated with one or more users. In some implementations, a client device is any of: a personal computer, a mobile electronic device, a wearable computing device, a laptop, a tablet computer, a mobile phone, a feature phone, a smart phone, a digital media player, or any other electronic device capable of executing commands for playing media content. In some implementations, client device 102-1 and client device 102-2 are the same type of device (e.g., client device 102-1 and client device 102-2 are both mobile devices). Alternatively, client device 102-1 and client device 102-2 are different types of devices.

In some implementations, client devices 102-1 and 102-2 send and receive information through the networks 112. For example, through the networks 112, client devices 102 may send data to the media content server 104 (e.g., contextual data, indicating a track currently playing on a respective client device 102) and receive playback commands that cause corresponding media items (e.g., music tracks, videos, etc.) to be played. In some implementations, client devices 102 are associated with identifiers (e.g., unique hardware or application identifiers, network addresses, etc.) that the media content server 104 uses to uniquely identify and/or establish communications with the client devices 102. In some implementations, the media presentation system(s) 108 may be part of the client devices 102, such as built-in speakers, an audio jack, or a screen, or may be separate from the client devices 102, such as a wirelessly coupled speaker.

Client devices 102 (and optionally, the media presentation system 108) communicate with each other through one or more communications channels. In some implementations, client devices 102 communicate with each other through the one or more network(s) 112. For example, if the client devices 102 initiate a process for media context switching (e.g., swapping tracks), the client device 102-1 may send contextual data for a media item that it is currently playing to the media content server 104, and in response, a playback command is sent to the client device 102-2 that causes the media item to play on the client device 102-2. In some implementations, client devices 102 (and optionally, the media presentation system 108) communicate with each other directly through one or more wired and/or wireless communications channels 106 (e.g., BLUETOOTH/BLE communication technologies, radio-frequency-based near-field-communication (NFC) technologies, infrared communication technologies, etc.). For example (as described in greater detail below), client devices 102 may include a wireless communications interface (e.g., an NFC interface)

for establishing wireless communications channels **106** (e.g., NFC channels) with one another when they are within a threshold proximity of each other. Contextual data of a respective media items playing on the client devices **102** may be transferred via the wireless communications channels to perform media context switching (e.g., to swap tracks).

In some implementations, client device **102-1** and client device **102-2** each include a media application **222** (as shown in FIG. 2 and described in more detail below) that allows a user of the client device to browse and request playback of media content. Using the media application **222**, in some implementations, client devices **102** may also initiate a media context switching process (e.g., context switch module **226**). As an example, when the client devices **102** (or a client device **102** and the media presentation system **108**) are brought within a threshold proximity of one another, an affordance (e.g., affordance **410**, FIG. 4C) is displayed on one or both of the client devices **102**. Selection of the affordance initiates a media context switching process where contextual data is transferred between the client devices and playback commands are received by the client devices, causing corresponding media items to be played (e.g., causing tracks to be swapped).

In some implementations, the media content server **104** stores media content and provides the media content (e.g., in response to receiving contextual data from the client device **102-1** and/or **102-2**), via the network(s) **112**, to the client devices **102** and/or the media presentation system **108**. Content stored and served by the media content server **104**, in some implementations, includes any appropriate content, including text (e.g., audio (e.g., music, spoken word, podcasts, etc.), videos (e.g., short-form videos, music videos, television shows, movies, clips, previews, etc.), articles, blog posts, emails, etc.), images (e.g., photographs, drawings, renderings, etc.), games (e.g., 2- or 3-dimensional graphics-based computer games, etc.), or any combination of content types (e.g., web pages that include any combination of the foregoing types of content or other content not explicitly listed). In some implementations (e.g., as described for FIG. 5), contextual data (e.g., transferred between client devices **102** during a media context switching process) specifies media items in playback on respective devices, where the media items correspond to media content stored in the media content server **104**. For example, the contextual data includes a media-item identifier, a time marker, and/or a device identifier. The description of the media content server **104** as a “server” is intended as a functional description of the devices, systems, processor cores, and/or other components that provide the functionality attributed to the media content server **104**. It will be understood that the media content server **104** may be a single server computer, or may be multiple server computers. Moreover, the media content server **104** may be coupled to other servers and/or server systems, or other devices, such as other client devices, databases, content delivery networks (e.g., peer-to-peer networks), network caches, and the like. In some implementations, the media content server **104** is implemented by multiple computing devices working together to perform the actions of a server system (e.g., cloud computing).

As described above, media presentation systems **108** are capable of receiving media content (e.g., from the media content server **104**) and presenting the received media content. In some implementations, media presentation systems are thus devices to which the media content server **104** can send media content. For example, media presentation

systems include computers, dedicated media players, home entertainment systems, network-connected stereo and/or speaker systems, network-connected vehicle media systems, network-connected televisions, network-connected DVD players, and universal serial bus (USB) devices used to provide a playback device with network connectivity, and the like. In some implementations, each media presentation system **108** is associated with an identifier (e.g., a unique hardware or application identifier, a network address, etc.) that the media content server **104** and/or the client devices **102** use to uniquely identify and/or establish communications with the media presentation system. In some implementations, a media presentation system **108** receives from client devices **102** (e.g., using an NFC channel) contextual data for respective media items playing on the client devices **102**. The media presentation system **108** sends the contextual data (e.g., via a network **112**) to the media content server **104**, and afterwards receives a playback command from the media content server **104** that causes playback of the respective media items (e.g., media items queued in an order in which the contextual data was received from the client devices **102**). In these implementations, users may therefore perform media context switching with the media presentation system **108** by using client devices **102**, as described in greater detail with respect to the method **500** (FIG. 5). In some implementations, media presentation systems **108** are integrated into respective client devices **102**.

FIG. 2 is a block diagram illustrating an exemplary client device **102** (e.g., client device **102-1** and/or client device **102-2** of FIG. 1) in accordance with some implementations. The client device **102** typically includes one or more central processing units (CPU(s), e.g., processors or cores) **202**, one or more network (or other communications) interfaces **210**, memory **212**, and one or more communication buses **214** for interconnecting these components. The communication buses **214** optionally include circuitry (sometimes called a chipset) that interconnects and controls communications between system components.

As also shown in FIG. 2, the client device **102** includes a user interface **204**, including output device(s) **206** and input device(s) **208**. In some implementations, the input devices include a keyboard or track pad. Alternatively, or in addition, in some implementations, the user interface **204** includes a display device that includes a touch-sensitive surface, in which case the display device is a touch-sensitive display. In client devices that have a touch-sensitive display, a physical keyboard is optional (e.g., a soft keyboard may be displayed when keyboard entry is needed). The output devices (e.g., output device(s) **206**) also optionally include speakers or an audio output connection (i.e., audio jack) connected to speakers, earphones, or headphones. Furthermore, some client devices **102** use a microphone and voice recognition device to supplement or replace the keyboard. Optionally, the client device **102** includes an audio input device (e.g., a microphone) to capture audio (e.g., speech from a user). Optionally, the client device **102** includes a location-detection device, such as a GPS (global positioning satellite) or other geo-location receiver, and/or location-detection software for determining the location of the client device **102**.

In some implementations, the one or more network interfaces **210** include wireless and/or wired interfaces for receiving data from and/or transmitting data to other client devices **102**, media presentations systems **108**, media content server **104**, and/or other devices or systems. In some implementations, data communications are carried out using any of a variety of custom or standard wireless protocols (e.g., NFC, RFID, IEEE 802.15.4, Wi-Fi, ZigBee, 6LoW-

PAN, Thread, Z-Wave, Bluetooth, ISA100.11a, WirelessHART, MiWi, etc.). Furthermore, in some implementations, data communications are carried out using any of a variety of custom or standard wired protocols (e.g., USB, Firewire, Ethernet, etc.). For example, the one or more network interfaces **210** include an NFC interface **250** for enabling wireless data communications with other client devices **102**, media presentations systems **108**, and/or other NFC-compatible devices. Furthermore, in some implementations, the one or more network interfaces **210** includes a wireless LAN (WLAN) interface **252** for enabling data communications with other WLAN-compatible devices and/or the media content server **104** (via the one or more network(s) **112**, FIG. 1).

Memory **212** includes high-speed random-access memory, such as DRAM, SRAM, DDR RAM, or other random-access solid-state memory devices; and may include non-volatile memory, such as one or more magnetic disk storage devices, optical disk storage devices, flash memory devices, or other non-volatile solid-state storage devices. Memory **212** may optionally include one or more storage devices remotely located from the CPU(s) **202**. Memory **212**, or alternately, the non-volatile memory solid-state storage devices within memory **212**, includes a non-transitory computer-readable storage medium. In some implementations, memory **212** or the non-transitory computer-readable storage medium of memory **212** stores the following programs, modules, and data structures, or a subset or superset thereof:

- an operating system **216** that includes procedures for handling various basic system services and for performing hardware dependent tasks;

- network communication module(s) **218** for connecting the client device **102** to other computing devices (e.g., client devices **102**, media presentation systems **108**, media content server **104**, and/or other devices) via the one or more network interface(s) **210** (wired or wireless);

- a user interface module **220** that receives commands and/or inputs from a user via the user interface **204** (e.g., from the input devices **208**, which may include keyboards, touch screens, microphones, eye tracking components, three-dimensional gesture tracking components, and the like), and provides user interface objects and other outputs for display on the user interface **204** (e.g., the output devices **206**, which may include a display screen, a touchscreen, a speaker, etc.);

- a media application **222** (e.g., an application associated with a media content provider, including a media player, a streaming media application, or any other appropriate application or component of an application) for browsing, receiving, processing, and presenting media content (e.g., media content streams, media content files, advertisements, web pages, videos, audio, games, etc.). The media application **222** also includes the following modules (or sets of instructions), or a subset or superset thereof:

- an authentication module **224** for sending authentication tokens corresponding to one or more media presentation systems associated with the client device **102** (e.g., one or more of the media presentation systems **108** from FIG. 1), receiving authentication tokens from other client devices, and optionally generating authentication tokens for media presentation systems associated with client device **102**;

- a context switch module **226** for transferring (e.g., to another client device **102** using NFC), receiving (e.g., from another client device **102** using NFC), and/or sending (e.g., to a media content server **104**) contextual data (e.g., data specifying a media item playing on a respective client device **102**), and for receiving and executing playback commands for playing media items (e.g., receiving playback commands in response to sending contextual data to the media content server **104**);

- a media content browsing module **228** for providing controls and/or user interfaces enabling a user to navigate, select for playback, and otherwise control or interact with media content, whether the media content is stored locally or remotely;

- a web browser application **230** (e.g., Internet Explorer by Microsoft, Firefox by Mozilla, Safari by Apple, or Chrome by Google) for accessing, viewing, and interacting with web sites; and

- other applications **232**, such as applications for word processing, calendaring, mapping, weather, stocks, time keeping, virtual digital assistant, presenting, number crunching (spreadsheets), drawing, instant messaging, e-mail, telephony, video conferencing, photo management, video management, a digital music player, a digital video player, 2D gaming, 3D (e.g., virtual reality) gaming, electronic book reader, and/or workout support.

In some implementations, the media presentation systems **108** is a type of client device **102**, and includes some or all of the same components, modules, and sub-modules as described above with respect to the client device **102**.

FIG. 3 is a block diagram illustrating an exemplary media content server **104** in accordance with some implementations. The media content server **104** typically includes one or more central processing units/cores (CPUs) **302**, one or more network interfaces **304**, memory **306**, and one or more communication buses **308** for interconnecting these components.

Memory **306** includes high-speed random access memory, such as DRAM, SRAM, DDR RAM, or other random access solid-state memory devices; and may include non-volatile memory, such as one or more magnetic disk storage devices, optical disk storage devices, flash memory devices, or other non-volatile solid-state storage devices. Memory **306**, optionally, includes one or more storage devices remotely located from one or more CPUs **302**. Memory **306**, or, alternatively, the non-volatile solid-state memory device(s) within memory **306**, includes a non-transitory computer-readable storage medium. In some implementations, memory **306**, or the non-transitory computer-readable storage medium of memory **306**, stores the following programs, modules and data structures, or a subset or superset thereof:

- an operating system **310** that includes procedures for handling various basic system services and for performing hardware dependent tasks;

- a network communication module **312** that is used for connecting the media content server **104** to other computing devices via one or more network interfaces **304** (wired or wireless) connected to one or more networks **112** such as the Internet, other WANs, LANs, PANs, MANs, VPNs, peer-to-peer networks, content delivery networks, ad-hoc connections, and so on;

- one or more server application modules **314** for enabling the media content server **104** to perform various functions, the server application modules **314** including, but not limited to, one or more of:

an authentication module **316** for managing authentication and/or authorization requests, the authentication module **316** including, but not limited to, one or more of:

- a token generating module **318** for generating authentication tokens permitting use of media presentation systems **108** (FIG. 1); and
- a token validating module **320** for verifying that an authentication token is valid (e.g., has not yet expired or has not yet been revoked);
- a media request processing module **322** for processing requests for media content and facilitating access to requested media content items by client devices (e.g., the client device **102**) including, optionally, streaming media content to such devices or to one or more media presentation systems **108**, and sending playback commands for playing media items to client devices **102** and/or media presentation systems **108** (e.g., based on contextual data received from client devices **102**); and
- one or more server data module(s) **324** for handling the storage of and access to media content items and metadata relating to the media content items; in some implementations, the one or more server data module(s) **324** include:
  - a media content database **326** for storing media content items (e.g., audio files, video files, text files, etc.);
  - a metadata database **328** for storing metadata relating to the media content items including, but not limited to: contextual data **330** that specifies media items being played on client devices **102** and/or media presentation system **108**, and other associated information (e.g., contextual data includes a media-item identifier, a time marker, device identifier, etc.); and
  - a media account database **332** for storing account information for user media accounts, including user profiles, credentials (e.g., user identifiers, passwords, email addresses, etc.), credentials or identifiers of any linked accounts, and the like.

In some implementations, the media content server **104** includes web or Hypertext Transfer Protocol (HTTP) servers, File Transfer Protocol (FTP) servers, as well as web pages and applications implemented using Common Gateway Interface (CGI) script, PHP Hyper-text Preprocessor (PHP), Active Server Pages (ASP), Hyper Text Markup Language (HTML), Extensible Markup Language (XML), Java, JavaScript, Asynchronous JavaScript and XML (AJAX), XHP, Javelin, Wireless Universal Resource File (WURFL), and the like.

Each of the above identified modules stored in memory **212** and **306** corresponds to a set of instructions for performing a function described herein. The above identified modules or programs (i.e., sets of instructions) need not be implemented as separate software programs, procedures, or modules, and thus various subsets of these modules may be combined or otherwise re-arranged in various implementations. In some implementations, memory **212** and **306** optionally store a subset or superset of the respective modules and data structures identified above. Furthermore, memory **212** and **306** optionally store additional modules and data structures not described above.

Although FIG. 3 illustrates the media content server **104** in accordance with some implementations, FIG. 3 is intended more as a functional description of the various features that may be present in one or more media content servers than as a structural schematic of the implementations

described herein. In practice, items shown separately could be combined and some items could be separated. For example, some items shown separately in FIG. 3 could be implemented on single servers and single items could be implemented by one or more servers. The actual number of servers used to implement the media content server **104**, and how features are allocated among them, will vary from one implementation to another and, optionally, depends in part on the amount of data traffic that the server system handles during peak usage periods as well as during average usage periods.

In some implementations, the media content server **104** uses tables, databases, or other appropriate data structures to associate respective users with respective media presentation systems and to manage authentication tokens (i.e., access tokens) associated with respective media presentation systems.

FIGS. 4A-4E illustrate an interaction between electronic devices in which media context switching is performed, in accordance with some implementations. In this example, the electronic devices are client devices **102**. Also shown are implementations of graphical user interfaces (“GUIs”) that are displayed on the client devices **102** during a media context switching operation.

In FIG. 4A, client devices **102-1** and **102-2** are shown separately playing respective media items. The respective GUIs displayed on the client devices **102** visually indicate details of the respective media items playing on the client devices **102**, such as a track name (**400-1** and **400-2**), an artist (**402-1** and **402-2**), a playback context (**404-1** and **404-2**) (e.g., album, playlist), time marker information (**406-1** through **406-4**) (e.g., current position within playback **406-1** and **406-3**; length of track **406-2** and **406-4**), and an associated graphic (e.g., album covers **408-1** and **408-2**).

Referring now to FIG. 4B, while playing their respective media items, the client devices **102** are brought towards each other to initiate a transfer of contextual data from at least one client device to the other (e.g., between the two client devices). Contextual data for a respective client device includes data specifying a media item in playback on the respective client device, or associated details thereof. Contextual data specifies, for example, a media-item identifier (e.g., corresponding to track “Yellow” by artist “Coldplay”), a time marker (e.g., corresponding to time **2:05** of track length **4:29**), a device identifier (e.g., for client device **102-2**), a user identifier (e.g., for a user associated with the client device **102-2**), and/or a media-item context (e.g., track playing from a playlist **404-2** entitled “Summer Jamz”).

As illustrated in FIG. 4C, the client devices **102** are within a threshold proximity (distance  $d_r$ ) from one other, sufficient for establishing a wireless communications channel (e.g., using near-field-communication (NFC)) through which data can be transferred between the client devices. In this example, an optional affordance **410** appears on the GUI of client device **102-1**, requesting confirmation for the client device **102-1** to transfer contextual data to (and/or receive contextual data from) the client device **102-2**.

In response to detecting a user input **412** selecting the affordance **410**, contextual data for the media item playing on the client device **102-1** is transferred to the client device **102-2**. Afterwards, referring to FIGS. 4D and 4E, each client device **102** automatically receives a respective playback command corresponding to the media item that was playing on the other client device **102**. Playback commands thus are received without any user input beyond the user input **412** (or alternatively, without any user input at all). As indicated by the displayed GUIs, the client device **102-1** begins

playing the media item that was previously playing on the client device **102-2** in FIG. 4A, and similarly the client device **102-2** begins playing the media item that was previously playing on the client device **102-1**.

Both client devices **102** switch context in the example of FIGS. 4A-4E. Alternatively, only one of the two devices switches context. FIGS. 4A-4E illustrate context switching that occurs upon bringing the client devices into range of each other. Alternatively, context switching may be delayed until a client device finishes playing a current media item or play list. The context switching of FIGS. 4A-4E results in each device beginning to play a media item that was being played by the other device when the devices detected each other. Alternatively, context switching may cause a client device to start playback from the beginning of a playlist for the other devices.

Media context switching with client devices **102** as shown in FIGS. 4A-4E and described for these other examples is described in greater detail below in conjunction with the method **500** of FIG. 5.

FIG. 5 is a flow diagram illustrating a method **500** of media context switching among electronic devices, in accordance with some implementations. The method **500** is performed by a first electronic device **502-1** (e.g., client device **102-1**, FIGS. 1 and 2), a second electronic device **502-2** (e.g., client device **102-2**, FIGS. 1 and 2), and a remote server system **503** (e.g., media content server **104**, FIGS. 1 and 3). Operations performed in FIG. 5 correspond to instructions stored in computer memories (e.g., memory **212** of client devices **102**, FIG. 2, and memory **306** of media content server **104**, FIG. 3) or other computer-readable storage medium.

The first electronic device **502-1** plays (**504**) a first media item, and the second electronic device **502-2** simultaneously plays (**505**) a second media item. An example is provided in FIG. 4A, where the client device **102-1** is shown playing an audio track **400-1** "Time" by the artist **402-1** "Pink Floyd," and the client device **102-2** is shown playing an audio track **400-2** "Yellow" by the artist **402-2** "Coldplay." In some implementations, the first electronic device **502-1** continues playing the first media item until it begins playing the second media item in response to receiving the first playback command (step **516**, described below), and the second electronic device **502-2** continues playing the second media item until it begins playing the first media item in response to receiving the second playback command (step **518**, described below).

While playing the first media item, the first electronic device **502-1** establishes (**506**) a near-field-communication (NFC) channel with a second electronic device **502-2** (and the second electronic device establishes the NFC channel with the first electronic device) while the second electronic device is playing the second media item. In some implementations, the NFC channel is established when the first electronic device **502-1** and the second electronic device **502-2** are detected to be within a threshold proximity of one another (e.g., a threshold distance for the NFC interface of the electronic devices). An example is shown in FIG. 4C, where the client devices **102** establish an NFC channel when they are within a threshold distance  $d_t$  of each other.

In some implementations, playing (**504**) the first media item includes pausing the first media item (and/or playing (**505**) the second media item includes pausing the second media item), where the second electronic device **502-2** is detected while the first media item is paused (and/or the first electronic device **502-1** is detected while the second media item is paused).

In some implementations, the first electronic device **502-1** pauses the first media item in response to detecting the second electronic device **502-2** in sufficient proximity to the first electronic device. Similarly, the second electronic device **502-2** may pause the second media item in response to detecting the first electronic device in sufficient proximity to the second electronic device).

The first electronic device **502-1** transfers (**508**) first contextual data of the first electronic device to the second electronic device **502-2**, and the second electronic device **502-2** receives the first contextual data from the first electronic device, via the NFC channel. The first contextual data corresponds to the first media item.

In some implementations, the first contextual data specifies at least one of: a media-item identifier associated with the first media item (e.g., a unique ID for a music track); a time marker indicating a position within playback of the first media item (e.g., time marker **406-1** for the media item playing on the client device **102-1** in FIG. 4A is 3:15 for a track length of 6:53); a device identifier associated with the first electronic device (e.g., identifying information for the client device **102-1**, such as a unique ID, a network address (IP address, MAC address), etc.); a user identifier associated with a user of the first electronic device (e.g., username, account name, etc.); or a media-item context indicating the playback context within which the first media item is played (e.g., media-item context **404-1** for client device **102-1** in FIG. 4A is the album "Dark Side of the Moon"). Playback context may indicate a predefined sequence of media items (e.g., a playlist, an album, etc., where media items have a defined order) or a type of relation of multiple media items (e.g., genre, artist, etc.).

In some implementations, the first electronic device transfers (**508**), and the second electronic device receives, the first contextual data in response to establishing (**506**) the NFC channel.

In some implementations, the first electronic device transfers (step **508**), and the second electronic device receives, the first contextual data in response to the first and/or second electronic device detecting a user input authorizing the transfer of the first contextual data. The user input may, in some implementations, correspond to a selection of an affordance (e.g., user input **412** detected on affordance **410**, FIG. 4C). Furthermore, in some implementations, the affordance is displayed on the first and/or second electronic device in response to establishing (**506**) the NFC channel.

In some implementations, the first electronic device **502-1** ceases to play the first media item (and/or the second electronic device **502-2** ceases to play the second media item) after the first and second electronic devices establish the NFC channel with each other. In some implementations, the first electronic device **502-1** ceases to play the first media item (and/or the second electronic device **502-2** ceases to play the second media item) in response to the first electronic device transferring (**506**) the first contextual data to the second electronic device, and the second electronic device receiving the first contextual data from the first electronic device. The two electronic devices thus may stop playing their current media items (e.g., their current tracks) when the NFC channel is established or when the contextual data is transferred.

In some implementations, the second electronic device **502-2** sends (**510**) to the remote server system **503**, and the remote server system receives from the second electronic device, the first and second contextual data. The second contextual data of the second electronic device corresponds

to the second media item (examples of contextual data are described above with respect to the first contextual data).

The remote server system **503** sends (**512**) to the first electronic device **502-1**, and the first electronic device receives from the remote server system, a first playback command for the second media item in accordance with the second contextual data. Furthermore, the remote server system **503** sends (**514**) to the second electronic device **502-2**, and the second electronic device receives from the remote server system, a second playback command for the first media item in accordance with the first contextual data. In response to receiving the first playback command for the second media item, the first electronic device **502-1** starts (**516**) playing the second media item. Furthermore, in response to receiving the second playback command for the second media item, the second electronic device **502-2** starts (**518**) playing the first media item. In some implementations, playback of swapped media items (e.g., swapped tracks) begins upon receiving the commands.

An example is illustrated in FIGS. 4C-4E. In FIG. 4C, upon detecting the user input **412** on the affordance **410**, contextual data (e.g., media-item identifier, time marker, device identifier, etc.) is transferred from the client device **102-1** to the client device **102-2** using an NFC channel. As shown by the GUIs in FIGS. 4D and 4E, following the transfer of the contextual data, the client devices **102** switch contexts with each other (i.e., swap media items), resulting in each client device commencing playback of the media item that was previously being played on the other client device prior to the contextual data being transferred. Thus, contextual data for respective electronic devices may be used to identify media items in playback on the respective electronic devices (before or during the transfer of contextual data and/or the receipt of playback commands), and may be used (e.g., by a remote server system) to send corresponding commands to cause playback by each electronic device **502** of identified media items that were playing on the other electronic device **502**.

In some implementations, playback commands are instructions that, when executed (e.g., by electronic devices that receive the playback commands), cause playback of corresponding media items to commence automatically (e.g., automatically begin streaming or downloading media content to an electronic device). In some implementations, a playback command is specific to a particular media item or playlist that includes the particular media item (based on information specified by contextual data transferred between electronic devices). In some implementations, the first playback command provides to the first electronic device **502-1** access to the second media item and/or the second playback command provides to the second electronic device **502-2** access to the first media item. For example, a playback command causes automatic playback of a media item. In other examples, a playback command causes display of a graphic associated with a media item (e.g., a track) and a selectable user-interface affordance for commencing playback of the media item.

In some implementations, the first electronic device **502-1** receives (**516**) the first playback command and/or the second electronic device **502-2** receives (**518**) the second playback command from the remote server system **503** to which the first contextual data of the first electronic device and second contextual data of the second electronic device are sent by the second electronic device. A single remote server thus controls the context switching. Alternatively, the playback commands are received from a server in communication

with but distinct from the remote server system to which the first contextual data and the second contextual data are sent.

In some implementations, the first electronic device **502-1** receives the first playback command and/or the second electronic device **502-2** receives the second playback command from the remote server system **503** in response to the first and second contextual data being sent to the same remote server system **503**. In alternative implementations, the second electronic device **502-2** sends either the first or second contextual data (but not both) to the remote server system **503**. The first electronic device **502-1** then receives the first playback command for the second media item from the remote server system **503** in response to the second electronic device **502-2** sending the second contextual data, or the second electronic device receives the second playback command for the first media item from the remote server system in response to sending the first contextual data. Thus, in some implementations, only the first electronic device **502-1** or the second electronic device **502-2** switches context, but not both. The electronic device that switches context does so under the control of the remote server system **503**.

In some implementations, the remote server system **503** previously provided to the first electronic device **502-1** a command to play (**504**) the first media item and/or that previously provided to the second electronic device **502-2** a command to play (**505**) the second media item. A single remote server system thus may control all playback operations.

In some implementations, the first electronic device **502-1** receives from the second electronic device **502-2**, and the second electronic device sends to the first electronic device, the first playback command. In other words, the first playback command is sent directly by the second electronic device **502-2** to the first electronic device **502-1** without going through the remote server system **503**. Similarly, the first electronic device **502-1** may send the second playback command directly to the second electronic device **502-2** without going through the remote server system **503**. Context switching thus may occur independently of a remote server system.

In some implementations, the first electronic device **502-1** ceases to play the first media item after receiving the first playback command for the second media item (and/or the second electronic device **502-2** ceases to play the second media item after receiving the second playback command for the first media item). For example, the first electronic device **502-1** continues playing the first media item while the second electronic device **502-2** receives the first contextual data and sends the second contextual data to the remote server system **503**, and continues playing the first media item until the remote server system **503** sends the first playback command to the first electronic device (or until the first electronic device receives the first playback command). The second electronic device **502-2** may operate similarly. The electronic devices may continue to play their original media items (e.g., tracks) until playback commands for the context switching are received.

In some implementations, the first electronic device **502-1** plays the second media item (step **516**) after ceasing to play the first media item (and/or the second electronic device **502-2** plays the first media item (step **518**) after ceasing to play the second media item). In other words, the first electronic device **502-1** ceases playback of the first media item first before it commences playback of the second media item.

In some implementations, the first electronic device **502-1** directly transitions to playing the second media item in response to the first command. Similarly, the second electronic device **502-2** directly transitions to playing the first media item in response to the second command. That is, in some implementations, the first electronic device **502-1** ceases to play the first media item upon receiving the first playback command for the second media item, and plays **(516)** the second media item upon ceasing to play the first media item. In addition, or alternatively, the second electronic device **502-2** ceases to play the second media item upon receiving the second playback command for the first media item, and plays **(518)** the first media item upon ceasing to play the second media item. Context switching thus may be almost immediate.

In alternative implementations, each electronic device finishes playing its current media item before switching context. The first electronic device **502-1** finishes playing the first media item before transitioning to playing the second media item and/or the second electronic device **502-2** finishes playing the second media item before transitioning to playing the first media item. The first electronic device **502-1** plays **(516)** the second media item after reaching the end of the first media item and ceasing to play the first media item. In addition, or alternatively, the second electronic device **502-2** plays **(518)** the first media item after reaching the end of the second media item and ceasing to play the second media item. Media items to be played in response to playback commands are thus placed in a playback queue.

An electronic device may finish playing its current playlist and/or start playing a playlist for the other device from the beginning. In some implementations, upon ceasing to play the first media item and before playing the second media item, the first electronic device **502-1** plays one or more additional media items distinct from the first and second media items. Similarly, upon ceasing to play the second media item and before playing the first media item, the second electronic device **502-2** may play one or more additional media items distinct from the first and second media items. The one or more additional media items to be played by one electronic device include media items in a playlist of the other electronic device as specified by contextual data for the other electronic device (e.g., the first electronic device **502-1** starts playing from the beginning of, or from another position within, a playlist of the second device in response to the playback command). Alternatively, or in addition, the one or more additional media items to be played by an electronic device include remaining media items in a current playlist of that electronic device. For example, the first electronic device finishes playing media items from its own playlist first before playing the second media item.

In other implementations, the second media item is preceded by additional media items in a predefined sequence of media items (e.g., a playlist), but the first electronic device **502-1** plays the second media item first upon ceasing to play the first media item. The first electronic device **502-1** thus does not begin from the beginning of the playlist of the second electronic device **502-2**. Similarly, the first media item is preceded by additional media items in a predefined sequence of media items, but the second electronic device **502-2** plays the first media item upon ceasing to play the second media item. The second electronic device **502-2** thus does not begin from the beginning of the playlist of the first electronic device **502-1**.

Context switching may involve swapping all or a portion of a playlist. In some implementations, after playing the second media item, the first electronic device **502-1** plays one or more additional media items distinct from the first and second media items, wherein the one or more additional media items follow the second media item in a playlist (e.g., a user playlist, an album, etc.) Likewise, after playing the first media item, the second electronic device **502-2** may play one or more additional media items distinct from the first and second media items, wherein the one or more additional media items follow the first media item in a playlist). If the one or more additional media items are the last media items in a sequence defined by the playlist, in some implementations, the first electronic device **502-1** plays another media item distinct from the first, second, and one or more media items, and corresponding to the beginning of the playlist (i.e., once the first electronic devices **502-1** reaches the end of a playlist that includes the second media item, it starts from the beginning of the playlist).

Playback of a swapped media item may be followed by playback of one or more media items that are similar or related. In some implementations, after playing the second media item, the first electronic device **502-1** plays one or more additional media items having a predefined association with the second media item (and/or after playing the first media item, the second electronic device **502-2** plays one or more additional media items having a predefined association with the first media item). The predefined association may be a common artist, music genre, or other shared characteristics (e.g., tempo, key, etc.).

In some implementations, when transitioning from playing one media item to playing another media item (e.g., the first electronic device **502-1** transitions from playing the first media item to playing the second media item), the first electronic device **502-1** and/or second electronic device **502-2** plays a transition effect (e.g., a gradual cross-fade, an audio gap, a sound effect, etc.).

In some implementations, playing **(516)** the second media item includes the first electronic device **502-1** commencing playback at a time marker of the second media item as specified in the first playback command (and/or playing **(518)** the first media item includes the second electronic device **502-2** commencing playback at a time marker of the first media item as specified in the second playback command). In some implementations, the time marker is a time specified by the corresponding contextual data.

The time marker may be the beginning of a corresponding media item. Alternatively, the time marker specifies a position within playback of the second media item (or the first media item, with respect to the second electronic device **502-2**) that corresponds to a time at which the first contextual data was transferred (e.g., when the second electronic device **502-2** receives the first contextual data). In some implementations, the time marker specifies a position within playback of the second media item (or the first media item, with respect to the second electronic device **502-2**) that corresponds to a time at which the second electronic device **502-2** ceases playback of the second media item (or a time at which the first electronic device **502-1** ceases playback of the first media item). In some implementations, the time marker corresponds to a time at which the second electronic device **502-2** sends **(510)** the second contextual data to the remote server system **503** (step **510**). In some implementations, the time marker corresponds to a time when the NFC channel is established.

Context switching may involve swapping graphics associated with media items (e.g., album-cover images associ-

ated with tracks). In some implementations, the first electronic device **502-1** displays a first graphic associated with the first media item while playing (**504**) the first media item (and/or the second electronic device **502-2** displays a second graphic associated with the second media item while playing (**505**) the second media item. The first electronic device **502-1** ceases to play the first media item after receiving the first playback command for the second media item (and/or the second electronic device **502-2** ceases to play the second media item after receiving the second playback command for the first media item). Concurrently with ceasing to play the first media item, the first electronic device **502-1** ceases to display the first graphic (and/or concurrently with ceasing to play the second media item, the second electronic device **502-2** ceases to display the second graphic). Furthermore, the first electronic device **502-1** displays the second graphic associated with the second media item while playing the second media item (and/or the second electronic device **502-2** displays the first graphic associated with the first media item while playing the first media item). An example is shown in FIGS. **4A** and **4E**, where FIG. **4A** illustrates GUIs displayed on the client devices **102** before, and FIG. **4E** illustrates GUIs displayed on the client devices **102** after, performing a process for media context switching.

The second electronic device **502-2** may sometimes receive contextual data at different times from multiple electronic devices, where media items corresponding to the received contextual data are queued for playback. Here, the second electronic device **502-2** may be a media presentation system **108**, such as a jukebox sound system that is accessible by multiple users. In these implementations, while playing a media item (e.g., the second media item, or the first media item, if the second playback command has already been received), the second electronic device **502-2** establishes a second NFC channel with a third electronic device (e.g., a client device **102**) while the third electronic device is playing a third media item. The second electronic device **502-2** receives third contextual data via the second NFC channel from the third electronic device, wherein third contextual data of the third electronic device corresponds to the third media item. After receiving the third contextual data, the second electronic device **502-2** receives a third playback command for the third media item. After receiving the third playback command for the third media item, the second electronic device **502-2** plays the third media item. In some implementations, the first NFC channel is established (**506**) with the first electronic device **502-1** (and then broken when the devices are separated) before establishing the second NFC channel with the third electronic device, and the second electronic device **502-2** plays the third media item after playing (**518**) the first media item. Thus, the second electronic device **502-2** manages a queue of media items for playback, and plays media items in the order in which contextual data is exchanged, or playback commands are received.

Although some of various drawings illustrate a number of logical stages in a particular order, stages which are not order dependent may be reordered and other stages may be combined or broken out. Furthermore, in some implementations, some stages may be performed in parallel and/or simultaneously with other stages. While some reordering or other groupings are specifically mentioned, others will be apparent to those of ordinary skill in the art, so the ordering and groupings presented herein are not an exhaustive list of alternatives. Moreover, it should be recognized that the stages could be implemented in hardware, firmware, software, or any combination thereof.

The foregoing description, for purpose of explanation, has been described with reference to specific implementations. However, the illustrative discussions above are not intended to be exhaustive or to limit the implementations to the precise forms disclosed. Many modifications and variations are possible in view of the above teachings. The implementations were chosen and described in order to best explain the principles and their practical applications, to thereby enable others skilled in the art to best utilize the implementations and various implementations with various modifications as are suited to the particular use contemplated.

What is claimed is:

**1.** A method, comprising:

at a first electronic device associated with a first user, the first electronic device having one or more processors and memory storing instructions for execution by the one or more processors:

while playing a first media item, establishing a wireless communication channel with a second electronic device, wherein the second electronic device is distinct from the first electronic device and associated with a second user distinct from the first user;

transferring, from the first electronic device, first contextual data of the first electronic device via the wireless communication channel, wherein the first contextual data indicates a first predefined sequence of media items that includes the first media item;

receiving, from the second electronic device, second contextual data of the second electronic device via the wireless communication channel, wherein the second contextual data indicates a second predefined sequence of media items that includes a second media item that is currently playing on the second electronic device;

receiving a playback command, at the first electronic device, for the second media item currently playing on the second electronic device; and

in response to receiving the playback command for the second media item, playing one or more media items from the second predefined sequence of media items and the second media item at the first electronic device without additional user input at the first electronic device.

**2.** The method of claim **1**, wherein the playback command is received from a remote server system, distinct from the first and second electronic devices, to which the first contextual data of the first electronic device and the second contextual data of the second electronic device are sent by the first electronic device.

**3.** The method of claim **1**, wherein the playback command is received from a remote server system, distinct from the first and second electronic devices, that previously provided to the first electronic device a command to play the first media item.

**4.** The method of claim **1**, wherein the playback command for the second media item currently playing on the second electronic device is received after the first contextual data is transferred to the second electronic device.

**5.** The method of claim **1**, further comprising swapping contextual data of respective media items playing at the first and second electronic devices, wherein the swapping includes:

receiving, from the second electronic device, the second contextual data of the second electronic device via the wireless communication channel;

transferring, from the first electronic device, the first contextual data corresponding to the first media item to the second electronic device;

receiving the playback command, at the first electronic device, for the second media item currently playing on the second electronic device; and

playing the second media item at the first electronic device without additional user input at the first electronic device.

6. The method of claim 1, wherein the playback command is received from the second electronic device.

7. The method of claim 1, wherein the second contextual data of the second electronic device specifies at least one of:

- a device identifier associated with the second electronic device; and
- a user identifier associated with a user of the second electronic device.

8. The method of claim 1, wherein:

- playing the second media item includes pausing the first media item; and
- the second electronic device is detected while the first media item is paused.

9. The method of claim 1, further comprising pausing the first media item in response to detecting the second electronic device in sufficient proximity to the first electronic device.

10. The method of claim 1, wherein receiving the second contextual data of the second electronic device is performed in response to establishing the wireless communication channel.

11. The method of claim 1, further comprising ceasing to play the first media item in response to receiving the second contextual data of the second electronic device.

12. The method of claim 1, further comprising ceasing to play the first media item after receiving the playback command for the second media item.

13. The method of claim 12, wherein the second media item is played after ceasing to play the first media item.

14. The method of claim 13, wherein ceasing to play the first media item corresponds to reaching an end of the first media item.

15. The method of claim 12, further comprising, upon ceasing to play the first media item and before playing the second media item:

- playing one or more additional media items distinct from the first and second media items.

16. The method of claim 1, further comprising, after playing the second media item, playing one or more additional media items having a predefined association with the second media item.

17. The method of claim 1, wherein playing the second media item comprises commencing playback at a time marker of the second media item as specified in the playback command.

18. The method of claim 17, wherein the time marker specifies a position within playback of the second media item that corresponds to a time at which the second contextual data of the second electronic device was received.

19. A first electronic device associated with a first user, comprising:

- one or more processors; and
- memory storing one or more programs for execution by the one or more processors, the one or more programs including instructions for:
  - while playing a first media item, establishing a wireless communication channel with a second electronic device, wherein the second electronic device is distinct from the first electronic device and associated with a second user distinct from the first user;
  - transferring, from the first electronic device, first contextual data of the first electronic device via the wireless communication channel, wherein the first contextual data indicates a first predefined sequence of media items that includes the first media item;
  - receiving, from the second electronic device, second contextual data of the second electronic device via the wireless communication channel, wherein the second contextual data indicates a second predefined sequence of media items that includes a second media item that is currently playing on the second electronic device;
  - receiving a playback command, at the first electronic device, for the second media item currently playing on the second electronic device; and
  - in response to receiving the playback command for the second media item, playing one or more media items from the second predefined sequence of media items and the second media item at the first electronic device without additional user input at the first electronic device.

20. A non-transitory computer-readable storage medium storing one or more programs for execution by one or more processors of a first electronic device associated with a first user, the one or more programs including instructions for:

- while playing a first media item, establishing a wireless communication channel with a second electronic device, wherein the second electronic device is distinct from the first electronic device and associated with a second user distinct from the first user;
- transferring, from the first electronic device, first contextual data of the first electronic device via the wireless communication channel, wherein the first contextual data indicates a first predefined sequence of media items that includes the first media item;
- receiving, from the second electronic device, second contextual data of the second electronic device via the wireless communication channel, wherein the second contextual data indicates a second predefined sequence of media items that includes a second media item that is currently playing on the second electronic device;
- receiving a playback command, at the first electronic device, for the second media item currently playing on the second electronic device; and
- in response to receiving the playback command for the second media item, playing one or more media items from the second predefined sequence of media items and the second media item at the first electronic device without additional user input at the first electronic device.

21. The method of claim 1, wherein the one or more media items from the second predefined sequence of media items are played at the first electronic device after playback of the second media item.