




(22) Date de dépôt/Filing Date: 1999/09/30
(41) Mise à la disp. pub./Open to Public Insp.: 2001/04/12
(45) Date de délivrance/Issue Date: 2013/04/23
(62) Demande originale/Original Application: 2 386 531

(51) Cl.Int./Int.Cl. *C10L 5/44* (2006.01),
C10L 11/04 (2006.01)
(72) Inventeurs/Inventors:
PETERSON, GREGORY J., US;
FLINT, GARY M., US
(73) Propriétaires/Owners:
PETERSON, GREGORY J., US;
FLINT, GARY M., US
(74) Agent: MARKS & CLERK

(54) Titre : APPAREIL PRODUISANT DES BUCHES ARTIFICIELLES ET DES CUBES ALLUME-FEU, PROCEDE ET PRODUITS OBTENUS DE LA SORTE
(54) Title: ARTIFICIAL FIRELOG AND FIRESTARTER CHIP PRODUCING APPARATUS AND METHOD AND PRODUCTS PRODUCED THEREFROM



(57) Abrégé/Abstract:

An artificial firelog and firestarter chip producing apparatus comprising a cutting assembly, a compression conveyor auger assembly and a die. The apparatus converts standard waxed corrugated cardboard boxes into artificial firelogs by first slicing

(57) **Abrégé(suite)/Abstract(continued):**

cardboard sheets into cardboard strips, then chopping the cardboard strips into cardboard segments in the cutting assembly. The cardboard segments are horizontally disposed between the rifling and compressed in the compression conveyor auger assembly and extruded in the die to form generally horizontally disposed, circular, longitudinally-shaped sections of a firelog. Firestarter chips are fabricated by the cutting assembly, which slices waxed cardboard sheets in conjunction with paper sheets into waxed cardboard and paper strips, then chopping the waxed cardboard strips into waxed cardboard segments and the paper strips into paper segments and waxed cardboard segments mix.

Abstract

An artificial firelog and firestarter chip producing apparatus comprising a cutting assembly, a compression conveyor auger assembly and a die. The apparatus converts standard waxed corrugated cardboard boxes into artificial firelogs by first slicing cardboard sheets into cardboard strips, then chopping the cardboard strips into cardboard segments in the cutting assembly. The cardboard segments are horizontally disposed between the rifling and compressed in the compression conveyor auger assembly and extruded in the die to form generally horizontally disposed, circular, longitudinally-shaped sections of a firelog. Firestarter chips are fabricated by the cutting assembly, which slices waxed cardboard sheets in conjunction with paper sheets into waxed cardboard and paper strips, then chopping the waxed cardboard strips into waxed cardboard segments and the paper strips into paper segments and waxed cardboard segments mix.

ARTIFICIAL FIRELOG AND FIRESTARTER CHIP PRODUCING APPARATUS AND METHOD AND PRODUCTS PRODUCED THEREFROM

This is a divisional application of Canadian Patent Application Serial No.
5 2,386,531 filed on September 30, 1999.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention pertains generally to a fuel manufacturing apparatus,
and more particularly to an apparatus and method for converting flammable
10 material, such as waxed corrugated cardboard, into compact artificial firelogs or
firestarter chips.

It should be understood that the expression the invention and the like
encompasses the subject-matter of both the parent and the divisional applications.

2. Description of the Background Art

15 The popularity of log burning fireplaces as an amenity and as a
supplemental source of heat continues to grow. With cutting restrictions on
Government land, as well as the closing of many wood processing plants, wood
logs can be difficult and expensive to obtain. As a result, artificial firelogs, which
generally burn cleaner and light faster, have been gaining in popularity.

20 On the other hand, boxes and containers made from cardboard are widely
used in an almost infinite variety of applications such as packaging produce,
shipping and storage of goods and the like. As such, there is an abundant supply
of discarded cardboard boxes readily available for recycling. It has been
recognized that discarded cardboard boxes form a potential fuel material, and the

WO 01/24996

PCT/US99/23007

general concept of converting used or discarded cardboard boxes into burnable firelogs has been applied with some level of success.

Machines have been previously developed to convert such cardboard boxes into compact burnable firelogs. Such machines include a feed system, such as a hammermill for receiving a sheet of cardboard, a cutting mechanism for slicing the cardboard sheet into strips and then cutting the strips into chips, and a compacting/compressing punch press assembly for shaping the chips into compact firelog structures which can be burned in a fireplace. Binders, such as glue, are used to hold the chips together after compression. Additionally, the finished firelogs can be dipped into wax to create an outer wax coating to enhance their burn capability.

These existing machines, however, are designed to cut and shape plain cardboard boxes; that is, cardboard without a wax or wax-like coating thereon. Existing machines are not made to cut and shape waxed corrugated cardboard. Furthermore, the design of these machines does not take into account that, by using glue as a binder to hold regular unwaxed cardboard together into a compressed log, the corrugations are destroyed when the strips or chips are smashed and glued together. Quite significantly, we have found that regular and waxed corrugated cardboard has a memory and, while the corrugated segments stick together they are flattened and compressed, if glue is not used as a binder, upon heating the corrugated segments expand back into an open structure through which airflow is increased which leads to more efficient burning. Current fire log production machines are not able to make use of this memory property of corrugated cardboard.

It will be appreciated that resource conservation continues to be important as our population increases and our level of resources diminish. Therefore corrugated cardboard boxes, as is the case with many other materials, are generally recycled to reduce waste. Wax-coated corrugated cardboard boxes, however, are generally non-recyclable. Wax-coated corrugated cardboard boxes are commonly coated with a paraffin-based wax which is very expensive to separate from the cardboard within a normal re-pulping systems. Consequently, used wax-coated corrugated cardboard boxes (WOCC) are generally discarded in landfills. In view of present interests regarding conservation of resources and

WO 01/24996

PCT/US99/23007

environmental consciousness, the ability to reuse such discarded material in a form of fuel would serve to reduce the demand for other types of fuels, such as oil, gas or coal, thus further conserving natural resources and preserving the environment.

5 Additionally, current log manufacturing machines destroy the corrugation within the corrugated cardboard which reduces the flow and permeation of wax and oxygen throughout the firelog which results in an incomplete and inefficient burning of the firelog.

 Moreover, current log manufacturing machines produce firelogs with "cold
10 joints" at the intervals between punches or presses. These cold joints are also formed when the chips are compressed vertically within the structure of the log rather than disposed horizontally around the log in a circular fashion. Cold joints are weak links within the firelog that easily break up into multiple sections when any shear or tensile force is exerted upon them. The punch or press machine
15 creates vertical arrangements of the chips within the firelog. When burned, the vertical chip arrangement causes chips to burn from the edge rather than from the side. Therefore chips of corrugated cardboard, so pressed into a log, are not allowed to open and expand with heat because of the vertical arrangement and the glued corrugations.

20 Accordingly, there exists a need for an artificial firelog manufacturing apparatus that provides the capability to recycle pre-waxed corrugated cardboard boxes into firelogs that are more structurally rigid and that burn more efficiently, using horizontally disposed segments, over that which is presently known in the art. The present invention satisfies those needs, as well as others, and
25 overcomes the deficiencies found in currently known artificial firelog producing machines.

BRIEF SUMMARY OF THE INVENTION

 The present invention is an apparatus which converts standard wax coated corrugated cardboard sheets into artificial firelogs, or firestarter chips. The
30 apparatus can therefore create firelogs from the wax-coated corrugated material that would otherwise be disposed of within landfills. Recycling this wax-coated material by means of this apparatus can create the equivalent of 600 million, 5-pound firelogs annually.

WO 01/24996

PCT/US99/23007

The invention produces artificial firelogs or firestarter chips, by first slicing waxed corrugated cardboard sheets into strips, and then cutting the strips into segments. Each cut segment retains its original corrugated structure and wax content. The wax-coated corrugated cardboard segments are then compressed and shaped longitudinally into firelogs which are generally cylindrical. The longitudinal orientation of the segments, whose corrugated structure has been retained, coupled with the memory effect exhibited by the compressed corrugated cardboard, results in a more efficient burn as the segments open up to increase airflow. Furthermore, by adding wax, or wax-like materials, any form of new, remnant, or recycled unwaxed corrugated cardboard can be processed into artificial firelogs and firestarters.

By way of example and not of limitation, the artificial firelog producing apparatus of the present invention generally comprises a cardboard strip cutting mechanism, a segment cutting mechanism, and a conveyor compression mechanism. The strip cutting mechanism employs a plurality of upper circular blades with teeth juxtaposed axially, and a plurality of lower circular blades with teeth juxtaposed axially such that the cutting edge of the upper circular blades overlap the cutting edge of the lower circular blades whose interaction cuts the waxed corrugated cardboard sheets into waxed corrugated cardboard strips. A segment cutting mechanism in the form of a cutting reel is disposed adjacent to the lower circular blade which then cuts the strips of waxed corrugated cardboard into segments. A conveyor compression mechanism in the form of an auger is positioned beneath the cutting reel and terminates in a log forming die for conveying and compressing the corrugated segments into a log shaped extrusion.

The upper and lower circular blades in the strip cutting mechanism effectively meter and slice multiple waxed corrugated cardboard sheets fed therein into waxed corrugated cardboard strips. The waxed corrugated cardboard strips are then fed through the cutting reel which cuts the waxed corrugated cardboard strips into waxed corrugated cardboard segments. The waxed corrugated cardboard segments are then fed into the conveyor compression auger for transport and compression into a log die. As the conveyor compression auger transports the waxed corrugated cardboard segments, the segments are horizontally disposed around the housing between rifling in a circular interlocking

WO 01/24996

PCT/US99/23007

manner and are gradually compressed and forced into the log die. The log die compresses and shapes the waxed corrugated cardboard segments into artificial firelogs. Alternately the exit portion of the housing may be configured to perform the functions of the log die; however this precludes changing log forms without
5 major changes to the apparatus. Firestarter chips are produced by bypassing the auger and log die.

Use of a conveyor compression auger results is a significant improvement over punch press-type machines, because the conveyor compression auger horizontally (based on the longitudinal axis of the firelog) flattens the waxed
10 corrugated cardboard segments, as opposed to vertically flattening or crushing the cardboard segments which, as a result, form cold joints in logs produced from these piston style systems. The conveyor compression auger with its internal rifling also eliminates cold joints in the firelog by spinning the flattened chips horizontally and interlocking them throughout the log, thus eliminating the
15 likelihood of the firelog breaking into segments on the fireplace grate. The horizontal (longitudinal) orientation also allows the segments to expand and burn off the exterior of the log, layer after flattened layer. As each flattened corrugated segment is being consumed by the flames, it expands from the memory effect in the corrugations which thereby allows the air to flow through the segment for a
20 more efficient burn. Once a segment has been consumed, it falls away as the next layered segment starts burning. This burning sequence continues until the entire log has been consumed. Therefore the inventive apparatus retains the corrugation structure and creates a longitudinal segment orientation to provide for the manufacture of firelogs which do not easily break and which burn in a similar
25 manner to genuine wood bark.

An object of the invention is to provide an apparatus capable of processing pre-waxed corrugated cardboard to produce artificial firelogs.

Another object of the invention is to provide an apparatus capable of producing artificial firelogs more efficiently than firelog producing machines
30 presently known or available.

Another object of the invention is to provide an apparatus capable of reliably feeding, slicing and cutting waxed corrugated cardboard sheets and paper sheets into waxed corrugated cardboard segments and paper segments mix.

Another object of the invention is to provide an apparatus capable of reliably slicing and cutting waxed corrugated cardboard sheets and waxed corrugated cardboard segments without the need of removing the wax or with the result of destroying the corrugations within.

5 Another object of the invention is to provide an apparatus capable of producing artificial firelogs without the necessity of adding glue or wax.

Another object of the invention is to provide an apparatus that produces firelogs without cold joints.

10 Another object of the invention is to provide an apparatus that produces a firelog with horizontally interlocking arranged segments.

Another object of the invention is to provide an apparatus wherein waxed corrugated cardboard segments are transported and compressed into an artificial firelog in which the segments are spun horizontally and disposed radially in an interlocking manner around the outside of the firelog, so that each sequential
15 flattened layer of segments expands open when burning.

Another object of the invention is to provide an apparatus which is capable of producing firestarter chips.

Another object of the invention is to provide an apparatus which is capable of producing firestarter blends containing a variety of different materials.

20 Another object of the invention is to provide an apparatus capable of producing a log having a outer covering which can be used as a post.

Further objects and advantages of the invention will be brought out in the following portions of the specification, wherein the detailed description is for the purpose of fully disclosing preferred embodiments of the invention without placing
25 limitations thereon.

In one aspect, the invention provides a method for manufacturing firestarter chips, the method comprising the steps of:

30 (a) providing a waxed corrugated cardboard cutting assembly having a plurality of lower circular blades, a plurality of upper circular blades, said plurality of lower and upper circular blades configured to slice the cardboard sheet placed therebetween into cardboard strips, a cutting reel positioned to receive the

cardboard strips, said cutting reel capable of cutting the cardboard strips into cardboard segments;

(b) slicing a waxed corrugated cardboard sheet into cardboard strips;

(c) slicing at least one sheet of paper into paper strips simultaneously with said
5 slicing of said waxed corrugated cardboard sheet;

(d) chopping said cardboard strips and said paper strips into waxed corrugated cardboard segments and paper segments, respectively; and

(e) forming a firestarter chip from said cardboard and paper segments by adhering said segments to each other.

10 In one aspect, the invention provides an apparatus for cutting, segmenting, compressing and extruding waxed corrugated cardboard sheets into a firelog having radially interlocking segments, the apparatus comprising:

a housing having an inlet end and an outlet end;

a plurality of lower circular blades juxtaposed along a first common axis, said
15 plurality of lower circular blades each including a first cutting edge;

a plurality of upper circular blades juxtaposed along a second common axis, said plurality of upper circular blades each including a second cutting edge;

a circular blade axial adjustment mechanism wherein the axial position of at
least one axis of said circular blades can be positioned in relation to the other
20 axis of circular blades to thereby provide control of the juxtaposition forces between upper and lower circular blades;

said plurality of upper and lower circular blades configured to slice at least one waxed corrugated cardboard sheet placed generally into the inlet end of said housing into cardboard strips;

25 wherein said first cutting edge overlaps said second cutting edge, and wherein said cutting blades are configured so that interaction between said upper cutting blades and said lower cutting blades proximal the location of cutting edge overlap causes corrugated cardboard being sliceably passed therethrough to exhibit cut edges containing significant fraying;

30 a cutting mechanism configured to cut the cardboard strips into cardboard segments;

a compression conveyor auger having shaft carrying a helical blade with a plurality of flights; and

a die, wherein said auger is configured to convey said cardboard segments into
35 said die wherein the segments are compressed into a firelog.

In one aspect, the invention provides a firelog manufacturing apparatus, wherein waxed corrugated cardboard sheets are segmented and compressed as radially interlocking segments within a manufactured composite firelog extrusion, the apparatus comprising:

a housing for the apparatus which includes an inlet end and an outlet end;

a plurality of lower circular blades juxtaposed along a first common axis, said plurality of lower circular blades each including a first cutting edge;

a plurality of upper circular blades juxtaposed along a second common axis;

10 said plurality of upper circular blades each including a second cutting edge; said plurality of lower and upper circular blades configured to slice at least one waxed corrugated cardboard sheet placed therebetween and generally into the input end of said housing, into cardboard strips, whereby said first common axis is approximately parallel to said second common axis, and said first cutting edge
15 overlaps said second cutting edge;

a cutting mechanism positioned to receive the waxed corrugated cardboard strips, said cutting mechanism configured to cut the waxed corrugated cardboard strips into waxed corrugated cardboard segments;

a conveyor auger housing which includes an inlet end and an outlet end,
20 wherein said outlet end is tapered, said conveyor auger housing is held in a fixed relation to said apparatus housing;

an opening on said conveyor auger housing, wherethrough waxed cardboard segments enter said conveyor auger housing;

a compression conveyor screw rotatably disposed within said conveyor auger
25 housing, said compression conveyor screw including a helical blade extending toward said outlet end of said conveyor auger housing, said helical blade including a plurality of flights;

a log extrusion orifice configured on the terminating end of said outlet end of said conveyor auger housing, wherethrough composite material is extruded, as a
30 result of the rotation of the compression conveyor screw, into a predetermined cross-sectional shape; and

means for segmenting the composite firelog extrusion into individual log sections;

wherein said cutting blades are configured so that interaction between said
35 upper cutting blades and said lower cutting blades proximal the location of

cutting edge overlap causes corrugated cardboard being sliceably passed therethrough to exhibit cut edges containing significant fraying.

In one aspect, the invention provides a method for manufacturing an artificial firelog, the method comprising:

- 5 converting waxed corrugated cardboard sheets into segments;
- compressing said waxed corrugated cardboard segments to a ratio approximately between 5:1 and 8:1;
- extruding said compressed waxed corrugated cardboard segments into a continuous log structure; and
- 10 cutting said continuous log structure into individual firelog; wherein said segments are compressed circumferentially in relation to a central longitudinal axis of the firelog;
- wherein said segments have surfaces that are positioned radially outward in relation to the central longitudinal axis of the first firelog.

15 In one aspect, the invention provides an artificial firelog material, comprising:

- a plurality of waxed cardboard segments with exterior surfaces and a corrugated interior compressed circumferentially in relation to a central longitudinal axis of the firelog; and
- 20 wherein the exterior surfaces of at least some of said segments are substantially oriented radially outward in relation to the central longitudinal axis of the firelog.

In one aspect, the invention provides an artificial firelog material, comprising:

- 25 a plurality of waxed corrugated cardboard segments;
- wherein a majority of said segments have faces that are compressed circumferentially in relation to a central longitudinal axis of the firelog;
- wherein a majority of said segments have faces that are positioned radially outward in relation to the central longitudinal axis of the firelog; and
- 30 wherein said segments are adhered together in an overlapping configuration.

In one aspect, the invention provides an artificial firelog material, comprising:

- a plurality of waxed corrugated cardboard segments;
- wherein a majority of said segments have faces that are compressed
- 35 circumferentially in relation to a central longitudinal axis of the firelog;

wherein a majority of said segments have faces that are positioned radially outward in relation to the central longitudinal axis of the firelog;
 wherein said segments are adhered together in an overlapping configuration;
 5 wherein said segments open or expand with heat when burned; and
 wherein corrugations in said segments channel oxygen throughout the segments.

In another aspect, the invention provides a compression conveyor auger apparatus, for transporting and compressing waxed corrugated cardboard
 10 segments, the apparatus comprising:

- (a) a housing, said housing including an inlet end and an outlet end, wherein said outlet end is tapered;
- (b) an opening on said housing, said opening disposed adjacent said inlet end of said housing; and
- 15 (c) a compression conveyor screw rotatably disposed within said housing, said compression conveyor screw including a helical blade extending between said inlet end and said outlet end of said housing, said helical blade including a plurality of flights; wherein said housing and said compression conveyor screw are configured to orient and align the cardboard segments in a circumferentially-
 20 disposed manner about a periphery of said compression conveyor screw and to move said cardboard segments forward while said cardboard segments are being disposed horizontally.

In another aspect, the invention provides an artificial firelog material, comprising:

- 25 a plurality of waxed corrugated cardboard segments;
 wherein at least a portion of said segments have faces that are compressed circumferentially in relation to a central longitudinal axis of the firelog; and
 wherein at least a portion of said segments have faces that are positioned radially outward in relation to the central longitudinal axis of the firelog.

30 In one aspect, the invention provides an artificial firelog material, comprising:

a plurality of waxed cardboard segments with exterior surfaces and a corrugated interior compressed circumferentially in relation to a central longitudinal axis of the firelog;

wherein the exterior surfaces of at least some of said segments are substantially oriented radially outward in relation to the central longitudinal axis of the firelog; and

wherein said segments are adhered together in an overlapping configuration.

5 In one aspect, the invention provides an artificial firelog material, comprising:

a plurality of waxed corrugated cardboard segments;

wherein at least a portion of said segments have faces that are compressed circumferentially in relation to a central longitudinal axis of the firelog;

10 wherein at least a portion of said segments have faces that are positioned radially outward in relation to the central longitudinal axis of the firelog;

wherein said segments are adhered together in an overlapping configuration;

wherein said segments open or expand with heat when burned; and

15 wherein corrugations in said segments channel oxygen throughout the segments.

 In one aspect, the invention provides an artificial firelog material, comprising:

20 a plurality of waxed corrugated cardboard segments with exterior surfaces, said segments positioned in a longitudinally shaped structure with planar rectangular sides;

wherein said structure has a square cross-section and a longitudinal axis;

wherein said segments are compressed circumferentially around the longitudinal axis of said structure; and

25 wherein the exterior surfaces of at least some of said segments are oriented outwardly toward the planar rectangular sides and corners of said longitudinally shaped structure.

 In one aspect, the invention provides an artificial firelog material, comprising:

30 a plurality of waxed corrugated cardboard segments, said segments positioned in a longitudinally shaped structure;

wherein said structure has a square circumference and a longitudinal axis;

wherein a majority of said segments have faces that are compressed circumferentially around the longitudinal axis of said structure; and

wherein said corners of said square circumference are radiused.

35 In one aspect, the invention provides an artificial firelog material, comprising:

a plurality of waxed corrugated cardboard segments, said segments positioned in a longitudinally shaped structure;

wherein said structure has a square circumference and a longitudinal axis;

wherein a portion of said segments have faces that are compressed

5 circumferentially around the longitudinal axis of said structure;

wherein said segments are adhered together in an overlapping configuration; and

wherein said segments are densely compacted together in an extrusion process.

10 In one aspect, the invention provides a method for manufacturing a firelog, the method comprising:

providing a waxed corrugated cardboard cutting assembly, said cutting assembly comprising:

a plurality of lower circular blades;

15 a plurality of upper circular blades, said plurality of lower and upper circular blades configured to slice the cardboard sheet placed therebetween into cardboard strips, and

a cutting reel positioned to receive the cardboard strips, said cutting reel capable of cutting the cardboard strips into cardboard segments;

20 slicing a waxed corrugated cardboard sheet into cardboard strips with said cutting assembly;

chopping said cardboard strips into segments using said cutting assembly; and forming a firelog from said cardboard by adhering said segments to each other.

In another aspect, the invention provides a method for manufacturing a firelog, the method comprising:

25 providing a waxed corrugated cardboard cutting assembly, said cutting assembly comprising:

a plurality of lower circular blades;

30 a plurality of upper circular blades, said plurality of lower and upper circular blades configured to slice the cardboard sheet placed therebetween into cardboard strips, and

a cutting reel positioned to receive the cardboard strips, said cutting reel capable of cutting the cardboard strips into cardboard segments;

slicing a waxed corrugated cardboard sheet into cardboard strips with said cutting assembly;

chopping said cardboard strips into segments using said cutting assembly;
and

compressing said segments into each other forming a firelog.

In another aspect, the invention provides a method for manufacturing a

5 firelog, the method comprising the steps of:

providing a waxed corrugated cardboard cutting assembly, said cutting assembly
comprising:

a plurality of lower circular blades;

10 a plurality of upper circular blades, said plurality of lower and upper circular
blades configured to slice the cardboard sheet placed therebetween into
cardboard strips; and

a cutting reel positioned to receive the cardboard strips, said cutting reel
capable of cutting the cardboard strips into cardboard segments;

15 slicing a waxed corrugated cardboard sheet into cardboard strips with said
cutting assembly;

chopping said cardboard strips into segments using said cutting assembly;
making a longitudinally shape structure with said segments;

compressing said segments circumferentially around a central longitudinal
axis of said longitudinally shaped structure; and

20 compressing said segments into each other forming a firelog.

Aspects of the present invention are provided by the following clauses.

Clauses

25 1. An apparatus for cutting, segmenting, compressing and extruding waxed
corrugated cardboard sheets into a firelog having radially interlocking segments,
comprising:

(a) a housing having an inlet end and an outlet end;

(b) a plurality of circular blades configured to slice at least one waxed
corrugated cardboard sheet placed generally into the inlet end of said housing
into cardboard strips;

(c) a cutting reel configured to cut the cardboard strips into cardboard
segments;

(d) a compression conveyor auger having shaft carrying a helical blade with a plurality of flights; and

(e) a die, wherein said auger is configured to convey said cardboard segments into said die wherein the segments are compressed into a firelog.

5

2. An apparatus as recited in clause 1, further comprising at least one blade spacer positioned between adjacent circular blades.

10 3. An apparatus as recited in clause 2, wherein said blade spacers are configured with recessed centers to minimize the contact with an irregular inner surface of said circular blades to maintain a desired clearance between said blades.

15 4. An apparatus as recited in clause 1, wherein said plurality of circular blades comprises:

(a) a plurality of lower circular blades juxtaposed along a first common axis, said plurality of lower circular blades each including a first cutting edge;

(b) a plurality of upper circular blades juxtaposed along a second common axis, said plurality of upper circular blades each including a second cutting edge; and

20 (c) a circular blade axial adjustment mechanism wherein the axial position of at least one axis of said circular blades can be positioned in relation to the other axis of circular blades to thereby provide control of the juxtaposition forces between upper and lower circular blades.

25 5. An apparatus as recited in clause 4, wherein said first common axis and said second common axis are along a first shaft and a second shaft, respectively, whereby rotation of said first shaft causes rotation of said lower circular blades and rotation of said second shaft causes rotation of said upper circular blades.

30

6. An apparatus as recited in clause 5, further comprising means for rotating said first and second shafts.

7. An apparatus as recited in clause 6, wherein said rotating means comprises a spur gear.

8. An apparatus as recited in clause 1, wherein said cutting blades are
5 configured with teeth which are annularly disposed on the perimeter of said cutting blades.

9. An apparatus as recited in clause 8, wherein said teeth are non-fluted.

10 10. An apparatus as recited in clause 1, wherein said cutting blades are hollow ground.

11. An apparatus as recited in clause 4, wherein said first cutting edge overlaps said second cutting edge, and wherein said cutting blades are
15 configured so that interaction between said upper cutting blades and said lower cutting blades proximal the location of cutting edge overlap causes corrugated cardboard being sliceably passed therethrough to exhibit cut edges containing significant fraying.

20 12. An apparatus as recited in clause 11, wherein said significant fraying is created by the rotating interaction of two hollow ground, non-fluted cutting blades.

13. An apparatus as recited in clause 8, wherein said first cutting edge
25 overlaps said second cutting edge, and wherein said overlap of first cutting edge and second cutting edge of said teeth provide a metered input feed of waxed corrugated cardboard as the teeth grip the waxed corrugated cardboard and the movement of the cutting blades pulls the waxed corrugated cardboard therethrough at a predetermined rate proportional to the rotational speed of the
30 cutters.

14. An apparatus as recited in clause 1, further comprising at least one guide plate attached to the housing, said guide plate having slots configured to allow a

generally arcuate portion of said circular blades to pass therethrough, wherein said guide plates direct, or guide, the insertion of waxed corrugated cardboard into the proper feed direction for slicing.

5 15. An apparatus as recited in clause 1, wherein a vertical guide plate is attached to the housing rearward of said circular blades in relation to the direction of cardboard feed, and wherein a lower portion of said vertical guide is aligned proximal to an upper guide plate on a lower end and extends upwardly to a height which provides for separation of waxed corrugated cardboard strips prior
10 to contact with said cutting reel and additionally prevents reverse flow of material back into said circular blades.

16. An apparatus as recited in clause 1, wherein said cutting reel is mounted at a fifteen degree angle above the feed path of said waxed corrugated
15 cardboard strips into said cutting reel.

17. An apparatus as recited in clause 1, further comprising a geared drive mechanism for rotating said cutting reel.

20 18. An apparatus as recited in clause 17, wherein said geared drive includes a set of spur gears connected to said cutting reel through which power is applied to rotate said cutting reel.

19. An apparatus as recited in clause 1, wherein said cutting reel comprises:

25 (a) a first and a second end plate;

(b) an axial shaft positioned perpendicularly between said first and said second end plate; and

(c) a plurality of longitudinal cutting blades disposed around said axial shaft, paddle-wheel style, which are retained generally parallel to said axial shaft and
30 attached to said first and said second end plate.

20. An apparatus as recited in clause 19, wherein said cutting blades in said cutting reel include a helical twist extending between said first and said second end plate.

5 21. An apparatus as recited in clause 19, wherein a bed bar knife is attached to said housing anterior of said circular blades in relation to the direction of cardboard material feed, and wherein said bed bar knife is aligned proximal to lower guide plate positioned such that an edge of said bed bar knife is brought into material shearing proximity with said longitudinal cutting blades of said
10 cutting reel so that the strips of waxed corrugated cardboard material passing rearwardly of said circular cutting blades are placed in shearing contact between the bed bar knife and reel for the production of segments thereof.

22. An apparatus as recited in clause 21, wherein a bed plate is configured for
15 retention of said bed bar knife to allow interchangeable replacement of bed bar knives, wherein said bed plate is attached to said housing and retains said bed bar knife using at least one fastener in a position which provides shearing of the waxed corrugated cardboard strips into waxed corrugated cardboard segments.

20 23. An apparatus as recited in clause 22, wherein said bed bar knife is retained by said bed plate with non-adjustable fasteners.

24. An apparatus as recited in clause 22, wherein said bed bar knife is retained by at least one fastener which provides longitudinal adjustment of the
25 bed bar knife in relation to the bed plate.

25. An apparatus as recited in clause 24, wherein said fastener comprises a turnbuckle.

30 26. An apparatus as recited in clause 1, further comprising a conveyor auger housing, said conveyor auger housing including rifling to aid the control of radial disposition and interlocking alignment of the waxed cardboard segments as extruded into the artificial firelog.

27. An apparatus as recited in clause 1, wherein the cardboard segments are compressed to a ratio between approximately 5:1 and approximately 8:1.

5 28. An apparatus as recited in clause 1, further comprising means for rotating said compression conveyor auger.

29. An apparatus as recited in clause 28, wherein said rotating means comprises a spur gear.

10

30. An apparatus as recited in clause 1, wherein said helical blade is tapered.

31. An apparatus as recited in clause 1, wherein said flights of said helical blade decrease in length toward said housing.

15

32. An apparatus as recited in clause 1, wherein the side profile of said helical blade becomes increasingly cupped towards said outlet end of said housing.

33. An apparatus as recited in clause 1, wherein said helical blade is
20 configured with a buildup of weld material of a predetermined shape at the junction of said helical blade and said auger shaft, wherein said buildup of weld material provides a final pushing thrust of said segments into said die.

34. An apparatus as recited in clause 1, wherein said log die sets the cross-
25 sectional shape of an extruded firelog.

35. An apparatus as recited in clause 34, wherein said log die includes a compression zone.

30 36. An apparatus as recited in clause 1, wherein said log die includes at least one longitudinal surface groove which produces logs with protruding ridges.

37. An artificial firelog manufacturing apparatus, comprising:

- (a) an enclosure;
- (b) means for converting waxed corrugated cardboard into waxed corrugated cardboard segments, said converting means located within said enclosure;
- (c) a housing within said enclosure, said housing including an inlet end and an outlet end, wherein said outlet end is tapered;
- (d) an opening on said housing, said opening disposed adjacent said inlet end of said housing; and
- (e) a compression conveyor screw rotatably disposed within said housing, said conveyor screw including a helical blade extending between said inlet end and said outlet end of said housing, said helical blade including a plurality of flights.

38. An apparatus as recited in clause 37, wherein the diameter of said helical blade tapers towards said outlet end of said housing.

39. An apparatus as recited in clause 38, wherein said housing has a length greater than seventeen inches and wherein the tapering of said helical blade occurs approximately within approximately the final seventeen inches of the housing toward said outlet end.

40. An apparatus as recited in clause 37, wherein said flights have a length that diminishes toward said outlet end of said housing.

41. An apparatus as recited in clause 37, wherein said helical blade is cupped and canted forward toward said outlet end of the last two flights.

42. An apparatus as recited in clause 37, wherein the attachment area of the last helical flight of said helical blade with said shaft includes a fillet between said shaft and said helical blade which provides thrust, or final pushing, of said segments into the compression die.

43. An apparatus as recited in clause 42, wherein said fillet is formed from weld material.

44. An apparatus as recited in clause 37, further comprising a hopper disposed within said enclosure, said hopper in communication with said opening of said housing and said waxed corrugated cardboard sheet converting means.

5 45. An apparatus as recited in clause 37, wherein said waxed corrugated cardboard converting means comprises:

(a) a plurality of lower circular blades juxtaposed along a first common axis, said plurality of lower circular blades each including a first cutting edge;

10 (b) a plurality of upper circular blades juxtaposed along a second common axis, said plurality of upper circular blades each including a second cutting edge;

(c) said plurality of lower and upper circular blades configured to slice the waxed corrugated cardboard placed therebetween into waxed corrugated cardboard strips, whereby said first common axis is parallel to said second common axis, and said first cutting edge overlaps said second cutting edge; and

15 (d) a cutting reel positioned to receive the waxed corrugated cardboard strips, said cutting reel capable of chopping the waxed corrugated cardboard strips into waxed corrugated cardboard segments.

20 46. An apparatus as recited in clause 45, where each of said cutting edges of said lower circular blades and said upper circular blades comprises a plurality of teeth.

47. An apparatus as recited in clause 46, wherein said teeth are non-fluted.

25 48. An apparatus as recited in clause 45, wherein a plurality of blade spacers are interleaved between said plurality of lower and upper circular blades such that the spacing between cutting blades, and thereby the width of the waxed corrugated cardboard slices, is set by the thickness of the spacers used.

30 49. An apparatus as recited in clause 48, wherein said blade spacers are configured with recessed centers to minimize the contact with the irregular inner surface of the circular blades to maintain proper clearances between blades.

50. An apparatus as recited in clause 45, wherein an upper guide plate and lower guide plate are positioned in relation to the upper and lower circular blades, respectively, and adjusted so as to direct waxed corrugated cardboard into said apparatus for proper slicing by the combination of upper and lower
5 circular blades.

51. A firelog manufacturing apparatus, wherein waxed corrugated cardboard sheets are segmented and compressed as radially interlocking segments within a manufactured composite firelog extrusion, comprising:

- 10 (a) a housing for the apparatus which includes an inlet end and an outlet end;
- (b) a plurality of lower circular blades juxtaposed along a first common axis, said plurality of lower circular blades each including a first cutting edge;
- (c) a plurality of upper circular blades juxtaposed along a second common axis; said plurality of upper circular blades each including a second cutting edge;
- 15 (d) said plurality of lower and upper circular blades configured to slice at least one waxed corrugated cardboard sheet placed therebetween and generally into the input end of said housing, into cardboard strips, whereby said first common axis is approximately parallel to said second common axis, and said first cutting edge overlaps said second cutting edge;
- 20 (e) a cutting reel positioned to receive the waxed corrugated cardboard strips, said cutting reel capable of cutting the waxed corrugated cardboard strips into waxed corrugated cardboard segments;
- (f) a conveyor auger housing which includes an inlet end and an outlet end, wherein said outlet end is tapered, said conveyor auger housing is held in a fixed
25 relation to said apparatus housing;
- (g) an opening on said conveyor auger housing, wherethrough waxed cardboard segments enter said conveyor auger housing;
- (h) a compression conveyor screw rotatably disposed within said conveyor auger housing, said compression conveyor screw including a helical blade
30 extending toward said outlet end of said conveyor auger housing, said helical blade including a plurality of flights;
- (i) a log extrusion orifice configured on the terminating end of said outlet end of said conveyor auger housing, wherethrough composite material is extruded, as a

result of the rotation of the compression conveyor screw, into a predetermined cross-sectional shape; and

(j) means for segmenting the composite firelog extrusion into individual log section.

5

52. An apparatus as recited in clause 51, wherein at least one blade spacer separates and provides spacing between each of said plurality of lower and upper circular blades.

10 53. An apparatus as recited in clause 52, wherein said blade spacers are configured with recessed centers to minimize the contact with the irregular inner surface of the circular blades to maintain proper clearances between blades.

15 54. An apparatus as recited in clause 51, further including a circular blade axial adjustment wherein the axial position of at least one axis of said circular blades can be positioned in relation to the other axis of circular blades to thereby provide control of the juxtaposition forces between upper and lower circular blades.

20 55. An apparatus as recited in clause 51, wherein said first common axis and said second common axis comprise a first shaft and a second shaft, respectively, whereupon rotation of said first shaft causes rotation of said lower circular blades and rotation of said second shaft causes rotation of said upper circular blades.

25 56. An apparatus as recited in clause 55, further comprising means for rotating said first common axis and said second common axis.

57. An apparatus as recited in clause 56, wherein said rotating means comprises a spur gear.

30 58. An apparatus as recited in clause 51, wherein said cutting blades are configured with teeth which are annularly disposed on the perimeter of said cutting blades, wherein said teeth facilitate the rapid cutting of the waxed corrugated cardboard without slippage.

59. An apparatus as recited in clause 58, wherein said teeth disposed on perimeter of said cutting blades are non-fluted.

5 60. An apparatus as recited in clause 51, wherein said cutting blades are hollow ground.

61. An apparatus as recited in clause 51, wherein said cutting blades are configured so that interaction between said upper cutting blades and said lower
10 cutting blades proximal the location of cutting edge overlap causes corrugated cardboard being sliceably passed therethrough to exhibit cut edges containing significant fraying.

62. An apparatus as recited in clause 61, wherein said significant fraying is
15 created by the rotating interaction of two hollow ground, non-fluted cutting blades.

63. An apparatus as recited in clause 51, wherein said overlap of first cutting edge and second cutting edge of said teeth provide a metered input feed of
20 waxed corrugated cardboard as the teeth grip the waxed corrugated cardboard and the movement of the cutting blades pulls the waxed corrugated cardboard therethrough at a predetermined rate proportional to the rotational speed of the cutters.

25 64. An apparatus as recited in clause 51, wherein at least one guide plate is attached to the housing, wherein said guide plates are configured with slots to allow a generally arcuate portion of said circular blades to pass therethrough, wherein said guide plates direct, or guide, the insertion of waxed corrugated cardboard into the proper feed direction for slicing by the combination of upper
30 and lower circular blades.

65. An apparatus as recited in clause 51, wherein a vertical guide plate is attached to the housing anterior of said circular blades, in relation to the direction

of material feed, and wherein a lower portion of said vertical guide is aligned proximal to upper guide plate on a lower end and extends upwardly to a height which provides for separation of waxed corrugated cardboard strips prior to contact with cutting reel and additionally prevents reverse flow of material back
5 into said circular blades.

66. An apparatus as recited in clause 51, wherein said cutting reel is mounted at a fifteen degree angle above the feed path of said waxed corrugated cardboard strips into said cutting reel.

10

67. An apparatus as recited in clause 51, further comprising a geared drive for rotating said cutting reel.

68. An apparatus as recited in clause 67, wherein said geared drive includes
15 a set of spur gears connected to said cutting reel through which power is applied to rotate said cutting reels.

69. An apparatus as recited in clause 51, wherein said cutting reel comprises:
(a) a first and a second end plate;
20 (b) an axial shaft positioned perpendicularly between said first and said second end plate; and
(c) a plurality of longitudinal cutting blades disposed around said axial shaft, paddle-wheel style, which are retained generally parallel to said axial shaft and attached to said first and said second end plate.

25

70. An apparatus as recited in clause 51, wherein said cutting blade of said cutting reel includes a helical twist extending between said first and said second end plate.

30 71. An apparatus as recited in clause 69, wherein a bed bar knife is attached to said apparatus housing anterior of said circular blades, in relation to the direction of material feed, and said bed bar knife is aligned proximal to lower guide plate positioned such that an edge of said bed bar knife is brought into

material shearing proximity with said longitudinal cutting blades of said cutting reel so that the strips of waxed corrugated cardboard material passing rearwardly of said circular cutting blades are placed in shearing contact therebetween bed bar knife and reel for the production of segments thereof.

5

72. An apparatus as recited in clause 71, wherein a bed plate is configured for retention of said bed bar knife, to allow interchangeable replacement of bed bar knives, wherein said bed plate is attached to said apparatus housing and therein retains said bed bar knife by means of at least one fastener, in a position which provides shearing of the waxed corrugated cardboard strips into waxed corrugated cardboard segments.

10

73. An apparatus as recited in clause 72, wherein said bed bar knife is retained by said bed plate with non-adjustable fasteners.

15

74. An apparatus as recited in clause 72, wherein said bed bar knife is retained by at least one fastener which provides longitudinal adjustment of the bed bar knife in relation to the bed plate.

75. An apparatus as recited in clause 74, wherein said fastener is a turnbuckle.

20

76. An apparatus as recited in clause 51, further including rifling within said conveyor auger housing, wherein said rifling aids the control of radial disposition and interlocking alignment of the waxed cardboard segments as extruded into the artificial firelog.

25

77. An apparatus as recited in clause 51, wherein the cardboard segments being transported through the conveyor auger housing are compressed to a ratio between approximately 5:1 and approximately 8:1.

30

78. An apparatus as recited in clause 51, further comprising a means for rotating said compression conveyor screw.

79. An apparatus as recited in clause 78, wherein said conveyor screw rotating means comprises a spur gear.

5 80. An apparatus as recited in clause 51, wherein said helical blade includes a diameter that decreases towards said outlet end of said conveyor auger housing.

10 81. An apparatus as recited in clause 51, wherein said flights of said helical blade decrease in length toward said outlet of end of said conveyor auger housing.

15 82. An apparatus as recited in clause 51, wherein the side profile of said helical blade becomes increasingly cupped towards said outlet end of said conveyor auger housing.

20 83. An apparatus as recited in clause 51, wherein said helical blade is configured with a buildup of weld material of a predetermined shaped at the junction of said helical blade and said auger shaft, wherein said buildup of weld material provides a final pushing thrust of said segments through outlet end of said conveyor auger housing.

25 84. An apparatus as recited in clause 51, further including a log die attached to said log extrusion orifice, wherein said log die provides for modifying the cross-sectional shape of the extrusion.

85. An apparatus as recited in clause 84, wherein said log die comprises a compression zone proximal to the attachment of said auger.

30 86. An apparatus as recited in clause 51, wherein said log die includes at least one longitudinal internal surface groove which produces logs with protruding ridges.

87. A compression conveyor auger assembly, for transporting and compressing waxed corrugated cardboard segments, comprising:

(a) a housing, said housing including an inlet end and an outlet end, wherein said outlet end is tapered;

5 (b) an opening on said housing, said opening disposed adjacent said inlet end of said housing; and

(c) a compression conveyor screw rotatably disposed within said housing, said compression conveyor screw including a helical blade extending between said inlet end and said outlet end of said housing, said helical blade including a
10 plurality of flights.

88. An apparatus as recited in clause 87, wherein the diameter of said helical blade decreases towards said outlet end of said housing, and wherein said flights decrease in length toward said outlet end of said housing.

15

89. An apparatus as recited in clause 88, further comprising a log die attached to said outlet end of said housing.

90. An apparatus as recited in clause 89, wherein said log die includes at
20 least one internal longitudinal groove therein.

91. An apparatus as recited in clause 87, wherein said housing includes a circular passageway having rifling.

25 92. An apparatus as recited in clause 87, wherein the cardboard segments being transported therethrough are compressed to a ratio between approximately 5:1 and approximately 8:1.

93. An apparatus as recited in clause 87, further comprising means for
30 rotating said compression conveyor screw.

94. An apparatus as recited in clause 93, wherein said conveyor screw rotating means comprising a spur gear.

95. An apparatus as recited in clause 87, further including means for segmenting the composite firelog extrusion into individual log sections.

5 96. An apparatus as recited in clause 87, wherein said helical blade includes a diameter that decreases towards said outlet end of said housing.

97. An apparatus as recited in clause 96, wherein said flights of said helical blade decreases in length toward said outlet end of said housing.

10

98. A waxed corrugated cardboard cutting assembly, comprising:

(a) a plurality of lower circular blades juxtaposed along a first common axis, said plurality of lower circular blades each including a first cutting edge;

15 (b) a plurality of upper circular blades juxtaposed along a second common axis; said plurality of upper circular blades each including a second cutting edge;

(c) said plurality of lower and upper circular blades configured to slice the at least one waxed corrugated cardboard sheet placed therebetween into cardboard strips, whereby said first common axis is generally parallel to said second common axis, and said first cutting edge overlaps said second cutting edge; and

20

(d) a cutting reel positioned to receive the waxed corrugated cardboard strips, said cutting reel capable of cutting the waxed corrugated cardboard strips into waxed corrugated cardboard segments.

25 99. An apparatus as recited in clause 98, wherein said common axis of said circular blades is axially adjustable to provide control of the interface force between upper and lower circular blades.

100. An apparatus as recited in clause 98, wherein each of said cutting edges of said lower circular blades and said upper circular blades comprise a plurality of non-fluted teeth.

30

101. An apparatus as recited in clause 98, wherein said first common axis and said second common axis comprise a first shaft and a second shaft, respectively, whereupon rotation of said first shaft causes rotation of said lower circular blades and rotation of said second shaft causes rotation of said upper circular blades.

5

102. An apparatus as recited in clause 101, further comprising means for rotating said first and second shafts.

103. An apparatus as recited in clause 102, wherein said first and said second shaft rotating means comprises spur gears.

10

104. An apparatus as recited in clause 98, further comprising means for rotating said cutting reel.

105. An apparatus as recited in clause 104, wherein said cutting reel rotating means comprising a spur gear.

15

106. An apparatus as recited in clause 98, further comprising:

20

(a) a lower guide plate which includes a plurality of slots through which said first cutting edges of said lower circular blades extend therethrough; and

25

(b) an upper guide plate which includes a plurality of slots through which said second cutting edges of said upper circular blades extend therethrough, wherein said lower guide plate and said upper guide plate form a channel therebetween for receiving and aligning waxed corrugated cardboard sheets for cutting by the circular blades.

30

107. An apparatus as recited in clause 98, wherein a vertical guide plate is positioned anterior of said upper circular blades with a lower end aligned proximal to the upper guide plate with an upper end extending upwardly to a height which provides for separation of waxed corrugated cardboard strips prior to contact with cutting reel and prevents reverse flow of material back into said circular blades.

108. An apparatus as recited in clause 98, wherein a bed bar knife is positioned anterior of said lower circular blades with a top portion aligned proximal to lower guide plate wheresopositioned at least one edge of said bed bar knife is in material shearing proximity with moveable portions of said reel
5 such that interposing waxed corrugated cardboard material being fed into the apparatus is placed in shearing contact therebetween bed bar knife and reel and shearing into waxed corrugated cardboard segments.

109. An apparatus as recited in clause 98, wherein a bed plate is configured for
10 attachment of said bed bar knife, and wherein said bed plate retains said bed bar knife in a position for material shearing therebetween said cutting reel.

110. An apparatus as recited in clause 109, wherein said bed bar knife is retained by said bed plate with non-adjustable fasteners.

15

111. An apparatus as recited in clause 109, wherein said bed bar knife is retained by at least one fastener which provides longitudinal adjustment of the bed bar knife in relation to the bed plate.

20 112. An apparatus as recited in clause 111, wherein said fastener comprises a bolt with a nut which flexibly retains bed bar knife to bed plate and a turnbuckle configured to provide an adjusting force wherein the bed bar knife may be adjustably retained in the correct shearing position in relation to the cutting reel.

25 113. An apparatus as recited in clause 98, wherein said cutting reel is mounted at an approximate fifteen degree angle above the direction in which the waxed corrugated cardboard slices travel upon exiting anterior of said upper and lower cutting blades after being sliced.

30 114. An apparatus as recited in clause 98, wherein said cutting reel comprises:
(a) a first and second end plate;
(b) an axial shaft positioned perpendicularly between said first and said second end plate; and

(c) a plurality of cutting blades disposed around said axial shaft, said cutting blades spaced equally apart and generally parallel to said axial shaft; said cutting blades attached to said first and second end plate;

5 wherein each said cutting blade includes a helical twist extending between said first and said second end plate.

115. An apparatus as recited in clause 114, wherein said helical twist of each said cutting blade does not exceed an angle generally over 13 degrees between said first and second end plates.

10

116. An artificial firelog comprising a plurality of compressed segments of waxed corrugated cardboard which are radially disposed within said firelog.

117. An artificial firelog as recited in clause 116, wherein said compressed
15 segments have been compressed to a thickness between approximately 1/8th and approximately 1/5th of their original thickness without generally having their corrugated structure destroyed or glued together.

118. An artificial firelog as recited in clause 116, wherein said compressed
20 segments of waxed compressed corrugated cardboard have opposing frayed edges.

119. A firestarter chip manufactured using a cutting assembly as recited in clause 98, comprising:

25 (a) a first substantially planar member;

(b) a second substantially planar member;

(c) a corrugated section disposed between said first substantially planar member and said second substantially planar member; and

(d) means for adhering said corrugated section to said first substantially planar
30 member and said second substantially planar member.

120. An artificial firelog manufactured by an apparatus as recited in clause 1, comprising a plurality of compressed segments of waxed corrugated cardboard which are radially disposed within said firelog.

5 121. An artificial firelog as recited in clause 120, wherein said compressed segments have been compressed to a thickness between approximately 1/8th and approximately 1/5th of their original thickness without generally having their corrugated structure destroyed or glued together.

10 122. An artificial firelog as recited in clause 120, wherein said compressed segments of waxed compressed corrugated cardboard include opposing frayed edges.

123. A firelog as recited in clause 120, wherein said firelog includes at least
15 one longitudinally-disposed rail thereon.

124. A method for manufacturing firestarter chips using the cutting assembly recited in clause 98, comprising the steps of:

- (a) slicing a waxed corrugated cardboard sheet into cardboard strips;
- 20 (b) slicing at least one sheet of paper into paper strips simultaneous to said slicing said waxed corrugated cardboard sheet strips; and
- (c) chopping said cardboard strips and said paper strips into waxed corrugated cardboard segments and paper segments, respectively.

25 125. A method for manufacturing firestarter chips as recited in clause 124, further comprising the steps of:

- (a) gathering said waxed corrugated cardboard segments and said paper segments; and
- (b) packaging said waxed corrugated cardboard segments and said paper
30 segments.

126. A method for manufacturing an artificial firelog using an apparatus recited in clause 37, comprising the steps of:

- (a) converting waxed corrugated cardboard sheets into segments;
- (b) compressing said waxed corrugated cardboard segments to a ratio approximately between 5:1 and 8:1;
- (c) extruding said compressed waxed corrugated cardboard segments into a continuous log structure; and
- (d) cutting said continuous log structure into individual firelogs.

127. A method for manufacturing an artificial firelog as recited in clause 126, further comprising the step of arranging waxed corrugated cardboard segments flat horizontally disposed between the rifling in the housing and helical blade of the conveyor screw wherein so aligned said corrugated cardboard segments become radially disposed interlocking segments within the artificial firelog extrusion.

128. A method for manufacturing segments of waxed corrugated cardboard from waxed corrugated cardboard sheets in accordance with the apparatus of clause 98, comprising the steps of:

- (a) slicing said waxed corrugated cardboard sheets into waxed corrugated cardboard strips; and
- (b) chopping said waxed corrugated cardboard strips into waxed corrugated cardboard segments.

129. A method as recited in clause 128, wherein said step of slicing said waxed corrugated cardboard sheets is preformed so that opposing frayed edges are created on said waxed corrugated cardboard strips.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention will be more fully understood by reference to the following drawings which are for illustrative purposes only:

FIG. 1 is a front sectional view of an artificial firelog producing apparatus of the present invention shown with guide plates removed.

FIG. 2 is a front sectional view of the artificial firelog producing apparatus of FIG. 1 shown with guide plates installed.

WO 01/24996

PCT/US99/23007

FIG. 3 is a rear view of the artificial firelog producing apparatus shown in FIG. 1.

FIG. 4 is a front sectional partial view of the conveyor compression auger assembly and firelog die portions of the present invention shown with an extruded
5 firelog.

FIG. 5 is a detailed front sectional view of the conveyor compression auger assembly and firelog die shown in FIG. 4.

FIG. 6 is a detailed front sectional view of the conveyor compression auger assembly and firelog die of FIG. 5 showing the forward pitch of the helical blade
10 of the conveyor compression auger assembly of the present invention.

FIG. 7 is a front view of the conveyor compression auger of the present invention shown from left to right.

FIG. 8 is a half conical schematic of the conveyor compression auger of FIG. 7 shown from right to left.

FIG. 9 is a schematic side view of the conveyor compression auger of
15 FIG. 7 showing flights and stations along the helical auger blade as seen from right to left.

FIG. 10 is a schematic side view of the conveyor compression auger of FIG. 7 as seen from left to right showing the forward pitch and weld fill of the
20 blade cross for the 1st 15 degree sweep (0 - 15 degrees).

FIG. 11 is a schematic side view of the conveyor compression auger of FIG. 7 as seen from left to right showing the 2nd 15 degree sweep (15 - 30 degrees).

FIG. 12 is a schematic side view of the conveyor compression auger of
25 FIG. 7 as seen from left to right showing the 3rd 15 degree sweep (30 - 45 degrees).

FIG. 13 is a schematic side view of the conveyor compression auger of FIG. 7 as seen from left to right showing the 4th 15 degree sweep (45 - 60 degrees).

FIG. 14 is a schematic side view of the conveyor compression auger of
30 FIG. 7 as seen from left to right showing the 5th 15 degree sweep (60 - 75 degrees).

WO 01/24996

PCT/US99/23007

FIG. 15 is a schematic side view of the conveyor compression auger of FIG. 7 as seen from left to right showing the 6th 15 degree sweep (75 - 90 degrees).

FIG. 16 is a schematic side view of the conveyor compression auger of FIG. 7 as seen from left to right showing the 7th 15 degree sweep (90 - 105 degrees).

FIG. 17 is a schematic side view of the conveyor compression auger of FIG. 7 as seen from left to right showing the 8th 15 degree sweep (105 - 120 degrees).

FIG. 18 is a schematic side view of the conveyor compression auger of FIG. 7 as seen from left to right showing the 9th 15 degree sweep (120 - 135 degrees).

FIG. 19 is a schematic side view of the conveyor compression auger of FIG. 7 as seen from left to right showing the 10th 15 degree sweep (135 - 150 degrees).

FIG. 20 is a schematic side view of the conveyor compression auger of FIG. 7 as seen from left to right showing the 11th 15 degree sweep (150 - 165 degrees).

FIG. 21 is a schematic side view of the conveyor compression auger of FIG. 7 as seen from left to right showing the 12th through 24th 15 degree sweep (180 - 360 degrees).

FIG. 22 is a schematic side view of the conveyor compression auger of FIG. 7 as seen from left to right showing the 25th through 48th 15 degree sweep of the second flight (0 - 360 degrees).

FIG. 23 is a schematic side view of the conveyor compression auger of FIG. 7 as seen from left to right showing the 49th through 63rd 15 degree sweep of the third flight (0 - 225 degrees).

FIG. 24 is a schematic side view of the conveyor compression auger of FIG. 7 as seen from left to right showing the 64th through 73rd 15 degree sweep of the third flight (225 - 0 degrees) and the first 15 degree sweep of the fourth flight (0 -15 degrees).

FIG. 25 is a schematic side view of the conveyor compression auger of FIG. 7 as seen from left to right showing the 74th through 97th 15 degree sweep of

WO 01/24996

PCT/US99/23007

the fourth flight (30 - 360 degrees) and the first (0 - 15 degrees) of the fifth flight.

FIG. 26 is a schematic side view of the conveyor compression auger of FIG. 7 as seen from left to right showing the 98th through 107th 15 degree sweep of the fifth flight (30 - 150).

5 FIG. 27 is a pictorial side view of the 0 - 15 degree cross section of the unwelded tip of the conveyor compression auger assembly of the present invention.

FIG. 28 is a pictorial side view of the 0 - 15 degree cross section of the no front weld push tip of the conveyor compression auger assembly of the present
10 invention.

FIG. 29 is a pictorial side view of the 0 - 15 degree cross section of the fully welded tip and push section of the conveyor compression auger assembly of the present invention.

FIG. 30 is a pictorial side view of the 15 - 30 degree cross section of the
15 unwelded tip of the conveyor compression auger assembly of the present invention.

FIG. 31 is a pictorial side view of the 15 - 30 degree cross section of the no front weld push tip of the conveyor compression auger assembly of the present invention.

20 FIG. 32 is a pictorial side view of the 15 - 30 degree cross section of the fully welded tip and push section of the conveyor compression auger assembly of the present invention.

FIG. 33 is a pictorial side view of the 30 - 45 degree cross section of the unwelded tip of the conveyor compression auger assembly of the present
25 invention.

FIG. 34 is a pictorial side view of the 30 - 45 degree cross section of the no weld push tip of the conveyor compression auger assembly of the present invention.

FIG. 35 is a pictorial side view of the 30 - 45 degree cross section of the
30 fully welded tip and push section of the conveyor compression auger assembly of the present invention.

FIG. 36 is a pictorial side view of the 45 - 60 degree cross section of the unwelded tip of the conveyor compression auger assembly of the present

WO 01/24996

PCT/US99/23007

invention.

FIG. 37 is a pictorial side view of the 45 - 60 degree cross section of the no front weld push tip of the conveyor compression auger assembly of the present invention.

5 FIG. 38 is a pictorial side view of the 45 - 60 degree cross section of the fully welded tip and push section of the conveyor compression auger assembly of the present invention.

FIG. 39 is a pictorial side view of the 60 - 75 degree cross section of the unwelded tip of the conveyor compression auger assembly of the present
10 invention.

FIG. 40 is a pictorial side view of the 60 - 75 degree cross section of the no front weld push tip of the conveyor compression auger assembly of the present invention.

FIG. 41 is a pictorial side view of the 60 - 75 degree cross section of the
15 fully welded tip of the conveyor compression auger assembly of the present invention.

FIG. 42 is a pictorial side view of the 75 - 90 degree cross section of the unwelded tip of the conveyor compression auger assembly of the present invention.

20 FIG. 43 is a pictorial side view of the 75 - 90 degree cross section of the no front weld push tip of the conveyor compression auger assembly of the present invention.

FIG. 44 is a pictorial side view of the 75 - 90 degree cross section of the fully welded tip and push section of the conveyor compression auger assembly of
25 the present invention.

FIG. 45 is a pictorial opposing side view of the 15 - 30 degree cross section of FIG. 32.

FIG. 46 is a side view of the conical housing portion of the conveyor compression auger assembly of the present invention.

30 FIG. 47 is an end view of the conical housing shown in FIG. 46 seen from the attachment point with the enclosure.

FIG. 48 is a side view of the log die and cooling jacket of the present invention.

WO 01/24996

PCT/US99/23007

FIG. 49 is an end view of the cooling jacket of FIG. 48 shown from the attachment point with the conical housing shown in FIG. 46.

FIG. 50 is a cross-sectional schematic of the auger housing showing the cut cardboard segments during extrusion of a firelog (helical blade not shown).

5 FIG. 51 is a cross section view of the interior space within a terminal portion of the log die shown with representative waxed corrugated cardboard segments radially compressed.

FIG. 52 is a side elevation view of the conical housing shown attached to a 4-inch firelog die corresponding to that shown in FIG. 4 but seen from right to left.

10 FIG. 53 is a side elevation view of the conical housing shown attached to a 3.5-inch firelog die.

FIG. 54 is end view of the firelog die shown in FIG. 52.

FIG. 55 is a side view of an alternative embodiment of a firelog die according to the present invention.

15 FIG. 56 is an exploded end view of the firelog die embodiment of FIG 55.

FIG. 57 is a partial right side view of the invention showing the waxed corrugated cardboard cutting assembly.

FIG. 58 is a side view of a blade used within the cutting reel of the invention.

20 FIG. 59 is a side view of the cutting reel of the invention showing the helical placement of the blades.

FIG. 60 is a partial front view of the assembly for cutting waxed corrugated cardboard strips, showing the relationship between the upper and lower circular blades and the central portions of the upper and lower guide plates.

25 FIG. 61 is a side view of a cutting blade spacer according to the invention.

FIG. 62 is a front view of the cutting blade spacer of FIG. 61.

FIG. 63 is a side view of the overlapping section of the upper and lower circular blades as shown in FIG. 60.

FIG. 64 is a top plan view of the lower guide plate shown in FIG. 57.

30 FIG. 65 is a right side view of the cutting assemblies of the invention shown with a waxed corrugated cardboard sheet and paper sheet being fed into the machine along with the waxed corrugated cardboard segments and paper segments produced.

WO 01/24996

PCT/US99/23007

FIG. 66 is a side elevation view of a bed bar assembly of the invention with the angle shown between the bed bar assembly and the center shaft of the reel of the present invention.

FIG. 67 is a left side view of the apparatus shown in FIG. 1.

5 FIG. 68 is a right side view of the apparatus shown in FIG. 1.

FIG. 69 is a perspective view of an artificial firelog manufactured by the apparatus of FIG. 1, showing representative horizontally disposed radially displaced interlocking segments and exterior log ridges.

10 FIG. 70 is a top plan view (magnified) of a waxed corrugated cardboard segment as used within the apparatus to form the firelog shown in FIG. 69.

FIG. 71 is a cross sectional view of the waxed corrugated cardboard segment taken along line 71-71 in FIG. 70.

FIG. 72 is a cross sectional view of the waxed corrugated cardboard segment of FIG. 71 which has been compressed.

15 FIG. 73 is a cross sectional view of the waxed compressed corrugated cardboard segment of FIG. 72 after re-expansion when heated.

FIG. 74 is a flowchart of the steps to fabricate the firelog shown in FIG. 69.

DETAILED DESCRIPTION OF THE INVENTION

Referring more specifically to the drawings, for illustrative purposes the present invention is embodied in the apparatus and methods generally shown and described in FIG. 1 through FIG. 74, wherein like reference numerals denote like parts. It will be appreciated that the apparatus may vary as to configuration and as to details of the parts and that the method may vary as to the steps and their sequence without departing from the basic concepts as disclosed herein.

25 Referring first to FIG. 1 through FIG. 3, an artificial firelog manufacturing apparatus 10 of the present invention is generally shown. Apparatus 10 generally comprises a waxed corrugated cardboard sheet cutting assembly 12, an enclosure 14, a compression auger conveyor assembly 16, a hopper 18 and a firelog die 20. Waxed corrugated cardboard sheet cutting assembly 12 is positioned on
30 enclosure 14 above hopper 18. Hopper 18 is disposed within enclosure 14 and includes an upper opening 22, a discharge chute 24, and an auger trough 46. Discharge chute 24 is positioned adjacent auger conveyor assembly 16 so that materials exiting from discharge chute 24 will be fed into auger conveyor assembly

16 by means of auger trough 46.

Conveyor compression auger assembly 16 is a compression type which comprises an auger trough 46, an auger housing 26, a log die 20, and a conveyor compression screw 28. Auger trough 46 is a semi-circular section formed on the bottom of hopper 18 which includes an inlet end 30 and an outlet end 32. An opening 34 within the conveyor compression auger assembly 16, is in material communication with hopper 18, in which an adjacent inlet end 30 is disposed within auger trough 46. A bore or circular passageway 64 is disposed longitudinally through auger trough 46, auger housing 26, and log die 20.

Conveyor compression screw 28 has a first end 36 and a second end 40 of a shaft 42, upon which is attached an annularly disposed helical screw 44. First end 36 of shaft 42 is driven by attached spur gear 56. A shoulder 38 of the shaft 42 is adjacent inlet end 30 of auger trough 46. A second end 40 of shaft 42 on the conveyor compression screw 28 terminates adjacent recompression zone 184 of log die 20. Shaft 42 incorporates a helical screw 44, between inlet end 30 of auger trough 46 and recompression zone 184 of log die 20.

Shaft 42 is approximately 69-inches long and extends through enclosure 14, therethrough inlet end 30 of auger trough 46 at the bottom of hopper 18, and terminates within the log die 20. Shaft 42 is rotatably disposed within a first pilot bearing 54 and a second pilot bearing 52, the bearings in combination support the cantilevered section of shaft 42 as the conveyor compression screw 28 transports cardboard segments 48a therethrough. First pilot bearing 54 is located on enclosure 14, and second pilot bearing 52 is located on an opening within the support plate 50 adjacent the auger trough 46. Shaft 42 typically has an approximate diameter of 2-½ inches for the first 35 inches of its length, which begins at a first end 36 and continues through first pilot bearing 54 and second pilot bearings 52 to a shoulder 38 of the shaft 42. The shaft 42 at the shoulder 38 steps up to an approximate 3 inch diameter as the cantilevered section of helical screw 44 begins. Shaft 42, containing helical screw 44, remains a constant diameter of 3 inches for 19 inches, and then tapers down in the final 15 inches to approximately a 1-inch diameter, terminating adjacent the start of the recompression zone 184, within the log die 20. There is a 6-inch standard keyway (not shown) beginning at the first end 36 of shaft 42 adjacent first pilot bearing 54.

Located around shaft 42 and keyway are a nut (not shown), lockwasher (not shown) and spur gear 56.

Helical screw 44 adjacent second end 40 of conveyor screw 28 and includes 5 flights 58a - 58e through to the shoulder 38 of the conveyor compression screw 28. Measuring from crest-to-crest, flights 58a - 58e are spaced apart, from second end 40 to shoulder 38 of conveyor screw 28, with proportionately increasing lengths. Flight 58a has a maximum diameter of about 4-inches at second end 40 of conveyor compression screw 28 and increases to about 7- $\frac{1}{2}$ inches in the first three flights 58a, 58b, 58c, and remains constant through flights 58d to 58f. Flight 58f is a partial flight of 4.5 inches.

Referring also to FIG. 4 through FIG. 7, auger housing 26 comprises a conical section 62 with a circular bolt flange 66 that attaches to the enclosure 14, and a square bolt flange 70, to which the square bolt flange 84 of the log die 20 is attached. At the point of attachment with the enclosure 14, the conical section 62 of auger housing 26 has an inner diameter of approximately 8-inches and an outer diameter of approximately 8- $\frac{1}{2}$ inches. Within the enclosure 14, starting at the support plate 50, a semi-circular section comprises an auger trough 46 which partially surrounds the helical screw 44 for approximately 15-inches. The upper portion provides for opening 34 to access conveyor compression screw 28. Auger housing 26 has a conical section 62 with a 2-inch wide circular bolt flange 66 which is configured to attach to the enclosure 14. Conical section 62 begins with an approximate inner diameter of 8-inches at the enclosure 14 and tapers down to an approximate inner diameter of just under 5 $\frac{1}{2}$ inches at the log die 20. The taper of conical section 62 is preferably between approximately 5° and 7.5°. A log die 20 is attached to the narrow end of the auger housing 26. The log die 20 receives the terminal end of the conveyor compression screw 28 within a conical zone 182. Final compression of the waxed corrugated cardboard segments is accomplished within the recompression zone 184 of the log die 20, and a final shaping zone 186 determines the size and shape of the resultant artificial firelog being extruded. A circular passageway 64 extends continuously from a partial enclosure by auger trough 46, through fully encircled regions within auger housing 26 and log die 20.

WO 01/24996

PCT/US99/23007

Circular passageway 64 incorporates longitudinal rifling 72 along the majority of its length, including the inner walls of the auger trough 46, the auger housing 26, and the conical zone 182 of the log die 20. The rifling 72 comprises a rail of four $\frac{1}{4}$ " x $\frac{1}{4}$ " keyway material positioned at 60°, 120°, 240° and 300°, respectively, along the interior walls of circular passageway 64. Rifling 72 keeps waxed corrugated cardboard segments 48a moving forward while being disposed horizontally as seen in FIG. 50, thereby controlling the friction and heat generated between the interior of both the auger housing 26 and log die 20, and the waxed corrugated cardboard segments 48a. It should be noted that various waxed corrugated cardboard segment "states" are considered in the disclosure. A brief look at FIG. 71 through FIG. 73 shows that three states are addressed: (1) uncompressed waxed corrugated cardboard segments 48a, (2) compressed waxed corrugated cardboard segments 48b, and (3) partially uncompressed 48c as a result of memory characteristics when the compressed segment is heated.

Bleed holes (not shown) can be incorporated near the input end of the conical section 62 of the auger housing 26 to provide a means for introducing scented oils and colors or additional wax with anti-bacterial properties during operation of conveyor compression screw 28.

As can be seen in FIG. 6, the flights of the helical blade are angled forward towards log die 20 at various angles to more effectively push materials therethrough. The angles $a1$ - $a5$ are contained in Table 1 where a = forward angle of blade (FIG. 6), f = flight length (FIG. 8), h = blade height (FIG. 8), r = distance from exterior of blade to auger housing (FIG. 8), and s = distance between stations (FIG. 9).

FIG. 7 shows the conveyor compression screw 28 in isolation. A machined shaft section of length $e1$ (35.00 inches) and a diameter $e1$ (2.500 inches) is held at both ends by bearings which stabilize the remaining cantilevered section of the shaft containing the helical auger blade. A non-tapered section of the conveyor compression screw extends within the enclosure for a length $e2$ (19.00 inches) with a fixed exterior diameter $d2$ (3.0 inches). A tapered section of length $e3$ (15.00 inches) with a diameter that tapers to a minimum of $d4$ (1.000 inches) at the end of the conical zone within the log die 20.

WO 01/24996

PCT/US99/23007

FIG. 8 is a conveyor compression screw 28 cross-section diagram showing dimensions marks for the five flights of its helical screw 44. The length of each flight is given by **f1 - f5** and the height of the blades above the shaft 42 is given by **h1 - h5** as provided in Table 1. It should be noted that the auger diameter correspondingly begins to taper as it enters the tapered section of the auger housing 26; the start of the taper being further broken down into sections **a - d**, for each of which a separate blade height value is given in Table 1. Space between the conveyor compression screw 28 and the interior of the circular passageway 64, is given by **r** which remains as a constant gap of (0.2500). The gap of **r** provides spacing for the rifling 72 within the compression screw housing so that the segments can be interlocked on their way to complete formation within the log die 20. FIG. 9 is a diagram of the five flights which depicts stations along the length of the conveyor compression screw 28. The angular displacement of the conveyor compression screw changes by 15° between stations and the distance between each station varies with flight. The distance between stations is given by **s1 - s5** within Table 1.

Representative blades are shown in FIG. 10 through FIG. 26 with noted dimensions given within Table 2 where **St No.** = Station Number, **Flt** = flight number(s), **Degree** = degrees covered within flight, **s** = station-to-station distance, **b** = blade height, **p** = length of pusher side weld buildup, **w** = length of rear-side weld buildup, **y** = height of pusher weld buildup, **t** = height of rear-side weld buildup, **g** = forward tilt of blade. Measurements are provided individually for the stations along the first half-flight, as a number of dimensions vary, whereas the remaining station data is given for ranges of stations (12 to 24, 24 to 48, etc.). It can be seen from the progression of these figures the manner in which the blade height increases, the amount of tilt decreases, and the pusher-side and rear-side weld buildups get less pronounced on sections of the blade further away from the exit point of the log extrusion. It must be remembered that these measurements, being provided for the preferred embodiment, in no way limit the practice of the invention; numerous obvious dimensional and structural changes may be introduced without inventive effort or departure from the underlying principles thereof.

Representative blades of the first 90 degrees of the conveyor compression screw are shown pictorially in FIG. 27 through FIG. 45 at various stations. Each section shows the helical screw 44 attached to the shaft 42 of the conveyor compression screw 28 in an unwelded state, without a pusher-side front weld buildup 154, and then with both a pusher-side front weld buildup 154 and a rear-side weld buildup 156. The chosen fillet material used within this embodiment is a buildup of weld material, however any conventional fillet material may be used. The angles β_1 , β_2 , β_3 , as shown in the figures, are given in Table 3. FIG. 45 shows the important first 15 degree section of the screw from the opposite direction wherein the exit face of the blade can be seen.

FIG. 46 and FIG. 47 show a side and end view of the auger housing 26 as shown in FIG. 1. A conical section 62 of the auger housing provides a taper matching that of the conveyor compression screw (not shown). The auger housing 26 is attached to the enclosure (not shown) by means of a circular bolt flange 66. A log die (not shown) is attached by means of a square bolt flange 84, preferably of a $\frac{1}{2}$ " x 10" x 10" configuration to the auger housing 26. Rifling 72 is shown within the interior of the conical section 62 of the auger housing 26.

FIG. 48 and FIG. 49 show a side and an end view of the log die 20 as shown in FIG. 1. The log die 20 comprises a housing 74, approximately 18 inches in length, containing both an inlet side 76 and a material outlet side 78. The log die is attached to the conical auger housing via square bolt flange 84 wherein the inner opening 80 of the log die receives the waxed compressed cardboard material pushed by the conveyor compression screw (not shown). Three sections, or zones, exist along the length of the log die: a conical zone 182 wherein the shape and rifling 72 of the conical section 62 are continued, a recompression zone 184 wherein the material after leaving the rifled sections is recompressed, and a shaping zone 186 wherein the waxed corrugated cardboard segment material is finally shaped such that the material exiting the log die 20 is of the desired diameter and shape for the artificial firelog being produced.

As it has been found desirable to control the temperature of the log die 20 during the formation of artificial firelogs 90, the log die 20 is configured with a cooling jacket 82 surrounding the inner walls of the log die. The cooling jacket 82 allows the temperature of the log die to be controlled by varying the amount and

WO 01/24996

PCT/US99/23007

temperature of incoming coolant which is routed into input 88 through the cooling jacket 82. The coolant exits the cooling jacket 82 by way of the outlet 92.

Alternately the log die could be cooled with conventional means such as fans, cooling fins or similar heat dissipation structures. In addition it may be desirable to
 5 cool the conveyor housing 26. The conveyor housing may be cooled with conventionally known methods, such as a combination of cooling fins and fans. A cooling jacket (not shown), may also be added to the conical auger housing section 62 in similar manner to the cooling jacket 82 of the log die 20.

FIG. 50 is a schematic of the alignment of waxed corrugated cardboard
 10 segments 48 around the periphery of the conveyor compression screw upon shaft 42. A clearance of approximately $\frac{1}{4}$ " exists between the outer circumferential edges of the helical blade and the circular passageway 64, as seen in FIG. 50, the clearance allows interlocking of the compressed circumferentially-disposed waxed corrugated cardboard segments 48a near the inner surfaces of conical section 62
 15 and log die 20. Because waxed corrugated cardboard segments 48 are compressed circumferentially around firelog 90, they open or expand (because of memory) with heat when burned, and the corrugations channel oxygen throughout the segments within a firelog 90. Waxed corrugated cardboard segments are more tightly twisted in the center of firelog 90, increasing their burn time. These
 20 radially disposed segments within the firelog 90, provide for easy ignition and a high burn efficiency, while the resulting flames appear similar to the burning of a genuine bark firelog.

FIG. 51 is a schematic of a firelog cross-section showing orientation of a few of the waxed corrugated cardboard segments 48b radially disposed within the
 25 firelog.

FIG. 52 through FIG. 54 depict two log dies alternately being connected with the conical auger housing 26 (for clarity no fasteners are shown). FIG. 52 is a log die 20 for producing 4 inch artificial firelogs. FIG. 53 is a log die 20 for producing 3 $\frac{1}{2}$ inch artificial firelogs. FIG. 54 is an end-view of the combined log
 30 die and auger housing 26. It can be noted in these figures that the two sections mate together with smooth transitions from within the conical section 62 of the auger housing 26 to the conical zone 182 of the log die 20, this transition includes proper alignment of the rifling 72. Although logs can be produced without the

WO 01/24996

PCT/US99/23007

alignment and smooth transitions, they allow the extrusion of logs under reduced pressures.

FIG. 55 and FIG. 56 are a side and end view of an alternate log die design 190. This log die schematic is shown with two separating halves 192, 194 which are bolted together and attached to the conical auger housing (not shown). Additionally die-spacers 196, 198 are shown. By varying the width of the die-spacers 196, 198, firelogs may be extruded with variously sized longitudinal rails. The die-spacers can alternately be made to extend into the log extrusion area such that logs are produced with longitudinal grooves.

FIG. 57 is a side view of the cutting assembly for the waxed corrugated cardboard. A plurality of lower circular blades 98 with teeth 120, and a plurality of upper circular blades 100 with teeth perform slicing of the waxed corrugated cardboard into strips and a cutting reel 102 in conjunction with a bed bar knife 144 then cuts the strips into waxed corrugated cardboard segments. Lower circular blades 98 are juxtaposed along a lower axis 104 and are separated by spacers 106 which maintain a constant distance between each lower circular blade 98. The spacers 106 are made with a recessed center to minimize the contact with the irregular surface of the inner portion of the cutting blades. Upper circular blades 100 are juxtaposed along an upper axis 108 and are separated by spacers 110. Waxed corrugated cardboard sheets are fed along channel 132 between a lower guide plate 128 and an upper guide plate 130. The cardboard material is cut into strips by the cutting edges 116, 118. A vertical guide plate 140 prevents material strips that exit the cutting blades from becoming re-engaged with the cutting blades.

Waxed corrugated cardboard strips then arrive at shearing contact between cutting reel 102 that contains cutting blades 164 which shear the cardboard against a cutting surface 142 of a bed bar knife retained on a bed plate 146.

FIG. 58 shows one of the cutting blades 164 of the cutting reel 102 as depicted in FIG. 57. The cutting blade is a generally rectangular member containing a steel-edged longitudinal cutting surface which is used in combination with the bed bar knife (not shown) to shear the waxed corrugated cardboard strips into cardboard segments.

WO 01/24996

PCT/US99/23007

FIG. 59 is the cutting reel 102 (non-mower type) as shown in FIG. 57. The cutting reel retains a plurality of cutting blades 164 about a central axis 162. The cutting blades 164 are shown helically attached to the cutting reel 102 annularly disposed about the axis 162 in connection with a first and a second end panel 158, 160. Three inner support panels (not shown) are spaced evenly between first and second end panels 158, 160 to retain the blades at a fixed radial distance from the central axis 162. Cutting blades 164 are positioned circumferentially between first and second end panels 158, 160 starting and ending with an angle of generally less than or equal to angle θ shown. Cutting blades 164 are generally retained parallel to the axial shaft 162 whereby rotation of axial shaft 162 thereby causes rotation of attached cutting blades 164. Typically the cutting reel 102 should have a diameter of at least approximately 8-inches, and the axial shaft 162 typically should have a diameter of at least approximately 1-½ inches. Axial shaft 162 is typically 49-inches in length, with 2-inch threads, a 6-inch standard key.

The cutting reel may be fabricated from mild steel, case hardened steel or like material. Cutting reel 102 herein uses cutting blades 164 wherein 8 such blades are preferred. The cutting blades 164 are equally spaced apart, each having a length of approximately 36-inches. First and second end panels 158, 160 and the three inner support panels have slots (not shown) to provide access for cutting blades 164 to be longitudinally inserted therethrough at their proper angles. The angle θ of the helical mounting of the blades is important, as too great an angle causes the chips to jam to one side of the machine. The angle θ used within this embodiment is 12.5 degrees, as larger angles began causing waxed corrugated strips to be pushed to one side making a wad that the cutting reel jams on. To facilitate cutting and aid in the migration of waxed corrugated cardboard segments, the cutting blades 164 are helically configured within the cutting reel 102. In this preferred configuration the cutting blades 164 have a left hand helix while cutting reel 102 rotates counterclockwise.

FIG. 60 the mechanism which cuts the waxed corrugated cardboard into strips is shown with a series of upper circular blades 100 juxtaposed along an upper axis 108, comprising a shaft 114, wherein each of the upper circular blades are separated by spacers 110. Lower axis 104 comprises a lower shaft 112 upon which a series of lower circular blades 98 separated by spacers 106 are

WO 01/24996

PCT/US99/23007

juxtaposed along a lower axis 104. Both lower shaft 112 and upper shaft 114 are parallel and spaced apart such that the cutting edges 116 of lower circular blades 98 partially overlap the cutting edges 118 of upper circular blades 100. Lower and upper shafts 112, 114, are of a diameter to fit into a correspondingly sized bore within lower and upper circular blades 98, 100. A range of 40 to 50 blades are typically used per axis. Upper shaft 114 used herein is approximately 50-1/8 inches in length and contains a full length standard keyway (not shown) with a 2-inch threads portion starting from its left end. A collar (not shown) welded thereon allows for axially adjusting upper shaft 114 to allow for some compression between lower and upper circular blades 98, 100. Lower shaft 112 used within this embodiment is approximately 56 inches long and includes a full length standard keyway (not shown) and 2-inches of threads at each end. Lower and upper shafts 112, 114 are fabricated from mild steel, case hardened steel or like material. Lower and upper circular blades 98, 100 within this embodiment can range between approximately 7-1/4 inches to 12-inches in diameter, but preferably, 8-inch non-fluted hollow ground blades are should be used, because their cutting edges 116, 118 have non-fluted (straight) teeth 120 which are necessary for grabbing and metered pulling of the material into the machine evenly for slicing and then pushing the waxed corrugated cardboard strips to the cutting reel without slipping. The large number of cutting teeth, although non-fluted, create uneven cutting tracks to provide a fuzzy edge on the waxed corrugated cardboard being cut. Slices of waxed corrugated cardboard sheets 122, or waxed corrugated cardboard boxes, are imparted with a fuzzy edge which operates to decrease the time required to ignite a segment. FIG. 61 and FIG. 62 are side and facing views of the spacer 106 used between the lower cutting blades; the spacers 110 used between the upper blades within this embodiment are interchangeable with the spacers 106 for the lower cutting blades. The annular face 200 of the spacer 106 is the only portion of the spacer visible exterior of the assembled apparatus. Spacers are mounted to a shaft via mounting hole 202 and retained by a shaft key engagement of the keyway 204.

FIG. 63 depicts the interaction of the upper and lower circular blades within the embodiment. Using an 8-inch circular blade, the depth of the overlap 138 between the cutting edges 116, 118 should be at least 1/4-inch. Teeth 120 are

angled in such a manner to draw or pull one or more waxed corrugated cardboard sheets into the cutting edges 116, 118, while not allowing the sheets to slip. During cutting, the teeth of the cutting blades impart a fuzzy edge to the waxed corrugated cardboard being cut. Circular blades 98, 100 within the embodiment
 5 are case hardened to a Rockwell hardness of 45 or greater, and are thick enough (approximately 0.080 inches) so as not to flex apart. Lower and upper spacers 106, 110 have a diameter of approximately 4-½ inches to 5-inches when used with an 8-inch cutting blade since a minimum separation of 2-½ inches must be maintained between cutting edges 116 of lower circular blade 98 and lower
 10 spacers 106 and also between cutting edges 118 of upper circular blades 118 and upper spacers 110. The included angle α is measured between the tips of the fully overlapping blades 98, 100 at cutting edges 116, 118 through the point 128 wherein the blade tips coincide. The embodiment of the apparatus is configured with angle α set to 14.4 degrees to ensure proper and reliable feeding of waxed corrugated
 15 cardboard sheets, or boxes, 122 into cutting assembly.

FIG. 64 is a plan view of the lower guide plate 128 with a plurality of slots 126. The upper guide plate 130 (not shown) is similarly slotted. The slots within the lower and upper guides plates 128, 130 allow the cutting edges 116 of lower circular blades 98, and cutting edges 118 of upper circular blades 110 to extend
 20 therethrough for engagement and cutting of the waxed corrugated cardboard material. Slots 126 are typically no greater than ¼ inches wide to help prevent lower and upper circular blades 98, 100 from clogging. Lower and upper circular blades are self-clearing due to their minimal clearances within slots 126 in upper and lower guides plates 128, 130, as the slots 126 extend only approximately
 25 0.010 inches beyond the interposing circular blades.

FIG. 65 is a side view of the waxed corrugated cardboard cutting assembly 12 showing waxed corrugated cardboard sheets 122 being fed into the input side wherein the material is sliced into waxed corrugated cardboard strips 134 and then segmented into waxed corrugated cardboard segments 148. Lower and upper
 30 guide plates 128, 130 reside as generally planar sections between the lower and upper circular blades 98, 100, and are typically parallel to each other near the junction of the upper and lower cutting surfaces. These two guide plates form a defined path, or channel, 132 through which waxed corrugated cardboard sheets

122 can enter cutting assembly 12 and through which sliced waxed corrugated cardboard strips 134 pass on their way to being segmented. The distance between the upper and lower guide plates 130, 128, respectively, provide a channel 132 that helps direct the waxed corrugated cardboard sheets 122 into the cutting blades.

A vertical guide plate 140 extends upwardly from upper guide plate 130 proximate to cutting reel 102 for separating waxed corrugated cardboard strips 134 just prior to contact with cutting reel 102 which prevent reverse flow of material. Lower guide plate 128 terminates at the inner edge directly above the cutting surface 142 of a bed bar knife 144. A bed plate 146 disposed below bed bar knife 144 directs waxed corrugated cardboard segments 48a towards, as shown in FIG. 1 through FIG. 3, an opening 34 which is in material communication with conveyor compression auger assembly 16. Attachment means 148, such as a nut and bolt, are used to attach bed bar knife 144 onto bed plate 146. The bed plate attaches by two outer studs which are threaded into each end of the bed plate and are fitted through the outer wall of the cutting assembly. The bed plates are not fixed but swivel freely to allow adjustment; however they remain ridged in their horizontal angle relationship to the reel. The pitch angle of bed plate 146 can be configured to provide for adjustment of the angle and to partially compensate for wear of the bed bar knife. As cutting blades 164 revolve, each blade passes in close proximity to cutting surface 142 of bed bar knife 144, which results in shearing of the waxed corrugated cardboard strips 134 passing therethrough into waxed corrugated cardboard segments 48. Paper sheet layers may be added to the waxed corrugated cardboard sheets 122 so that a paper mix 60 is created with the waxed corrugated cardboard segments 48a. This paper mix is typically used for firestarter material.

FIG. 66 is a schematic of the cutting reel 102 position in relation to the cutting edge 142 of the bed bar knife 144. The axis of rotation of the cutting reel within the embodiment is vertically disposed by an angle λ , which for the embodiment is approximately 15 degrees from the cutting edge 142 of the bed bar knife 144 when taken in relation to direction of the lower guide plate 128.

FIG. 67 and FIG. 68, the left side and right side, respectively, of apparatus 10 is generally shown. A motor (not shown), or like means, provides the power

WO 01/24996

PCT/US99/23007

necessary to operate apparatus 10. Those skilled in the art will appreciate that the motor can be electrically powered, an internal combustion engine and/or be remotely located and coupled to apparatus 10 through a gear box (not shown). It has been determined, however, that for the embodiment thusly described, the
 5 motor must provide an output of at least 40 horsepower in order to produce firelogs 90 while operating all the various subassemblies simultaneously.

In the preferred configuration (FIG. 67 and FIG. 68), the motor (not shown), powered by a frequency drive for speed control, directly drives an 18-inch primary spur gear 166 that is axially mounted on a primary driveshaft 168 which rotates
 10 within enclosure 14. Primary spur gear 166 in turn engages and drives a cutting assembly gear 170, which is a 16-inch spur gear. Cutting assembly gear 170 is axially mounted on lower shaft 112 of the cutting assembly adjacent the left side 172 of enclosure 14. Rotation of cutting assembly gear 170 rotates lower shaft 112 and hence, lower circular blades 98. In FIG. 68, a lower shaft spur gear 174
 15 is axially mounted on lower shaft 112 adjacent the right side 178 of enclosure 14. The relationships of these gears can also be seen in FIG. 1 through FIG. 3, along with first gear housing 150 and second gear housing 188 which enhance safety. Primary spur gear 166 and driveshaft 168 are directly behind gear 56 and shaft 42 and can not be seen in FIG. 1 or FIG. 2, yet are in full view in the rear view of FIG.
 20 3. Lower shaft spur gear 174 engages and drives upper shaft spur gear 176, which is attached to upper shaft 114 adjacent the right side 178 of enclosure 14. Rotation of upper shaft spur gear 176 rotates upper shaft 114 and hence, rotates upper circular blades 100. Lower shaft spur gear 174 and upper shaft spur gear 176 are identically configured so that the rotational velocities of lower and upper
 25 circular blades 98, 100 are the same. In the preferred embodiment, lower shaft and upper shaft spur gears 174, 176, respectively, are approximately 8-inches in diameter.

Referring again to FIG. 67 the cutting reel 102 is driven by spur gear 170, which is driven by primary spur gear 166. Axial shaft 162 of cutting reel 102
 30 includes a gear 180 adjacent the left side 172 which is driven by spur gear 170, which engages primary spur gear 166. In the preferred configuration, gear 180 of cutting reel 102 is a spur gear that is configured to provide a rotational velocity of approximately 4:1 between lower circular blades 98 and cutting reel 102. The 4:1

WO 01/24996

PCT/US99/23007

ratio between lower circular blades 98 and cutting reel 102 is somewhat critical as it determines the length and size of waxed corrugated cardboard segments 48. The higher the ratio, the smaller the waxed segments 48, and conversely, the lower the ratio, the larger the waxed segments 48.

5 Primary spur gear 166 also drives shaft 42 of conveyor compression auger screw 28. Primary spur gear 166 engages conveyor compression auger screw spur gear 56, which is mounted on shaft 42. Conveyor compression auger screw spur gear 56, preferably, is also approximately 18-inches in diameter to allow for the same rotational velocity in conveyor compression auger screw 28. Although
10 gearing mechanisms are disclosed to drive cutting assembly 12 and conveyor compression auger assembly 16, those skilled in the art will appreciate that chain and sprocket assemblies (not shown), belt and pulley assemblies (not shown) and/or a combination of any of the aforementioned can be used to achieve the same objective.

15 To fabricate artificial firelog 90, flattened waxed corrugated cardboard boxes in the form of waxed corrugated cardboard sheets 122, as shown in FIG. 65, are fed into channel or opening 132 until grasped by lower and upper circular blades with teeth 98, 100. Lower and upper circular blades 98, 100 draw or pull waxed corrugated cardboard sheets 122 into and meter through channel 132
20 while slicing waxed corrugated cardboard sheets 122 into strips 134 while simultaneously applying fuzzy frayed edges to the strips. As waxed corrugated cardboard strips 134 pass through and exit channel 132, cutting blades 164 on cutting reel 102 chop waxed corrugated cardboard strips 134 into waxed corrugated cardboard segments 48. Referring now to FIG. 4, the waxed
25 corrugated cardboard segments fall from the cutting reel into hopper 18 and are guided into opening 34 of conveyor compression auger assembly 16. The cardboard segments are then radially disposed to the inner walls of the conical section 62 where the $\frac{1}{4}$ riffling 72 guides the compressed segments 48b continually forward and through the conical zone 182 of the log die 20. The riffling
30 72 also insures that the outer layer of the log will have a consistent layer of flattened radially disposed segments. These segments are compressed through each flight of the compression auger. As the segments reach the final compression (push) flight they have been arranged flat, horizontally, longitudinally

WO 01/24996

PCT/US99/23007

disposed, and helically compressed from the center of the log outward. The log die puts the last compression into the log extrusion and forms the received compressed segments into various firelog products. A firelog 90, as manufactured by the embodied apparatus, is shown in FIG. 69 with a few representative waxed corrugated cardboard segments shown disposed radially on the surface of the log. For clarity, only a few segments are shown, however the log is comprised principally of these waxed corrugated cardboard segments 48. The firelog 90 shown additionally contains a rail 96 which was formed by using a log die containing a longitudinal channel, or groove, such as the one described in regard to the alternate log die of FIG. 55 and FIG. 56. Rails 96 within the embodied log are approximately $\frac{1}{8}$ to $\frac{1}{4}$ inches in width and extend approximately $\frac{1}{8}$ to $\frac{1}{4}$ inches above the surface of firelog 90. Rails 96 function similarly to a candle-wick, and facilitate lighting of the firelog 90. The rails 96 also keep any log overwrapping material from sticking onto the surface of the firelog 90, whereby an air-gap is maintained to promote ignition of the firelog.

FIG. 70, the waxed corrugated cardboard segments 48a produced by the cutting assembly of the preferred embodiment are approximately $\frac{1}{2}$ to 1 square inch in size with frayed edges on each of two opposing sides created by the teeth on the pair of cutting blades within the mechanism which performs the slicing operation. The wax coating and corrugations of the original waxed corrugated cardboard sheets remain intact within these waxed corrugated cardboard segments.

Foreign metallic substances, such as staples, commonly found with waxed corrugated cardboard sheets may be easily removed by using magnets, if this is desired, however the apparatus will operate without removing the staples. FIG. 67 shows the hopper walls 152 whereupon whose exterior magnetic means may be applied to prevent such metallic substances from entering the conveyor compression auger.

Waxed corrugated cardboard segments may also be directed from the cutting apparatus to a drying apparatus and then returned to the hopper before entering the conveyor compression auger.

To fabricate firestarter chips, a mix of paper and waxed corrugated cardboard segments are produced by using cutting mechanism within the

WO 01/24996

PCT/US99/23007

inventive apparatus. Referring to FIG. 65, paper sheets 124, preferably with 10% to 25% paper, are laid over waxed corrugated cardboard sheets 122 and both are fed into opening 132 until grasped by lower and upper circular blades 98, 100. Lower and upper circular blades 98, 100 slice waxed corrugated cardboard sheets 122 and paper sheets 124 into waxed corrugated cardboard strips 134 and paper strips 136, respectively. Cutting blades 164 on cutting reel 102, chop waxed corrugated cardboard strips 134 and paper strips 136 into waxed corrugated cardboard segments 48a and paper mix 60, respectively. Waxed corrugated cardboard segments 48a and paper mix 60 are gathered or directed into to a standard bagging machine (not shown) for packaging the waxed corrugated cardboard segments 48a and paper mix 60 as an aggregate firestarter mix composed of approximately 80% waxed corrugated cardboard segments 48a and approximately 10% to 25% paper mix 60. Those skilled in the art will appreciate that approximately 20% of waxed corrugated cardboard segments 48a can be hammer-milled into a cotton-like fiber which can be used in lieu of paper mix 60. This cotton-like fiber promotes rapid ignition when in an uncompressed state, such as the firestarter mix, however when the hammer-milled material is compressed, the opposite effect occurs and rapid ignition is prevented.

Firelogs may be produced by leaving off the above described paper sheets and further processing the waxed corrugated cardboard segments, that have been heretofore cut into segments. Referring to FIG. 4, after the uncompressed waxed corrugated cardboard segments 48a are cut, they fall into the hopper 18 and enter opening 34, the rotation of conveyor compression screw 28 transports waxed corrugated cardboard segments 48a into and through auger housing 26. Conveyor compression screw 28 rotates and compresses waxed corrugated cardboard segments 48a along the length of the circular passageway 64, into compressed waxed corrugated cardboard segments 48b. As the waxed corrugated cardboard segments 48b being compressed approach the recompression zone 184 of the log die 20, the segments 48b are heated up due to the compression friction and centrifugal force occurring therein. This heating propagates uniformly and thereby adheres waxed corrugated cardboard segments 48b together in a generally interlocking planar fashion. This interlocking planar adhesion of segments 48b gives finished firelog 90 additional cohesive strength

WO 01/24996

PCT/US99/23007

with no cold joints. The conveyor compression auger assembly 16, is operated (with regard to speed, cooling flow, and adjustment) so as to maintain the temperature of compressed waxed corrugated cardboard segments 48b under 150° F. At temperatures above 150° F the "wet glue" used to form the waxed
5 cardboard corrugations can melt resulting in corrugation delamination. Also, the wax used on the waxed cardboard segments 48a has a blocking point temperature of approximately 110° F and a melting point temperature of approximately 142° F. The heat necessary to form firelog 90, without melting the wet glue and wax in the corrugated cardboard, is generated only by conveyor
10 compression screw 28 and is typically about 50° F to 55° F above ambient temperature. Firelogs 90 have been found to generally form best between temperatures of approximately 108° F and 148° F, thus requiring an ambient temperature range of approximately 53° F to 93° F, which is well within the range of most factories or manufacturing facilities. It has been determined that when the
15 ambient temperature is lower, conveyor compression auger assembly 16 can be run faster and consequently, more firelogs 90 can be produced. Therefore, the ability to vary the ambient temperature of the manufacturing environment is desirable. A cooling section, as previously described and shown may be applied around the log die to increase the production capability by further cooling and
20 controlling the temperature.

Maintaining the integrity of the cellular structure 214, as shown in FIG. 71, is essential for allowing oxygen and wax to flow through the waxed segments to provide for easier ignition and more efficient burning of the firelog 90 of FIG. 70. The centrifugal force within the conveyor compression auger assembly urges
25 segments radially outward to the periphery of firelog 90 so as to lay "flat" along the outer surface of the conical auger housing wherein upon compression these segments become radially disposed within firelog 90. Being radially disposed, the waxed corrugated cardboard segments are free to expand when heated, thereby providing a log which burns more efficiently and in a manner resembling genuine
30 wood bark. Waxed corrugated cardboard segments are compressed within the apparatus by a factor of approximately 5 to 8. The amount of compression, as set by the conveyor compression auger assembly, is a determiner of fuel density and a factor in regulating the burn rate of the log.

WO 01/24996

PCT/US99/23007

Additional wax or glue is not required within a firelog formed within the current invention, due to the unique configuration of the conveyor compression auger assembly, whose functioning includes compressing, radially disposing, and interlocking the waxed corrugated cardboard segments into a firelog extrusion that does not easily break apart. If desired, however, openings (not shown) can be placed within conical section of the conveyor compression auger assembly so that extra liquid wax can be added to waxed corrugated cardboard segments. This extra wax can be used to achieve longer burn time, greater BTU's, or to reduce friction within the production process. The addition of wax, or a wax replacement substance, may also be used with non-waxed corrugated cardboard sheets or paper if used. As the firelog 90 burns, corrugations 210 of the cellular structure 214 on the waxed corrugated cardboard segments 48b expand to 48c (FIG. 73), allowing oxygen and wax to permeate throughout firelog 90, resulting in a clean and efficient burning firelog 90. The outermost segments of firelog 90 fall off and the next outermost layer continues burning.

An outer coating or cover (not shown) can be extruded along with firelog 90 by adding bleed holes on conical section 62 to allow for the introduction of plastic or hot glues into the conveyor compression to form the outer coating or cover for firelog 90 during compression and extrusion. A means can also be provided wherein the plastic or hot glue is inserted beyond exit 76 of die 20. The outer coating or cover gives the log structure a significantly greater compressive strength, thereby allowing the production of a log product extrusion whose outer coating may be made sufficiently durable so that the extrusion can be used for posts, pillars or the like.

Referring now to FIG. 69 through FIG. 73, a firelog 90 of FIG. 69, manufactured by apparatus 10 of the present invention is generally shown. As will be seen, firelog 90 is a longitudinally-shaped structure that comprises waxed corrugated cardboard segments 48b which have been radially disposed and densely compacted together. The basic material used to form firelog 90 is waxed corrugated cardboard sheets as found within ordinary waxed corrugated cardboard boxes. The waxed corrugated cardboard sheet(s) are cut into small segments 48a of FIG. 70. The waxed corrugated cardboard segments are preferably cut to a size between $\frac{1}{2}$ square inch to 1 square inch in size to produce

WO 01/24996

PCT/US99/23007

a decorative burn aspect of firelog 90. Alternatively, one can use waxed corrugated cardboard segments 48a smaller than the preferred range, but this would result in a higher manufacturing cost and the possible introduction of cold joints.

5 It is essential the waxed corrugated cardboard segments 48a used, retain a cellular structure 214. The cellular structure must remain intact in the form of corrugations 210 of cardboard material, which allow air to flow through the waxed corrugated cardboard segment 48a, which thereby results in an efficient and prolonged burn. The waxed corrugated cardboard segments 48a additionally
10 have been found to burn in a manner wherein they may be used as firestarter chips. Since waxed corrugated cardboard segments 48a are fabricated from waxed corrugated cardboard sheets, they contain a first substantially planar member 212 and a second substantially planar member 216 covering corrugations 210 containing a cellular structure 214.

15 Waxed corrugated cardboard segments 48a are compressed to a ratio preferably between 5:1 and 8:1, resulting in a compressed waxed corrugated cardboard segment 48b as depicted in FIG. 72. The range between 5:1 and 8:1 has been determined to be the preferred compression ratio as compressing waxed corrugated cardboard segment 48 beyond this range would cause damage to the
20 cellular structure 214, thus effectively eliminating the effect of corrugations 210. After being compressed in the conveyor compression auger assembly, waxed corrugated cardboard segments 48b are densely packed together during an extrusion process through log die 20 and then cut in generally evenly-spaced sections to form firelogs such as firelog 90 having a generally cylindrical-shaped
25 structure. Biomass may be added in with waxed corrugated cardboard segments 48 during the compression process, including but not limited to saw dust, almond shells, walnut shells, peanut shells, olive pits, cherry pits, coal. The addition of such biomass provides firelog 90 with desired aromatic characteristics when firelogs 90 are burned. Biomass can also serve to increase or decrease the
30 friction level within conveyor compression auger assembly during compression of waxed corrugated cardboard segments 48.

FIG. 72 depicts the compressed waxed corrugated cardboard segments 48b as firelog begins to burn. Corrugations 210 then expand due to the heat,

WO 01/24996

PCT/US99/23007

allowing air to efficiently flow throughout the segments which expand to 48c of FIG. 73 as they burn on the outside of the firelog.

Referring finally to FIG. 74, a flow chart 220 of the manufacturing process for a firelog is generally depicted. The first step 222 involves cutting waxed
5 corrugated cardboard sheet into segments. The second step 224 involves compressing waxed corrugated cardboard segments to a ratio between 5:1 and 8:1. In the third step 226, waxed corrugated cardboard segments are extruded into a continuous log structure. The fourth and final step 228 involves cutting the continuous log structure into individual firelogs.

10 Accordingly, it will be seen that this invention converts standard waxed corrugated cardboard sheets into artificial firelogs by slicing the waxed corrugated cardboard sheets into strips, cutting waxed corrugated cardboard strips into waxed corrugated cardboard segments, and compressing waxed corrugated cardboard segments, while providing for radial disposition and interlocking of the segments,
15 to form an artificial firelog. Although the description above contains many specificities, these should not be construed as limiting the scope of the invention but as merely providing illustrations of some of the presently preferred embodiments of this invention. Thus the scope of this invention should be determined by the appended claims and their legal equivalents.

20

WO 01/24996

PCT/US99/23007

Table 1

Flight	a	f	h	r	s
1	48.4°	5.500	1.239	0.2500	0.2292
2	51.4°	7.299	1.442	0.2500	0.3021
3 a	57.4°	7.776	1.797	0.2500	0.3229
b	--	--	1.873	--	--
c	--	--	2.092	--	--
d	--	--	2.227	--	--
4	57.4°	9.000	2.227	0.2500	0.3750
5	57.4°	4.489	2.227	0.2500	0.4167

WO 01/24996

PCT/US99/23007

Table 2

St No.	Flt	Degree	s	b	p	w	y	t	g
1	1	0-15	0.2292	1.77	0.27	1.43	1.77	1.77	0.250
2	1	15-30	0.2292	1.80	0.48	1.42	1.80	1.80	0.250
3	1	30-45	0.2292	1.82	0.69	1.33	1.82	1.09	0.250
4	1	45-60	0.2292	1.85	0.95	1.23	1.85	0.98	0.250
5	1	60-75	0.2292	1.87	1.02	1.14	1.21	0.94	0.250
6	1	75-90	0.2292	1.90	1.10	1.09	1.11	0.86	0.250
7	1	90-105	0.2292	1.92	1.10	1.09	0.83	0.84	0.250
8	1	105-120	0.2292	1.95	1.10	1.09	0.84	0.75	0.250
9	1	120-135	0.2292	1.97	1.10	1.09	0.63	0.75	0.250
10	1	135-150	0.2292	2.00	0.93	1.10	0.61	0.75	0.250
11	1	150-165	0.2292	2.02	0.67	1.10	0.54	0.75	0.250
12-24	1	165-360	0.2292	2.05-2.32	0.50	1.10	0.54	0.78	0.250
25-48	2	0-360	0.3021	2.34-3.18	0.50	1.10	0.52	0.67	0.125
49-63	3	0-225	0.3229	3.22-3.72	-s-	-s-	-s-	-s-	0.00
64-73	3-4	225-15	0.3229	3.72	-s-	-s-	-s-	-s-	0.00
74-97	4-5	15-15	0.3750	3.72	-s-	-s-	-s-	-s-	0.00
98-107	5	15-165	0.4167	3.72	-s-	-s-	-s-	-s-	0.00

WO 01/24996

PCT/US99/23007

Table 3

Degree	β_1	β_2	β_3
0-15	88.2°	48.1°	51.4°
15-30	100.3°	---	---
30-45	110.8°	---	---
45-60	117.7°	---	---
60-75	126.9°	---	---
75-90	131.2°	---	---

5

The embodiments of the invention in which an exclusive property or privilege is claimed are defined as follows:

1. An artificial firelog material, comprising:
a plurality of waxed cardboard segments with exterior surfaces and a corrugated interior compressed circumferentially in relation to a central longitudinal axis of the firelog; and
wherein the exterior surfaces of at least some of said segments are substantially oriented radially outward in relation to the central longitudinal axis of the firelog.
2. An artificial firelog material as recited in claim 1, wherein said waxed cardboard segments open or expand with heat when burned; and wherein corrugations in said segments channel oxygen throughout the segments.
3. An artificial firelog material as recited in claim 1 or 2, wherein said segments are adhered together in an overlapping configuration.
4. An artificial firelog material as recited in claim 1, 2 or 3, further comprising biomass material incorporated into the artificial firelog material.
5. An artificial firelog material as recited in claim 4, wherein said biomass material is saw dust, almond shells, walnut shells, peanut shells, olive pits, cherry pits, or coal.
6. An artificial firelog material, comprising:
a plurality of waxed cardboard segments with exterior surfaces and a corrugated interior compressed circumferentially in relation to a central longitudinal axis of the firelog;
wherein the exterior surfaces of at least some of said segments are substantially oriented radially outward in relation to the central longitudinal axis of the firelog; and
wherein said segments are adhered together in an overlapping configuration.

7. An artificial firelog material as recited in claim 6, wherein said waxed cardboard segments open or expand with heat when burned and corrugations in said segments channel oxygen throughout the segments.
8. An artificial firelog material as recited in claim 6 or 7, further comprising biomass material incorporated into the artificial firelog material.
9. An artificial firelog material as recited in claim 8, wherein said biomass material is saw dust, almond shells, walnut shells, peanut shells, olive pits, cherry pits, or coal.
10. An artificial firelog material as recited in claim 1 or 4, wherein said waxed cardboard segments are compressed to a ratio approximately between 5:1 and 8:1.
11. An artificial firelog material, comprising:
 - a plurality of waxed corrugated cardboard segments with exterior surfaces, said segments positioned in a longitudinally shaped structure with planar rectangular sides;
 - wherein said structure has a square cross-section and a longitudinal axis;
 - wherein said segments are compressed circumferentially around the longitudinal axis of said structure; and
 - wherein the exterior surfaces of at least some of said segments are oriented outwardly toward the planar rectangular sides and corners of said longitudinally shaped structure.
12. An artificial firelog material as recited in claim 11, wherein said segments are adhered together in an overlapping configuration.
13. An artificial firelog material as recited in claim 11 or 12, wherein said segments are densely compacted together during an extrusion process.

14. An artificial firelog material as recited in claim 11, 12 or 13, wherein said segments are compressed to a ratio approximately between 5:1 and 8:1.




FIG. - 1




FIG. - 2




FIG. - 3




FIG. - 4

5/47




FIG. - 5




FIG. - 6

WO 01/24996

PCT/US99/23007




FIG. - 7

WO 01/24996

PCT/US99/23007

8/47




FIG. - 8




FIG. - 9




FIG. - 10




FIG. - 11




FIG. - 12

WO 01/24996

PCT/US99/23007

10/47




FIG. - 13




FIG. - 14




FIG. - 15




FIG. - 16




FIG. - 17




FIG. - 18

12/47




FIG. - 19




FIG. - 20




FIG. - 21

WO 01/24996

PCT/US99/23007

13/47




FIG. - 22

WO 01/24996

PCT/US99/23007

14/47




FIG. - 23

WO 01/24996

PCT/US99/23007

15/47




FIG. - 24




FIG. - 25

WO 01/24996

PCT/US99/23007

16/47




FIG. - 26

WO 01/24996

PCT/US99/23007

17/47




FIG. - 27




FIG. - 28

WO 01/24996

PCT/US99/23007

18/47




FIG. - 29




FIG. - 30




FIG. - 31




FIG. - 32

WO 01/24996

PCT/US99/23007

20/47




FIG. - 33




FIG. - 34

WO 01/24996

PCT/US99/23007

21/47




FIG. - 35




FIG. - 36

WO 01/24996

PCT/US99/23007

22/47




FIG. - 37




FIG. - 38

WO 01/24996

PCT/US99/23007

23/47




FIG. - 39






FIG. - 40

WO 01/24996

PCT/US99/23007

24/47



WO 01/24996

PCT/US99/23007

25/47




FIG. - 43




FIG. - 44




FIG. - 45

WO 01/24996

PCT/US99/23007

27/47




FIG. - 47




FIG. - 46




FIG. - 49

FIG. - 48




FIG. - 50

WO 01/24996

PCT/US99/23007

30/47




FIG. -- 51

WO 01/24996

PCT/US99/23007

31/47




FIG. - 52




FIG. - 53




FIG. - 54

WO 01/24996

PCT/US99/23007

34/47




FIG. - 56




FIG. - 55




FIG. - 57

WO 01/24996

PCT/US99/23007

36/47




FIG. - 58




FIG. - 59




FIG. - 60

WO 01/24996

PCT/US99/23007

38/47




FIG. - 62




FIG. - 61

WO 01/24996

PCT/US99/23007

39/47




FIG. - 63

WO 01/24996

PCT/US99/23007

40/47




FIG. - 64




FIG. - 65

WO 01/24996

PCT/US99/23007

42/47





FIG. - 66



WO 01/24996

PCT/US99/23007

44/47




FIG. - 68

45/47




FIG. - 69




FIG. - 70




FIG. - 72




FIG. - 73

47/47

220




FIG. - 74

