

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
10 September 2004 (10.09.2004)

PCT

(10) International Publication Number  
**WO 2004/077107 A2**

(51) International Patent Classification<sup>7</sup>: **G02B**

(21) International Application Number:  
PCT/US2004/005380

(22) International Filing Date: 24 February 2004 (24.02.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
60/450,244 24 February 2003 (24.02.2003) US  
10/640,942 13 August 2003 (13.08.2003) US

GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant (for all designated States except US): **ELECTRONIC SCRIPTING PRODUCTS, INC.** [US/US]; 2555 Park Boulevard, Suite 2, Palo Alto, CA 94306 (US).

(72) Inventor: **CARL, Stewart, R.**; 2334 Amherst Street, Palo Alto, CA 94306 (US).

(74) Agent: **ALBOSZTA, Marek**; 2555 Park Boulevard, Suite 2, Palo Alto, CA 94306 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,

**Declarations under Rule 4.17:**

- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for all designations
- as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) for all designations
- of inventorship (Rule 4.17(iv)) for US only

**Published:**

- without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.



WO 2004/077107 A2

(54) Title: IMPLEMENT FOR OPTICALLY INFERRING INFORMATION FROM A PLANAR JOTTING SURFACE

(57) Abstract: The present invention relates to a jotting implement that infers hand-jotted information from a jotting surface. The hand-jotted information is any information marked on the jotting surface as a result of writing, jotting, drawing, sketching, or in any other manner of marking or depositing marks on the jotting surface. Hand-jotted information is also information traced on the jotting surface without leaving any markings thereon or otherwise produced by the motions executed by the jotting implement with respect to the jotting surface while in contact with the jotting surface. The jotting implement has a nib for jotting and an arrangement for determining when the nib is jotting on the jotting surface. Further, the implement has an optical unit for viewing the jotting surface. The implement also has a processing unit for receiving optical data of said jotting surface from the optical unit and determining from it the physical coordinates of the nib with respect to at least one corner of the jotting surface and at least one edge of the jotting surface and/or other landmarks or optically recognizable features on the jotting surface.

5

10

**Implement for Optically Inferring Information from a Planar  
Jotting Surface**

15

**RELATED APPLICATIONS**

This application claims priority from United States Provisional Patent Application No. 60/450,244 filed on February 24<sup>th</sup>, 2003.

**FIELD OF THE INVENTION**

20 The present invention relates generally to acquisition of information written, drawn, sketched or otherwise marked on a jotting or writing surface by a user with the aid of a hand-held implement, such as a writing implement.

**BACKGROUND OF THE INVENTION**

25 The art of writing and drawing is ancient and rich in traditions. Over the ages various types of implements have been used for writing down words as well as drawing, sketching, marking and painting. Most of these implements have a generally elongate shape, an essentially round  
30 cross-section and they are terminated at one end by a

writing nib or tip. They are typically designed to be hand-held and operated by the user's preferred hand (e.g., by the right hand for right-handed persons). More specifically, the user moves the implement across a writing or jotting surface such that the writing nib leaves a visible trace marking its motion on the surface. The marking can be produced by a material deposited from the nib, e.g., through abrasion of the marking material (such as charcoal in the case of a pencil) or by direct wetting of the surface by an ink (as in the case of the pen). The marking can also include any other physical trace left on the surface.

The most widely used writing and drawing implements include pens and pencils while the most convenient jotting surfaces include sheets of paper of various sizes and other generally planar objects capable of being marked. In fact, despite the tremendous advances in sciences and engineering, pen and paper remain among the simplest and most intuitive devices for writing, drawing, marking and sketching even in the electronic age.

The challenge of communicating with electronic devices is in the very input interface to the electronic device. For example, computers take advantage of input devices such as keyboards, buttons, pointer devices, mice and various other types of apparatus that encode motion and convert it to data that the computer can process. Unfortunately, none of these devices are as user-friendly and accepted as pen and paper.

This input interface problem has been recognized in the prior art and a variety of solutions have been proposed. Most of these solutions attempt to derive electronic, i.e., digital data from the motions of a pen on paper or some other writing surface, e.g., a writing tablet. Of these prior art teachings the following references are of note:

U.S. Patents:

4,471,162	4,896,543	5,103,486	5,215,397	5,226,091
5,294,792	5,333,209	5,434,371	5,484,966	5,517,579
5,548,092	5,661,506	5,577,135	5,581,276	5,587,558
5,587,560	5,652,412	5,661,506	5,717,168	5,737,740
5,750,939	5,774,602	5,781,661	5,902,968	5,939,702
5,959,617	5,960,124	5,977,958	6,031,936	6,044,165
6,050,490	6,081,261	6,100,877	6,104,387	6,104,388
6,108,444	6,111,565	6,124,847	6,130,666	6,147,681
6,153,836	6,177,927	6,181,329	6,184,873	6,188,392
6,213,398	6,243,503	6,262,719	6,292,177	6,330,359
6,334,003	6,335,723	6,335,724	6,335,727	6,348,914
6,396,481	6,414,673	6,421,042	6,422,775	6,424,340
6,429,856	6,437,314	6,456,749	6,492,981	6,498,604

10 U.S. Published Applications:

2002-0001029	2002-0028017	2002-0118181	2002-0148655	2002-0158848
2002-0163511				

European Patent Specifications:

0,649,549 B1

15 International Patent Applications:

WO 02/017222 A2	WO 02/058029 A2	WO 02/064380 A1	WO 02/069247 A1
WO 02/084634 A1			

Although the above-referenced teachings provide a number of approaches they are cumbersome to the user. Many of these approaches provide the user with pens that are difficult to handle, impose special writing and/or monitoring conditions and/or they require cumbersome auxiliary systems and devices to track and digitize the information written on the writing surface. Thus, the problem of a user-friendly input interface based on a writing implement has not been solved.

10

#### SUMMARY OF THE INVENTION

The present invention provides a jotting implement that infers hand-jotted information from a jotting surface. For the purposes of this invention, hand-jotted information comprises any information marked on the jotting surface as a result of any of the following actions: writing, jotting, drawing, sketching or in any other manner of marking or depositing marks on the jotting surface. Additionally, hand-jotted information for the purposes of this application also means information traced on the jotting surface without leaving any markings on the jotting surface. The jotting implement has a nib for jotting and an arrangement for determining when the nib is jotting on the jotting surface. Further, the implement has an optical unit for viewing the jotting surface. The optical unit is preferably mounted at a distal end of the implement with respect to the nib and indexed to it. For the purposes of this invention indexed to the nib means that the optical axis of the optical unit is referenced to the nib, e.g., the optical axis of the optical unit passes through the nib. The implement also has a processing unit for receiving optical data of said jotting surface from said

25  
30

optical unit and for determining from said optical data the physical coordinates of the nib with respect to at least one corner of the jotting surface and at least one edge of the jotting surface.

5

It should be noted that in contrast to the prior art the implement of the invention infers the physical coordinates of the nib indirectly, i.e., from the optical data of the jotting surface obtained from the optical unit. Therefore, any optical data about the jotting surface sufficient to make the determination of the physical coordinates of the nib can be used. For example, optical data of all corners or a number of corners, edges or portions thereof can be used. Alternatively, landmarks or any optically recognizable features on the jotting surface can be used as well.

The arrangement for determining when the nib is jotting on the jotting surface preferably comprises a pressure sensitive unit mounted in the jotting implement. Strain gauges, mechanical pressure sensors, piezoelectric elements and other types of arrangements recognizing contact between the nib and the jotting surface can be used for this purpose.

25

In the preferred embodiment the optical unit is an imaging unit for imaging the jotting surface or a portion thereof. It is further preferred that the imaging unit be equipped with a photodetector array for projecting an image of the jotting surface thereon. The processing unit has an edge detection unit or circuit (e.g., firmware in a

30

microprocessor of the processing unit) for detecting edges and corners of the jotting surface in the image.

The jotting implement is further equipped with an image transformation unit for applying one or more transformations to the image. Specifically, the image transformation unit can include appropriate physical optics (e.g., lenses) for correcting the image as well as software routines for correcting the image and performing various operations on the image. For example, the image transformation unit has an image deformation transformer that corrects the image for a plane projection. Alternatively, the image transformation unit has an image deformation transformer that corrects the image for a spherical projection. In the same or a different embodiment, the image transformation unit has an image transformer for determining Euler angles of the jotting implement with respect to the jotting surface.

In the preferred embodiment the corrections and transformations are applied only to the edges and/or corners of the image that are identified by the edge detection unit. In other words, only a part of the image corresponding to the jotting surface and in particular its edges, corners, landmarks or other optically recognizable features and/or their portions are corrected and transformed.

A ratio computation module belonging to the processing unit determines the physical coordinates of the nib from the image. Again, in the preferred embodiment this

determination is made from the relevant part of the image corresponding to the jotting surface and in particular its edges, corners, landmarks or other optically recognizable features and/or their portions.

5

The photodetector array can be any suitable array of photodetectors, including a photodiode or phototransistor array and preferably a CMOS photodetector array. The optics used by the imaging unit can include refractive  
10 and/or reflective optics and preferably include a catadioptric system. In any event, the field of view of the optics should be substantially larger than the area of the jotting surface such that the imaging unit can always detect at least one edge and one corner of the jotting  
15 surface for any possible position of the jotting implement when the nib is in contact with the jotting surface.

In order to determine the physical coordinates of the nib at a sufficient rate to determine what the user has  
20 written, sketched or drawn the implement has a frame control unit. The frame control unit sets a certain frame rate at which the jotting surface is imaged. Preferably, this frame rate is at least 15 Hz, and more preferably it is in excess of 30 Hz.

25

Finally, the jotting implement is provided with a device for communicating the physical coordinates of the nib with an external unit. The device for communicating these coordinates can include any type of data transmission port  
30 including but not limited to infra-red (IR) ports, ultrasound ports, optical ports and the like. The external



unit can be a computer, a hand-held device, a network terminal, a downloading unit, an electronic gateway into a wide area network (WAN) (e.g., the internet) or a local area network (LAN), a storage device, a printer or any other external unit which can store, print, relay and/or  
5 further process the physical coordinates of the nib. It should be noted that, depending on the application and requirements, the physical coordinates of the nib can be processed in real time or not.

10

In the preferred embodiment the implement is further equipped with an arrangement for initializing and recognizing the jotting surface. Of course, the sizes and types of jotting surfaces can also be selected or input by  
15 the user. The arrangement for initializing and recognizing can include the optical unit and processing unit described above and a memory with standard sizes of likely jotting surfaces. For example, when the jotting surfaces are expected to be sheets of paper of standard sizes, the  
20 images of such sheets can be stored in the memory. Preferably, these stored images are taken at well-known positions and orientations of the jotting implement with respect to the jotting surface. In other words, they are taken at known physical coordinates of the nib on the  
25 jotting surface and known spatial orientation of the jotting implement (e.g., at known Euler angles).

The details of the invention will now be explained in the attached detailed description with reference to the  
30 attached drawing figures.

**BRIEF DESCRIPTION OF THE DRAWINGS**

- Fig. 1 is a side view of a jotting implement in accordance with the invention where the jotting implement is shown in the plane of an inclination angle  $\theta$  (Euler angle  $\theta$ ).
- 5 Fig. 2 is a three-dimensional diagram illustrating the physical parameters of the jotting implement of Fig. 1 when in use.
- Fig. 3 is a plan side view of the jotting implement of Fig. 1 illustrating the principle of imaging.
- 10 Fig. 4 is a block diagram of the processing unit of the jotting implement of Fig. 1.
- Fig. 5 is a diagram illustrating the image of the jotting surface projected onto a photodetector array belonging to the imaging unit.
- 15 Fig. 6 is a diagram illustrating the process of edge and/or corner detection applied to the image of the jotting surface.
- Fig. 7A-D are diagrams illustrating the functions performed by the processing unit on the image to determine the orientation of the jotting implement with respect to the jotting surface in terms of Euler angles.
- 20 Fig. 8 is a side view illustrating an alternative embodiment of a jotting implement having an orienting grip.
- 25 Fig. 9 is a diagram illustrating the process of image correction and parametrization.
- Fig. 10 is a diagram illustrating the parameterized corrected image.
- 30

Fig. 11 is a diagram illustrating the parametrized, corrected and transformed image from which the physical coordinates of the nib are determined.

Fig. 12 is a diagram illustrating a correspondence between the image of the jotting surface and the physical jotting surface as can be used for initialization and cross-check purposes.

Fig. 13 illustrates another embodiment of an optical unit using a catadioptric system.

Fig. 14 illustrates the top portion of a writing implement employing the catadioptric system of Fig. 13.

Fig. 15 is a three-dimensional diagram illustrating the use of alternative landmarks and features to determine the physical coordinates of the nib.

#### DETAILED DESCRIPTION

The present invention will be best understood by initially referring to the side view of Fig. 1 illustrating a jotting implement **10** in accordance with the invention and the diagrams of Figs. 2 through 4. Jotting implement **10** shown in Fig. 1 is a pen, more specifically an ink pen, and still more precisely a ball-point pen. However, it will be appreciated that jotting implement **10** can be a marker, a pencil, a brush or indeed any other writing, sketching, drawing or painting implement that can jot information on a jotting surface **12**. Alternatively, jotting implement **10** can also be stylus or any device that jots information on jotting surface **12** by tracing that information without leaving any permanent markings or deformations on the jotting surface. Such jotting surface can include a

pressure-sensitive digitizing tablet or any other surface provided specifically for input into an electronic data processing device. In the present embodiment jotting implement has a shape generally resembling known writing, sketching, drawing, or painting devices. Specifically, 5 jotting implement **10** has an elongate body **14** of generally round cross-section designed to be held in a user's hand **16**.

10 In general, jotting surface **12** is a sheet of planar material on which implement **10** can perform a jotting function as defined above. For geometrical reasons, it is preferable that jotting surface **12** be rectangular. In the present embodiment jotting surface **12** is a sheet of paper 15 of any standard or non-standard dimensions laying flat on a support surface **18**. In cases where jotting surface **12** is a digitizing tablet such as a tablet of a PDA device, a computer screen or any other sturdy surface then support surface **18** may not be required. It is important, however, 20 that jotting surface **12** have optically recognizable features such as corners, edges, landmarks or the like. It is also important that these features not change their position with respect to the remainder of jotting surface **12** during the jotting operation.

25

Implement **10** has a nib **20** terminating in a ball-point **22**. A pressure sensor **24** is mounted proximate nib **20** for determining when nib **20** is jotting. Jotting occurs when ball-point **22** is in contact with jotting surface **12**. 30 Conveniently, pressure sensor **24** is a strain gauge. Alternatively, pressure sensor **24** is a mechanical pressure

sensor or a piezoelectric element. A person skilled in the art will recognize that other pressure sensors can also be used. Implement 10 also has an initialization switch 26. Switch 26 is provided for the user to communicating whether  
5 jotting is occurring on the same jotting surface 12 or on a new jotting surface (not shown).

An optical unit 30 is mounted at a distal end 32 of implement 10. Optical unit 30 is designed for viewing  
10 jotting surface 12 and it has a field of view 34 demarked by a delimiting line that extends beyond jotting surface, as described in more detail below. In the present embodiment optical unit 30 is mounted on three support  
15 members 36. Members 36 can have any construction that ensures mechanical stability and obstructs a negligible portion of field of view 34. Optical unit 30 has an optical axis 39 that is indexed to nib 20. More specifically, optical axis 39 passes through nib 20. Thus, field of view 34 of optical unit 30 is centered on nib 20.  
20 Alternatively, optical axis 39 can be indexed to nib 20 at some predetermined offset. For reasons of symmetry of field of view 34, however, it is preferred that optical unit 30 be indexed to nib 20 by passing optical axis 39 through nib 20 and through the center of ball-point 22.

25 Implement 10 has a device 38 for communicating with an external unit 40 (see Fig. 2). In the present embodiment device 38 is an infra-red (IR) port for transmitting and receiving data encoded in IR radiation 42. Of course, any  
30 type of data transmission port including but not limited to ultrasound ports or optical ports can be used as device 38.

Meanwhile, external unit **40** can be a computer, a hand-held device, a network terminal, a downloading unit, an electronic gateway into a wide area network (WAN) (e.g., the internet) or a local area network (LAN), a storage  
5 device, a printer or any other external unit which can store, print, relay and/or further process the physical coordinates of nib **20**.

Referring now to Fig. 2, the physical parameters of  
10 implement **10** are conveniently described in terms of a Cartesian coordinate system and a polar coordinate system. The origins of these coordinate systems coincide at the position of nib **20** and more specifically at the position where ball-point **22** contacts jotting surface **12**. The  
15 Cartesian system has its X- and Y-axes in the plane of jotting surface **12** and aligned with the width and length of jotting surface **12**. The Z-axis of the Cartesian system is perpendicular or normal to the plane of jotting surface **12**.

20 A number of features **44A**, **44B**, **44C** are defined by corresponding vectors  $v_1$ ,  $v_2$ ,  $v_3$  drawn from the origin of the Cartesian system. In the present case features **44A**, **44B**, **44C** are three corners of jotting surface **12**. Alternatively, features **44** can include any edge **43** of  
25 jotting surface **12** or any other optically recognizable landmark or feature of jotting surface **12**. It should be noted that features produced on jotting surface **12** by the user, including any marks jotted by implement **10**, are legitimate features for this purpose.

30

The polar coordinate system is used to define the orientation of implement **10** with respect to jotting surface **12**. The Z-axis of the polar system is coincident with the Z-axis of the Cartesian system. Since optical axis **39** is indexed to nib **20** it passes through the origins of the two coordinate systems. Thus, in the polar system optical axis **39** defines the polar coordinate  $r$  and the length of  $r$ , i.e.,  $|r|$  is the length of implement **10**. The inclination of implement **10** with respect to the Z-axis is expressed by polar angle  $\theta$ , hereafter referred to as inclination angle  $\theta$ . The angle of rotation of implement **10** about the Z-axis is expressed by polar angle  $\phi$ .

It is preferred that optical unit **30** be an imaging unit, as shown in the plan view of Fig. 3. Specifically, optical unit **30** is preferably an imaging unit capable of imaging objects present in its field of view **34** and in particular imaging jotting surface **12** with relatively low distortion. In the present embodiment imaging unit **30** has refractive imaging optics **46** indicated by lenses **48A**, **48B**. It will be appreciated by a person skilled in the art that suitable refractive imaging optics **46** include lenses which afford a wide field of view with good off-axis optical performance, such as fish-eye lenses or wide-field-of-view lenses. For more specifics on such types of lenses the reader is referred to U.S. Patents 4,203,653; 4,235,520; 4,257,678 as well as the article by James "Jay" Kumler et al., "Fisheye lens designs and their relative performance", SPIE, all of which are herein incorporated by reference.

30

Imaging optics **46** define an image plane **50** as indicated by the dashed line. Imaging unit **30** is further equipped with a photodetector array **52** positioned in image plane **50**. An image **12'** of jotting surface **12** is projected onto array **52** by imaging optics **46**. Preferably, array **52** is a CMOS photodetector array. Of course, other types of photodetector arrays including arrays employing photodiodes or phototransistors of various types can be used as photodetector array **52**. A CMOS photodetector array, however, tends to be more efficient and responsive and it tends to consume less power. In addition CMOS arrays have a small pitch thus enabling high resolution.

Field of view **34** afforded by optics **46** is substantially larger than the area of jotting surface **12**. In fact, field of view **34** is large enough such that image **12'** of entire jotting surface **12** is always projected onto array **52**. This condition holds for any jotting position that may be assumed by jotting implement **10** during a jotting operation performed by the user, such as writing near an edge or corner of jotting surface **12** at a maximum possible inclination angle  $\theta$  (e.g.,  $\theta \approx 40^\circ$ ). Thus, forward and backward portions  $y_1$ ,  $y_2$  of jotting surface **12** are always imaged on array **52** as portions  $y'_1$ ,  $y'_2$  as long as not obstructed by user's hand **16** or by other obstacles.

It is noted that for purposes of clarity primed reference numbers are used herein to denote parts in image space corresponding to parts bearing the same but unprimed reference numbers in physical space. As additional transformations and operations are applied to parts in the



image space, more primes are added to the reference numbers.

Jotting implement **10** has a processing unit **54**, which is illustrated in more detail in Fig 4. Processing unit **54** is designed for receiving optical data of jotting surface **12**. In this embodiment the optical data is represented by image **12'** of jotting surface **12**. From this optical data, processing unit **54** determines the physical coordinates of nib **20** with respect to at least one corner and at least one edge of jotting surface **12**. In the present embodiment processing unit **54** is designed to determine vectors  $v_1$ ,  $v_2$ ,  $v_3$  in the Cartesian coordinate system defined in Fig. 2.

To achieve its function, processing unit **54** is equipped with an image processor **56**, a frame control **58**, a memory **60** as well as an uplink port **62** and a downlink port **64**. Ports **62**, **64** belong to communication device **38**. Image processor **56** preferably includes an edge detection unit **66**, an origin localization unit **68**, an image transformation unit **70** and a ratio computation unit **72**, as better shown in Fig. 5. In addition to these elements, image processor **56** has a demultiplexer **74** for receiving and demultiplexing raw image data **76** containing image **12'**. Data **76** is delivered from the row **78A** and column **78B** multiplexing blocks of array **52**.

During operation, the user moves implement **10**. Once nib **20** of implement **10** is brought in contact with jotting surface **12** pressure sensor **24** activates the acquisition mode of optical unit **30**. In the acquisition mode processing unit

**54** receives optical data i.e. image **12'** of jotting surface **12** as imaged on the pixels of array **52**.

Now, image processor **56** captures raw image data **76** of image **12'** at a certain frame rate. The frame rate is controlled by frame control **58**. The frame rate is fast enough to accurately track the jotting activity of the user. To achieve this the frame rate is set by frame control **58** at 15 Hz or even at 30 Hz or higher.

10

In contrast with the prior art, the information jotted by the user is not determined by inspecting or imaging the information itself. Rather, the jotted information is inferred by determining the physical coordinates of nib **20** or, more precisely of ball-point **22** with respect to optically recognizable features of jotting surface **12**. These recognizable features can include corners, edges or any other landmarks or features produced by the user on jotting surface **12**. To determine all information jotted by the user the physical coordinates of nib **20** with respect to the recognizable features are acquired at the set frame rate whenever the acquisition mode is activated by pressure sensor **24**.

25 In the present embodiment, the physical coordinates of nib **20** are determined with respect to three corners **44A**, **44B** and **44C** of jotting surface **12** parametrized with the aid of vectors  $v_1$ ,  $v_2$  and  $v_3$  (see Fig. 2). To accomplish this goal, processing unit **54** recovers vectors  $v_1$ ,  $v_2$ , and  $v_3$  from imaged vectors  $v'_1$ ,  $v'_2$  and  $v'_3$  of image **12'** (see Fig. 5). This process requires a number of steps.

30

In a first step image processor 56 of processing unit 54 demultiplexes raw image data 76 from row and column blocks 78A, 78B of array 52 with the aid of demultiplexer 74.

5 Next, image processor 56 sends image data 76 to edge detection unit 66. Edge detection unit 66 identifies the edges and corners of image 12' of jotting surface 12. This process is better illustrated in Fig. 6 where unobstructed portions 80' of imaged edges 43' are used for edge

10 detection. For more information on edge detection in images and edge detection algorithms the reader is referred to U.S. Patents 6,023,291 and 6,408,109 and to Simon Baker and Shree K. Nayar, "Global Measures of Coherence for Edge Detector Evaluation", Conference on Computer Vision and

15 Pattern Recognition, June 1999, Vol. 2, pp. 373-379 and J. Canny, "A Computational Approach to Edge Detection", IEEE Transactions on Pattern Analysis and Machine Intelligence, Vol. 8, No. 6, Nov. 1986 for basic edge detection all of which are herein incorporated by reference.

20

In practice, user's hand 16 is an obstruction that obscures a portion of jotting surface 12. Hence, a corresponding shadow 16' is present in image 12'. Another shadow 17' (or a number of shadows) will frequently be produced by other

25 objects covering jotting surface 12 or located between jotting surface 12 and optical unit 30. Such objects typically include the user's other hand and/or body parts such as hair (not shown). For the purposes of the present invention it is only necessary that image 12' have a few

30 unobstructed portions 80' of imaged edges 43', preferably including two or more corners, e.g., 44A', 44B' and 44C' to

enable recovery of vectors  $v_1$ ,  $v_2$  and  $v_3$  and consequent determination of the physical coordinates of nib 20.

Thus, despite shadows 16' and 17' several unobstructed  
5 portions 80' of imaged edges 43' are available to edge  
detection unit 66. A number of pixel groups 82 whose  
optical data 76 can be used by edge detection unit 66 for  
edge detection purposes are indicated. It should be noted  
that in some circumstances a pixel group 83 which is  
10 obscured by a shadow, e.g., by shadow 16' may become  
visible and can then be used to detect corner 44D'.

Edge detection unit 66 recognizes edges 43' and describes  
them in terms of their vector equations or other suitable  
15 mathematical expressions with reference to a center 84 of  
field of view 34. In order to serve as reference, center  
84 is set with the aid of origin localization unit 68.  
This can be performed prior to operating jotting implement  
10, e.g., during first initialization and testing of  
20 jotting implement 10 and whenever re-calibration of origin  
location becomes necessary due to mechanical reasons. The  
initialization can be performed with the aid of any  
suitable algorithm for fixing the center of an imaging  
system. For further information the reader is referred to  
25 Carlo Tomasi and John Zhang, "How to Rotate a Camera",  
Computer Science Department Publication, Stanford  
University and Berthold K.P. Horn, "Tsai's Camera  
Calibration Method Revisited", which are herein  
incorporated by reference and attached as appendices  
30 hereto.

In accordance with the invention center **84** coincides with optical axis because optical unit **30** is indexed to nib **20**. Hence, for any orientation of jotting implement **10** in physical space, i.e., for any value of inclination angle  $\theta$  and polar angle  $\phi$ , center **84** of field of view **34** is always coincident with the position of nib **20** and its image **20'**. Systems having this property are commonly referred to as central systems in the art and they include various types of central panoramic systems and the like. It should be noted that image **20'** of nib **20** is not actually visible in field of view **34**, because body **14** of jotting implement **10** obscures center **84** at all times.

Due to optical effects including aberration associated with imaging optics **46**, the detected portion of image **12'** will exhibit a certain amount of rounding of edges **43'**, as indicated in dashed lines. This rounding can be compensated optically by lenses **48A**, **48B** and/or by any additional lenses (not shown) as well as electronically by processing unit **54**. Preferably, the rounding is accounted for by applying a transformation to detected portion of image **12'** by image transformation unit **70**. For example, image transformation unit **70** has an image deformation transformer based on a plane projection to produce a perspective view. Alternatively, image transformation unit **70** has an image deformation transformer based on a spherical projection to produce a spherical projection. Advantageously, such spherical projection can be transformed to a plane projection with the aid of well-known methods, e.g., as described by Christopher Geyer and Kostas Daniilidis, "A Unifying Theory for Central Panoramic

Systems and Practical Implications", [www.cis.upenn.edu](http://www.cis.upenn.edu),  
Omid Shakernia, et al., "Infinitesimal Motion Estimation  
from Multiple Central Panoramic Views", Department of EECS,  
University of California, Berkeley, and Adnan Ansar and  
5 Kostas Daniilidis, "Linear Pose Estimation from Points or  
Lines", Jet Propulsion Laboratory, California Institute of  
Technology and GRASP Laboratory, University of Pennsylvania  
which are herein incorporated by reference and attached as  
appendices hereto.

10

Now, once image **12'** is recognized and transformed the  
orientation of jotting implement **10** is determined. This  
can be done in a number of ways. For example, when working  
with the spherical projection, i.e., with the spherical  
15 projection of unobstructed portions image **12'**, a direct  
three-dimensional rotation estimation can be applied to  
recover inclination angle  $\theta$  and polar angle  $\phi$ . For this  
purpose a normal view of jotting surface **12** is stored in  
memory **60**, such that it is available to transformation unit  
20 **70** for reference purposes. The transformation then yields  
the Euler angles of jotting implement **10** with respect to  
jotting surface **12** by applying the generalized shift  
theorem. This theorem is related to the Euler theorem  
stating that any motion in three-dimensional space with one  
25 point fixed (in this case the point where nib **20** is in  
contact with jotting surface **12** is considered fixed for the  
duration of each frame) can be described by a rotation  
about some axis. For more information about the shift  
theorem the reader is referred to Ameesh Makadia and Kostas  
30 Daniilidis, "Direct 3D-Rotation Estimation from Spherical  
Images via a Generalized Shift Theorem", Department of

Computer and Information Science, University of Pennsylvania, which is herein incorporated by reference.

Alternatively, when working with a plane projection  
5 producing a perspective view of unobstructed portions of  
image **12'** one can use standard rules of geometry to  
determine inclination angle  $\theta$  and polar angle  $\phi$ . Several  
geometrical methods taking advantage of the rules of  
perspective views can be employed in this case.

10

One geometrical method is shown in Fig. 7A, where entire  
image **12'** is shown for clarity (disregarding obstructed  
portions or filling them in with equations of edges **43'**  
derived in the above step), two edges **43'** are extended to  
15 vanishing point **86**. A connecting line  $\Psi$  from center **84** to  
vanishing point **86** is constructed. A line  $\Sigma$  in the plane  
of inclination angle  $\theta$  is also constructed. Now, the angle  
between lines  $\Psi$  and  $\Sigma$  is equal to polar angle  $\phi$ .  
Meanwhile, the length of line  $\Psi$  from center **84** to  
20 vanishing point **86** is inversely proportional to inclination  
angle  $\theta$ . Preferably, a look-up table with values of  $\Psi$   
corresponding to values of inclination angle  $\theta$  is stored in  
memory **60** to facilitate rapid identification of angle  $\theta$   
during each frame. It should be noted that in order to  
25 keep track of the plane of inclination angle  $\theta$  rotation of  
jotting implement **10** around optical axis **39** has to be  
known. This rotation can be established by providing a key  
e.g., in the form of a grip **90** on jotting implement **10**, as  
shown in Fig. 8. Grip **90** forces hand **16** of the user to  
30 hold jotting implement without rotating it around axis **39**.

Another geometrical method is shown in Fig. 7B, where entire image **12'** is once again shown for clarity. Here, again, two edges **43'** are extended to vanishing point **86**. A connecting line  $\Psi$  from center **84** to vanishing point **86** is constructed. A line  $\Gamma$  in the plane perpendicular to the plane of inclination angle  $\theta$  is also constructed. Now, a line  $\Pi$  is constructed from vanishing point **86** and perpendicular to line  $\Gamma$ . The angle between lines  $\Pi$  and  $\Psi$  is equal to polar angle  $\phi$ . Meanwhile, the length of line  $\Pi$  from intercept with line  $\Gamma$  to vanishing point **86** is inversely proportional to inclination angle  $\theta$ . Preferably, a look-up table with values of  $\Pi$  corresponding to values of inclination angle  $\theta$  is stored in memory **60** to facilitate rapid identification of angle  $\theta$  during each frame. In this embodiment a key-mark **92** on array **52** or on some other part of jotting implement **10** is used to keep track of the plane perpendicular to the plane of inclination angle  $\theta$  and it is indexed to an appropriate grip on the pen, e.g., as the one shown in Fig. 8.

20

Yet another geometrical method is shown in Fig. 7C based on entire image **12'**. Here, connecting line  $\Psi$  is constructed from center **84** to vanishing point **86** defined by two edges **43'**. A second vanishing point **94** is located by extending the other two edges **43'**. Second vanishing point **94** is then joined by line  $\Omega$  with vanishing point **86**. Line  $\Sigma$  is now constructed from center **84** to line  $\Omega$  such that it intersects line  $\Omega$  at a right angle. The angle between lines  $\Psi$  and  $\Sigma$  is equal to polar angle  $\phi$  and either the length of line  $\Psi$  or the length of line  $\Sigma$  (or even the length of line  $\Omega$ ) can be used to derive inclination angle

30



0. Once again, the use of corresponding look-up tables is recommended for rapid processing. It should be noted that this embodiment does not require the use of a key-mark or grip since rotation of jotting implement **10** around optical axis **39** (which is also the center axis of jotting implement **10**) does not affect this geometrical construction.

Still another geometrical method is shown in Fig. 7D. In this case corner angles  $\alpha$ ,  $\beta$ ,  $\gamma$  and  $\delta$  (when unobstructed) as well as the area integral of image **12'** are used to determine  $\theta$  and  $\phi$ . Specifically, the values of corner angles  $\alpha$ ,  $\beta$ ,  $\gamma$  and  $\delta$  uniquely define angle  $\phi$ . Likewise, the values of the area integral uniquely define  $\theta$ . Corresponding look-up tables stored in memory **60** can be used for rapid processing and determination of angles  $\theta$ ,  $\phi$  in this embodiment.

In the case where imaging optics **46** invert image **12'** with respect to the physical orientation of jotting surface **12** image **12'** needs to be inverted, as illustrated in Fig. 9. This inversion can be performed by transformation unit **70** at any point in time. For example, image **12'** can be inverted before applying the above steps for determining  $\theta$  and  $\phi$  or after. If image **12'** is not inverted, then no inversion needs to be performed.

A transformed and inverted (as necessary) image **12''** is illustrated in Fig. 10. At this point vectors  $v''_1$ ,  $v''_2$  and  $v''_3$  are re-computed. An additional vector  $v''_n$  from center **84** to a feature or landmark on an edge **43''** is also shown. Such landmark on edge **43** of jotting surface **12** can be used

instead of a corner for determining the physical coordinates of nib **20**. This is especially important when two corners are obstructed by the user or any object(s) located between jotting surface **12** and optical unit **30**.

5

At this point image **12''** is corrected for rotations by angles  $\theta$  and  $\phi$  to obtain final transformed and corrected image **12'''**, as shown in Fig. 11. This is done by applying the appropriate inverse rotations to transformed (and  
 10 inverted, as the case may be) image **12''**. (These inverse rotations correspond to Euler rotations in physical space of jotting implement **10** with respect to jotting surface **12**. Standard Euler transformation is described in any classical mechanics textbook such as Goldstein, *Classical Mechanics*).

15

Now the physical coordinates of nib **20** can be determined directly from vectors  $v'''_1$ ,  $v'''_2$ ,  $v'''_3$  and/or vector  $v'''_n$ . This function is performed by ratio computation unit **72**, which takes advantage of the fact that the  
 20 proportions of image **12'''** to jotting surface **12** are preserved. Specifically, computation unit **72** employs the following ratios:

$$\frac{x_1}{x_2} = \frac{x'''_1}{x'''_2}, \text{ and}$$

25

$$\frac{y_1}{y_2} = \frac{y'''_1}{y'''_2}.$$

These values can be obtained from the vectors and the scaling factor due to the magnification  $M$  of imaging optics  
 30 **46** can be used, as shown in Fig. 12 as an additional cross-

check and constraint to ensure that the values obtained are correct.

Jotting implements according to the invention admit of  
5 numerous other embodiments. For example, an alternative  
optical unit **100** employing a catadioptric system with a  
parabolic (or hyperbolic) mirror **102** and a lens **104** is  
shown in Fig. 13. The construction of optical unit **100** has  
to be altered to accommodate optical unit **100** on a jotting  
10 implement **108** (only top part shown) as in Fig. 14. In this  
embodiment a photodetector array **106** is placed at a distal  
end **109** of a jotting implement **108**. Support members **110**  
are extended with extensions **111** in this embodiment.

15 Jotting implement **10** can take advantage of features and  
landmarks other than corners and edges of a jotting surface  
**120**. For example, as shown in Fig. 15, jotting implement  
takes advantage of a feature **122** produced by the user.  
Feature **122** is in fact a letter "A" written by the user.  
20 In the present case a particularly easy-to-locate point on  
the letter (e.g., a point yielding high contrast for easy  
detection and tracking) is used for tracking and a vector  
 $v_r$  is constructed to this point from the origin of the  
Cartesian coordinate system. Jotting implement **10** also  
25 takes advantage of a landmark **124** located along an edge  
**126**. A vector  $v_s$  is constructed to landmark **122** from the  
origin. Finally, implement **10** uses a corner **128** of jotting  
surface **120** identified by corresponding vector  $v_q$ .

30 In this embodiment, during operation, edge detection  
algorithms described above and any other algorithms for

detecting high-contrast points are applied to localize the lines and corners in the image and locate feature **122**, landmark **124** and corner **128**. Then, angles  $\theta$ ,  $\phi$  are determined and the corresponding transformations applied to imaged vectors  $v'_q$ ,  $v'_r$  and  $v'_s$  of the image of jotting surface **120**, as described above. The physical coordinates of nib **120** are determined from the transformed vectors.

Of course, a person skilled in the art will recognize that the number of features and landmarks tracked will generally improve the accuracy of determining physical coordinates of nib **20** on jotting surface **120**. Thus, the more landmarks and features are tracked, the more processing effort will be required. If real-time operation of jotting implement **10** is required, e.g., in cases where the jotting action is transmitted from jotting implement **10** to a receiver in real time, the number of features and landmarks should be limited. Alternatively, if the information jotted down can be downloaded by the user at a later time and/or no real-time processing is required, then more landmarks and features can be used to improve the accuracy with which the physical coordinates of nib **20** are determined. This will generally lead to an improved resolution of jotting surface **120**. It should also be kept in mind, that the features and landmarks have to provide absolute references, i.e., their positions on jotting surface **120** cannot change in time. However, it should be remembered that the landmarks or features being used for determining the physical coordinates of nib **20** need not be the same from frame to frame.

It will be evident to a person skilled in the art that the present invention admits of various other embodiments.

1 Claims:

2

3 1. A jotting implement for inferring hand-jotted  
4 information from a jotting surface, said jotting  
5 implement comprising:

6 a) a nib for jotting;

7 b) a means for determining when said nib is jotting on  
8 said jotting surface;

9 c) an optical unit for viewing said jotting surface,  
10 said optical unit being indexed to said nib; and

11 d) a processing unit for receiving optical data of  
12 said jotting surface from said optical unit and for  
13 determining from said optical data physical  
14 coordinates of said nib with respect to at least  
15 one corner of said jotting surface and at least one  
16 edge of said jotting surface.

17

1 2. The jotting implement of claim 1, wherein said  
2 optical unit is an imaging unit for imaging said  
3 jotting surface.

1 3. The jotting implement of claim 2, wherein said  
2 imaging unit further comprises a photodetector  
3 array whereon an image of said jotting surface  
4 is projected.

5

1 4. The jotting implement of claim 3, wherein  
2 said processing unit further comprises an  
3 edge detection unit for detecting edges and  
4 corners of said jotting surface in said  
5 image.

6

- 1           5. The jotting implement of claim 3, further  
2           comprising an image transformation unit for  
3           applying at least one transformation to  
4           said image.  
5
- 1           6. The jotting implement of claim 5,  
2           wherein said image transformation unit  
3           comprises an image deformation  
4           transformer based on a plane projection.  
5
- 1           7. The jotting implement of claim 5,  
2           wherein said image transformation unit  
3           comprises an image deformation  
4           transformer based on a spherical  
5           projection.  
6
- 1           8. The jotting implement of claim 5,  
2           wherein said image transformation unit  
3           comprises an image transformer for  
4           determining Euler angles of said jotting  
5           implement with respect to said jotting  
6           surface.  
7
- 1           9. The jotting implement of claim 3, wherein  
2           said photodetector array is a CMOS  
3           photodetector array.  
4
- 1           10. The jotting implement of claim 2, wherein said  
2           imaging unit produces a perspective projection  
3           of said jotting surface.  
4

1           11. The jotting implement of claim 10, wherein  
2           at least one angle associated with an  
3           orientation of said jotting implement with  
4           respect to said jotting surface is  
5           determined from said perspective  
6           projection.

1           12. The jotting implement of claim 11,  
2           wherein said at least one angle  
3           comprises an inclination angle  $\theta$  and a  
4           polar angle  $\phi$ .

1           13. The jotting implement of claim 2, wherein said  
2           processing unit further comprises a ratio  
3           computation module for determining said  
4           physical coordinates from said image.

1           14. The jotting implement of claim 2, wherein said  
2           imaging unit comprises refractive imaging  
3           optics.

1           15. The jotting implement of claim 14, wherein  
2           said refractive imaging optics have a field  
3           of view substantially larger than an area  
4           of said jotting surface.

1           16. The jotting implement of claim 2, wherein said  
2           imaging unit comprises reflective imaging  
3           optics.

4



1           17. The jotting implement of claim 16, wherein  
2           said reflective imaging optics have a field  
3           of view substantially larger than an area  
4           of said jotting surface.

5

1           18. The jotting implement of claim 2, further  
2           comprising a frame control for imaging said  
3           jotting surface at a predetermined frame rate.

4

1           19. The jotting implement of claim 1, wherein said  
2           means for determining when said nib is jotting is  
3           selected from the group of strain gauges,  
4           mechanical pressure sensors, piezoelectric  
5           elements.

6

1           20. The jotting implement of claim 1, further  
2           comprising a means for communicating said physical  
3           coordinates with an external unit.

4

1           21. The jotting implement of claim 1, further  
2           comprising a means for initializing and recognizing  
3           said jotting surface.

4

1           22. The jotting implement of claim 1, wherein said  
2           optical unit is mounted on a distal end of said  
3           jotting implement.

4

1           23. A jotting implement for inferring information from a  
2           jotting surface, said jotting implement comprising:  
3           a) a jotting end having a nib for jotting;

- 4       b) a means for determining when said nib is jotting on  
5           said jotting surface;
- 6       c) a distal end having an optical unit for viewing  
7           said jotting surface, said optical unit being  
8           indexed to said nib; and
- 9       d) a processing unit for receiving optical data of  
10           said jotting surface from said optical unit and for  
11           determining from said optical data physical  
12           coordinates of said nib with respect to at least  
13           two corners of said jotting surface.

14

1   24. A jotting implement for optically capturing handwritten  
2       information from a jotting surface, said jotting  
3       implement comprising:

- 4       a) a jotting end having a nib for jotting;
- 5       b) a means for determining when said nib is jotting on  
6           said jotting surface;
- 7       c) a distal end having an optical unit for viewing  
8           said jotting surface, said optical unit being  
9           indexed to said nib; and
- 10       d) a processing unit for receiving optical data of  
11           said jotting surface from said optical unit and for  
12           determining from said optical data physical  
13           coordinates of said nib with respect to at least  
14           two landmarks on said jotting surface.

15

1       25. The jotting implement of claim 24, wherein said at  
2       least two landmarks are markings created by a used  
3       on said jotting surface.

4

1           26. The jotting implement of claim 25, wherein said  
2           markings comprise hand-jotting of said user.

3  
1           27. The jotting implement of claim 24, wherein said  
2           landmarks further comprise data about said jotting  
3           surface.

4  
1           28. The jotting implement of claim 27, wherein said  
2           jotting surface comprises a sheet of paper and  
3           said data indicates a size of said sheet of  
4           paper.

5  
1   29. A jotting implement for inferring hand-jotted  
2   information from a jotting surface, said jotting  
3   implement comprising:  
4   a) a nib for jotting;  
5   b) a means for determining when said nib is jotting on  
6   said jotting surface;  
7   c) an optical unit for viewing said jotting surface,  
8   said optical unit being indexed to said nib; and  
9   d) a processing unit for receiving optical data of  
10   said jotting surface from said optical unit and for  
11   determining from said optical data physical  
12   coordinates of said nib with respect to at least  
13   two corners of said jotting surface.

14

1/14




FIG. 1




FIG. 2

3/14




FIG. 3




FIG. 4




FIG. 5

5/14




FIG. 6



6/14




FIG. 7A

7/14





FIG. 8




Look-up Table

$\Pi$	$\theta$
$\infty$	$0^\circ$
.	.
.	.
.	.
0	$90^\circ$

FIG. 7B



9/14



Look-up  
Table 1

$\alpha$	$\beta$	$\gamma$	$\delta$	$\phi$
$0^\circ$				$0^\circ$
.	.....			.
.				.
.				.
$90^\circ$				$360^\circ$

Look-up  
Table 2

$\int Ad\eta$	$\theta$
area	$0^\circ$
.	.
.	.
.	.
.	$45^\circ$

FIG. 7D

10/14




FIG. 9

11/14




FIG. 10




FIG. 11

12/14




FIG. 12

13/14




FIG. 13




FIG. 14



14/14




FIG. 15