



(51) International Patent Classification:
H04N 7/15 (2006.01) *H04N 7/14* (2006.01)

(21) International Application Number:
PCT/US2009/001070

(22) International Filing Date:
16 February 2009 (16.02.2009)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
12/031,209 14 February 2008 (14.02.2008) US

(71) Applicant (for all designated States except US): **CISCO TECHNOLOGY, INC.** [US/US]; 170 West Tasman Drive, San Jose, CA 95134-1706 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **CHEN, Wen-Hsiung** [US/US]; 668 Inverness Way, Sunnyvale, CA 94087 (US). **BUCKINGHAM, Patrik** [US/US]; 3700 Wild Turkey Lane, Gilroy, CA 95020 (US). **PRASAD, Chandrodaya** [US/US]; 1119 Reed Avenue Apt. B, Sunnyvale, CA 94086 (US). **MIRIYALA, Prasad** [US/US]; 4500 Alvarado Blvd., Union City, CA 94587 (US).

(74) Agent: **PATENT CAPITAL GROUP - CISCO**; 6119 Mccommas, Dallas, TX 75214 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

— as to the identity of the inventor (Rule 4.17(i))

Published:

— without international search report and to be republished upon receipt of that report (Rule 48.2(g))

(54) Title: METHODS AND SYSTEMS FOR OPTIMIZED PROCESSING IN A TELEPRESENCE SYSTEM FOR 360 DEGREE VIDEO CONFERENCING TECHNICAL FIELD




FIG. 1

(57) Abstract: systems and methods for image processing, comprising receiving a video frame, coding a first portion of the video frame at a different quality than a second portion of the video frame, based on an optical property, and displaying the video frame.

**METHODS AND SYSTEMS FOR OPTIMIZED PROCESSING IN A TELEPRESENCE
SYSTEM FOR 360 DEGREE VIDEO CONFERENCING**

TECHNICAL FIELD

[0001] The invention generally relates to telecommunications and more specifically to video conferencing.

BACKGROUND

[0002] Telepresence systems, featured by the life-size, high definition (HD) video and stereo quality audio, provide a lifelike face-to-face interaction experience to people who are at distances. It delivers a unique, "in-person" experience over the converged network. Using advanced visual, audio, and collaboration technologies, these "Telepresence" applications deliver real-time, face-to-face interactions between people and places in their work and personal lives. In some cases, these products use a room-within-a-room environment along with life-size images, and high-definition resolution with spatial and discrete audio to create a live, face-to-face meeting around a single "virtual" table.

[0003] A drawback of current Telepresence systems is the inability to provide a 360° view of the participants in a conference room. In current systems all the participants in the conference have to be located on the same side facing the camera. If there is a round-table conference and the participants are spread all around the table, the cameras just offer one view and do not offer a 360° view of all the participants in the conference.

[0004] Also, in current systems these "virtual" meeting rooms have to be specifically arranged for Telepresence functionality. Typically the arrangements force all the local participants to sit in a row, with cameras and displays opposite them. This typical arrangement cuts the room in half and makes it suitable only for Telepresence.

[0005] Therefore, it is desirable to have a multipoint conference system where local participants are able to sit around a conference table, as they

would naturally. New approaches are needed in three areas, 1) room, camera and display arrangements; 2) Image capture and presentation techniques, and 3) Image and data processing specifically to support a 360° view.

SUMMARY

[0006] Described herein are embodiments of systems and methods for image processing in a Telepresence system. In one embodiment, the methods can comprise receiving a video frame, coding a first portion of the video frame at a different quality than a second portion of the video frame, based on an optical property, and displaying the video frame.

[0007] Additional advantages will be set forth in part in the description which follows or may be learned by practice. The advantages will be realized and attained by means of the elements and combinations particularly pointed out in the appended claims. It is to be understood that both the foregoing general description and the following detailed description are examples and explanatory only and are not restrictive, as claimed.

BRIEF DESCRIPTION OF THE DRAWINGS

[0008] The accompanying drawings, which are incorporated in and constitute a part of this specification and are not drawn to scale, illustrate embodiments and together with the description, serve to explain the principles of the methods and systems:

Figure 1 illustrates a communications system that includes two endpoints engaged in a video conference;

Figures 2a-2b illustrate endpoints that use cameras and multiple view display devices to concurrently provide local participants with perspective-dependent views of remote participants;

Figure 3 is an example illustration of a multi-point videoconferencing system having two endpoints showing two triples talking to each other, which can be referred to as a 2x3 conference;

Figure 4 shows a multipoint conference occurring between four people in different locations, which can be referred to as a 4x1 conference;

Figure 5a-5c illustrate an example of a multi-point videoconferencing system having two endpoints showing a group of six participants at one endpoint talking to one participant at another endpoint;

Figure 6 illustrates an example panoramic lens and a panoramic image;

Figure 7 is an example flowchart for image processing in a videoconferencing system; and

Figure 8 is an illustration of an embodiment of a multi-point videoconferencing system.

DETAILED DESCRIPTION

[0009] Before the present methods and systems are disclosed and described, it is to be understood that the methods and systems are not limited to specific synthetic methods, specific components, or to particular compositions, as such may, of course, vary. It is also to be understood that the terminology used herein is for the purpose of describing particular embodiments only and is not intended to be limiting.

[0010] As used in the specification and the appended claims, the singular forms "a," "an" and "the" include plural referents unless the context clearly dictates otherwise. Ranges may be expressed herein as from "about" one particular value, and/or to "about" another particular value. When such a range is expressed, another embodiment includes from the one particular value and/or to the other particular value. Similarly, when values are expressed as approximations, by use of the antecedent "about," it will be understood that the particular value forms another embodiment. It will be further understood that the endpoints of each of the ranges are significant both in relation to the other endpoint, and independently of the other endpoint.

[0011] "Exemplary" as used herein means "an example of" and is not meant to convey a sense of an ideal or preferred embodiment.

[0012] “Optional” or “optionally” means that the subsequently described event or circumstance may or may not occur, and that the description includes instances where said event or circumstance occurs and instances where it does not.

[0013] The present methods and systems may be understood more readily by reference to the following detailed description of preferred embodiments and the Examples included therein and to the Figures and their previous and following description.

[0014] **FIG. 1** illustrates a communications system, indicated generally at **10**, that includes two endpoints engaged in a video conference. As illustrated, communications system **10** includes network **12** connecting endpoints **14** and a videoconference manager **16**. While not illustrated, communications system **10** may also include any other suitable elements to facilitate video conferences.

[0015] In general, during a video conference, a display at a local endpoint **14** is configured to concurrently display multiple video streams of a remote endpoint **14**. These video streams may each include an image of the remote endpoint **14** as seen from different angles or perspectives. In some instances, positions at the local endpoints can be unoccupied or the camera angle may not be optimized for participants in occupied positions. By reconfiguring cameras at a local endpoint, images of empty positions can be prevented and participant gaze can be improved, which may result in a more realistic video conferencing experience.

[0016] Network **12** interconnects the elements of communications system **10** and facilitates video conferences between endpoints **14** in communications system **10**. While not illustrated, network **12** may include any suitable devices to facilitate communications between endpoints **14**, videoconference manager **16**, and other elements in communications system **10**. Network **12** represents communication equipment including hardware and any appropriate controlling logic for interconnecting elements coupled to or within network **12**. Network **12** may include a local area network (LAN), metropolitan area network (MAN), a wide area network (WAN), any other

public or private network, a local, regional, or global communication network, an enterprise intranet, other suitable wireline or wireless communication link, or any combination of any suitable network. Network 12 may include any combination of gateways, routers, hubs, switches, access points, base stations, and any other hardware or software implementing suitable protocols and communications.

[0017] Endpoints 14 (or just "points") represent telecommunications equipment that supports participation in video conferences. A user of communications system 10 may employ one of endpoints 14 in order to participate in a video conference with another one of endpoints 14 or another device in communications system 10. In particular embodiments, endpoints 14 are deployed in conference rooms at geographically remote locations. Endpoints 14 may be used during a video conference to provide participants with a seamless video conferencing experience that aims to approximate a face-to-face meeting. Each endpoint 14 may be designed to transmit and receive any suitable number of audio and/or video streams conveying the sounds and/or images of participants at that endpoint 14. Endpoints 14 in communications system 10 may generate any suitable number of audio, video, and/or data streams and receive any suitable number of streams from other endpoints 14 participating in a video conference. Moreover, endpoints 14 may include any suitable components and devices to establish and facilitate a video conference using any suitable protocol techniques or methods. For example, Session Initiation Protocol (SIP) or H.323 may be used. Additionally, endpoints 14 may support and be interoperable with other video systems supporting other standards such as H.261, H.263, and/or H.264, as well as with pure audio telephony devices. As illustrated, endpoints 14 include a controller 18, memory 20, network interface 22, microphones 24, speakers 26, cameras 28, and displays 30. Also, while not illustrated, endpoints 14 may include any other suitable video conferencing equipment, for example, a speaker phone, a scanner for transmitting data, and a display for viewing transmitted data.

[0018] Controller 18 controls the operation and administration of endpoint

14. Controller **18** may process information and signals received from other elements such as network interface **22**, microphones **24**, speakers **26**, cameras **28**, and displays **30**. Controller **18** may include any suitable hardware, software, and/or logic. For example, controller **18** may be a programmable logic device, a microcontroller, a microprocessor, a processor, any suitable processing device, or any combination of the preceding. Memory **20** may store any data or logic used by controller **18** in providing video conference functionality. In some embodiments, memory **20** may store all, some, or no data received by elements within its corresponding endpoint **14** and data received from remote endpoints **14**. Memory **20** may include any form of volatile or non-volatile memory including, without limitation, magnetic media, optical media, random access memory (RAM), read-only memory (ROM), removable media, or any other suitable local or remote memory component. Network interface **22** may communicate information and signals to and receive information and signals from network **12**. Network interface **22** represents any port or connection, real or virtual, including any suitable hardware and/or software that allow endpoint **14** to exchange information and signals with network **12**, other endpoints **14**, videoconference manager **16**, and/or any other devices in communications system **10**.

[0019] Microphones **24** and speakers **26** generate and project audio streams during a video conference. Microphones **24** provide for audio input from users participating in the video conference. Microphones **24** may generate audio streams from received sound waves. Speakers **26** may include any suitable hardware and/or software to facilitate receiving audio stream(s) and projecting the received audio stream(s) so that they can be heard by the local participants. For example, speakers **26** may include high-fidelity speakers. Endpoint **14** may contain any suitable number of microphones **24** and speakers **26**, and they may each be associated with any suitable number of participants.

[0020] Cameras **28** and displays **30** generate and project video streams during a video conference. Cameras **28** may include any suitable hardware

and/or software to facilitate capturing an image of one or more local participants and the surrounding area as well as sending the image to remote participants. Each video signal may be transmitted as a separate video stream (e.g., each camera **28** transmits its own video stream). In particular embodiments, cameras **28** capture and transmit the image of one or more users **30** as a high-definition video signal. Displays **30** may include any suitable hardware and/or software to facilitate receiving video stream(s) and displaying the received video streams to participants. For example, displays **30** may include a notebook PC, a wall mounted monitor, a floor mounted monitor, or a free standing monitor. In particular embodiments, one or more of displays **30** are plasma display devices or liquid crystal display devices. Endpoint **14** may contain any suitable number of cameras **28** and displays **30**, and they may each be associated with any suitable number of local participants.

[0021] While each endpoint **14** is depicted as a single element containing a particular configuration and arrangement of modules, it should be noted that this is a logical depiction, and the constituent components and their functionality may be performed by any suitable number, type, and configuration of devices. In the illustrated embodiment, communications system **10** includes two endpoints **14a**, **14b**, but it is to be understood that communications system **10** may include any suitable number of endpoints **14**.

[0022] Videoconference manager **16** generally coordinates the initiation, maintenance, and termination of video conferences between endpoints **14**. Video conference manager **16** may obtain information regarding scheduled video conferences and may reserve devices in network **12** for each of those conferences. In addition to reserving devices or resources prior to initiation of a video conference, videoconference manager may monitor the progress of the video conference and may modify reservations as appropriate. Also, video conference manager **16** may be responsible for freeing resources after a video conference is terminated. Although video conference manager **16** has been illustrated and described as a single device connected to network

12, it is to be understood that its functionality may be implemented by any suitable number of devices located at one or more locations in communication system **10**.

[0023] In an example operation, one of endpoints **14a**, **14b** initiates a video conference with the other of endpoints **14a**, **14b**. The initiating endpoint **14** may send a message to video conference manager **16** that includes details specifying the time of, endpoints **14** to participate in, and estimated duration of the desired video conference. Video conference manager **16** may then reserve resources in network **12** and may facilitate the signaling required to initiate the video conference between endpoint **14a** and endpoint **14b**. During the video conference, endpoints **14a**, **14b** may exchange one or more audio streams, one or more video streams, and one or more data streams. In particular embodiments, endpoint **14a** may send and receive the same number of video streams as endpoint **14b**. In certain embodiments, each of endpoints **14a**, **14b** send and receive the same number of audio streams and video streams. In some embodiments, endpoints **14a**, **14b** send and receive more video streams than audio streams.

[0024] During the video conference, each endpoint **14a**, **14b** may generate and transmit multiple video streams that provide different perspective-dependent views to the other endpoint **14a**, **14b**. For example, endpoint **14a** may generate three video streams that each provide a perspective-dependent view of participants at endpoint **14a**. These may show the participants at endpoint **14a** from three different angles, e.g., left, center, and right. After receiving these video streams, endpoint **14b** may concurrently display these three video streams on a display so that participants situated to the left of the display view one of the video streams, while participants situated directly in front of the display view a second of the video streams. Likewise, participants situated to the right of the display may view the third of the video streams. Accordingly, endpoint **14b** may display different perspective-dependent views of remote participants to local participants. By providing different images to different participants, local participants may be able to more easily interpret the meaning of certain

nonverbal clues (e.g., eye gaze, pointing) while looking at a two-dimensional image of a remote participant.

[0025] When the participants decide that the video conference should be terminated, endpoint **14a** or endpoint **14b** may send a message to video conference manager **16**, who may then un-reserve the reserved resources in network **12** and facilitate signaling to terminate the video conference. While this video conference has been described as occurring between two endpoints – endpoint **14a** and endpoint **14b** – it is to be understood that any suitable number of endpoints **14** at any suitable locations may be involved in a video conference.

[0026] An example of a communications system with two endpoints engaged in a video conference has been described. This example is provided to explain a particular embodiment and is not intended to be all inclusive. While system **10** is depicted as containing a certain configuration and arrangement of elements, it should be noted that this is simply a logical depiction, and the components and functionality of system **10** may be combined, separated and distributed as appropriate both logically and physically. Also, the functionality of system **10** may be provided by any suitable collection and arrangement of components.

[0027] **FIG. 2a** and **FIG. 2b** illustrate endpoints, indicated generally at **50** and **70**, that use cameras and multiple view display devices to concurrently provide local participants with perspective-dependent views of remote participants. As used throughout this disclosure, “local” and “remote” are used as relational terms to identify, from the perspective of a “local” endpoint, the interactions between and operations and functionality within multiple different endpoints participating in a video conference. Accordingly, the terms “local” and “remote” may be switched when the perspective is that of the other endpoint.

[0028] **FIG. 2a** illustrates an example of a setup that may be provided at endpoint **50**. In particular embodiments, endpoint **50** is one of endpoints **14**. As illustrated, endpoint **50** includes a table **52**, three participants **54**, three displays **56**, and three camera clusters **58**. While not illustrated, endpoint **50**

may also include any suitable number of microphones, speakers, data input devices, data output devices, and/or any other suitable equipment to be used during or in conjunction with a video conference.

[0029] As illustrated, participants **54a**, **54b**, **54c** are positioned around one side of table **52**. On the other side of table **52** sits three displays **56d**, **56e**, **56f**, and one of camera clusters **58d**, **58e**, **58f** is positioned above each display **56d**, **56e**, **56f**. In the illustrated embodiment, each camera cluster **58** contains three cameras, with one camera pointed in the direction of each of the local participants **54a**, **54b**, **54c**. While endpoint **50** is shown having this particular configuration, it is to be understood that any suitable configuration may be employed at endpoint **50** in order to facilitate a desired video conference between participants at endpoint **50** and participants at a remote endpoint **14**. As an example, camera clusters **58** may be positioned below or behind displays **56**. Additionally, endpoint **50** may include any suitable number of participants **54**, displays **56**, and camera clusters **58**.

[0030] In the illustrated embodiment, each display **56d**, **56e**, **56f** shows one of the remote participants **54d**, **54e**, **54f**. Display **56d** shows the image of remote participant **54d**; display **56e** shows the image of remote participant **54e**; and display **56f** shows the image of remote participant **54f**. These remote participants may be participating in the video conference through a remote endpoint **70**, as is described below with respect to FIG. 2b. Using traditional methods, each local participant **54a**, **54b**, **54c** would see the same image of each remote participant **54**. For example, when three different individuals look at a traditional television screen or computer monitor, each individual sees the same two-dimensional image as the other two individuals. However, when multiple individuals see the same image, they may be unable to distinguish perspective-dependent non-verbal clues provided by the image. For example, remote participant **54** may point at one of the three local participants **54a**, **54b**, **54c** to indicate to whom he is speaking. If the three local participants **54a**, **54b**, **54c** view the same two-dimensional image of the remote participant **54**, it may be difficult to determine which of the local participants **54** has been selected by the remote participant **54** because

the local participants **54** would not easily understand the non-verbal clue provided by the remote participant **54**.

[0031] However, displays **56** are configured to provide multiple perspective-dependent views to local participants **54**. As an example, consider display **56e**, which shows an image of remote participant **54e**. In the illustrated embodiment, display **56e** concurrently displays three different perspective-dependent views of remote participant **54e**. Local participant **54a** sees view A; local participant **54b** sees view B; and participant **54c** sees view C. Views A, B, and C all show different perspective-dependent views of remote participant **54e**. View A may show an image of remote participant **54e** from the left of remote participant **54e**. Likewise, views B and C may show an image of remote participant **54e** from the center and right, respectively, of remote participant **54e**. In particular embodiments, view A shows the image of remote participant **54e** that would be seen from a camera placed substantially near the image of local participant **54a** that is presented to remote participant **54e**. Accordingly, when remote participant **54e** looks at the displayed image of local participant **54a**, it appears (to local participant **54a**) as if remote participant **54e** were looking directly at local participant **54a**. Concurrently, and by similar techniques, views B and C (shown to participants **54b** and **54c**, respectively) may see an image of remote participant **54e** that indicated that remote participant **54e** was looking at local participant **54a**.

[0032] Camera clusters **58** generate video streams conveying the image of local participants **54a**, **54b**, **54c** for transmission to remote participants **54d**, **54e**, **54f**. These video streams may be generated in a substantially similar way as is described below in **FIG. 2b** with respect to remote endpoint **70**. Moreover, the video streams may be displayed by remote displays **56a**, **56b**, **56c** in a substantially similar way to that previously described for local displays **56d**, **56e**, **56f**.

[0033] **FIG. 2b** illustrates an example of a setup that may be provided at the remote endpoint described above, indicated generally at **70**. In particular embodiments, endpoint **70** is one of endpoints **14a**, **14b** in communication

system 10. As illustrated, endpoint 70 includes a table 72, participants 54d, 54e, and 54f, displays 56a, 56b, 56c, and camera clusters 58.

[0034] In the illustrated embodiment, three participants 54d, 54e, 54f local to endpoint 70 sit on one side of table 72 while three displays 56a, 56b, and 56c are positioned on the other side of table 72. Each display 56a, 56b, and 56c shows an image of a corresponding participant 54 remote to endpoint 70. These displays 56a, 56b, and 56c may be substantially similar to displays 56d, 56e, 56f at endpoint 50. These displayed participants may be the participants 54a, 54b, 54c described above as participating in a video conference through endpoint 50. Above each display 56 is positioned a corresponding camera cluster 58. While endpoint 70 is shown having this particular configuration, it is to be understood that any suitable configuration may be employed at endpoint 70 in order to facilitate a desired video conference between participants at endpoint 70 and a remote endpoint 14 (which, in the illustrated embodiment, is endpoint 50). As an example, camera clusters 58 may be positioned below or behind displays 56. Additionally, endpoint 70 may include any suitable number of participants 54, displays 56, and camera clusters 58.

[0035] As illustrated, each camera cluster 58a, 58b, 58c includes three cameras that are each able to generate a video stream. Accordingly, with the illustrated configuration, endpoint 70 includes nine cameras. In particular embodiments, fewer cameras are used and certain video streams or portions of a video stream are synthesized using a mathematical model. In other embodiments, more cameras are used to create multiple three dimensional images of participants 54. In some embodiments, the cameras in camera clusters 58 are cameras 28. In some instances, single cameras can be used. In some instances the single cameras are moveable and can be remotely controlled.

[0036] In each camera cluster 58, one camera is positioned to capture the image of one of the local participants 54d, 54e, 54f. Accordingly, each local participant 54d, 54e, 54f has three cameras, one from each camera cluster 58, directed towards him or her. For example, three different video streams

containing an image of participant **54e** may be generated by the middle camera in camera cluster **58a**, the middle camera in camera cluster **58b**, and the middle camera in camera cluster **58c**, as is illustrated by the shaded cameras. The three cameras corresponding to local participant **54e** will each generate an image of participant **54e** from a different angle. Likewise, three video streams may be created to include different perspectives of participant **54d**, and three video streams may be created to include different perspectives of participant **54f**. However, it may be desirable to have a video stream from only one camera (e.g. turning off camera clusters **58d** and **58e** when imaging participant **54e**), not image positions at the endpoint that are not occupied, or to optimize the direction and angle of any of the cameras to facilitate be able to more easily interpret non-verbal cues, such as eye gaze and pointing.

[0037] Particular embodiments of endpoints **50**, **70** and their constituent components have been described and are not intended to be all inclusive. While these endpoints **50**, **70** are depicted as containing a certain configuration and arrangement of elements, components, devices, etc., it should be noted that this is simply an example, and the components and functionality of each endpoint **50**, **70** may be combined, separated and distributed as appropriate both logically and physically. In particular embodiments, endpoint **50** and endpoint **70** have substantially similar configurations and include substantially similar functionality. In other embodiments, each of endpoints **50**, **70** may include any suitable configuration, which may be the same as, different than, or similar to the configuration of another endpoint participating in a video conference. Moreover, while endpoints **50**, **70** are described as each including three participants **54**, three displays **56**, and three camera clusters **58**, endpoints **50**, **70** may include any suitable number of participant **54**, displays **56**, and cameras or camera clusters **58**. In addition, the number of participant **54**, displays **56**, and/or camera clusters **58** may differ from the number of one or more of the other described aspects of endpoint **50**, **70**. Any suitable number

of video streams may be generated to convey the image of participants 54 during a video conference.

[0038] As shown in reference to FIG. 2a and FIG. 2b, in a video conference room with multiple chairs (i.e., multiple positions), human presence can be detected by using multiple video cameras pointed at the chairs. Based on the number of people in each room in each endpoint of the conference, embodiments of the videoconferencing system can configure conference geometry by selecting from a plurality of cameras pointed at the participants from different angles. This can result in a more natural eye-gaze between conference members.

[0039] In one embodiment, human presence (i.e., presence detection) can be accomplished using face detection algorithms and technology. Face detection is performed on the video signal from cameras which cover all the possible seating positions in the room. Face detection, in one embodiment, can be performed on an input to the video encoder as a HD resolution picture captured in a video conferencing system. The video encoder can be comprised of one or more processors, each of which processes and encodes one row of macroblocks of the picture. For each 16 x 16 macroblock (MB), the one or more processors perform pre-processing e.g. color space conversion, edge detection, edge thinning, color segmentation, and feature summarization, before coding the block. At the end, the one or more processors transfer two results to a base processor: the total number of original edge features in the MB and the total number of thinned, color-segmented edge features in the MB. The base processor collects the results for all the MBs and performs fast detection of face regions, while the one or more processors can proceed with general video coding tasks including motion estimation, motion compensation, and block transform. With feedback from the base processor, the one or more processors then encode the transform coefficients of the MBs based on the face detection result, following a pre-defined scheme to assign coding parameters such as quantization step size.

- [0040] The raw face detection is refined by tracking and hysteresis to produce high-confidence data on how many people are in the room and which chairs (i.e., positions) they are in.
- [0041] Other methods of presence detection can also be employed in embodiments according to the present invention such as motion detection, chair sensors, or presence monitoring with RFID or ID badges, which require external infrastructure and personal encumbrance.
- [0042] Videoconference endpoints **14** of **FIG. 1** can be configured in various ways. For instance, in one embodiment the videoconference endpoint is comprised of a plurality of large video displays that can be mounted end to end, on one side of a room, with a slight inward tilt to the outer two (see **FIG. 2a** and **FIG. 2b**). Nominally, a three video display system (the "triple") is configured to allow six people to participate, with cameras pointed at pairs accordingly. Other configurations can have only one video display.
- [0043] In multi-point conferences, there can be various combinations of singles talking to triples. For instance, **FIG. 3** is an example illustration of a multi-point videoconferencing system having two endpoints **300**, **302** showing two triples talking to each other, which can be referred to as a 2x3 conference. Each video display **304**, **306** at each endpoint **300**, **302** displays video from a corresponding camera **308**, **310** in the other endpoint.
- [0044] In order to preserve an illusion of a single room divided by a sheet of glass, the cameras **308**, **310** can be placed over the center video display **304b**, **306b** in each room, allowing the geometry of the room to be preserved. The multiple cameras **308**, **310** act as one wide angle camera. Each participant is picked up by one and only one camera depending upon the position occupied by the participant.
- [0045] **FIG. 4** shows multipoint conferences occurring between four people in different locations, which can be referred to as a 4x1 conference. This situation is sometimes depicted with location tags on each screen such as, for example, Paris, London, New York and Tokyo (P, L, T, NY). A participant in Paris would see London, New York, Tokyo; a participant in London would see Paris, New York and Tokyo; etc. To create and maintain the illusion that

these four people are seated at one large round table, then if Paris can see London on his left, then London should see Paris on his right; cameras should be located over each of the three screens, all pointed towards the solo person at the desk; the signal from the left camera should be sent to the endpoint that is shown on a left screen, etc. That is, the camera over the Paris screen in any of the three endpoints other than Paris is the camera that is providing the video signal from the present endpoint (London, New York or Tokyo) to the Paris endpoint.

[0046] **FIG. 5a, FIG. 5b, and FIG. 5c** provide an example illustration of a multi-point videoconferencing system having two endpoints **500** and **501**. Endpoint **500** can comprise a plurality of local participants, in this case six. Screen **502** can be used to display one or more remote participants. For example, screen **502** can be used to display the remote participant from endpoint **501**. Camera **503** can comprise any suitable hardware and/or software to facilitate capturing an image of the local participants and the surrounding area as well as sending the image to remote participants. In an embodiment, camera **503** can be a single wide angle lens capturing a 360° view, two cameras each capturing a 180° view, one or more cameras capturing a greater than 180° view, or any configuration which captures a 360° feed, sends it to an application which processes the same and provides a panoramic view on screen **504** to a remote participant at endpoint **501**.

[0047] Camera **505** at endpoint **501** can comprise any suitable hardware and/or software to facilitate capturing an image of the remote participant at endpoint **501** and the surrounding area as well as sending the image to the local participants at endpoint **500**. Screen **504** at endpoint **501** can be used to provide a panoramic view of the local participants from endpoint **500**.

[0048] As shown in **FIG. 6**, use of a panoramic lens **601** causes distortion to a captured video frame **602**. The image of all the surroundings is reflected twice on two reflective surfaces, one in the lower part of the lens and the other at the top and the image is formed in a ring shape **606** on a CCD **607**. Line **603** corresponds to the topmost part of the video frame **602**, while line **604** corresponds to the bottommost part of the video frame **602**. In the

embodiment shown, everything around the lens to be imaged within a range of approximately 70° above the plane of the lens and 17° below that plane will be imaged.

[0049] Typically the upper part of the resultant rectilinear frame (indicated with diagonal lines in the ring shape 606 and the video frame 602) results in poorer image resolution, because the lens has “squeezed” a wider view of the panoramic scene into the upper part of the frame. Depending on lens orientation off either upward or downward, the distortion will be either in the upper or lower portion of the frame. The methods are described herein, as applied to an upper portion of the video frame 602 whereby the upper portion is more distorted than the lower portion. However, it is specifically contemplated that the methods can be applied to the more distorted region, regardless of its relative position in the frame.

[0050] In one embodiment, provided are methods for panoramic image processing in a Telepresence environment. The disclosed methods can utilized adaptive and variable compression techniques and projection placement techniques. These methods, when combined with Telepresence’s existing audio, video and networking capability, create a true “in-person” solution and overcome the drawbacks of current Telepresence offerings.

[0051] In one embodiment provided are variable and adaptive compression methods that apply higher quality coding (less compression) to portions of the frame that have been highly squeezed by the panoramic lens. This adaptive compression can be line by line or sector by sector. This adaptive compression can also be frame by frame by applying more frame rate to the corresponding areas of the frame that are more squeezed.

[0052] The system provided can perform coding of images according to the MPEG (Moving Picture Experts Group) series standards (MPEG-1, MPEG-2, and MPEG-4) standardized by the international standardization organization ISO (International Organization for Standardization)/IEC (International Electrotechnical Commission), the H.26x series standards (H.261, H.262, H.263) standardized by the international standardization organization with respect to electric communication ITU-T (International Telecommunication

Union-Telecommunication Standardization Sector), or the H.264/AVC standard which is a moving image compression coding standard jointly standardized by both the standardization organizations.

[0053] With the MPEG series standards, in a case of coding an image frame in the intra-frame coding mode, the image frame to be coded is referred to as the "I (Intra) frame". In a case of coding an image frame with a prior frame as a reference image, i.e., in the forward interframe prediction coding mode, the image frame to be coded is referred to as the "P (Predictive) frame". In a case of coding an image frame with a prior frame and an upcoming frame as reference images, i.e., in the bi-directional interframe prediction coding mode, the image frame to be coded is referred to as the "B frame".

[0054] In modern block based transform compression techniques, image data can be systematically divided into segments or blocks that are transformed, quantized, and encoded independently. An exemplary video bitstream can be made up of blocks of pixels, macroblocks (MB), pictures, groups of pictures (GOP), and video sequences. In one aspect, the smallest element, a block, can consist of 8 lines x 8 pixels per line or 4 lines x 4 pixels per line (H.264). As is known in the art, H.264 consists of 16x16 (macro block), 16x8, 8x16, 8x8, 8x4, 4x8, and 4x4 blocks and MPEG4 Part 2 consists of 16x16 and 8x8 blocks, any such block can be used. Blocks are grouped into macroblocks (MB), according to a predefined profile. The system provided can receive an input signal, such as moving images in units of frames, perform coding of the moving images, and output a coded stream. The input signal can be, for example, a 360° feed of images. If required, motion compensation can be performed for each macro block or sub-macro block of a P frame or B frame. Discrete Cosine Transform (DCT) processing can be used to transform image information to the frequency domain, resulting in DCT coefficients. The DCT coefficients thus obtained can then be quantized. The DCT coefficients can be weighted and truncated, providing the first significant compression. The coefficients can then be scanned along a predetermined path such as a zigzag scan to increase the probability that the significant coefficients occur early in the scan. Other predetermined

scanning paths as known in the art can be used. After the last non-zero coefficient, an EOB (end of block) code can be generated.

[0055] The quantization parameters (QP) used to determine the fineness and coarseness of quantizing coefficients in the coded blocks can be assigned with a lower value at the upper part of the rectilinear frame. This can provide higher quality coding to the upper part of the frame. In one embodiment, the quantization parameter can be increased gradually from the upper part of the rectilinear frame to the lower part of the rectilinear frame.

[0056] For example, in one embodiment, let the rectilinear frame be represented by k lines with the pixel resolution at the first/top line and last/bottom line be represented by n and $(n+m)$, respectively. Then the pixel resolution for i th line of the rectilinear frame can be represented by $n+(i-1)m/(k-1)$, $i = 1, 2, 3, \dots, k$. The adaptive quantization parameter for i th line or a group of lines adjacent to the i th line can be defined using a function or a look up table. The functional relationship between the QP and the resolution can be determined experimentally. As an example, assuming the QP is directly proportional to the square root of the resolution, then the QP which is used to code the rectilinear frame can be represented by taking the round off value of the square root of $\{[n+(i-1)m/(k-1)]/n\}$ QP. The QP within a group of lines can be further adjusted to ensure that the same QP value is used for each macroblock in a block based transform compression.

[0057] As another example, the correlation coefficient of adjacent pixels can be measured for each line or group of lines and QP can be adjusted with respect to the correlation coefficient. The higher the correlation coefficient, the larger the QP. The relationship between the QP and the correlation coefficient can be determined experimentally.

[0058] In a motion compensated transform coding, a block (or a group of blocks) in the present frame is compared to the block (or group of blocks) in the past and/or future frame to determine the closeness of the blocks (or group of blocks). The comparison can be carried out by finding the differences between the pixels in the present block (or group of blocks) and

the pixels in the past and/or future block, summarizing the differences in absolute value, and comparing the summarized absolute difference with a predetermined threshold. The smaller or tighter the threshold, the more accurate the block is classified and, thereby, the finer the quality of the block coding.

[0059] In another embodiment, the thresholds used to determine predicted block types or macroblock types can be tightened at the upper part of the rectilinear frame to push more macroblocks from non-motion compensated blocks to motion compensated blocks, from non-coded blocks to coded blocks, and from inter blocks to intraframe blocks. This can provide higher quality coding to the upper part of the frame at the expense of higher bit rate (less compression). The thresholds can be loosened gradually from the upper part of the rectilinear frame to the lower part of the rectilinear frame.

[0060] As shown in the example flowchart of **FIG. 7**, provided are methods for image processing, comprising receiving a video frame at **701**, coding a first portion of the video frame at a different quality than a second portion of the video frame, based on an optical property at **702**, and displaying the video frame at **703**.

[0061] The video frame can be received from a panoramic video camera, a plurality of cameras providing a 360° feed, or a plurality of cameras providing a feed greater than 180°.

[0062] Coding the first portion of the video frame at a different quality than the second portion of the video frame, based on an optical property can comprises transforming the first and second portions of the video frame, resulting in a first and second plurality of coefficients, quantizing the first plurality of coefficients based on a first plurality of quantization parameters, and quantizing the second plurality of coefficients based on a second plurality of quantization parameters.

[0063] The methods can further comprise determining the first plurality of quantization parameters based on the optical property. The optical property can be an optical property of a panoramic video camera. The optical property can be an optical distortion property of a panoramic video camera.

The optical distortion property can be predetermined. The optical distortion property can be predetermined by measuring distortion of a known video frame. The optical distortion property can be predetermined by at least one of, measuring distortion of a known video frame at different camera focal lengths, measuring distortion of a known video frame by determining pixel resolution for a line or a group of lines, or measuring distortion of a known video frame by determining correlation coefficients between adjacent pixels. The distortion of a known video frame can be pixel resolution for a line or a group of lines and/or the correlation coefficients between adjacent pixels. The optical distortion property can be predetermined by measuring distortion of a known video frame at different camera focal lengths. The difference in resolution between lines or groups of lines and the difference in pixel correlation within a line or a group of lines are all distortions created by warping a panoramic picture to a rectilinear picture.

[0064] Quantizing the first plurality of coefficients based on a first plurality of quantization parameters and quantizing the second plurality of coefficients based on a second plurality of quantization parameters can comprise quantizing the first plurality of coefficients more than the second plurality of coefficients, resulting in higher quality coding of the first portion of the video frame.

[0065] Quantizing the first plurality of coefficients based on a first plurality of quantization parameters and quantizing the second plurality of coefficients based on a second plurality of quantization parameters can comprise quantizing the first plurality of coefficients less than the second plurality of coefficients, resulting in lower quality coding of the first portion of the video frame.

[0066] **FIG. 8** is a block diagram illustrating an example operating environment for performing the disclosed method. One skilled in the art will appreciate that provided is a functional description and that the respective functions can be performed by software, hardware, or a combination of software and hardware. This example operating environment is only an example of an operating environment and is not intended to suggest any

limitation as to the scope of use or functionality of operating environment architecture. Neither should the operating environment be interpreted as having any dependency or requirement relating to any one or combination of components illustrated in the example operating environment.

[0067] The present methods and systems can be operational with numerous other general purpose or special purpose computing system environments or configurations. Examples of well known computing systems, environments, and/or configurations that can be suitable for use with the system and method comprise, but are not limited to, personal computers, server computers, laptop devices, and multiprocessor systems. Additional examples comprise set top boxes, programmable consumer electronics, network PCs, minicomputers, mainframe computers, distributed computing environments that comprise any of the above systems or devices, and the like.

[0068] The processing of the disclosed methods and systems can be performed by software components. The disclosed system and method can be described in the general context of computer-executable instructions, such as program modules, being executed by one or more computers or other devices. Generally, program modules comprise computer code, routines, programs, objects, components, data structures, etc. that perform particular tasks or implement particular abstract data types. The disclosed method can also be practiced in grid-based and distributed computing environments where tasks are performed by remote processing devices that are linked through a communications network. In a distributed computing environment, program modules can be located in both local and remote computer storage media including memory storage devices.

[0069] Further, one skilled in the art will appreciate that the system and method disclosed herein can be implemented via a general-purpose computing device in the form of a computer **801**. The components of the computer **801** can comprise, but are not limited to, one or more processors or processing units **803**, a system memory **812**, and a system bus **813** that couples various system components including the processor **803** to the

system memory **812**. In the case of multiple processing units **803**, the system can utilize parallel computing.

[0070] The system bus **813** represents one or more of several possible types of bus structures, including a memory bus or memory controller, a peripheral bus, an accelerated graphics port, and a processor or local bus using any of a variety of bus architectures. By way of example, such architectures can comprise an Industry Standard Architecture (ISA) bus, a Micro Channel Architecture (MCA) bus, an Enhanced ISA (EISA) bus, a Video Electronics Standards Association (VESA) local bus, an Accelerated Graphics Port (AGP) bus, and a Peripheral Component Interconnects (PCI) bus also known as a Mezzanine bus. The bus **813**, and all buses specified in this description can also be implemented over a wired or wireless network connection and each of the subsystems, including the processor **803**, a mass storage device **804**, an operating system **805**, videoconference software **806**, videoconference data **807**, a network adapter **808**, system memory **812**, an input/output interface **810**, a display adapter **809**, a display device **811**, a human machine interface **802**, and a camera **816**, can be contained within a local endpoint **814** and one or more remote endpoints **814a,b,c** at physically separate locations, connected through buses of this form, in effect implementing a fully distributed system.

[0071] The computer **801** typically comprises a variety of computer readable media. Example readable media can be any available media that is accessible by the computer **801** and comprises, for example and not meant to be limiting, both volatile and non-volatile media, removable and non-removable media. The system memory **812** comprises computer readable media in the form of volatile memory, such as random access memory (RAM), and/or non-volatile memory, such as read only memory (ROM). The system memory **812** typically contains data such as videoconference data **807** and/or program modules such as operating system **805** and videoconference software **806** that are immediately accessible to and/or are presently operated on by the processing unit **803**.

[0072] In another embodiment, the computer **801** can also comprise other removable/non-removable, volatile/non-volatile computer storage media. By way of example, **FIG. 8** illustrates a mass storage device **804** which can provide non-volatile storage of computer code, computer readable instructions, data structures, program modules, and other data for the computer **801**. For example and not meant to be limiting, a mass storage device **804** can be a hard disk, a removable magnetic disk, a removable optical disk, magnetic cassettes or other magnetic storage devices, flash memory cards, CD-ROM, digital versatile disks (DVD) or other optical storage, random access memories (RAM), read only memories (ROM), electrically erasable programmable read-only memory (EEPROM), and the like.

[0073] Optionally, any number of program modules can be stored on the mass storage device **804**, including by way of example, an operating system **805** and videoconference software **806**. Each of the operating system **805** and videoconference software **806** (or some combination thereof) can comprise elements of the programming and the videoconference software **806**. Videoconference data **807** can also be stored on the mass storage device **804**. Videoconference data **807** can be stored in any of one or more databases known in the art. Examples of such databases comprise, DB2®, Microsoft® Access, Microsoft® SQL Server, Oracle®, MySQL, PostgreSQL, and the like. The databases can be centralized or distributed across multiple systems.

[0074] In another embodiment, the user can enter commands and information into the computer **801** via an input device (not shown). Examples of such input devices comprise, but are not limited to, a keyboard, pointing device (e.g., a "mouse"), a microphone, a joystick, a scanner, tactile input devices such as gloves, and other body coverings, and the like. These and other input devices can be connected to the processing unit **803** via a human machine interface **802** that is coupled to the system bus **813**, but can be connected by other interface and bus structures, such as a parallel port, game port, an IEEE 1394 Port (also known as a Firewire port), a serial port, or a universal serial bus (USB).

[0075] In yet another embodiment, a display device **811**, such as a video display, can also be connected to the system bus **813** via an interface, such as a display adapter **809**. It is contemplated that the computer **801** can have more than one display adapter **809** and the computer **801** can have more than one display device **811**. For example, a display device can be a monitor, an LCD (Liquid Crystal Display), or a projector. In addition to the display device **811**, other output peripheral devices can comprise components such as speakers (not shown) and a printer (not shown) which can be connected to the computer **801** via Input/Output Interface **810**.

[0076] The computer **801** can operate in a networked environment using logical connections to one or more remote endpoints **814a,b,c**. By way of example, a remote computing device at a remote endpoint **814** can be a personal computer, portable computer, a server, a router, a network computer, a peer device or other common network node, and so on. Logical connections between the computer **801** and a remote endpoint **814a,b,c** can be made via a local area network (LAN) and a general wide area network (WAN). Such network connections can be through a network adapter **808**. A network adapter **808** can be implemented in both wired and wireless environments. Such networking environments are conventional and commonplace in offices, enterprise-wide computer networks, intranets, and the Internet **815**.

[0077] For purposes of illustration, application programs and other executable program components such as the operating system **805** are illustrated herein as discrete blocks, although it is recognized that such programs and components reside at various times in different storage components of the computing device **801**, and are executed by the data processor(s) of the computer. An implementation of videoconference software **806** can be stored on or transmitted across some form of computer readable media. Computer readable media can be any available media that can be accessed by a computer. By way of example and not meant to be limiting, computer readable media can comprise "computer storage media" and "communications media." "Computer storage media" comprise volatile

and non-volatile, removable and non-removable media implemented in any method or technology for storage of information such as computer readable instructions, data structures, program modules, or other data. Example computer storage media comprises, but is not limited to, RAM, ROM, EEPROM, flash memory or other memory technology, CD-ROM, digital versatile disks (DVD) or other optical storage, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, or any other medium which can be used to store the desired information and which can be accessed by a computer.

[0078] The methods and systems can employ Artificial Intelligence techniques such as machine learning and iterative learning. Examples of such techniques include, but are not limited to, expert systems, case based reasoning, Bayesian networks, behavior based AI, neural networks, fuzzy systems, evolutionary computation (e.g. genetic algorithms), swarm intelligence (e.g. ant algorithms), and hybrid intelligent systems (e.g. Expert inference rules generated through a neural network or production rules from statistical learning).

[0079] While the methods and systems have been described in connection with preferred embodiments and specific examples, it is not intended that the scope be limited to the particular embodiments set forth, as the embodiments herein are intended in all respects to be illustrative rather than restrictive.

[0080] Unless otherwise expressly stated, it is in no way intended that any method set forth herein be construed as requiring that its steps be performed in a specific order. Accordingly, where a method claim does not actually recite an order to be followed by its steps or it is not otherwise specifically stated in the claims or descriptions that the steps are to be limited to a specific order, it is no way intended that an order be inferred, in any respect. This holds for any possible non-express basis for interpretation, including: matters of logic with respect to arrangement of steps or operational flow; plain meaning derived from grammatical organization or

punctuation; the number or type of embodiments described in the specification.

[0081] It will be apparent to those skilled in the art that various modifications and variations can be made without departing from the scope or spirit. Other embodiments will be apparent to those skilled in the art from consideration of the specification and practice disclosed herein. It is intended that the specification and examples be considered as exemplary only, with a true scope and spirit being indicated by the following claims.

CLAIMS

What is claimed is:

1. A method for image processing, comprising:
 - receiving a video frame;
 - coding a first portion of the video frame at a different quality than a second portion of the video frame, based on an optical property; and
 - displaying the video frame.
2. The method of claim 1, wherein the video frame is received from a panoramic video camera.
3. The method of claim 1, wherein coding the first portion of the video frame at a different quality than the second portion of the video frame, based on an optical property comprises:
 - transforming the first and second portions of the video frame, resulting in a first and second plurality of coefficients;
 - quantizing the first plurality of coefficients based on a first plurality of quantization parameters; and
 - quantizing the second plurality of coefficients based on a second plurality of quantization parameters.
4. The method of claim 3, further comprising determining the first plurality of quantization parameters based on the optical property.
5. The method of claim 4, wherein the optical property is an optical property of a panoramic video camera.
6. The method of claim 4, wherein the optical property is an optical distortion property of a panoramic video camera.

7. The method of claim 6, wherein the optical distortion property is predetermined.
8. The method of claim 6, wherein the optical distortion property is predetermined by measuring distortion of a known video frame.
9. The method of claim 6, wherein the optical distortion property is predetermined by at least one of, measuring distortion of a known video frame at different camera focal lengths, measuring distortion of a known video frame by determining pixel resolution for a line or a group of lines, or measuring distortion of a known video frame by determining correlation coefficients between adjacent pixels.
10. The method of claim 3, wherein quantizing the first plurality of coefficients based on a first plurality of quantization parameters and quantizing the second plurality of coefficients based on a second plurality of quantization parameters comprises quantizing the first plurality of coefficients more than the second plurality of coefficients, resulting in higher quality coding of the first portion of the video frame.
11. The method of claim 3, wherein quantizing the first plurality of coefficients based on a first plurality of quantization parameters and quantizing the second plurality of coefficients based on a second plurality of quantization parameters comprises quantizing the first plurality of coefficients less than the second plurality of coefficients, resulting in lower quality coding of the first portion of the video frame.

12. A multi-point videoconferencing system comprised of:

- a first point of the multi-point videoconferencing system comprised of a first camera, a first video display, and one or more first positions, wherein a video frame captured at the first point is a panoramic image;
- a second point of the multi-point videoconferencing system comprised of a second camera, a second video display, one or more second positions; and
- a processor operably connected with the first camera, wherein the processor is configured to code a first portion of the video frame at a different quality than a second portion of the video frame, based on an optical property.

13. The system of claim 12, wherein the first camera is a panoramic video camera.

14. The system of claim 12, wherein the processor is further configured to:

- transform the first and second portions of the video frame, resulting in a first and second plurality of coefficients;
- quantize the first plurality of coefficients based on a first plurality of quantization parameters; and
- quantize the second plurality of coefficients based on a second plurality of quantization parameters.

15. The system of claim 14, wherein the processor is further configured to determine the first plurality of quantization parameters based on the optical property.

16. The system of claim 15, wherein the optical property is an optical property of the first camera.

17. The system of claim 14, the processor is further configured to quantize the first plurality of coefficients more than the second plurality of coefficients, resulting in higher quality coding of the first portion of the video frame.
18. The system of claim 14, wherein the processor is further configured to quantize the first plurality of coefficients less than the second plurality of coefficients, resulting in lower quality coding of the first portion of the video frame.
19. A computer readable medium having computer executable instructions embodied thereon for image processing, comprising:
 - receiving a video frame;
 - coding a first portion of the video frame at a different quality than a second portion of the video frame, based on an optical property; and
 - displaying the video frame.
20. The computer readable medium of claim 19, further comprising:
 - transforming the first and second portions of the video frame, resulting in a first and second plurality of coefficients;
 - quantizing the first plurality of coefficients based on a first plurality of quantization parameters; and
 - quantizing the second plurality of coefficients based on a second plurality of quantization parameters.

FIG. 1




FIG. 2a




FIG. 2b




FIG. 3




FIG. 4




FIG. 5a





FIG. 6




FIG. 7




FIG. 8

