



(19) **United States**

(12) **Patent Application Publication**

Monteiro et al.

(10) **Pub. No.: US 2001/0023513 A1**

(43) **Pub. Date: Sep. 27, 2001**

(54) **METHOD AND APPARATUS FOR CONTAINING AND AGITATING THE CONTENTS OF A CONTAINER**

(30) **Foreign Application Priority Data**

May 12, 1998 (GB)..... 9810173.6

(76) Inventors: **Andre Fraser Monteiro**, Malmesbury (GB); **Geoffrey Michael Burlington**, Gloucestershire (GB); **Simon Paul Wells**, Bath (GB)

Publication Classification

(51) **Int. Cl.⁷** **D06F 21/00**

(52) **U.S. Cl.** **8/158; 8/159; 68/143; 68/140**

Correspondence Address:

Richard D. Jordan
Morrison & Foerster LLP
Suite 5500
2000 Pennsylvania Avenue, N.W.
Washington, DC 20006-8396 (US)

(57) **ABSTRACT**

The invention provides an apparatus comprising a drum for containing and agitating an article, wherein the drum comprises at least two rotatable drum portions in rotatable connection with one another, a rotator member in connection with each rotatable drum portion for rotating the drum portion about an axis. The apparatus is preferably a washing machine, and the method of operating the apparatus comprises inserting at least one article, preferably a plurality of articles, into the drum; and rotating each rotatable drum portion independently of one another to agitate the article or articles.

(21) Appl. No.: **09/853,689**

(22) Filed: **May 14, 2001**

Related U.S. Application Data

(62) Division of application No. 09/309,865, filed on May 11, 1999.




Fig. 1.





Fig. 2.






Fig. 3a.




Fig. 3b.






Fig. 4.

Fig. 5.










Fig. 9.





Fig. 10.




Fig. 11a.




Fig. 11b.

METHOD AND APPARATUS FOR CONTAINING AND AGITATING THE CONTENTS OF A CONTAINER

FIELD OF THE INVENTION

[0001] The invention relates to a method and apparatus for containing and agitating at least one article. The invention has application in any situation where articles are required to be treated by agitation for purposes as varied as cleaning, polishing, grinding, granulating, peeling and coating. Preferably, the invention is used in the laundry field in order to carry out cleaning (washing) or fabric treatment processes. Particularly, but not exclusively, the invention relates to an improved washing machine.

BACKGROUND OF THE INVENTION

[0002] Devices which agitate articles within a rotating drum in the presence of a fluid are known. For example, U.S. Pat. No. 5,350,323, discloses a dual drum mixer which can be used to mix, homogenize or react at least two components. The device is a container made of two separately driveable pipe lengths adjacent to one another. The container is sealed, with fluid being injected into the container through its longitudinal axes. The device is limited in use in that fluid entry is only through its axes and the fluid must be sealed within the container in order for proper mixing or agitation to occur.

[0003] In agitation devices such as conventional washing machines, a perforated drum is used to contain articles as they are agitated in the presence of water and detergent in order to remove dirt. The dirt is displaced into the water, and the water is removed from the drum by passing through the perforations. In front-loading washing machines, agitation is caused by the rotation of the drum about a generally horizontal axis so that the articles tumble over one another and rub against each other and against the walls of the drum. However, the rotational speed of the drum is limited because, if the speed is too high, the articles will merely be pressed under centrifugal forces against the interior walls of the drum. The articles then rotate with the drum and no agitation with respect to the drum or with respect to other articles is achieved. The amount of agitation which can be applied to the articles by front-loading washing machines is therefore limited. This means that, in order to achieve a specific standard of cleanliness, the machine must operate for a minimum period of time.

SUMMARY OF THE INVENTION

[0004] In order to overcome many problems inherent in the prior art, the present invention provides an apparatus and method for enhancing the agitation of articles. The apparatus comprises a drum for containing and agitating an article, wherein the drum comprises at least two rotatable drum portions in rotatable connection with one another, a rotator member in connection with each rotatable drum portion for rotating the drum portion about an axis. Preferably the drum has at least one port for intake or exhaust of a liquid into or out of an area internal to the drum. More preferably, the at least one port is located on a peripheral portion of at least one of the rotatable drum portions. The drum can be seated within a tank.

[0005] The apparatus can include a drive in connection with each rotator member. The rotatable drum portions are,

preferably, rotatable about a common axis, and the axis can be horizontal or inclined to the vertical. The rotatable drum portions can be of a variety of shapes and sizes so that the apparatus can function as a polisher, grinder, granulator, peeler, coater or washing machine. The apparatus is preferably a washing machine.

[0006] The drive comprises a motor connected to a coupler, and a controller can be connected to the motor to control speed and directional rotation of the rotatable drum portions. The rotator member can be connected to a periphery of each rotatable drum portion, or it can be connected to a shaft adjoining each rotatable drum portion. The rotator member acts as a friction providing element to facilitate rotation of the rotatable drum portions.

[0007] The drive and rotator member couple such that the rotatable drum portions can rotate independently of one another. The rotatable drum portions can be rotated at different speeds and different directions in order to enhance agitation.

[0008] The invention also encompasses a method of providing enhanced agitation. The method comprises inserting at least one solid article into a drum, wherein the drum comprises a first rotatable drum portion and a second rotatable drum portion in rotatable connection with one another; and rotating the first and second drum portions independently of one another to agitate the article. Preferably, a fluid is provided within the drum as the first and second drum portions are rotated. The fluid is preferably added to or exhausted from the drum through at least one port at a peripheral portion of the drum.

[0009] The rotatable drum portions can be rotated at a variety of speeds and directions. For example, the rotatable drum portions can be rotated in opposite directions; at the same speed in opposite directions; at different speeds in the same direction; at different speeds in opposite directions; at the same speed and in the same direction; or at least one of the rotatable drum portions can be held stationary while the other rotatable drum portion is rotated.

[0010] In another embodiment, the invention provides an apparatus which comprises a drum for containing and agitating an article, wherein the drum comprises at least two rotatable drum portions in rotatable connection with one another, and a rotator member in connection with each rotatable drum portion for rotating the drum portion about an axis. Two of the rotatable drum portions at opposite ends of the drum have end walls attached thereto. An opening for inserting the article into the drum can be provided at an end wall or at a peripheral portion of one or more rotatable drum portions. A door can be provided to maintain the article within the drum during operation. Preferably, one of the rotatable drum portions is located inside another rotatable drum portion, and the rotatable drum portions can be mounted on concentric shafts.

DESCRIPTION OF THE DRAWINGS

[0011] The present invention will be better understood by reference to the Detailed Description of the Invention when taken together with the attached drawings, wherein:

[0012] **FIG. 1** is a schematic perspective view of apparatus according to a first embodiment of the invention;

[0013] FIG. 2 is a longitudinal cross-sectional view of the apparatus of FIG. 1 in use and forming part of a washing machine;

[0014] FIG. 3a is a front view of the driving mechanism forming part of the apparatus of FIG. 2;

[0015] FIG. 3b is a side view of the driving mechanism of FIG. 3a;

[0016] FIG. 4 is a schematic perspective view of apparatus according to a second embodiment of the invention;

[0017] FIG. 5 is a longitudinal cross-sectional view of the apparatus of FIG. 4 in use and forming part of a washing machine;

[0018] FIGS. 6a, b and c are schematic perspective views, similar to FIG. 1, of apparatus according to third, fourth and fifth embodiments of the invention;

[0019] FIG. 7a is a front view of a seventh embodiment of the invention;

[0020] FIG. 7b is a perspective view of the embodiment shown in FIG. 7a in an open position;

[0021] FIG. 8 is a perspective view of a ninth embodiment of the invention similar to the first embodiment but illustrating an alternative method of opening the drum;

[0022] FIG. 9 is a longitudinal cross-section through a tenth embodiment of the invention;

[0023] FIG. 10 is an exploded view of the rotating portions of the drum forming part of the embodiment shown in FIG. 9; and

[0024] FIGS. 11a and 11b are side and plan views respectively of a paddle which forms part of the embodiment shown and illustrated in FIGS. 9 and 10.

DETAILED DESCRIPTION OF THE INVENTION

[0025] The present invention is directed to an apparatus comprising a drum for containing and agitating an article, and a method of agitating an article. The drum of the apparatus comprises at least two rotatable drum portions in rotatable connection with one another, a rotator member in connection with each rotatable drum portion for rotating the drum portion about an axis, with at least one of the rotatable drum portions being perforated. In the method of agitating an article, the drum is operated in such a manner that relative rotation is produced between adjacent rotatable drum portions of the drum.

[0026] In a preferred embodiment, the drum has a drive that is capable of rotating the rotatable drum portions at different speeds and/or in different directions. More preferably, the drive is capable of rotating adjacent rotatable drum portions at different speeds in the same direction, at different speeds in opposite directions and/or at the same speed in opposite directions. The relative rotation between the adjacent rotatable drum portions prevents the articles from becoming adhered to the interior wall of the drum. Therefore, the rotational speed of the rotatable drum portions can be increased above that at which the articles would normally cease to be agitated, and the amount of agitation applied to

the articles can be made more intense. The articles are therefore treated more intensively that they would be in conventional apparatus.

[0027] When the drum is used in a washing machine, dirt is released from the articles at a higher rate than in known machines, and the cleaning process is either more thorough in a given time or else the desired standard of cleanliness is achieved more quickly. Preferably, the drum comprises at least one motor, a controller to control the speed and direction of rotation of the drum portions, and a coupler that connects the motor to the drum portions. The type of motor, controller or coupler used is not critical and will be apparent to one of ordinary skill in the art.

[0028] Preferably, the drum includes at least two essentially cylindrical rotatable drum portions. Advantageously, the rotatable drum portions are capable of being driven at the same speed in opposite directions. This maximizes the agitation of the contents of the drum and, in the context of a washing machine, allows articles to be cleaned to a specific standard very quickly or, if desired, to a very high standard in a specific time. In alternative embodiments, the rotatable drum portions can be driven at different speeds in the same direction or at different speeds in opposite directions. It is also envisaged that it will be possible to achieve the same effect by retaining one rotatable drum portion stationary and rotating the other portion in either direction.

[0029] The invention also provides a method of containing and agitating a plurality of articles within a defined space, comprising the steps of introducing the articles to the interior of a drum which delimits the defined space and which is rotatable by drive means, and rotating the drum so as to cause agitation between the articles, characterized in that, during at least part of the step of rotating the drum so as to cause agitation between the articles, the drive is operated in such a manner that relative rotation is produced between adjacent rotatable drum portions of the drum. The method according to the invention will have advantages similar to those of the apparatus according to the invention.

[0030] One embodiment of the invention is illustrated in FIG. 1. Essentially, the apparatus 10 comprises a cylindrical drum 12 mounted rotatably about an axis 14. The drum 12 is made up of two separately rotatable drum portions 16a, 16b, each consisting of a cylindrical wall and a circular end wall. Each circular end wall closes the respective rotatable drum portion 16a, 16b at one side, the open side facing the other respective rotatable drum portion 16b, 16a. One of the circular end walls has an opening therein for inserting an article or articles into the drum. A door 15 can be incorporated within the opening to maintain the article or articles within the drum during operation. The door 15 is mounted in a conventional manner and will not be described any further here. It will be understood that this is only one way of providing access to the interior of the drum 12 and, as an alternative, one of the rotatable drum portions 16a, 16b can have an opening at a peripheral area, and a door 15 could alternatively be mounted within the opening to maintain the article or articles within the drum. The rotatable drum portions 16a, 16b are individually mounted so as to be rotatable about the axis 14, for example by support bearings 17, and are each driven by a separate drive 24a, 24b (see FIGS. 2 and 3). The drives 24a, 24b are arranged and adapted so that each rotatable drum portion 16a, 16b can be

rotated about the axis **14** at a speed or in a direction which is different from that of the other rotatable drum portion **16b**, **16a**. In the illustrated embodiment, the rotatable drum portion **16a** can be rotated in the direction of arrow **18a** at the same time that the rotatable drum portion **16b** can be rotated at the same speed in the direction of arrow **18b**.

[0031] In FIG. 2, the drum **12** is seated in a tub or tank **20**, and contains articles **21** and a liquid **23**. The tub or tank **20** can be a polisher, grinder or cleaning machine, preferably a washing machine. The liquid can be a cleaning fluid, preferably a solution of water and detergent or any other type of cleaning composition.

[0032] The drum **12** has at least one port, such as a perforation or simple opening, through at least one of the rotatable drum portions **16a**, **16b** in order to allow water to flow into the drum **12** from the tub or tank **20** and vice versa. Preferably, each drum portion **16a**, **16b** will have a plurality of ports. Preferably the port or port will be located on a periphery of the drum. The port or ports can be located in an area between adjoining drum portions **16a**, **16b**. Although, it is preferred that there be at least one port on a peripheral portion of at least one of the rotatable drum portions **16a**, **16b**. There is no need for the rotatable drum portions **16a**, **16b** to be sealed against one another since the flow of water into and out from the drum **12** is acceptable. Two separate drives **24a**, **24b** are positioned above the rotatable drum portions **16a**, **16b** in order to drive, independently of one another, the said rotatable drum portions **16a**, **16b**.

[0033] When the drives **24a**, **24b** are activated, rotatable drum portion **16a** is driven by drive **24a** in the direction of arrow **18a** and rotatable drum portion **16b** is driven by drive **24b** in the direction of arrow **18b**. The rotatable drum portions **16a**, **16b** thus rotate about the axis **14** at the same speed but in opposite directions. The articles **22** contained within the drum **12** are agitated as the rotatable drum portions **16a**, **16b** rotate. The articles **22** are continually prevented from sticking to the cylindrical wall of either of the rotatable drum portions **16a**, **16b** by virtue of the fact that a portion of the articles are being rotated in the opposite direction by the other rotatable drum portion **16b**, **16a**. The articles collide and pull one another from the wall of the rotatable drum portion **16a**, **16b** in which they are located. The speed of rotation of each rotatable drum portion of the apparatus can therefore be higher than can be achieved in known agitation devices. Achieving a higher degree of agitation in a much shorter period of time is also made possible. When the tub or tank **20** is used as a washing machine, a much higher standard of cleanliness in a given period of time can be attained than has previously been possible.

[0034] One of the drives **24a**, **24b** is illustrated in FIGS. **3a** and **3b**. It will be appreciated that the drives **24a**, **24b** illustrated in FIG. 2 can be identical to one another. For this reason, only one drive is illustrated here. The illustrated drive to be described below is not to be understood as being the only drive suitable for this purpose. Other drives equally suitable for this application will be immediately apparent to one of ordinary skill in the art. Preferably, the drive comprises a motor and coupler in connection with the motor. A controller for controlling the speed and direction of the drive can also be included.

[0035] In the embodiment shown in FIGS. **3a** and **3b**, the drive comprises a motor **30** connected to a single coupler

unit, the coupler unit being in contact with a rotator member mechanism on the rotatable drum portion. The coupler unit includes a shaft **32** carrying a first toothed wheel **34**. A chain **36** or other linked member engages the first toothed wheel **34** and also a second toothed wheel **38** fixed to a second shaft **40**. If desired the shaft **32** or second shaft **40** can be mounted to a support structure on the apparatus housing the drum. The second shaft **40** also carries a third toothed wheel **42**, the teeth **44** of which are designed to engage with a rotator member **46**. The rotator member is separate from the coupler unit and is connected to the rotatable drum portion in a fashion such that it can act to rotate the rotatable drum portion, and can be made of any type of friction providing member. Preferably, the rotator member is a toothed attachment or a chain. In FIG. **3a** and FIG. **3b** the rotator member **46** is arranged around the periphery of one of the rotatable drum portions **16a**, **16b**. When the motor **30** is operated, the shaft **32** rotates causing the first toothed wheel **34** to rotate. This drives the chain **36** which causes the second toothed wheel **38** to rotate and, in turn, the third toothed wheel **42**. Rotation of the third toothed wheel **42** forces the rotatable drum portion to which the drive is attached to rotate about the axis **14**. The direction of rotation and speed of rotation of the rotatable drum portion can be determined by the direction of rotation of the motor and by the particular gearing used in the coupler unit. A controller can be used to control the speed and direction of the motor; and the number of gears, gear radius and tooth arrangement of each gear can determine speed and direction of the rotatable drum portions independently of the controller and motor. This type of speed and directional control will be readily apparent to one of ordinary skill in the art.

[0036] It will be appreciated that the toothed wheels **34**, **38**, **42** and chain or rotator member **36**, **46** can be replaced where appropriate by pulleys and drive belts or other equivalent components. If a drive belt is used to drive the rotatable drum portion **16a**, **16b** itself, the drive belt may best be wrapped around a pulley located on or concentric with the axis **14** shown in FIG. 1. The motor can also be connected to a second coupler unit to drive a second drum portion. For example, shaft **32** can extend through the toothed wheel **34** and connect to an additional toothed wheel rotation assembly. The assembly can contact a rotator member on a second drum portion, and the two drum portions can be driven by one motor. The type of gearing used is not critical to the operation of the invention, and can be any type of gearing arrangement that would be known to one of ordinary skill in the art.

[0037] Another embodiment is illustrated in FIG. 4. In this embodiment, the drum **120** is made up of three separate rotatable drum portions **160a**, **160b**, **160c**. Each of the rotatable drum portions **160a**, **160b**, **160c** has a cylindrical wall and the outermost portions **160a**, **160c** also have circular end walls so that the cylindrical drum **120** is essentially closed. An opening can be provided on one of the circular end walls for inserting an article or articles into the drum. A door **150** can be provided in the opening to maintain the article or articles within the drum during operation. Drives similar to those shown in FIG. 3 can be used in order to rotate each rotatable drum portion **160a**, **160b**, **160c** about the axis **140**. Outermost rotatable drum portions **160a** and **160c** are each rotatable in a first direction (see arrows **180a**,

180c), whereas the central rotatable drum portion 160b is rotatable in the opposite direction (see arrow 180b), but at the same speed.

[0038] The agitation provided to the contents of the drum 120 is once again significantly higher than would be achievable with a conventional washing machine. The rotation of adjacent rotatable drum portions 180a, 180b; 180b, 180c in opposite directions prevents the articles from becoming stuck to the cylindrical walls of the drum 120 simply because other articles, which are being rotated in the opposite direction, will not allow them to be carried around the drum 120. The other articles effectively drag the first articles off the walls and the agitation action is continued, even at high rotational speeds of the rotatable drum portions 180a, 180b, 180c.

[0039] In the arrangement shown in FIG. 5, the agitation provided to the articles 220 contained within the drum 120 is significantly higher than that which can be achieved using known arrangements. As before, the drum 120 is located within a tank or tub 200 containing a fluid, and at least one of the drum portions is perforated so that the fluid can flow from the drum 120 to the tank or tub 200 and vice versa. In this arrangement, however, the drum 120 is mounted within the tank 200 about an inclined axis 140 instead of about a horizontal axis.

[0040] It will be appreciated that the embodiments described above can be adapted in order to achieve the same or similar effect, particularly with regard to the respective speeds and directions of the rotatable drum portions. Illustrations of alternative arrangements are given in FIGS. 6a, 6b and 6c. In FIG. 6a, the rotatable drum portions 161a, 161b are shown rotating in the same direction but at different speeds by arrows 181a, 181b. In FIG. 6b, the rotatable drum portions 162a, 162b are shown rotating at different speeds but in opposite directions by arrows 182a, 182b. In FIG. 6c, one rotatable drum portion 163b is shown as being held stationary (cross 183b) while the other rotatable drum portion 163a rotates (see arrow 183a). In all three cases, there is relative rotation between the rotatable drum portions 161a, 161b; 162a, 162b; 163a, 163b so that the effect of producing increased agitation of the contents of the drum 120 is achieved. It will be appreciated that the arrangements shown in FIG. 6 are also applicable to drums consisting of three or even more rotatable drum portions.

[0041] A further alternative arrangement is illustrated in FIGS. 7a and 7b. In this arrangement, the washing machine 300 comprises a stationary tank 310 within which are supported, in any known manner, two rotatable drum portions 320a, 320b arranged on either side of a stationary portion 330. The stationary portion 330 incorporates an opening for inserting articles into the interior of the rotatable drum portions 320a, 320b. A door 332 can hingedly mounted about an axis 334 on the stationary portion 330 so as to maintain articles within the rotatable drum portions 320a, 320b during operation. The stationary portion 330 is essentially triangular in side view as shown in FIG. 7a. This allows the axes 312a, 312b about which the rotatable drum portions 320a, 320b are rotatable to be inclined to one another.

[0042] In use, the door 332 is opened in order to allow articles to be introduced through the opening of the stationary portion 330 and into the interior of the drum 314, and the

door 332 is then closed. During operation, the rotatable drum portions 320a, 320b are rotated about the axes 312a, 312b while the stationary portion 330 remains stationary. This produces relative motion between each rotatable drum portion 320a, 320b and the stationary portion 330, even when the rotatable drum portions 320a, 320b are rotated at the same speed and in the same direction. However, it is expected that a higher degree of agitation will be achieved if the rotatable drum portions 320a, 320b are rotated about their respective axes 312a, 312b at different speeds and/or in different directions. As before, the tank or tub 310 contains a fluid, and at least one of the drum portions is perforated so that the fluid can flow from the drum 314 to the tank or tub 310 and vice versa.

[0043] It will be appreciated that drums which consist of two or more essentially cylindrical portions which are rotatable about a common axis can be opened to allow access without necessarily providing an openable door in a wall or peripheral portion of the drum. Since the drum is made up of separate portions, it is possible to allow for one of those portions to move away from the adjacent portion in order to provide access. One way of achieving this is illustrated schematically in FIG. 8. The drum 414 comprises two rotatable drum portions 420a, 420b which are rotatable about a common axis 412. No door is provided in either the cylindrical walls or circular end walls of either rotatable drum portion 420a, 420b. Instead, one of the rotatable drum portions 420b is mounted so that, when the drum 414 is to be opened, the entire rotatable drum portion 420b is pivoted away from the other rotatable drum portion 420a. The open position is illustrated in dotted lines in FIG. 8. In other respects, the construction of the embodiment illustrated in FIG. 8 is similar to that of the embodiments illustrated and described above.

[0044] A further embodiment of the invention is illustrated in FIG. 9. The apparatus 500 has a tub or tank 502 which surrounds and accommodates the drum 550. The tub or tank 502 is watertight so as to contain fluid therein. The tub or tank 502 has an inlet 504 and an outlet 506 for the inlet and drainage of fluid respectively. A door 508 is provided on the front wall of the tub or tank 502 so as to allow articles to be introduced through an opening into the interior of the drum 550. Preferably, the apparatus 500 is a washing machine, and all other elements not described specifically herein are conventional, not requiring further description.

[0045] The drum 550 is shown mounted in a cantilever fashion on the wall of the tub or tank 502 remote from the door 508. In accordance with the invention, the drum 550 is made up of two separate rotatable drum portions 560, 570. The first outer rotatable drum portion 560, is supported on a hollow cylindrical shaft 561. An angular contact bearing 562 is located between the rear wall of the tub 502 and the hollow cylindrical shaft 561. The outer rotatable drum portion 560 is dimensioned so as to substantially fill the interior of the tub 502. More specifically, the outer rotatable drum portion 560 has a generally circular rear wall 563 extending from the hollow cylindrical shaft 561 towards the cylindrical wall of the tub 502, a generally cylindrical wall 564 extending generally parallel to the cylindrical walls of the tub 502 from the rear wall 563 towards the front wall of the tub 502, and a generally annular front face 565 extending from the cylindrical wall 564, and having an opening for receiving the door 508. Sufficient clearance is allowed

between the walls **563**, **564**, **565** of the outer rotatable drum portion **560** and the tub **502** to prevent the outer rotatable drum portion **560** from coming into contact with the tub **502** when the drum **550** is made to spin.

[0046] An inner cylindrical wall **566** is also provided on the interior of the cylindrical wall **564** of the outer rotatable drum portion **560**. The inner cylindrical wall **566** extends from a point which is substantially midway between the rear wall **563** and the front face **565** to the front face **565**. The space between the interior cylindrical wall **566** and the cylindrical wall **564** is hollow but, if desired, could be filled with a strengthening material. In this event, the strengthening material must be lightweight. The provision of parallel cylindrical walls **564**, **566** in the portion of the outer rotatable drum portion **560** closest to the front face **565** provides strength to the whole of the outer rotatable drum portion **560** while reducing the internal diameter of the outer rotatable drum portion **560** in this region.

[0047] The inner rotatable drum portion **570** is supported on a central shaft **571**, which in turn, is supported by deep groove bearings **572** located between the central shaft **571** and the hollow cylindrical shaft **561**. The inner rotatable drum portion **570** essentially comprises a generally circular rear wall **573** extending from the central shaft **571** towards the cylindrical wall of the tub **502**, and a cylindrical wall **574** extending from the periphery of the rear wall **573** towards the front wall of the tub **502**. The diameter of the cylindrical wall **574** of the inner rotatable drum portion **570** is substantially the same as the diameter of the inner cylindrical wall **566** of the outer rotatable drum portion **560**. The cylindrical wall **574** of the inner rotatable drum portion **570** is dimensioned so that the distal end thereof approaches the end of the cylindrical wall **566** closest thereto. It is advantageous to keep the gap between these two cylindrical walls **574**, **566** as small as possible. An annular sealing ring **567** is located on the cylindrical wall **564** of the outer cylindrical portion **560** immediately adjacent to the end of the inner cylindrical wall **566** closest to the inner cylindrical portion **570** so as to provide support for the distal end of the cylindrical wall **574** thereof.

[0048] The central shaft **571** and the hollow cylindrical shaft **561** are each driven separately by drives **580**, **582**. The type of gearing used to couple the drives **580**, **582** to the shafts **561**, **571** is not critical to the operation of the invention, and any type of rotator member or coupling arrangement that would be known to one of ordinary skill in the art can be used. For example, a single or dual coupler unit as described in accordance with **FIG. 3a** and **FIG. 3b** can be used, with the rotator member being located on the shafts of the rotatable drum portions rather than on the periphery.

[0049] An exploded illustration of the inner and outer rotatable drum portions **570**, **560** is shown in **FIG. 10**. As can be seen from **FIGS. 9** and **10**, the inner rotatable drum portion **570** is located inside the outer rotatable drum portion **560** so that the cylindrical wall **574** of the inner rotatable drum portion **570** is aligned with the inner cylindrical wall **566** of the outer rotatable drum portion. The central shaft **571** lies inside the hollow cylindrical shaft **561**. Both of the inner and outer rotatable drum portions are preferably manufactured from stainless steel using manufacturing techniques which include clinching and welding, however the manner

of manufacture is not essential to the present invention and it is envisaged that the rotatable drum portions could also be molded from a suitable plastics material.

[0050] Also located within each of the rotatable drum portions **560**, **570** are paddles **590**. In the illustrated embodiment, three equi-angularly spaced paddles **590** are located on the cylindrical walls **574**, **566** of each respective rotatable drum portion **570**, **560**. More or fewer paddles could be provided if desired. All of the paddles **590** are substantially identical and the shape thereof is illustrated in **FIGS. 11a** and **11b**. As can be seen from **FIG. 11a**, the paddle **590** has a height which reduces significantly from one end **592** towards the other end **594**. In each case, the end **592** will be placed directly adjacent the circular wall or end face of the rotatable drum portion **560**, **570** to which the paddle **590** is attached. In the case of paddles **590** attached to the outer rotatable drum portion **560**, the end **592** will be directly adjacent the annular end face **565**, and in the case of paddles **590** attached to the inner rotatable drum portion **570**, the end **592** of the paddle **590** will be directly adjacent the rear wall **573**. The upper surface **596** of the paddle **590** has an arcuate portion adjacent the end **592** and this arcuate portion can extend over as little as one third or as much as three quarters of the length of the paddle **590**. In the illustrated embodiment, the arcuate portion extends over more than half of the length of the paddle **590**, more specifically over approximately two thirds of the length thereof. The remainder of the upper edge **596** of the paddle **590** extends parallel to the lower surface **598** thereof. Seen in plan view, as shown in **FIG. 11b**, the side edges **599** of the paddle **590** approach one another as they approach the distal end **594** of the paddle **590**. Again, the side edges **599** are arcuate over part of their length, the remainder of the length thereof being parallel to one another.

[0051] The length of each paddle **590** is selected so that, when the paddles **590** are positioned on the cylindrical walls **566**, **574** of the outer and inner rotatable drum portions **560**, **570**, the distal end **594** of each paddle **590** extends to a distance of between 10 and 30 millimeters from the gap between the cylindrical walls **566**, **574**. The shape of the upper surface **596** of each paddle **590** is selected so that the height of each paddle **590** adjacent the end **592** is sufficient to ensure that rotation of articles contained within the drum **550** is continuous when the drum is full or when heavy items are being agitated. However, the height of the paddles **590** is sufficiently small, adjacent the distal end **594**, to provide a gentle agitation for delicate articles when this is required. In the preferred embodiment, when the apparatus **500** is a washing machine, suitable dimensions for a typical paddle are: a maximum height of substantially 50 millimeters, a minimum height of substantially 20 millimeters and a paddle length of substantially 190 millimeters.

[0052] The apparatus described above can be used in the following manner. Articles to be agitated are placed inside the drum **550** and liquid, preferably water, is introduced via the inlet **504** in a known manner. The temperature of the liquid can be adjusted as desired before being introduced into the apparatus **500** or it can be heated to a desired temperature by the apparatus **500** itself using any known heating mechanism. The rotatable drum portions **560**, **570** are then rotated by the drives **580**, **582** so that the speed and/or direction of rotation of one of the rotatable drum portions **560** is different from that of the other rotatable drum

portion **570**. The rotatable drum portions **560, 570** can be rotated at different speeds in the same direction, at the same speed in opposite directions, or at different speeds in opposite directions. Alternatively, one portion **560, 570** can be held stationary while the other portion **570, 560** rotates. In any event the speed of rotation of the rotating portions **570, 560** can be increased above the normal speed of rotation of washing machine drums during the washing cycle. In known machines this would not normally exceed 50 rpm. Even at speeds of rotation far in excess of 50 rpm, the contents of the drum **550** according to the invention do not stick to the wall of the drum and therefore the agitation applied to the said contents can be greatly increased.

[**0053**] When apparatus **500** is used as a washing machine, a rinsing cycle can be employed by draining wash water from the drum **550** via the outlet **506** in a known manner, and introducing clean water via the inlet **504**. The rotatable drum portions **560, 570** continue to be rotated in the same manner as that during typical agitation in order to maintain a high level of agitation while rinsing the articles. After rinsing, the rotatable drum portions **560, 570** are rotated at the same speed and in the same direction in order to spin excess water from the articles in the usual way. The rotatable drum portions **560, 570** may be fixed together at this point by locking the drum portions together in order to ensure that there is little or no relative movement between the rotatable drum portions **560, 570** during spinning. If this fixing occurs, all but one of the drives **580, 582** may be shut off so that all or both portions **560, 570** are driven by a single drive. Alternatively, the drives **580, 582** may be arranged so that all or both rotatable drum portions **560, 570** are driven in the same direction and at the same speed during spinning with any minor differences in speed being kept under control merely by the presence of the contents of the drum **550**. With the increased agitation of the contents of the drum **550**, it is envisaged that the duration of a normal agitation cycle, currently about 90 minutes in a washing machine, can be reduced by about half, possibly more, without there being any reduction in the standard of quality.

[**0054**] The drum of the present invention can be advantageously applied to any apparatus in which the contents of a container requires to be agitated to a high degree and where a shortening of the duration of the agitation would be an advantage. It is preferable that the drum be used in a washing machine. However, other applications include polishing (e.g. of semi-precious stones), grinding, granulating, peeling (e.g. of foodstuffs such as potatoes) and coating. Furthermore, variations of the apparatus described above are intended to be included within the scope of the invention. For example, the shape of the drum need not be cylindrical and spherical and ovoid drums are envisaged. The rotatable drum portions may also be arranged so that they are not generally similar to one another. For example, in a cylindrical drum, one portion may make up the cylindrical wall of the drum while another portion may make up a circular end wall of the drum.

[**0055**] Having now fully described this invention, it will be appreciated by those persons of ordinary skill in the art that the invention can be performed within a wide range of parameters without departing from the spirit and scope of the invention. The embodiments described herein are meant to be illustrative of the overall invention and should not be taken as limiting the invention from what is claimed.

What is claimed is:

1. An apparatus comprising a drum for containing and agitating an article, wherein the drum comprises at least two rotatable drum portions in rotatable connection with one another, a rotator member in connection with each rotatable drum portion for rotating the drum portion about an axis, with at least one of the rotatable drum portions having at least one port for intake or exhaust of a liquid to or from an area internal to the drum.

2. An apparatus as claimed in claim 1, wherein the at least one port is on a peripheral portion of the drum.

3. An apparatus as claimed in claim 2, wherein the at least one port is on a peripheral portion of at least one of the rotatable drum portions.

4. An apparatus as claimed in claim 1, wherein the drum is seated in a tank.

5. An apparatus as claimed in claim 1, wherein a drive is in connection with each rotator member.

6. An apparatus as claimed in claim 1 or 2, wherein the rotatable drum portions are rotatable about a common axis.

7. An apparatus as claimed in claim 6, wherein the axis is horizontal.

8. An apparatus as claimed in claim 6, wherein the axis is inclined to the vertical.

9. An apparatus as claimed in claim 1, wherein the rotatable drum portions of the drum are each substantially cylindrical in shape.

10. An apparatus as claimed in claim 1, wherein the rotatable drum portions of the drum each have substantially similar dimensions.

11. An apparatus as claimed in claim 1, wherein the drum comprises two rotatable drum portions, each rotatable drum portion being substantially cylindrical in shape.

12. An apparatus as claimed in claim 1, wherein the drum comprises three rotatable drum portions, each rotatable drum portion being generally cylindrical in shape.

13. An apparatus as claimed in claim 5, wherein the drive is connected to a controller capable of controlling the rotatable drum portions to rotate at different speeds in the same direction.

14. An apparatus as claimed in claim 5, wherein the drive is connected to a controller capable of controlling the rotatable drum portions to rotate at the same speed in opposite directions.

15. An apparatus as claimed in claim 5, wherein the drive is connected to a controller capable of controlling the rotatable drum portions to rotate at different speeds in opposite directions.

16. Apparatus as claimed in claim 5, wherein the drive comprises a motor connected to a coupler, with a controller connected to the motor to control speed and directional rotation of the rotatable drum portions.

17. An apparatus as claimed in claim, **5** or **16** wherein each rotatable drum portion is connected to a common drive.

18. An apparatus as claimed in claim 5 or 16, wherein each rotatable drum portion is connected to a separate drive.

19. An apparatus as claimed in claim 1, wherein a first of the rotatable drum portions is located inside a second rotatable drum portion.

20. An apparatus as claimed in claim 19, wherein the second rotatable drum portion has a recess portion in which the first rotatable drum portion is accommodated.

21. An apparatus as claimed in claim 20, wherein the second rotatable drum portion has an operative portion separate from the recess portion.

22. An apparatus as claimed in claim 21, wherein the operative portion of the second rotatable drum portion has a diameter that is substantially the same as the diameter of the first rotatable drum portion.

23. An apparatus as claimed in claim 19, wherein the first and second rotatable drum portions are mounted on concentric shafts.

24. An apparatus as claimed in claim 1, wherein at least one of the rotatable drum portions comprises a plurality of paddles within an interior area of the drum portion.

25. An apparatus as claimed in claim 24, wherein each paddle is shaped so that the height thereof decreases continuously over at least one third of the length of the paddle, measured in a direction parallel to the axis.

26. An apparatus as claimed in claim 25, wherein the height of each paddle decreases continuously over at least one half of the length thereof.

27. An apparatus as claimed in claim 26, wherein the height of each paddle decreases continuously over at least three quarters of the length thereof.

28. An apparatus as claimed in claim 24, wherein each paddle has a distal edge that is arcuate over at least one third of the length thereof, measured in a direction parallel to the axis.

29. An apparatus as claimed in claim 28, wherein the distal edge of each paddle is arcuate over at least one half of the length thereof.

30. An apparatus as claimed in claim 29, wherein the distal edge of each paddle is arcuate over at least three quarters of the length thereof.

31. An apparatus as claimed in of claim 24, wherein three paddles are provided on each rotatable drum portion.

32. An apparatus as claimed in claim 1 or 5, wherein the apparatus is a polisher, grinder, granulator, peeler, coater or washing machine.

33. An apparatus as claimed in claim 1, wherein the rotator member is connected to a periphery of each rotatable drum portion.

34. An apparatus as claimed in claim 1, wherein the rotator member is connected to a shaft adjoining each rotatable drum portion.

35. An apparatus as claimed in claim 1, wherein the rotator member is a friction providing element.

36. A washing machine comprising a drum for containing and agitating an article of clothing, wherein the drum comprises at least two rotatable drum portions in rotatable connection with one another, and a rotator member in connection with each rotatable drum portion for rotating the drum portion about an axis.

37. A washing machine as claimed in claim 36, wherein the drum has at least one port for intake or exhaust of a liquid to or from an area internal to the drum.

38. A washing machine as claimed in claim 36, wherein at least one of the rotatable drum portions has at least one port for intake or exhaust of a liquid to or from an area internal to the drum.

39. An apparatus as claimed in claim 37, wherein the at least one port is on a peripheral portion of the drum.

40. An apparatus as claimed in claim 37, wherein the at least one port is on a peripheral portion of at least one of the rotatable drum portions.

41. An apparatus as claimed in claim 36, wherein the drum is seated in a tank.

42. A washing machine as claimed in claim 36, wherein a drive is in connection with each rotator member.

43. A washing machine as claimed in claim 36, wherein the rotatable drum portions are rotatable about a common axis.

44. A washing machine as claimed in claim 43, wherein the axis is horizontal.

45. A washing machine as claimed in claim 36, wherein the drum comprises two rotatable drum portions, each rotatable drum portion being substantially cylindrical in shape.

46. A washing machine as claimed in claim 42, wherein the drive comprises a controller capable of controlling adjacent rotatable drum portions to rotate at different speeds in the same direction.

47. A washing machine as claimed in claim 42, wherein the drive comprises a controller capable of controlling adjacent rotatable drum portions to rotate at the same speed in opposite directions.

48. A washing machine as claimed in claim 42, wherein the drive comprises a controller capable of controlling adjacent rotatable drum portions to rotate at different speeds in opposite directions.

49. A washing machine as claimed in claim 42, wherein the drive comprises a motor connected to a coupler, and a controller connected to the motor to control speed and directional rotation of the rotatable drum portions.

50. A washing machine as claimed in claim, 42 wherein each rotatable drum portion is connected to a common drive.

51. A washing machine as claimed in claim 42, wherein each rotatable drum portion is connected to a separate drive.

52. A washing machine as claimed in claim 36, wherein a first of the rotatable drum portions is located inside a second rotatable drum portion.

53. A washing machine as claimed in claim 52, wherein the second rotatable drum portion has a recess portion in which the first rotatable drum portion is accommodated.

54. A washing machine as claimed in claim 53, wherein the second rotatable drum portion has an operative portion separate from the recess portion.

55. A washing machine as claimed in claim 54, wherein the operative portion of the second rotatable drum portion has a diameter that is substantially the same as the diameter of the first rotatable drum portion.

56. A washing machine as claimed in claim 52, wherein the first and second rotatable drum portions are mounted on concentric shafts.

57. A washing machine as claimed in claim 36, wherein at least one of the rotatable drum portions comprises a plurality of paddles within an interior area of the drum portion.

58. A washing machine as claimed in claim 57, wherein each paddle is shaped so that the height thereof decreases continuously over at least one third of the length of the paddle, measured in a direction parallel to the axis.

59. A washing machine as claimed in claim 42, wherein the rotator member is connected to a periphery of each rotatable drum portion.

60. A washing machine as claimed in claim 42, wherein the rotator member is connected to a shaft adjoining each rotatable drum portion.

61. A washing machine as claimed in claim 42, wherein the rotator member is a friction providing element.

62. A method of agitating at least one solid article, comprising:

inserting the article into a drum, wherein the drum comprises a first rotatable drum portion and a second rotatable drum portion in rotatable connection with one another; and

rotating the first and second drum portions independently of one another to agitate the article.

63. The method of claim 62, wherein fluid is provided within the drum as the first and second drum portions are rotated.

64. The method of claim 62, wherein the fluid is added to or exhausted from the drum through at least one port at a peripheral portion of the drum.

65. The method of claim 64, wherein the fluid is added to or exhausted from the drum through at least one port at a peripheral portion of at least one of the drum portions.

66. The method of claim 63, wherein the fluid is water.

67. The method of claim 62, wherein the solid at least one article is an article of clothing.

68. The method of claim 62, wherein the drum is provided horizontally within the tank.

69. The method of claim 62, wherein the rotatable drum portions are rotated in opposite directions.

70. The method of claim 62, wherein the rotatable drum portions are rotated at the same speed in opposite directions.

71. The method of claim 62, wherein the rotatable drum portions are rotated at different speeds in the same direction.

72. The method of claim 62, wherein the rotatable drum portions are rotated at different speeds in opposite directions.

73. The method of claim 62, wherein at least one of the rotatable drum portions is held stationary while the other rotatable drum portion is rotated.

74. The method of claim 62, wherein the rotatable drum portions are rotated at the same speed and in the same direction.

75. An apparatus comprising a drum for containing and agitating an article, wherein the drum comprises at least two rotatable drum portions in rotatable connection with one another, and a rotator member in connection with each rotatable drum portion for rotating the drum portion about an axis, wherein one of the rotatable drum portions has an end wall attached thereto and another of the rotatable drum portions has an end wall with an opening therein for inserting the article into the drum.

76. The apparatus as claimed in claim 75, wherein at least one port is located on the drum for intake or exhaust of a liquid to or from an area internal to the drum.

77. An apparatus as claimed in claim 76, wherein the at least one port is on a peripheral portion of the drum.

78. An apparatus as claimed in claim 77, wherein the at least one port is on a peripheral portion of at least one of the rotatable drum portions.

79. An apparatus as claimed in claim 75, wherein the drum is seated in a tank.

80. An apparatus as claimed in claim 75, wherein a one of the rotatable drum portions is located inside another rotatable drum portion.

81. An apparatus as claimed in claim 80, wherein the rotatable drum portions are mounted on concentric shafts.

82. An apparatus as claimed in claim 75, wherein at least one of the rotatable drum portions comprises a plurality of paddles within an interior area of the drum portion.

83. An apparatus comprising a drum for containing and agitating an article, wherein the drum comprises at least two rotatable drum portions in rotatable connection with one another, and a rotator member in connection with each rotatable drum portion for rotating the drum portion about an axis, wherein an opening for inserting the article into the drum is provided at a peripheral portion of one or more of the rotatable drum portions.

84. The apparatus as claimed in claim 83, wherein at least one port is located on the drum for intake or exhaust of a liquid to or from an area internal to the drum.

85. An apparatus as claimed in claim 84, wherein the at least one port is on a peripheral portion of the drum.

86. An apparatus as claimed in claim 85, wherein the at least one port is on a peripheral portion of at least one of the rotatable drum portions.

87. An apparatus as claimed in claim 83, wherein the drum is seated in a tank.

88. An apparatus as claimed in claim 83, wherein a one of the rotatable drum portions is located inside another rotatable drum portion.

89. An apparatus as claimed in claim 88, wherein the rotatable drum portions are mounted on concentric shafts.

90. An apparatus as claimed in claim 83, wherein at least one of the rotatable drum portions comprises a plurality of paddles within an interior area of the drum portion.

* * * * *