




(86) Date de dépôt PCT/PCT Filing Date: 2000/12/05
(87) Date publication PCT/PCT Publication Date: 2001/06/14
(45) Date de délivrance/Issue Date: 2006/10/24
(85) Entrée phase nationale/National Entry: 2002/05/27
(86) N° demande PCT/PCT Application No.: US 2000/042561
(87) N° publication PCT/PCT Publication No.: 2001/041948
(30) Priorité/Priority: 1999/12/08 (US09/456,345)

(51) Cl.Int./Int.Cl. *B21D 51/38* (2006.01),
B21D 51/32 (2006.01), *B21D 51/44* (2006.01)
(72) Inventeur/Inventor:
NEINER, CHRISTOPHER G., US
(73) Propriétaire/Owner:
METAL CONTAINER CORPORATION, US
(74) Agent: KIRBY EADES GALE BAKER

(54) Titre : FERMETURE DE COUVERCLE DE CANETTE ET PROCEDE D'ASSEMBLAGE D'UNE FERMETURE DE
COUVERCLE DE CANETTE A UN CORPS DE CANETTE
(54) Title: CAN LID CLOSURE AND METHOD OF JOINING A CAN LID CLOSURE TO A CAN BODY



(57) Abrégé/Abstract:

A preferred embodiment of the disclosed can lid has a center panel (12) having a central axis (14) that is perpendicular to a diameter of the outer rim, or peripheral curl portion (38), of the can lid (10), an annular countersink (16) surrounding the center panel (12), an arcuate chuckwall (132) extending radially outward from the annular countersink (16), an arcuate step portion (34) extending radially outward from the arcuate chuckwall (132), a transitional portion (36) extending radially outward from the arcuate step portion (34), and a peripheral curl portion (38) extending outwardly from the transitional portion (36).

ABSTRACT OF THE DISCLOSURE

A preferred embodiment of the disclosed can lid has a center panel (12) having a central axis (14) that is perpendicular to a diameter of the outer rim, or peripheral curl portion (38), of the can lid (10), an annular countersink (16) surrounding the center panel (12), an arcuate chuckwall (132) extending radially outward from the annular countersink (16), an arcuate step portion (34) extending radially outward from the arcuate chuckwall (132), a transitional portion (36) extending radially outward from the arcuate step portion (34), and a peripheral curl portion (38) extending outwardly from the transitional portion (36).

**CAN LID CLOSURE AND METHOD OF JOINING A
CAN LID CLOSURE TO A CAN BODY
TECHNICAL FIELD**

5 The present invention relates generally to metal containers, and more particularly to metal cans.

BACKGROUND OF THE INVENTION

10 Aluminum cans are used primarily as containers for retail sale of beverages in individual portions. Annual sales of such cans are in the billions and consequently, over the years, their design has been refined to reduce cost and improve performance. Other refinements have been made for ecological purposes, to improve reclamation and promote recycling.

15 Cost reductions may be realized in material savings, scrap reduction and improved production rates. Performance improvements may be functional in nature, such as better sealing and higher ultimate pressure capacity. Such improvements can allow the use of thinner sheet metal, which leads directly to material cost reductions. Performance improvements may also be ergonomic in nature, such as a can end configured to allow for easier pull tab access or better lip contact.

20 Aluminum cans are usually formed from a precoated aluminum alloy, such as the aluminum alloy 5182. The cans, which are typically made from relatively thin sheet metal, must be capable of withstanding pressures approaching 100 psi (7.03 kscm; 689.5 kilopascals), with 90 psi (6.32 kscm; 620.5 kilopascals) being an industry recognized requirement. The cans are usually formed from a can body to which is joined a can lid or
25 closure. Each of these components has certain specifications and requirements. For instance, the upper surface of the can lids must be configured to nest with the lower surface of the can bottoms so that the cans can be easily stacked one on top of the other. It is also desirable to have the can lids themselves nest with each other in a stacked arrangement for handling and shipping purposes prior to attaching the can lid to the can body. The ability to
30 satisfy these functional requirements with the use of ever less material continues to develop.

A prior art disclosure, published under the Patent Cooperation Treaty in International Publication Number WO 96/37414, discloses can lid design for reduced metal usage and improved pressure capability. This can lid comprises a peripheral portion or "curl," a frustroconical chuckwall depending from the interior of the peripheral curl, an outwardly concave annular reinforcing bead or "countersink" extending radially inwards from the chuckwall, and a center panel supported by the inner portion of the countersink. The frustroconical chuckwall is inclined at an angle of between 20° and 60° with respect to an axis perpendicular to the center panel. A double seam is formed between this can end and a can body by a process wherein the peripheral curl is centered on the can body flange by a frustroconical/cylindrical chuck designed to fit into the frustroconical chuckwall of the can lid. The overlap of the peripheral curl on the lid with the can body flange is described to be by a conventional amount. Rotation of the can lid/can body, first against a seaming roll and then a flattening roll completes a double seam between the two parts. During the flattening operation, the portion of the chuckwall adjacent to the peripheral curl is bent to a cylindrical shape and flattened against the cylindrical surface of the chuck. The lid of International Publication Number WO 96/37414 incorporates known dimensions for the peripheral curl portion which is seamed to the can.

The can lid disclosed in International Publication Number WO 96/37414 requires a greater amount of metal than the can lid of the present invention, thereby increasing the manufacturing costs. The increased metal usage in this prior art stems from a higher, or deeper, countersink, a larger peripheral curl portion than is disclosed in the present invention and the use of a frustroconical chuckwall that is characterized by a single angle with respect to an axis perpendicular to the central panel. The can lid disclosed in WO 96/37414 is also susceptible to increased metal deformation during seaming and failure at lower pressures. The can lid disclosed in International Publication Number WO 96/37414 neither discloses nor suggests a can lid having an arcuate chuckwall. Neither does International Publication Number WO 96/37414 disclose or suggest a can lid having an optional step portion or transitional portion between the chuckwall and peripheral curl portions. Therefore, International Publication Number WO 96/37414 does not fully anticipate the invention disclosed in the present application.

Similarly, while UK Patent Application GB-A- 2 315 478 and European Patent Specification EP-A-0 340 955 describe can end shells, neither disclose or suggest a can lid having an arcuate chuckwall or an optional step portion or transitional portion between the chuckwall and peripheral curl portions. Therefore, neither UK Patent Application GB-A- 2 315 or European Patent Specification EP-A-0 340 955 fully anticipate the invention disclosed in the present application.

Although PCT published patent application WO 98/34743 discloses a can lid that has a two part chuckwall, similar to a can lid having a chuckwall and step portion, nothing in patent application WO 98/34743 suggests or discloses that either the chuckwall or step portion be of an arcuate shape as does the invention disclosed in the present application. Nor would it be an obvious improvement to one skilled in the art to create a chuckwall or step portion having an arcuate shape.

SUMMARY OF THE INVENTION

15

The present invention contemplates improved aluminum can lids combining an arcuate chuckwall with a reduced seam. A preferred embodiment of the disclosed can lid has a center panel having a central axis that is perpendicular to a diameter of the outer rim of the can lid, an annular countersink extending radially outward from the center panel, an arcuate chuckwall extending radially outward from the annular countersink, a step portion, a transitional portion extending radially outward from the chuckwall, and a peripheral curl extending outwardly from the transitional portion. The step portion improves the consistency and integrity of a double seam formed between the can lid and the can body while the arcuate chuckwall improves the strength of the can lid as compared to a simple frustroconical chuckwall. These features reduce metal usage in manufacturing and are expected to reduce filled can failures, and allow the use of thinner sheet metal for the can lid.

20
25

3a

In accordance with one aspect of the present invention there is provided a method of forming a double seam joining a can body to a can lid, the can lid having an arcuate chuckwall inclined at an angle of from about 20° to about 80°, a step portion joining the arcuate chuckwall to a transitional portion, and a peripheral curl, and the

5 can body having a can body flange, comprising the steps of: supporting the can body on a base plate; positioning the can lid on the can body with the transitional portion resting on the can body flange; providing a chuck having a lower portion and a substantially cylindrical upper portion, the lower portion configured to closely conform to the arcuate chuckwall surface and the surface of the step portion when the

10 chuck is in engagement with the can lid; engaging the can lid with the chuck; rolling the peripheral curl and can body flange together to form an intermediate interlocking peripheral seam; and compressing the intermediate interlocking peripheral seam against the upper portion of the chuck to form a double seam..

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings are incorporated into and form a part of the specification to assist in explaining the present inventions. The drawings are intended for illustrative purposes only and are not intended as exact representations of the embodiments of the present inventions. The drawings further illustrate preferred examples of how the inventions can be made and used and are not to be construed as limiting the inventions to only those examples illustrated and described. The various advantages and features of the present inventions will be apparent from a consideration of the drawings in which:

10 **FIGURE 1 shows an elevational cross-sectional view of a can lid constructed in accordance with the invention;**

FIGURE 2 shows an elevational cross-sectional view of a can lid on a can body before forming of a double seam;

15 **FIGURE 3 shows an elevational cross-sectional view of a can lid on a can body as it appears during the first step of forming a double seam;**

FIGURE 4 shows an elevational cross-sectional view of a can lid on a can body as it appears during the final step of forming a double seam;

FIGURE 5 shows an elevational cross-sectional view of the manner of stacking can lids constructed in accordance with the invention; and

20 **FIGURE 6 shows an elevational cross-sectional view of the manner of stacking filled cans of the present inventions.**

DETAILED DESCRIPTION OF THE DRAWINGS

The present inventions are described in the following text by reference to drawings of examples of how the inventions can be made and used. The drawings are for illustrative purposes only and are not exact scale representations of the embodiments of the present inventions. In these drawings, the same reference characters are used throughout the views to indicate like or corresponding parts. Figure 1 illustrates one preferred embodiment of can lid 10. The embodiments shown and described herein are exemplary. Many details are well known in the art, and as such are neither shown nor described. It is not claimed that all of the details, parts, elements, or steps described and shown were invented herein. Even though numerous characteristics and advantages of the present inventions have been described in the drawings and accompanying text, the description is illustrative only, and changes may be made, especially in matters of arrangement, shape and size of the parts, within the principles of the invention to the full extent indicated by the broad general meaning of the terms used in the claims. The dimensions provided in the description are tooling dimensions and the actual dimensions of can lids manufactured in accordance with the present invention may vary.

FIGURE 1 is a cross-section view of a can lid 10, illustrative of a preferred embodiment of the present inventions. Can lid 10 is preferably made from aluminum sheet metal. Typically, an aluminum alloy is used, such as aluminum alloy 5182. The sheet metal typically has a thickness of from about 0.080 to about 0.100 inches (2.032 to about 2.540 mm), more preferably from about 0.082 to about 0.094 inches (2.083 to about 2.388 mm), and still more preferably from about 0.084 to about 0.088 inches (2.134 to about 2.235 mm). The sheet metal may be coated with a coating (not shown) on at least one side. This coating is usually provided on that side of the sheet metal that will form the interior of the can. Can lids are usually formed in a multi-step operation. Those skilled in the art will be well acquainted with such methods of forming can lids to provide the configuration and geometry of the can lid 10 as described herein.

The can lid 10 has a center panel 12. The center panel 12 is generally circular in shape but may be intentionally noncircular. The center panel 12 may have a diameter d_1 of from about 1.5 to about 2 inches (38.099 to about 50.8 mm), more preferably from about 1.6 to about 1.9 inches (40.64 to about 48.26 mm), and still more preferably from about 1.7 to

about 1.8 inches (43.18 to about 45.72 mm). Although the center panel 12 is shown as being flat, it may also have a peaked or domed configuration as well, and is not necessarily limited to the flat or planar configuration. The center panel 12 has a central axis 14 that is perpendicular to a diameter d_2 of the outer rim, or peripheral curl portion 38, of can lid 10. The diameter d_1 of center panel 12 is preferably less than 80% of the diameter d_2 of the outer rim, or peripheral curl portion 38, of can lid 10.

Surrounding the center panel is an annular countersink 16 that is formed from an interior wall 20 and an exterior wall 28, which are spaced apart and joined together by a curved bottom portion 24. The inner and outer walls 20, 28 are generally flat and may be parallel to one another or at a slight angle, with the bottom portion 24 being curved. The inner and outer walls 20, 28 are preferably parallel to central axis 14 but either or both may diverge by an angle of about as much as 15° . The annular countersink 16 is joined to the center panel 12 along the upper edge of the interior wall 20. The curved juncture 18 joining interior wall 20 and edge of the center panel 12 has a radius of curvature r_1 , that is from about 0.013 to about 0.017 inches (.330 to about .431 mm), more preferably from about 0.014 to about 0.016 inches (.355 to about .406 mm), and still more preferably from about 0.01425 to about 0.01525 inches (.3619 to about .387 mm), though this radius of curvature r_1 is not considered critical. The center-point of radius of curvature r_1 is located below the profile of can lid 10. Interior wall 20 is joined to bottom portion 24 by curved juncture 22 having a radius of curvature r_2 . Radius of curvature r_2 is from about 0.006 to about 0.018 inches (.152 to about .457 mm), more preferably from about 0.009 to about 0.015 inches (.228 to about .380 mm), and still more preferably from about 0.011 inches to about 0.013 inches (.279 to about .330 mm), though radius of curvature r_2 is not considered critical. The center-point of radius of curvature r_2 is located above the profile of can lid 10. Bottom portion 24 is joined to outer wall 28 by curved juncture 26, having a radius of curvature r_3 that is from about 0.010 to about 0.022 inches (.254 to about .559 mm), more preferably from about 0.012 to about 0.020 inches (.304 to about .508 mm), and still more preferably from about 0.014 to about 0.018 inches (.355 to about .457 mm). Radius of curvature r_3 has a center-point located above the profile of can lid 10 and is also not considered critical. The annular countersink 16 has a height h_1 of from about 0.03 to about 0.115 inches (.761 to about 2.921 mm), more

preferably from about 0.05 inches to about 0.095 inches (1.27 to about 2.413 mm), and still more preferably from about 0.06 to about 0.085 inches (1.523 to about 2.159 mm).

The annular countersink 16 is joined to chuckwall 132 by curved juncture 30 having a radius of curvature r_4 of from about 0.03 to about 0.07 inches (.762 to about 1.778 mm), more preferably from about 0.035 to about 0.06 inches (.889 to about 1.524 mm), and still more preferably from about 0.0375 to about 0.05 inches (.952 to about 1.27 mm), though not considered critical. The center-point of radius of curvature r_4 is located below the profile of can lid 10. Chuckwall 132 is shown as an arcuate chuckwall having a radius of curvature r_5 that is from about 0.4 to about 1 inch (10.16 to about 25.4 mm), more preferably from about 0.520 to about 0.845 inches (13.208 to about 21.463 mm), still more preferably from about 0.620 to about 0.745 inches (15.748 to about 18.923 mm), and most preferably from about 0.670 to about 0.695 inches (17.108 to about 17.653 mm). The center-point of radius of curvature r_5 is located below the profile of can lid 10. The arcuate chuckwall 132 is such that a line passing through the innermost end of arcuate chuckwall 132, near the terminus of curved juncture 30, and the outermost end of the arcuate chuckwall 132, near the beginning of step portion 34, forms an acute angle with respect to central axis 14 of the center panel 12. This acute angle is from about 20° to about 80° , and more preferably from about 30° to about 60° , and still more preferably from about 40° to about 50° .

The step portion 34 extends radially outward from the arcuate chuckwall 132. Step portion 34 is preferably curved with a radius of curvature r_6 of from about 0.02 to about 0.06 inches (.508 to about 1.524 mm), more preferably from about 0.025 to about 0.05 inches (.635 to about 1.27 mm), still more preferably from about 0.03 to about 0.05 inches (.762 to about 1.27 mm), and most preferably from about 0.035 to about 0.045 inches (.889 to about 1.143 mm). The radius of curvature r_6 has a center-point located above the profile of the can lid 10.

Transitional portion 36 extends radially outward from step portion 34. Transitional portion 36 has a radius of curvature r_7 of from about 0.04 to about 0.09 inches (1.016 to about 2.286 mm), more preferably from about 0.05 to about 0.08 inches (1.27 to about 2.032 mm), and still more preferably from about 0.06 to about 0.07 inches (1.524 to about 1.778 mm). Radius of curvature r_7 has a center-point located below the profile of can lid 10. Peripheral curl portion 38 extends radially outward from transitional portion 36. Peripheral curl portion

38 has a height h_2 of from about 0.04 to about 0.09 inches (1.016 to about 2.286 mm), more preferably from about 0.0475 to about 0.0825 inches (1.206 to about 2.096 mm), still more preferably from about 0.055 to about 0.075 inches (1.397 to about 1.905 mm), and most preferably from about 0.06 to about 0.07 inches (1.524 to about 1.778 mm).

5 Transitional portion 36 extends radially outward from chuckwall 132, as opposed to extending radially outward from step portion 34 when the can lid has no step portion 34. Chuckwall 132 is connected to peripheral curl portion 38 by transitional portion 36.

FIGURE 2 shows can lid 10 resting on can body 40, and particularly resting on flange 42 of can body 40. Can body 40 is supported by a base plate 45 (not shown) which together
10 with chuck 44 is mounted for rotation about axis 14. Chuck 44 includes a driving surface 46 configured to match and engage with the surface of chuckwall 132 and with radius of curvature r_6 . Chuck 44 includes a substantially cylindrical upper portion 48. As discussed below, upper portion 48 may be modified by a draft angle for production purposes. A limited clamping force between chuck 44 and base plate 45 (not shown) provides adequate friction
15 between chuck 44 and chuckwall 132 for positive rotation of can lid 10 and can body 40.

FIGURE 3 shows the initial stage of double seam formation between can lid 10 and can body 40. Roller 50 bears against peripheral curl portion 38 and the centering force exerted by chuck 44. Chuck 44 drives can lid 10 and can body 40 to rotate, generating a rolling, swaging action that reforms transitional portion 36, peripheral curl portion 38, and
20 flange 42 into an intermediate peripheral seam 52. Radius of curvature r_6 bears against chuck 44 to support transitional portion 36 and peripheral curl portion 38 leads the rolling deformation against roller 50. Thus positive support and guidance work together to achieve consistent and reliable results in producing intermediate peripheral seam 52.

FIGURE 4 shows the final stage of forming a double seam between can lid 10 and can
25 body 40. Here, roller 60 bears against intermediate peripheral seam 52 as it is supported by chuck 44. Chuck 44 drives can lid 10 and can body 40 to rotate, so that the pressure of roller 60 flattens intermediate peripheral seam 52 against upper portion 48 of chuck 44, producing double seam 54. Upper portion 48 of chuck 44 may be modified to include a draft angle for ease of separation of can lid 10 after this operation.

30 FIGURE 5 shows the manner in which a plurality of can lids 10 stack for handling, packaging, and feeding a seaming machine. Annular countersink 16a of can lid 10a bears

down against chuckwall 132b near curved juncture 30b of adjacent can lid 10b. Can lid 10a is supported and separated from can lid 10b by a height h_3 sufficient to accommodate the thickness of a pull-tab (not shown). In this manner, can lids 10 are compactly and efficiently handled and are more readily positioned for magazine feeding of a mechanized seaming operation.

FIGURE 6 shows the manner of stacking filled can 64a, closed and sealed according to the present invention on a like filled can 64b. Stand bead 66a rests upon double seam 54b.

The following table indicates model test results on buckle pressures for a prior art can lid and an embodiment of the present invention. The buckle pressure is the pressure at which a sealed can experiences seam failure. The industry standard for minimum acceptable buckle pressure is around 90 psi (6.32 kscm; 620.5 kilopascals). This table is based solely on model results and is included for illustrative purposes only. These model results indicate that implementation of an embodiment of the present invention will result in obtaining a buckle pressure no worse than a prior art can lid.

CAN LID	BUCKLE PRESSURE (PSI)
Prior Art Can Lid With Mini Seam and Nonarcuate Chuckwall	Basis
Can Lid of FIG. 1 With Reduced Seam Peripheral Curl, Arcuate Chuckwall, and Step Portion	4 psi (<u>0.028 kscm; 27.6 kilopascals</u>) above basis

The embodiments shown and described above are exemplary. Many details are often found in the art and, therefore, many such details are neither shown nor described. It is not claimed that all of the details, parts, elements, or steps described and shown were invented herein. Even though numerous characteristics and advantages of the present inventions have been described in the drawings and accompanying text, the description is illustrative only, and changes may be made in the detail, especially in matters of shape, size, and arrangement of the parts within the principles of the inventions to the full extent indicated by the broad meaning of the terms of the attached claims.

The restrictive description and drawings of the specific examples above do not point out what an infringement of this patent would be, but are to provide at least one explanation

of how to use and make the inventions. The limits of the inventions and the bounds of the patent protection are measured by and defined in the following claims.

I claim:

1. A lid for a can body comprising:
 - a center panel having a central axis that is perpendicular to a diameter of the outer rim of said lid;
 - 5 an annular countersink surrounding said center panel;
 - an arcuate chuckwall extending radially outward from said annular countersink, wherein a line passing through the ends of said chuckwall is at an angle with respect to said central axis of the center panel of from about 20° to about 80°; and
 - a peripheral curl portion having a height less than 0.091 inches (2.311 mm) extending
 - 10 radially outward from said chuckwall.
2. The can lid according to claim 1 wherein a line passing through the ends of said chuckwall is at an angle with respect to said central axis of the center panel of from about 30° to about 60°.
- 15 3. The can lid according to claim 1 wherein a line passing through the ends of said chuckwall is at an angle with respect to said central axis of the center panel of from about 40° to about 50°.
- 20 4. The can lid according to claim 1 wherein the height of said peripheral curl portion is from about 0.04 to about 0.09 inches (1.016 to about 2.286 mm).
5. The can lid according to claim 1 further comprising a transitional portion extending radially outward from said chuckwall, wherein the peripheral curl portion extends radially
- 25 outward from said transitional portion.
6. The can lid according to claim 1 wherein said center panel is substantially flat or planar.
- 30 7. The can lid according to claim 1 wherein said center panel is arcuate.

8. The can lid according to claim 1 wherein said arcuate chuckwall has a radius of curvature of from about 0.4 to about 1 inch (10.16 to about 25.4 mm), the center-point of said radius located below the profile of said lid.

5 9. The can lid according to claim 1 further comprising a step portion extending radially outward from said chuckwall.

10. The can lid according to claim 9 wherein said step portion is arcuate.

10 11. The can lid according to claim 10 wherein said arcuate step portion has a radius of curvature of from about 0.02 to about 0.06 inches (.508 to about 1.524 mm), the center-point of said radius being located above the profile of said lid.

12. The can lid according to claim 1 wherein said annular countersink has a height of
15 from about 0.030 to about 0.115 inches (.762 to about 2.921 mm).

13. The can lid according to claim 1 further comprising:
a step portion extending radially outward from said chuckwall; and
a transitional portion extending radially outward from said step portion.

20

14. The can lid according to claim 13 wherein said step portion is an arcuate step portion.

15. The can lid according to claim 1 wherein said annular countersink has a height of
from about 0.030 to about 0.115 inches (.762 to about 2.921 mm);

25 wherein an arcuate step portion extends radially outward from said arcuate chuckwall
wherein said arcuate step portion has a radius of curvature of from about 0.02 to about 0.06
inches (.508 to about 1.524 mm), the center-point of said radius being located above the
profile of said lid;

wherein a transitional portion extends radially outward from said arcuate step portion;

30 and

wherein said peripheral curl portion extends radially outward from said transitional
portion.

16. A method of forming a double seam joining a can body to a can lid, the can lid having an arcuate chuckwall inclined at an angle of from about 20° to about 80°, a step portion joining the arcuate chuckwall to a transitional portion, and a peripheral curl, and the can body having a can body flange, comprising the steps of:

5 supporting the can body on a base plate;

positioning the can lid on the can body with the transitional portion resting on the can body flange;

providing a chuck having a lower portion and a substantially cylindrical upper portion, the lower portion configured to closely conform to the arcuate chuckwall
10 surface and the surface of the step portion when the chuck is in engagement with the can lid;

engaging the can lid with the chuck;

rolling the peripheral curl and can body flange together to form an intermediate interlocking peripheral seam; and

15 compressing the intermediate interlocking peripheral seam against the upper portion of the chuck to form a double seam.

1/3

FIG. 1





FIG. 2



2/3

FIG. 3




FIG. 4




FIG. 5




FIG. 6

