United States Patent [19]

Davis, Jr.

[11] **3,813,834**

[45] **June 4, 1974**

[54] **JOIST WITH NAILING STRIP AND POSITIONING MEMBERS**

[75] Inventor: **George Bradley Davis, Jr.**, Boulder, Colo.

[73] Assignee: **Products Engineering, Inc.**, Boulder, Colo.

[22] Filed: **May 24, 1972**

[21] Appl. No.: **256,257**

Related U.S. Application Data

[63] Continuation-in-part of Ser. No. 41,426, May 28, 1970, abandoned.

[52] **U.S. Cl.** **52/223,** 52/364, 52/374, 52/699

[51] **Int. Cl.** **E04b 1/41,** E04c 3/18

[58] **Field of Search** 52/364, 368, 374, 699, 52/223; 249/28, 30

[56] **References Cited**

UNITED STATES PATENTS


1,251,150	12/1917	Widmer	52/331
1,466,264	8/1923	Ambursen	52/328
1,470,727	10/1923	Hall	52/699 X
1,953,138	4/1934	Sylvester	52/699
2,123,923	7/1938	Alsted	52/327
3,289,379	12/1966	Watts	52/689
3,528,209	9/1970	Schillinger	52/223

Primary Examiner—Alfred C. Perham
Attorney, Agent, or Firm—Duane Burton

[57] **ABSTRACT**

A structural element having a fire rating of approximately two hours when tested with the standard time-temperature curve established by the American Standards for Testing Materials, said element including prestressed concrete joists each having a plate-like body portion and one or more integrally formed reinforced support ledges wherein each ledge has a nailing strip integrally molded adjacent the bottom thereof and each nailing strip including a penetratable area formed internally adjacent thereof, a plurality of sheets of material disposed adjacent the ends of said ledges, each sheet of material forming at least one butt joint with an adjacent sheet wherein said butt joint extends longitudinally along a portion of one of said ledges, a plurality of channel-shaped members disposed along each butt joint intermediate said ledge portion and said sheets and attachment means for attaching said channel-shaped members to the nailing strips and, also, for attaching sheets of material to said nailing strips and channel-shaped members whereby said sheets of material are secured to the joist while preventing undesirable distortion or warping thereof during the fire rating tests. This invention also relates to a pretensioned concrete joist of the T-type comprising a concrete plate-like body portion, a channel-shaped support ledge, a nailing strip integrally molded in the bottom of said ledge, said nailing strip including a channel-shaped member having a penetratable layer of material disposed therein and a plurality of positioning members longitudinally spaced along said channel-shaped member, and pretensioning steel extending longitudinally of said ledge and disposed in contacting engagement with said positioning members, said pretensioning steel and said positioning members cooperating to secure and maintain the nailing strip of the bottom surface of the ledge prior to and during placement of the concrete during forming of said joist. This invention also relates to a novel form member for producing a pretensioned concrete member having a nailing strip molded therein, and to a novel positioning member made from a single piece of plastic material.

9 Claims, 11 Drawing Figures






FIG. 2




FIG. 1

INVENTOR
GEORGE BRADLEY DAVIS, JR.
BY Sheridan, Ross & Burton
ATTORNEYS




FIG. 3




FIG. 4




FIG. 5




FIG. 6

INVENTOR
GEORGE BRADLEY DAVIS, JR.
BY Sheridan, Ross & Burton
ATTORNEYS




Fig. 7




Fig. 8




Fig. 9




Fig. 10




Fig. 11

JOIST WITH NAILING STRIP AND POSITIONING MEMBERS

This is a continuation-in-part application of U.S. Pat. application Ser. No. 41,426 filed on May 28, 1970 now abandoned.

BACKGROUND OF THE INVENTION

Joists or structural beams of the T-type (as used herein the term T-type shall also include twin T and quad T-types) are well known in the art. The ledge or ledges of this type of joists contain the main reinforcing of the structural member and act as the supporting member from which the ceiling is suspended. In the past, various expedients have been used to attach the wall or ceiling board to the ends of the ledges of the joists. The most common expedient is the use of the so-called "nailing strips" incorporated into the ends of the ledges. The nailing strips are ordinarily mechanically attached to the outside of a ledge as exemplified by the structure shown in U.S. Pat. No. 2,123,923. They are adapted to reeive bolts, screws, nails and the like to secure the wall board or other structural element to the ledges. The nails or screws are driven or screwed into a wooden beam, disposed behind the plate, after passing through the nailing plate itself.

Various means have been used to affix the nailing plate to the end of the ledges as shown in the above-referenced patent and in U.S. Pat. No. 1,466,264, for example. Anchors for supporting structural elements on the end of the ledges have been incorporated into the ends of the ledges by various means as illustrated by U.S. Pat. Nos. 1,251,150 and 1,953,138. Other patents relating generally to the field of the invention are U.S. Pat. No. 1,470,727 and British Pat. No. 838,452.

The known expedients for attaching nailing plates to the ends of the ledges of T-type joists are subject to various disadvantages. Wooden nailing plates are subject to shrinkage, rotting, destruction by termites and the like so that they are not generally satisfactory for permanent installations. The metal anchors, hooks and the like are subject to the disadvantage, along with the wooden nailing plates, that their installation is difficult and time-consuming and, consequently, expensive.

Heretofore, various structural elements have been proposed which have a fire rating of approximately two hours when tested with the standard time-temperature curve established by the American Standards for Testing Materials. However, any such structural element incorporating therein a T-type joist and which has successfully met this requirement involves the use of a T-type joist requiring approximately twice as much concrete to form as required in the structural element of this invention. More concrete was required to form the prior art type of joist since either thicker plate-like body portions and/or more massive ledges were required in order to withstand the temperatures involved.

Accordingly, it is a principal object of this invention to provide a novel structural element having a fire rating of approximately two hours when tested with the standard time-temperature curve established by the American Standards for Testing Materials, particularly when tested under the unrestrained assembly classification.

Another object of this invention is to provide a structural element as aforeaid comprising one or more prestressed concrete joists, each joist having a plate-like

body portion forming at least a part of a first side of said element, one or more integrally formed, reinforced support ledges disposed normal to the plate-like body portion, and a nailing strip integrally molded in the bottom of each ledge, each nailing strip including a penetratable area formed internally adjacent thereof, a plurality of sheets of material disposed adjacent the ends of said ledges, each sheet being formed from a material from the class consisting of gypsum or a mineral fiber mixture, said sheets forming the second side of said element and having a thickness equalling one-half inch or more, each sheet of material forming at least one butt joint with an adjacent sheet wherein said butt joint extends longitudinally along a portion of one of said ledges, a plurality of channel-shaped members disposed along each butt joint and intermediate said ledge portion and said sheets, attachment means for attaching said channel-shaped member to the nailing strips of said ledge portions, and additional attachment means for attaching said sheets of material to said nailing strips and said channel-shaped members, said additional attachment means, channel-shaped members and nailing strips cooperating to secure the sheets to said joist while preventing undesirable distortion or warping thereof during the fire rating test.

Another object of this invention is to provide a structural element as aforesaid in which each of the additional attachment means used to attach the sheets of material to the channel-shaped members disposed along said butt joints is positioned a minimum ditance of approximately one and one-fourth inches from the adjacent edge of each sheet.

Another object of this invention is to provide a structural element as aforedescribed in which each ledge of each joist has a plate-like body portion associated therewith, each ledge being disposed generally centrally of said associated therewith, each ledge being disposed generally centrally of said associated part, each associated part extending laterally of both sides of its associated ledge, taken along a line disposed normal to the longitudinal axis of its associated ledge to a point midway between said associated ledge and an adjacent ledge or the end of said plate-like body portion, whichever is the closer, the ratio of the cross-sectional area of the part of said plate-like body portion taken along a line disposed normal to the longitudinal axis of said ledge, to the width of its associated ledge, said width of said ledge being measureed along a line normal to the longitudinal axis of said associated ledge at the line of intersection of said ledge with said part, varying between approximately 7.5 to 10 inches, and the ratio of the cross-sectional area of its associated part, taken along a line disposed normal to the longitudinal axis of said ledge, being equal to approximately 2 or less.

Another object of this invention is to provide a structural element as aforesaid in which the ratio of the cross-sectional area of the part of the plate-like body portion to the width of its associated ledge varies between approximately 8 to 9 inches and the ratio of the cross-sectional area of each ledge to each cross-sectional area of its associated part is equal to approximately one or less.

Another object of this invention is to provide a pretensioned concrete joist of T-type comprising a concrete plate-like body portion, a channel-shaped concrete support ledge disposed normal to said body portion along the length thereof, a nailing strip integrally

molded in the bottom of said ledge, said nailing strip comprising a channel-shaped member, a longitudinally extending U-shaped portion formed along the upper edge of each side wall of each channel-shaped member with the longitudinal axis of each U-shaped portion lying in a plane in which is disposed generally parallel with the plane in which is disposed the bottom wall of said channel-shaped member and the bight of each U-shaped portion extending inwardly of its associated side wall, and a longitudinally extending penetratable layer of material disposed within said channel-shaped member and upper surface portions of said channel-shaped member and having portions thereof disposed within the U-shaped portions extending longitudinally along the upper edge of each side wall of said channel-shaped member, and pretensioning steel extending longitudinally of said ledge and disposed in contacting engagement with the upper surface of said positioning members, said pretensioning steel and said positioning members cooperating to secure and maintain the nailing strip on the bottom surface of the ledge prior to and during placing of the concrete during forming of the joist.

Another object of this invention is to provide a pretensioned concrete joist as aforedescribed in which each of said positioning members comprises an elongate support portion, and a pair of L-shaped portions each L-shaped portion including a pair of arms, each L-shaped portion depending from a corresponding one of the arms of said support portions and having one of said arms disposed parallel with said support portion, each L-shaped portion being contructed for limited pivotal movement relative to said support portion, each free end of the arms that are disposed generally parallel with said support portion being positioned within a corresponding one of the longitudinally extending U-shaped portions formed along the upper edge of each side wall of said channel-shaped member

Another object of this invention is to provide a form member for use with a mold for making a pretensioned concrete member having a nailing strip molded therein, said form member comprising a longitudinally extending, channel-shaped member for disposition in the bottom of said mold member and a plurality of positioning members longitudinally spaced along said channel-shaped member and secured thereto.

Another object of this invention is to provide a novel positioning member for positioning an object in a hollow member such as a mold member, said positioning member being formed from a single piece of plastic material and comprising an elongate support portion the upper surface of which is concave in configuration, and a pair of L-shaped portions, each L-shaped portion including a pair of arms, each L-shaped portion depending from a corresponding one of the ends of said support portions and having one of said arms disposed parallel with said support portion, each L-shaped portion being constructed for limited pivotal movement relative to said support portion, and the free ends of said arms that are disposed generally parallel with said support portion, lying generally in a common plane and spaced apart one from the other, said free ends being constructed for engaging a portion of the object.

Another object of this invention is to provide a novel positioning member as aforesaid in which each of the arms of said L-shaped portions that are integrally attached to said support portion are convergently disposed one to the other in a direction proceeding from said support portion toward the arms disposed generally parallel with said support portion.

Another object of this invention is to provide a novel positioning member as aforedescribed in which the angle of convergence of the arms that are integrally attached to said support portion equals at least approximately 4° or more, and preferably approximately 6°.

Another object of this invention is to provide a novel positioning member as aforedescribed in which the upper surface of said support portion is concave in configuration.

Another object of this invention is to provide a novel positioning member as aforedescribed including means interconnecting a portion adjacent the free end of each arm disposed generally parallel with said support portion thereby preventing undesirable entanglement of one plastic member with another when packed "loosely" in a contaier.

Another object of this invention is to provide a novel positioning member including tab means extending longitudinally outwardly of the opposite ends of said support portion and longitudinally outwardly of the pair of arms disposed generally parallel with said support portion.

Another object of this invention is to provide a novel positioning member as aforedescribed in which each free end of each arm lying genernally in a common plane includes a portion disposed generally normal to the longitudinal axis of its corresponding arm and likewise is disposed within said common plane.

Another object of this invention is to provide a novel positioning member as aforedescribed in which each L-shaped portion includes stiffening means for controlling the overall stiffness thereof wherein said stiffening means preferably includes a diagonally disposed member interconnecting the arms of each L-shaped portion.

Another object of this invention is to provide a novel positioning member as aforedescribed in which the outer ends of said support portion and said L-shaped portions are connected by a pair of convergently disposed lines proceeding along said lines in a direction from each outer end of said support portion to the corresponding outer end of said L-shaped portion.

SUMMARY OF THE INVENTION

A structural element having a fire rating of approximately two hours when tested with the standard time-temperature curve established by the American Standards for Testing Materials, said element having first and second sides, said second side, during the fire rating test of said element being exposed to flames, said element comprising one or more prestressed concrete joists wherein each joist has a plate-like body portion forming at least a part of the first side of said element and one or more integrally formed, reinforced support ledges disposed normal to the plate-like body portion, each ledge having a nailing strip integrally molded at the bottom thereof, each nailing strip including a penetratable area formed internally adjacent thereof, a plurality of sheets of material disposed adjacent the ends of said ledges, said sheets being formed from a material selected from the class consisting of gypsum or a mineral fiber mixture, said sheets forming the second side of said element and having the thickness of said material equaling one-half inch or more, each sheet forming at least one butt joint with an adjacent sheet, said butt

joint extending longitudinally along a portion of one of said ledges, a plurality of channel-shaped members, each channel-shaped member being disposed along each butt joint and intermediate said ledge portions and said sheets, and attachment means for attaching said channel shaped members to the nailing strips of said ledge means and, also, for attaching said sheets of material to said nailing strips and said channel-shaped members, said attachement means, channel-shaped members and nailing strips cooperating to secure the sheets to said joist while preventing undesirable distortion or warping thereof during the fire rating test. The channel-shaped members prevent the edge of the sheet adjacent said butt joint from pulling away from the adjacent sheet as a result of the stresses to which same is subjected during the fire rating test. The pretensioned concrete joist of the T-type includes a nailing strip integrally molded in the bottom of said ledge, said nailing strip comprising a channel-shaped member having longitudinally extending U-shaped portions formed along the upper edge of each side wall of each channel-shaped member, the longitudinal axis of each U-shaped portion lying in a plane disposed generally parallel with a plane in which is disposed a bottom wall of said channel-shaped member, the bight of each U-shaped portion extending inwardly of its associated side wall, and a longitudinally extending attachment means-penetrating layer of material disposed within said channel-shaped member, said layer of material having a lower surface portion disposed in contact with the bottom wall of said channel-shaped member and upper surface portions disposed in abutting contact with said U-shaped portions of said channel-shaped member, said attachment-means-penetrating layer of material preventing concrete from entering into said channel-shaped member, and a plurality of positioning members longitudinally spaced along said channel-shaped member and having portions thereof disposed within the U-shaped portion thereof, and pretensioning steel extending longitudinally of said ledge and disposed in contacting engagement with the concave surface of the frame members of said positioning members, said pretensioning steel and said positioning members cooperating to secure and maintain the nailing strip on the bottom surface of the ledge prior to and during placing of the concrete during forming of said joist. The nailing strip includes a channel-shaped member as aforedescribed and the plurality of positioning members as aforedescribed.

One preferred embodiment of a novel positioning member is formed from a single piece of plastic material and comprises an elongate support portion and a pair of L-shaped portions, each L-shaped portion including a pair of arms, each L-shaped portion depending from a corresponding one of the ends of said support portion and having one of said arms disposed generally parallel with said support portion, each L-shaped portion being contructed for limited pivotal movement relative to said support portion, and the free ends of said arms, that are disposed generally parallel with said support portion, lying generally in a common plane and spaced apart one from the other, said free ends being constructed for engaging a portion of the channel-shaped member with which same is to be used.

Another embodiment of a positioning member useful in the form, joist and structural element of this invention is a member comprising an inverted U-shaped frame member including a bight portion overlying the upper edges of the channel-shaped member of the nailing strip and a pair of leg portions, the outer surface of said bight portion being generally concave in configuration and adapted to engage a pretensioning steel after the form member has been positioned within the mold, said frame portion lying in a plane disposed generally normal to the longitudinal axis of said channel-shaped member, a pair of legs, each leg having a first part attached to a corresponding one of the leg portions of the U-shaped frame member and a second part securely disposed within a corresponding one of the U-shaped portions of said channel-shaped member of said nailing strip, said second parts lying in a plane disposed generally normal to the plane in which is disposed said frame member, the outer surfaces of said U-shaped frame member being spaced such that they are adapted to be received between the opposed walls of the mold in which same is to be used whereby said outer surfaces of said leg portions serve as means for centering and positioning said form member within the channel-shaped portion of the mold in which same are to be used upon being dropped therein and are adapted to be disposed adjacent the inside surfaces of the opposed walls of the mold within which same are to be used.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention will now be described with reference to the accompanying drawings in which:

FIG. 1 is an end view of a T-type joist;

FIG. 2 is a partial cross section of the mold form in which a T-type joist is molded;

FIG. 3 is a partial cross section of the end of one of the legs of the mold of FIG. 2 showing the nailing strip and positioning member supported in the leg section of the mold;

FIG. 4 is a view taken on lines 4—4 of FIG. 3;

FIG. 5 is a cross-sectional view of a portion of a structural element constructed in accordance with the subject invention;

FIG. 6 is an elevational view of another embodiment of a structural element constructed in accordance with the subject invention, said element incorporating therein F-type joists;

FIG. 7 is a partial view showing the reflected ceiling plan of a structural element constructed in accordance with this invention;

FIG. 8 is a cross-sectional view of a portion of the structural element illustrated in FIG. 7 and showing a butt joint;

FIG. 9 is a perspective view of a preferred embodiment of a positioning member constructed in accordance with this invention:

FIG. 10 is a front elevational view of the positioning member shown in FIG. 9; and

FIG. 11 is a cross-sectional view taken on line 11-11 of FIG. 10.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring to FIG. 1, there is shown a structural element constructed in accordance with the subject invention, said element including an assembly of typical T-type joists 10 usually constructed of prestressed reinforced concrete. Each joist comprises a relatively thin concrete plate-like body portion 12 having integrally molded support ledges or ribs 14 that contain the main

reinforcing steel and the nailing strip or plate which supports a sheet of material **16** forming the ceiling or wall board. The sheet of material **16** is schematically shown attached to the ends of the ledges **14.** The two joists **10** are connected by a joint **17** filled with grout. The structural element also includes means (not shown in FIG. **1**) for satisfactorily attaching the sheet of material **16** to the ends of the ledge **14.**

Referring to FIG. **2,** a mold form **18** is shown in which a typical T-type joist shown in FIG. **1** is molded. The form **18** is comprised of a body section **20** in which the plate-like body portion of the joist is molded, and integral leg sections **22** in which the integral ledges or ribs **14** are molded. The form **18** is conventionally supported by means of gussets **24** and braces **26** suitably positioned to support the mold **18** when concrete is poured into it. The structure for supporting the mold forms no part of this invention.

Referring to FIGS. **3** and **4,** there is shown an assembly of nailing strip and positioning member positioned inside the leg of the mold prior to pouring concrete for molding a typical T-type joist and molding a nailing strip in the support ledge thereof. The nailing strip **28,** suitably made of sheet metal, such as a 25 ga. hot dipped galvanized sheet metal, extends the entire length of the leg **22** of the mold. The nailing stip **28** is of channel-shaped construction, as shown, with its base **30** resting on the inside or bottom surface of the end of leg **22** and its open channel section facing upwardly. The legs **22** are convergently formed, proceeding in a direction along said legs toward the base **30,** and this feature enhances the securement of said nailing strip within the concrete after it has set up. It includes sides **32** integrally connected to the base **30** and terminating at their upper ends in U-shaped sections **34** for a purpose to be described later. The longitudinal axis of each of the U-shaped sections **34** lie in a plane disposed generally parallel with a plane in which is disposed the base or bottom wall **30.** The bight of each said U-shaped portion extends inwardly of its associated side wall. The interior **36** of the channel-shaped nailing strip **28,** which is enclosed by the base **30** and the sides **32,** comprises a penetrable area into which nails, screw and the like used to attach the sheet of material **16** to the base **30,** penetrate. In order to prevent the space **36** from filling with concrete when the joist is molded, it is filled with a blocking material, such as expanded polystyrene, which is preferably secured to said nailing strip with contact cement. This prevents concrete from entering the interior of the channel-shaped nailing strip and still provides a penetrable area into which screws, nails and the like may penetrate when a wall or ceiling board is attached to the base **30** of the nailing strip.

In order to center properly the nailing strip **28** in the leg **22,** longitudinally spaced centering and hold down frames **38** are attached to the nailing strip **30** and inserted in the end of the leg **22** with it. The positioning frames **38** are suitably constructed from an elongated piece of material, such as metal wire, plastic and the like, and comprise a rectangular frame member having sides **40** joined at the top by U-shaped bridge member **42** and comprising a pair of legs having end members. Each leg has a first part **44** attached to a corresponding one of the sides **40** and extending inwardly in the same plane as the bridge member **42.** Each leg also has a second part **46** extending perpendicular to the plane of the frame **38** and disposed or seated in one of the U-shaped sections **34** of the nailing plate **28.** This construction maintains the U-shaped bridge member **42,** the sides **40** and the end the first parts **44** of said legs in a vertical plane, as viewed in FIGS. **3** and **4,** and precludes the necessity of forming notches or openings within the sides **32** and eliminates the time and labor required for precise positioning of said second parts **46** within any such openings. The positioning and supporting frames **38** are so dimensioned that their sides are disposed adjacent the inside surfaces of the sides of the leg **22** to center the nailing plate **28.** The bottom of the trough of the U-shaped bridge member **42** is the point at which the pretensioned reinforcing steel **15** exerts a downward force on the positioning frame **38** which in turn exerts a downward and inward locking force on the U-shaped channel **28.** It has been found that the application of a downwardly directed force by the steel **15** against members **42** causes the sides **40** to bow outwardly thereby increasing the securement of the frames **38** within the U-shaped sections **34.**

The molding of a prestressed reinforced joist of the T-type in accordance with the invention is performed as follows. The mold is cleaned and conventional release agents are applied to the interior thereof. The assembly of nailing strip **28** and its assembled centering and hold down frames **38,** with the channel-shaped nailing strip **28** being filled with expanded polystyrene or suitable material, is positioned in the end of leg **22** of the mold form **18.** Continuous reinforcing steel **15** is then positioned in the trough of the bridge section **42** of the support frames **38** disposed in the legs. The reinforcing steel **15** is then put under tension, thus making it rigid and causing it to exert a downward force on the frames **38.** The mold form **18** is then filled with concrete which is allowed to set properly. After the concrete is properly set, the finished joist is removed from the mold. The ledges **14** of the joist will have the nailing strip **28** integrally molded in the ends or along the bottoms thereof, as well as the support frames **38** and the reinforcing steel **15.**

FIG. **5** shows a support ledge of the T-type joist of the invention in which a ceiling or wall board element **50** is shown attached by screws **52** to the base **30** of nailing plate **28** with the screws penetrating into the penetrable area **36** and the penetrable material therein.

In FIG. **6** is shown another, although generally less commonly used, embodiment of a structural element constructed in accordance with the subject invention. The structural element **54** comprises one or more prestressed, concrete, F-type joists **56,** one or more sheets of material **58,** and attachement means (not shown) for attaching the sheet of material to the joist **56.** Each joist **56** includes a plate-like body portion **60** and one or more integrally formed, reinforced support ledges **62** disposed normal to the plate-like body portion **60.** Each ledge **62** of the element **54** has a nailing strip (not shown) integrally molded in the end thereof. Each ledge **62** of the element **54** has a part of said plate-like body **60** associated therewith, the length of each part being indicated generally by the arrow **64,** it being noted that each ledge **62** is disposed generally centrally of its associated part, taken along a line disposed normal to the longitudinal axis of said ledge. The rato of the cross-sectional area of the part of said plate-like body portion, taken along a line disposed normal to the longitudinal axis of said ledge, to the width of its associated ledge, said width of said ledge being measured

along the line of intersection of the sides of said ledge with the lower surface of the plate-like body portion, varies between approximately 7.5 to 10 inches. Although a transfer or preferably an arcuate surface may interconnect the ledges to the body portion, the width of the ledge referred to herein is limited to the distance between an extension of the sides of the ledge as aforesaid. The ratio of the cross-sectional area of each ledge to the cross-sectional area of its associated part, taken along a line disposed normal to the longitudinal axis of said ledge, is equal to approximately two or less, and preferably to approximately one or less. The sheet of material **58** disposed adjacent the ends of the ledges **62** is formed from a material selected from the class consisting of gypsum or mineral-fiber mixture, said mixture being non-combustible. The thickness of the material used to form the sheet **58** equals approximately one-half inch or more and preferably five-eigths inch or more where gypsum material is involved. It will be understood that the flames are exposed to the sheet of material **58** during the fire rating test.

In FIG. 7 is shown a partial view of a structural element **68** constructed in accordance with this invention and having a fire rating of approximately two hours when tested with the standard time-temperature curve established by the American Standards for Testing Materials where said element has an unrestrained classification. More specifically, the structural element **68** comprises a pair of longitudinally extending prestressed concrete joists **70** and **72.** One of the joists **70** has four longitudinally extending support ledges **74** while the other joist **72** has three longitudinally extending support ledges **76.** A grout joint (not shown) similar to grout joint **17** shown in FIG. **1** interconnects the adjacent sides of said joist **70** and **72.** Each joist includes a plate-like body portion forming at least a part of the first side of said element **68.** Each support ledge of each joist is integrally formed with the plate-like body portion of each joist disposed generally normal to said plate-like body portion. Each ledge is suitably reinforced with pretensioned steel **78,** see FIG. **8,** and has a nailing strip **80** integrally molded at the end or along the bottom surface of each ledge. A layer of penetrable material **82** is disposed within the channel-shaped member from which the nailing strip **80** is constructed.

The element **68** includes a plurality of sheets of material **84, 86, 88, 90, 92, 94** and **96** attached to the ends or the bottom surfaces of said ledges **72** and **74.** Said sheets are formed from a material selected from the class consisting of gypsum or a mineral fiber mixture. The sheets of material form the second side of said structural element **68** and the thickness of the material from which said sheets are made equals one-half inch or more and preferably five-eighths inches or more. Each sheet of material forms at least one butt joint **98** with an adjacent sheet of material. The butt joints **98** extend longitudinally along a portion of a corresponding one of said ledges.

The structural element **68** also includes a plurality of channel-shaped members **100,** shown only in FIG. **8.** The channel-shaped members **100** are disposed along each butt joint **98** and intermediate said ledge portion and said sheets of material. The channel-shaped member **100** is securely attached to the nailing strip **80** of its associated ledge through the use of attachment means **102** which extend through the bottom wall of the channel-shaped member forming the nailing strip **80** and into the penetrable layer of material **82.** The bottom wall of the channel-shaped member **100** extends laterally of the opposite sides of the ledge by a sufficient amount to permit ready attachment of the sheets of material to said channel-shaped member by attachment means **104.** For example, where the width of the bottom surface of the ledge, as shown in FIG. **8,** is approximately 3 to 3 ¼ inches, the width of the bottom wall of the channel-shaped member **100** is approximately 6 inches. The use of a 1 and ¼ inches by 6 inches, **20** gauge hot dipped galvanized metal **54** inches in length to form the channel-shaped member **100** has been found to be adequate. In this connection, it must be realized that channel-shaped member **100** must be sufficiently rigid to prevent undesirable distortion of the sheets of material attached thereto during the fire rating test and, at the same time, to provide a minimum distance of approximately 1 and ¼ inches between the edges of the sheets of material forming the butt joint **98** and the attachment means **104.** This insures that the edges of the sheets of material will not pull away from the butt joint **98** during the fire rating test.

As shown in FIG. **8,** a positioning member **108** formed from a single piece of plastic material and also shown in greater detail in FIGS. **9–11,** may be used in lieu of the positioning members or frames **38** as shown in FIGS. **2–5.** The positioning member **108** is made from a suitable plastic material such as polyethylene. The members are spaced longitudinally along the channel-shaped member used to form the nailing strip **80** by any suitable spacing such as approximately 4 feet apart. The member **108** comprises an elongate support portion **110** having an upper surface formed to position therein the pretensioning steel **78.** An upper surface concave in configuration has been found to be a prefered configuration. The member **108** also includes a pair of L-shaped portions **112.** Each L-shaped portion **112** includes a pair of arms **114** and **116** with arm **114** being integrally attached adjacent one end of the support portion **110** and generally depending therefrom while the other arm **116** is disposed generally parallel with the support portion **110.** Each L-shaped portion **112** is constructed for limited pivotal movement, approximately 3° to 8°, relative to said support portion, said pivotal movement occuring in a plane in which is disposed said support portion and said L-shaped portions. Each of the arms **114** of said L-shaped portion that are integrally attached to said support portion are convergently disposed one to the other, taken in a direction proceeding away from said support portion **110** toward the arms **116** that are disposed generally parallel with said support portion. The angle of convergence of said arms **114** equals at least approximately 4° or more and preferably approximately 6°. With the arms **114** being convergently formed as aforesaid and the L-shaped portions being mounted for limited pivotal movement relative to said support portion, it has been found that upon application of a force downwardly against the upper surface of the support portion **110** (such as occurs from contacting engagement of the pretensioning steel **78** upon the support portion **110**), the L-shaped portions **112** will pivot a limited amount, depending in part upon the amount of the applied force and the resistance encountered by the channel-shaped member used to form the nailing strip **80,** when the member **108** is mounted upon the nailing strip **80.** A positioning member **108** constructed in this manner has

been found to be quite advantageous since the pretensioning steel **78**, see FIG. **8**, when positioned upon the upper surface of the support portion **110** provides a downwardly directed force thereagainst.

The free ends **118** of the arms **116** are constructed for engaging the nailing strip **80** in a manner to secure the member **108** to said nailing strip **80** as shown in FIG. **8**. More specifically, as shown in FIG. **8**, the channel-shaped member used to form the nailing strip **80** includes a pair of side walls each of which has a longitudinally extending U-shaped portion formed adjacent the upper edge thereof. The longitudinal axis of each U-shaped portion lies in a plane disposed generally parallel with a plane in which is disposed the bottom wall of said channel-shaped member and the bight of said U-shaped portion extends inwardly of its associated side wall.

Each L-shaped portion **112** includes stiffening means for controlling the overall stiffness thereof. The stiffening means includes a diagonally disposed member **120** having one end thereof integrally attached to each of the arms **114** (below the pivot point) and **116**. The stiffening means may also include a rib **122** extending longitudinally along the inner surface of each of the arms **114** from the attachment of the member **120** to arm **114** down to the intersection of arm **114** with arm **116** where same flares out by a sufficient amount to provide increased rigidity of the intersection itself.

The member **108** also includes means **124** interconnecting a portion adjacent the free ends of each arm **116**. The means **124** preferably comprises a thin strip of plastic constructed as shown. The strip of plastic is generally rectangular in cross-section and has its largest dimension, when viewed in cross-section, disposed in a plane disposed normal to the plane in which lies the support portion **110** and the L-shaped portions **112**. The means **124** prevents undesirable entanglement of one plastic member with another when a plurality of plastic members **108** are loosely packed in a container. It will be noted that without the use of the means **124**, each of the free ends of the L-shaped portions **112** would function in the manner of a hook thereby becoming intermixed with other members **108** which would require some time on the part of the user to separate one member **108** from another such member.

As shown in FIGS. **9–11**, the member **108** may also include tab means **126** and **128** extending longitudinally outwardly of the opposite ends of the support portion **110** and longitudinally outwardly of the pair of arms **116**. It will be understood that the member **108** may be formed either with or without these tab means **126** and **128**. The purpose of the tab means is to permit the use of one size of member **108** within leg sections **22** having different widths without the necessity of having separate molds for each member **108**. The formation of member **108** either with or without such tab means, as aforesaid, is accomplished by means well known in the art of forming plastic items.

When tab means **126** and **128** are formed on the member **108**, said tab means are preferably L-shaped, in plan form, as shown in FIG. **11**. The purpose for using this configuration is to provide increased flexibility thereof adjacent the outer ends of the tab means thereby minimizing the effects of tolerance differences in the width of the leg sections **22** of various mold members **18**.

The free end **118** of each of the arms **116** preferably includes a portion or portions **130** disposed generally normal to the longitudinal axis of the arm **116**. The portions **130** are disposed within the same plane within which lies the free ends **118** of the arms **116**. It will be understood that the portions **130** provide an additional bearing area for the member **108** when the free ends **118** and the portions **130** are disposed within the bight of the U-shaped portion formed along the upper edges of the side walls of the channel-shaped member used to form the nailing strip **80**.

The outer ends of the support portion **110** and the L-shaped portions are preferably formed such that said outer ends are connected or circumscribed by a pair of convergently disposed lines, taken in a direction proceeding along said lines from said outer end of each support portion to the corresponding outer end of each L-shaped portion, such that the outer ends of said member **108** will be readily accomodated by the convergently formed sides of the leg sections **22** of the mold **18**.

Although each of the positioning members described herein are suitable for the intended purpose, it has been found that the positioning member **108** formed from a plastic material is advantageous under many applications since the surface portions thereof are never coated with rust. Additionally, it has also been found that the positioning member **108** is more readily attached to the nailing trip than is the positioning member **38**. Thus, at the present time, the prefered embodiment for a positioning member is considered to be that shown in FIGS. **9–11**.

In order for a structural element constructed in accordance with the subject invention to be used in certain applications, it must have a fire rating classification of approximately two hours when tested with the standard time-temperature curve established by the American Standards for Testing Materials. Two tests made on a structural element similar to that shown in FIGS. **1** and **7** (frame **38** having been used rather than member **108**), one structural element measuring approximately 9 feet long by 8 feet wide, the other element measuring approximately 17 feet long by 14 feet wide, each element containing one grout joint to connect two individual T-type joists together, and the sheet of material **16** being formed from a gypsum material having a thickness of approximately five-eights of an inch, showed that such structural elements had a fire rating classification of 2 hours, the first element above described lasting 2 hours and 8 minutes before reaching a specified end point in the test and the second above described element lasting two hours and eleven minutes before reaching a specified end point in the test. Based upon the known fact that each additional one-eighth inch of gypsum material used is considered to extend by approximately eight minutes the time that a structural element can withstand the fire rating test as aforespecified and since the above-referenced test exceeded the 2-hour period by 8 minutes, it is concluded that a structural element constructed in accordance with the subject invention and using a sheet of material formed from gypsum in which the thickness of the gypsum is approximately one-half inch or more would meet the fire rating test requirement.

In view of the foregoing, it will be readily appreciated that a novel structural element, concrete prestressed joists of either the T-type or F-type (the terms F-type

and T-type being generally used interchangeably herein), form members for use with a mold for making such joists, and positioning members have been described. It is an advantage of the subject invention that the metal nailing strip is securely embedded in the center of the end of the ledge and flush with the surface of the concrete ledge, and that same will not swell, rot, warp or the like. A nailing strip can be readily incorporated into the ledges of the joist during molding simply by dropping the assembly of nailing strip and supporting frames in the ends of the mold sections in which the ledges are molded. The use of the positioning member **38** or **108** insures that the nailing strip is centrally positioned and is held down in contact with the form surface. Through the use of suitabe attachment means, the sheet of material will be securely anchored to the ledges of the joist either directly or indirectly in the case of attachment adjacent the butt joints. The number of parts necessary to attach elements to the ledges of the joist is reduced to a minimum. Precise position of the attachment means longitudinally along the ledges is not a requirement since attachment of the sheet of material to the nailing strip may be effected anywhere therealong. A suitable leeway laterally of the ledges is also permitted due to the width of the nailing strips. The use of the nailing strip of this invention insures the formation and retention of a penetrable area inside same into which attachment means for structural elements can readily penetrate. The filling material, which prevents concrete from entering the interior of the nailing strip, serves the function of providing a medium into which the attachment means for the element secured to the nailing strip can penetrate. The cost of manufacturing a joist in accordance with the subject invention has been substantiall reduced since the amount of concrete required is approximately one-half of that of prior art joists. For example, a joist constructed in accordance with the subject invention from 150 pounds per cubic feet concrete and having the following dimensions will weigh only approximately 35 pounds per square foot:

Thickness of the plate-like body portion	1 ½"
Width of joist	8'
Height of ledge	8 ½"
No. of ledges	4
Width of ledge measured at intersection of an extension of the sides thereof with the bottom ssurface of the plate-like body portion	4"
Width at bottom of ledge	3.25"
Cross-sectional area of ledge	30.8 in.²
Nailing strip (includes ⅛" diameter U-shaped portion formed along upper edge of side walls)	11/16" × 1 ⅜", 25 ga. hot dipped galvanized metal
Layer of penetrable material (expanded polyethylene)	½" × 1 ⅜"

I claim:

1. A form member for use with a mold for making a pretensioned concrete member having a nailing strip molded therein, the mold having a longitudinally extending, generally channel-shaped portion in which said form member is adapted to be disposed to form a nailing strip, said channel-shaped portion of said mold including a bottom surface and opposed walls, said form member comprising:

a. a longitudinally extending, channel-shaped member having

1. a bottom wall adapted to be disposed in contacting engagement with the bottom surface of the channel-shaped portion of said mold,
2. a pair of side walls, each of which has a longitudinally extending upper edge,
3. a longitudinally extending U-shaped portion formed along the upper edge of each side wall, the longitudinal axis of each U-shaped portion lying in a plane disposed generally parallel with a plane in which is disposed said bottom wall, the bight of said U-shaped portion extending inwardly of its associated side wall, and
4. a longitudinally extending attachment-means-penetrating layer of material disposed within said channel-shaped member, said layer of material having a lower surface portion disposed adjacent the bottom wall of said channel-shaped member and upper surface portions disposed adjacent said U-shaped portions of said channel-shaped member whereby said U-shaped portions retain said attachment means-penetrating layer of material within said channel-shaped member and said layer of material prevents concrete from entering said channel-shaped member; and

b. a plurality of positioning members longitudinally spaced along said channel-shaped member and securely disposed within the U-shaped portions thereof, each positioning member comprising

1. an inverted U-shaped frame member including a bight portion overlying said upper edges and a pair of leg portions, the outer surface of said bight portion being generally concave in configuration and adapted to engage pretensioning steel after the form member has been positioned within the mold, said frame portion lying in a plane disposed generally normal to the longitudinal axis of said channel-shaped member,
2. a pair of legs, each leg having (i) a first part attached to a corresponding one of the leg portions of said U-shaped frame member, and (ii) a second part securely disposed within a corresponding one of the U-shaped portions of said channel-shaped member, said second parts lying in a plane disposed generaly normal to the plane in which is disposed said frame member,
3. the outer surfaces of the leg portions of said U-shaped frame member being spaced such that they are adapted to be received between the opposed walls of the mold in which same is to be used whereby said outer surfaces of said leg portions serve as means for centering and positioning said form member within the channel-shaped portion of the mold in which same are to be used upon being dropped therein and are adapted to be disposed adjacent the inside surfaces of the opposed walls of the mold in which same are to be used, and
4. said positioning members being constructed for transmitting a force to said channel-shaped member when positioned within the mold in which same are to be used and in contacting engagement with the pretensioning steel to be used within the mold.

2. A form member as described in claim **1** in which the sidewalls of said channel-shaped member are convergently disposed, taken in a direction proceeding along said sidewalls toward said bottom wall, and each

of the legs of said positioning members includes an L-shaped configuration, the first parts of said legs lying in a plane in which is disposed said U-shaped frame member.

3. A form member as described in claim 1 in which the second parts of the legs of said positioning members cooperate with the U-shaped portions of said channel-shaped member to secure the frame member of said positioning members in a plane disposed normal to the longitudinal axis of said channel-shaped member.

4. A form member for use with a mold for making a pretensioned concrete member having a nailing strip molded therein, the mold having a longitudinally extending, generaly channel-shaped portion in which said form member is adapted to be disposed to form a nailing strip, said channel-shaped portion of said mold including a bottom surface and opposed walls, said form member comprising:

a. a longitudinally extending, channel-shaped member having
   1. a bottom wall adapted to be disposed in contacting engagement with the bottom surface of the channel-shaped portion of said mold,
   2. a pair of side walls, each of which has a longitudinally extending upper edge,
   3. a longitudinally extending U-shaped portion formed along the upper edge of each side wall, the longitudinal axis of each U-shaped portion lying in a plane disposed generally parallel with a plane in which is disposed said bottom wall, the bight of said U-shaped portion extending inwardly of its associated side wall, and
   4. a longitudinally extending attachment-means-penetrating layer of material disposed within said channel-shaped member, said layer of material having a lower surface portion disposed adjacent the bottom wall of said channel-shaped member and upper surface portions disposed adjacent said U-shaped portions of said channel-shaped member whereby said U-shaped portions retain said attachment-means-penetrating layer of material within said channel-shaped member and said layer of material prevents concrete from entering said channel-shaped member; and

b. a plurality of positioning members longitudinally spaced along said channel-shaped member and disposed within the U-shaped portions thereof, each positioning member being formed from a single piece of plastic material and comprising:
   1. an elongate support portion, and
   2. a pair of L-shaped portions (i) each L-shaped portion including a pair of arms, (ii) each L-shaped portion depending from a corresponding one of the ends of said support portions and having one of said arms disposed generally parallel with said support portion, (iii) each L-shaped portion being constructed for limited pivotal movement relative to said support portion, (iv) the free end of each arm that is disposed generally parallel with said support portion being disposed within a corresponding one of the U-shaped portions of said channel-shaped member, and (v) said positioning member being constructed for transmitting a force to said channel-shaped member when positioned within the mold in which same are to be used and in contacting engagement with the pretensioning steel to be used within the mold.

5. A form member as described in claim 4 in which said support portion has an upper surface concave in configuration, each of the arms of said L-shaped portions of said positioning members that are integrally attached to said support portion are convergently disposed one to the other in a direction proceeding from said support portion toward the arms disposed generally parallel with said support portion, and each free end of the arms that are disposed generally parallel with said support portion includes a portion disposed generally normal to the longitudinal axis of its corresponding arm, said normally disposed portion being positioned within a corresponding one of said longitudinally extending U-shaped portions of said channel-shaped member.

6. A pretensioned concrete joist of the T-type comprising:

a. a concrete plate-like body portion;

b. a channel-shaped concrete support ledge disposed normal to said body portion along the length thereof, said ledge having a bottom surface and opposed side walls;

c. a nailing strip integrally molded in the bottom of said ledge, said strip comprising
   1. a channel-shaped member having (i) a bottom wall disposed along the bottom surface of said ledge, (ii) a pair of side walls each of which has a longitudinally extending upper edge, (iii) a longitudinally extending U-shaped portion formed along the upper edge of each side wall, the longitudinal axis of each U-shaped portion lying in a plane disposed generally parallel with a plane in which is disposed said bottom wall, the bight of each U-shaped portion extending inwardly of its associated side wall, and (iv) a longitudinally extending, attachment-means-penetrating layer of material disposed within said channel shaped member, said layer of material having a lower surface portion disposed in contact with the bottom wall of said channel-shaped member and upper surface portions disposed in abutting contact with said U-shaped portions of said channel-shaped member, said attachment-means-penetrating layer of material preventing concrete from entering into said channel-shaped member, and
   2. a plurality of positioning members longitudinally spaced along said channel-shaped member and disposed within the U-shaped portions thereof, each positioning member comprising (i) an inverted U-shaped frame member including a bight portion and a pair of leg portions, the outer surface of said bight portion being generally concave in configuration, said frame portion lying in a plane disposed generally normal to the longitudinal axis of said channel-shaped member, (ii) a pair of legs, each leg having a first part attached to the corresponding one of the leg portions of said U-shaped frame member and a second part securely disposed within one of the U-shaped portions of said channel-shaped member, said second parts lying in a plane disposed generally normal to the plane in which is disposed said frame member, and (iii) the distance separating the outer surfaces of said U-shaped frame mem-

ber being less than the distance separating the opposed walls of said ledge whereby said outer surfaces are disposed adjacent the inside surfaces of the opposed side walls of said ledge; and

d. pretensioning steel extending longitudinally of said ledge and disposed in contacting engagement with the concave surface of the frame members of said positioning members, said pretensioning steel and said positioning members cooperating to secure and maintain the nailing strip on the bottom surface of the ledge prior to and during placing of the concrete during forming of said joist.

7. A pretensioned concrete joist as described in Claim **6** in which the side walls of said channel-shaped member are convergently disposed, taken in a direction proceeding along said side walls toward said bottom wall, and each of the legs of said positioning members includes an L-shaped configuration the first parts of said legs lying in a plane in which is disposed said U-shaped frame member.

8. A pretensioned concrete joist of the T-type comprising:

a. a concrete plate-like body portion;

b. a channel-shaped concrete support ledge disposed normal to said body portion along the length thereof, said ledge having a bottom surface and opposed side walls;

c. a nailing strip integrally molded in the bottom of said ledge, said strip comprising

1. a channel-shaped member having (i) a bottom wall disposed along the bottom surface of said ledge, (ii) a pair of side walls each of which has a longitudinally extending upper edge, (iii) a longitudinally extending U-shaped portion formed along the upper edge of each side wall, the longitudinal axis of each U-shaped portion lying in a plane disposed generally parallel with a plane in which is disposed said bottom wall, the bight of each U-shaped portion extending inwardly of its associated side wall, and (iv) a longitudinally extending, attachment-means penetrating layer of material disposed within said channel shaped member, said layer of material having a lower surface portion disposed in contact with the bottom wall of said channel-shaped member and upper surface portions disposed in abutting contact with said U-shaped portions of said channel-shaped member, said attachment-means-penetrating layer of material preventing concrete from entering into said channel-shaped member, and

2. a plurality of positioning members longitudinally spaced along said channel-shaped member and disposed within the U-shaped portion thereof, each positioning member comprising (i) an elongate support portion, and (ii) a pair of L-shaped portions, each L-shaped portion including a pair of arms, each L-shaped portion depending from a corresponding one of the ends of said support portions and having one of said arms disposed parallel with said support portion, each L-shaped portion being constructed for limited pivotal movement relative to said support portion, each free end of the arms that are disposed generally parallel with said support portion being positioned within a corresponding one of the longitudinally extending U-shaped portions formed along the upper edge of each side wall of said channel-shaped member; and

d. pretensioning steel extending longitudinally of said ledge and disposed in contacting engagement with the upper surface of said positioning members, said pretensioning steel and said positioning members cooperating to secure and maintain the nailing strip on the bottom surface of said ledge prior to and during placing of the concrete during forming of said joist.

9. A pretensioned concrete joist as described in claim **8** in which said elongate support portion has an upper surface concave in configuration, each of the arms of said L-shaped portions of said positioning members that are integrally attached to said support portion are convergently disposed one to the other in a direction proceeding from said support portion twoard the arms that are disposed generally parallel with said support portion, and each free end of the arms of said L-shaped portion that are disposed generally parallel with said support portion includes a portion disposed generally normal to the longitudinal axis of its corresponding arm, said normally disposed portion being positioned within a corresponding one of said longitudinally extending U-shaped portions formed along the upper edge of each side wall of said channel-shaped member.

* * * * *

UNITED STATES PATENT OFFICE
CERTIFICATE OF CORRECTION

Patent No. 3,813,834 Dated June 4, 1974

Inventor(s) George Bradley Davis, Jr.

It is certified that error appears in the above-identified patent and that said Letters Patent are hereby corrected as shown below:

Column 3, line 32, "contructed" should read -- constructed --;

Column 5, line 58, "contructed" should read -- constructed --;

Column 8, line 28, before the word "leg" insert -- each --;

Column 12, line 29, "trip" should read -- strip --;

Column 18, line 37, "twoard" should read -- toward --.

Signed and sealed this 18th day of February 1975.

(SEAL)
Attest:

RUTH C. MASON
Attesting Officer

C. MARSHALL DANN
Commissioner of Patents
and Trademarks

FORM PO-1050 (10-69)

USCOMM-DC 60376-P69
* U.S. GOVERNMENT PRINTING OFFICE : 1969 O—366-334.