

(12) STANDARD PATENT
(19) AUSTRALIAN PATENT OFFICE

(11) Application No. AU 2013348300 B2

(54) Title
Low GWP heat transfer compositions

(51) International Patent Classification(s)
C09K 5/04 (2006.01) **F25B 1/00** (2006.01)

(21) Application No: **2013348300** (22) Date of Filing: **2013.10.29**

(87) WIPO No: **WO14/081539**

(30) Priority Data

(31) Number (32) Date (33) Country
61/729,291 **2012.11.21** **US**
13/796,460 **2013.03.12** **US**

(43) Publication Date: **2014.05.30**
(44) Accepted Journal Date: **2017.03.30**

(71) Applicant(s)
Honeywell International Inc.

(72) Inventor(s)
Yana Motta, Samuel F.;Spatz, Mark W.;Vera Becerra, Elizabet Del Carmen;Sethi, Ankit;Morris, Thomas

(74) Agent / Attorney
Davies Collison Cave Pty Ltd, Level 15 1 Nicholson Street, MELBOURNE, VIC, 3000, AU

(56) Related Art
WO 2010/129920 A1

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau



WIPO | PCT



(10) International Publication Number

WO 2014/081539 A1

(43) International Publication Date

30 May 2014 (30.05.2014)

(51) International Patent Classification:

C09K 5/04 (2006.01) F25B 1/00 (2006.01)

Services M/S AB/2B, 101 Columbia Road, P. O. Box 2245, Morristown, New Jersey 07962-2245 (US).

(21) International Application Number:

PCT/US2013/067222

(74) Agent: BEATUS, Carrie; Honeywell International Inc., Patent Services M/S AB/2B, 101 Columbia Road, P. O. Box 2245, Morristown, New Jersey 07962-2245 (US).

(22) International Filing Date:

29 October 2013 (29.10.2013)

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(71) Applicant: HONEYWELL INTERNATIONAL INC. [US/US]; Patent Services M/S AB/2B, 101 Columbia Road, P. O. Box 2245, Morristown, New Jersey 07962-2245 (US).

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))



WO 2014/081539 A1

(54) Title: LOW GWP HEAT TRANSFER COMPOSITIONS

(57) Abstract: The present invention relates, in part, to heat transfer and refrigerant compositions and methods that include HFC-32, HFO-1234ze and HFC-125.

LOW GWP HEAT TRANSFER COMPOSITIONS

CROSS REFERENCES TO RELATED APPLICATIONS

The present application claims priority to U.S. Provisional Application Serial No. 5 61/729,291, filed November 21, 2012, the contents of which are incorporated herein by reference in its entirety.

FIELD OF THE INVENTION

This invention relates to compositions, methods and systems having utility particularly in 10 refrigeration applications, and in particular aspects to heat transfer and refrigerant compositions useful in systems that typically utilize the refrigerant R-410A for heating and/or cooling applications.

BACKGROUND

15 Fluorocarbon based fluids have found widespread use in many commercial and industrial applications, including as the working fluid in systems such as air conditioning, heat pump and refrigeration systems, among other uses such as aerosol propellants, as blowing agents, and as gaseous dielectrics.

Heat transfer fluids, to be commercially viable, must satisfy certain very specific and in 20 certain cases very stringent combinations of physical, chemical and economic properties. Moreover, there are many different types of heat transfer systems and heat transfer equipment, and in many cases it is important that the heat transfer fluid used in such systems posses a particular combination of properties that match the needs of the individual system. For example,

systems based on the vapor compression cycle usually involve the phase change of the refrigerant from the liquid to the vapor phase through heat absorption at a relatively low pressure and compressing the vapor to a relatively elevated pressure, condensing the vapor to the liquid phase through heat removal at this relatively elevated pressure and temperature, and then

5 reducing the pressure to start the cycle over again.

Certain fluorocarbons, for example, have been a preferred component in many heat exchange fluids, such as refrigerants, for many years in many applications. Fluoroalkanes, such as chlorofluoromethanes and chlorofluoroethanes, have gained widespread use as refrigerants in applications including air conditioning and heat pump applications owing to their unique

10 combination of chemical and physical properties, such as heat capacity, flammability, stability under the conditions of operation, and miscibility with the lubricant (if any) used in the system. Moreover, many of the refrigerants commonly utilized in vapor compression systems are either single components fluids, or zeotropic, azeotropic mixtures.

Concern has increased in recent years about potential damage to the earth's atmosphere

15 and climate, and certain chlorine-based compounds have been identified as particularly problematic in this regard. The use of chlorine-containing compositions (such as chlorofluorocarbons (CFCs), hydrochlorofluorocarbons (HCFCs) and the like) as refrigerants in air-conditioning and refrigeration systems has become disfavored because of the ozone-depleting properties associated with many of such compounds. There has thus been an increasing need for

20 new fluorocarbon and hydrofluorocarbon compounds that offer alternatives for refrigeration and heat pump applications. By way of example, in certain aspects, it has become desirable to retrofit chlorine-containing refrigeration systems by replacing chlorine-containing refrigerants with non-chlorine-containing refrigerant compounds that will not deplete the ozone layer, such

as hydrofluorocarbons (HFCs).

Another concern surrounding many existing refrigerants is the tendency of many such products to cause global warming. This characteristic is commonly measured as global warming potential (GWP). The GWP of a compound is a measure of the potential contribution to the green house effect of the chemical against a known reference molecule, namely, CO₂ which has a GWP = 1. For example, the following known refrigerants possess the following Global Warming Potentials:

REFRIGERANT	GWP
R410A	2088
R-507	3985
R404A	3922
R407C	1774

10 While each of the above-noted refrigerants has proven effective in many respects, these materials are become increasingly less preferred since it is frequently undesirable to use materials having GWPs greater than about 1000. A need exists, therefore, for substitutes for these and other existing refrigerants having undesirable GWPs.

15 There has thus been an increasing need for new fluorocarbon and hydrofluorocarbon compounds and compositions that are attractive alternatives to the compositions heretofore used in these and other applications. For example, it has become desirable to retrofit certain systems, including chlorine-containing and certain HFC-containing refrigeration systems by replacing the existing refrigerants with refrigerant compositions that will not deplete the ozone layer, will not cause unwanted levels of global worming, and at the same time will satisfy all of the other 20 stringent requirements of such systems for the materials used as the heat transfer material.

With respect to performance properties, the present applicants have come to appreciate that any potential substitute refrigerant must also possess those properties present in many of the most widely used fluids, such as excellent heat transfer properties, chemical stability, low- or no- toxicity, low or non-flammability and lubricant compatibility, among others.

5 With regard to efficiency in use, it is important to note that a loss in refrigerant thermodynamic performance or energy efficiency may have secondary environmental impacts through increased fossil fuel usage arising from an increased demand for electrical energy.

Furthermore, it is generally considered desirable for refrigerant substitutes to be effective without major engineering changes to conventional vapor compression technology currently used
10 with existing refrigerants, such as CFC-containing refrigerants.

Flammability is another important property for many applications. That is, it is considered either important or essential in many applications, including particularly in heat transfer applications, to use compositions which are non-flammable or of relatively low
15 flammability. As used herein, the term “nonflammable” refers to compounds or compositions which are determined to be nonflammable as determined in accordance with ASTM standard E-681, dated 2002, which is incorporated herein by reference. Unfortunately, many HFC’s and
HFOs which might otherwise be desirable for use in refrigerant compositions are flammable.
20 For example, the fluoroalkane difluoroethane (HFC-152a) and the fluoroalkene 1,1,1-trifluoropropene (HFO-1243zf) are each flammable and therefore not viable for use alone in many applications.

Applicants have thus come to appreciate a need for compositions, and particularly heat transfer compositions, that are potentially useful in numerous applications, including vapor compression heating and cooling systems and methods, while avoiding one or more of the

21 Feb 2017

2013348300

H:\Kzh\Interwoven\NRPorth\NDCC\KZH\3195270_1.docx-21/02/2017

disadvantages noted above.

The reference in this specification to any prior publication (or information derived from it), or to any matter which is known, is not, and should not be taken as an acknowledgment or admission or any form of suggestion that that prior publication (or 5 information derived from it) or known matter forms part of the common general knowledge in the field of endeavour to which this specification relates.

Throughout this specification and the claims which follow, unless the context requires otherwise, the word "comprise", and variations such as "comprises" and "comprising", will be understood to imply the inclusion of a stated integer or step or group 10 of integers or steps but not the exclusion of any other integer or step or group of integers or steps.

SUMMARY

In certain aspects, the present invention relates to compositions, methods, uses and 15 systems which comprise or utilize a multi-component mixture comprising: (a) from about 60% to about 70% by weight of HFC-32; (b) from about 20% to about 40% by weight of HFO-1234ze; and (c) from greater than about 0% to about 10% by weight of HFC-125, provided that the amount of component (c) is effective to improve one or more of the 20 composition's glide; heating capacity; burning velocity; and/or hazard value. Unless otherwise stated herein, weight percentage values is based on total of components (a), (b) and (c).

In certain aspects of the foregoing or any embodiment herein, component (b) may further comprise at least one compound selected from unsaturated, -CF₃ terminated

propenes, unsaturated, -CF₃ terminated butenes, and combinations of these, wherein the compound is a compound other than HFO-1234ze.

In alternative aspects, the composition includes (a) from about 63% to about 69% by weight of HFC-32; (b) from about 25% to about 37% by weight of HFO-1234ze; and 5 (c) from greater than about 0% to about 6% by weight of HFC-125, provided, again, that the amount of component (c) is effective to improve one or more of the composition's glide; heating capacity; burning velocity; and/or hazard value.

The term HFO-1234ze is used herein generically to refer to 1,1,1,3-tetrafluoropropene, independent of whether it is the cis- or trans- form. The terms 10 "cisHFO-1234ze" and "transHFO-1234ze" are used herein to describe the cis- and trans-forms of 1,1,1,3-tetrafluoropropene respectively. The term "HFO-1234ze" therefore includes within its scope cisHFO-1234ze, transHFO-1234ze, and all combinations and mixtures of these. In certain preferred aspects, the HFO-1234ze comprises, consists essentially of, or consists of transHFO-1234ze.

15 In one aspect, the invention provides a heat transfer composition comprising:
(a) from about 60% to about 70% by weight of HFC-32;
(b) from about 20% to about 40% by weight of trans-HFO-1234ze; and
(c) from greater than about 0% to about 10% by weight of HFC-125,
provided that the amount of component (c) is effective to improve one or more of 20 glide of the composition; heating capacity of the composition, burning velocity of the composition; and/or hazard value of the composition.

The present invention provides also methods and systems which utilize the compositions of the present invention, including methods and systems for transferring heat, and methods and systems for replacing an existing heat transfer fluid in an existing heat

21 Feb 2017

2013348300

transfer system, and methods of selecting a heat transfer fluid in accordance with the present invention to replace one or more existing heat transfer fluids. While in certain embodiments the compositions, methods, and systems of the present invention can be used to replace any known heat transfer fluid, in further, and in some cases preferred

5 embodiments, the compositions of the present application may be used as a replacement for R-410A.

Refrigeration systems contemplated in accordance with the present invention include, but are not limited to, automotive air conditioning systems, residential air conditioning systems, commercial air conditioning systems, residential refrigerator systems, residential freezer systems, commercial refrigerator systems, commercial freezer systems, chiller air conditioning systems, chiller refrigeration systems, heat pump systems, and combinations of two or more of these. In certain preferred embodiments, the refrigeration systems include stationary refrigeration systems and heat pump systems or any system where R-410A is used as the refrigerant.

15

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

R-410A is commonly used in air conditioning systems, particularly stationary air conditioning units, stationary refrigeration units, and heat pump systems. It has an estimated Global Warming Potential (GWP) of 2088, which is much higher than is desired or required. Applicants have found that the compositions of the present invention satisfy 20 in an exceptional

and unexpected way the need for new compositions for such applications, particularly though not exclusively air conditioning and heat pump systems, having improved performance with respect to environmental impact while at the same time providing other important performance characteristics, such as, but not limited to, capacity, efficiency, flammability and toxicity. In 5 preferred embodiments the present compositions provide alternatives and/or replacements for refrigerants currently used in such applications, particularly and preferably R-410A, that at once have lower GWP values and have a close match in heating and cooling capacity to R-410A in such systems.

10 HEAT TRANSFER COMPOSITIONS

The compositions of the present invention are generally adaptable for use in heat transfer applications, that is, as a heating and/or cooling medium, but are particularly well adapted for use, as mentioned above, in AC and heat pump systems that have heretofore used R-410A.

Applicants have found that use of the components of the present invention within the 15 stated ranges is important to achieve the important but difficult to achieve combinations of properties exhibited by the present compositions, particularly in the preferred systems and methods.

In certain embodiments, the HFC-32 is present in the compositions of the invention in an amount of from about 60 wt. % to about 70 wt. % by weight. In certain preferred embodiments, 20 the HFC-32 is present in the compositions of the invention in an amount of from about 63 wt. % to about 69 wt. % by weight.

In further embodiments, the second component includes HFO-1234ze, preferably from about 20 wt. % to about 40 wt. % by weight. In further embodiments, HFO-1234ze is provided

in an amount from about 25 wt. % to about 37 wt.% by weight. In certain embodiments, the second component consists essentially of, or consists of, HFO-1234ze, and in further embodiments it comprises, consists essentially of, or consists of transHFO-1234ze. This second component may also include one or more additional compounds, other than HFO-1234ze, which 5 may be selected from unsaturated -CF₃ terminated propenes, unsaturated -CF₃ terminated butenes, and combinations of these.

In even further embodiments, the compositions of the invention include HFC-125 in an amount from greater than about 0 wt. % to about 10 wt. %. In further embodiments, HFC-125 is provided in an amount from greater than about 0 wt. % to about 6 wt. %. In further 10 embodiments, the compositions of the present invention may include from about 1% to about 8% by weight of HFC-125; from about 1% to about 6% by weight of HFC-125; from about 2% to about 8% by weight of HFC-125; from about 2% to about 6% by weight of HFC-125; from about 3% to about 8% by weight of HFC-125; and from about 3% to about 6% by weight of HFC-125.

15 In certain preferred aspects, the compositions of the present invention do not include any substantial amount of R-134a, and in certain preferred embodiments does not include more than about 0.5% of R-134a and in other preferred embodiments does not include more than trace amounts of R-134a. R-134a is not preferred, at least in part, in certain of these embodiments because it increases the GWP of the composition and does not significantly improve the 20 performance of the composition.

In further aspects of the invention, Applicants have surprisingly and unexpectedly found that the inclusion of HFC-125 in the compositions of the present invention decreases the resulting glide and improves heating capacity at low temperature conditions. As used herein,

“glide” refers to the difference between the starting and ending temperatures of a phase-change process by a refrigerant within a refrigerating system. An increase in glide typically forces the system to work at lower suction pressures, which results in a decrease in performance.

Applicants demonstrate herein, however, that the addition of HFC-125 to compositions including

5 HFO-1234 and HFC-32 in accordance with the preferred aspects of the present invention surprisingly and unexpectedly decreases composition glide, thus improving system capacity.

Applicants have also found that the inclusion of HFC-125 in accordance with the preferred aspects of the present invention provides surprising and unexpected improvement of flammability and hazard values to the resulting composition. As demonstrated in the examples,

10 below, compositions having HFC-125 in accordance with the preferred aspects of the present invention exhibited burn velocities below those compositions lacking this component.

Significantly (and also unexpectedly), the burning velocities observed were much lower than the expected values, based on known calculations. Applicants have similarly demonstrated that the inclusion of HFC-125 in accordance with the preferred aspects of the present invention lowers

15 the hazard value of the composition, as demonstrated by the Cube Test performed and described in Example 3.

The compositions of the present invention are also advantageous as having low GWP.

By way of non-limiting example, the following Table A illustrates the substantial GWP superiority of certain compositions of the present invention, which are described in parenthesis in 20 terms of weight fraction of each component, in comparison to the GWP of R-410A, which has a GWP of 2088.

TABLE A

Name	Composition	GWP	GWP %R410A
410A	R32/R125 (50/50)	2088	
A	R32/1234ze(E)/(0.68/0.32)	461	22%
B	R32/1234ze(E)/R125(0.68/0.26/0.06)	669	32%
C	R32/1234ze(E)/R125(0.68/0.28/0.04)	600	29%

The compositions of the present invention may include other components for the purpose of enhancing or providing certain functionality to the composition, or in some cases to reduce the 5 cost of the composition. For example, heat transfer compositions which include the preferred compositions of the present invention as a refrigerant, especially as a refrigerant used in vapor compression systems, will also include one or more lubricants, generally in amounts of from about 30 to about 50 percent by weight of the entire heat transfer composition, and in some case potentially in amount greater than about 50 percent and other cases in amounts as low as about 10 percent by weight of the entire heat transfer composition.

Applicants have found that Polyol Esters (POEs) and Poly Vinyl Ethers (PVEs), PAG oils, silicone oil, lubricants that have been used in refrigeration machinery with previously used hydrofluorocarbon (HFC) refrigerants may, in certain embodiments, be used to advantage in the heat transfer compositions of the present invention. Commercially available esters include 15 neopentyl glycol dipelargonate, which is available as Emery 2917 (registered trademark) and Hatcol 2370 (registered trademark). Other useful esters include phosphate esters, dibasic acid esters, and fluoroesters. Preferred lubricants include POEs and PVEs. Of course, different mixtures of different types of lubricants may be used.

HEAT TRANSFER METHODS AND SYSTEMS

The present methods, systems and compositions are thus adaptable for use in connection with a wide variety of heat transfer systems in general and refrigeration systems in particular, such as air-conditioning (including both stationary and mobile air conditioning systems), 5 refrigeration, heat-pump systems, and the like. Generally speaking, such refrigeration systems contemplated in accordance with the present invention include, but are not limited to, automotive air conditioning systems, residential air conditioning systems, commercial air conditioning systems, residential refrigerator systems, residential freezer systems, commercial refrigerator systems, commercial freezer systems, chiller air conditioning systems, chiller refrigeration 10 systems, heat pump systems, and combinations of two or more of these.

In certain preferred embodiments, the compositions of the present invention are used in refrigeration systems originally designed for use with an HCFC refrigerant, such as, for example, R-410A. Such refrigeration systems may include, but are not limited to, stationary refrigeration systems and heat pump systems or any system where R-410A is used as the refrigerant.

15 The preferred compositions of the present invention tend to exhibit many of the desirable characteristics of R-410A but have a GWP that is substantially lower than that of R-410A while at the same time having a capacity that is substantially similar to or substantially matches, and preferably is as high as or higher than R-410A. In particular, applicants have recognized that certain preferred embodiments of the present compositions tend to exhibit relatively low global 20 warming potentials (“GWPs”), preferably less than about 1500, preferably not greater than 1000, and more preferably not greater than about 700. Applicants have also surprisingly and unexpectedly recognized that such compositions have significantly reduced flammability and hazard values.

As mentioned above, the present invention achieves exceptional advantages in connection with commercial refrigeration systems, and in certain preferred aspects stationary refrigeration systems. Non-limiting examples of such stationary refrigeration systems are provided in Examples 4 and 5, below. To this end, such systems may include low temperature 5 commercial applications (Example 5), including commercial freezers or systems that may be used for the storage and maintenance of frozen goods. They may also include medium-temperature commercial application (Example 4), such as commercial refrigerators, including systems for the storage of fresh goods. The examples below provide typical conditions and parameters that are used for such applications. These conditions, however, are not considered 10 limiting to the invention, as one of skill in the art will appreciate that they may be varied based on one or more of a myriad of factors, including but not limited to, ambient conditions, intended application, time of year, and the like. Such examples are also not necessarily limiting to the definition of the term “stationary refrigeration.” The compositions provided herein may be used in similar type systems or, in certain embodiments, in any alternative system where R-410A is or 15 may be adapted for use as a refrigerant.

It is contemplated that in certain embodiments the present invention provides retrofitting methods which comprise replacing at least a substantial portion of the heat transfer fluid (including the refrigerant and optionally the lubricant) in an existing system with a composition of the present invention, without substantial modification of the system. In certain preferred 20 embodiments the replacement step is a drop-in replacement in the sense that no substantial redesign of the system is required and no major item of equipment needs to be replaced in order to accommodate the composition of the present invention as the heat transfer fluid. In certain preferred embodiments, the methods comprise a drop-in replacement in which the capacity of the

system is at least about 70%, preferably at least about 85%, even more preferably at least about 90%, and even more preferably at least about 95% of the system capacity prior to replacement, and preferably not greater than about 130%, even more preferably less than about 115%, even more preferably less than about 110%, and even more preferably less than about 105%. In

5 certain preferred embodiments, the methods comprise a drop-in replacement in which the suction pressure and/or the discharge pressure of the system, and even more preferably both, is/are at least about 70%, more preferably at least about 90% and even more preferably at least about 95% of the suction pressure and/or the discharge pressure prior to replacement, and preferably not greater than about 130%, even more preferably less than about 115, even more preferably

10 less than about 110%, and even more preferably less than about 105%. In certain preferred embodiments, the methods comprise a drop-in replacement in which the mass flow of the system is at least about 80%, even more preferably at least 90%, and even more preferably at least 95% of the mass flow prior to replacement, and preferably not greater than about 130%, even more preferably less than about 115, even more preferably less than about 110%, and even more

15 preferably less than about 105%.

In certain other preferred embodiments, the refrigeration compositions of the present invention may be used in refrigeration systems containing a lubricant used conventionally with R-410A, such as polyolester oils, and the like, or may be used with other lubricants traditionally used with HFC refrigerants, as discussed in greater detail above. As used herein the term

20 “refrigeration system” refers generally to any system or apparatus, or any part or portion of such a system or apparatus, which employs a refrigerant to provide heating or cooling. Such air refrigeration systems include, for example, air conditioners, electric refrigerators, chillers, or any of the systems identified herein or otherwise known in the art.

EXAMPLES

The following examples are provided for the purpose of illustrating the present invention but without limiting the scope thereof.

5

EXAMPLE 1 - Performance

The following examples are provided for the purpose of illustrating the present invention but without limiting the scope thereof.

A representative air-to-air reversible heat pump designed for R410A was tested. This
10 ducted unit was tested in Honeywell's Buffalo, New York application laboratory. The ducted unit is a 3-ton (10.5 kW cooling capacity) 13 SEER (3.8 cooling seasonal performance factor, SPF) with a heating capacity of 10.1 kW and an HSPF of 8.5 (rated heating SPF of ~2.5), equipped with a scroll compressor. This system has tube-and-fin heat exchangers, reversing valves and thermostatic expansion valves for each operating mode. Due to the different pressures
15 and densities of the refrigerants tested, some of the tests required the use of Electronic Expansion Valves (EEV) to reproduce the same degrees of superheat observed with the original refrigerants.

Tests shown in tables 1 and 2 were performed using standard [AHRI, 2008] operating
20 conditions. All tests were performed inside environmental chambers equipped with instrumentation to measure both air-side and refrigerant-side parameters. Refrigerant flow was measured using a coriolis flow meter while air flow and capacity was measured using an air-enthalpy tunnel designed according to industry standards [ASHRAE, 1992]. All primary measurement sensors were calibrated to $\pm 0.25^\circ\text{C}$ for temperatures and ± 0.25 psi for pressure. Experimental uncertainties for capacity and efficiency were on average $\pm 5\%$. Capacity values

represent the air-side measurements, which were carefully calibrated using the reference fluid (R-410A). The developmental blend, L-41 was tested in this heat pump in both cooling and heating modes along with the baseline refrigerant R-410A.

5

Table 1 Standard Operating Conditions in Cooling Mode

Operating Conditions (Cooling Mode)				
Test Condition	Indoor Ambient		Outdoor Ambient	
	DB(°C)*	WB(°C)*	DB(°C)*	WB(°C)*
AHRI Std. A	26.7	19	35	24
AHRI Std. B	26.7	19	27.8	18
AHRI Std. MOC	26.7	19	46.1	24

*DB refers to Dry Bulb temperature and WB refers to Wet Bulb temperature throughout the tables

Table 2 Standard Operating Conditions in Heating Mode

Operating Conditions (Heating Mode)				
Test Condition	Indoor Ambient		Outdoor Ambient	
	DB(°C)	WB(°C)	DB(°C)	WB(°C)
AHRI Std. H1	21.1	15.6	8.3	6.1
AHRI Std. H3	21.1	15.6	-8.3	-9.4

10

Table 3 Capacity Evaluations

	Characteristics			Capacity in Heating Mode		Capacity in Cooling Mode	
	Refrigerant	Comp	GWP	Glide Ev	Rating (H1)	Low Temperature (H3)	Rating (A)
R410A	R32/R125(50/50)	2088			100%	100%	100%

R32	R32 (100)	675	0	105%	102%	108%
HDR-89	R32/1234ze (68/32)	459	4.4	93%	90%	95%
HDR-89 (*)	R32/1234ze (68/32)	459	4.4	101%	98%	101%
HDR-92	R32/1234ze/R125 (68/26/6)	669	3.8	96%	-	96%
HDR-92(*)	R32/1234ze/R125 (68/26/6)	669	3.8	104%	105%	104%
HDR-95(*)	R32/1234ze/R125 (68/28/4)	600	4.0	103%	103%	103%

Lower amounts of R32 increase glide (HDR-89), which affects performance in heating mode especially at the low temperature condition (H3). This happens even after full capacity recovery at standard operating conditions (A and H1). Adding R125 (HDR-92) reduces glide, 5 making a better heat transfer fluid. This allows full capacity recovery in all operating conditions. This is also valid for a blend containing smaller amounts of R125 (HDR-95), which also experiences capacity recovery in the whole range.

Table 4 - Efficiency

	Characteristics			Efficiency in Heating Mode	Efficiency in Cooling Mode
Refrigerant	Comp	GWP	Glide Ev	Rating (H1)	Rating (B)
R410A	R32/R125(50/50)	2088		100%	100%
R32	R32 (100)	675	0	100%	101%
HDR-89	R32/1234ze (68/32)	459	4.4	103%	103%
HDR-89 (*)	R32/1234ze (68/32)	459	4.4	100%	100%
HDR-92	R32/1234ze/R125 (68/26/6)	669	3.8	103%	102%
HDR-92(*)	R32/1234ze/R125 (68/26/6)	669	3.8	101%	100%
HDR-95(*)	R32/1234ze/R125 (68/28/4)	600	4.0	101%	100%

Table 5 Reliability at extreme operating conditions (AHRI MOC)

	Characteristics			Discharge Temperature (Deg C)
Refrigerant	Comp	GWP	Glide Ev	Rating (H1)
R410A	R32/R125(50/50)	2088		95.5
R32	R32 (100)	675	0	119.4
HDR-89	R32/1234ze (68/32)	459	4.4	107.7
HDR-89 (*)	R32/1234ze (68/32)	459	4.4	112.2
HDR-92	R32/1234ze/R125 (68/26/6)	669	3.8	107.2
HDR-92(*)	R32/1234ze/R125 (68/26/6)	669	3.8	108.8
HDR-95(*)	R32/1234ze/R125 (68/28/4)	600	4.0	108.8

The AHRI MOC condition tests the equipment at extreme ambient temperatures to verify

5 that all parameters do not exceed the design limits for the equipment. One of the important parameters is the discharge temperature, which should be lower than 115 deg C if the current compressor technologies are used.

Table 5 shows clearly that compositions containing lower amount of R32 (example: HDR92 with 68% \pm 2%) maintain this parameter inside the acceptable range.

10

EXAMPLE 2 - Burning Velocity

Applicants have found that the burning velocity of HFC/HFO mixtures compositions is typically and substantially linearly related to the weight averaged burning velocity of the components according to the Formula I:

15
$$BV_{comp} = \sum(wt\%i \cdot BV_i)$$

where BV_{comp} is the burning velocity of the composition, and i is summed for each of the above listed components in the composition, and preferably the amounts of each of the above listed components are selected to ensure that BV is less than about 10, more preferably less than about 4, as refrigerants with such low BV exhibit unstable flames.

5 The burning velocities of common pure component refrigerants are given in the following Table 6.

Table 6: Burning velocities of pure components

Refrigerant	BV, cm/s
HFC-32	6.7
HFC-125	0
1234yf	1.5
1234ze(E)	0

The burning velocities of all the mixtures in Table 7 were calculated and using the linear 10 relationship, above. All of the mixtures have a burning velocity of less than 10 cm/s and therefore would be expected to be classified as A2L refrigerants. When tested, however, blends containing small amounts of R125 exhibit unexpected low burning velocities, not predicted by the linear relationship.

Table 7: Burning velocity of mixtures

Name	Calculated BV (cm/s)	Measured BV (cm/s)
R32		6.7
1234ze		0
1234yf		1.5

Name	Calculated BV (cm/s)	Measured BV (cm/s)
HDR-89 R32/1234ze(68/32)	4.5	4.5±0.3
HDR-92 R32/1234ze/R125 (68/26/6)	6.5	~2
HDR-95 R32/1234ze/R125 (68/28/4)	6.5	~2

EXAMPLE 3 - Hazard Evaluations

The Cube Test is performed pursuant to the procedure described herein. Specifically, each material being tested is separately released into a transparent cube chamber which has an 5 internal volume of 1 ft³. A low power fan is used to mix components. An electrical spark with enough energy to ignite the test fluids is used. The results of all tests are recorded using a video camera. The cube is filled with the composition being tested so as to ensure a stoichiometric concentration for each refrigerant tested. The fan is used to mix the components. Effort is made to ignite the fluid using the spark generator for 1 min. Record the test using HD camcorder.

10 As also mentioned above, the compositions of the present invention should exhibit a degree of hazard value as low as possible. As used herein, degree of hazardousness is measured by observing the results of a cube test using the composition in question and applying a value to that test as indicated by the guidelines provided in the table below.

HAZARD VALUE GUIDELINE TABLE

TEST RESULT	HAZARD VALUE RANGE
No ignition). Exemplary of this hazard level are the pure materials R-134a and transHFO-1234ze.	0
Incomplete burning process and little or no energy imparted to indicator balls and no	1 – 2

TEST RESULT	HAZARD VALUE RANGE
substantial pressure rise in the cube (all balls rise an amount that is barely observable or not all from the cube holes and essentially no movement of the cube observed). Exemplary of this hazard level is the pure material HFO-1234yf, with a value of 2.	
Substantially complete burning process and low amount of energy imparted to some of the balls and substantially no pressure rise in the the cube (some balls rise an observable small distance and return to the starting position, and essentially no movement of the cube observed).). Exemplary of this hazard level is the pure material R-32, with a value of 4.	3 – 5
Substantially complete burning process and substantial amount of energy imparted to most balls and high pressure rise in the cube but little or no movement of the cube (most balls rise an observable distance and do not return to the top of the cube, but little or no movement of the cube observed).	6 – 7
High Hazard Conditions – Rapid burning and	8 -10

TEST RESULT	HAZARD VALUE RANGE
substantial imparted to all balls and substantial energy imparted to the cube (substantially all balls rise from the cube and do not return to the starting position, and substantial movement of the cube observed).). Exemplary of this hazard level are the pure materials R-152a and R-600a, with values of 8 and 10 respectively.	

The Hazardous rating of all the mixtures were calculated and are shown below in Table 8. All of the mixtures have a hazard rating of less than 7 and therefore would be expected to be safely used in air conditioning systems.

5

Table 8: Hazard Value of mixtures

Name	Hazard
R32	4
1234ze	0
1234yf	2
HDR-89 R32/1234ze(68/32)	4
HDR-92 R32/1234ze/R125 (68/26/6)	2
HDR-95 R32/1234ze/R125 (68/28/4)	2

Those skilled in the art will appreciate that the foregoing description and examples are intended to be illustrative of the invention but not necessarily limiting of the full and true broad scope of the invention, which will be represented by the appended claims as presented now or 10 hereinafter.

EXAMPLE 4 – Performance in stationary refrigeration (commercial refrigeration) - medium temperature applications:

The performance of some preferred compositions were evaluated against other refrigerant

5 compositions at conditions typical of medium temperature refrigeration. This application covers the refrigeration of fresh food. The conditions at which the compositions were evaluated are shown in Table 9:

Evaporating Temperature	20°F (-6.7°C)
Condensing Temperature	110°F (43.3°C)
Evaporator Superheat	10°F (5.5°C)
Condenser Subcooling	9°F (5°C)
Compressor Displacement	1.0 ft ³ /min (0.028 m ³ /min)
Compressor Isentropic Eff.	65%
Compressor Return Temp	45°F (7.2°C)

Table 9

10

Table 10 compares compositions of interest to the baseline refrigerant, R-410A, a 50/50 near-azeotropic blend of R-32 and R-125 in typical medium temperature application.

Name	Composition	Capacity Rel. to R-410A	Efficiency Rel. to R-410A	Capacity with Increased Displ.
HDR-92	32/1234ze/125 (68/26/6)	91%	104%	102%
HDR-95	32/1234ze/125 (68/28/4)	90%	104%	101%

Table 10

15

As can be seen, the compositions exceed the efficiency of the baseline refrigerant, R-410A and

are within 10% of the capacity. In addition with a modest 12% increase in the displacement of the compressor, equivalent capacity is reached.

EXAMPLE 5 – Performance in stationary refrigeration (commercial refrigeration) - low 5 temperature applications:

The performance of some preferred compositions were evaluated against other refrigerant compositions at conditions typical of low temperature refrigeration. This application covers the refrigeration of frozen food. The conditions at which the compositions were evaluated are shown in Table 11:

Evaporating Temperature	-15°F (-26.1°C)
Condensing Temperature	110°F (43.3°C)
Evaporator Superheat	10°F (5.5°C)
Condenser Subcooling	9°F (5°C)
Compressor Displacement	1.0 ft ³ /min (0.028 m ³ /min)
Compressor Isentropic Eff.	65%
Compressor Return Temp	30°F (-1.1°C)

10

Table 11

Table 12 compares compositions of interest to the baseline refrigerant, R-410A, a 50/50 near-azeotropic blend of R-32 and R-125 in typical medium temperature application.

15

Name	Composition	Capacity Rel. to R-410A	Efficiency Rel. to R-410A	Capacity with Increased Displ.
HDR-92	32/1234ze/125 (68/26/6)	91%	105%	102%
HDR-95	32/1234ze/125 (68/28/4)	90%	105%	100%

Table 12

As can be seen, the compositions again exceed the efficiency of the baseline refrigerant, R-410A and are within 10% of the capacity. In addition with a modest 12% increase in the displacement of the compressor, equivalent capacity is reached at low temperature conditions.

5

EXAMPLE 6 – Miscibility with common compressor lubricants:

One of the compositions of interest, HDR-95 (68% R-32 / 28% R-1234ze(E) / 4% R-125) was experimentally evaluated to determine its miscibility with a lubricant supplied by Emerson's Copeland division termed "Ultra 22" POE lubricant that has a viscosity of 22 cSt at 40°C. It 10 showed a marked improvement over pure R-32 which was immiscible over this range tested (-40°C to 70°C) except for small quantities of refrigerant (<5% refrigerant in oil between 12°C and 62°C). The 73% R-32 / 27% 1234ze(E) blend was miscible between -5°C to 65°C but HDR-95 showed miscibility down to -10°C and up to 75°C for all concentrations and it showed miscibility 15 down to -30°C for 5% refrigerant in oil. This improved miscibility at low temperature is especially important for heat pump and refrigeration applications.

THE CLAIMS DEFINING THE INVENTION ARE AS FOLLOWS:

1. A heat transfer composition comprising:

- (a) from about 60% to about 70% by weight of HFC-32;
- 5 (b) from about 20% to about 40% by weight of trans-HFO-1234ze; and
- (c) from greater than about 0% to about 10% by weight of HFC-125,

provided that the amount of component (c) is effective to improve one or more of glide of the composition; heating capacity of the composition, burning velocity of the composition; and/or hazard value of the composition.

10 2. The heat transfer composition of claim 1, comprising from about 1% to about 10% by weight of HFC-125.

3. The heat transfer composition of claim 1 or claim 2, comprising from about 3% to about 10% by weight of HFC-125.

15 4. The heat transfer composition of any one of claims 1 to 3, comprising from about 3% to about 8% by weight of HFC-125.

5. The heat transfer composition of any one of claims 1 to 4, comprising about 8% by weight of HFC-125.

6. The heat transfer composition of any one of claims 1 to 5, comprising from about 63% to about 69% by weight of HFC-32.

20 7. The heat transfer composition of any one of claims 1 to 6, comprising 68% by weight of HFC-32.

8. The heat transfer composition of any one of claims 1 to 7, comprising from about 20% to about 25% by weight of trans-HFO-1234ze.

9. The heat transfer composition of any one of claims 1 to 8, comprising about 25% by weight of trans-HFO-1234ze.
10. The heat transfer composition of claim 1, comprising:
 - i) 68% by weight of HFC-32, 28% by weight of trans-HFO-1234ze and 4% by weight of HFC-125, or
 - ii) 68% by weight of HFC-32, 26% by weight of trans-HFO-1234ze and 6% by weight of HFC-125.
11. The heat transfer composition of any one of the preceding claims, wherein said composition consists essentially of components (a) to (c).
- 10 12. The heat transfer composition of any one of the preceding claims, wherein said composition consists of components (a) to (c).
13. The heat transfer composition of any one of claims 1 to 10, wherein said composition additionally comprises a lubricant,
14. The heat transfer composition of claim 13, wherein the lubricant is a polyol ester (POE) or a polyvinyl ether (PVE).
15. The heat transfer composition of any one of the preceding claims, wherein said composition has a Global Warming Potential (GWP) of not greater than about 1000.
16. The heat transfer composition of any one of the preceding claims, wherein said composition has a Global Warming Potential (GWP) of not greater than about 700.
- 20 17. The heat transfer composition of any one of the preceding claims, wherein said composition has Class 2L flammability as determined in accordance with ASTM standard E-681, dated 2002.
18. The heat transfer composition of any one of the preceding claims, wherein said composition has a burning velocity of less than about 10 cm/s.

19. The heat transfer composition of claim 18, wherein said composition has a burning velocity of less than about 4 cm/s.

20. The heat transfer composition of claim 19, wherein said composition has a burning velocity of about 2 cm/s.

5 21. The heat transfer composition of any one of the preceding claims, wherein said composition has a hazard value of less than about 7.

22. The heat transfer composition of claim 21, wherein said composition has a hazard value of about 2.

23. A method of replacing an existing heat transfer fluid contained in heat transfer system comprising removing at least a portion of said existing heat transfer fluid from said system, said existing heat transfer fluid being HFC-410A and replacing at least a portion of said existing heat transfer fluid by introducing into said system a heat transfer composition of any one of claims 1-22.

10 24. The method of claim 23, wherein the capacity of the system is at least about 95% of the capacity of the system prior to the replacement step.

15 25. The method of claim 23 or 24, wherein the capacity of the system is less than about 105% of the capacity of the system prior to the replacement step.

26. The method of any one of claims 23 to 25, wherein the efficiency of the system is at least about 100% of the efficiency of the system prior to the replacement step.

20 27. A heat transfer system comprising a compressor, a condenser and an evaporator in fluid communication, and a heat transfer composition in said system, said heat transfer composition comprising the composition of any one of claims 1-22.

28. The method of any one of claims 23 to 26 or the heat transfer system of claim 27, wherein the heat transfer system is a refrigeration system selected from an automotive air conditioning system, a residential air conditioning system, a commercial air conditioning system, a residential refrigerator system, a residential freezer system, a commercial refrigerator system, a commercial freezer system, a chiller air conditioning system, a chiller refrigeration system, a heat pump system, and combinations of two or more of these.
29. The method of any one of claims 23 to 26 or the heat transfer system of claim 27, wherein the heat transfer system is a commercial air conditioning system, a residential air conditioning system, a chiller air conditioning system, or a heat pump.
30. A method of transferring heat to or from a fluid or body comprising causing a phase change in a composition of any one of claims 1-22, and exchanging heat with said fluid or body during said phase change.
31. Use as a replacement for R410A of a heat transfer composition as defined in any one of claims 1-22.
32. The use of claim 31, wherein the heat transfer composition is used in a system selected from an automotive air conditioning system, a residential air conditioning system, a commercial air conditioning system, a residential refrigerator system, a residential freezer system, a commercial refrigerator system, a commercial freezer system, a chiller air conditioning system, a chiller refrigeration system, a heat pump system, and combinations of two or more of these.

21 Feb 2017

2013348300

33. The use of claim 31, wherein the heat transfer composition is used in a commercial air conditioning system, a residential air conditioning system, a chiller air conditioning system, or a heat pump.