




(86) Date de dépôt PCT/PCT Filing Date: 2012/08/30
(87) Date publication PCT/PCT Publication Date: 2013/03/07
(45) Date de délivrance/Issue Date: 2018/05/22
(85) Entrée phase nationale/National Entry: 2014/02/26
(86) N° demande PCT/PCT Application No.: CA 2012/000815
(87) N° publication PCT/PCT Publication No.: 2013/029165
(30) Priorités/Priorities: 2011/08/31 (US61/529,639);
2011/10/03 (US61/542,551)

(51) Cl.Int./Int.Cl. *B62D 55/00* (2006.01),
E02F 9/16 (2006.01)
(72) Inventeurs/Inventors:
STEBEN, ERIC, CA;
MARLEAU, BENOIT, CA
(73) Propriétaire/Owner:
PRINOTH LTD., CA
(74) Agent: SMART & BIGGAR

(54) Titre : VEHICULE A CHENILLES
(54) Title: TRACKED VEHICLE



(57) **Abrégé/Abstract:**

A tracked vehicle, such as tracked carrier to carry and enable use of work equipment (e.g., a crane, an aerial work platform, a drill rig, etc.) on various terrains, is provided. The tracked vehicle may comprise a frame comprising an equipment mounting area for mounting work equipment above the frame. The frame may comprise a pair of side rails that have a spacing in a widthwise direction of the tracked vehicle which corresponds to a standard truck frame side rail spacing (e.g., 34 inches). An operator cabin comprises a seating area which may comprise a single seat for an operator or a first seat for the operator and a second seat for a second person next to the operator. At least part of a power plant of the tracked vehicle may be mounted above the frame and behind the operator cabin. The tracked vehicle comprises a plurality of track assemblies for traction of the tracked vehicle.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property

Organization

International Bureau

(43) International Publication Date
7 March 2013 (07.03.2013)

(10) International Publication Number

WO 2013/029165 A1

(51) International Patent Classification:

B62D 55/00 (2006.01) **E02F 9/16** (2006.01)

(21) International Application Number:

PCT/CA2012/000815

(22) International Filing Date:

30 August 2012 (30.08.2012)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:


61/529,639	31 August 2011 (31.08.2011)	US
61/542,551	3 October 2011 (03.10.2011)	US

(71) **Applicant** (for all designated States except US): **ROLIC INVEST SARL** [LU/LU]; 41, Boulevard Henri, L-1724 Luxembourg (LU).(72) **Inventors; and**(75) **Inventors/Applicants** (for US only): **STEBEN, Eric** [CA/CA]; 723 Dunlavy, Bromont, Québec J2L 0J5 (CA). **MARLEAU, Benoît** [CA/CA]; 1280 Sainte-Catherine, St-Hyacinthe, Québec J2S 5Z4 (CA).(74) **Agent: SMART & BIGGAR**; 1000 de la Gauchetière Street West, Suite 3300, Montréal, Québec H3B 4W5 (CA).(81) **Designated States** (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,

AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) **Designated States** (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).**Published:**

- with international search report (Art. 21(3))
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))

(54) **Title:** TRACKED VEHICLE**FIG. 1**

(57) **Abstract:** A tracked vehicle, such as tracked carrier to carry and enable use of work equipment (e.g., a crane, an aerial work platform, a drill rig, etc.) on various terrains, is provided. The tracked vehicle may comprise a frame comprising an equipment mounting area for mounting work equipment above the frame. The frame may comprise a pair of side rails that have a spacing in a widthwise direction of the tracked vehicle which corresponds to a standard truck frame side rail spacing (e.g., 34 inches). An operator cabin comprises a seating area which may comprise a single seat for an operator or a first seat for the operator and a second seat for a second person next to the operator. At least part of a power plant of the tracked vehicle may be mounted above the frame and behind the operator cabin. The tracked vehicle comprises a plurality of track assemblies for traction of the tracked vehicle.

TRACKED VEHICLE

CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims priority from U.S. Provisional Patent Application No. 61/529,639 filed on August 31, 2011 and U.S. Provisional Patent Application No. 61/542,551 filed on October 3, 2011.

FIELD OF THE INVENTION

The invention relates to tracked vehicles designed to travel on various terrains, including rugged terrain, and, in particular, to tracked utility vehicles carrying work equipment.

BACKGROUND

One type of tracked vehicle is a tracked utility vehicle, sometimes referred to as a "tracked carrier" or "tracked equipment carrier" vehicle, which carries and enables use of work equipment, such as a crane, an aerial device, a drill rig, a digger derrick, and/or any other industrial apparatus, on various terrains, including rugged terrain (e.g., with mud, steep hills, swamps, rocks, mud, and/or snow).

It is often desirable for a tracked utility vehicle to have a carrying capacity as large as possible but yet be sized such that the vehicle can fit a public road infrastructure. For example, it may be desirable that the vehicle be low enough to fit below an underpass or otherwise respect a vehicle height limit of the public road infrastructure (e.g., when transported on a truck's deck trailer). This typically imposes certain limitations on components of the vehicle. For instance, this may

limit a size of an operator cabin of the vehicle, to avoid interference with the work equipment carried by the vehicle.

The work equipment carried by a tracked utility vehicle is normally mounted to the vehicle's frame. This can often present issues or challenges. For example, the work equipment is often designed to be installed on a truck's frame. Since the tracked utility vehicle's frame is typically very different from a truck's frame, the work equipment cannot be mounted as readily to the tracked utility vehicle's frame than to a truck's frame. Rather, modifications may have to be made to the work equipment and/or to the tracked utility vehicle to allow the work equipment to be installed on the tracked utility vehicle's frame. For instance, in some cases, an intermediate support structure may need to be installed between the work equipment and the tracked utility vehicle's frame to support and anchor the work equipment.

15

Each track assembly of a tracked utility vehicle comprises an endless track disposed around a set of wheels and engaging the ground to generate traction. Installing the endless track around the set of wheels can sometimes be difficult. For instance, in some case, the endless track's inner side may have guide projections which may interfere with some of the wheels during installation of the track around the set of wheels. Also, tension in the endless track may be maintained by an independent tensioner (e.g., a hydraulic accumulator and cylinder or a spring-loaded actuator) which may cause certain issues (e.g., difficulties in maintaining constant tension over displacement of the cylinder or actuator).

25

Challenges similar to those discussed above in respect of a tracked utility vehicle may be encountered in other types of industrial tracked vehicles.

Accordingly, there is a need for improvements in tracked utility vehicles and other tracked vehicles.

30

SUMMARY OF THE INVENTION

In accordance with an aspect of the invention, there is provided a tracked vehicle comprising: a) a chassis comprising a frame extending along a longitudinal direction of the tracked vehicle; b) an operator cabin mounted to the frame, the frame comprising a pair of side members extending in an area behind the operator cabin in the longitudinal direction of the tracked vehicle, the pair of side members being spaced apart in a widthwise direction of the tracked vehicle for supporting work equipment carried by the tracked vehicle; c) a power plant mounted above the side members, at least part of the power plant occupying a space next to the operator cabin along the widthwise direction of the tracked vehicle and extending past the operator cabin along the longitudinal direction of the tracked vehicle; and d) a plurality of track assemblies for traction of the tracked vehicle, a first one of the track assemblies being on a first side of the tracked vehicle, a second one of the track assemblies being on a second side of the tracked vehicle, each track assembly of the plurality of track assemblies being mounted to the frame and comprising: (i) a plurality of wheels including: a drive wheel; an end wheel spaced apart from the drive wheel in the longitudinal direction of the tracked vehicle; and a plurality of support wheels arranged in an inline configuration between the drive wheel and the end wheel; and (ii) an endless track disposed around the plurality of wheels for engaging the ground, the endless track comprising: a top run extending between the drive wheel and the end wheel over the support wheels without contacting the support wheels; and a ground-engaging bottom run extending under the support wheels, the drive wheel being in driving engagement with the endless track to impart motion to the endless track; at least part of the prime mover being mounted to the frame and located directly above at least part of the first one of said track assemblies; each of the side members extending rearwards in the longitudinal direction of the tracked vehicle past the operator cabin and past said part of the power plant that extends past the operator cabin.

5 In accordance with another aspect of the invention, there is provided a tracked vehicle comprising: a) a chassis comprising a frame extending along a longitudinal direction of the tracked vehicle, the frame comprising a pair of elongated structural members spaced apart in a widthwise direction of the tracked vehicle for supporting work equipment carried by the tracked vehicle; b) an operator cabin mounted to the frame; c) a power
10 plant mounted to the frame and comprising a prime mover, wherein the power plant comprises a housing which houses at least the prime mover, the housing having an L-shaped configuration extending behind and next to the operator cabin, there being no portion of the prime mover under the operator cabin; and d) a plurality of track assemblies for traction of the tracked vehicle, a first one of the track assemblies being
15 on a first side of the tracked vehicle, a second one of the track assemblies being on a second side of the tracked vehicle, each track assembly of the plurality of track assemblies being mounted to the frame and comprising: (i) a plurality of wheels including: a drive wheel; an end wheel spaced apart from the drive wheel in the longitudinal direction of the tracked vehicle; and a plurality of support wheels arranged in
20 an inline configuration between the drive wheel and the end wheel; and (ii) an endless track disposed around the plurality of wheels for engaging the ground, the endless track comprising: a top run extending between the drive wheel and the end wheel over the support wheels; and a ground-engaging bottom run extending under the support wheels, the drive wheel being in driving engagement with the endless track to impart motion to
25 the endless track, the elongated structural members having a bottom surface below the top run of the endless track and a top surface above at least part of the top run of the endless track.

In accordance with another aspect of the invention, there is provided a tracked vehicle comprising: a) a chassis comprising a frame extending along a longitudinal direction of
30 the tracked vehicle; b) an operator cabin mounted to the frame, the frame comprising a pair of side members extending in an area behind the operator cabin in the longitudinal direction of the tracked vehicle, the pair of side members being spaced apart in a widthwise direction of the tracked vehicle for mounting work equipment carried by the

5 tracked vehicle to the side members; c) a power plant mounted to the frame and comprising a prime mover, the prime mover being mounted above the side members, at least part of the power plant occupying a space next to the operator cabin along the widthwise direction of the tracked vehicle and extending past the operator cabin along the longitudinal direction of the tracked vehicle; and d) a plurality of track assemblies for
10 traction of the tracked vehicle, a first one of the track assemblies being on a first side of the tracked vehicle, a second one of the track assemblies being on a second side of the tracked vehicle, each track assembly of the plurality of track assemblies being mounted to the frame and comprising: (i) a plurality of wheels including: a drive wheel; an end wheel spaced apart from the drive wheel in the longitudinal direction of the tracked
15 vehicle; and a plurality of support wheels arranged in an inline configuration between the drive wheel and the end wheel; and (ii) an endless track disposed around the plurality of wheels for engaging the ground, the endless track comprising: a top run extending between the drive wheel and the end wheel over the support wheels without contacting the support wheels; and a ground-engaging bottom run extending under the support
20 wheels, the drive wheel being in driving engagement with the endless track to impart motion to the endless track; wherein the side members extend along the longitudinal direction of the tracked vehicle and wherein each of the side members extends longitudinally at one end past the drive wheel of a corresponding one of the endless tracks and at another end past the end wheel of the corresponding endless track.

25 In accordance with another aspect of the invention, there is provided a tracked vehicle comprising: a) a chassis comprising a frame extending along a longitudinal direction of the tracked vehicle, the frame comprising an equipment mounting area for mounting work equipment above the frame; b) an operator cabin mounted to the frame, the frame comprising a pair of side members extending in an area behind the operator cabin in the
30 longitudinal direction of the tracked vehicle, the pair of side members being spaced apart in a widthwise direction of the tracked vehicle for supporting work equipment carried by the tracked vehicle; c) a power plant mounted to the frame and comprising a prime mover, the prime mover being mounted above the side members, at least part of

5 the power plant occupying a space next to the operator cabin along the widthwise
direction of the tracked vehicle and extending past the operator cabin along the
longitudinal direction of the tracked vehicle; and d) a plurality of track assemblies for
traction of the tracked vehicle, a first one of the track assemblies being on a first side of
the tracked vehicle, a second one of the track assemblies being on a second side of the
10 tracked vehicle, each track assembly of the plurality of track assemblies being mounted
to the frame and comprising: (i) a plurality of wheels including: a drive wheel; an end
wheel spaced apart from the drive wheel in the longitudinal direction of the tracked
vehicle; and a plurality of support wheels arranged in an inline configuration between the
drive wheel and the end wheel; and (ii) an endless track disposed around the plurality of
15 wheels for engaging the ground, the endless track comprising: a top run extending
between the drive wheel and the end wheel over the support wheels without contacting
the support wheels; and a ground-engaging bottom run extending under the support
wheels, the drive wheel being in driving engagement with the endless track to impart
motion to the endless track, at least part of the prime mover being mounted to the frame
20 and located directly above at least part of the first one of said track assemblies; wherein
each of the side members extends longitudinally at one end past the drive wheel or the
end wheel of the corresponding endless track.

In accordance with another aspect of the invention, there is provided a tracked vehicle
comprising: a) a chassis comprising a frame extending along a longitudinal direction of
25 the tracked vehicle, the frame comprising an equipment mounting area for mounting
work equipment above the frame; b) an operator cabin mounted to the frame, the frame
comprising a pair of side members extending in an area behind the operator cabin in the
longitudinal direction of the tracked vehicle, the pair of side members being spaced
apart in a widthwise direction of the tracked vehicle for supporting work equipment
30 carried by the tracked vehicle; c) a power plant mounted to the frame and comprising a
prime mover, the prime mover being mounted above the side members, at least part of
the power plant occupying a space next to the operator cabin along the widthwise
direction of the tracked vehicle and extending past the operator cabin along the

5 longitudinal direction of the tracked vehicle; and d) a plurality of track assemblies for
traction of the tracked vehicle, a first one of the track assemblies being on a first side of
the tracked vehicle, a second one of the track assemblies being on a second side of the
tracked vehicle, each track assembly of the plurality of track assemblies being mounted
to the frame and comprising: (i) a plurality of wheels including: a drive wheel; an end
10 wheel spaced apart from the drive wheel in the longitudinal direction of the tracked
vehicle; and a plurality of support wheels arranged in an inline configuration between the
drive wheel and the end wheel; and (ii) an endless track disposed around the plurality of
wheels for engaging the ground, the endless track comprising: a top run extending
between the drive wheel and the end wheel over the support wheels without contacting
15 the support wheels; and a ground-engaging bottom run extending under the support
wheels, the drive wheel being in driving engagement with the endless track to impart
motion to the endless track; at least part of the prime mover being mounted to the frame
and located directly above at least part of the first one of said track assemblies; wherein
the power plant comprises a housing which houses at least the prime mover, the
20 housing having an L-shaped configuration extending behind and next to the operator
cabin.

In accordance with another aspect of the invention, there is provided a tracked vehicle
comprising: a) a chassis comprising a frame extending along a longitudinal direction of
the tracked vehicle, the frame comprising an equipment mounting area for mounting
25 work equipment above the frame; b) an operator cabin mounted to the frame, the
operator cabin comprising a seating area for allowing an operator to sit and a user
interface for enabling the operator to control the tracked vehicle, the seating area
defining a plurality of seat positions along a widthwise direction of the tracked vehicle,
the seating area having a first seat for the operator and a second seat for a person
30 sitting next to the operator, the operator cabin being off-center along a widthwise
direction of the tracked vehicle and extending over a majority of the width of the frame;
c) a power plant mounted to the frame and comprising a prime mover; and d) a plurality
of track assemblies for traction of the tracked vehicle, a first one of the track assemblies

5 being on a first lateral side of the tracked vehicle, a second one of the track assemblies
being on a second lateral side of the tracked vehicle, each track assembly of the
plurality of track assemblies being mounted to the frame and comprising: (i) a plurality of
wheels including: a drive wheel; an end wheel spaced apart from the drive wheel in the
longitudinal direction of the tracked vehicle; and a plurality of support wheels arranged in
10 an inline configuration between the drive wheel and the end wheel; and (ii) an endless
track disposed around the plurality of wheels for engaging the ground, the endless track
comprising: a top run extending between the drive wheel and the end wheel over the
support wheels; and a ground-engaging bottom run extending under the support wheels,
the drive wheel being in driving engagement with the endless track to impart motion to
15 the endless track.

In accordance with another aspect of the invention, there is provided a tracked vehicle
comprising: a) a chassis comprising a frame extending along a longitudinal direction of
the tracked vehicle, the frame comprising an equipment mounting area for mounting
work equipment above the frame; b) an operator cabin mounted to the frame, the
20 operator cabin comprising a seating area for allowing an operator to sit and a user
interface for enabling the operator to control the tracked vehicle, the seating area
defining a plurality of seat positions along a widthwise direction of the tracked vehicle,
the seating area having a first seat for the operator and a second seat for a person
sitting next to the operator, the operator cabin being off-center along a widthwise
25 direction of the tracked vehicle and extending over a majority of the width of the frame;
c) a power plant mounted to the frame and comprising a prime mover, wherein the
power plant comprises a hydraulic pump connected to the prime mover and mounted
above the frame and behind the operator cabin; and d) a plurality of track assemblies for
traction of the tracked vehicle, a first one of the track assemblies being on a first lateral
30 side of the tracked vehicle, a second one of the track assemblies being on a second
lateral side of the tracked vehicle, each track assembly of the plurality of track
assemblies being mounted to the frame and comprising: (i) a plurality of wheels
including: a drive wheel; an end wheel spaced apart from the drive wheel in the

5 longitudinal direction of the tracked vehicle; and a plurality of support wheels arranged in
an inline configuration between the drive wheel and the end wheel; and (ii) an endless
track disposed around the plurality of wheels for engaging the ground, the endless track
comprising: a top run extending between the drive wheel and the end wheel over the
support wheels; and a ground-engaging bottom run extending under the support wheels,
10 the drive wheel being in driving engagement with the endless track to impart motion to
the endless track.

In accordance with another aspect of the invention, there is provided a tracked vehicle
comprising: a) a chassis comprising a frame extending along a longitudinal direction of
the tracked vehicle, the frame comprising an equipment mounting area for mounting
15 work equipment above the frame; b) an operator cabin mounted to the frame, the
operator cabin comprising a seating area for allowing an operator to sit and a user
interface for enabling the operator to control the tracked vehicle, the seating area
defining a plurality of seat positions along a widthwise direction of the tracked vehicle,
the seating area having a first seat for the operator and a second seat for a person
20 sitting next to the operator, the operator cabin being off-center along a widthwise
direction of the tracked vehicle and extending over a majority of the width of the frame;
c) a power plant mounted to the frame and comprising a prime mover, wherein at least
part of the power plant is mounted above the frame and on a lateral side of the operator
cabin; and d) a plurality of track assemblies for traction of the tracked vehicle, a first one
25 of the track assemblies being on a first lateral side of the tracked vehicle, a second one
of the track assemblies being on a second lateral side of the tracked vehicle, each track
assembly of the plurality of track assemblies being mounted to the frame and
comprising: (i) a plurality of wheels including: a drive wheel; an end wheel spaced apart
from the drive wheel in the longitudinal direction of the tracked vehicle; and a plurality of
30 support wheels arranged in an inline configuration between the drive wheel and the end
wheel; and (ii) an endless track disposed around the plurality of wheels for engaging the
ground, the endless track comprising: a top run extending between the drive wheel and
the end wheel over the support wheels; and a ground-engaging bottom run extending

- 5 under the support wheels, the drive wheel being in driving engagement with the endless track to impart motion to the endless track.

In accordance with another aspect of the invention, there is provided a tracked vehicle comprising: a) a chassis comprising a frame extending along a longitudinal direction of the tracked vehicle, the frame comprising an equipment mounting area for mounting
10 work equipment above the frame; b) an operator cabin mounted to the frame, the operator cabin comprising a seating area for allowing an operator to sit and a user interface for enabling the operator to control the tracked vehicle, the seating area defining a plurality of seat positions along a widthwise direction of the tracked vehicle, the seating area having a first seat for the operator and a second seat for a person
15 sitting next to the operator, the operator cabin being off-center along a widthwise direction of the tracked vehicle and extending over a majority of the width of the frame; the operator cabin extending over a majority of the height of the vehicle in an absence of the work equipment; c) an engine mounted above the frame; and d) a plurality of track assemblies for traction of the tracked vehicle, a first one of the track assemblies being
20 on a first lateral side of the tracked vehicle, a second one of the track assemblies being on a second lateral side of the tracked vehicle, each track assembly of the plurality of track assemblies being mounted to the frame and comprising: (i) a plurality of wheels including: a drive wheel; an end wheel spaced apart from the drive wheel in the longitudinal direction of the tracked vehicle; and a plurality of support wheels arranged in
25 an inline configuration between the drive wheel and the end wheel; and (ii) an endless track disposed around the plurality of wheels for engaging the ground, the endless track comprising: a top run extending between the drive wheel and the end wheel over the support wheels; and a ground-engaging bottom run extending under the support wheels, the drive wheel being in driving engagement with the endless track to impart motion to
30 the endless track.

In accordance with another aspect of the invention, there is provided a tracked vehicle comprising: a) a chassis comprising a frame extending along a longitudinal direction of

5 the tracked vehicle, the frame comprising an equipment mounting area for mounting
work equipment above the frame; b) an operator cabin mounted to the frame; c) a power
plant mounted to the frame and comprising a prime mover, at least part of the power
plant being mounted above the frame and behind the operator cabin; and d) a plurality
of track assemblies for traction of the tracked vehicle, a first one of the track assemblies
10 being on a first lateral side of the tracked vehicle, a second one of the track assemblies
being on a second lateral side of the tracked vehicle, each track assembly of the
plurality of track assemblies being mounted to the frame and comprising: (i) a plurality of
wheels including: a drive wheel; an end wheel spaced apart from the drive wheel in the
longitudinal direction of the tracked vehicle; and a plurality of support wheels arranged in
15 an inline configuration between the drive wheel and the end wheel; the end wheel and a
rearmost one of the support wheels overlapping in the longitudinal direction of the
tracked vehicle; and (ii) an endless track disposed around the plurality of wheels for
engaging the ground, the endless track comprising: a top run extending between the
drive wheel and the end wheel over the support wheels; and a ground-engaging bottom
20 run extending under the support wheels, the drive wheel being in driving engagement
with the endless track to impart motion to the endless track.

In accordance with another aspect of the invention, there is provided a tracked vehicle
comprising: a) a chassis comprising a frame extending along a longitudinal direction of
the tracked vehicle, the frame comprising an equipment mounting area for mounting
25 work equipment above the frame; b) an operator cabin mounted to the frame, the
operator cabin comprising: (i) a seating area for allowing an operator to sit; and (ii) a
user interface for enabling the operator to control the tracked vehicle, the user interface
comprising: an accelerator for controlling a speed of the tracked vehicle and a steering
device for steering the tracked vehicle; c) the operator cabin being configurable in a
30 plurality of cabin configurations including: (i) a first cabin configuration in which the
operator sits in a first seat position of the seating area along a widthwise direction of the
track assembly and the steering device is in a first steering device position along the
widthwise direction of the track assembly; and (ii) a second cabin configuration in which

5 the operator sits in a second seat position of the seating area along the widthwise direction of the track assembly and the steering device is in a second steering device position along the widthwise direction of the track assembly, d) a power plant mounted to the frame and comprising a prime mover; and e) a plurality of track assemblies for traction of the tracked vehicle, a first one of the track assemblies being on a first lateral
10 side of the tracked vehicle, a second one of the track assemblies being on a second lateral side of the tracked vehicle, each track assembly of the plurality of track assemblies being mounted to the frame and comprising: (i) a plurality of wheels including: a drive wheel; an end wheel spaced apart from the drive wheel in the longitudinal direction of the tracked vehicle; and a plurality of support wheels arranged in
15 an inline configuration between the drive wheel and the end wheel; and (ii) an endless track disposed around the plurality of wheels for engaging the ground, the endless track comprising: a top run extending between the drive wheel and the end wheel over the support wheels; and a ground-engaging bottom run extending under the support wheels, the drive wheel being in driving engagement with the endless track to impart motion to
20 the endless track.

In accordance with another aspect of the invention, there is provided a tracked vehicle comprising: a) a chassis comprising a frame extending along a longitudinal direction of the tracked vehicle; b) an operator cabin mounted to the frame, the frame comprising a pair of side members extending in an area behind the operator cabin in the longitudinal
25 direction of the tracked vehicle, the pair of side members being spaced apart in a widthwise direction of the tracked vehicle for supporting work equipment carried by the tracked vehicle; c) a power plant mounted to the frame and comprising a prime mover; and d) a plurality of track assemblies for traction of the tracked vehicle, a first one of the track assemblies being on a first side of the tracked vehicle, a second one of the track
30 assemblies being on a second side of the tracked vehicle, each track assembly of the plurality of track assemblies being mounted to the frame and comprising: (i) a plurality of wheels including: a drive wheel; an end wheel spaced apart from the drive wheel in the longitudinal direction of the tracked vehicle; and a plurality of support wheels arranged in

5 an inline configuration between the drive wheel and the end wheel; the end wheel and one of the support wheels overlapping in the longitudinal direction of the tracked vehicle; and (ii) an endless track disposed around the plurality of wheels for engaging the ground, the endless track comprising: a top run extending between the drive wheel and the end wheel over the support wheels; and a ground-engaging bottom run extending
10 under the support wheels, the drive wheel being in driving engagement with the endless track to impart motion to the endless track.

In accordance with another aspect of the invention, there is provided tracked vehicle comprising: a) a chassis comprising a frame extending along a longitudinal direction of the tracked vehicle; b) an operator cabin mounted to the frame, the frame comprising a
15 pair of side members extending in an area behind the operator cabin in the longitudinal direction of the tracked vehicle, the pair of side members being spaced apart in a widthwise direction of the tracked vehicle for supporting work equipment carried by the tracked vehicle; c) a power plant mounted to the frame and comprising a prime mover; and d) a plurality of track assemblies for traction of the tracked vehicle, a first one of the
20 track assemblies being on a first side of the tracked vehicle, a second one of the track assemblies being on a second side of the tracked vehicle, each track assembly of the plurality of track assemblies being mounted to the frame and comprising: (i) a plurality of wheels including: a drive wheel; an end wheel spaced apart from the drive wheel in the longitudinal direction of the tracked vehicle; and a plurality of support wheels arranged in
25 an inline configuration between the drive wheel and the end wheel; wherein at least one of the support wheels comprises an inboard support wheel member connected to an outboard support wheel member, the inboard and outboard support wheel members defining a guiding space therebetween; and (ii) an endless track disposed around the plurality of wheels for engaging the ground, the endless track comprising: a top run
30 extending between the drive wheel and the end wheel over the support wheels; a ground-engaging bottom run extending under the support wheels, the drive wheel being in driving engagement with the endless track to impart motion to the endless track; and

- 5 a wheel guide configured to pass through the guiding space of the at least one support wheel as the endless track moves around the plurality of wheels.

In accordance with another aspect of the invention, there is provided a tracked vehicle comprising: a) a chassis comprising a frame extending along a longitudinal direction of the tracked vehicle; b) an operator cabin mounted to the frame and located entirely
10 within a front half of the tracked vehicle, the frame comprising a pair of side members extending in an area behind the operator cabin in the longitudinal direction of the tracked vehicle, the pair of side members being spaced apart in a widthwise direction of the tracked vehicle for supporting work equipment carried by the tracked vehicle; c) a power plant mounted to the frame and comprising a prime mover; and d) a plurality of track
15 assemblies for traction of the tracked vehicle, a first one of the track assemblies being on a first side of the tracked vehicle, a second one of the track assemblies being on a second side of the tracked vehicle, each track assembly of the plurality of track assemblies being mounted to the frame and comprising: (i) a plurality of wheels including: a first wheel at a first end and a wheel at a second end spaced apart from the
20 first wheel in the longitudinal direction of the tracked vehicle; and a plurality of support wheels arranged in an inline configuration between the first wheel and the second wheel; at least the first wheel and one of the support wheels overlapping in the longitudinal direction of the tracked vehicle; and (ii) an endless track disposed around the plurality of wheels for engaging the ground, the endless track comprising: a top run
25 extending between the first wheel and the second wheel over the support wheels; and a ground-engaging bottom run extending under the support wheels, one of the first wheel and the second wheel being in driving engagement with the endless track to impart motion to the endless track.

These and other aspects of the invention will now become apparent to those of ordinary
30 skill in the art upon review of the following description of embodiments of the invention in conjunction with the accompanying drawings.

5 In accordance with another aspect of the invention, there is provided a tracked vehicle comprising: a. a frame comprising a pair of side members extending in a longitudinal direction of the tracked vehicle and being spaced apart in a widthwise direction of the tracked vehicle for supporting work equipment, each side member of the pair of side members having a respective uppermost surface; b. a first track assembly and a second
10 track assembly for traction of the tracked vehicle, the first track assembly being on a first side of the tracked vehicle, the second track assembly being on a second side of the tracked vehicle, each of the track assemblies being mounted to the frame and comprising, respectively: (i) a plurality of wheels including: a drive wheel; an end wheel spaced apart from the drive wheel in the longitudinal direction; and a plurality of support
15 wheels arranged in an inline configuration between the drive wheel and the end wheel; and (ii) an endless track disposed around the plurality of wheels for engaging the ground, the endless track comprising: I. a top run extending between the drive wheel and the end wheel over the support wheels; and II. A ground-engaging bottom run extending under the support wheels, the drive wheel being in driving engagement with
20 the endless track to impart motion to the endless track; c. operator cabin mounted to the frame and comprising a floor, wherein an entirety of the floor is at a higher elevation, with respect to the bottom run of each of the track assemblies, than the uppermost surface of each of the side members, wherein the operator cabin extends in the longitudinal direction, and wherein each of the side members extends in the longitudinal
25 direction past the operator cabin; and d. an internal combustion engine mounted to the frame, wherein an entirety of the internal combustion engine is at a higher elevation, with respect to the bottom run of each of the track assemblies, than the uppermost surface of each of the side members, and wherein at least a portion of the internal combustion engine overlies at least a portion of at least one of the track assemblies.

BRIEF DESCRIPTION OF THE DRAWINGS

A detailed description of embodiments of the invention is provided below, by way of example only, with reference to the accompanying drawings, in which:

- Figures 1 to 6 show a first perspective view, a second perspective view, a side view, a front view, a rear view, and a top view of an example of a tracked vehicle equipped with work equipment in accordance with an embodiment of the invention;
- Figures 7 to 13 show a first perspective view, a second perspective view, a side view, a front view, a rear view, a top view, and a bottom view of the tracked vehicle without the work equipment;
- Figures 14 to 18 show a perspective view, a side view, a top view, a front view, and a rear view of a chassis including a frame and track assemblies of the tracked vehicle;

- Figures 19 to 25 show a perspective view, a side view, a top view, a bottom view, a front view, a rear view, and a cross-sectional view of the frame and the track assemblies without endless tracks of the track assemblies;
- Figures 26 to 28 show examples of attachment devices which secure the work
5 equipment to the frame of the tracked vehicle;
- Figures 29 and 30 show a top view of an inner side, and a cross-sectional view, of an endless track in accordance with an embodiment of the invention;

- Figures 31 and 32 show a perspective view of a ground-engaging outer side, and a perspective view of an inner side, of an endless track in accordance with another embodiment of the invention;
- Figures 33 and 34 show front and rear perspective views of a power plant
5 of the tracked vehicle with panels of a housing of the power plant removed;
- Figures 35 and 36 show cross-sectional views of a support wheel of a track assembly with and without the endless track;
- Figures 37 and 38 show a perspective view and a cross-sectional view of
10 a track tensioner in relation to wheels of a track assembly;
- Figures 39 and 40 show a perspective view and a cross-sectional view of a support wheel of a track assembly in accordance with another embodiment of the invention;
- Figure 41 shows an operator cabin of the tracked vehicle configured in a
15 one-person configuration;
- Figure 42 shows the operator cabin in the one-person configuration with a seat and components of a user interface removed;
- Figure 43 shows the operator cabin configured in a two-person configuration;
- Figure 44 shows the operator cabin in the two-person configuration with
20 seats and components of the user interface removed;
- Figure 45 shows components of the user interface connected to other components of the tracked vehicle;
- Figure 46 shows a seat support and part of a user interface support of the
25 operator cabin;
- Figure 47 shows the seat support and the user interface support of the operator cabin; and
- Figures 48 to 50 show track tensioners of the track assemblies hydraulically connected to a hydraulic drive system of the tracked vehicle.

In the drawings, embodiments of the invention are illustrated by way of example. It is to be expressly understood that the description and drawings are only for the purpose of illustrating certain embodiments of the invention and are an aid for understanding. They are not intended to be a definition of the limits of the
5 invention.

DETAILED DESCRIPTION OF EMBODIMENTS

Figures 1 to 13 show an example of a tracked utility vehicle 10 in accordance
10 with an embodiment of the invention. The tracked utility vehicle 10 is designed to carry and enable use of work equipment 41, which includes one or more work implements such as, for example, a crane, a ladder, an aerial device, an aerial work platform, a lift, a drill rig, a digger derrick, a material handler, and/or any other industrial apparatus, on various terrains, including rugged terrain (e.g., with mud,
15 steep hills, swamps, rocks, mud, and/or snow). This type of vehicle can sometimes be referred to as a "tracked carrier" or "tracked equipment carrier" vehicle.

The tracked utility vehicle 10 has a length L_v , a width W_v , and a height H_v
20 (measured without taking into account the work equipment 41). These dimensions may allow the vehicle 10 to have a large payload capacity while being able to be used in a public road infrastructure. For example, in some embodiments, the length L_v may be at least 5 m, such as between 5 m and 10 m, in some cases between 6 m and 9 m, and in some cases between 7 m and 8 m;
25 the width W_v may be at least 2 m, such as between 2 m and 5 m, in some cases between 2.5 m and 4.5 m, and in some cases between 3 m and 4 m; and the height H_v may be no more than 4 m, in some cases no more than 3.5 m, and in some cases no more than 3 m. The length L_v , width W_v , and height H_v may take on various other values in other embodiments.

30

The tracked utility vehicle 10 has a payload capacity which can be quite large. For example, in some embodiments, the payload capacity of the vehicle 10 may be at least 10000 lbs (about 4536 kg), in some cases at least 15000 lbs (about 6804 kg), in some cases at least 20000 lbs (about 9072 kg), in some cases at least 30000 lbs (about 13608 kg), and in some cases at least 40000 lbs (18144 kg). The payload capacity may take on various other values in other embodiments.

In this embodiment, the tracked utility vehicle 10 comprises a chassis 12, a power plant 14, a plurality of track assemblies 16₁, 16₂, and an operator cabin 20. The vehicle 10 has a longitudinal axis 59 defining a longitudinal direction of the vehicle 10 (i.e., a direction generally parallel to its longitudinal axis 59) and transversal directions (i.e., directions transverse to its longitudinal axis 59), including a widthwise direction (i.e., a lateral direction generally perpendicular to its longitudinal axis 59). The vehicle 10 also has a height direction which is normal to both its longitudinal direction and its widthwise direction.

a) Power plant

The power plant 14 generates power to move the tracked utility vehicle 10. To that end, the power plant 14 comprises a prime mover 17. For example, the prime mover 17 may comprise an internal combustion engine and/or one or more other types of motors (e.g., electric motors, etc.) for generating motive power to move the vehicle 10.

25

The power plant 14 is in a driving relationship with each of the track assemblies 16₁, 16₂. That is, power derived from the power plant 14 is transmitted to each of the track assemblies 16₁, 16₂ in order to drive the track assemblies 16₁, 16₂. In this embodiment, with additional reference to Figure 33, power from the power plant 14 is transmitted to the track assemblies 16₁, 16₂ via a hydraulic drive system 21. For instance, in this example, the hydraulic drive system 21

30

comprises, for each of the track assemblies 16₁, 16₂, a hydraulic pump 26 driven by the prime mover 17 and connected to a hydraulic motor (not shown) which drives that track assembly. Power from the power plant 14 may be transmitted to the track assemblies 16₁, 16₂ in various other ways in other embodiments.

5

In this embodiment, the power plant 14 includes a housing 46 which houses the prime mover 17 and other components of the power plant 14. More particularly, in this embodiment, the housing 46 houses: hydraulic components including each hydraulic pump 26 of the hydraulic drive system 21 and a hydraulic fluid
10 reservoir; a cooling system for cooling the prime mover 17 and hydraulic fluid of the hydraulic drive system 21; batteries; components of an exhaust system; pipes; and cables. Other components of the power plant 14 may be housed in the housing 46 in other embodiments.

15 The housing 46 and the components of the power plant 14 that it houses are mounted on top of the chassis 12. More particularly, in this embodiment, the housing 46 comprises a back housing portion 47₁ which houses a first portion of the power plant 14 and is located above the chassis 12 behind the operator cabin 20 and a side housing portion 47₂ which houses a second portion of the power
20 plant 14 and is located above the chassis 12 on a right side of the operator cabin 20. Thus, in this embodiment, the housing 46 has a generally L-shaped configuration that extends behind and next to the operator cabin 20, with the back housing portion 47₁ being elongated in the widthwise direction of the vehicle 10 and the side housing portion 47₂ being elongated in the longitudinal direction
25 of the vehicle 10.

Mounting of the housing 46 and the components of the power plant 14 that it houses above the chassis 12 may facilitate installation and servicing of the power plant 14. For example, maintenance or other servicing activities may be
30 performed by accessing components of the power plant 14 without being obstructed by the work equipment 41.

Also, components of the power plant 14, including the prime mover 17, the hydraulic pumps of the hydraulic drive system 21, and the housing 46, may be secured to one another to constitute a "power plant module" that can be installed
5 on and removable from the chassis 12 together as a unit. This may allow the tracked utility vehicle 10 to be easily equipped with a particular one of a plurality of different power plant modules during manufacturing of the vehicle 10 depending on an application or environment in which the vehicle 10 will be used. For example, in some embodiments, the plurality of different power plant
10 modules may comprise different types of prime movers. For instance, in some cases, the different types of prime movers may be different types of internal combustion engines, such as different types of engines that conform to requirements of different engine tiers (e.g., an engine conforming to requirements of a T3 engine tier and an engine conforming to requirements of a T4 engine
15 tier). In such examples of implementation, a controller controlling the prime mover 17 (e.g., an engine control unit (ECU) may comprise software that can control the different types of engines and receives an input indicating a particular type of engine to which the prime mover 17 corresponds to control it accordingly.

20 Furthermore, mounting of the housing 46 and the components of the power plant 14 that it houses above the chassis 12 may allow the height H_v of the tracked utility vehicle 10 to be kept small. This may be beneficial in various cases.

For example, in this embodiment, the operator cabin 20 can seat two individuals
25 (i.e., can comprise two seats) as further discussed later on, and the tracked utility vehicle 10 carrying the work equipment 41 can travel on a public road infrastructure. The vehicle 10 may travel on the public road infrastructure by self-propulsion or by being transported on another vehicle (e.g., on a flatbed truck). The vehicle 10 may therefore respect a vehicle height limit (i.e., a maximum
30 vehicle height allowable) for travel on the public road infrastructure. The vehicle height limit is normally set by a government responsible for the public road

infrastructure. For example, in some cases, the vehicle height limit for travel on the public road infrastructure may be between 13.5 feet (4.1 m) and 14 feet (4.3 m). The vehicle height limit for travel on the public road infrastructure may have any other suitable value in other cases. An overall height H_{v-o} of the vehicle 10, measured with the work equipment 41 in a retracted nonworking state, may thus be designed taking into account the vehicle height limit and a height of a trailer on which the vehicle 10 may be transported on the public road infrastructure. For example, if a trailer having a height of 24 inches is expected to be used for transporting the vehicle 10, the overall height H_{v-o} of the vehicle 10 may be no more than 11.5 feet (3.5 m) if the vehicle height limit is 13.5 feet or no more than 12 feet (3.7 m) if the vehicle height limit is 14 feet. As another example, if a trailer having a height of 18 inches is expected to be used for transporting the vehicle 10, the overall height H_{v-o} of the vehicle 10 may be no more than 12 feet if the vehicle height limit is 13.5 feet or no more than 12.5 feet if the vehicle height limit is 14 feet. Thus, in various examples, the overall height H_{v-o} of the vehicle 10 may be no more than 12.5 feet, in some cases no more than 12 feet, and in some cases no more than 11.5 feet.

More particularly, in this embodiment, when the work equipment 41 is in a retracted nonworking state (i.e., a state in which it is retracted onto the vehicle 10 and not performing any work operation, as opposed to an extended working state in which it is extended outwardly from the vehicle 10 to perform a work operation), the work equipment 41 is arranged such that it extends frontward in the longitudinal direction of the vehicle 10 beyond a rear side 114 of the operator cabin 20. In this example of implementation, the work equipment 41 extends frontward in the longitudinal direction of the vehicle 10 beyond a front side 112 of the operator cabin 20, next to a right side 116₂ of the operator cabin 20, above the side housing portion 47₂. The work equipment 41 also extends above a roof 118 of the operator cabin 20. Mounting part of the power plant 14, including the prime mover 17, on top of the chassis 12 and behind the operator cabin 20 (e.g., as opposed to within an internal space or "tub" defined by the chassis 12) allows

the operator cabin 20, which can comprise two seats, to be low enough for installing the work equipment 41 in this manner. For example, in some embodiments, the height H_v of the vehicle 10 to the roof 118 of the operator cabin 20 may be no more than 2.8 m, in some cases no more than 2.7 m, and in
5 some cases no more than 2.6 m. For instance, in this embodiment, the height H_v of the vehicle 10 may be about 2.5 m.

As another example, the tracked utility vehicle 10, without the work equipment 41 installed thereon, may fit in a closed shipping container for transport (e.g.,
10 overseas). For instance, in some examples, a maximum height for a shipping container may be no more than 3 m, in some cases no more than 2.8 m, and in some cases no more than 2.6 m, and the vehicle 10 may fit in that shipping container.

15 As yet another example, keeping the height H_v of the tracked utility vehicle 10 small may permit a vertical distance between a top of the operator cabin 20 and the chassis 12 to be identical or similar to a corresponding distance in trucks to allow work equipment such as the work equipment 41 possibly designed primarily for mounting on trucks to be easily mountable on the vehicle 10.

20

In addition to generating motive power to propel the tracked utility vehicle 10, in some embodiments, the power plant 14 may power the work equipment 41 carried by the vehicle 10. For instance, in some cases, the prime mover 17 may be used to supply power to the work equipment 41. In other cases, the power
25 plant 14 may comprise another prime mover for to supply power to the work equipment 41.

b) Track assemblies

30 The track assemblies 16₁, 16₂ are used to propel the tracked utility vehicle 10 on the ground. The track assembly 16₁ is on a first lateral side of the vehicle 10,

while the track assembly 16₂ is on a second lateral side of the vehicle 10. Each of the track assemblies 16₁, 16₂ supports a portion of a weight of the vehicle 10 in use. In this example, the track assemblies 16₁, 16₂ are similarly configured and are disposed symmetrically relative to the chassis 12 and thus the portion of the weight of the vehicle 10 supported by each of the track assemblies 16₁, 16₂ is about half of the weight of the vehicle 10. In other examples, the portion of the weight of the vehicle 10 supported by each of the track assemblies 16₁, 16₂ may be other than one-half of the weight of the vehicle 10.

With additional reference to Figures 14 to 18, in this embodiment, each track assembly 16_i comprises a plurality of wheels, which includes a drive wheel 24, an idler wheel 23, and a plurality of support wheels 28₁-28₄, and an endless track 22 disposed around the wheels 24, 23, 28₁-28₄. The track assembly 16_i has a length L_{ta}, a width W_{ta}, and a height H_{ta}. A longitudinal direction of the track assembly 16_i is generally parallel to the longitudinal direction of the tracked utility vehicle 10. The track assembly 16_i also has transversal directions, including a widthwise direction which is generally parallel to the widthwise direction of the tracked vehicle 10, and a height direction which is generally parallel to the height direction of the vehicle 10.

20

The endless track 22 engages the ground to provide traction. The endless track 22 is disposed around the wheels 24, 23, 28₁-28₄ and includes a top run 40 and a bottom run 42. The top run 40 and the bottom run 42 of the endless track 22 are generally parallel to one another and extend along the longitudinal direction of the tracked utility vehicle 10. The top run 40 of the endless track 22 is generally horizontal and has a length that is generally defined by the distance between the drive wheel 24 and the idler wheel 23. The bottom run 42 of the endless track 22 is that portion of the endless track 22 which is beneath the support wheels 28₁-28₄ and which engages the ground. The bottom run 42 of the endless track 22 has a length that is generally defined by the distance between a frontmost one of the support wheel 28₁-28₄, in this case, the support wheel 28₁,

30

and a rearmost one of the support wheel 28₁-28₄, in this case, the support wheel 28₄.

The drive wheel 24 is in a driven relationship with the power plant 14 to impart
5 movement of the endless track 22 in order to propel the vehicle 10 on the ground. The drive wheel 24 is rotatable about an axis of rotation which is transverse to the longitudinal direction of the vehicle 10 by power derived from the power plant 14 to impart movement of the endless track 22. In this embodiment, the drive wheel 24, which is located in a front region of the chassis
10 12, comprises a sprocket that engages the endless track 22. The drive wheel 24 may be configured in various other ways in other embodiments.

The idler wheel 23 does not convert power derived from the power plant 14 to motive force for movement of the endless track 22, but rather guides the endless
15 track 22 and maintains it under tension as it is driven by the drive wheel 24. The idler wheel 23 is rotatable about an axis of rotation which is transverse to the longitudinal direction of the tracked utility vehicle 10. In this embodiment, the idler wheel 23, which is located in a rear region of the chassis 12, may comprise a sprocket or any other type of wheel that engages the endless track 22.

20

The support wheels 28₁-28₄ are arranged in an in-line configuration extending along the longitudinal direction of tracked utility vehicle 10 and roll on the bottom run 42 of the endless track 22 as the vehicle 10 moves on the ground. The support wheels 28₁-28₄ do not convert power derived from the power plant 14 to
25 motive force for movement of the endless track 22, but rather support and distribute onto the ground via the endless track 22 the portion of the weight of the vehicle 10 that is supported by the track assembly 16_i. The support wheels 28₁-28₄ may also maintain the shape and position of the endless track 22, as well as keep the track 22 generally aligned with the general direction of vehicular
30 movement.

Each of the support wheels 28_1 - 28_4 occupies most of the height H_{ta} of the track assembly 16_i . That is, each of the support wheels 28_1 - 28_4 has a diameter D_{sw} corresponding to at least half, in some cases at least two-thirds, and in some cases at least three-quarters of the height H_{ta} of the track assembly 16_i . In this case, the diameter D_{sw} of each of the support wheels 28_1 - 28_4 corresponds to about 65% of the height H_{ta} of the track assembly 16_i . In some embodiments, the diameter D_{sw} of each of the support wheels 28_1 - 28_4 may be such that the top run 40 of the endless track 22 can contact the support wheels 28_1 - 28_4 in use. In other embodiments, the support wheels 28_1 - 28_4 may be made smaller such that there is no contact between the top run 40 of the endless track 22 and the support wheels 28_1 - 28_4 in use.

The support wheels 28_1 - 28_4 are carried by a plurality of wheel-carrying assemblies 50_1 , 50_2 of the track assembly 16_i . Each of the wheel-carrying assemblies 50_1 , 50_2 carries at least two of the support wheels 28_1 - 28_4 and, since it is an assembly carrying wheels, will be referred to as a "bogie". More particularly, in this embodiment, the bogie 50_1 carries the support wheels 28_1 , 28_2 and the bogie 50_2 carries the support wheels 28_3 , 28_4 .

The bogie 50_1 comprises a link 70 interconnecting the support wheels 28_1 , 28_2 and pivotable relative to the chassis 12 about a pivot 71 which defines a pivot axis. The link 70 is a connecting structure that may have any suitable form (e.g., a single member or a plurality of members connected to one another by one or more fasteners, welding, etc.). The support wheels 28_1 , 28_2 are rotatably mounted to the link 70 via respective axles which define respective axes of rotation of the support wheels 28_1 , 28_2 . In this embodiment, the pivot axis of the link 70 lies closer to the axis of rotation of the support wheel 28_1 than that of the support wheel 28_2 and above the axes of rotation of the support wheels 28_1 , 28_2 . The pivot axis of the link 70 and the axes of rotation of the support wheels 28_1 , 28_2 may be positioned differently in relation to one another in other embodiments (e.g., the pivot axis of the link 70 may lie equidistant between the axes of rotation

of the support wheels 28₁, 28₂). The bogie 50₂ is configured similarly to the bogie 50₁ and will thus not be further discussed.

In this embodiment, each support wheel 28_i facilitates installation of the endless track 22. More particularly, in this embodiment, with additional reference to Figures 35 and 36, the support wheel 28_i comprises a first support wheel member 35₁ and a second support wheel member 35₂ which each have a circumference of the support wheel 28_i, are rotatable about the axle of support wheel 28_i, and are installable in and removable from the track assembly 16_i separately from one another. The support wheel member 35₁, which is farthest from a centerline of the vehicle 1, can be viewed as an "outboard" support wheel member while the support wheel member 35₂, which is nearest to the centerline of the vehicle 10, can be viewed as an "inboard" support wheel member. The endless track 22 can be installed while the inboard support wheel member 35₂ is in place but before placement of the outboard support wheel member 35₁, which is put in place after installation of the endless track 22. This makes it easier to install or replace the endless track 22.

More particularly, in this embodiment, the outboard and inboard support wheel members 35₁, 35₂ are secured to a hub 36 by fasteners 48₁-48_F (e.g., bolts and nuts). The hub 36 includes an opening 52 that receives the axle of the support wheel 28_i. In this embodiment, bearings (e.g., tapered bearings) are positioned in the opening 52 of the hub 36 and receive the axle of the support wheel 28_i. A cap 54 covers an end of the axle of the support wheel 28_i. The axle of the support wheel 28_i extends and is fixed to the link 70 of the bogie 50_i. In this case, a fastener 56 (e.g., a bolt) extends transversally to the axle of the support wheel 28_i and through the link 70 to fix the axle to the link 70. The outboard and inboard support wheel members 35₁, 35₂ may be mounted in any other suitable way in other embodiments.

As further discussed later, in this embodiment, the outboard and inboard support wheel members 35₁, 35₂ define in between them a guiding space 38 for receiving a wheel guide of the endless track 22 to guide the endless track 22 as it moves around the wheels 24, 23, 28₁-28₄.

5

In this embodiment, each support wheel member 35_i comprises a rim portion 57, a hub portion 58, and a radially-extending portion 61 therebetween. The rim portion 57 is in rolling contact with the bottom run 42 of the endless track 22. The hub portion 58 is a central portion of the support wheel member 35_i which
10 receives the axle of the support wheel 28_i. In this example, the hub portion 58 engages the hub 36 and is secured thereto by the fasteners 48₁-48_F. The radially-extending portion 61 extends from the rim portion 57 to the hub portion 58. In this example, the radially-extending portion 61 comprises a plurality of spokes 63₁-63₈ and a plurality of interspoke openings 67₁-67₈ between adjacent
15 ones of the spokes 63₁-63₈.

More particularly, in this embodiment, the rim portion 57, the hub portion 58, and the radially-extending portion 61 are configured such that the support wheel member 35_i is a concave support wheel member defining a concavity 69. Each of
20 the spokes 63₁-63₈ tapers radially towards the hub portion 58. The support wheel member 35_i may have any other suitable shape in other embodiments.

In this example of implementation, the support wheel member 35_i is a metallic support wheel member (e.g., a steel support wheel member) that has been cast
25 into shape. The support wheel member 35_i may be made of any other suitable material and/or using any other suitable manufacturing process in other examples of implementation.

The support wheels 28₁-28₄ may be configured in various other ways in other
30 embodiments. For example, in other embodiments, a support wheel member 35_i of a support wheel 28_i may comprise a rubber or other elastomeric covering on

its rim portion 57 to be in rolling contact with the bottom run 42 of the endless track 22. As another example, in other embodiments, a support wheel 28_i may be a unitary support wheel which does not comprise separate outboard and inboard support wheel members as discussed above. For instance, in some
5 embodiments, as shown in Figures 39 and 40, a support wheel 28_i may be a unitary support wheel which comprises a metallic wheel body 93 on which is mounted a tire 91 that is in rolling contact with the bottom run 42 of the endless track 22.

10 In this embodiment, as shown in Figures 3, 9, 15 and 20, the idler wheel 23 overlaps the rearmost support wheel 28₄ in the longitudinal direction of the tracked utility vehicle 10. This may be beneficial for stability of the vehicle 10 when the work equipment 41 applies a significant load in a rear end region of the chassis 12 (e.g., when a drill, dump bucket or other piece of equipment is raised
15 in the rear end region of the chassis 12). The longitudinal overlap between the idler wheel 23 and the support wheel 28₄ allows the longitudinal distance between the pivot axis defined by the pivot 71 of the bogie 50₂ and the rear end region of the chassis 12 to be less than if there was no longitudinal overlap between the idler wheel 23 and the support wheel 28₄. This smaller longitudinal
20 distance results in a smaller moment arm and, consequently, a smaller moment associated with the load applied by the work equipment 41 in the rear end region of the chassis 12.

More particularly, in this embodiment, the idler wheel 23 longitudinally overlaps
25 the support wheel 28₄ by being located in the guiding space 38 between the inboard and outboard wheel members 35₁, 35₂ of the support wheel 28₄. The longitudinal overlap between the idler wheel 23 and the support wheel 28₄ may be achieved in various ways in other embodiments. For example, in
30 embodiments in which the support wheel 28₄ is a unitary support wheel which does not comprise separate outboard and inboard support wheel members (e.g., as shown in Figures 39 and 40), the idler wheel 23 may comprise an inboard

idler wheel member and an outboard idler wheel member that define a space therebetween in which the support wheel 28₄ may be located such that the idler wheel 23 and the support wheel 28₄ longitudinally overlap.

- 5 The endless track 22 engages the ground to provide traction to the tracked utility vehicle 10. More particularly, as the drive wheel 24 is rotated by power derived from the power plant 14, the drive wheel 24 imparts motion to the endless track 22 for traction of the vehicle 10 on the ground. The endless track 22 has an inner side 32 facing the wheels 24, 23, 28₁-28₄ and a ground-engaging outer side 33,
10 opposite the inner side 32, for engaging the ground.

In this embodiment, as shown in Figures 29 and 30, the endless track 22 comprises an elastomeric body 37 underlying its inner side 32 and its ground-engaging outer side 33. The body 37 is elastomeric in that it comprises
15 elastomeric material which allows the track 22 to elastically change in shape as it is in motion around the wheels 24, 23, 28₁-28₄. The elastomeric material of the body 37 can be any polymeric material with suitable elasticity. In this embodiment, the elastomeric material includes rubber. Various rubber compounds may be used and, in some cases, different rubber compounds may
20 be present in different areas of the track 22. In other embodiments, the elastomeric material may include another elastomer in addition to or instead of rubber (e.g., polyurethane elastomer).

A plurality of cores 21₁-21_C are embedded in the elastomeric material of the body
25 37 of the endless track 22, spaced apart along the longitudinal direction of the track 22, and extending transversally to the longitudinal direction of the track 22 to impart transverse rigidity to the track 22. The cores 21₁-21_C are made of rigid material. For instance, in this embodiment, the cores 21₁-21_C are metallic (e.g., steel) cores. This type of track can thus sometimes be referred to as a "metal-
30 embedded rubber track" (MERT).

The cores 21₁-21_C interact with the wheels 24, 23, 28₁-28₄ to impart and/or guide motion of the endless track 22. For example, in this embodiment, the track 22 has a plurality of drive openings 19₁-19_O for receiving teeth of the drive wheel 24 such that the drive wheel 24 can engage parts of the track 22 where are located
5 individual ones of the cores 21₁-21_C in order to apply motive force to the track 22. The cores 21₁-21_C also guide motion of the track 22 as it is driven by the drive wheel 24. More particularly, each core 21_i comprises a pair of wings 29₁, 29₂ and a wheel guide 25 between the wings 29₁, 29₂. The wheel guide 25 comprises at least one, in this case, two guide projections 36₁, 36₂ projecting on the inner side
10 32 of the endless track 22. In this embodiment, when its teeth enter the drive openings 19₁-19_O of the track 22, the drive wheel 24 engages the wheel guide 25 of the core 21_i between the guide projections 36₁, 36₂ to drive the track 22, while the guide projections 36₁, 36₂ pass in the guiding space 38 defined by each of the support wheels 28₁-28₄ in order to guide the track 22 relative to the support
15 wheels 28₁-28₄.

One or more reinforcements may be embedded in the elastomeric material of the body 37 of the endless track 22. For instance, a reinforcement may be a layer of reinforcing cables 43₁-43_R that are adjacent to one another and that extend in the
20 longitudinal direction of the track 22 to enhance strength in tension of the track 22 along its longitudinal direction. In some cases, a reinforcing cable 43_i may be a cord or wire rope including a plurality of strands or wires. In other cases, a reinforcing cable 43_i may be another type of cable and may be made of any material suitably flexible longitudinally (e.g., fibers or wires of metal, plastic or
25 composite material). Various other types of reinforcements may be provided in other embodiments.

The ground-engaging outer side 33 of the endless track 22 comprises a tread pattern to enhance traction on the ground. The tread pattern comprises a plurality
30 of traction projections 49₁-49_T, which can be referred to as "traction lugs", spaced

apart along the longitudinal direction of the track 22 and engaging the ground to enhance traction.

The inner side 32 of the endless track 22 comprises the guide projections 36₁, 36₂ of each of the cores 21₁-21_C. In addition, the inner side 32 of the track 22 comprises rolling surfaces 39₁, 39₂ on which the support wheels 28₁-28₄ roll to apply the track 22 onto the ground.

The endless track 22 may be configured in various other ways in other embodiments.

For example, in some embodiments, as shown in Figures 31 and 32, the endless track 22 may comprise a pair of belts 30₁, 30₂ spaced apart to accommodate the wheels 24, 23, 28₁-28₄ and a series of cross-links 31₁-31_N distributed longitudinally along the track 22 and extending transversally to interconnect the belts 30₁, 30₂.

Each belt 30_i is elastomeric in that it comprises rubber and/or other elastomeric material. The belt 30_i may comprise one or more reinforcements such as a layer of cables embedded in its rubber and/or other elastomeric material. In this case, the belt 30_i is made up of a series of belt sections connected to one another. In other cases, the belt 30_i may be a one-piece belt.

The cross-links 31₁-31_N interconnect the belts 30₁, 30₂ and interact with the wheels 24, 23, 28₁-28₄ as the endless track 22 moves around these wheels. For example, in this embodiment, as the drive wheel 24 rotates, individual ones of the cross-links 31₁-31_N engage recesses between the teeth of the drive wheel 24, thereby causing the track 22 to be driven. Also, the cross-links 31₁-31_N help to guide motion of the track 22 by contacting the support wheels 28₁-28₄. More particularly, each cross-link 31_i comprises a wheel guide 44 including a pair of guide projections 45₁, 45₂ projecting on the inner side 32 of the endless track 22.

In this embodiment, when its teeth enter gaps between the cross-links 31_1 - 31_N , the drive wheel 24 engages the wheel guide 44 of the cross-links 28_1 - 28_4 between the guide projections 45_1 , 45_2 to drive the track 22, while the support wheels 28_1 - 28_4 pass between the guide projections 45_1 , 45_2 in order to guide the track 22 relative to the support wheels 28_1 - 28_4 . In such embodiments, each of the support wheels 28_1 - 28_4 may be a unitary support wheel as shown in Figures 39 and 40.

Each cross-link 31_i comprises an elongated member 73 extending transversally to the longitudinal direction of the endless track 22 to interconnect the belts 30_1 , 30_2 . The elongated member 73 is made of rigid material, in this case metallic material (e.g., steel). The elongated member 73 is secured to the belts 30_1 , 30_2 by fasteners which extend through the elongated member 73, the belts 30_1 , 30_2 , and backing plates 75_1 , 75_2 disposed on the inner side 32 of the track 22. In this embodiment, the cross-link 31_1 comprises a polymeric sole 77 mounted to the elongated member 73. The polymeric sole 77 can be used when the vehicle 10 is to travel on a hard surface (e.g., a paved surface) in order to minimize an impact of the cross-link 31_i on that surface. In other embodiments, the cross-link 31_i may not include any polymeric sole.

20

As another example, in some embodiments, the endless track 22 may comprises an endless elastomeric body underlying its inner side 32 and its ground-engaging outer side 33, similar to the elastomeric body 37 discussed above in respect of Figures 29 and 30, but without cores embedded in the elastomeric body (e.g., an “all-rubber” track).

25

In this embodiment, the track assembly 16_i comprises a plurality of wheel mounting structures for mounting the wheels 24, 23, 28_1 - 28_4 to the chassis 12, including a drive wheel mounting structure 88_1 , a pair of support wheel mounting structures 88_2 , 88_3 , and an idler wheel mounting structure 88_4 , which are secured to the chassis 12 and spaced apart in the longitudinal direction of the tracked

30

utility vehicle 10. Each of the wheel mounting structures 88₁-88₄ supports at least one of the wheels 24, 23, 28₁-28₄. Specifically, in this case, the drive wheel mounting structure 88₁ supports the drive wheel 24, the support wheel mounting structures 88₂, 88₃ support the bogies 50₁, 50₂ carrying the support wheels 28₁-
5 28₄, and the idler wheel mounting structure 88₄ supports the idler wheel 23.

The track assembly 16_i comprises a track tensioner 85 for maintaining tension of the endless track 22. In this embodiment, the track tensioner 85 is connected between the support wheel mounting structure 88₃ and axle of the idler wheel 23
10 to urge the idler wheel 23 in a direction to maintain the tension of the endless track 22. Also, in this embodiment, the track tensioner 68 is a fluidic tensioning system, e.g., a hydraulic or pneumatic tensioning system, which comprises a piston-cylinder tensioning actuator 79 connected to a fluid reservoir. In this example of implementation, the tensioning actuator 79 is a hydraulic piston-
15 cylinder actuator.

More particularly, in this embodiment, with additional reference to Figures 37 and 38, the tensioning actuator 79 is connected to the support wheel mounting structure 88₃ and to an idler wheel support arm 83 which is pivotable about an
20 axle 89 that is fixed to the idler wheel mounting structure 88₄. The axle of the idler wheel 23 is fixed to the idler wheel support arm 83. The tensioning actuator 79 can apply the tension in the track 22 by extending or retracting to turn the idler wheel support arm 83 about the axle 89 and thus move the idler wheel 23 further or closer to the drive wheel 24.

25

In this embodiment, the track tensioner 85 becomes active when the tracked utility vehicle 10 is started. That is, the track tensioner 85 applies a force to generate the tension in the endless track 22 when the prime mover 17 of the vehicle 10 is started.

30

With additional reference to Figure 48, in this embodiment, the track tensioner 85 is hydraulically connected to the hydraulic drive system 21 of the vehicle 10 such that the tension in the endless track 22 is generated by the hydraulic fluid of the hydraulic drive system 21. The tensioning actuator 79 is in hydraulic
5 communication with the hydraulic drive system 21 such that, when the prime mover 17 is started and starts to power the hydraulic drive system 21, the hydraulic fluid of the hydraulic drive system 21 acts on the tensioning actuator 79, which applies a force to generate the tension in the endless track 22.

10 More particularly, as shown in Figure 49, in this embodiment, the hydraulic drive system 21 comprises a charge pump 27 hydraulically connected to the tensioning actuator 79 via a track tensioner hydraulic circuit 13.

The charge pump 27 is operative to maintain a minimum pressure in the
15 hydraulic drive system 21 when the vehicle 10 is turned on. For example, in some embodiments, the minimum pressure may be at least 300 psi, in some cases at least 325 psi, and in some cases at least 350 psi. For instance, in this embodiment, the minimum pressure is about 375 psi. The minimum pressure in the hydraulic drive system 21 may have any other suitable value in other
20 embodiments. In this example of implementation, the charge pump 27 is a fixed displacement pump. For instance, the charge pump 27 may be a gear pump, a gerotor pump or any other suitable type of pump.

The hydraulic fluid from the charge pump 27 causes the tensioning actuator 79 to
25 apply a force to generate the tension in the endless track 22. This force corresponds to the pressure of the hydraulic fluid in the tensioning actuator 79 multiplied by a cross-sectional area of the piston-cylinder arrangement of the tensioning actuator 79. For example, in some embodiments, the force may be at least 5000 pounds, in some cases at least 6000 pounds, in some cases at least
30 7000 pounds, and in some cases even more (e.g., up to 10000 pounds). For instance, in this embodiment, the piston-cylinder arrangement of the tensioning

actuator 79 may have an internal diameter of 5 inches such that its internal cross-sectional area is approximately 19.6 square inches and, at the minimum pressure of 375 psi, the force applied by the tensioning actuator 79 is about 7363 pounds. The force may have any other value in other embodiments.

5

The track tensioner hydraulic circuit 13 regulates flow of hydraulic fluid between the charge pump 27 and the tensioning actuator 79. For example, in this embodiment, the track tensioner hydraulic circuit 13 limits a maximum pressure that is applicable to the tensioning actuator 79. This may be useful, for instance,
10 to prevent situations (e.g., hard debris becoming stuck between the drive wheel 24 and the endless track 22) where the tension in the endless track 22 would become too high. More particularly, with additional reference to Figure 50, in this embodiment, the track tensioner hydraulic circuit 13 comprises a pressure limiter 98 to limit the maximum pressure that is applicable to the tensioning actuator 79.
15 In this example of implementation, the pressure limiter 79 comprises a valve 97 (e.g., a relief valve) which opens at a preset pressure which corresponds to the maximum pressure that is not to be exceeded in the tensioning actuator 97. For example, in some embodiments, the preset pressure at which the valve 97 opens, which corresponds to the maximum pressure allowable in the tensioning
20 actuator 79, may be at least 1000 psi, in some cases at least 1200 psi, in some cases at least 1400 psi, and in some cases even more. For instance, in this embodiment, the preset pressure at which the valve 97 opens is 1400 psi such that the pressure in the tensioning actuator 79 can vary between 375 psi and 1400 psi. The maximum pressure may have any other suitable value in other
25 embodiments

In this embodiment, the track tensioner hydraulic circuit 13 is arranged such that, if the vehicle 10 is momentarily turned off (e.g., for a few minutes) the tension in the endless track 22 is maintained by the tensioning cylinder 79. For example, in
30 this embodiment, the track tensioner hydraulic circuit 13 comprises a check valve 123 arranged for that purpose.

Although in this embodiment the track tensioner 85 is hydraulically connected to the hydraulic drive system 21 of the vehicle 10 via the charge pump 27 such that the tension in the endless track 22 is generated when the prime mover 17 is started and starts to power the hydraulic drive system 21, the track tensioner 85 may be connected in other ways such that it would become active when the vehicle 10 is started (e.g., there may be a dedicated pump for the track tensioner 85).

The track assembly 16_i may be configured in various other ways in other embodiments. For example, although in this embodiment it comprises four (4) support wheels 28₁-28₄, the track assembly 16_i may comprise more than four support wheels (e.g., five (5) support wheels) in other embodiments. As another example, while in this embodiment the drive wheel 24 is located in a front region of the chassis 12 and the idler wheel 23 is located in a rear region of the chassis 12, this may be reversed in other embodiments such that the drive wheel 24 is located in a rear region of the chassis 12 and the idler wheel 23 of the track assembly 16_i is located in a front region of the chassis 12. As yet another example, while in this embodiment the idler wheel 23 is not in a driven relationship with the power plant 14, in other embodiments, the idler wheel 23 may be replaced by another drive wheel that is in a driven relationship with the power plant 14.

c) Operator cabin

25

The operator cabin 20 is where an operator sits and controls the tracked utility vehicle 10. In this embodiment, the operator cabin 20 comprises a front side 112, a rear side 114, a pair of lateral sides 116₁, 116₂, a roof 118, and a floor 120. The lateral side 116₁ of the operator cabin 20 defines an access opening 122 that can be closed by a door 124 and that allows the operator to enter or exit the operator

30

cabin 20. A plurality of windows 126₁-126_w are provided to allow the operator to see outside of the vehicle 10.

With additional reference to Figure 41, the operator cabin 20 comprises a seating
5 area 132 and a user interface 130. As further discussed later on, in this embodiment, the operator cabin 20 is configurable in a plurality of cabin configurations in which the seating area 132 and the user interface 130 are configured differently.

10 The user interface 130 enables the operator to interact with the tracked utility vehicle 10. For example, the user interface 130 comprises controls allowing the operator to move the tracked utility vehicle 10 on the ground. In some cases, the user interface 130 may also include controls for controlling the work equipment
41 carried by the vehicle 10. The user interface 130 comprises an input portion to
15 allow the operator to input commands for execution by the vehicle 10 and an output portion to convey information to the operator.

In this embodiment, the input portion of the user interface 130 comprises an accelerator 133, a steering device 134, a transmission state selector 135, a
20 starter switch 137, and a control lever 138. More particularly:

- The accelerator 133 allows the operator to control a speed of the vehicle 10 on the ground. In this example, the accelerator 133 comprises a speed pedal operated by a foot of the operator. The accelerator 133 may be implemented
25 in other ways in other examples (e.g., a hand-operated accelerator).
- The steering device 134 allows the operator to steer the vehicle 10 on the ground. In this example, the steering device 134 comprises a steering wheel that is rotatable relative to a steering column 144 about a steering axis. In
30 addition to the steering wheel 134, in this example of implementation, the steering column 144 supports the transmission state selector 135, the starter

switch 137, and the control lever 138. The steering device 134 may be implemented in other ways in other embodiments (e.g., a joystick).

- The transmission state selector 135 allows the operator to control a state of power transmission to the track assemblies 16₁, 16₂. For instance, in this example, the transmission state selector 135 comprises a proportional front-neutral-reverse selector to control whether power is transmitted to the track assemblies 16₁, 16₂ to move in a forward or reverse direction or not transmitted to the track assemblies 16₁, 16₂. The transmission state selector 135 may be implemented in other ways in other embodiments.
- The starter switch 137 allows the operator to start the prime mover 17 of the vehicle 10. For instance, in this example, the starter switch 137 comprises a key-receiving unit to receive a key to start the prime mover 17 of the vehicle 10. The starter switch 137 may be implemented in other ways in other embodiments (e.g., a start button, a code entry device, a biometric authentication device, etc.).
- The control lever 138 allows the operator to control various devices of the vehicle 10. For instance, in this example, the control lever 138 includes a wiper control which allows the operator to control a wiper 140 of the front window 126₁ of the operator cabin 20, a washer fluid control which allows the operator to control outflow of washer fluid from a washer fluid nozzle onto the front window 126₁, and a turning indicator 141 control which allows the operator to control a turning indicator of the vehicle 10. The control lever 138 may include any other suitable control in other examples.

The input portion of the user interface 130 may comprise any other input device (e.g., a set of buttons, a joystick, a trackball, etc.) in other embodiments.

0/10/-33

In this embodiment, the output portion of the user interface 130 comprises a display 140 to visually convey information to the operator. The display 140 may be any suitable type of electronic display (e.g., a liquid-crystal display (LCD), etc.). Various information can be conveyed to the operator on the display 140.

5 For example, in some embodiments, the display 140 may implement an instrument panel that provides: a speedometer indicator which conveys information indicative of the speed at which the vehicle 10 is moving as measured by a speedometer of the vehicle 10; a tachometer indicator which conveys information indicative of the speed at which the prime mover 17 is

10 running as measured by a tachometer of the vehicle 10; an odometer indicator which conveys information indicative of a distance traveled by the vehicle 10 as measured by an odometer of the vehicle 10; a fuel gauge indicator which conveys information indicative of a quantity of fuel remaining in the vehicle 10; and/or any other indicator conveying information to the user. Each of the

15 speedometer indicator, the tachometer indicator, the odometer indicator, and/or other indicators may comprise a digital numerical reading, a digital dial, a digital bar graph, a digital symbol, and/or any other element displayable on the display 140 to convey information to the operator.

20 The output portion of the user interface 130 may comprise any other output device (e.g., one or more mechanical dials (e.g., a speedometer dial, a fuel gauge dial, etc.) or other mechanical indicators (e.g., a mechanical odometer); one or more light indicators (e.g., low fuel light indicator, etc.); a speaker; etc.) in other embodiments.

25

The user interface 130 is connected to other components of the tracked utility vehicle 10 to cause execution of commands provided by the operator and to present information to the operator. More particularly, in this embodiment, there are a plurality of connections 142_1 - 142_C between the user interface 130 and

30 other components of the vehicle 10. These connections 142_1 - 142_C may comprise one or more mechanical links, wires, cables, wireless links, and/or other

connecting elements depending on how the user interface 130 is connected to other components of the vehicle 10 (e.g., via mechanical control systems and/or via electromechanical systems (e.g., "drive-by-wire" systems)). For example, with additional reference to Figure 45, in this embodiment:

5

- The connection 142₁ is between the speed pedal 133 and the prime mover 17. For instance, in this embodiment, the connection 142₁ may comprise a wire connected to a pedal position sensor (e.g., comprising a potentiometer) for sensing a position of the speed pedal 133 and transmitting a signal
10 indicative of this position to a powertrain controller 147 controlling the prime mover 17 (e.g., an engine control unit (ECU)). In other embodiments, the connection 142₁ may comprise a mechanical link between the speed pedal 133 and a throttle for the prime mover 17.
- 15 - The connection 142₂ is between the steering wheel 134 and a steering controller 143 which controls a steering direction of the vehicle 10 by controlling the hydraulic motors of the hydraulic drive system 21 to cause the endless track 22 of one of the track assemblies 16₁, 16₂ to move faster than the endless track 22 of the other one of the track assemblies 16₁, 16₂ when
20 the vehicle 10 turns. For instance, in this embodiment, the connection 142₂ comprises a steering device angle sensor for sensing an angle in which the steering wheel 134 is positioned and transmitting a signal indicative of this angle to the steering controller 143.
- 25 - The connection 142₃ is between the proportional front-neutral-reverse selector 135 and the powertrain controller 147. For instance, in this embodiment, the connection 142₃ may comprise a wire transmitting a signal indicative of the state of the selector 135 to the powertrain controller 147.

- The connection 142₄ is between the starter switch 137 and the prime mover 17. For instance, in this embodiment, the connection 142₄ may comprise a wire between the starter switch 137 and the powertrain controller 147.
- 5 - The connections 142₅-142_C are between the control lever 138 and the wiper 140, the washer fluid nozzle, the turning indicator 141 and/or any other device of the vehicle 10 which can be controlled via inputs at the control lever 138. For instance, in this embodiment, the connections 142₆-142_N may comprise wires between the control lever 138 and an outside functionality controller 149
10 of the vehicle 10 which sends signals to these devices of the vehicle 10 to control these devices. In other embodiments, the connections 142₆-142_N may comprise wires directly connected to these devices.

Controllers of the tracked utility vehicle 10, such as the powertrain controller 147,
15 the steering controller 143 and the outside functionality controller 149, with which the user interface 130 may interact may be implemented in various manners. A controller comprises suitable hardware and/or software (e.g., firmware) implementing: an interface for receiving and transmitting signals to other components of the vehicle 10 to which it is connected; a processing portion
20 comprising one or more processors for performing processing operations, where a processor may be a general-purpose processor executing program code stored in the controller or a specific-purpose processor comprising one or more preprogrammed hardware or firmware elements (e.g., application-specific integrated circuits (ASICs), electrically erasable programmable read-only
25 memories (EEPROMs), etc.); and a memory portion comprising one or more memories for storing program code executed by the processing portion and/or data used during operation of the processing portion, where a memory may be a semiconductor memory (e.g., read-only memory (ROM) and/or random-access memory (RAM)), a magnetic storage medium, an optical storage medium, and/or
30 any other suitable type of memory. In some embodiments, two (2) or more (e.g., all) controllers of the vehicle 10 may be physically distinct from one another and

may be connected to one another via a bus (e.g., a controller-area network (CAN) bus or other suitable bus). In other embodiments, two (2) or more (e.g., all) controllers of the vehicle 10 may be functional entities of a single physical control unit (e.g., a vehicle controller).

5

The seating area 132 comprises a seat 150 for the operator of the tracked utility vehicle 10. The seat 150, which will be referred to as an “operator seat”, is positioned relative to the user interface 130 to allow the operator to easily interact with the user interface 130.

10

As mentioned previously, in this embodiment, the operator cabin 20 is configurable into a plurality of cabin configurations in which the seating area 132 and the user interface 130 are configured differently. More particularly, in this embodiment, the plurality of cabin configurations in which the operator cabin can be configured includes a first cabin configuration, which is shown in Figures 41 and 42 and will be referred to as a “one-person cabin configuration”, and a second cabin configuration, which will be referred to as a “two-person cabin configuration” and is shown in Figures 43 and 44.

20 As shown in Figure 41, the operator cabin 20 can be configured in the one-person cabin configuration when only the operator is to sit therein. More particularly, in this embodiment, the operator seat 150 is a sole seat of the seating area 132 and is located in an operator seat position 176 which, in this example, is generally in a center of a width of an interior of the operator cabin 20.

25 Various devices of the user interface 130, including the steering wheel 134 and its steering column 144, the speed pedal 133, the front-neutral reverse selector 135, the starter switch 137, and the control lever 138, are also located in respective user device positions which, in this example, are generally in the center of the width of the interior of the operator cabin 20.

30

As shown in Figure 43, the operator cabin 20 can be configured in the two-person cabin configuration when the operator and a second person are to sit therein. More particularly, in this embodiment, the operator cabin 20 is sized such that it allows the second person, who will be referred to as a “passenger”, to sit in
5 the seating area 132 with the operator. To that end, the seating area 132 allows a second seat 152 to be provided for the passenger. The seat 152, which will be referred to as a “passenger seat”, is located adjacent to the operator seat 150 such that the operator and the passenger sit side-by-side.

10 The seating area 132 and the user interface 130 in the one-person cabin configuration are configured differently than in the two-person cabin configuration. More particularly, in this embodiment, the operator seat 150 and devices of the user interface 130 in the two-person cabin configuration are located in respective positions that are different from those in which they are
15 located in the one-person cabin configuration.

An operator seat position 177 of the operator seat 150 in the two-person cabin configuration is different from the operator seat position 176 of the operator seat 150 in the one-person cabin configuration. In this example, the operator seat
20 position 177 of the operator seat 150 in the two-person cabin configuration is displaced in the widthwise direction of the vehicle 10 such that the operator seat 150 is closer to the right side 116₂ of the operator cabin 20 in the two-person cabin configuration than in the one-person cabin configuration. The passenger seat 152 is located at a passenger seat position 178 that is between the left side
25 116₁ of the operator cabin 20 than the operator seat 150.

The seating area 132 thus defines a plurality of seat positions along the widthwise direction of the vehicle 10, including the operator seat position 176 in the one-person cabin configuration, the operator seat position 177 in the two-
30 person cabin configuration, and the passenger seat position 178 in the two-person cabin configuration. In this embodiment, the seating area 132 comprises

a seat support 151 for mounting the operator seat 150 in its operator seat positions 176, 177 in the one-person cabin configuration and the two-person cabin configuration and for mounting the passenger seat 152 in its passenger seat position 178 adjacent to the operator seat 150 in the two-person cabin configuration. More particularly, in this embodiment, the seat support 151 comprises mounting holes 154₁-154_H in the floor 120 of the operator cabin 20 to receive fasteners (e.g., bolts) for mounting the operator seat 150 or the passenger seat 152 to the seat support 151 (e.g., four bolts in four corners of the seat's base). In other embodiments, the seat support 151 may comprise mounting projections, mounting brackets, and/or other mounting structures to mount the operator seat 150 or the passenger seat 152 to the seat support 151. Also, in this embodiment, a seatbelt for the operator seat 150 remains the same in the one-person cabin configuration and the two-person cabin configuration, while an additional seatbelt is installed on the passenger's side in the two-person cabin configuration.

User device positions of devices of the user interface 130, including the steering wheel 134 and its steering column 144, the speed pedal 133, the front-neutral reverse selector 135, the starter switch 137, and the control lever 138, in the two-person cabin configuration are different from the user device positions of these devices in the one-person cabin configuration. In this example, the positions of the steering wheel 134 and its steering column 144, the speed pedal 133, the front-neutral reverse selector 135, the starter switch 137, and the control lever 138 in the two-person cabin configuration are displaced in the widthwise direction of the vehicle 10 such that these devices are closer to right side 116₂ of the operator cabin 20 in the two-person cabin configuration than in the one-person cabin configuration.

The operator cabin 20 comprises a user interface support 160 for mounting devices of the user interface 130, including the steering wheel 134 and its steering column 144, the speed pedal 133, the front-neutral reverse selector 135,

the starter switch 137, and the control lever 138, such that these devices are movable between the one-person cabin configuration and the two-person cabin configuration. More particularly, in this embodiment, the speed pedal 133 and the steering column 144, which supports the steering wheel 134, the front-neutral
5 reverse selector 135, the starter switch 137, and the control lever 138, are mounted to the user interface support 160 such that they are movable in the widthwise direction of the vehicle 10 to change the operator cabin 20 between the one-person cabin configuration and the two-person cabin configuration.

10 The user interface support 160 defines a plurality of steering device positions for the steering wheel 134 and its steering column 144 along the widthwise direction of the vehicle 10, including a central steering device position 161 in the one-person cabin configuration and a side steering device position 162 in the two-person cabin configuration. The user interface support 160 also defines a
15 plurality of accelerator positions for the speed pedal 133 along the widthwise direction of the vehicle 10, including a central accelerator position 163 in the one-person cabin configuration and a side accelerator position 164 in the two-person cabin configuration. In this embodiment, with additional reference to Figure 46, the user interface support 160 comprises mounting holes 167₁-167₂₀ for receiving
20 fasteners (e.g., bolts) to fasten the steering column 144 and the speed pedal 133 to the user interface support 160 in respective ones of their central and side steering device positions 161, 162 and central and side accelerator positions 163, 164 in the one-person cabin configuration and the two-person cabin configuration. In other embodiments, the user interface support 160 may
25 comprise mounting projections, mounting brackets, and/or other mounting structures to mount the steering column 144 and the speed pedal 133 to the user interface support 160.

More particularly, in this embodiment, the user interface support 160 comprises a
30 fixed support structure 165 and a movable support structure 166 that can be moved relative to the fixed support structure 165. The support structures 165,

166 define respective ones of the mounting holes 167₁-167₂₀ which can be aligned with one another to receive fasteners.

In this example of implementation, the fixed support structure 165 comprises a
5 fixed plate 169 which extends obliquely to a horizontal surface of the floor 120
and another fixed plate 170 which also extends obliquely to the horizontal
surface of the floor 120 but at a lesser angle than the fixed plate 169. The fixed
plates 169, 170 define the mounting holes 167₁-167₁₅. The movable support
structure 166 comprises a movable plate 171 and another movable plate 173
10 which respectively overlap the fixed plates 169, 170 and define the mounting
holes 167₁₆-167₂₀. The movable plate 171 also comprises a steering column
opening 172 through which wires from the steering column 144 extend and
mounting holes 175₁-175₄ to receive fasteners fastening the steering column 144
to the user interface support 160.

15

The steering column 144 can be moved from its central steering device position
161 in the one-person cabin configuration to its side steering device position 162
in the two-person cabin configuration by: releasing fasteners (e.g., unscrewing
bolts) received in the mounting holes 167₁, 167₂, 167₄, 167₆, 167₇ of the fixed
20 plates 169, 170 and the mounting holes 167₁₆-167₂₀ of the movable plates 171,
173; moving the movable support structure 166 relative to the fixed support
structure 165 in the widthwise direction of the vehicle 10 toward the right such
that the mounting holes 167₁₆-167₂₀ of the movable support structure 166 align
with the mounting holes 167₃, 167₄, 167₅, 167₁₁, 167₁₂ of the fixed support
25 structure 165; and using fasteners in these aligned ones of the mounting holes
167₁-167₂₀ to re-fasten the movable support structure 166 to the fixed support
structure 165. Wires from the steering column 144 can be disconnected, moved,
and reconnected to move the steering column 144 between its central steering
device position and side steering device position.

30

The speed pedal 133 can be moved from its central accelerator position 163 in the one-person cabin configuration to its side accelerator position 164 in the two-person cabin configuration by: releasing fasteners (e.g., unscrewing bolts) received in the mounting holes 167₈-167₁₀ of the fixed plate 170 and holes of the speed pedal 133; moving the speed pedal 133 relative to the fixed support structure 165 in the widthwise direction of the vehicle 10 toward the right such that the holes of the speed pedal 133 align with the mounting holes 167₁₃- 167₁₅ of the fixed support structure 165; and using fasteners in these aligned holes to re-fasten the speed pedal 133 to the fixed support structure 165.

10

The steering column 144 and the speed pedal 133 can be moved from their side steering device position 162 and side accelerator position 164 in the two-person cabin configuration to their central steering device position 161 and central accelerator position 163 in the one-person cabin configuration using a procedure that is reverse to that described above.

15

The seat support 151 and/or the user interface support 160 may be constructed in various other ways in other embodiments to provide the different seat positions 176, 177, 178, steering device positions 161, 162, and/or accelerator positions 163, 164. For example, in other embodiments, the seat support 151 and/or the user interface support 160 may provide the different seat positions 176, 177, 178, steering device positions 161, 162, and/or accelerator positions 163, 164 by allowing the operator seat 150, the steering column 144, and/or the speed pedal 133 to be moved between such different positions without having to untighten bolts or other fasteners (e.g., a rail mechanism which allows the steering column 144 and/or the speed pedal 133 to be unlocked, slid on a rail to a desired position, and locked in place; an electromechanical system comprising an actuator that can be activated to cause the steering column 144 and/or the speed pedal 133 to automatically move to a desired position; etc.).

20

25

30

The operator cabin 20 thus allows a user of the tracked utility vehicle 10, who may be the operator or another user (e.g., an owner of the vehicle 10 or an employee of an entity owning the vehicle 10), to select a desired one of the one-person cabin configuration and the two-person cabin configuration and readily
5 configure the operator cabin 20 in that selected configuration. This can enhance a versatility of the vehicle 10 depending on an application or environment in which it is used.

While in this embodiment the plurality of cabin configurations in which the
10 operator cabin 20 can be configured include the one-person cabin configuration and the two-person cabin configuration, in other embodiments, the plurality of cabin configurations in which the operator cabin 20 can be configured may include any number of different cabin configurations. For example, in other
15 embodiments, the plurality of cabin configurations in which the operator cabin 20 can be configured may include two (2) or more one-person cabin configurations that are different from one another, and may or may not include a two-person cabin configuration. For instance, in some embodiments, the operator cabin 20 may be configured in a first one-person cabin configuration in which the operator
20 seat 150 is in a first operator seat position (e.g., the operator seat position 176 in the cabin configuration shown in Figure 41) and in a second one-person cabin configuration in which the operator seat 150 is in a second operator seat position different from the first operator seat position (e.g., the operator seat position 177 in the cabin configuration shown in Figure 43), without including the passenger
25 seat 152. This may allow the operator of the vehicle 10 to sit and operate the vehicle 10 in different positions in the operator cabin 20 depending on a need or preference of the operator and/or an application or environment in which the vehicle 10 is used.

The operator cabin 20, including the user interface 130 and the seating area 132,
30 may be constructed in various other ways in other embodiments. For example, in other embodiments, the operator cabin 20 may not be configurable in different

cabin configurations, but may rather have only a single cabin configuration. For instance, in some cases, the operator cabin 20 may always comprise only the operator seat 150, i.e., always have a one-person cabin configuration, or both the operator seat 150 and the passenger seat 152, i.e., always have a two-person
5 cabin configuration.

d) Chassis

The chassis 12 comprises a frame 15 extending along the longitudinal axis 59 of
10 the tracked utility vehicle 10 and supporting various components of the vehicle 10, including the power plant 14, the track assemblies 16₁, 16₂, and the operator cabin 20. The frame 15 also supports the work equipment 41 carried by the vehicle 10.

15 As further discussed below, in this embodiment, the frame 15 is "truck-like" in that at least part of it is configured like a truck frame. This enables the work equipment 41 to be mounted to the frame 15 like on a truck frame. In particular, the frame 15 is configured such that the work equipment 41 can be supported on an area like that standardly supporting such work equipment in truck frames and
20 can be secured to the frame 15 using attachment devices (e.g., attachment plates or attachment threaded rod assemblies) standardly used for securing such work equipment to truck frames. As a result, work equipment such as the work equipment 41 may be as easily installable on the tracked utility vehicle 10 as on trucks. Work equipment such as the work equipment 41 which may be primarily
25 designed for trucks due to a potentially larger market for trucks can therefore also be easily installed on the tracked utility vehicle 10.

With additional reference to Figures 19 to 25, in this embodiment, the frame 15 comprises an upper frame structure 60 and a lower frame structure 62.

30

The upper frame structure 60 is that portion of the frame 15 on which rests and to which is secured the work equipment 41 carried by the tracked utility vehicle 10. To that end, the upper frame structure 60 includes an equipment mounting area 99 for mounting the work equipment 41 above the frame 15. In this embodiment, 5 the upper frame structure 60 comprises a pair of side rails 64₁, 64₂ extending along the longitudinal direction of the vehicle 10 and spaced apart in the widthwise direction of the vehicle 10. The upper frame structure 60 also comprises a plurality of crossmembers 66₁, 66₂ extending transversally to the longitudinal direction of the vehicle 10 between the side rails 64₁, 64₂. The upper 10 frame structure 60 can thus be viewed as being a type of "ladder frame" construction.

In this embodiment, each side rail 64_i is a C-shaped channel including a web 68 extending between a top flange 70₁ and a bottom flange 70₂. The side rail 64_i is 15 made of metallic material, in this case steel. The side rail 64_i is dimensioned such that the side rails 64₁, 64₂ are able to support the work equipment 41. For example, in some examples of implementation: the web 68 may have a height H_w of at least 10 inches, in some cases at least 14 inches, and in some cases at least 18 inches and/or a thickness T_w of at least 1/4 inches, in some cases at 20 least 5/8 inches, and in some cases at least 1 inch; and/or each of the flanges 70₁, 70₂ may have a width W_f of at least 2 inches, in some cases at least 5 inches, and in some cases at least 8 inches and/or a thickness T_f of at least 1/4 inches, in some cases at least 5/8 inches, and in some cases at least 1 inch. In this example, the side rail 64_i is made by bending a metallic plate to give it its C- 25 shape cross-section. Dimensions of the side rails 64₁, 64₂ may take on various other values in other embodiments.

The side rails 64₁, 64₂ may be configured in various other ways in other embodiments. For example, in some embodiments, each of the side rails 64₁, 64₂ 30 may be: a channel having a cross-sectional shape other than a C-shape (e.g., a U-shape); a hollow beam (e.g., a rectangular box beam); or any other suitable

elongated structural member. As another example, in some embodiments, the side rails 64₁, 64₂ may be made of material other than steel.

The crossmembers 66₁, 66₂ are secured to the side rails 64₁, 64₂ to interconnect
5 the side rails 64₁, 64₂. More particularly, in this embodiment, fasteners (e.g., bolts and/or rivets) secure the crossmembers 66₁, 66₂ to the side rails 64₁, 64₂. In other embodiments, the crossmembers 66₁, 66₂ may be secured to the side rails 64₁, 64₂ in other ways (e.g., by welding). Also, in this embodiment, the crossmember 66₁ is connected to the side rails 64₁, 64₂, while the crossmember
10 66₂ is connected to extension rail members 65₁, 65₂ that are secured to the side rails 64₁, 64₂. In this case, the extension rail members 65₁, 65₂ are C-shape channels fitted within the C-shape channels 64₁, 64₂.

In this embodiment, each crossmember 66_i is a channel-like elongated structural
15 member including a web 72 extending between a top flange 74₁, a bottom flange 74₂, and opposite end flanges 74₃, 74₄. The crossmember 66_i is made of metallic material, in this case steel. A plurality of openings 76₁-76₅ are provided in the web 72 for passing cables (e.g., hydraulic cables and/or electric cables) connected to components of the vehicle 10 and/or the work equipment 41.

20

The crossmembers 66₁, 66₂ may be configured in various other ways in other embodiments. For example, in some embodiments, each of the crossmembers 66₁, 66₂ may be a hollow beam (e.g., a rectangular box beam) or any other suitable elongated structural member. As another example, in some
25 embodiments, the crossmembers 66₁, 66₂ may be made of material other than steel.

A spacing S_r of the side rails 64₁, 64₂ in the widthwise direction of the tracked utility vehicle 10 may take on various values. In this embodiment, the spacing S_r
30 of the side rails 64₁, 64₂ corresponds to a standard truck frame side rail spacing. The "standard truck frame side rail spacing" refers to an industry-standard

spacing of side rails of a frame of a truck chassis for trucks with a gross vehicle weight rating (GVWR) over 14000 lbs (6351 kg). A truck's GVWR corresponds to a curb weight of the truck plus a cargo and passenger weight capacity of the truck. In the United States., a GVWR over 14000 lbs would be a class 4 or higher class according to the U.S. Department of Transportation's truck classification. A truck frame side rail spacing is considered to be "standard" if a majority of truck models with a GVWR rating over 14000 lbs sold by truck manufacturers in a given year in the country where the tracked utility vehicle 10 is manufactured and/or used have that truck frame side rail spacing.

10

For example, in this embodiment, the standard truck frame side rail spacing is 34 inches and thus the spacing S_r of the side rails 64₁, 64₂ is 34 inches. This may be useful, for instance, in cases where the vehicle 10 is manufactured or used in the United States. The standard truck frame side rail spacing, and thus the spacing S_r of the side rails 64₁, 64₂, may take on other values in other embodiments (e.g., 30 inches in Europe).

15

In other embodiments, the spacing S_r of the side rails 64₁, 64₂ may not correspond to a standard truck frame side rail spacing, but may be selected taking into account truck frame side rail spacings. For example, in some embodiments, the spacing S_r of the side rails 64₁, 64₂ may be no greater than 34 inches (about 0.86 m). For instance, in some embodiments, the spacing S_r of the side rails 64₁, 64₂ may be between 30 inches and 34 inches, in some cases between 32 inches and 34 inches, and in some cases between 33 inches and 34 inches.

25

In yet other embodiments, the spacing S_r of the side rails 64₁, 64₂ may be selected without considering any truck frame side rail spacing, and can thus have any suitable value.

30

The lower frame structure 62 is disposed below the upper frame structure 60 and provides a main structure for supporting the track assemblies 16₁, 16₂. In this embodiment, the lower frame structure 62 is more rigid than the upper frame structure 60. In this case, the lower frame structure 62 is the most rigid portion of the frame 15 and provides torsional rigidity. In this embodiment, the lower frame structure 62 comprises a pair of side beams 80₁, 80₂ extending along the longitudinal direction of the tracked utility vehicle 10 and spaced apart in the widthwise direction of the vehicle 10. The lower frame structure 62 also comprises a plurality of crossmembers 82₁-82₅ extending transversally to the longitudinal direction of the vehicle 10 between the side beams 80₁, 80₂. The lower frame structure 62 can thus also be viewed as being a type of "ladder frame" construction. The lower frame structure 62 also comprises a base plate 81 extending between the side beams 80₁, 80₂ to protect a fuel tank. The lower frame structure 62 also comprises a front drawbar 87₁ and a rear drawbar 87₂.

15

In this embodiment, each of the side beams 80₁, 80₂ is a rectangular box beam made of metallic material, in this case steel. The side beams 80₁, 80₂ may be configured in various other ways in other embodiments. For example, in some embodiments, each of the side beams 80₁, 80₂ may be: a hollow beam having a cross-sectional shape other than rectangular (e.g., circular or otherwise curved); a channel having a C-shape, U-shape or other suitable shape; or any other suitable elongated structural member. As another example, in some embodiments, the side beams 80₁, 80₂ may be made of material other than steel.

25 The crossmembers 82₁-82₅ are secured to the side beams 80₁, 80₂ to interconnect the side beams 80₁, 80₂. More particularly, in this embodiment, the crossmembers 82₁-82₅ are secured to the side beams 80₁, 80₂ by welding. The crossmembers 82₁-82₅ may be secured to the side beams 80₁, 80₂ in other ways in other embodiments (e.g., by fasteners such as bolts and/or rivets).

30

In this embodiment, the frame 15 defines an internal space 86. This internal space 86, which will be referred to as a “tub”, can be used to receive components of the tracked utility vehicle 10 and/or part of the work equipment 41 carried by the tracked utility vehicle 10 (e.g., the vehicle’s fuel tank, pipes, cables, a dump box’s hydraulic cylinder, a crane’s torque box, etc.).

As shown in Figure 20, in this embodiment, the frame 15 defines a vertical gap 78 between the upper frame structure 60 and the lower frame structure 62. The vertical gap 78 may facilitate use of attachment threaded rod assemblies or other attachment devices for attaching the work equipment 41 to the frame 15, as further discussed later on. For example, in some embodiments, the vertical gap 78 may have a height H_g in the height direction of the tracked utility vehicle 10 of at least 0.5 inches, in some cases at least 0.75 inches, in some cases at least 1 inch, in some cases 1.25 inches, and even more in some cases (e.g., 2 inches or more). In other embodiments, the upper frame structure 60 and the lower frame structure 62 may be contiguous such that there is no such vertical gap between them.

The track assemblies 16_1 , 16_2 are mounted to the frame 15. In this embodiment, the track assemblies 16_1 , 16_2 are mounted to both the lower frame structure 62 and the upper frame structure 60. More particularly, in this embodiment, each of the wheel mounting structures 88_1 - 88_4 is secured to both the lower frame structure 62 and the upper frame structure 60. In this case, each of the wheel mounting structures 88_1 - 88_4 is welded to the side beams 80_1 , 80_2 of the lower frame structure 62 and fastened to the side rails 64_1 , 64_2 of the upper frame structure 60 by fasteners (e.g., bolts and/or rivets). In other cases, each of the wheel mounting structures 88_1 - 88_4 may be fastened to the side beams 80_1 , 80_2 of the lower frame structure 62 by fasteners (e.g., bolts and/or rivets) and/or welded to the side rails 64_1 , 64_2 of the upper frame structure 60. In this embodiment, the support wheel mounting structures 88_2 , 88_3 are also welded to the crossmembers 82_1 , 82_4 .

The work equipment 41 is mounted to the frame 15. In this embodiment, the work equipment 41 is mounted to the upper frame structure 60. More particularly, in this embodiment, the work equipment 41 rests on and is secured to the side rails
5 64₁, 64₂. Since the side rails 64₁, 64₂ are C-shape channels standardly used in truck frames and since the spacing S_r of the side rails 64₁, 64₂ corresponds to the standard truck frame side rail spacing, work equipment such as the work equipment 41 may be as easily installable on the tracked utility vehicle 10 as on trucks, even if it was primarily designed for trucks.

10

With additional reference to Figures 26 to 28, in this embodiment, a base 90 of the work equipment 41 rests on the side rails 64₁, 64₂ of the frame 15. The base 90 of the work equipment 41 is secured to the side rails 64₁, 64₂ by a plurality of attachment devices 92₁-92_R, 94₁-94_P. For example, in this embodiment, each of
15 the attachment devices 92₁-92_R includes an attachment threaded rod assembly, and each of the attachment devices 94₁-94_P includes an attachment plate. Such attachment threaded rod assemblies and attachment plates are standardly used for securing work equipment such as the work equipment 41 to trucks.

20 Each attachment threaded rod assembly 92_i includes a pair of threaded rods 95₁, 95₂ and a bottom link 96 disposed around the side rail 64_i. The side rail 64_i is located between the threaded rods 95₁, 95₂ which are secured to the bottom link 96 and an attachment part 95 of the base 90 of the work equipment 41 with fasteners (e.g., nuts) to clamp the side rail 64_i. In this embodiment, the vertical
25 gap 78 between the side rail 64_i and the side beam 80₁ facilitates installation of the attachment threaded rod assembly 92_i. In particular, the gap 78 facilitates positioning of the bottom link 96 beneath the side rail 64_i and tightening of the fasteners on the threaded rods 95₁, 95₂.

30 Each attachment plate 94_i is secured to the side rail 64_i and to the base 90 of the work equipment 41. More particularly, in this embodiment, the attachment plate

94_i is fastened to the web 68 of the side rail 64_i by fasteners (e.g., bolts and/or rivets) and welded to the base 90 of the work equipment 41. This type of attachment plate can sometimes be referred to as a “fish plate”. The attachment plate 94_i may be secured to the side rail 64_i and to the base 90 of the work equipment 41 in other ways in other embodiments (e.g., by being fastened to the base 90 of the work equipment and/or welded to the side rail 64_i).

In this example of implementation, the attachment plate 94_i includes a generally rectangular lower part 51 fastened to the side rail 64_i and a curved, in this case generally semicircular, upper part 53 welded to the base 90 of the work equipment 41. The upper part 53 of the attachment plate 94_i includes an opening 55, which may allow a greater length of weld bead when the attachment plate 94_i is welded to the base 90 of the work equipment 41. The attachment plate 94_i may have various other shapes in other examples of implementation.

15

Although in this embodiment the attachment devices 92₁-92_R, 94₁-94_P securing the work equipment 41 to the frame 15 are attachment threaded rod assemblies and attachment plates, various other types of attachment devices may be used in other embodiments.

20

While in embodiments considered above the tracked vehicle 10 is a tracked carrier vehicle carrying work equipment, in other embodiments, certain features (e.g., the track tensioner 85 connected to the hydraulic drive system 21) of the tracked vehicle 10 may be implemented in other types of industrial tracked vehicles, such as an agricultural vehicle (e.g., a tractor, a harvester, etc.) or a construction vehicle (e.g., a loader, a bulldozer, an excavator, etc.).

Any feature of any embodiment discussed herein may be combined with any feature of any other embodiment discussed herein in some examples of implementation.

30

Although various embodiments have been illustrated, this was for the purpose of describing, but not limiting, the invention. Various modifications will become apparent to those skilled in the art and are within the scope of this invention, which is defined by the following claims.

CLAIMS

1. A tracked vehicle comprising:
 - a) a chassis comprising a frame extending along a longitudinal direction of the tracked vehicle;
 - b) an operator cabin mounted to the frame, the frame comprising a pair of side members extending in an area behind the operator cabin in the longitudinal direction of the tracked vehicle, the pair of side members being spaced apart in a widthwise direction of the tracked vehicle for supporting work equipment carried by the tracked vehicle;
 - c) a power plant mounted above the side members, at least part of the power plant occupying a space next to the operator cabin along the widthwise direction of the tracked vehicle and extending past the operator cabin along the longitudinal direction of the tracked vehicle; and
 - d) a plurality of track assemblies for traction of the tracked vehicle, a first one of the track assemblies being on a first side of the tracked vehicle, a second one of the track assemblies being on a second side of the tracked vehicle, each track assembly of the plurality of track assemblies being mounted to the frame and comprising:
 - i. a plurality of wheels including:
 - a drive wheel;
 - an end wheel spaced apart from the drive wheel in the longitudinal direction of the tracked vehicle; and
 - a plurality of support wheels arranged in an inline configuration between the drive wheel and the end wheel;
- and

ii. an endless track disposed around the plurality of wheels for engaging the ground, the endless track comprising:

- a top run extending between the drive wheel and the end wheel over the support wheels without contacting the support wheels; and
- a ground-engaging bottom run extending under the support wheels, the drive wheel being in driving engagement with the endless track to impart motion to the endless track;

at least part of the prime mover being mounted to the frame and located directly above at least part of the first one of said track assemblies;

each of the side members extending rearwards in the longitudinal direction of the tracked vehicle past the operator cabin and past said part of the power plant that extends past the operator cabin.

2. The tracked vehicle of claim 1, wherein the frame comprises (i) an upper frame structure including the pair of side members and (ii) a lower frame structure below the upper frame structure, the frame defining a vertical gap between the upper frame structure and the lower frame structure.
3. The tracked vehicle of claim 2, wherein the track assembly comprises a plurality of wheel mounting structures secured to the frame and spaced apart in the longitudinal direction of the tracked vehicle, each wheel mounting structure of the plurality of wheel mounting structures supporting at least one of the plurality of wheels of the track assembly, the wheel mounting structure being secured to both (i) a given one of the side members and (ii) the lower frame structure.
4. The tracked vehicle of claim 2, wherein the vertical gap has a height in a height direction of the tracked vehicle of at least 0.5 inches.

5. The tracked vehicle of claim 2, wherein the vertical gap facilitates installation of an attachment threaded rod assembly for attaching the work equipment to the side members.
6. The tracked vehicle of claim 2, wherein the lower frame structure comprises a pair of hollow beams spaced apart in the widthwise direction of the tracked vehicle.
7. The tracked vehicle of claim 1, wherein each side member of the pair of side members includes a C-shape channel.
8. The tracked vehicle of claim 1, wherein the frame comprises a plurality of crossmembers extending transversally to the longitudinal direction of the tracked vehicle and interconnecting the side members.
9. The tracked vehicle of claim 1, wherein the seating area is configured for allowing an operator to sit therein, the seating area defining a plurality of seat positions along a widthwise direction of the tracked vehicle.
10. The tracked vehicle of claim 9, wherein the tracked vehicle, with the work equipment mounted to the frame, respects a vehicle height limit for travel on a public road infrastructure.
11. The tracked vehicle of claim 10, wherein the vehicle height limit for travel on the public road infrastructure is between 13.5 feet and 14 feet.
12. The tracked vehicle of claim 9, wherein an overall height of the tracked vehicle, measured with the work equipment in a retracted nonworking state, is no more than 12.5 feet.
13. The tracked vehicle of claim 1, wherein the tracked vehicle is configured such that, when the work equipment is in a retracted nonworking state, the work

equipment extends frontward in the longitudinal direction of the tracked vehicle beyond a rear side of the operator cabin.

14. The tracked vehicle of claim 13, wherein the tracked vehicle is configured such that, when the work equipment is in the retracted nonworking state, the work equipment extends frontward in the longitudinal direction of the tracked vehicle beyond a front side of the operator cabin.
15. The tracked vehicle of claim 9, wherein the operator cabin comprises a first seat at a first one of the seat positions for the operator and a second seat at a second one of the seat positions for a person sitting next to the operator.
16. The tracked vehicle of claim 1, wherein the end wheel is a rear wheel, the rear wheel and a rearmost one of the support wheels overlapping in the longitudinal direction of the tracked vehicle.
17. The tracked vehicle of claim 1, wherein each support wheel of the plurality of support wheels occupies a majority of a height of the track assembly.
18. The tracked vehicle of claim 1, wherein the tracked vehicle has a length of at least 5 m, a width of at least 2 m, and a height of no more than 4 m.
19. The tracked vehicle of claim 1, wherein the tracked vehicle has a payload capacity of at least 10000 lbs.
20. The tracked vehicle of claim 1, wherein the side members comprise side rails.
21. The tracked vehicle of claim 1, wherein the spacing of the side members in the widthwise direction of the tracked vehicle is 34 inches.
22. The tracked vehicle defined in claim 1, each of the wheels having a respective axis of rotation, wherein the axes of rotation of the drive wheel and of the idle

wheel are further from the ground than the axes of rotation of all of the support wheels.

23. The tracked vehicle defined in claim 1, wherein the side members extend along the longitudinal direction of the tracked vehicle and wherein each of the side members extends longitudinally at one end past the drive wheel of a corresponding one of the endless tracks and at another end past the end wheel of the corresponding endless track.
24. The tracked vehicle defined in claim 1, wherein the side members extend under the operator cabin.
25. The tracked vehicle defined in claim 1, wherein part of the power plant extending past the operator cabin along the longitudinal direction of the tracked vehicle is visible by an operator seated inside the operator cabin via a window.
26. The tracked vehicle defined in claim 1, wherein each of the side members extends longitudinally at one end past the drive wheel or the end wheel of the corresponding endless track.
27. The tracked vehicle defined in claim 1, wherein the power plant comprises a housing which houses at least the prime mover, the housing having an L-shaped configuration extending behind and next to the operator cabin.
28. The tracked vehicle of claim 1, the prime mover comprising an internal combustion engine, at least part of the internal combustion engine being located directly above said part of the first one of the track assemblies.
29. The tracked vehicle of claim 1, at least part of the operator cabin being located directly above at least part of the second one of said track assemblies.

30. The tracked vehicle of claim 1, wherein the tracked vehicle has a width of at least 2 m, the operator cabin occupying more than half the width of the tracked vehicle.
31. The tracked vehicle of claim 1, wherein at least a portion of the prime mover that is located directly above said part of the first one of the track assemblies is located in an area behind the operator cabin.
32. The tracked vehicle of claim 1, wherein the prime mover includes a part that is above the side members and behind the operator cabin.
33. The tracked vehicle of claim 32, wherein at least part of the prime mover that is behind the operator cabin occupies more space along the widthwise direction of the tracked vehicle than does the operator cabin.
34. The tracked vehicle of claim 33, wherein the power plant comprises a hydraulic pump connected to the prime mover and mounted above the frame and behind the operator cabin.
35. The tracked vehicle of claim 34, wherein the power plant comprises a housing which houses the prime mover and the hydraulic pump, and the housing, the prime mover and the hydraulic pump are installable on and removable from the frame together as a unit.
36. The tracked vehicle of claim 1, wherein the power plant further comprises a hydraulic pump, a hydraulic fluid reservoir, a cooling system and at least one battery, all disposed above the side members.
37. The tracked vehicle of claim 36, wherein the power plant further comprises a housing that houses the prime mover, the hydraulic pump, the hydraulic fluid reservoir, the cooling system and the at least one battery.

38. The tracked vehicle of claim 37, wherein the housing has an L-shaped configuration when viewed from above the tracked vehicle.
39. The tracked vehicle of claim 28, wherein at least another part of the prime mover is mounted to the frame directly above at least part of the second one of the track assemblies.
40. The tracked vehicle of claim 20, wherein the side rails are configured to define a spacing along the widthwise direction of the tracked vehicle corresponding to a standard truck frame side rail spacing.
41. The tracked vehicle of claim 20, wherein the standard truck frame side rail spacing is 34 inches such that the spacing of the side rails in the widthwise direction of the tracked vehicle is 34 inches.
42. A tracked vehicle comprising:
 - a) a chassis comprising a frame extending along a longitudinal direction of the tracked vehicle, the frame comprising a pair of elongated structural members spaced apart in a widthwise direction of the tracked vehicle for supporting work equipment carried by the tracked vehicle;
 - b) an operator cabin mounted to the frame;
 - c) a power plant mounted to the frame and comprising a prime mover, wherein the power plant comprises a housing which houses at least the prime mover, the housing having an L-shaped configuration extending behind and next to the operator cabin, there being no portion of the prime mover under the operator cabin; and
 - d) a plurality of track assemblies for traction of the tracked vehicle, a first one of the track assemblies being on a first side of the tracked vehicle, a second one of the track assemblies being on a second side of the tracked

vehicle, each track assembly of the plurality of track assemblies being mounted to the frame and comprising:

- i. a plurality of wheels including:
 - a drive wheel;
 - an end wheel spaced apart from the drive wheel in the longitudinal direction of the tracked vehicle; and
 - a plurality of support wheels arranged in an inline configuration between the drive wheel and the end wheel;

and

- ii. an endless track disposed around the plurality of wheels for engaging the ground, the endless track comprising:
 - I. a top run extending between the drive wheel and the end wheel over the support wheels; and
 - II. a ground-engaging bottom run extending under the support wheels, the drive wheel being in driving engagement with the endless track to impart motion to the endless track,

the elongated structural members having a bottom surface below the top run of the endless track and a top surface above at least part of the top run of the endless track.

- 43. The tracked vehicle of claim 42, at least part of the power plant being mounted above the elongated structural members, occupying a space next to the operator cabin along the widthwise direction of the tracked vehicle, and extending past the operator cabin along the longitudinal direction of the tracked vehicle.

44. The tracked vehicle defined in claim 42, wherein the top run of each of the endless track extends between the respective drive wheel and the respective end wheel without contacting any of the respective support wheels.
45. The tracked vehicle defined in claim 42, a spacing of the elongated structural members in the widthwise direction of the tracked vehicle being no greater than 34 inches.
46. The tracked vehicle defined in claim 42, wherein the prime mover is mounted above the frame and behind the operator cabin.
47. The tracked vehicle of claim 42, wherein the operator cabin comprises a seating area for allowing an operator to sit therein, the seating area defining a plurality of seat positions along a widthwise direction of the tracked vehicle.
48. The tracked vehicle of claim 42, wherein the end wheel is a rear wheel, the rear wheel and a rearmost one of the support wheels overlapping in the longitudinal direction of the tracked vehicle.
49. The tracked vehicle of claim 42, wherein each support wheel of the plurality of support wheels occupies a majority of a height of the track assembly.
50. The tracked vehicle of claim 42, wherein the pair of elongated structural members extends in an area behind the operator cabin in the longitudinal direction of the tracked vehicle.
51. The tracked vehicle of claim 42, wherein the tracked vehicle is configured such that, when the work equipment is in a retracted nonworking state, the work equipment extends frontward in the longitudinal direction of the tracked vehicle beyond a front side of the operator cabin.

52. The tracked vehicle of claim 42, wherein the elongated structural members comprise side rails.
53. The tracked vehicle defined in claim 42, wherein the elongated structural members extend along the longitudinal direction of the tracked vehicle and wherein each of the elongated structural members extends longitudinally at one end past the drive wheel of a corresponding one of the endless tracks and at another end past the end wheel of the corresponding endless track.
54. A tracked vehicle comprising:
- a) a chassis comprising a frame extending along a longitudinal direction of the tracked vehicle;
 - b) an operator cabin mounted to the frame, the frame comprising a pair of side members extending in an area behind the operator cabin in the longitudinal direction of the tracked vehicle, the pair of side members being spaced apart in a widthwise direction of the tracked vehicle for mounting work equipment carried by the tracked vehicle to the side members;
 - c) a power plant mounted to the frame and comprising a prime mover, the prime mover being mounted above the side members, at least part of the power plant occupying a space next to the operator cabin along the widthwise direction of the tracked vehicle and extending past the operator cabin along the longitudinal direction of the tracked vehicle; and
 - d) a plurality of track assemblies for traction of the tracked vehicle, a first one of the track assemblies being on a first side of the tracked vehicle, a second one of the track assemblies being on a second side of the tracked vehicle, each track assembly of the plurality of track assemblies being mounted to the frame and comprising:
 - i. a plurality of wheels including:

- a drive wheel;
- an end wheel spaced apart from the drive wheel in the longitudinal direction of the tracked vehicle; and
- a plurality of support wheels arranged in an inline configuration between the drive wheel and the end wheel;

and

ii. an endless track disposed around the plurality of wheels for engaging the ground, the endless track comprising:

- a top run extending between the drive wheel and the end wheel over the support wheels without contacting the support wheels; and
- a ground-engaging bottom run extending under the support wheels, the drive wheel being in driving engagement with the endless track to impart motion to the endless track;

wherein the side members extend along the longitudinal direction of the tracked vehicle and wherein each of the side members extends longitudinally at one end past the drive wheel of a corresponding one of the endless tracks and at another end past the end wheel of the corresponding endless track.

55. The tracked vehicle of claim 54, wherein the tracked vehicle is configured such that, when the work equipment is in a retracted nonworking state, the work equipment extends frontward in the longitudinal direction of the tracked vehicle beyond a front side of the operator cabin.

56. The tracked vehicle of claim 54, wherein each support wheel of the plurality of support wheels occupies a majority of a height of the track assembly.

57. The tracked vehicle of claim 54, wherein the side members comprise side rails.
58. The tracked vehicle defined in claim 54, wherein the side members extend along the longitudinal direction of the tracked vehicle and wherein each of the side members extends longitudinally at one end past the drive wheel of a corresponding one of the endless tracks and at another end past the end wheel of the corresponding endless track.
59. The tracked vehicle defined in claim 54, a spacing of the side members in the widthwise direction of the tracked vehicle being no greater than 34 inches.
60. A tracked vehicle comprising:
- a) a chassis comprising a frame extending along a longitudinal direction of the tracked vehicle, the frame comprising an equipment mounting area for mounting work equipment above the frame;
 - b) an operator cabin mounted to the frame, the frame comprising a pair of side members extending in an area behind the operator cabin in the longitudinal direction of the tracked vehicle, the pair of side members being spaced apart in a widthwise direction of the tracked vehicle for supporting work equipment carried by the tracked vehicle;
 - c) a power plant mounted to the frame and comprising a prime mover, the prime mover being mounted above the side members, at least part of the power plant occupying a space next to the operator cabin along the widthwise direction of the tracked vehicle and extending past the operator cabin along the longitudinal direction of the tracked vehicle; and
 - d) a plurality of track assemblies for traction of the tracked vehicle, a first one of the track assemblies being on a first side of the tracked vehicle, a second one of the track assemblies being on a second side of the tracked

vehicle, each track assembly of the plurality of track assemblies being mounted to the frame and comprising:

- i. a plurality of wheels including:
 - a drive wheel;
 - an end wheel spaced apart from the drive wheel in the longitudinal direction of the tracked vehicle; and
 - a plurality of support wheels arranged in an inline configuration between the drive wheel and the end wheel;

and

- ii. an endless track disposed around the plurality of wheels for engaging the ground, the endless track comprising:
 - a top run extending between the drive wheel and the end wheel over the support wheels without contacting the support wheels; and
 - a ground-engaging bottom run extending under the support wheels, the drive wheel being in driving engagement with the endless track to impart motion to the endless track,

at least part of the prime mover being mounted to the frame and located directly above at least part of the first one of said track assemblies;

wherein each of the side members extends longitudinally at one end past the drive wheel or the end wheel of the corresponding endless track.

- 61. The tracked vehicle of claim 60, wherein the tracked vehicle is configured such that, when the work equipment is in a retracted nonworking state, the work equipment extends frontward in the longitudinal direction of the tracked vehicle beyond a front side of the operator cabin.

62. The tracked vehicle of claim 60, wherein each support wheel of the plurality of support wheels occupies a majority of a height of the track assembly.
63. The tracked vehicle of claim 60, wherein the side members comprise side rails.
64. The tracked vehicle defined in claim 60, wherein the side members extend along the longitudinal direction of the tracked vehicle and wherein each of the side members extends longitudinally at one end past the drive wheel of a corresponding one of the endless tracks and at another end past the end wheel of the corresponding endless track.
65. The tracked vehicle defined in claim 60, a spacing of the side members in the widthwise direction of the tracked vehicle being no greater than 34 inches.
66. The tracked vehicle of claim 60, wherein the tracked vehicle has a width of at least 2 m, the operator cabin occupying more than half the width of the tracked vehicle.
67. A tracked vehicle comprising:
 - a) a chassis comprising a frame extending along a longitudinal direction of the tracked vehicle, the frame comprising an equipment mounting area for mounting work equipment above the frame;
 - b) an operator cabin mounted to the frame, the frame comprising a pair of side members extending in an area behind the operator cabin in the longitudinal direction of the tracked vehicle, the pair of side members being spaced apart in a widthwise direction of the tracked vehicle for supporting work equipment carried by the tracked vehicle;
 - c) a power plant mounted to the frame and comprising a prime mover, the prime mover being mounted above the side members, at least part of the power plant occupying a space next to the operator cabin along the

widthwise direction of the tracked vehicle and extending past the operator cabin along the longitudinal direction of the tracked vehicle; and

d) a plurality of track assemblies for traction of the tracked vehicle, a first one of the track assemblies being on a first side of the tracked vehicle, a second one of the track assemblies being on a second side of the tracked vehicle, each track assembly of the plurality of track assemblies being mounted to the frame and comprising:

i. a plurality of wheels including:

- a drive wheel;
- an end wheel spaced apart from the drive wheel in the longitudinal direction of the tracked vehicle; and
- a plurality of support wheels arranged in an inline configuration between the drive wheel and the end wheel;

and

ii. an endless track disposed around the plurality of wheels for engaging the ground, the endless track comprising:

- a top run extending between the drive wheel and the end wheel over the support wheels without contacting the support wheels; and
- a ground-engaging bottom run extending under the support wheels, the drive wheel being in driving engagement with the endless track to impart motion to the endless track;

at least part of the prime mover being mounted to the frame and located directly above at least part of the first one of said track assemblies;

wherein the power plant comprises a housing which houses at least the prime mover, the housing having an L-shaped configuration extending behind and next to the operator cabin.

68. The tracked vehicle of claim 67, wherein the tracked vehicle is configured such that, when the work equipment is in a retracted nonworking state, the work equipment extends frontward in the longitudinal direction of the tracked vehicle beyond a front side of the operator cabin.
69. The tracked vehicle of claim 67, wherein each support wheel of the plurality of support wheels occupies a majority of a height of the track assembly.
70. The tracked vehicle of claim 67, wherein the side members comprise side rails.
71. The tracked vehicle defined in claim 67, wherein the side members extend along the longitudinal direction of the tracked vehicle and wherein each of the side members extends longitudinally at one end past the drive wheel of a corresponding one of the endless tracks and at another end past the end wheel of the corresponding endless track.
72. The tracked vehicle defined in claim 67, a spacing of the side members in the widthwise direction of the tracked vehicle being no greater than 34 inches.
73. A tracked vehicle comprising:
 - a) a chassis comprising a frame extending along a longitudinal direction of the tracked vehicle, the frame comprising an equipment mounting area for mounting work equipment above the frame;
 - b) an operator cabin mounted to the frame, the operator cabin comprising a seating area for allowing an operator to sit and a user interface for enabling the operator to control the tracked vehicle, the seating area defining a plurality of seat positions along a widthwise direction of the

tracked vehicle, the seating area having a first seat for the operator and a second seat for a person sitting next to the operator, the operator cabin being off-center along a widthwise direction of the tracked vehicle and extending over a majority of the width of the frame;

- c) a power plant mounted to the frame and comprising a prime mover; and
- d) a plurality of track assemblies for traction of the tracked vehicle, a first one of the track assemblies being on a first lateral side of the tracked vehicle, a second one of the track assemblies being on a second lateral side of the tracked vehicle, each track assembly of the plurality of track assemblies being mounted to the frame and comprising:

- i. a plurality of wheels including:

- a drive wheel;
- an end wheel spaced apart from the drive wheel in the longitudinal direction of the tracked vehicle; and
- a plurality of support wheels arranged in an inline configuration between the drive wheel and the end wheel;

and

- ii. an endless track disposed around the plurality of wheels for engaging the ground, the endless track comprising:

- a top run extending between the drive wheel and the end wheel over the support wheels; and
- a ground-engaging bottom run extending under the support wheels,

the drive wheel being in driving engagement with the endless track to impart motion to the endless track.

74. The tracked vehicle of claim 73, wherein the tracked vehicle, with the work equipment mounted to the frame, respects a vehicle height limit for travel on a public road infrastructure.
75. The tracked vehicle of claim 74, wherein the vehicle height limit for travel on the public road infrastructure is between 13.5 feet and 14 feet.
76. The tracked vehicle of claim 73, wherein an overall height of the tracked vehicle, measured with the work equipment in a retracted nonworking state, is no more than 12.5 feet.
77. The tracked vehicle of claim 73, wherein an overall height of the tracked vehicle, measured with the work equipment in a retracted nonworking state, is no more than 12 feet.
78. The tracked vehicle of claim 73, wherein the tracked vehicle is configured such that, when the work equipment is in a retracted nonworking state, the work equipment extends frontward in the longitudinal direction of the tracked vehicle beyond a rear side of the operator cabin.
79. The tracked vehicle of claim 78, wherein the tracked vehicle is configured such that, when the work equipment is in the retracted nonworking state, the work equipment extends frontward in the longitudinal direction of the tracked vehicle beyond a front side of the operator cabin.
80. The tracked vehicle of claim 73, wherein the operator cabin comprises a roof defining a height of the tracked vehicle, the height of the tracked vehicle to the roof being no more than 2.8 m.
81. The tracked vehicle of claim 80, wherein the height of the tracked vehicle to the roof is no more than 2.6 m.

82. The tracked vehicle of claim 73, wherein at least part of the power plant is mounted above the frame and behind the operator cabin.
83. The tracked vehicle of claim 82, wherein the prime mover is mounted above the frame and behind the operator cabin.
84. The tracked vehicle of claim 73, the user interface comprising an accelerator for controlling a speed of the tracked vehicle and a steering device for steering the tracked vehicle.
85. The tracked vehicle of claim 73, wherein the frame comprises a pair of side rails spaced apart in the widthwise direction of the tracked vehicle for mounting the work equipment to the side rails, a spacing of the side rails in the widthwise direction of the tracked vehicle corresponding to a standard truck frame side rail spacing.
86. The tracked vehicle of claim 85, wherein the standard truck frame side rail spacing is 34 inches such that the spacing of the side rails in the widthwise direction of the tracked vehicle is 34 inches.
87. The tracked vehicle of claim 73, wherein the frame comprises a pair of side rails spaced apart in the widthwise direction of the tracked vehicle for mounting the work equipment to the side rails, a spacing of the side rails in the widthwise direction of the tracked vehicle being no greater than 34 inches.
88. The tracked vehicle of claim 73, wherein each support wheel of the plurality of support wheels occupies a majority of a height of the track assembly.
89. The tracked vehicle of claim 73, wherein the tracked vehicle has a length of at least 5 m, a width of at least 2 m, and a height of no more than 4 m.

90. The tracked vehicle of claim 73, wherein the tracked vehicle has a payload capacity of at least 10000 lbs.
91. The tracked vehicle of claim 73, wherein at least part of the power plant is located adjacent a side of the operator cabin along the widthwise direction of the tracked vehicle.
92. The tracked vehicle of claim 91, wherein at least part of the power plant has an L-shaped configuration that extends behind the operator cabin in the longitudinal direction of the tracked vehicle.
93. The tracked vehicle of claim 73, wherein the operator cabin comprises a door located on a side opposite the side of the cabin adjacent to which said at least part of the power plant is located.
94. The tracked vehicle of claim 84, wherein the accelerator comprises a speed pedal and wherein the steering device comprises a steering wheel.
95. A tracked vehicle comprising:
 - a) a chassis comprising a frame extending along a longitudinal direction of the tracked vehicle, the frame comprising an equipment mounting area for mounting work equipment above the frame;
 - b) an operator cabin mounted to the frame, the operator cabin comprising a seating area for allowing an operator to sit and a user interface for enabling the operator to control the tracked vehicle, the seating area defining a plurality of seat positions along a widthwise direction of the tracked vehicle, the seating area having a first seat for the operator and a second seat for a person sitting next to the operator, the operator cabin being off-center along a widthwise direction of the tracked vehicle and extending over a majority of the width of the frame;

- c) a power plant mounted to the frame and comprising a prime mover, wherein the power plant comprises a hydraulic pump connected to the prime mover and mounted above the frame and behind the operator cabin; and
- d) a plurality of track assemblies for traction of the tracked vehicle, a first one of the track assemblies being on a first lateral side of the tracked vehicle, a second one of the track assemblies being on a second lateral side of the tracked vehicle, each track assembly of the plurality of track assemblies being mounted to the frame and comprising:
 - i. a plurality of wheels including:
 - a drive wheel;
 - an end wheel spaced apart from the drive wheel in the longitudinal direction of the tracked vehicle; and
 - a plurality of support wheels arranged in an inline configuration between the drive wheel and the end wheel;
 - and
 - ii. an endless track disposed around the plurality of wheels for engaging the ground, the endless track comprising:
 - a top run extending between the drive wheel and the end wheel over the support wheels; and
 - a ground-engaging bottom run extending under the support wheels,

the drive wheel being in driving engagement with the endless track to impart motion to the endless track.

96. The tracked vehicle of claim 95, wherein the power plant comprises a housing which houses the prime mover and the hydraulic pump, and the housing, the prime mover and the hydraulic pump are installable on and removable from the frame together as a unit.
97. A tracked vehicle comprising:
- a) a chassis comprising a frame extending along a longitudinal direction of the tracked vehicle, the frame comprising an equipment mounting area for mounting work equipment above the frame;
 - b) an operator cabin mounted to the frame, the operator cabin comprising a seating area for allowing an operator to sit and a user interface for enabling the operator to control the tracked vehicle, the seating area defining a plurality of seat positions along a widthwise direction of the tracked vehicle, the seating area having a first seat for the operator and a second seat for a person sitting next to the operator, the operator cabin being off-center along a widthwise direction of the tracked vehicle and extending over a majority of the width of the frame;
 - c) a power plant mounted to the frame and comprising a prime mover, wherein at least part of the power plant is mounted above the frame and on a lateral side of the operator cabin; and
 - d) a plurality of track assemblies for traction of the tracked vehicle, a first one of the track assemblies being on a first lateral side of the tracked vehicle, a second one of the track assemblies being on a second lateral side of the tracked vehicle, each track assembly of the plurality of track assemblies being mounted to the frame and comprising:
 - i. a plurality of wheels including:
 - a drive wheel;

- an end wheel spaced apart from the drive wheel in the longitudinal direction of the tracked vehicle; and
 - a plurality of support wheels arranged in an inline configuration between the drive wheel and the end wheel;
- and
- ii. an endless track disposed around the plurality of wheels for engaging the ground, the endless track comprising:
 - a top run extending between the drive wheel and the end wheel over the support wheels; and
 - a ground-engaging bottom run extending under the support wheels, the drive wheel being in driving engagement with the endless track to impart motion to the endless track.

98. A tracked vehicle comprising:

- a) a chassis comprising a frame extending along a longitudinal direction of the tracked vehicle, the frame comprising an equipment mounting area for mounting work equipment above the frame;
- b) an operator cabin mounted to the frame, the operator cabin comprising a seating area for allowing an operator to sit and a user interface for enabling the operator to control the tracked vehicle, the seating area defining a plurality of seat positions along a widthwise direction of the tracked vehicle, the seating area having a first seat for the operator and a second seat for a person sitting next to the operator, the operator cabin being off-center along a widthwise direction of the tracked vehicle and extending over a majority of the width of the frame; the operator cabin extending over a majority of the height of the vehicle in an absence of the work equipment;

- c) an engine mounted above the frame; and
- d) a plurality of track assemblies for traction of the tracked vehicle, a first one of the track assemblies being on a first lateral side of the tracked vehicle, a second one of the track assemblies being on a second lateral side of the tracked vehicle, each track assembly of the plurality of track assemblies being mounted to the frame and comprising:
 - i. a plurality of wheels including:
 - a drive wheel;
 - an end wheel spaced apart from the drive wheel in the longitudinal direction of the tracked vehicle; and
 - a plurality of support wheels arranged in an inline configuration between the drive wheel and the end wheel;

and

- ii. an endless track disposed around the plurality of wheels for engaging the ground, the endless track comprising:
 - a top run extending between the drive wheel and the end wheel over the support wheels; and
 - a ground-engaging bottom run extending under the support wheels,

the drive wheel being in driving engagement with the endless track to impart motion to the endless track.

99. A tracked vehicle comprising:

- a) a chassis comprising a frame extending along a longitudinal direction of the tracked vehicle, the frame comprising an equipment mounting area for mounting work equipment above the frame;

- b) an operator cabin mounted to the frame;
- c) a power plant mounted to the frame and comprising a prime mover, at least part of the power plant being mounted above the frame and behind the operator cabin; and
- d) a plurality of track assemblies for traction of the tracked vehicle, a first one of the track assemblies being on a first lateral side of the tracked vehicle, a second one of the track assemblies being on a second lateral side of the tracked vehicle, each track assembly of the plurality of track assemblies being mounted to the frame and comprising:
 - i. a plurality of wheels including:
 - a drive wheel;
 - an end wheel spaced apart from the drive wheel in the longitudinal direction of the tracked vehicle; and
 - a plurality of support wheels arranged in an inline configuration between the drive wheel and the end wheel;

the end wheel and a rearmost one of the support wheels overlapping in the longitudinal direction of the tracked vehicle;

and

- ii. an endless track disposed around the plurality of wheels for engaging the ground, the endless track comprising:
 - a top run extending between the drive wheel and the end wheel over the support wheels; and
 - a ground-engaging bottom run extending under the support wheels,

the drive wheel being in driving engagement with the endless track to impart motion to the endless track.

100. A tracked vehicle comprising:

- a) a chassis comprising a frame extending along a longitudinal direction of the tracked vehicle, the frame comprising an equipment mounting area for mounting work equipment above the frame;
- b) an operator cabin mounted to the frame, the operator cabin comprising:
 - i. a seating area for allowing an operator to sit; and
 - ii. a user interface for enabling the operator to control the tracked vehicle, the user interface comprising:
 - an accelerator for controlling a speed of the tracked vehicle and
 - a steering device for steering the tracked vehicle;
- c) the operator cabin being configurable in a plurality of cabin configurations including:
 - i. a first cabin configuration in which the operator sits in a first seat position of the seating area along a widthwise direction of the track assembly and the steering device is in a first steering device position along the widthwise direction of the track assembly; and
 - ii. a second cabin configuration in which the operator sits in a second seat position of the seating area along the widthwise direction of the track assembly and the steering device is in a second steering device position along the widthwise direction of the track assembly,
- d) a power plant mounted to the frame and comprising a prime mover; and
- e) a plurality of track assemblies for traction of the tracked vehicle, a first one of the track assemblies being on a first lateral side of the tracked vehicle, a

second one of the track assemblies being on a second lateral side of the tracked vehicle, each track assembly of the plurality of track assemblies being mounted to the frame and comprising:

- i. a plurality of wheels including:
 - a drive wheel; an end wheel spaced apart from the drive wheel in the longitudinal direction of the tracked vehicle; and
 - a plurality of support wheels arranged in an inline configuration between the drive wheel and the end wheel; and
- ii. an endless track disposed around the plurality of wheels for engaging the ground, the endless track comprising:
 - a top run extending between the drive wheel and the end wheel over the support wheels; and
 - a ground-engaging bottom run extending under the support wheels, the drive wheel being in driving engagement with the endless track to impart motion to the endless track.

101. A tracked vehicle comprising:

- a) a chassis comprising a frame extending along a longitudinal direction of the tracked vehicle;
- b) an operator cabin mounted to the frame, the frame comprising a pair of side members extending in an area behind the operator cabin in the longitudinal direction of the tracked vehicle, the pair of side members being spaced apart in a widthwise direction of the tracked vehicle for supporting work equipment carried by the tracked vehicle;
- c) a power plant mounted to the frame and comprising a prime mover; and
- d) a plurality of track assemblies for traction of the tracked vehicle, a first one of the track assemblies being on a first side of the tracked vehicle, a

second one of the track assemblies being on a second side of the tracked vehicle, each track assembly of the plurality of track assemblies being mounted to the frame and comprising:

- i. a plurality of wheels including:
 - a drive wheel;
 - an end wheel spaced apart from the drive wheel in the longitudinal direction of the tracked vehicle; and
 - a plurality of support wheels arranged in an inline configuration between the drive wheel and the end wheel;

the end wheel and one of the support wheels overlapping in the longitudinal direction of the tracked vehicle;

and

- ii. an endless track disposed around the plurality of wheels for engaging the ground, the endless track comprising:
 - a top run extending between the drive wheel and the end wheel over the support wheels; and
 - a ground-engaging bottom run extending under the support wheels, the drive wheel being in driving engagement with the endless track to impart motion to the endless track.

102. The tracked vehicle defined in claim 101, wherein, for each of the track assemblies, the one of the support wheels with which the end wheel overlaps is at the end of the inline configuration of the support wheels.

103. The tracked vehicle defined in claim 101, wherein, for each of the track assemblies, the distance between a center of rotation of the end wheel and a

center of rotation of one of the support wheels is less than a sum of the radius of the end wheel and the radius of the one of the support wheels.

104. The tracked vehicle defined in claim 101, wherein the cabin is off-center along the widthwise direction of the tracked vehicle.
105. The tracked vehicle defined in claim 101, wherein the side members extend beyond the track assemblies both frontwards of and rearwards of the tracked vehicle.
106. The tracked vehicle defined in claim 101, wherein the cabin and the power plant are mounted above the frame.
107. The tracked vehicle defined in claim 101, wherein the side members comprise side rails.
108. A tracked vehicle comprising:
 - a) a chassis comprising a frame extending along a longitudinal direction of the tracked vehicle;
 - b) an operator cabin mounted to the frame, the frame comprising a pair of side members extending in an area behind the operator cabin in the longitudinal direction of the tracked vehicle, the pair of side members being spaced apart in a widthwise direction of the tracked vehicle for supporting work equipment carried by the tracked vehicle;
 - c) a power plant mounted to the frame and comprising a prime mover; and
 - d) a plurality of track assemblies for traction of the tracked vehicle, a first one of the track assemblies being on a first side of the tracked vehicle, a second one of the track assemblies being on a second side of the tracked vehicle, each track assembly of the plurality of track assemblies being mounted to the frame and comprising:

- i. a plurality of wheels including:
 - a drive wheel;
 - an end wheel spaced apart from the drive wheel in the longitudinal direction of the tracked vehicle; and
 - a plurality of support wheels arranged in an inline configuration between the drive wheel and the end wheel;

wherein at least one of the support wheels comprises an inboard support wheel member connected to an outboard support wheel member, the inboard and outboard support wheel members defining a guiding space therebetween;

and

- ii. an endless track disposed around the plurality of wheels for engaging the ground, the endless track comprising:
 - a top run extending between the drive wheel and the end wheel over the support wheels;
 - a ground-engaging bottom run extending under the support wheels, the drive wheel being in driving engagement with the endless track to impart motion to the endless track; and
 - a wheel guide configured to pass through the guiding space of the at least one support wheel as the endless track moves around the plurality of wheels.

109. The tracked vehicle defined in claim 108, wherein for each of the track assemblies, the end wheel and a particular one of the support wheels overlap in the longitudinal direction of the tracked vehicle.

110. The tracked vehicle defined in claim 109, wherein for each of the track assemblies, the particular one of the support wheels is at the end of the inline configuration of the support wheels.
111. The tracked vehicle defined in claim 110, wherein for each of the track assemblies, the end wheel is at least partly within the guiding space of the particular one of the support wheels.
112. The tracked vehicle defined in claim 108, wherein, for each of the track assemblies, the distance between a center of rotation of the end wheel and a center of rotation of one of the support wheels is less than a sum of the radius of the end wheel and the radius of the one of the support wheels.
113. The tracked vehicle defined in claim 108, wherein the cabin is off-center along the widthwise direction of the tracked vehicle.
114. The tracked vehicle defined in claim 108, wherein the side members extend beyond the track assemblies in both frontwards of rearwards of the tracked vehicle.
115. The tracked vehicle defined in claim 108, wherein the cabin and the power plant are mounted above the frame.
116. The tracked vehicle defined in claim 108, wherein the side members comprise side rails.
117. A tracked vehicle comprising:
- a) a chassis comprising a frame extending along a longitudinal direction of the tracked vehicle;
 - b) an operator cabin mounted to the frame and located entirely within a front half of the tracked vehicle, the frame comprising a pair of side members

extending in an area behind the operator cabin in the longitudinal direction of the tracked vehicle, the pair of side members being spaced apart in a widthwise direction of the tracked vehicle for supporting work equipment carried by the tracked vehicle;

- c) a power plant mounted to the frame and comprising a prime mover; and
- d) a plurality of track assemblies for traction of the tracked vehicle, a first one of the track assemblies being on a first side of the tracked vehicle, a second one of the track assemblies being on a second side of the tracked vehicle, each track assembly of the plurality of track assemblies being mounted to the frame and comprising:
 - i. a plurality of wheels including:
 - a first wheel at a first end and a wheel at a second end spaced apart from the first wheel in the longitudinal direction of the tracked vehicle; and
 - a plurality of support wheels arranged in an inline configuration between the first wheel and the second wheel;

at least the first wheel and one of the support wheels overlapping in the longitudinal direction of the tracked vehicle;

and

- ii. an endless track disposed around the plurality of wheels for engaging the ground, the endless track comprising:
 - a top run extending between the first wheel and the second wheel over the support wheels; and
 - a ground-engaging bottom run extending under the support wheels, one of the first wheel and the second wheel being in

driving engagement with the endless track to impart motion to the endless track.

- 118. The tracked vehicle defined in claim 117, wherein a front of each of the track assemblies ends at a point directly underneath the operator cabin.
- 119. The tracked vehicle defined in claim 118, wherein the cabin is off-center along the widthwise direction of the tracked vehicle.
- 120. The tracked vehicle defined in claim 119, wherein the cabin and the power plant are mounted above the frame.
- 121. The tracked vehicle defined in claim 117, wherein the first wheel of each of the track assemblies is an idler wheel.
- 122. The tracked vehicle defined in claim 117, wherein the first wheel of each of the track assemblies is a drive wheel.
- 123. The tracked vehicle defined in claim 117, wherein the first wheel of each of the track assemblies is furthest to the rear of the plurality of wheels.
- 124. The tracked vehicle defined in claim 117, wherein, for each of the track assemblies, the distance between a center of rotation of the first wheel and a center of rotation of one of the support wheels is less than a sum of the radius of the first wheel and the radius of the one of the support wheels with which it overlaps.
- 125. The tracked vehicle defined in claim 117, wherein the side members extend beyond the track assemblies frontwards or rearwards of the tracked vehicle.
- 126. The tracked vehicle defined in claim 125, wherein the side members comprise side rails.

127. The tracked vehicle defined in claim 101, wherein each of the endless tracks has an elastomeric body.
128. The tracked vehicle defined in claim 127, wherein the elastomeric body of each of the endless tracks comprises elastomeric material.
129. The tracked vehicle defined in claim 128, wherein each of the endless tracks comprises a plurality of spaced-apart cores embedded in the elastomeric material of the body of the respective track.
130. The tracked vehicle defined in claim 129, wherein the cores extend in a direction transverse to the longitudinal direction of the tracked vehicle.
131. The tracked vehicle defined in claim 101, wherein each of the endless tracks is a metal-embedded rubber track (MERT).
132. The tracked vehicle defined in claim 108, wherein each of the endless tracks has an elastomeric body.
133. The tracked vehicle defined in claim 132, wherein the elastomeric body of each of the endless tracks comprises elastomeric material.
134. The tracked vehicle defined in claim 133, wherein each of the endless tracks comprises a plurality of spaced-apart cores embedded in the elastomeric material of the body of the respective track.
135. The tracked vehicle defined in claim 134, wherein the cores extend in a direction transverse to the longitudinal direction of the tracked vehicle.
136. The tracked vehicle defined in claim 108, wherein each of the endless tracks is a metal-embedded rubber track (MERT).

137. The tracked vehicle defined in claim 117, wherein each of the endless tracks has an elastomeric body.
138. The tracked vehicle defined in claim 137, wherein the elastomeric body of each of the endless tracks comprises elastomeric material.
139. The tracked vehicle defined in claim 138, wherein each of the endless tracks comprises a plurality of spaced-apart cores embedded in the elastomeric material of the body of the respective track.
140. The tracked vehicle defined in claim 139, wherein the cores extend in a direction transverse to the longitudinal direction of the tracked vehicle.
141. The tracked vehicle defined in claim 117, wherein each of the endless tracks is a metal-embedded rubber track (MERT).
142. A tracked vehicle comprising:
- a. a frame comprising a pair of side members extending in a longitudinal direction of the tracked vehicle and being spaced apart in a widthwise direction of the tracked vehicle for supporting work equipment, each side member of the pair of side members having a respective uppermost surface;
 - b. a first track assembly and a second track assembly for traction of the tracked vehicle, the first track assembly being on a first side of the tracked vehicle, the second track assembly being on a second side of the tracked vehicle, each of the track assemblies being mounted to the frame and comprising, respectively:
 - (i) a plurality of wheels including: a drive wheel; an end wheel spaced apart from the drive wheel in the longitudinal direction; and a plurality of support wheels arranged in an

inline configuration between the drive wheel and the end wheel; and

(ii) an endless track disposed around the plurality of wheels for engaging the ground, the endless track comprising:

I. a top run extending between the drive wheel and the end wheel over the support wheels; and

II. a ground-engaging bottom run extending under the support wheels, the drive wheel being in driving engagement with the endless track to impart motion to the endless track;

c. an operator cabin mounted to the frame and comprising a floor, wherein an entirety of the floor is at a higher elevation, with respect to the bottom run of each of the track assemblies, than the uppermost surface of each of the side members, wherein the operator cabin extends in the longitudinal direction, and wherein each of the side members extends in the longitudinal direction past the operator cabin; and

d. an internal combustion engine mounted to the frame, wherein an entirety of the internal combustion engine is at a higher elevation, with respect to the bottom run of each of the track assemblies, than the uppermost surface of each of the side members, and wherein at least a portion of the internal combustion engine overlies at least a portion of at least one of the track assemblies.

143. The tracked vehicle defined in claim 142, wherein at least part of the operator cabin is located directly above at least part of one of the track assemblies.

144. The tracked vehicle defined in claim 142 or 143, wherein a portion of the internal combustion engine that overlies the at least a portion of at least one of the track assemblies is located in an area rearwards of the operator cabin in the longitudinal direction.

145. The tracked vehicle defined in any one of claims 142 to 144, further comprising a housing on two sides of the operator cabin, the housing covering the internal combustion engine.
146. The tracked vehicle defined in claim 145, wherein the housing is L-shaped when viewed from above the tracked vehicle.

1/49




FIG. 1

2/29




FIG. 2




FIG. 3

4/49




FIG. 4

5/49




FIG. 5




FIG. 6




FIG. 7




FIG. 8






FIG. 9

FIG. 10



11/49

FIG. 11






FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16

17/49




FIG. 17

18/49





FIG. 18






FIG. 20




FIG. 21




FIG. 22

23/49




FIG. 23

24/49




FIG. 24

25/49




FIG. 25

26/49




FIG. 26

27/49




FIG. 27

28/49




FIG. 28








FIG. 29



31/49





32/49




33/49

FIG. 34



**FIG. 35**

35/49

**FIG. 36**




FIG. 37





FIG. 38



39/49





FIG. 40



41/49





FIG. 42


42/49

FIG. 43



43/49

FIG. 44






FIG. 45

45/49




FIG. 46






FIG. 47

47/49

**FIG. 48**

48/49

**FIG. 49**




FIG. 50

