



US009527614B1

(12) **United States Patent**
Kilgore et al.

(10) **Patent No.:** **US 9,527,614 B1**
(45) **Date of Patent:** ***Dec. 27, 2016**

(54) **METHOD OF PACKAGING CAMERA
FACILITATING EASE OF INSTALLATION**

(71) Applicant: **GOOGLE INC.**, Mountain View, CA
(US)

(72) Inventors: **Adam Scott Kilgore**, San Rafael, CA
(US); **Adam Duckworth Mittleman**,
Redwood City, CA (US); **Francois
Rybarczyk**, San Francisco, CA (US);
Jason Evans Goulden, Los Gatos, CA
(US); **Michael Joseph Solomon**, Foster
City, CA (US)

(73) Assignee: **GOOGLE INC.**, Mountain View, CA
(US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

This patent is subject to a terminal dis-
claimer.

(21) Appl. No.: **15/097,211**

(22) Filed: **Apr. 12, 2016**

Related U.S. Application Data

(63) Continuation of application No. 14/738,882, filed on
Jun. 13, 2015, now Pat. No. 9,309,012.

(51) **Int. Cl.**
B65B 5/04 (2006.01)
B65D 85/00 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC . **B65B 5/04** (2013.01); **F16B 1/00** (2013.01);
F16M 11/126 (2013.01); **F16M 11/16**
(2013.01);
(Continued)

(58) **Field of Classification Search**

CPC . B65B 5/04; B65D 2585/6835; F16M 11/126;
F16M 11/14; F16M 11/2078

(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

77,996 A 12/1904 Applegate
2,833,849 A 5/1958 Abel

(Continued)

FOREIGN PATENT DOCUMENTS

DE 9407862 U1 9/1995
DE 202012101588 7/2012
WO WO 2013/133461 9/2013



Primary Examiner — Stephen F Gerrity

(74) *Attorney, Agent, or Firm* — Morgan, Lewis &
Bockius LLP

(57) **ABSTRACT**

This application is directed to packaging a camera product. A base is attached to a holding element that is configured to physically hold a camera and includes a holding element fastener structure. The holding element fastener structure is configured to mate with a base fastener structure associated with the base, providing both a first degree of freedom of motion and a second degree of freedom of motion for the holding element relative to the base. The holding element is rotated in a first direction via the first degree of freedom until the holding element reaches a first nominal position. The holding element is rotated in a second direction via the second degree of freedom until the holding element reaches a second nominal position. The holding element is configured to lie substantially in parallel with a planar surface of the base when it is rotated along the first and second directions.

20 Claims, 28 Drawing Sheets



(51)	Int. Cl.		6,474,471 B1 *	11/2002	Miyake	B65D 75/32 206/316.2
	<i>F16M 11/12</i>	(2006.01)	D498,624 S	11/2004	Chen	
	<i>F16M 11/20</i>	(2006.01)	7,126,556 B1	10/2006	Wang	
	<i>F16B 1/00</i>	(2006.01)	D537,668 S	3/2007	Murray	
	<i>F16M 13/00</i>	(2006.01)	7,298,969 B2	11/2007	Elberbaum	
	<i>F16M 11/24</i>	(2006.01)	7,303,171 B1	12/2007	Chen	
	<i>F16M 11/16</i>	(2006.01)	D569,713 S	5/2008	Sandidge	
(52)	U.S. Cl.		7,559,518 B2	7/2009	Ye	
	CPC	<i>F16M 11/2064</i> (2013.01); <i>F16M 11/242</i> (2013.01); <i>F16M 13/005</i> (2013.01); <i>B65D</i> <i>2585/6835</i> (2013.01); <i>F16B 2001/0035</i> (2013.01)	D621,077 S	8/2010	Fleischman	
			8,072,536 B1	12/2011	Campbell	
			8,511,625 B2	8/2013	Stefan	
			8,596,890 B2	12/2013	Yim et al.	
			D700,504 S	3/2014	Blocker	
			D719,605 S	12/2014	Dordick	
(58)	Field of Classification Search		8,902,355 B2	12/2014	Dudkowski	
	USPC	53/429, 472, 473; 206/316.2, 320, 471, 206/701, 722-724; 248/521, 528, 136, 188.6, 248/315	D726,806 S	4/2015	Demars	
	See application file for complete search history.		8,998,512 B1	4/2015	Celler	
			9,057,934 B2	6/2015	Lelky et al.	
			9,309,012 B1 *	4/2016	Kilgore et al.	B65B 5/04
			9,327,851 B1 *	5/2016	Kilgore et al.	F16M 11/2064
			9,377,157 B1 *	6/2016	Kilgore et al.	F16M 11/2064
			9,388,934 B1 *	7/2016	Kilgore et al.	F16M 11/2064
			9,415,921 B2 *	8/2016	Marchetti et al.	B65B 5/04
(56)	References Cited		9,423,672 B1 *	8/2016	Kilgore et al.	F16M 11/2064
	U.S. PATENT DOCUMENTS		2001/0020975 A1	9/2001	Kerai et al.	
	3,138,661 A	6/1964 Grashow	2003/0161623 A1	8/2003	Saruhashi	
	3,428,286 A	2/1969 Del Pesco	2003/0201371 A1 *	10/2003	Zadok	B65D 83/525 248/276.1
	3,626,421 A	12/1971 Santana et al.	2005/0122424 A1	6/2005	Overstreet	
	4,336,916 A	6/1982 Blanchard	2006/0113214 A1	6/2006	Shimizu et al.	
	4,739,353 A *	4/1988 Heuer et al.	2007/0278366 A1	12/2007	McGill	
			2007/0284496 A1	12/2007	Yokota	
	4,804,984 A *	2/1989 Heuer et al.	2008/0061199 A1	3/2008	Chen	
			2008/0068493 A1	3/2008	Hida et al.	
	4,953,698 A	9/1990 Gregorich et al.	2008/0093514 A1	4/2008	Carnevali	
	D367,418 S	2/1996 Lathrop	2009/0308993 A1	12/2009	Chang	
	5,523,934 A	6/1996 Dworman et al.	2011/0163211 A1	7/2011	Cicco	
	5,597,149 A	1/1997 Hodge	2012/0043439 A1	2/2012	Liao	
	5,649,256 A	7/1997 Wen	2013/0010143 A1	1/2013	Phillips	
	5,738,321 A	4/1998 Moriyasu	2013/0244816 A1	9/2013	Lignelli et al.	
	5,764,194 A	6/1998 Brown	2013/0270317 A1	10/2013	Wang	
	6,042,080 A	3/2000 Shepherd et al.	2013/0292531 A1	11/2013	Schaefer et al.	
	D429,998 S	8/2000 Snell	2014/0226061 A1	8/2014	Kuehl et al.	
	D445,819 S	7/2001 Backs et al.				
	6,357,936 B1 *	3/2002 Elberbaum				
	D465,188 S	11/2002 McCoy et al.				

* cited by examiner




Figure 1




Figure 2A






Figure 2B






Figure 4A




Figure 4B




Figure 4C




Figure 5




Figure 6A




Figure 6B




Figure 6C




Figure 6D




Figure 6E




Figure 6F




Figure 7A




Figure 7B




Figure 7C




Figure 7D




Figure 7E




Figure 7F




Figure 8A




Figure 8B




Figure 8C




Figure 9A




Figure 9B




Figure 10A




Figure 10B




Figure 11




Figure 12A




Figure 12B




Figure 12C




Figure 13A




Figure 13B




Figure 13C




Figure 14A




Figure 14C

Figure 14B




Figure 14D




Figure 14E




Figure 14F




Figure 15




Figure 16




Figure 17

METHOD OF PACKAGING CAMERA FACILITATING EASE OF INSTALLATION

RELATED APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 14/738,882, filed Jun. 13, 2015, entitled "Method of Packaging Camera Facilitating Ease of Installation," which is hereby incorporated by reference in its entirety.

This application is related to U.S. patent application Ser. No. 14/738,915, filed Jun. 14, 2015, entitled "Method of Packaging Camera Facilitating Ease of Installation," which is hereby incorporated by reference in its entirety.

This application is also related to U.S. patent application Ser. No. 14/738,880, filed Jun. 13, 2015, entitled "Camera Stand Having Constant Resistance For A Portion Of A Range Of Motion Along An Axis Of Rotation," U.S. patent application Ser. No. 14/738,885, filed Jun. 13, 2015, entitled "Camera Stand Having an Unlimited Range of Motion Along an Axis of Rotation," U.S. patent application Ser. No. 14/738,911, filed Jun. 14, 2015, entitled "Camera Stand Having Constant Resistance for a Portion of a Range of Motion Along an Axis of Rotation," and U.S. patent application Ser. No. 14/738,912, filed Jun. 14, 2015, entitled "Camera Stand Having an Unlimited Range of Motion Along an Axis of Rotation," all of which are hereby incorporated by reference in their entirety.

TECHNICAL FIELD

This relates generally to an assembly, including but not limited to methods and systems for mechanically supporting an electronic device and providing one or more degrees of freedom of motion to the electronic device.

BACKGROUND

A smart home environment is created at a venue by integrating a plurality of smart devices, including intelligent, multi-sensing, network-connected devices, seamlessly with each other in a local area network and/or with a central server or a cloud-computing system to provide a variety of useful smart home functions. Sometimes, the smart home environment includes one or more network-connected cameras that are configured to provide video monitoring and security in the smart home environment. These smart devices (e.g., the network-connected cameras) are normally placed on surfaces or mounted on walls at different locations of the smart home environment. As such, each smart device must include a base that could match and come into contact with different types of surfaces including a desktop, the wall or other surfaces. It would be beneficial to mechanically couple a smart device to its base in a compact and robust manner, while maintaining at least one or more degrees of freedom of motion for the smart device.

SUMMARY

Accordingly, there is a need for a compact and robust stand assembly that can support an electronic device and provide one or more degrees of freedom of motion to the electronic device. In various implementations of this application, a module (i.e., an electronic device) is mounted on a stand assembly that further includes a receiving element and a base assembly. The receiving element physically receives the module and is mechanically coupled to the base assembly

by using matching fastener structures. The base assembly further includes a base shaped to rest against a supporting surface, and a joint where one of the matching fastener structures is located. The matching fastener structures and the joint of the stand are configured to provide two independent degrees of freedom of motion of the receiving element with respect to the base of the base assembly.

In accordance with one aspect of this application, a stand assembly includes a receiving element for physically receiving a module, and a base assembly for supporting the receiving element. The receiving element further includes a module holding structure configured to hold the module, an extended portion that extends from the module holding structure, and a first fastener structure coupled to an end of the extended portion located opposite another end of the extended portion that extends from the module holding structure. The base assembly further includes a base shaped to rest against a supporting surface, and a second fastener structure coupled to the base at a joint, and the second fastener structure is configured to mate with the first fastener structure. The first fastener structure and the joint are configured to provide a first degree of freedom of motion and a second degree of freedom of motion of the receiving element with respect to the base, respectively. The movement of the receiving element at the first degree of freedom has substantially consistent resistance through first part of a first full range of motion associated with the first degree of freedom of motion, and the movement of the receiving element at the second degree of freedom has substantially consistent resistance through a second full range of motion associated with the second degree of freedom.

In accordance with another aspect of this application, a stand assembly includes a receiving element for physically receiving a module, and a base assembly for supporting the receiving element. The receiving element further includes a module holding structure configured to hold the module, an extended portion that extends from the module holding structure, and a first fastener structure coupled to an end of the extended portion located opposite another end of the extended portion that extends from the module holding structure. The base assembly further includes a base shaped to rest against a supporting surface, and a second fastener structure coupled to the base at a joint, and the second fastener structure is configured to mate with the first fastener structure. The first fastener structure and the joint are configured to provide a first degree of freedom of motion and a second degree of freedom of motion of the receiving element with respect to the base, respectively. The movement of the receiving element at the first degree of freedom is unlimited in a first direction of travel associated with the first degree of freedom, and the movement of the receiving element at the second degree of freedom is limited in a direction of travel associated with the second degree of freedom.

In some implementations, the first degree of freedom is associated with a reverse direction of travel that is opposite to the first direction of travel associated with the unlimited movement at the first degree of freedom, and the first and second fastener structures are unfastened when the receiving element moves with respect to the base assembly in the reverse direction of travel associated with the first degree of freedom.

In accordance with an aspect of this application, a method of packaging an assembly includes providing a base assembly that includes a base and a second fastener structure. The second fastener structure is coupled to the base at a joint.

The method of packaging the assembly further includes attaching to the base assembly a receiving element that is configured to physically receive a module and includes a first fastener structure. Attaching to the base assembly the receiving element further includes tightening the first fastener structure onto the second fastener structure until the first fastener structure reaches a tightened position. The first fastener structure of the receiving element and the joint of the base assembly are configured to provide a first degree of freedom of motion and a second degree of freedom of motion of the receiving element with respect to the base assembly, respectively. The method of packaging the assembly further includes after determining that the first fastener structure reaches the tightened position, rotating the receiving element reversely at the first degree of freedom of motion by a first angle to orient the receiving element to a nominal position. At the nominal position, the receiving element and the module received thereby are configured to face substantially up when they are flipped down via the joint at the second degree of freedom of motion.

In accordance with another aspect of this application, a method of packaging an assembly includes providing a base assembly that includes a base and a second fastener structure. The second fastener structure is coupled to the base at a joint. The method of packaging the assembly further includes attaching to the base assembly a receiving element that is configured to physically receive a module and includes a first fastener structure. The first fastener structure is configured to mate with the second fastener structure and provide a first degree of freedom of motion of the receiving element with respect to the base, and the movement of the receiving element at the first degree of freedom is unlimited in a first direction of travel associated with the first degree of freedom of motion. The joint is configured to provide a second degree of freedom of motion of the receiving element with respect to the base. The method of packaging the assembly further includes rotating the receiving element along the first direction of travel associated with the first degree of freedom until the receiving element reaches a nominal position. At the nominal position, the receiving element and the module received thereby are configured to face substantially up when they are flipped down via the joint at the second degree of freedom of motion.

BRIEF DESCRIPTION OF THE DRAWINGS

For a better understanding of the various described implementations, reference should be made to the Description of Implementations below, in conjunction with the following drawings in which like reference numerals refer to corresponding parts throughout the figures.

FIG. 1 is an example smart home environment in accordance with some implementations.

FIG. 2A is a perspective view of a camera assembly that includes a stand assembly and a camera module in accordance with some implementations.

FIG. 2B is a block diagram of a camera assembly shown in FIG. 2A in accordance with some implementations.

FIGS. 3A-3D illustrate a perspective view, a front view, a rear view and a side view of a camera module in accordance with some implementations, respectively.

FIG. 4A is a perspective view of a stand assembly for supporting a module (e.g., a camera module) in accordance with some implementations.

FIG. 4B illustrates a stand assembly that is decoupled to a receiving element and a base assembly in accordance with some implementations.

FIG. 4C illustrates a stand assembly that includes fastener structures for mechanically coupling a receiving element to a base assembly in accordance with some implementations.

FIG. 5 is an exploded view of a stand assembly for supporting a sensor module in accordance with some implementations.

FIGS. 6A-6F illustrate three positions of a receiving element when the receiving element is twisted with respect to a base assembly at a first degree of freedom of motion in accordance with some implementation.

FIG. 7A is a side view of a stand assembly in accordance with some implementations.

FIG. 7B is a cross sectional view of cross section A-A' of the stand assembly shown in FIG. 7A.

FIG. 7C is an enlarged view of two fastener structures that couple a receiving element to a base assembly in the stand assembly shown in FIGS. 7A and 7B in accordance with some implementations.

FIGS. 7D, 7E and 7F illustrate an exploded view, a cross-sectional view (cross section A-A'), and a side view of a joint of a stand assembly shown in FIG. 7B in accordance with some implementations, respectively.

FIG. 8A illustrates another exemplary stand assembly in which movement of a receiving element with respect to a base assembly is unlimited in a direction of travel associated with a first degree of freedom of motion in accordance with some implementations.

FIG. 8B is an exploded view of a receiving element that has an unlimited movement range in a direction of travel associated with a first degree of freedom of motion as shown in FIG. 8A in accordance with some implementations.

FIG. 8C is a cross sectional view of fastener structures of a stand assembly that enable an unlimited movement range in a direction of travel associated with a first degree of freedom of motion as shown in FIG. 8A in accordance with some implementations.

FIG. 9A illustrate another exemplary stand assembly in which movement of a receiving element with respect to a base assembly is limited at a second degree of freedom of motion in accordance with some implementations.

FIG. 9B is an exploded view of a joint that is assembled onto a hinge carrier to provide to a receiving element a limited movement range at a second degree of freedom of motion shown in FIG. 9A in accordance with some implementations.

FIGS. 10A and 10B illustrate a process for assembling a stand assembly in accordance with some implementations.

FIG. 11 is an exploded view of a stand assembly that includes a magnet plate in its base assembly in accordance with some implementations.

FIG. 12A illustrates a mount structure or mounting a stand assembly onto a mounting surface in accordance with some implementations.

FIG. 12B illustrates another exemplary mount structure onto which a detachable foam plate is attached in accordance with some implementations.

FIG. 12C is an exploded view of a stand assembly, a detachable foam plate and a mount structure in accordance with some implementations.

FIG. 13A is an exploded view of a stand assembly, a cable guide ring and a mount structure that function together to support a module on a mounting surface in accordance with some implementations.

FIG. 13B illustrates another mount structure in accordance with some implementations.

FIG. 13C illustrates a cable guide ring in accordance with some implementations.

5

FIG. 14A is a top view of a camera assembly in which a receiving element and a camera module 204 mounted thereon are packaged in accordance with some implementations.

FIGS. 14B-14F illustrate a packaging process for packaging a camera assembly as shown in FIG. 14A and its accessories in a multilayer shipping package in accordance with some implementations.

FIG. 15 illustrates a receiving element that is mechanically coupled on a standard tripod in accordance with some implementations.

FIG. 16 is a flow chart of a method for packaging a stand assembly configured to support a module (e.g., a camera module) in accordance with some implementations.

FIG. 17 is a flow chart of another exemplary method for packaging a stand assembly configured for supporting a module (e.g., a camera module) in accordance with some implementations.

Like reference numerals refer to corresponding parts throughout the several views of the drawings.

DESCRIPTION OF IMPLEMENTATIONS

In accordance with various implementations of the present invention, a stand assembly is applied to support an electronic device at different locations in a smart home environment. The electronic device includes, but is not limited to, a surveillance camera, a microphone, a speaker, a thermostat, a hazard detector, or other types of smart devices. The stand assembly includes a receiving element for physically receiving the electronic device, and a base assembly for supporting the receiving element and the electronic device mounted thereon. The stand assembly is configured to provide at least two degrees of freedom of motion such that the receiving element and the electronic device mounted thereon can be oriented differently with respect to the base assembly. In some implementations, the two degrees of freedom of motion allow the receiving element and the electronic device mounted thereon to flip down and lie substantially in parallel with a bottom surface of the base assembly, and therefore, the stand assembly and the electronic device can be packaged within a shipping box in a compact, reliable and consistent manner. Also, such consistent packaging ensures that the electronic device when removed from a package will provide an optimal and consistent range of adjustability to reduce customer frustration and improve likelihood of customer success with the product. Further, in some implementations, the stand assembly offers a high aesthetic level in product design by hiding fastener structures used to assemble the stand assembly and rendering them structurally invisible to a user of the electronic device.

FIG. 1 is an example smart home environment 100 in accordance with some implementations. The smart home environment 100 includes a structure 150 (e.g., a house, office building, garage, or mobile home) with various integrated devices. It will be appreciated that devices may also be integrated into a smart home environment 100 that does not include an entire structure 150, such as an apartment, condominium, or office space. Further, the smart home environment 100 may control and/or be coupled to devices outside of the actual structure 150. Indeed, several devices in the smart home environment 100 need not be physically within the structure 150. For example, a device controlling a pool heater 114 or irrigation system 116 may be located outside of the structure 150.

6

The depicted structure 150 includes a plurality of rooms 152, separated at least partly from each other via walls 154. The walls 154 may include interior walls or exterior walls. Each room may further include a floor 156 and a ceiling 158. Devices may be mounted on, integrated with and/or supported by a wall 154, floor 156 or ceiling 158.

In some implementations, the integrated devices of the smart home environment 100 include intelligent, multi-sensing, network-connected devices that integrate seamlessly with each other in a smart home network and/or with a central server or a cloud-computing system to provide a variety of useful smart home functions. The smart home environment 100 may include one or more intelligent, multi-sensing, network-connected thermostats 102 (hereinafter referred to as “smart thermostats 102”), one or more intelligent, network-connected, multi-sensing hazard detection units 104 (hereinafter referred to as “smart hazard detectors 104”), one or more intelligent, multi-sensing, network-connected entryway interface devices 106 and 120 (hereinafter referred to as “smart doorbells 106” and “smart door locks 120”), and one or more intelligent, multi-sensing, network-connected alarm systems 122 (hereinafter referred to as “smart alarm systems 122”).

In some implementations, the one or more smart thermostats 102 detect ambient climate characteristics (e.g., temperature and/or humidity) and control a HVAC system 103 accordingly. For example, a respective smart thermostat 102 includes an ambient temperature sensor.

The one or more smart hazard detectors 104 may include thermal radiation sensors directed at respective heat sources (e.g., a stove, oven, other appliances, a fireplace, etc.). For example, a smart hazard detector 104 in a kitchen 153 includes a thermal radiation sensor directed at a stove/oven 112. A thermal radiation sensor may determine the temperature of the respective heat source (or a portion thereof) at which it is directed and may provide corresponding black-body radiation data as output.

The smart doorbell 106 and/or the smart door lock 120 may detect a person's approach to or departure from a location (e.g., an outer door), control doorbell/door locking functionality (e.g., receive user inputs from a portable electronic device 166-1 to actuate bolt of the smart door lock 120), announce a person's approach or departure via audio or visual means, and/or control settings on a security system (e.g., to activate or deactivate the security system when occupants go and come).

The smart alarm system 122 may detect the presence of an individual within close proximity (e.g., using built-in IR sensors), sound an alarm (e.g., through a built-in speaker, or by sending commands to one or more external speakers), and send notifications to entities or users within/outside of the smart home network 100. In some implementations, the smart alarm system 122 also includes one or more input devices or sensors (e.g., keypad, biometric scanner, NFC transceiver, microphone) for verifying the identity of a user, and one or more output devices (e.g., display, speaker). In some implementations, the smart alarm system 122 may also be set to an “armed” mode, such that detection of a trigger condition or event causes the alarm to be sounded unless a disarming action is performed.

In some implementations, the smart home environment 100 includes one or more intelligent, multi-sensing, network-connected wall switches 108 (hereinafter referred to as “smart wall switches 108”), along with one or more intelligent, multi-sensing, network-connected wall plug interfaces 110 (hereinafter referred to as “smart wall plugs 110”).

The smart wall switches **108** may detect ambient lighting conditions, detect room-occupancy states, and control a power and/or dim state of one or more lights. In some instances, smart wall switches **108** may also control a power state or speed of a fan, such as a ceiling fan. The smart wall plugs **110** may detect occupancy of a room or enclosure and control supply of power to one or more wall plugs (e.g., such that power is not supplied to the plug if nobody is at home).

In some implementations, the smart home environment **100** of FIG. **1** includes a plurality of intelligent, multi-sensing, network-connected appliances **112** (hereinafter referred to as “smart appliances **112**”), such as refrigerators, stoves, ovens, televisions, washers, dryers, lights, stereos, intercom systems, garage-door openers, floor fans, ceiling fans, wall air conditioners, pool heaters, irrigation systems, security systems, space heaters, window AC units, motorized duct vents, and so forth. In some implementations, when plugged in, an appliance may announce itself to the smart home network, such as by indicating what type of appliance it is, and it may automatically integrate with the controls of the smart home. Such communication by the appliance to the smart home may be facilitated by either a wired or wireless communication protocol. The smart home may also include a variety of non-communicating legacy appliances **140**, such as old conventional washer/dryers, refrigerators, and the like, which may be controlled by smart wall plugs **110**. The smart home environment **100** may further include a variety of partially communicating legacy appliances **142**, such as infrared (“IR”) controlled wall air conditioners or other IR-controlled devices, which may be controlled by IR signals provided by the smart hazard detectors **104** or the smart wall switches **108**.

In some implementations, the smart home environment **100** includes one or more network-connected cameras **118** that are configured to provide video monitoring and security in the smart home environment **100**. The cameras **118** may be used to determine occupancy of the structure **150** and/or particular rooms **152** in the structure **150**, and thus may act as occupancy sensors. For example, video captured by the cameras **118** may be processed to identify the presence of an occupant in the structure **150** (e.g., in a particular room **152**). Specific individuals may be identified based, for example, on their appearance (e.g., height, face) and/or movement (e.g., their walk/gait). Cameras **118** may additionally include one or more sensors (e.g., IR sensors, motion detectors), input devices (e.g., microphone for capturing audio), and output devices (e.g., speaker for outputting audio).

Alternatively, in some implementations, the smart home environment **100** includes one or more network-connected microphone device **124** that are configured to capture audio and provide security functions in the smart home environment **100**. Optionally, the microphone device **124** is a stand-alone device that is not included in any other smart device, and can be regarded as a type of smart home device in this application. Optionally, the microphone device **124** is part of another client device **502** or another smart electronic device other than the cameras **118**. The microphone device **124** may be used to determine occupancy of the structure **150** and/or particular rooms **152** in the structure **150**, and thus may act as occupancy sensors. Specifically, audio captured by the microphone device **124** may be processed to identify the presence of an occupant in the structure **150** (e.g., in a particular room **152**). Specific individuals may be identified based, for example, on characteristic of their voices.

In some implementations, audio captured by the microphones in the cameras **118** or the microphone device **124**

may also be processed to identify audio features (e.g., a baby sound), and relevant signature events (e.g., a baby cry event) when the audio features meet predetermined criteria.

The smart home environment **100** may additionally or alternatively include one or more other occupancy sensors (e.g., the smart doorbell **106**, smart door locks **120**, touch screens, IR sensors, microphones, ambient light sensors, motion detectors, smart nightlights **170**, etc.). In some implementations, the smart home environment **100** includes radio-frequency identification (RFID) readers (e.g., in each room **152** or a portion thereof) that determine occupancy based on RFID tags located on or embedded in occupants. For example, RFID readers may be integrated into the smart hazard detectors **104**.

The smart home environment **100** may also include communication with devices outside of the physical home but within a proximate geographical range of the home. For example, the smart home environment **100** may include a pool heater monitor **114** that communicates a current pool temperature to other devices within the smart home environment **100** and/or receives commands for controlling the pool temperature. Similarly, the smart home environment **100** may include an irrigation monitor **116** that communicates information regarding irrigation systems within the smart home environment **100** and/or receives control information for controlling such irrigation systems.

By virtue of network connectivity, one or more of the smart home devices of FIG. **1** may further allow a user to interact with the device even if the user is not proximate to the device. For example, a user may communicate with a device using a computer (e.g., a desktop computer, laptop computer, or tablet) or other portable electronic device **166** (e.g., a mobile phone, such as a smart phone). A webpage or application may be configured to receive communications from the user and control the device based on the communications and/or to present information about the device's operation to the user. For example, the user may view a current set point temperature for a device (e.g., a stove) and adjust it using a computer. The user may be in the structure during this remote communication or outside the structure.

As discussed above, users may control smart devices in the smart home environment **100** using a network-connected computer or portable electronic device **166**. In some examples, some or all of the occupants (e.g., individuals who live in the home) may register their device **166** with the smart home environment **100**. Such registration may be made at a central server to authenticate the occupant and/or the device as being associated with the home and to give permission to the occupant to use the device to control the smart devices in the home. An occupant may use their registered device **166** to remotely control the smart devices of the home, such as when the occupant is at work or on vacation. The occupant may also use their registered device to control the smart devices when the occupant is actually located inside the home, such as when the occupant is sitting on a couch inside the home. It should be appreciated that instead of or in addition to registering devices **166**, the smart home environment **100** may make inferences about which individuals live in the home and are therefore occupants and which devices **166** are associated with those individuals. As such, the smart home environment may “learn” who is an occupant and permit the devices **166** associated with those individuals to control the smart devices of the home.

In some implementations, in addition to containing processing and sensing capabilities, devices **102**, **104**, **106**, **108**, **110**, **112**, **114**, **116**, **118**, **120**, **122** and/or **124** (collectively referred to as “the smart devices”) are capable of data

communications and information sharing with other smart devices, a central server or cloud-computing system, and/or other devices that are network-connected. Data communications may be carried out using any of a variety of custom or standard wireless protocols (e.g., IEEE 802.15.4, Wi-Fi, ZigBee, 6LoWPAN, Thread, Z-Wave, Bluetooth Smart, ISA100.11a, WirelessHART, MiWi, etc.) and/or any of a variety of custom or standard wired protocols (e.g., Ethernet, HomePlug, etc.), or any other suitable communication protocol, including communication protocols not yet developed as of the filing date of this document.

In some implementations, the smart devices serve as wireless or wired repeaters. In some implementations, a first one of the smart devices communicates with a second one of the smart devices via a wireless router. The smart devices may further communicate with each other via a connection (e.g., network interface 160) to a network, such as the Internet 162. Through the Internet 162, the smart devices may communicate with a smart home provider server system 164 (also called a central server system and/or a cloud-computing system herein). The smart home provider server system 164 may be associated with a manufacturer, support entity, or service provider associated with the smart device(s). In some implementations, a user is able to contact customer support using a smart device itself rather than needing to use other communication means, such as a telephone or Internet-connected computer. In some implementations, software updates are automatically sent from the smart home provider server system 164 to smart devices (e.g., when available, when purchased, or at routine intervals).

In some implementations, the network interface 160 includes a conventional network device (e.g., a router), and the smart home environment 100 of FIG. 1 includes a hub device 180 that is communicatively coupled to the network(s) 162 directly or via the network interface 160. The hub device 180 is further communicatively coupled to one or more of the above intelligent, multi-sensing, network-connected devices (e.g., smart devices of the smart home environment 100). Each of these smart devices optionally communicates with the hub device 180 using one or more radio communication networks available at least in the smart home environment 100 (e.g., ZigBee, Z-Wave, Insteon, Bluetooth, Wi-Fi and other radio communication networks). In some implementations, the hub device 180 and devices coupled with/to the hub device can be controlled and/or interacted with via an application running on a smart phone, household controller, laptop, tablet computer, game console or similar electronic device. In some implementations, a user of such controller application can view status of the hub device or coupled smart devices, configure the hub device to interoperate with smart devices newly introduced to the home network, commission new smart devices, and adjust or view settings of connected smart devices, etc. In some implementations the hub device extends capabilities of low capability smart device to match capabilities of the highly capable smart devices of the same type, integrates functionality of multiple different device types—even across different communication protocols, and is configured to streamline adding of new devices and commissioning of the hub device.

FIG. 2A is a perspective view of a camera assembly 200 that includes a stand assembly 202 and a camera module 204 in accordance with some implementations, and FIG. 2B is a block diagram of a camera assembly 200 shown in FIG. 2A in accordance with some implementations. Referring to FIG. 2B, the stand assembly 202 includes a receiving element 206

for receiving the camera module 204, and a base assembly 208 for supporting the receiving element 206. The base assembly 208 includes a base 210 shaped to rest against a supporting surface, and a joint 212 coupled to the base 210.

The receiving element 206 further includes a module holding structure 214 that is configured to hold the camera module 204 (FIG. 2A). Specifically, in some implementations, the module holding structure 214 includes a cutout opening that has a shape conforming to a contour of the camera module 204, and is configured to hold the camera module 204 when the module is inserted within the cutout opening 204. Alternatively, in some implementations, the cutout opening has a non-conforming shape that is distinct from that associated with the contour of the camera module 204, and the camera module 204 is configured to fit within the non-conforming shape of the cutout opening when the module is inserted within the cutout opening 204. For example, the camera module 204 has a circular contour, and the cutout opening of the module holding structure 214 is associated with a polygon (e.g., a square, a pentagon, a hexagon, etc.) into which the circular contour can fit. In some implementations, the camera module 204 is held onto the receiving element 206 by one or more module fasteners 216 (e.g., a snap). When the module fasteners 216 are depressed, the camera module 204 is removed from the cutout opening of the receiving element 206.

Referring to FIG. 2A, the receiving element 206 and the camera module 204 held thereon have at least two degrees of freedom of motion with respect to the base assembly 208. In accordance with a first degree of freedom of motion, the receiving element 206 and the camera module 204 can be rotated or twisted around a twisting axis 218 that passes through the receiving element 204 and is perpendicular to a planar surface of the base 210 (e.g., a bottom surface of the base 210). In accordance with a second degree of freedom of motion, the receiving element 206 and the camera module 204 can be flipped around a flipping axis 220 that passes through a joint 212 and is laid substantially in parallel to the planar surface of the base 210. In some implementations, when the camera module 204 is held onto the receiving element 206 by the module fasteners 216, it is configured to rotate within the cutout opening around a self rotation axis 222 that passes through a center of the camera module 204.

Optionally, the camera assembly 200 is placed on a desktop surface and sits on the bottom surface of the base 210 of the stand assembly 202. Optionally, the camera assembly 200 further includes a mount structure 224 for mounting the camera assembly 200 onto an alternative mounting surface. An example of the mount structure 224 is a wall mount that is configured to be fixed on a wall surface. When the base assembly 208 of the stand assembly 202 is attached to the mount structure 224, the camera is anchored at the location where the mount structure is fixed. In some implementations, the base assembly 208 and the mount structure 224 are attached to each other by a magnetic attraction force. The base assembly 208 can be rotated freely about its central axis with respect to the mounting structure 224 and can be fixed in place at any angle of rotation with respect to the mounting structure 224 (e.g., by using magnetic attraction as described herein, an adhesive, or mechanical attachment).

Further, in some implementations, the mount structure 224 includes a cable guide structure 226 that is arranged on the edge of the mount structure 224. The cable guide structure 226 is configured to guide a cable 250 or 252 that electrically couples the camera module 204 received in the receiving element 206 to an external power supply 228 or

11

another electronic device **242** (e.g., a computational machine). The camera module **204** is configured to receive power and data from the external power supply **228** and the electronic device **242** using the cables **250** and **252**. Alternatively, in some implementations, power is provided by a cable **250**, while data is provided wirelessly.

In accordance with various implementations of the application, the camera module **204** includes one or more of a camera lens **230**, image sensors **232**, a microphone **234**, a speaker **236**, wireless transceiver circuit **238** and one or more antennas **240**. In some implementations, the camera module **204** includes an HD (e.g., 720p, 1080p, or higher) camera made of the camera lens **230** and one or more high definition image sensors **232**. In some implementations, the camera module **204** includes a microphone and a speaker, such that a person reviewing a live video feed from the camera module **204** can talk in-real to someone being filmed by the camera module **204**. In some implementations, the camera module **204** includes a connection port (e.g., female adapter) to which a connection plug (e.g., male adapter) is able to be coupled to supply power or transfer data. For example, the connection port includes a Universal Serial Bus (USB) port, and is used as an input/output interface via which information about a Wi-Fi network is supplied to the camera module **204** (e.g., the name and password of the Wi-Fi network, an encryption key, etc.). Other examples of the connection port include, but are not limited to, an Ethernet port, a High-Definition Multimedia Interface (HDMI) port, and a Power-over-Ethernet (PoE) port. More details on the geometries, the components and the functions of the camera module **204** are explained below with reference to FIGS. 3A-3D.

In some implementations, the camera module **204** includes a Wi-Fi antenna and a Wi-Fi transceiver for communicating data (e.g., multimedia data captured by the camera module **204**) over a wireless local area network. In some implementations, the camera module **204** includes a Bluetooth antenna and a Bluetooth transceiver coupled to the Bluetooth antenna. The Bluetooth antenna is used to enable communication with a client device (e.g., a mobile phone) for the purposes of provisioning the camera module **204**. In some implementations, the camera module **204** includes a radio antenna and a radio transceiver coupled to the radio antenna. The radio antenna transmits and receives signals according to the IEEE 802.15.4 specifications, and is configured to facilitate communication between the camera module **204** and other smart home devices (e.g., the hub device **180** and the thermostats **102**).

In some implementations, the camera module **204** is associated with a software application and a related user interface displayed on a client device. The user interface is optionally an Internet browser application (e.g., Microsoft's Internet Explorer or Mozilla Firefox) running on a computer or a dedicated and/or downloaded application running on a smart phone. A user is able to view video captured by the camera module **204** remotely and/or via a network from the Internet browser application or the dedicated and/or downloaded mobile application.

It is noted that a stand assembly **202** can be configured to support other electronic devices in the smart home environment **100**, such as thermostats **102**, hazard detectors **104**, doorbells **106**, wall switches **108**, wall plugs **110**, pool heater monitor **114**, irrigation monitor **116**, alarm systems **122**, microphone devices **124**, and other occupancy sensors (e.g., IR sensors, ambient light sensors, motion detectors, etc.).

12

Specifically, the module holding structure **214** of the stand assembly **202** is configured to match the dimension and geometry of the electronic device supported by the stand assembly **202**.

FIGS. 3A-3D illustrate a perspective view, a front view, a rear view and a bottom view of a camera module **204** in accordance with some implementations, respectively. In some implementations, the camera module **204** has a circular contour, and the cutout opening of the receiving element **206** therefore has a circular shape conforming to the contour of the camera module **204** for the purposes of holding the camera module **204**.

In some implementations, the camera module **204** includes a status light **302** that is disposed in the proximity of the camera lens for the purposes of indicating whether the camera module **204** is powered on and/or filming. In some situations, when the status light **302** is in the red color, it indicates that the camera module **204** is powered on but not recording video data, and when the status light **302** is in the green color, it indicates that the camera module **204** is recording video data in real-time. When the status light **302** is powered off, it indicates that the camera module **204** is powered off. It is noted that in some implementations, the power and operation statuses of the camera module **204** are indicated by two or more status lights **302** rather than by the color of a single status light **302**.

In some implementations, the camera module **204** further includes an ambient light detector **308** that senses availability or intensity of ambient light. The resulting information is used to control parameters of the camera lens, enhance image processing of a captured image, or enable alternative illumination modes (e.g., an infrared light illumination mode).

In some implementations, the back of the camera module **204** is carved with a plurality of grooves **304**. The grooves increase friction with the camera module **204** and protect it from slipping to the ground, when the camera module **204** is assembled or disassembled onto the stand assembly **202**. Further, in some implementations, the microphone **234** or the speaker **236** is embedded under the carved grooves on the back of the camera module **204**. In some implementations, the back of the camera module **204** further includes a reset pin **320**. When a user of the camera module **204** presses the reset pin **320**, the camera module **204** is reset to its original status that it has when it is shipped out of factory.

Referring to FIG. 3D, in some implementations, the bottom of the camera module **204** further includes a connection port **306** to which a connection plug is able to be coupled to supply power or transfer data. For example, the connection port **306** includes one or more of a USB port, an Ethernet port, a HDMI port, and a PoE port. The connection port **306** is used as an input/output interface via which information about the Wi-Fi network is supplied to the camera module **204** (e.g., the name and password of the Wi-Fi network, an encryption key, etc.). In another example, the connection port **246** connects to a power cable that electrically couples the camera module **204** to an external power supply. In some implementation, the speaker **236** is disposed on the bottom of the camera module **204**.

It is noted that in the above implementations, the microphone **234**, the speaker **236**, the reset pin **320** and the connection port **306** are arranged on the back or the bottom of the camera module **204** to render a compact form factor. The locations of these components are not limited by the above arrangements, and can be arranged elsewhere, e.g., on the front or the periphery of the camera module **204**.

13

As shown in FIG. 3D, the camera module **204** has a relatively low profile. When it is flipped down around the flipping axis **220** that passes through the joint **212** of the base assembly **208**, the back of the camera module **204** can almost reach a desktop surface or a mounting surface against which the base assembly **208** rests. Under these circumstances, the low profile of the camera module **204** results in a large adjustable angle for the camera module **204**, and allows the camera module **204** to be packaged in a shipping box in a compact manner.

FIG. 4A is a perspective view of a stand assembly **202** for supporting a module (e.g., a camera module **204**) in accordance with some implementations, and FIG. 4B illustrates a stand assembly **202** that is decoupled to a receiving element **206** and a base assembly **208** in accordance with some implementations. Further, FIG. 4C illustrates a stand assembly **202** that includes fastener structures **404** and **406** for mechanically coupling a receiving element **206** to a base assembly **208** in accordance with some implementations.

As explained above, the stand assembly **202** includes the receiving element **206** and the base assembly **208**. The receiving element **206** includes a module holding structure **214** and an extended portion **402** that extends from the module holding structure **214**. In some implementations, the module holding structure **214** is substantially flat. Here, the camera module **204** is removed from the module holding structure **214** of the receiving element **206**. The receiving element **206** further includes a first fastener structure **404** coupled to an end of the extended portion **402** located opposite another end of the extended portion **402** that extends from the module holding structure **214**. In some implementations, the first fastener structure **404** is entirely hidden inside the extended portion **402** when the receiving element **206** is assembled onto the base assembly **208**.

In addition to the base **210**, the base assembly **208** further includes a second fastener structure **406**. As shown in FIG. 4B, in some implementations, the second fastener structure **406** is coupled to the base **210** of the base assembly **208** at a joint **212**. The second fastener structure **406** is configured to mate with the first fastener structure **404**. In a specific example, the first fastener structure **404** includes a screw hole, and the second fastener structure **406** includes a screw structure that matches the screw hole of the first fastener structure **404**. When the first fastener structure **404** is entirely hidden inside the extended portion **402**, both the fastener structures **404** and **406** are structurally invisible to a user when the receiving element **206** is assembled onto the base assembly **208**. As such, in some implementations, the first fastener structure **404** associated with the first degree of freedom of motion is structurally invisible to a user of the stand assembly **202**, and the joint **212** associated with the second degree of freedom of motion is structurally visible to the user of the stand assembly **202**.

FIG. 5 is an exploded view of a stand assembly **202** for supporting a sensor module in accordance with some implementations. As explained above, the stand assembly **202** includes the receiving element **206** and the base assembly **208**. The receiving element **206** includes:

- a module holding structure **214** and an extended portion **402** that are made of a piece of material; and
- a first fastener structure **404**.

The base assembly **208** further includes one or more of the following components:

- a base **210**;
- a second fastener structure **406**;
- one or more joint fasteners **212A-212D** for creating a joint **212** at the base **210**;

14

a hinge carrier **502** where the joint **212** and a magnet plate **504** are mounted;
the magnet plate **504** that is integrated in the base assembly **208**;

- one or more magnet fasteners **506** that fasten the magnet plate **504** to the hinge carrier **502** or the base **210**;
- one or more base fasteners **508** that fasten the hinge carrier **502** to the base **210**;
- a cover plate **510** that is attached to a bottom surface of the base **210** for sealing the hinge carrier **502** and the magnet plate **504** inside the base assembly **208**; and
- one or more rubber patches **512** that are attached to the bottom surface of the base **210** for increasing friction on the bottom surface.

In various implementations of the applications, the first fastener structure **404** and the joint **212** are configured to provide a first degree of freedom of motion and a second degree of freedom of motion of the receiving element **206** with respect to the base **210**, respectively. More details on the methods of assembling the first fastener structure **404** and the joint **212** are explained below with reference to FIGS. 7A-7F, 8A-8C, 9A, and 9B.

In some implementations, the stand assembly **202** further includes a mount structure **224** that is configured be attached and fixed onto a mounting surface using mount fasteners (e.g., screws). At least part of the mount structure **224** is made of magnetically attractable material, such that the stand assembly **202** can be mounted onto a mounting surface when the base **210** of the base assembly **208** magnetically adheres onto the mount structure **224**. Specifically, in some implementations, the mount structure **224** includes:

- a magnetically attractable plate **514** that is configured to adhere to the magnet plate **504** when they are placed in the proximity to or in contact with each other;
- a mount structure **224** that receives the magnetically attractable plate **514** and is configured for being fixed on a mounting surface; and
- one or more mount fasteners **518** that are applied to fasten the mount structure **224** to a mounting surface.

In some implementations, the stand assembly **202** further includes a detachable foam plate **520**. When the detachable foam plate **520** is disposed between the bottom surface of the base **210** and the mount structure **224**, the detachable foam plate **520** increases a distance between the magnet plate **504** of the base assembly **208** and the magnetically attractable plate **514** of the mount structure **224**, and therefore reduces a magnetic attraction force between the base assembly **208** and the mount structure **224**. In some implementations, the magnetic attraction force is relatively large, and it requires a large force to detach the base assembly **208** from the mount structure **224** once they adhere to each other. This detachable foam plate **520** protects the base assembly **208** from magnetically adhering to the mount structure **224** before the mount structure **224** is fixed on a mounting surface, thereby easing the difficulty of handling the stand assembly **202** for a user of the stand assembly **202**.

FIGS. 6A-6C illustrate three example positions of a receiving element **206** when the receiving element **206** is rotated/twisted with respect to a base assembly **208** at a first degree of freedom of motion in accordance with some implementation. The base **210** includes a planar surface (e.g., a bottom surface) for resting against a supporting surface, and the first degree of freedom of motion is associated with twisting of the receiving element **206** with respect to a twisting axis **218** that passes through the receiving element and is perpendicular to the planar surface of the base **210**. The movement of the receiving element **206**

15

at the first degree of freedom has substantially consistent resistance through first part of a first full range of motion associated with the first degree of freedom of motion. In a specific example, the first part of the first full range of motion is associated with a twisting angle that is substantially equal to 90 degrees. Stated another way, the receiving element **206** has a nominal position (FIG. **6B**), and is configured to be twisted up to 45 degrees in either the clockwise or counterclockwise direction to reach two end positions (FIGS. **6A** and **6C**).

FIGS. **6D** and **6E** illustrate two example end positions of a receiving element **206** when the receiving element **206** is rotated/flipped with respect to a base assembly **208** at a second degree of freedom of motion in accordance with some implementation. The base **210** includes a planar surface (e.g., a bottom surface) for resting against a supporting surface, and the second degree of freedom of motion that is enabled by a joint **212** is associated with rotating/flipping of the receiving element **206** with respect to a flipping axis **220** that passes through the joint **212** and is substantially parallel to the planar surface of the base **210**. The movement of the receiving element **206** at the second degree of freedom has substantially consistent resistance through a second full range of motion associated with the second degree of freedom. In a specific example, the receiving element **206** is configured to flip with respect to the flipping axis **220** by an angle that is substantially equal to 180 degrees. Stated another way, the receiving element **206** starts at a nominal position (FIG. **6B**), and is configured to be flipped up to 90 degrees in either the forward or backward direction to reach two end positions (FIGS. **6D** and **6E**).

In some implementations, the nominal position is reached when the module holding structure **214** of the receiving element **206** is arranged to align in parallel or overlap with both the twisting axis **218** and the flipping axis **220**. When the receiving element **206** is flipped at the second degree of freedom of motion to an end position (FIG. **6D** or **6E**), the receiving element **206** and the camera module **204** mounted there on are laid in a substantially flat position, i.e., substantially in parallel with the planar surface of the base **210**. The back of the camera module **204** can almost reach a desktop surface or a mounting surface against which the base assembly **208** rests. Under these circumstances, if the camera module **204** has a low profile, it would obtain a large adjustable angle at the fully flipped end positions, and can also be packaged in a shipping box in a compact manner (see FIGS. **14A-14F**).

FIG. **6F** illustrates a receiving element **206** that is both twisted at the first degree of freedom of motion and rotated at the second degree of freedom of motion in accordance with some implementation. Specifically, in this example, the receiving element **206** is twisted by a first twisting angle in a clockwise direction associated with the first degree of freedom of motion, and flipped by a second flipping angle in a backward direction associated with the second degree of freedom of motion. Optionally, both the first twisting angle and the second flipping angle are measured with reference to the nominal position (FIG. **6B**). Likewise, the clockwise, counterclockwise, forward and backward directions are also described with reference to the nominal position.

FIG. **7A** is a side view of a stand assembly **202** in accordance with some implementations, and FIG. **7B** is a cross sectional view **702** of a cross section A-A' of the stand assembly **202** shown in FIG. **7A**. FIG. **7C** is an enlarged view **704** of a region B shown in FIG. **7B** in accordance with some implementations. The region B includes two fastener structures that couple a receiving element **206** to a base

16

assembly **208** in the stand assembly **202**. FIGS. **7D**, **7E** and **7F** illustrate an exploded view, a cross-sectional view **706** (cross section A-A'), and a side view **708** of a joint **212** of a stand assembly **202** shown in FIG. **7B** in accordance with some implementations, respectively.

As explained above, the receiving element **206** is configured to move with respect to the base **210** at the first degree of freedom of motion when the first fastener structure **404** is fastened onto the second fastener structure **406** of the base assembly **208**. In accordance with the enlarged view of the two fastener structures (FIG. **7C**), the first fastener structure **404** of the receiving element **206** further includes a screw hole **710** and a nylon-like bushing **712** coupled at the end of the screw hole **710**. The screw hole **710** matches a screw structure **714** of the second fastener structure **406**. The screw hole **710** has a predetermined thread length, and provides a second part of the first full range of motion when the first fastener structure **404** is fastened onto the second fastener structure **406** via the screw hole **710** and the screw structure **714**. The nylon-like bushing **712** has a predetermined bushing depth, and provides the first part of the first full range of motion when the first fastener structure **404** is fastened onto the second fastener structure **406** via the screw hole **710** and the screw structure **714**. The second part of the first full range of motion is distinct from the first part of the first full range of motion. As such, the second fastener structure **406** sequentially passes the second part and the first part of the first full range of motion associated with the first degree of freedom of motion, when it is fastened into the first fastener structure **404** of the receiving element **206**.

In some implementations, the nylon-like bushing has a first coefficient of friction that is associated with the substantially consistent resistance through the first part of the first full range of motion, and the screw hole has a second coefficient of friction that is associated with alternative resistance through the second part of the first full range of motion. The alternative resistance through the second part of the first full range of motion is distinct from the substantially consistent resistance through the first part of the first full range of motion.

When the second fastener structure **406** is fully tightened into the screw hole **710** and the nylon-like bushing **712** of the first fastener structure **404**, the first fastener structure **404** is coupled to the second fastener structure **406** at its tightened position. The tightened position of the first fastener structure **404** is associated with an end position (FIG. **6A** or **6C**) that the receiving element **206** has within the first part of the first full range of motion associated with the first degree of freedom of motion.

As shown in FIG. **7D**, in some implementations, the second fastener structure **406** of the base assembly **208** is flattened to have two substantially flat surfaces, such that it can fit into a base opening slot **716** on the base assembly **208**. The second fastener structure **406** includes a screw structure **714** on its top half and a joint hole **718** on its bottom half. While the top half of the second fastener structure **406** is fastened to the first fastener structure **404**, the bottom half of the second fastener structure **406** fits into the base opening slot **716** to form the joint **212** that rotates with respect to the joint hole **718**.

In some implementations, a hinge carrier **720** is used as a platform to create a joint **212**. The joint **212** includes a plurality of joint fasteners, e.g., a first bushing **212A**, a second bushing **212B**, a bevel spring stack **212C** and a hinge screw **212D**. The joint fasteners **212A-212D** together fasten the bottom half of the second fastener structure **406** onto the carrier slot **720** of the hinge carrier **502** to form the joint **212**.

17

Specifically, the first and second bushings **212A** and **212B** are disposed on two sides of the second fastener structure **406**, and between the respective side of the second fastener structure **406** and the carrier slot **710** of the hinge carrier **502**. The first and second bushings **212A** and **212B** provide side to side location and smooth bearing surfaces for the joint **212**. In addition, the bevel spring stack **212C** provides positive tension on the hinge screw **212D**, and creates frictional resistance and torque around a hinge axis **730** when the hinge screw **212D** is tightened through the joint hole **718** and a screw hole **722** on the hinge carrier **502** to form the joint **212**. The hinge axis **730** passes through the center of the joint hole **718** on the second fastener structure **406**, and substantially overlaps the flipping axis **220** associated with the second degree of freedom of motion of the receiving element **206** with respect to the base assembly **208**.

When the hinge carrier **502** is assembled into the base **210**, the screw structure **714** of the second fastener structure **406** extends beyond the base opening slot **716**. The second fastener structure **406** is configured to rotate around the hinge axis **730** while being constrained within the base opening slot **716**. When the screw structure **714** of the second fastener structure **406** is fastened with the first fastener structure **404**, the receiving element **206** is mounted onto the base assembly **208**, and therefore can rotate or flip with respect to its flipping axis **220** (i.e., the hinge axis **730**) to provide the second degree of freedom of motion for a module mounted onto the module holding structure **214**.

FIG. **8A** illustrates another exemplary stand assembly **202** in which movement of a receiving element **206** with respect to a base assembly **208** is unlimited in a direction of travel associated with a first degree of freedom of motion in accordance with some implementations. FIG. **8B** is an exploded view of a receiving element **206** that has an unlimited movement range in a direction of travel associated with a first degree of freedom of motion as shown in FIG. **8A** in accordance with some implementations. FIG. **8C** is a cross sectional view of fastener structures of a stand assembly **202** that enable an unlimited movement range in a direction of travel associated with a first degree of freedom of motion as shown in FIG. **8A** in accordance with some implementations.

The movement of the receiving element **206** at the first degree of freedom is unlimited in a first direction (e.g., a clockwise direction) of travel associated with the first degree of freedom. The first degree of freedom is associated with a reverse direction (e.g., a counterclockwise direction) of travel that is opposite to the first direction of travel associated with the unlimited movement at the first degree of freedom, and the first and second fastener structures **404** and **406** are unfastened when the receiving element **206** moves with respect to the base assembly **208** in the reverse direction of travel associated with the first degree of freedom. As such, in some implementations, a user of the stand assembly **202** is required to adjust the orientation of the module mounted onto the receiving element **206** by twisting the receiving element **206** only in the first direction of travel.

Referring to FIGS. **8B** and **8C**, in some implementations, the first fastener structure **404** further includes a shoulder screw **802**, a sleeve bushing **804**, a spring washer **806**, and a collar **808**. The collar **808** is fastened inside the sleeve bushing **804** to provide a screw hole that matches a screw structure of the second fastener structure **406**. The screw hole of the collar **808** is configured to be tightened onto the screw structure of the second fastener structure **406** along the first direction of travel associated with the first degree of

18

freedom. When the receiving element **206** moves further along the first direction of travel, the sleeve bushing **804** and the screw hole of the first fastener structure **404** do not move and therefore are fixed with respect to the second fastener structure **406** of the base assembly **208**.

The extended portion **402** of the receiving element **206** includes a thread locker **812** embedded therein, the shoulder screw **802** is configured to lock into place with the thread locker **812** for the purposes of fastening the first fastener structure **404** to the receiving element **206**. As such, the first fastener structure **404** is configured to be loosely suspended within the extended portion **402** of the receiving element **206** via the shoulder screw **802**. The spring washer **806** is mounted on the top of the sleeve bushing **804**. When the first fastener structure **404** is fastened into the extended portion **402**, the spring washer **806** can touch the interior wall of the extended portion **402**, and compression of the spring washer **806** defines a torque resistance for rotating the receiving element **206** at the first degree of freedom of motion.

The receiving element **206** further includes a low friction bushing **810** that is attached onto the interior wall of the extended portion **402**. In accordance with the unlimited motion in the direction of travel associated with the first degree of freedom of motion, the sleeve bushing **804** of the first fastener structure **404** is tightened onto the second fastener structure **406** and rotates against the surface of the low friction bushing **810** inside the extended portion **402**. Stated another way, the low friction bushing **810** wraps around the first fastener structure, and rotates as part of the receiving element **206** with respect to the base assembly **208**, and with respect to the first fastener structure **404** when the first fastener structure **404** is tightened onto the second fastener structure **406** of the base assembly **208**. The torque resistance associated with the rotation is defined by the spring washer **806** mounted on the top of the sleeve bushing **804**. Moreover, the low friction bushing **810** is configured to hug the first fastener structure **404** closely, such that the first fastener structure **404** does not wobble inside the extended portion **402** or cause an unstable support for the module mounted on the stand assembly **202**. In some implementations, the low friction bushing **810** is made of elastic rubber material.

In some implementations, the spring washer **806** renders a substantially consistent resistance for the unlimited movement of the receiving element **206** in the first direction of travel associated with the first degree of freedom of motion. Further, in some implementations, the unlimited movement of the receiving element at the first direction of travel is associated with a first torque resistance optionally created by the spring washer **806**, and the first torque resistance is substantially greater than a second torque resistance that is required to unfasten the receiving element from the base assembly in the reverse direction of travel.

FIG. **9A** illustrate another exemplary stand assembly **202** in which movement of a receiving element **206** with respect to a base assembly **208** is limited at a second degree of freedom of motion in accordance with some implementations. The second degree of freedom of motion is associated with flipping of the receiving element **206** at a joint **212** of the base assembly **208** with respect to a flipping axis **220**, and the flipping axis **220** passes through the joint **212** and is substantially parallel to a planar surface (e.g., a bottom surface) of the base **210**. The movement of the receiving element **206** at the second degree of freedom has substantially consistent resistance through a second full range of motion associated with the second degree of freedom. The second full range of motion is limited. In a specific example,

19

the receiving element **206** is configured to flip with respect to the flipping axis **220** by an angle that is substantially equal to 180 degrees. Stated another way, the receiving element **206** starts at a nominal position (e.g., a vertical position shown in FIG. 6B), and is configured to be flipped up to 90 degrees in either the forward or backward direction to reach its end positions of a second full range of motion associated with the second degree of freedom of motion.

FIG. 9B is an exploded view of a joint **212** that is assembled onto a hinge carrier **502** to provide to a receiving element **206** a limited movement range at a second degree of freedom of motion shown in FIG. 9A in accordance with some implementations. The second fastener structure **406** includes a screw structure **714** on its top half and a collar **902** on its bottom half, and a joint hole **718** is formed on the collar **902**. In some implementations, both the screw structure **714** and the collar **902** are flattened to have two substantially flat surfaces, such that they fit into a base opening slot **716** on the base assembly **208**. In some implementations as shown in FIG. 9B, the screw structure **714** has a screw diameter that fits into the base opening slot **716**, while the collar **902** is flattened for fitting into the base opening slot **716**. While the top half of the second fastener structure **406** is fastened into the first fastener structure **404**, the bottom half of the second fastener structure **406** is fastened onto a hinge carrier **502** to form the joint **212** that can rotate around the joint hole **718**.

The hinge carrier **720** is used as a platform to create the joint **212**. The joint **212** includes a plurality of joint fasteners **212A-212D** that further includes a collar bushing **212A**, a thrust bushing **212B**, a spring washer set **212C** and a shoulder screw **212D**. The joint fasteners **212A-212D** together fasten the bottom half of the second fastener structure **406** onto a carrier slot **720** of a hinge carrier **502**. The collar bushing **212A** and the thrust bushing **212B** provide side to side location and smooth bearing surfaces in contact with the collar **902**. Additionally, the spring washer set **212C** provides positive tension on the shoulder screw **212D**, and creates frictional resistance and/or torque around a hinge axis **730** when the hinge screw **212D** is tightened through the joint hole **718** and a screw hole **722** on the hinge carrier **502** to form the joint **212**. The hinge axis **730** passes through the center of the joint hole **718** on the second fastener structure **406**, and substantially overlaps the flipping axis **220** associated with the second degree of freedom of motion of the receiving element **206** with respect to the base assembly **208**.

As explained above with reference to FIGS. 7E and 7F, when the hinge carrier **502** is assembled into the base **210**, the screw structure **714** of the second fastener structure **406** extends beyond the base opening slot **716**. The second fastener structure **406** is configured to rotate around the hinge axis **730** while being constrained within the base opening slot **716**. When the screw structure **714** of the second fastener structure **406** is fastened with the first fastener structure **404**, the receiving element **206** is mounted onto the base assembly **208**, and therefore can flip with respect to its flipping axis **220** (i.e., the hinge axis **730**) to provide the second degree of freedom of motion for a module mounted onto its module holding structure **214**.

FIGS. 10A and 10B illustrate a process **1000** for assembling a stand assembly **202** in accordance with some implementations. As shown in FIG. 10A, a second fastener structure **406** is mounted on a hinge carrier **502** to provide a joint **212**. The hinge carrier **502** is then assembled to a base **210**, and fixed thereon via one or more base fasteners **506**.

20

In some implementations, as shown in the inset of FIG. 10A, the one or more base fasteners **506** include screws that are fastened through screw holes on a bottom surface of the hinge carrier **502**, and anchored onto screw holes inside the base **210**. As such, the hinge carrier **502** is fully assembled to the base **210** to provide a base assembly **208** in which the second fastener structure **406** extends from a base opening slot **716** of the base **210**.

In some implementations, a standalone first fastener structure **404** is then tightened onto the exposed second fastener structure **406** of the base assembly **208**, until the first fastener structure **404** reaches a tightened position of its full range of motion. It is noted that the tightened position of the first fastener structure is associated with an end position (FIG. 6A or 6C) that the receiving element **206** has within a first part of a first full range of motion associated with the first degree of freedom. After the first fastener structure **404** is tightened onto the second fastener structure **406**, the module holding structure **214** and the extended portion **402** of the receiving element **206** is pressed onto the first fastener structure **404** to mount the receiving element **206** to the base assembly **208**. After the mount press, the first fastener structure **404** is mechanically coupled inside the extended portion **402** of the receiving element **206**. In some implementations, the first fastener structure **404** cannot be detached from the receiving element **206** without causing damage to the first fastener structure **404** or the receiving element **206**.

In some implementations, after it is determined that the first fastener structure **404** reaches its tightened position, the receiving element **206** is reversely twisted at the first degree of freedom of motion by a first angle to orient the receiving element **206** to a nominal position (FIG. 6B). At the nominal position, the module holding structure **214** of the receiving element **206** is aligned in parallel or overlaps with both the twisting axis **218** and the flipping axis **220**, and therefore, the receiving element **206** and a module received thereby are configured to face substantially up when they are flipped down via the joint **212** at the second degree of freedom of motion.

In some implementations, the first angle is half of a first part of a first full range of motion associated with the first degree of freedom of motion. Stated another way, the nominal position is located substantially in the middle of the first part of the first full range of motion associated with the first degree of freedom of motion. To obtain such a nominal position, the module holding structure **214** of the receiving element **206** needs to be properly oriented prior to and during the mount press according to the end position associated with the first part of the first full range of motion associated with the first degree of freedom as shown in FIG. 6A. Under some circumstances, the module holding structure **214** of the receiving element **206** is not properly oriented prior to and during the mount press according to the end position associated with the first degree of freedom as shown in FIG. 6A. The first part of the first full range of motion is not centered at the nominal position. The receiving element **206** has a larger range of motion on one of the clockwise and counterclockwise directions than the other of these two directions.

Alternatively, in some implementations not illustrated in FIGS. 10A and 10B, the first fastener structure **404** is attached to the receiving element **206** before it is fastened onto the second fastener structure **406** of the base assembly **208**. The first fastener structure **404** needs to be aligned to the module holding structure **214** properly, such that when the receiving element **206** is fastened onto the base assembly

21

208, the resulting stand assembly 202 properly provides the first part of a first full range of motion and the nominal position both associated with the first degree of freedom of motion.

FIG. 11 is an exploded view of a stand assembly 202 that includes a magnet plate 504 in its base assembly 208 in accordance with some implementations. The magnet plate 504 is mechanically coupled to the base 210 such that the magnet plate 502 is adjacent to or forms a portion of a bottom surface of the base 210. The magnet plate 504 has a bottom surface area that is smaller than a surface area of the bottom surface of the base 510. Specifically, in some implementations, the magnet plate 504 is mechanically coupled to the base 210 using one or more magnet fasteners 506. Optionally, the magnet plate 504 is directly coupled to the base 210, or indirectly coupled to the hinge carrier 502 that is configured to fit into and couple to the base 210.

In some implementations, the base assembly 208 further includes a cover plate 510. Optionally, the cover plate 510 is made of plastic, metal or other materials. The cover plate 510 is glued onto the bottom surface of the base 510 to cover the magnet plate 504 that has been mechanically coupled to the base 510, and the magnet plate 504 is sandwiched between the bottom surface of the base 210 and the cover plate 510. The cover plate 510 has a surface area that is substantially equal to or slightly larger than that of the magnet plate 504 such that the cover plate 510 entirely seals the magnet plate inside the base assembly 208. As such, in some implementations, mechanical fasteners of the base assembly 208 are structurally visible to the user of the stand assembly 202 except the joint 212.

In some implementations, the base assembly 208 further includes one or more rubber patches 512 that are attached to a bottom surface of the base assembly 208 to provide additional friction between the stand assembly 202 and the supporting surface against which the base is rested. In an example (FIG. 5), the one or more rubber patches 512 includes a rubber ring that is attached to the bottom surface of the base assembly 208 and surrounds the cover plate 510.

FIG. 12A illustrates a mount structure 224 for mounting a stand assembly 202 onto a mounting surface in accordance with some implementations. At least part of the mount structure 224 is made of magnetically attractable material, e.g., iron, steel, copper, and brass. The stand assembly 202 is mounted onto the mounting surface when the base 210 of the base assembly 208 magnetically adheres onto the mount structure 224. In some implementations, the at least part of the mount structure 224 includes a magnetically attractable plate 514 that has been integrated in the mount structure 224 before they are shipped to a user of the stand assembly 202.

The magnetic attraction force between the base 210 of the stand assembly 202 and the mount structure 226 enables secure attachment of an electronic device module that is mounted onto the mounting surface using the stand assembly 202. Such secure attachment satisfies one or more Underwriters Laboratories (UL) standards that set forth at least safety requirements for mounting the electronic device module onto a mounting surface. An example UL standard is UL 2442 Standard for Wall- and Ceiling-Mounts and Accessories, which applies to devices that provide structural support for the mounting of audio/video equipment, information technology equipment, and similar products, to the building structure and is intended for indoor use only.

The mount structure 224 has a surface area that is substantially larger than or equal to that of the bottom surface of the base assembly 208, and includes a cable guide structure 226 at the circumference of the mount structure

22

224. The cable guide structure 226 is configured to guide a power or data cable that electrically couples a module 204 received in the receiving element 206 to an external power supply or another electronic device (e.g., a computational machine). Specifically, one end of the power or data cable is electrically coupled to a connection port 306 of the module 204, while the other end is electrically coupled to the external power supply or the other electronic device. An intermediate node at the power or data cable is held by the cable guide structure 226, thereby protecting the power or data cable from wiggling around and disconnecting from the connection port 206.

Further, the mount structure 224 includes one or more open slots 1202 each having a respective width that matches a dimension of a head of a mount fastener (e.g., a screw or a nail). The open slots 1202 are configured to receive the mount fasteners 518. The mount structure 224 can be attached and fixed onto the mounting surface when the mount fasteners 518 are fastened onto the mounting surface via the open slots 202 of the mount structures 224. The open slots 1202 have predetermined lengths configured to accommodate an adjustment of an orientation of the mount structure 224 when the mount fasteners 518 are loosened from the mounting surface. In some implementations, the orientation of the mount structure 224 is adjusted for the purposes of varying the location of the cable guide structure 226 with respect to a module mounted on the mount structure 224 (e.g., the camera module 204). The predetermined lengths of the open slots as presented here are associated with an adjustment angle of 90 degrees for adjusting the orientation of the mount structure 224 and the location of the cable guide structure 226.

FIG. 12B illustrates another exemplary mount structure 224 onto which a detachable foam plate 520 is attached in accordance with some implementations. Specifically, the detachable foam plate 520 is attached onto the magnetically attractable part of the mount structure 224. In some implementations, the detachable foam plate 520 includes a back surface that is sticky, and adheres to the surface of the magnetically attractable part like a sticker. The front surface of the detachable foam plate 520 includes one or more instructions for assembling the stand assembly 202. In this example, the one or more instructions include an arrow that indicates that a user can peel off the detachable foam plate 520 from the mount structure 224. Additionally, the one or more instructions include specific language to guide the user to “screw plate to wall and remove sticker,” and “attach Nest Cam to plate.”

When the mounting structure 224 is mounted onto a mounting surface, it is arranged according to a preferred orientation such that the cable guide structure 226 is located at a preferred location (e.g., on a bottom rim of the mounting structure 224, or below a module after the module is mounted on the stand assembly 202). In some implementations, the one or more instructions on the detachable foam plate 520 include a notice that reminds the user of orienting the mount structure 224 according to the preferred orientation.

In some implementations, the detachable foam plate 520 includes a tab 1204. The tab 1204 is oriented according to the preferred orientation of the mounting structure 224, and used to guide the attachment of the mount structure 224 onto the mounting surface. Specifically, the detachable foam plate 520 is attached onto the mounting structure 224 with the tab 1204 aligned to the preferred orientation of the mounting structure 224. When the user mounts the mount structure 224 according to the orientation of the tab 1204, the cable

23

guide structure **226** is disposed at its preferred location. In a specific example, the user orients the tab **1204** of the mounting structure **224** to an upward direction, and obtains the preferred orientation of the mounting structure **224** and the preferred location of the cable guide structure **226** automatically.

FIG. **12C** is an exploded view of a stand assembly **202**, a detachable foam plate **520** and a mount structure **224a** in accordance with some implementations. After the mount structure **224a** is fixed onto the mounting surface with a preferred orientation, the tab **1204** is peeled off, and the stand assembly **202** is placed on top of the mount structure **224a**. The stand assembly **202** adheres to the mount structure **224a** firmly by way of the magnetic attraction force that exists between the magnet plate **504** sealed inside the base **210** and the magnetically attractable part **514** of the mount structure **224a**. In some implementations, the magnetic attraction force satisfies the UL standards for mounting an electronic device onto a mounting surface safely, and the stand assembly **202** would not be easily detached from the mount structure **224a**.

Conversely, the detachable foam plate **520** is applied to reduce the magnetic attraction force between the base **210** and the mount structure **224a**, before the mount structure **224** is fully prepared for receiving the stand assembly **202**. The detachable foam plate **520** is attached onto the mount structure **224a** to increase a distance and thereby reduce the magnetic attraction force between the magnet plate **504** of the base **210** and the magnetically attractable part **514** of the mount structure **224**. The reduced magnetic attraction force allows a user to separate the stand assembly **202** from the mount structure **224a** conveniently without resorting to any tool, particularly before the mount structure **224a** is fixed onto the mounting surface and prepared to receive the stand assembly **202**.

FIG. **13A** is an exploded view of a stand assembly **202**, a cable guide ring **1302** and a mount structure **224b** that function together to support a module **204** on a mounting surface in accordance with some implementations. FIG. **13B** illustrates another mount structure **224b** in accordance with some implementations, and FIG. **13C** illustrates a cable guide ring **1302** in accordance with some implementations. At least part of the mount structure **224b** is made of magnetically attractable material, e.g., iron, steel, copper, and brass. The stand assembly **202** is mounted onto the mounting surface when the base **210** of the base assembly **208** magnetically adheres onto the mount structure **224b**. The mount structure **224** has a surface area that is substantially smaller than that of the bottom surface of the base assembly **208**, and does not include a cable guide structure **226**. Rather, the functions of the cable guide structure **226** are provided separately by a cable guide ring **1302**.

The mount structure **224b** is substantially flat, and includes a plurality of openings **1304** each having a respective dimension that matches that of a head of a mount fastener **518** (e.g., a screw or a nail). The openings are configured to receive the mount fasteners. The mount structure **224b** is attached and fixed onto the mounting surface, when the mount fasteners **518** are fastened onto the mounting surface via the openings **1304** of the mount structure **224b**.

The cable guide ring **1302** has an inner diameter that is substantially larger than a diameter of the mount structure **224b**. When the stand assembly **202** is mounted onto the mounting surface, the cable guide ring **1302** surrounds the mount structure **224**, comes into contact with the mounting surface, and is thereby sandwiched between the mounting

24

surface and the base **210** of the stand assembly **202**. Further, the cable guide ring **1302** has an outer diameter that is substantially larger than or equal to that of the bottom surface of the base assembly **208**. The cable guide ring **1302** further includes a cable guide structure **226** located at its outer circumference for fixing a power or data cable. Optionally, the power or data cable is configured to electrically couple the module **204** received at the receiving element **206** of the stand assembly **202** to an external power supply or a separate electronic device.

In some implementations, the circumference of the mount structure **224** includes a groove, and the mount structure **224b** further includes an O-ring **1306**. The O-ring **1306** is configured to be seated in the groove of the mount structure **224**. The O-ring is compressed and creates a seal at an interface when the card guide ring **1302** is assembled onto the mount structure **224b**. In some implementations, the cable guide ring **1302** includes one or more protrusions **1308** on its surface to increase its friction with the bottom surface of the base **210**. The seal provided by the O-ring **1306** and the friction provided by the surface protrusions **1308** prevent the card guide ring **1302** from wobbling between the stand assembly **202** and the mounting surface, and thereby enable a secure cable guiding function for the power or data cable electrically coupled to the module **204**.

Referring to FIGS. **13A-13C**, the mount structure **224b** has a relatively simple form factor, and is easy to manufacture at an affordable cost. In some implementations, the stand assembly **202** is associated with more than one mount structures **224b** that can be mounted onto more than one mounting surfaces in a smart home environment. A user of the module **204** can conveniently remove the stand assembly **202** and the cable guide ring **1302** from one mount structure **224b** located at a first location, and mount them to another mount structure **224b** located at a second location without moving the mount structure **224**.

FIG. **14A** is a top view of a camera assembly **200** in which a receiving element **206** and a camera module **204** mounted thereon are packaged in accordance with some implementations. The receiving element **206** and the camera module **204** are flipped down to an end position, and face substantially up in the camera assembly **200**. As explained above with reference to FIGS. **6A-6F**, the stand assembly **202** is associated with a nominal position at which the module holding structure **214** of the receiving element **206** is arranged to align in parallel or overlap with both the twisting axis **218** (not shown in FIG. **14A**) and the flipping axis **220**. In accordance with a second degree of freedom of motion, the receiving element **206** and the camera module **204** can be flipped around the flipping axis **220** that passes through a joint **212** and lies substantially in parallel with a planar surface of the base **210**. As such, the receiving element **206** and the camera module **204** mounted thereon are flipped down and face substantially up (i.e., face opposite to the planar surface of the base **210**).

FIGS. **14B-14F** illustrate a packaging process **1400** for packaging a camera assembly **200** shown in FIG. **14A** and its accessories in a multilayer shipping package in accordance with some implementations. The multilayer shipping package includes a lid box **1402** and a container box **1404**. The container box **1404** is configured to contain the camera assembly **200** and its accessories, and the lid box is configured to cover the container box **1404**. The boxes **1402** and **1404** of the multilayer shipping package further include a plurality of packaging layers, e.g., four layers including layers **1406-1412** in this specific example, for organizing the

25

camera assembly 200 and its accessories in a compact, reliable, and user friendly manner.

When a user opens the shipping package shipped from a retailer or a manufacturer, the user sees that a camera assembly 200 lays flat on a top layer 1406 of the container box 1404 (FIG. 14C). The top layer 1406 includes a first recess 1412 that is formed according to a contour of the camera assembly 200 and configured to hold the camera assembly 200 firmly. On the other hand, the lid box 1402 includes a lid layer 1408, and the lid layer 1408 has a lid recess or protrusion 1416 that is also configured at least according to a contour of the receiving element 206 of the camera assembly 200. When the lid box 1402 is flipped over to cover the container box 1404, the camera assembly 200 is securely held between the lid recess or protrusion 1416 of the lid layer 1408 and the first recess 1412 of the top layer 1406, and thereby protected from some shipping damages that can occur in transit.

In some implementations, the first recess 1412 of the top layer 1406 includes one or more cutout openings (not shown in FIG. 14C). When the camera assembly 200 is removed from the first recess 1412 of the top layer 1406, the one or more cutout openings on the recess allow the user to pull the top layer 1406 out of the container box 1404 easily.

Further, after the top layer 1406 is removed from the container box 1404, a subset of camera accessories (e.g., a power cord and a power adapter) is exposed. In some implementations, the subset of camera accessories is supported by one or more underlying layers (e.g., a bottom layer 1410 and an intermediate layer 1412). The bottom layer 1410 includes a second recess 1418, and the intermediate layer 1412 is placed inside the second recess 1418 of the bottom layer 1410. A power cord is supported by the intermediate layer 1412 and held within the second recess 1418. The intermediate layer 1412 further includes a cutout opening 1420 that allows the user to pull the intermediate layer 14012 out of the second access 1418 of the bottom layer 1410.

After the intermediate layer 1412 is removed, a mount structure 224 that lies underneath the intermediate layer 1412 is exposed. The mount structure 224 is disposed at the bottom of the second access 1418 of the bottom layer 1410. In some implementations, the second access 1418 of the bottom layer 1410 is configured to hold one or more mount structures 224 and a card guide ring 1302 as shown in FIGS. 13A-13C.

In some implementations, the bottom layer 1410 further includes a third recess 1422 that is configured to hold the power adapter.

In some implementations, a user manual is disposed under the top layer 1406 and above the accessories that are organized and held by the intermediate and bottom layers 1410 and 1412.

In some implementations, the packaging layers 1406-1412 packaged inside the shipping package are made of recycled paper, and the recycled paper include at least a threshold amount of starch quantities. In an example, the threshold amount of starch quantities is equal to 40% of the packaging layers in weight.

FIG. 15 illustrates a receiving element 206 that is mechanically coupled on a standard tripod 1502 in accordance with some implementations. Specifically, a first fastener structure 404 includes a threaded screw hole that matches a tripod screw of a standard tripod, and the receiving element 206 is configured to mount on the standard tripod 1502 when the tripod screw is tightened into the threaded screw hole of the first fastener structure 404. In

26

some implementations, the tripod screw is part of a tripod adaptor. The first fastener structure 404 is fastened to the tripod adaptor, and the tripod adaptor is further fastened onto the standard tripod 1502. In some implementations, to match the tripod screw of a commonly used standard tripod, the threaded screw hole on the first fastener structure 404 is a ¼-20 socket that has a ¼ inch diameter and 20 threads per inch at its screw length.

FIG. 16 is a flow chart of a method 1600 for packaging a stand assembly 202 configured to support a module (e.g., a camera module 204) in accordance with some implementations. The stand assembly packaging method 1600 includes providing (1602) a base assembly 208 that includes a base 210 and a second fastener structure 406, and the second fastener structure 406 is coupled to the base 210 at a joint 212. As shown in FIGS. 10A and 10B, in some implementations, providing the base assembly 208 further includes: inserting the second fastener structure 406 into a base opening slot 716 on the base assembly 208, and forming the joint 212 by assembling the second fastener structure 406 in the base opening slot 716 using one or more joint fasteners. More details on the methods of providing the base assembly 208 including the joint 212 are explained above with reference to FIGS. 7D-7F and 9B.

The stand assembly packaging method 1600 further includes attaching (1604) to the base assembly 208 a receiving element 206. The receiving element 206 includes a first fastener structure 404 and is configured to physically receive the module 204. To attach the receiving element 206 to the base assembly 208, the first fastener structure 404 is tightened onto the second fastener structure 406 until the first fastener structure 404 reaches a tightened position. The first fastener structure 404 of the receiving element 206 and the joint 212 of the base assembly 208 are configured (1606) to provide a first degree of freedom of motion and a second degree of freedom of motion of the receiving element 206 with respect to the base assembly 208, respectively.

In some implementations, the receiving element 206 further includes a module holding structure 214 and an extended portion 402. To attach the receiving element 206 to the base assembly 208, after the first fastener structure 404 is tightened onto the second fastener structure 406, the module holding structure 214 and the extended portion 402 of the receiving element 206 are press mounted onto the first fastener structure 404 to mount the receiving element 206 to the base assembly 208.

The stand assembly packaging method 1600 further includes after determining that the first fastener structure 404 reaches the tightened position, rotating (1608) the receiving element 206 reversely at the first degree of freedom of motion by a first angle to orient the receiving element to a nominal position. At the nominal position, the receiving element 206 and the module 204 received thereby are configured (1610) to face substantially up when they are flipped down via the joint 212 at the second degree of freedom of motion. In some implementations, the first angle is substantially equal to half of a full range of motion of the first fastener structure 404. In a specific example, the first angle is substantially equal to 45 degrees. More details on the tightened position of the first fastener structure 404 and the nominal position of the receiving element 206 are explained above with reference to FIGS. 6A-6C.

In some implementations, the module is assembled (1612) onto the receiving element 206 to form a module assembly. When the module includes a camera module 204, a camera assembly is formed to support the camera module 204 assembled onto the receiving element 206.

As explained above, in some implementations, the movement of the receiving element **206** at the first degree of freedom has substantially consistent resistance through first part of a first full range of motion associated with the first degree of freedom of motion, and the movement of the receiving element **206** at the second degree of freedom has substantially consistent resistance through a second full range of motion associated with the second degree of freedom. Further, in some implementations, the first part of the first full range of motion associated with the first degree of freedom of motion is associated with a twisting angle, and the first angle is substantially equal to half of the twisting angle such that the nominal position is located at the center of the first part of the first full range of motion associated with the first degree of freedom of motion. In some implementations, the tightened position of the first fastener structure **404** is associated with an end position that the receiving element **206** has within the first part of the first full range of motion associated with the first degree of freedom. More details on the first and second degrees of freedom of motion of the receiving element **206** are explained above with reference to FIGS. 6A-6E.

In some implementations, the first fastener structure **404** of the receiving element **206** further includes a screw hole and a nylon-like bushing coupled at the end of the screw hole. The screw hole matches a screw structure of the second fastener structure **406**, and has a predetermined thread length. The screw hole is configured to provide a second part of the first full range of motion when the first fastener structure is fastened onto the second fastener structure via the screw hole and the screw structure. The nylon-like bushing has a predetermined bushing depth, and provides the first part of the first full range of motion when the first fastener structure is fastened onto the second fastener structure via the screw hole and the screw structure. The second part of the first full range of motion is distinct from the first part of the first full range of motion. More details on the first and second fastener structures that enable the stand assembly packaging method **1600** are explained above with reference to FIGS. 7A-7C.

In some implementations, the stand assembly packaging method **1600** further includes flipping the receiving element **206** via the joint **212** at the second degree of freedom of motion until the receiving element **206** and the module **204** received thereby face substantially up. After the receiving element **406** is flipped via the joint **212**, the assembly is placed within a shipping package. Specifically, the assembly is placed on a packaging layer (e.g., the layer **1406**) inside the shipping package with the receiving element **206** and the module **204** received thereby at least partially held in a recess (e.g., the recess **1412**) on the packaging layer. More details on a packaging process **1400** for packaging an assembly and its accessories in a multilayer shipping package are explained above with reference to FIGS. 14A-14F.

It should be understood that the particular order in which the operations in FIG. 16 have been described are merely exemplary and are not intended to indicate that the described order is the only order in which the operations can be performed. One of ordinary skill in the art would recognize various ways to package a stand assembly **202** as described herein. Additionally, it should be noted that details of other processes described herein with respect to method **1600** (e.g., FIG. 16) are also applicable in an analogous manner to method **1700** described below with respect to FIG. 17. For brevity, these details are not repeated here.

FIG. 17 is a flow chart of another exemplary method **1700** for packaging a stand assembly **202** configured for support-

ing a module (e.g., a camera module **204**) in accordance with some implementations. The stand assembly packaging method **1700** includes providing (**1702**) a base assembly **208** that includes a base **210** and a second fastener structure **406**, and the second fastener structure **406** is coupled to the base **210** at a joint **212**.

The stand assembly packaging method **1700** further includes attaching (**1704**) to the base assembly **208** a receiving element **206** that includes a first fastener structure **404** and is configured to physically receive the module **204**. The first fastener structure **404** of the receiving element **206** is configured (**1706**) to mate with the second fastener structure **406** and provide a first degree of freedom of motion of the receiving element **206** with respect to the base. The movement of the receiving element at the first degree of freedom is unlimited in a first direction of travel associated with the first degree of freedom. The joint **212** is configured (**1708**) to provide a second degree of freedom of motion of the receiving element **206** with respect to the base. The movement of the receiving element at the second degree of freedom is limited in a direction of travel associated with the second degree of freedom. Further, in some implementations, the first degree of freedom is associated with a reverse direction of travel that is opposite to the first direction of travel associated with the unlimited movement at the first degree of freedom, and the first and second fastener structures **406** and **406** are unfastened when the receiving element **206** moves with respect to the base assembly **208** in the reverse direction of travel associated with the first degree of freedom.

In some implementations, the receiving element **206** is configured to move with respect to the base **210** at the first degree of freedom of motion when the first fastener structure **404** is fastened onto the second fastener structure **406** of the base assembly **208**. The first fastener structure **404** of the receiving element **206** further includes a screw hole that matches a screw structure of the second fastener structure. The screw hole has a predetermined thread length, and provides the unlimited movement at the first degree of freedom of motion, when the first fastener structure **404** is fastened onto the second fastener structure **406** via the screw hole and the screw structure.

In some implementations, the first fastener structure further includes a shoulder screw **802**, a sleeve bushing **804**, a spring washer **806** and a screw hole, and the first fastener structure **404** is configured to be loosely suspended within the extended portion **402** of the receiving element **206** via the shoulder screw **802**.

In some implementations, an extended portion **402** of the receiving element **206** includes a thread locker **812** embedded therein, and the first fastener structure **404** includes a shoulder screw **802**. The shoulder screw **802** is configured to lock into place with the thread locker **812** for the purposes of fastening the first fastener structure **404** to the receiving element **206**. Further, in some implementations, a low friction bushing **810** is fixed inside an extended portion **402** of the receiving element **206**. In accordance with the unlimited movement of the receiving element at the first degree of freedom, the low friction bushing **810** wraps around the first fastener structure **404**, and rotates as part of the receiving element **206** with respect to the base assembly **208**, and with respect to the first fastener structure **404** when the first fastener structure **404** is tightened onto the second fastener structure **406** of the base assembly **208**.

More details on the first fastener structure **404** that enables the stand assembly packaging method **1700** are explained above with reference to FIGS. 8B and 8C.

The stand assembly packaging method **1600** further includes (1710) rotating the receiving element **206** along the first direction of travel associated with the first degree of freedom until the receiving element **206** reaches a nominal position. At the nominal position, the receiving element **206** and the module **204** received thereby are configured (1712) to face substantially up when they are flipped down via the joint **212** at the second degree of freedom of motion. In some implementations, the module is assembled (1714) onto the receiving element **206** to form a module assembly. When the module includes a camera module **204**, a camera assembly is formed to support the camera module **204** assembled onto the receiving element **206**.

In some implementations, the stand assembly packaging method **1600** further includes flipping the receiving element **206** via the joint **212** at the second degree of freedom of motion until the receiving element **206** and the module **204** received thereby face substantially up. After the receiving element **406** is flipped via the joint **212**, the assembly is placed within a shipping package. Specifically, the assembly is placed on a packaging layer (e.g., the layer **1406**) inside the shipping package with the receiving element **206** and the module **204** received thereby at least partially held in a recess (e.g., the recess **1412**) on the packaging layer. More details on a packaging process **1400** for packaging an assembly and its accessories in a multilayer shipping package are explained above with reference to FIGS. **14A-14F**.

It should be understood that the particular order in which the operations in FIG. **17** have been described are merely exemplary and are not intended to indicate that the described order is the only order in which the operations can be performed. One of ordinary skill in the art would recognize various ways to package a stand assembly **202** as described herein. Additionally, it should be noted that details of other processes described herein with respect to method **1700** (e.g., FIG. **17**) are also applicable in an analogous manner to method **1600** described above with respect to FIG. **16**. For brevity, these details are not repeated here.

Although various drawings illustrate a number of logical stages in a particular order, stages that are not order dependent may be reordered and other stages may be combined or broken out. While some reordering or other groupings are specifically mentioned, others will be obvious to those of ordinary skill in the art, so the ordering and groupings presented herein are not an exhaustive list of alternatives. Moreover, it should be recognized that the stages can be implemented in hardware, firmware, software or any combination thereof.

The foregoing description, for purpose of explanation, has been described with reference to specific implementations. However, the illustrative discussions above are not intended to be exhaustive or to limit the scope of the claims to the precise forms disclosed. Many modifications and variations are possible in view of the above teachings. The implementations were chosen in order to best explain the principles underlying the claims and their practical applications, to thereby enable others skilled in the art to best use the implementations with various modifications as are suited to the particular uses contemplated.

Reference will now be made in detail to implementations, examples of which are illustrated in the accompanying drawings. In the following detailed description, numerous specific details are set forth in order to provide a thorough understanding of the various described implementations. However, it will be apparent to one of ordinary skill in the art that the various described implementations may be practiced without these specific details. In other instances,

well-known methods, procedures, components, mechanical structures, circuits, and networks have not been described in detail so as not to unnecessarily obscure aspects of the implementations.

It will also be understood that, although the terms first, second, etc. are, in some instances, used herein to describe various elements, these elements should not be limited by these terms. These terms are only used to distinguish one element from another. For example, a first fastener structure can be termed a second fastener structure, and, similarly, a second fastener structure can be termed a first fastener structure, without departing from the scope of the various described implementations. The first fastener structure and the second fastener structure are both fastener structures, but they are not the same fastener structure.

The terminology used in the description of the various described implementations herein is for the purpose of describing particular implementations only and is not intended to be limiting. As used in the description of the various described implementations and the appended claims, the singular forms “a”, “an” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will also be understood that the term “and/or” as used herein refers to and encompasses any and all possible combinations of one or more of the associated listed items. It will be further understood that the terms “includes,” “including,” “comprises,” and/or “comprising,” when used in this specification, specify the presence of stated features, integers, steps, operations, elements, components, structures and/or groups, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, structures, and/or groups thereof.

As used herein, the term “if” is, optionally, construed to mean “when” or “upon” or “in response to determining” or “in response to detecting” or “in accordance with a determination that,” depending on the context. Similarly, the phrase “if it is determined” or “if [a stated condition or event] is detected” is, optionally, construed to mean “upon determining” or “in response to determining” or “upon detecting [the stated condition or event]” or “in response to detecting [the stated condition or event]” or “in accordance with a determination that [a stated condition or event] is detected,” depending on the context.

It is to be appreciated that “smart home environments” may refer to smart environments for homes such as a single-family house, but the scope of the present teachings is not so limited. The present teachings are also applicable, without limitation, to duplexes, townhomes, multi-unit apartment buildings, hotels, retail stores, office buildings, industrial buildings, and more generally any living space or work space.

It is also to be appreciated that while the terms user, customer, installer, homeowner, occupant, guest, tenant, landlord, repair person, and the like may be used to refer to the person or persons acting in the context of some particularly situations described herein, these references do not limit the scope of the present teachings with respect to the person or persons who are performing such actions. Thus, for example, the terms user, customer, purchaser, installer, subscriber, and homeowner may often refer to the same person in the case of a single-family residential dwelling, because the head of the household is often the person who makes the purchasing decision, buys the unit, and installs and configures the unit, and is also one of the users of the unit. However, in other scenarios, such as a landlord-tenant environment, the customer may be the landlord with respect

31

to purchasing the unit, the installer may be a local apartment supervisor, a first user may be the tenant, and a second user may again be the landlord with respect to remote control functionality. Importantly, while the identity of the person performing the action may be germane to a particular advantage provided by one or more of the implementations, such identity should not be construed in the descriptions that follow as necessarily limiting the scope of the present teachings to those particular individuals having those particular identities.

It is noted that the stand assemblies described herein are exemplary and are not intended to be limiting. For example, any dimensions, shapes, styles, and/or materials described herein are exemplary and are not intended to be limiting. Drawings are not to scale. For brevity, features or characters described in association with some implementations may not necessarily be repeated or reiterated when describing other implementations. Even though it may not be explicitly described therein, a feature or characteristic described in association with some implementations may be used by other implementations.

What is claimed is:

1. A method of packaging a camera product that includes a camera, comprising:

providing a base assembly that includes a base and a base fastener structure;

attaching to the base assembly a holding element that physically holds the camera and includes a holding element fastener structure, the holding element fastener structure being configured to mate with the base fastener structure, wherein the base fastener structure and the holding element fastener structure, when mated, are configured to provide a first degree of freedom of motion for the holding element relative to the base and a second degree of freedom of motion for the holding element relative to the base;

rotating the holding element in a first direction via the first degree of freedom until the holding element reaches a first nominal position, wherein at the first nominal position, the holding element is configured to extend in a direction substantially parallel to the base;

rotating the holding element in a second direction via the second degree of freedom until the holding element reaches a second nominal position, wherein at the second nominal position, the camera faces away from the base; and

after attaching the holding element to the base assembly and rotating the holding element in the first direction and the second direction, providing the base assembly and the holding element to a package physically configured to receive the camera product with the camera facing upward in the package.

2. The method of claim 1, wherein the holding element further includes an extended portion coupled to the holding element fastener structure, and wherein the first degree of freedom of motion includes rotation of the holding element with respect to a first axis that extends in the same direction as the extended portion, and is configured to facilitate panning of the camera.

3. The method of claim 2, wherein the second degree of freedom of motion includes rotation of the holding element with respect to a second axis that extends in a direction perpendicular to the first axis, and is configured to facilitate tilting of the camera.

4. The method of claim 1, wherein the rotation of the holding element at the first degree of freedom is unlimited

32

in at least one direction of travel associated with the first degree of freedom of motion.

5. The method of claim 1, wherein the rotation of the holding element at the second degree of freedom is limited.

6. The method of claim 1, wherein the holding element and the camera are physically integrated.

7. The method of claim 1, wherein the camera product includes a camera puck, and the camera puck further includes a camera lens and image sensors.

8. The method of claim 7, wherein the holding element includes a cutout opening that physically receives the camera puck.

9. The method of claim 1, wherein the holding element is attached to the base assembly to form an assembly, and providing the base assembly and the holding element to the package further comprises:

placing the assembly on a packaging layer inside the package with the holding element at least partially held in a recess on the packaging layer.

10. The method of claim 1, wherein the base assembly is configured for attaching and fixing onto a mounting surface using a mounting structure at least partially made of magnetically attractable material, and the holding element and the base assembly are mounted onto the mounting surface when the base of the base assembly magnetically adheres onto the mount structure.

11. The method of claim 1, wherein in accordance with the first direction associated with the first degree of freedom, the base fastener structure is configured to rotate within an open slot of the base, and at the second nominal position the camera is facing a direction that is substantially parallel to the open slot of the base.

12. A method of preparing a camera product for packaging, the camera product including a camera, comprising:

providing a base assembly that includes a base and a base fastener structure;

attaching to the base assembly a holding element that physically holds the camera and includes a holding element fastener structure, the holding element fastener structure being configured to mate with the base fastener structure, wherein the base fastener structure and the holding element fastener structure, when mated, are configured to provide a first degree of freedom of motion for the holding element relative to the base and a second degree of freedom of motion for the holding element relative to the base;

rotating the holding element in a first direction via the first degree of freedom until the holding element reaches a first nominal position, wherein at the first nominal position, the holding element is configured to extend in a direction substantially parallel to the base;

rotating the holding element in a second direction via the second degree of freedom until the holding element reaches a second nominal position, wherein at the second nominal position, the camera faces away from the base, such that when the base assembly and the holding element are provided to a package physically configured to receive the camera product with the camera, the camera faces upward in the package.

13. The method of claim 12, wherein the holding element further includes an extended portion coupled to the holding element fastener structure, and wherein the first degree of freedom of motion includes rotation of the holding element with respect to a first axis that extends in the same direction as the extended portion, and is configured to facilitate panning of the camera.

33

14. The method of claim 12, wherein the rotation of the holding element at the first degree of freedom is unlimited in at least one direction of travel associated with the first degree of freedom of motion.

15. The method of claim 12, wherein the holding element 5 and the camera are physically integrated.

16. The method of claim 12, wherein the camera product includes a camera puck, and the camera puck further includes a camera lens and image sensors, and wherein the holding element and the camera puck have the same shape. 10

17. A method of packaging a module assembly that includes a module, comprising:

providing a base assembly that includes a base and a base fastener structure;

attaching to the base assembly a holding element that 15 physically holds the module and includes a holding element fastener structure, the holding element fastener structure being configured to mate with the base fastener structure, wherein the base fastener structure and the holding element fastener structure, when mated, are 20 configured to provide a first degree of freedom of motion for the holding element relative to the base and a second degree of freedom of motion for the holding element relative to the base;

rotating the holding element in a first direction via the first 25 degree of freedom until the holding element reaches a first nominal position, wherein at the first nominal position, the holding element is configured to extend in a direction substantially parallel to the base;

34

rotating the holding element in a second direction via the second degree of freedom until the holding element reaches a second nominal position, wherein at the second nominal position, the module faces away from the base; and

after attaching the holding element to the base assembly and rotating the holding element in the first direction and the second direction, providing the base assembly and the holding element to a package physically configured to receive the module with the module facing upward in the package.

18. The method of claim 17, wherein the holding element further includes an extended portion coupled to the holding element fastener structure, and wherein the first degree of freedom of motion includes rotation of the holding element with respect to a first axis that extends in the same direction as the extended portion.

19. The method of claim 17, wherein the rotation of the holding element at the first degree of freedom is unlimited in at least one direction of travel associated with the first degree of freedom of motion.

20. The method of claim 17, wherein the base assembly is configured for attaching and fixing onto a mounting surface using a mounting structure at least partially made of magnetically attractable material, and the holding element and the base assembly are mounted onto the mounting surface when the base of the base assembly magnetically adheres onto the mount structure.

* * * * *