

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
19 April 2001 (19.04.2001)

PCT

(10) International Publication Number
WO 01/27965 A1

(51) International Patent Classification⁷: H01J 7/24, 27/00

(21) International Application Number: PCT/US00/28412

(22) International Filing Date: 13 October 2000 (13.10.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
09/419,720 14 October 1999 (14.10.1999) US

(71) Applicants and

(72) Inventors: KRICHTAFOVITCH, Igor, A. [UA/US]; 822
233rd Street, S. E., Bothell, WA 98021 (US). FUHRI-
MAN, Robert, L., Jr. [US/US]; 13910 S. E. 23rd Street,
Bellevue, WA 98005 (US).

(74) Agent: FEHR, Thompson, E.; Suite 703, The Aerospace
Center, 1104 Country Hills Drive, Ogden, UT 84403 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ,
DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR,
HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR,
LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ,
NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM,
TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian
patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European
patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,
IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG,
CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

— With international search report.

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: ELECTROSTATIC FLUID ACCELERATOR



(57) Abstract: An electrostatic fluid accelerator having a multiplicity of closely spaced corona electrodes (1). The close spacing of such corona electrodes (1) is obtainable because such corona electrodes (1) are isolated from one another with exciting electrodes (2). Either the exciting electrode (2) must be placed asymmetrically between adjacent corona electrodes (1) or an accelerating electrode must be employed. The accelerating electrode can be either an attracting (13) or a repelling electrode (19). Preferably, the voltage between the corona electrodes (1) and the exciting electrodes (2) is maintained between the corona onset voltage and the breakdown voltage with a flexible top high-voltage power supply. Optionally, however, the voltage between the corona electrodes (1) and the exciting electrodes (2) can be varied, even outside the range between the corona onset voltage and the breakdown voltage, in order to vary the flow of fluid. And, to achieve the greatest flow of fluid, multiple stages

(28, 29 and 30) of the individual Electrostatic Fluid Accelerator are utilized with a collecting electrode (31 or 32) between successive stages (28, 29 and 30) in order to preclude substantially all ions and other electrically charged particles from passing to the next stage (28, 29 or 30), where they would tend to be repelled and thereby impair the movement of the fluid. Finally, constructing the exciting electrode (2) in the form of a plate that extends downstream with respect to the desired direction of fluid flow also assures that more ions and, consequently, more fluid particles flow downstream.



WO 01/27965 A1

DESCRIPTION

ELECTROSTATIC FLUID ACCELERATOR

5 TECHNICAL FIELD

This invention relates to a device for accelerating, and thereby imparting velocity and momentum to a fluid, especially to air, through the use of ions and electrical fields.

10 BACKGROUND ART

A number of patents (*see, e.g.*, United States patent numbers 4,210,847 and 4,231,766) have recognized the fact that ions may be generated by an electrode (termed the "corona electrode"), attracted (and, therefore, accelerated) toward another electrode (termed the "attracting electrode"), and impart momentum, directed toward the
15 attracting electrode, to surrounding air molecules through collisions with such molecules.

The corona electrode must either have a sharp edge or be small in size, such as a thin wire, in order to create a corona discharge and thereby produce in the surrounding air ions of the air molecules. Such ions have the same electrical polarity as does the
20 corona electrode.

Any other configuration of corona electrodes and other electrodes where the potential differences between the electrodes are such that ion-generating corona discharge occurs at the corona electrodes may be used for ion generation and consequent fluid acceleration.

25 When the ions collide with other air molecules, not only do such ions impart momentum to such air molecules, but the ions also transfer some of their excess electric charge to these other air molecules, thereby creating additional molecules that are attracted toward the attracting electrode. These combined effects cause the so-called electric wind.

30 However, because a small number of ions are generated by the corona electrode in comparison to the number of air molecules which are in the vicinity of the corona electrode, the ions in the present electric wind generators must be given initial high velocities in order to move the surrounding air. To date, even these high initial ionic velocities have not produced significant speeds of air movement. And, even worse,

such high ionic velocities cause such excitation of surrounding air molecules that substantial quantities of ozone and nitrogen oxides, all of which have well-known detrimental environmental effects, are produced.

Presently, no invention has even attained significant speeds of air movement, let
5 alone doing so without generating undesirable quantities of ozone and nitrogen oxides.

Three patents, *viz.*, United States patent numbers 3,638,058; 4,380,720; and 5,077,500, have, however, employed on a rudimentary level some of the techniques which have enabled the present inventors to achieve significant speeds of air movement and to do so without generating undesirable quantities of ozone and nitrogen oxides.

10 United States patent number 5,077,500, in order to ensure that all corona electrodes “work under mutually the same conditions and will thus all engender mutually the same corona discharge,” uses other electrodes to shield the corona electrodes from the walls of the duct (in which the device of that patent is to be installed) and from other corona electrodes. These other electrodes, according to lines
15 59 through 60 in column 3 of the patent, “. . . will not take up any corona current”

Also, United States patent number 4,380,720 employs multiple stages, each consisting of pairs of a corona electrode and an attracting electrode, so that the air molecules which have been accelerated to a given speed by one stage will be further accelerated to an even greater speed by the subsequent stage. United States patent
20 number 4,380,720 does not, however, recognize the need to neutralize substantially all ions and other electrically charged particles, such as dust, prior to their approaching the corona electrode of the subsequent stage in order to avoid having such ions and particles repelled by that corona electrode in an upstream direction, *i.e.*, the direction opposite to the velocity produced by the attracting electrode of the previous stage.

25 And United States patent number 5,077,500, on lines 25 through 29 of column 1, states, “The air ions migrate rapidly from the corona electrode to the target electrode, under the influence of the electric field, and relinquish their electric charge to the target electrode and return to electrically neutral air molecules.” The fact that the target electrode is not, however, so effective as to neutralize substantially all of the air ions is
30 apparent from the discussion of ion current between the corona electrode **K** and the surfaces **4**, which discussion is located on lines 15 through 27 in column 4.

Similarly, United States patent number 3,638,058 provides, on line 66 of column 1 through line 13 of column 2, “. . . it can be seen that with a high DC voltage

impressed between cathode point 12 and ring anode 18, an electrostatic field will result causing a corona discharge region surrounding point 14. This corona discharge region will ionize the air molecules in proximity to point 14 which, being charged particles of the same polarity as the cathode, will, in turn, be attracted toward ring anode 18 which will also act as a focusing anode. The accelerated ions will impart kinetic energy to neutral air molecules by repeated collisions and attachment. Neutral air molecules thus accelerated, constitute the useful mechanical output of the ion wind generator. The majority of ions, however, will end their usefulness upon reaching the ring 18 where they fan out radially and collide with the ring producing anode current. A small portion of the ions will possess sufficient kinetic energy to continue on through the ring along with the neutral particles. These result in a slight loss of efficiency because they tend to be drawn back to the anode. The same theory will apply for cathode 13 and anode 17. Since opposite polarities are impressed on each cathode-anode pair, their exiting airstreams will contain oppositely charged ions which will merge and neutralize; i.e., being of opposite polarity, the ions will attract each other and be neutralized by recombination." It is, however, not clear that substantially all ions which escape the electrodes will merge because many ions emerging from the anode on the left are likely to have such momentum toward the left that the electrical attraction for ions emerging from the anode on the right with momentum toward the right is insufficient to overcome such opposite momenta. Furthermore, the distance required for such recombination as does occur is very probably so great that it would be a detriment to using multiple stages to provide increased speed to the air.

DISCLOSURE OF INVENTION

The present Electrostatic Fluid Accelerator employs two fundamental techniques to achieve significant speeds in the fluid flow, which can be virtually any fluid but is most often air, and which will not produce substantial undesired ozone and nitrogen oxides when the fluid is air.

First, to accelerate the fluid molecules significantly without having to impart high velocities to the ions, many ions are created within a given area so that there is a high density, or pressure, of ions. This is achieved by placing a multiplicity of corona electrodes close to one another. The corona electrodes can be placed near one another because they are electrically shielded from one another by exciting electrodes which have a potential difference, compared to the corona electrodes, adequate to generate a

corona discharge. An exciting electrode is placed between adjacent corona electrodes and, thus, across the intended direction of flow for the fluid molecules.

In order to cause ions to create fluid flow, either the exciting electrode must be asymmetrically located between the adjacent corona electrodes (in order to create an asymmetrically shaped electric field that, unlike a symmetrical field, will force ions in a preferred direction) or there must be an accelerating electrode.

Preferably, in the case of an accelerating electrode, such accelerating electrode is an attracting electrode placed downstream from the corona electrodes in order to cause the ions to move in the intended direction. The electric polarity of the attracting electrode is opposite to that of the corona electrode.

It has, however, been experimentally determined that, when the corona electrodes are close to one another, if the electric potential of the exciting electrode is between that of the of the corona electrode and that of the attracting electrode, as in the case with respect to United States patent number 5,077,500, the rate of fluid flow decreases. Indeed, when the electric potential of the exciting electrodes is the same as that of the corona electrode, no fluid flow occurs. This effect results from the fact that the electric field strength between the exciting electrode and the corona electrodes is not adequate to cause a corona discharge and produce ions; the corona discharge between the corona electrode and the attracting electrode is suppressed; and the consequent lower density of ions is inadequate to produce the desired flow of fluid, or, as explained above, any flow at all when the electric potential of the exciting electrodes is the same as that of the corona electrode. Furthermore, when the corona electrodes are placed close together in order to increase the density of ions, as described above, the electric field between the corona electrodes and the exciting electrodes influences the electric field between the corona electrodes and the attracting electrode. Thus, to achieve desirable flow rates, it is preferable to maintain the electric field strength between the exciting electrodes and the corona electrodes at a level that will produce a corona discharge and, consequently, a current flow from the corona electrodes to the exciting electrodes.

Yet, since the rate of fluid flow can be controlled by varying the electric field strength between the exciting electrode and the corona electrodes and since such electric field strength can be adjusted by varying the electric potential of the exciting electrode, the electric potential of the exciting electrodes can be varied in order to

control the flow rate of the fluid with less expenditure of energy than when this is accomplished by controlling the potential of the attracting electrode.

Optionally, as suggested above, rather than using an attracting electrode as the accelerating electrode, a repelling electrode can be placed upstream from the corona electrode. The electrical polarity of the repelling electrode is the same as that of the corona electrode. From a repelling electrode, however, there is no corona discharge.

Second, in order to achieve the greatest flow of fluid, multiple stages of corona discharge devices are used with a collecting electrode between each stage. The collecting electrode has opposite electrical polarity to that of the corona electrodes. The collecting electrode is designed to preclude substantially all ions and other electrically charged particles from passing to the next stage and, therefore, being repelled by the corona electrodes of the next stage, which repulsion would retard the rate of fluid flow. The corona discharge device can be any such device that is known in the art but is preferably one utilizing the construction discussed above for increasing the density of ions.

A further optional technique for maximizing the density of ions is having a high-voltage power supply with a variable maximum voltage that depends on the corona current, which is defined as the total current from the corona electrode to any other electrode. The output voltage of the high-voltage power supply is inversely proportional to the corona current. Therefore, the voltage applied to the corona electrodes is reduced sufficiently, when the corona current indicates that a breakdown is imminent, that such breakdown is precluded. Without this option, the voltage between the corona electrodes and the other electrodes (except, of course, repelling electrodes, where no corona discharge is desired) must be manually maintained between the corona inception voltage and the breakdown voltage to have a sufficient electric field strength to create a corona discharge between the corona electrodes and the other electrodes without causing a spark-producing breakdown that would preclude the creation of the desired ions. The closer the voltage between such electrodes approaches, without actually attaining, the breakdown voltage, however, the greater will be the density of the ions that are generated.

The voltage applied to any electrode other than the corona electrode can, furthermore, also be used to control the direction of movement of the ions and, therefore, of the fluid. If desired, electrodes may be introduced for this purpose alone.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 illustrates schematically, by the way of example, a multiple corona and exciting electrodes arrangement.

5 Figure 2 illustrates schematically, by the way of example, another implementation of multiple corona and exciting electrodes arrangement.

Figure 3 illustrates schematically, by the way of example, a multiple corona and exciting electrodes arrangement including multiple attracting electrodes arrangement.

10 Figure 4 illustrates schematically, by the way of example, a multiple corona and exciting electrodes arrangement including multiple repelling electrodes arrangement.

Figure 5 illustrates schematically, by the way of example, a flexible top power supply flow diagram.

Figure 6 illustrates schematically, by the way of example, a flexible top power supply circuit diagram.

15 Figure 7 illustrates schematically, by the way of example, several stages of electrostatic fluid accelerators placed in series with respect to the desired fluid flow.

Figure 8 illustrates schematically, by the way of example, an electrostatic fluid accelerator that is capable of controlling fluid flow by changing a potential at the exciting electrodes.

20

BEST MODE FOR CARRYING OUT THE INVENTION

In order to successfully create the desired rate of fluid flow, the high-voltage power supply should generate an output voltage that is higher than the corona onset voltage but, no matter what the surrounding environmental conditions, below the
25 breakdown voltage.

To prevent a breakdown between electrodes, the high-voltage power supply should be sensitive to conditions that affect the breakdown voltage, such as humidity, temperature, etc. and reduce the output voltage to a level below the breakdown point.

30 Achieving this goal could require a rather costly high-voltage power supply with voltage and other sensors as well as a feedback loop control.

However, it was experimentally determined by the inventors that the corona current depends on the same conditions which affect the breakdown voltage. Thus, as indicated above, the voltage between the corona electrode and other electrodes (except the repelling electrodes, for which a corona discharge is not desired) should be

maintained between the corona onset voltage and the breakdown voltage; and a preferred technique for maximizing the density of ions without having a breakdown, no matter what the surrounding environmental conditions are, is to utilize a high-voltage power supply with a variable maximum voltage that is inversely proportional to the
5 corona current.

Such a high-voltage power supply is termed a "flexible top" high-voltage power supply.

The "flexible top" high-voltage power supply preferably consists of two power supply units connected in series. The first unit, which is termed the "base unit,"
10 generates an output voltage, termed the "base voltage," which is close to (above or below) the corona onset voltage and below the breakdown voltage and which, because of a low internal impedance in the unit, is only slightly sensitive to the output current. The second unit, which is termed the "flexible top," generates an output voltage that is much more sensitive to the output current than is the voltage of the base unit, *i.e.*, the
15 base voltage, because of a large internal impedance. If output current increases, the base voltage will remain almost constant whereas the output voltage from the flexible top decreases. It is a matter of ordinary skill in the art to select the values of circuit components which will assure that, for any foreseeable environmental conditions, the combined resultant output voltage from the base unit and the flexible top will be greater
20 than the corona onset voltage but less than the breakdown voltage.

Moreover, once the need for the flexible top has been recognized, ordinary skill in the art can supply various methods of achieving such a power supply.

Perhaps, the simplest example of the flexible top high-voltage power supply is the following: A traditional high-voltage power supply is used for the base unit, and a
25 step-up transformer with larger leakage inductance is employed in the flexible top. The alternating current flows through the leakage inductance, thereby creating a voltage drop across such inductance. The more current that is drawn, the more voltage drops across the leakage inductance; and the more voltage that is dropped across the leakage inductor, the less is the output voltage of the flexible top.

30 A second example of a flexible top high-voltage power supply utilizes a combination of capacitors of a voltage multiplier as depicted in Figure 6. The first set of capacitors have a much greater capacitance and, therefore, much lower impedance than the second set. Therefore, the voltage across the first set of capacitors (the base

unit) is relatively insensitive to the current whereas the voltage across the second set of capacitors (the flexible top) is inversely proportional to the current.

It will be appreciated that a flexible top high-voltage power supply is any combination of bases units and flexible tops connected in series that do not depart from
5 the spirit of the invention. Therefore, the flexible top high-voltage power supply may consist of any number of base units and flexible tops connected in series in any desired order so that the resultant output voltage is within the desired range.

The Electrostatic Fluid Accelerator of the present invention, thus, comprises a multiplicity of closely spaced corona electrodes with an exciting electrode
10 asymmetrically located between the corona electrodes. A flexible top high-voltage power supply preferably controls the voltage between the corona electrodes and the exciting electrodes so that such voltage is maintained between the corona onset voltage and the breakdown voltage.

Optionally, however, the voltage between the corona electrodes and the exciting
15 electrodes can be varied even outside the preceding range in order to vary the flow of the fluid which it is desired to move.

And in lieu of locating the exciting electrode asymmetrically between the corona electrodes, the Electrostatic Fluid Accelerator may further comprise an accelerating electrode.

20 The accelerating electrode may, as discussed above, either be an attracting electrode, a repelling electrode, or a combination of attracting and repelling electrodes.

An attracting electrode has electric polarity opposite to that of the corona electrode and is located, with respect to the desired direction of fluid flow, downstream from the corona electrode. The repelling electrode has the same electrical polarity as
25 the corona electrode and is situated, with respect to the desired direction of fluid flow, upstream from the corona electrode.

To assure that more ions and, consequently, more fluid particles, flow downstream, the exciting electrode can be constructed in the form of a plate that extends downstream with respect to the desired direction of fluid flow.

30 Finally, as discussed above, in order to achieve the greatest flow of fluid, multiple stages of corona discharge devices, and preferably the Electrostatic Fluid Accelerator of the present invention, are used with a collecting electrode placed between each stage. The collecting electrode has opposite electrical polarity to that of

the corona electrodes and is designed to preclude substantially all ions and other electrically charged particles from passing to the next stage, where they would tend to be repelled and thereby impair the movement of the fluid. Preferably, the collecting electrode is a wire mesh that extends substantially across the intended path for the fluid particles.

Figure 1 illustrates schematically a first embodiment of electrostatic fluid accelerator according to the invention which comprises multiple corona electrodes (1), multiple exciting electrodes (2), power supply (3). Corona electrodes (1) and exciting electrodes (2) are connected to the respective terminals of the power supply (3) by the means of conductors (4 and 5). The desired fluid flow is shown by an arrow. Corona electrodes (1) are located asymmetrically between exciting electrodes (2) with respect to the desired fluid flow. In the illustrated embodiment is assumed that corona electrodes (1) are wire-like electrodes (shown in cross section), exciting electrodes (2) are plate-like electrodes (also shown in cross section) and a power supply (3) is a DC power supply. It will be understood that corona electrodes may be of any shape that ensures corona discharge and subsequent ion emission from one or more parts of said corona electrode. In general corona electrodes may be made in shape of needle, barbed wire, serrated plates or plates having sharp or thin parts that facilitate electric field raise at the vicinity of these parts of the corona electrodes. It will be understood that power supply may generate any voltage (direct, alternating or pulse) that has a magnitude great enough to raise an electric field strength at the vicinity of the corona electrodes (1) above corona onset value. In accordance with the present invention, the corona electrodes (1), exciting electrodes (2) and conductors (4 and 5) of the embodiment illustrated in FIG. 1 are made of electrically conductive material that is capable to conduct a desired electrical current to the ion emitting parts of the corona electrodes and to the exciting electrodes. Corona electrodes (1) are supported by a frame (not shown) that ensures the corona electrodes (1) being parallel to the exciting electrodes (2). Power supply (3) generates voltage that creates an electric field in the space between the corona electrodes (1) and exciting electrodes (2). This electric field receives a maximum magnitude in the vicinity of the corona electrodes (1). When maximum magnitude of the electric field exceeds a corona onset voltage the corona electrodes (1) emit ions. Ions being emitted from the corona electrodes (1) are attracted to the exciting electrodes (2). Due to asymmetrical location of the corona electrodes (1)

and the exciting electrodes (2) ions receive more acceleration toward the desired fluid flow shown by an arrow. More ions will therefore flow to the right (as shown in FIG. 1) than to the left. Ion movement to the direction of the desired fluid flow creates fluid flow to this direction due to ions' collision with the fluid molecules.

5 Figure 2 illustrates schematically a second embodiment of electrostatic fluid accelerator according to the invention which comprises multiple corona electrodes (6), multiple exciting electrodes (7), power supply (8). Corona electrodes (6) and exciting electrodes (7) are connected to the respective terminals of the power supply (8) by the means of conductors (9 and 10). The desired fluid flow is shown by an arrow. Corona
10 electrodes (6) are located asymmetrically between exciting electrodes (7) with respect to the desired fluid flow. Corona electrodes (6) and exciting electrodes (7) are connected to the respective terminals of the power supply (8) by the means of conductors (9 and 10). The desired fluid flow is shown by an arrow. Corona electrodes (6) are located asymmetrically between exciting electrodes (7) with respect to the
15 desired fluid flow. In the illustrated embodiment is assumed that corona electrodes (6) are razor-like electrodes (shown in cross section), exciting electrodes 7 are plate-like electrodes (also shown in cross section) and a power supply (8) is a DC power supply. It will be understood FIG. 2 may as well represent the corona electrodes (6) in a shape of needles and the exciting electrodes (7) located asymmetrically between the corona
20 needle-like electrodes. The preferred shape of the exciting electrodes (7) will be, but not limited to, honeycomb that separate the corona electrodes (6) from each other, said corona electrodes (6) are located near the center of the honeycomb-like exciting electrodes (7). The power supply (8) may, as in previous embodiment generate any voltage (direct, alternating or pulse) that has a magnitude great enough to raise an
25 electric field strength at the vicinity of the parts of the corona electrodes (6) that exceeds a corona onset value. In accordance with the present invention, the corona electrodes (6), exciting electrodes (7) and conductors (9 and 10) of the embodiment illustrated in FIG. 2 are made of electrically conductive material that is capable of conducting a desired electrical current to the ion emitting parts of the corona electrodes
30 (6) to the exciting electrodes (7). Corona electrodes (6) are supported by a frame (not shown) that ensures the corona electrodes (6) being parallel to the exciting electrodes (7). Power supply (8) generates voltage that creates an electric field in the space between the corona electrodes (6) and exciting electrodes (7). This electric field

receives a maximum magnitude in the vicinity of the sharp edges (or sharp points in case of needle-like corona electrodes) of the corona electrodes (6). When maximum magnitude of the electric field exceeds a corona onset voltage the corona electrodes (6) emit ions. Ions being emitted from the sharp edges (or points) of the corona electrodes (6) are attracted to the exciting electrodes (7). Due to asymmetrical location of the corona electrodes (6) and the exciting electrodes (7) ions receive more acceleration toward the desired fluid flow shown by an arrow. More ions will therefore flow to the right (as shown in FIG. 2) than to the left. Ions' movement to the direction of the desired fluid flow creates fluid flow to this direction due to ions' collision with the fluid molecules.

Figure 3 illustrates schematically a third embodiment of electrostatic fluid accelerator according to the invention which comprises multiple corona electrodes (11), multiple exciting electrodes (12), multiple attracting electrodes (13), power supply (14). Corona electrodes (11) from one hand and exciting electrodes (12) and attracting electrodes (13) from other hand are connected to the respective terminals of the power supply (14) by the means of conductors (15 and 16). The desired fluid flow is shown by an arrow. Corona electrodes (11) are located between exciting electrodes (12) and separated by the last from each other. As an example wire-like corona electrodes (11) are shown in cross section, exciting electrodes (12) are plate-like electrodes and attracting electrodes (13) are wire-like or rod-like electrodes (also shown in cross section) and a power supply (14) is a DC power supply. It will be understood FIG. 3 may as well represent the corona electrodes (11) in any other shape that ensures electric field strength in the vicinity of the corona electrodes (11) great enough to initiate corona discharge. The power supply (14) may, as in previous embodiments (FIG. 1 and FIG. 2) generate any voltage (direct, alternating or pulse) that has a magnitude great enough to raise an electric field strength at the vicinity of the parts of the corona electrodes (11) that exceeds a corona onset value. In accordance with the present invention, the corona electrodes (11), exciting electrodes (12), attracting electrodes (13) and conductors (15 and 16) of the embodiment illustrated in FIG. 3 are made of electrically conductive material that is capable of conducting a desired electrical current to the ion emitting parts of the corona electrodes to the exciting electrodes (12) and to the attracting electrodes (13). Corona electrodes (11) are supported by a frame (not shown) that ensures the corona electrodes (11) being substantially parallel to the

exciting electrodes (12) and to the attracting electrodes (13). Power supply (14) generates voltage that creates an electric field in the space between the corona electrodes (11) and exciting electrodes (12) and the attracting electrodes (13). This electric field receives a maximum magnitude in the vicinity of the corona electrodes (11) (or sharp edges or sharp points in case of razor-like or needle-like corona electrodes). When the maximum magnitude of the electric field exceeds a corona onset voltage the corona electrodes (11) emit ions. Ions being emitted from the sharp edges (or points) of the corona electrodes (11) are attracted to the exciting electrodes (12) and to the attracting electrodes (13). Due to electrostatic force ions receive acceleration toward the desired fluid flow shown by an arrow. Ions will therefore flow to the right (as shown in FIG. 3). Ions' movement in the direction of the desired fluid flow creates fluid flow in this direction due to ions' collision with the fluid molecules.

Figure 4 illustrates schematically a fourth embodiment of electrostatic fluid accelerator according to the invention which comprises multiple corona electrodes (17), multiple exciting electrodes (18), multiple repelling electrodes (19), power supply (20). Corona electrodes (17) together with repelling electrodes (19) from one hand and exciting electrodes (18) from other hand are connected to the respective terminals of the power supply (20) by the means of conductors (21 and 22). The desired fluid flow is shown by an arrow. Corona electrodes (17) are located between exciting electrodes (18) and separated by the latter from each other. As an example wire-like corona electrodes (17) are shown in cross section, exciting electrodes (18) are plate-like electrodes and repelling electrodes (19) are wire-like or rod-like electrodes (also shown in cross section) and a power supply (20) is a DC power supply. It will be understood FIG. 4 may as well represent the corona electrodes (17) in any other shape that ensures electric field strength in the vicinity of the corona electrodes (17) great enough to initiate corona discharge. The power supply (20) may, as in previous embodiments generate any voltage (direct, alternating or pulse) that has a magnitude great enough to raise an electric field strength at the vicinity of the parts of the corona electrodes (17) that exceeds a corona onset value. In accordance with the present invention, the corona electrodes (17), exciting electrodes (18), repelling electrodes (19) and conductors (21 and 22) of the embodiment illustrated in FIG. 4 are made of electrically conductive material that is capable to conduct a desired electrical current to the ion emitting parts of the corona electrodes to the exciting electrodes (17). Corona electrodes (17) are

supported by a frame (not shown) that ensures the corona electrodes (17) being substantially parallel to the exciting electrodes (18) and to the repelling electrodes (19). Power supply (20) generates voltage that creates an electric field in the space between the corona electrodes (17) and exciting electrodes (18). This electric field receives a maximum magnitude in the vicinity of the corona electrodes (17) (or sharp edges or sharp points in case of razor-like or needle-like corona electrodes). When maximum magnitude of the electric field exceeds a corona onset voltage the corona electrodes (17) emit ions. Ions being emitted from the sharp edges (or points) of the corona electrodes (17) are attracted to the exciting electrodes (18) and at the same time are repelled from repelling electrodes (19). Due to electrostatic force ions receive acceleration toward the desired fluid flow shown by an arrow. Ions will therefore flow to the right (as shown in FIG. 4). Ions' movement to the direction of the desired fluid flow creates fluid flow to this direction due to ions' collision with the fluid molecules. It will be understood that the repelling electrodes (19) may be made of any shape that ensures that an electric strength in the vicinity of the repelling electrodes (19) is below corona onset value. To ensure that comparatively low value the repelling electrodes (19) may be made of greater main size than the corona electrodes (17). As another option the repelling electrodes (19) may not have sharp edges or do not have serrated surface.

Figure 5 illustrates schematically flexible top power supply flow diagram. According to the invention the power supply consists of two functional parts - base part (23) and flexible part (24). The base part (23) produces output voltage (25) and flexible top part (24) produces output voltage (26). Both voltages (25 and 26) gives output voltage of power supply that is equal to their sum, i.e. (27). Each part of power supply in FIG. 5 may be made of any of known design. It may be a transformer-rectifier, or voltage multiplier, or fly-back configuration, or combination of the above. The base part (23) and flexible top part (24) may be of similar or different design as well. The only difference between the base part (23) and the flexible top part (24) that is relevant to the purpose of this invention is the dependence of output voltage of output current. The base part (23) generates output voltage (25) that is less dependent on output current. The flexible top part (24) generates output voltage (26) that drops significantly with output current increase. The base part (23) generates output voltage (25) that is close to the corona onset voltage of the corona electrodes. This voltage (25) may be

equal to the corona onset voltage or it may be slightly more or less than that corona onset voltage. This corona onset voltage depends on the electrodes geometry and environment as well. It is experimentally determined that the corona onset voltage has smaller value under higher temperature. From the other hand the base voltage (25) should not be greater than breakdown voltage between the corona and other electrodes. This breakdown voltage also varies with temperature and other factors. Therefore it is desirable to maintain voltage (25) at the level that is close to the corona onset voltage but does not exceed breakdown voltage under any environment condition specific for an application. The flexible part (24) generates output voltage that in combination with the voltage (25) gives total output voltage (27) that is greater than corona onset voltage but lesser than breakdown voltage. It is experimentally determined that corona current depends of the voltage between the electrodes nonlinearly. Corona current starts at the corona onset voltage and reaches maximum value as the voltage approaches a breakdown level. To ensure that total output voltage of power supply will never reach a breakdown level output voltage (26) decreases as the corona current approaches its maximum value. At the same time total output voltage (27) will always be above corona onset level. This ensures corona discharge and fluid flow at any condition.

Figure 6 illustrates flexible top power supply circuit diagram. Power supply shown in FIG. 6 generates high voltage at the level between 10,000V and 15,000V. Power train of this power supply consists of power transistor Q1, High Voltage fly-back inductor T1 and voltage multiplier (capacitors C1 - C8 and diodes D8 - D15). Pulse Width Modulator Integrated Circuit UC3843N periodically switches transistor Q1 ON and OFF with frequency that exceed audible frequency to ensure silent operation. Potentiometer 5k controls duty cycle and is used for output voltage control. Shunt 1 Ohm connected between Q1 source and ground senses output current and turns transistor Q1 OFF if current exceeds preset level. The preset level in power supply shown in FIG. 6 is equal approximately 1A. Capacitors C1 - C6 have value that exceeds the value of the capacitors C6 - C7. The sum of the voltages across capacitors C1, C4 and C6 constitutes the base voltage (25). The voltage across capacitor C8 represents the flexible top voltage (26). The sum of the voltages (25 and 26) represents output voltage (27) of the flexible top power supply. It will be understood that any configuration of power supply of a combination of power supplies that consists of one or more base parts or power supplies and one or more parts or flexible top power supplies falls under

spirit of this invention. As an another example of such flexible top power supply simplest transformer-rectifier configuration may be considered (not shown here). The transformer may consist of a primary winding and at least two secondary windings. Each secondary winding is connected to a separate rectifier. The DC outputs of these
5 rectifiers are connected in series. One of the secondary windings has greater leakage inductance with respect to the primary winding than the leakage inductance of another secondary winding with respect to the primary winding. When a corona current grows voltage drop across that greater leakage inductance grows and output voltage of the power supply decreases to safe level.

10 Figure 7 illustrates several stages (28, 29 and 30) of an electrostatic fluid accelerator placed in series with respect to the desired fluid flow. In accordance to the present invention each stage is separated from another stage by the collecting electrodes (31 and 32). Each stage (28, 29 and 30) is powered by power supply (33) and accelerates fluid by generating ions at corona discharge and then accelerating ions
15 toward the desired fluid flow (shown by the arrow). Ions and other charged particles travel from the vicinity of the corona electrodes through the area surrounded by the exciting electrodes and toward next stage. Part of these ions and particles settle on the exciting electrodes. Part of these particles, however, travel beyond the electrodes of a particular stage. These ions and particles go as far as to the next stage and repel from
20 the corona electrodes of the next stage. Ions and particles slow their movement toward the desired fluid movement and even travel back in the opposite direction. This event decreases total fluid velocity and fluid accelerator efficiency. To prevent such an event collecting electrodes (31 and 32) are installed in between of the stages. These collecting electrodes are placed close to each other and connected to the polarity that is opposite
25 to the polarity of the corona electrodes. Ions and charged particles that travel beyond the stages are attracted to the collecting electrodes (31 and 32) and give their charge to these electrodes. By that means no or almost no charged particles travel to the next stage. In the FIG. 7 all collecting electrodes are connected to the same power supply (33) terminal as the exciting electrodes of the stage (28, 29 and 30). It will be
30 understood that these collecting electrodes may be connected to or be under any electric potential that is opposite to the potential of the corona electrodes. It will be understood that some of the electrodes may be connected to different power supplies including variable power supplies.

Figure 8 illustrates an electrostatic fluid accelerator that is capable of controlling fluid flow by changing a potential at the exciting electrodes. The electrostatic fluid accelerator shown in FIG. 8 consists of multiple corona electrodes (41), multiple exciting electrodes (34) and multiple attracting electrodes (35). The geometry and mutual locating of all the electrodes is similar to what is shown in FIG. 3. The electrostatic fluid generator shown in FIG. 8 is powered by two power supplies. The attracting electrodes (35) are connected to the common point of the two power supplies. This common point is shown as a ground, but may be at any arbitrary electric potential. Power supply (36) is connected to the common point by means of conductors (40) and to the corona electrodes (41) by the mean of conductors (38). Power supply (36) produces stable DC voltage. Power supply (37) is connected to the common point by conductors (40) and to the exciting electrodes (34) by conductors (39). Power supply (37) produces variable DC voltage.

If electric field strength in the area between the corona electrodes (41) and the exciting electrodes (34) is approximately equal to the electric field strength in the area between the corona electrodes (41) and the attracting electrodes (35) the electric current's magnitude that flows from the corona electrodes (41) to the exciting electrodes (34) is approximately equal to the electric current's magnitude that flows from the corona electrodes (41) to the attracting electrodes (35). It is experimentally determined that approximately equal electric field strength is most favorable for the corona discharge for the described electrodes geometry and mutual location. It was further determined that when the electric field strength in the area between the corona electrodes (41) and the exciting electrodes (34) is less than that of the electric field strength in the area between the corona electrodes (41) and the attracting electrodes (35) the corona discharge is suppressed and fewer ions are emitted from the corona discharge. When electric field strength in the area between the corona electrodes (41) and the exciting electrodes (34) is approximately half of the electric field strength in the area between the corona electrodes (41) and the attracting electrodes (35) the corona discharge is almost totally suppressed and almost no fewer ions are emitted from the corona discharge and no fluid movement is detected.

It will be understood that because of nature of a corona discharge a flexible top power supply may be successfully used with any combination of electrodes for corona discharge initiating and maintenance.

It will be further understood that any set of multiple electrodes may be located and/or secured on the separate frame. This frame must have an opening through which fluid freely flows. It may be a rectangular frame or u-shape frame or any other. Two or more frames on which the multiple set of the electrodes is located are then secured in the manner that ensures sufficient distance along the surface to prevent so called creeping discharge along this surface.

The above arrangements were successfully tested. The distance between exciting electrodes was 2 to 5 mm., the diameter of the corona electrodes was 0.1 mm and the exciting electrodes' width was about 12 mm. The attracting electrodes' diameter was 0.75 mm. The corona electrodes were made of tungsten wire while the exciting electrodes were made of aluminum foil, and the exciting electrodes were made of brass and steel rods. At a voltage for the corona electrodes (the exciting and attracting electrodes being grounded) in the magnitude of 2,000 volts to 7,500 volts, air flow was measured at a maximum rate of 950 feet per minute. In terms of the voltage applied to the exciting electrodes, air flow was at a maximum value when the exciting electrodes' potential was close to voltage of the attracting electrodes. When the potential at the exciting electrodes approached the potential of the corona electrodes, the air flow decreased and eventually dropped to an undetectable level.

20 INDUSTRIAL APPLICABILITY

The way in which the electrostatic fluid accelerator is capable of exploitation in industry and the way in which the electrostatic fluid accelerator can be made and used are obvious from the description and the nature of the electrostatic fluid accelerator.

CLAIMS

We claim:

1. An electrostatic fluid accelerator, which comprises:
a multiplicity of closely spaced corona electrodes (1); and
at least one exciting electrode (2) asymmetrically located between said corona electrodes (1).
2. The electrostatic fluid accelerator as recited in claim 1, wherein:
the voltage between said corona electrodes (1) and said exciting electrodes (2) is maintained between the corona onset voltage and the breakdown voltage.
3. The electrostatic fluid accelerator as recited in claim 2, wherein:
the voltage between said corona electrodes (1) and said exciting electrodes (2) is controlled by a flexible top high-voltage power supply.
4. The electrostatic fluid accelerator as recited in claim 3, wherein:
said exciting electrode (2) is a plate or set of plates that extend downstream with respect to the desired direction of fluid flow.
5. The electrostatic fluid accelerator as recited in claim 4, further comprising:
one or more additional electrostatic fluid accelerators as recited in claim 4, each of said additional electrostatic fluid accelerators being located downstream, with respect to the desired direction of fluid flow, from said preceding electrostatic fluid accelerator; and
at least one collecting electrode (31 or 32) located between at least one pair of said electrostatic fluid accelerators.
5. The electrostatic fluid accelerator as recited in claim 3, further comprising:
one or more additional electrostatic fluid accelerators as recited in claim 3, each of said additional electrostatic fluid accelerators being located downstream, with respect to the desired direction of fluid flow, from said preceding electrostatic fluid accelerator; and
at least one collecting electrode (31 or 32) located between at least one pair of said electrostatic fluid accelerators.

7. The electrostatic fluid accelerator as recited in claim 2, wherein:
said exciting electrode (2) is a plate that extends downstream with respect to the desired direction of fluid flow.

8. The electrostatic fluid accelerator as recited in claim 7, further comprising:

one or more additional electrostatic fluid accelerators as recited in claim 7, each of said additional electrostatic fluid accelerators being located downstream, with respect to the desired direction of fluid flow, from said preceding electrostatic fluid accelerator; and

at least one collecting electrode (31 or 32) located between at least one pair of said electrostatic fluid accelerators.

9. The electrostatic fluid accelerator as recited in claim 2, further comprising:

one or more additional electrostatic fluid accelerators as recited in claim 2, each of said additional electrostatic fluid accelerators being located downstream, with respect to the desired direction of fluid flow, from said preceding electrostatic fluid accelerator; and

at least one collecting electrode (31 or 32) located between at least one pair of said electrostatic fluid accelerators.

10. The electrostatic fluid accelerator as recited in claim 1, wherein:
the voltage between said corona electrodes (1) and said exciting electrodes (2) is variable, even outside the range between the corona onset voltage and the breakdown voltage.

11. The electrostatic fluid accelerator as recited in claim 10, wherein:
said exciting electrode (2) is a plate that extends downstream with respect to the desired direction of fluid flow.

12. The electrostatic fluid accelerator as recited in claim 11 further comprising:

one or more additional electrostatic fluid accelerators as recited in claim 11, each of said additional electrostatic fluid accelerators being located downstream, with respect to the desired direction of fluid flow, from said preceding electrostatic fluid accelerator; and

at least one collecting electrode (31 or 32) located between at least one pair of said electrostatic fluid accelerators.

13. The electrostatic fluid accelerator as recited in claim 10 further comprising:

one or more additional electrostatic fluid accelerators as recited in claim 10, each of said additional electrostatic fluid accelerators being located downstream, with respect to the desired direction of fluid flow, from said preceding electrostatic fluid accelerator; and

at least one collecting electrode (31 or 32) located between at least one pair of said electrostatic fluid accelerators.

14. An electrostatic fluid accelerator, which comprises:

a multiplicity of closely spaced corona electrodes (1);

at least one exciting electrode (34) located between said corona electrodes (1); and

at least one accelerating electrode.

15. The electrostatic fluid accelerator as recited in claim 14, wherein:

the voltage between said corona electrodes (1) and said accelerating electrodes is maintained between the corona onset voltage and the breakdown voltage.

16. The electrostatic fluid accelerator as recited in claim 14, wherein:

the voltage between said corona electrodes (1) and said exciting electrodes (34) is maintained between the corona onset voltage and the breakdown voltage.

17. The electrostatic fluid accelerator as recited in claim 16, wherein:

the accelerating electrode is an attracting electrode (13), said attracting electrode (13) having opposite electrical polarity to that of said corona electrodes (1) and said attracting electrode (13) being located, with respect to the desired direction of fluid flow, downstream from said corona electrodes (1).

18. The electrostatic fluid accelerator as recited in claim 17, wherein:

the voltage between said corona electrodes (1) and said exciting electrode (34) is controlled by a flexible top high-voltage power supply.

19. The electrostatic fluid accelerator as recited in claim 18, wherein:
said exciting electrode (34) is a plate that extends downstream with respect to the desired direction of fluid flow.

20. The electrostatic fluid accelerator as recited in claim 19, further comprising:

one or more additional electrostatic fluid accelerators as recited in claim 19, each of said additional electrostatic fluid accelerators being located downstream, with respect to the desired direction of fluid flow, from said preceding electrostatic fluid accelerator; and

at least one collecting electrode (31 or 32) located between at least one pair of said electrostatic fluid accelerators.

21. The electrostatic fluid accelerator as recited in claim 18, further comprising:

one or more additional electrostatic fluid accelerators as recited in claim 18, each of said additional electrostatic fluid accelerators being located downstream, with respect to the desired direction of fluid flow, from said preceding electrostatic fluid accelerator; and

at least one collecting electrode (31 or 32) located between at least one pair of said electrostatic fluid accelerators.

22. The electrostatic fluid accelerator as recited in claim 17, wherein:
said exciting electrode (34) is a plate that extends downstream with respect to the desired direction of fluid flow.

23. The electrostatic fluid accelerator as recited in claim 22, further comprising:

one or more additional electrostatic fluid accelerators as recited in claim 22, each of said additional electrostatic fluid accelerators being located downstream, with respect to the desired direction of fluid flow, from said preceding electrostatic fluid accelerator; and

at least one collecting electrode (31 or 32) located between at least one pair of said electrostatic fluid accelerators.

24. The electrostatic fluid accelerator as recited in claim 17, further comprising:

5 one or more additional electrostatic fluid accelerators as recited in claim 17, each of said additional electrostatic fluid accelerators being located downstream, with respect to the desired direction of fluid flow, from said preceding electrostatic fluid accelerator; and

at least one collecting electrode (31 or 32) located between at least one pair of said electrostatic fluid accelerators.

25. The electrostatic fluid accelerator as recited in claim 16, wherein:

5 the accelerating electrode is a repelling electrode (19), said repelling electrode (19) having the same electrical polarity as that of said corona electrodes (1) and said repelling electrode (19) being located, with respect to the desired direction of fluid flow, upstream from said corona electrodes (1).

26. The electrostatic fluid accelerator as recited in claim 25, wherein:

the voltage between said corona electrodes (1) and said exciting electrode (34) is controlled by a flexible top high-voltage power supply.

27. The electrostatic fluid accelerator as recited in claim 26, wherein:

said exciting electrode (34) is a plate or set of plates that extends downstream with respect to the desired direction of fluid flow.

28. The electrostatic fluid accelerator as recited in claim 27, further comprising:

5 one or more additional electrostatic fluid accelerators as recited in claim 27, each of said additional electrostatic fluid accelerators being located downstream, with respect to the desired direction of fluid flow, from said preceding electrostatic fluid accelerator; and

at least one collecting electrode (31 or 32) located between at least one pair of said electrostatic fluid accelerators.

29. The electrostatic fluid accelerator as recited in claim 26, further comprising:

5 one or more additional electrostatic fluid accelerators as recited in claim 26, each of said additional electrostatic fluid accelerators being located downstream, with respect to the desired direction of fluid flow, from said preceding electrostatic fluid accelerator; and

at least one collecting electrode (31 or 32) located between at least one pair of said electrostatic fluid accelerators.

30. The electrostatic fluid accelerator as recited in claim 25, wherein:
said exciting electrode (34) is a plate that extends downstream with respect to the desired direction of fluid flow.

31. The electrostatic fluid accelerator as recited in claim 30, further comprising:

one or more additional electrostatic fluid accelerators as recited in claim 30, each of said additional electrostatic fluid accelerators being located downstream, with respect to the desired direction of fluid flow, from said preceding electrostatic fluid accelerator; and

at least one collecting electrode (31 or 32) located between at least one pair of said electrostatic fluid accelerators.

32. The electrostatic fluid accelerator as recited in claim 25, further comprising:

one or more additional electrostatic fluid accelerators as recited in claim 25, each of said additional electrostatic fluid accelerators being located downstream, with respect to the desired direction of fluid flow, from said preceding electrostatic fluid accelerator; and

at least one collecting electrode (31 or 32) located between at least one pair of said electrostatic fluid accelerators.

33. The electrostatic fluid accelerator as recited in claim 14, wherein:
the voltage between said corona electrodes (1) and said exciting electrodes (34) is variable, even outside the range between the corona onset voltage and the breakdown voltage.

34. The electrostatic fluid accelerator as recited in claim 33, wherein:
the accelerating electrode is an attracting electrode (13), said attracting electrode (13) having opposite electrical polarity to that of said corona electrodes (1) and said attracting electrode (13) being located, with respect to the desired direction of fluid flow, downstream from said corona electrodes (1).

35. The electrostatic fluid accelerator as recited in claim 34, wherein:
said exciting electrode (34) is a plate that extends downstream with respect to the desired direction of fluid flow.

36. The electrostatic fluid accelerator as recited in claim 35 further comprising:

5 one or more additional electrostatic fluid accelerators as recited in claim 35, each of said additional electrostatic fluid accelerators being located downstream, with respect to the desired direction of fluid flow, from said preceding electrostatic fluid accelerator; and

at least one collecting electrode (31 or 32) located between at least one pair of said electrostatic fluid accelerators.

37. The electrostatic fluid accelerator as recited in claim 34 further comprising:

5 one or more additional electrostatic fluid accelerators as recited in claim 34, each of said additional electrostatic fluid accelerators being located downstream, with respect to the desired direction of fluid flow, from said preceding electrostatic fluid accelerator; and

at least one collecting electrode (31 or 32) located between at least one pair of said electrostatic fluid accelerators.

38. The electrostatic fluid accelerator as recited in claim 33, wherein:

5 the accelerating electrode is a repelling electrode (19), said repelling electrode (19) having the same electrical polarity as that of said corona electrodes (1) and said repelling electrode (19) being located, with respect to the desired direction of fluid flow, upstream from said corona electrodes (1).

39. The electrostatic fluid accelerator as recited in claim 38, wherein:

said exciting electrode (34) is a plate that extends downstream with respect to the desired direction of fluid flow.

40. The electrostatic fluid accelerator as recited in claim 39 further comprising:

5 one or more additional electrostatic fluid accelerators as recited in claim 39, each of said additional electrostatic fluid accelerators being located downstream, with respect to the desired direction of fluid flow, from said preceding electrostatic fluid accelerator; and

at least one collecting electrode (31 or 32) located between at least one pair of said electrostatic fluid accelerators.

41. The electrostatic fluid accelerator as recited in claim 38 further comprising:

5 one or more additional electrostatic fluid accelerators as recited in claim 38, each of said additional electrostatic fluid accelerators being located downstream, with respect to the desired direction of fluid flow, from said preceding electrostatic fluid accelerator; and

at least one collecting electrode (31 or 32) located between at least one pair of said electrostatic fluid accelerators.

42. An electrostatic fluid accelerator, which comprises:

any corona discharge device that is well known in the art for moving a fluid;

5 one or more additional corona discharge devices that are well known in the art for moving a fluid, each of said additional corona discharge devices being located downstream, with respect to the desired direction of fluid flow, from said preceding corona discharge device; and

at least one collecting electrode (31 or 32) located between at least one pair of said electrostatic fluid accelerators.

43. A flexible top high-voltage power supply, which comprises:

a base unit (23) that produces a voltage which is only slightly sensitive to the output current of the power supply;

5 a second unit (24) that produces an output voltage which decreases with increasing output current from the power supply; and

a means for combining the voltages from said base unit and said second unit.

44. A device employing electrodes, which comprises:

a set of electrodes capable of producing a corona discharge; and

a flexible top high-voltage power supply electrically connected to said set of electrodes.

45. The device employing electrodes as recited in claim 44, wherein:

at least one set of electrodes is located in a separate frame having an opening for free fluid passage.




Fig. 1




Fig. 2




Fig. 3




Fig. 4

5/8




Fig. 5




Fig. 6

7/8




Fig. 7




Fig. 8

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US00/28412

A. CLASSIFICATION OF SUBJECT MATTER
 IPC(7) : H01J 7/24; H01J 27/00
 US CL : 315/111.91, 111.61; 250/423 R
 According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED
 Minimum documentation searched (classification system followed by classification symbols)
 U.S. : U.S.: 315/111.91, 111.81, 111.61, 111.31, 111.01, 111.21; 250/324, 423, 426

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)
 East, Derwent, EPO, JPO
 corona, electrostatic, electrode, exciting, collecting

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X ---- Y	US 5,077,500 A (Torok et al.) 31 December 1991, (31/12/91) Figs. 3, 4	1, 2, 7 ----- 4
X ---- Y	US 4,567,541 A (Terai) 28 January 1986, (28/01/86) Figs. 3, 6, 7	43 ----- 2, 3, 10, 15, 16, 18, 44
X ---- Y	US 4,600,411 A (Santamaria) 15 July 1986, (15/07/86) abstract, Fig. 1	43 ----- 2, 3, 10, 15, 16, 18, 44

Further documents are listed in the continuation of Box C. See patent family annex.

* Special categories of cited documents:	*T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
A document defining the general state of the art which is not considered to be of particular relevance	*X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
E earlier document published on or after the international filing date	*Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*&* document member of the same patent family
O document referring to an oral disclosure, use, exhibition or other means	
P document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search 15 DECEMBER 2000	Date of mailing of the international search report 12 JAN 2001
---	--

Name and mailing address of the ISA/US Commissioner of Patents and Trademarks Box PCT Washington, D.C. 20231 Facsimile No. (703) 305-3230	Authorized officer <i>EPHREM ALEMU</i> Telephone No. (703) 306-5983
---	---

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US00/28412

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5,055,118 A (Nagoshi et al.) 08 October 1991, (08/10/91) Figs. 1-11	1-45