

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 0 583 225 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention
of the grant of the patent:
20.11.1996 Bulletin 1996/47

(51) Int Cl.⁶: **G07F 9/02**, G07F 11/18

(21) Application number: **93830294.0**

(22) Date of filing: **06.07.1993**

(54) Improved apparatus for dispensing goods items

Verbesserte Vorrichtung zum Ausgeben von Warenstücken

Appareil perfectionné pour la distribution d'articles

(84) Designated Contracting States:
DE ES FR GB IE IT

(30) Priority: **16.07.1992 IT BO920278**

(43) Date of publication of application:
16.02.1994 Bulletin 1994/07

(73) Proprietor: **MECCANICA RIGO DI RIGO
LAMBERTO e C. s.n.c.
I-40033 Casalecchio di Reno (Bologna) (IT)**

(72) Inventor: **Lamberto, Rigo
I-40033 Casalecchio di Reno (Bologna) (IT)**

(74) Representative: **Dall'Olio, Giancarlo
INVENTION s.n.c.
Via del Cestello, 13
40124 Bologna (IT)**

(56) References cited:
**GB-A- 368 848 GB-A- 480 636
GB-A- 912 801 US-A- 1 686 949
US-A- 1 778 187**

EP 0 583 225 B1

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

Description

The invention relates to the technical field concerned with the production of automatic dispensing apparatuses.

Particularly the invention is directed to those apparatuses which dispense goods items encased in uniform, rigid wrappings.

Substantially, these dispensing apparatuses must comply with the following requirements:

- guaranteed working operation;
- good protection against robbery attempts of money or items;
- low production and maintenance costs.

Known dispensing apparatuses may be divided in two groups: a first group includes only mechanical apparatuses; a second group includes electro-mechanical apparatuses.

The apparatuses belonging to the first group are generally less expensive than the ones belonging to the second group, but involve problems in their working.

On the other hand, the second group dispensing apparatuses are generally more sophisticated than the ones belonging to the first group, but involve higher costs.

In many mechanical apparatuses it was found to be relatively easy to withdraw with fraud the goods items contained therein.

This fraud easiness is due to the conformation of the dispensing apparatuses, which include a store compartment within which there is located a stack of items resting on a slide that can be moved from outside.

In the forward stroke of the slide, the stack progressively looses the support given thereby, until the end of the slide stroke, when it goes to rest onto a surface positioned beneath the slide.

The backward stroke of the slide results in withdrawing a prefixed number of items to the outside through an opening made in the side walls of the slide and store compartment.

It appears that, with the help of a small hook or the like, it is possible to withdraw a number of items, while keeping the slide at the end position of the forward stroke.

Document GB-A-912.801 relates to a coil freed mechanism which supplies articles such as sweets or cigarettes from a machine to which the mechanism is applied in response to insertion of coins or tokens. The machine includes two box-shaped cases fitted one into the other one.

The inner case supports the coin released actuating mechanism for effecting delivery of the articles.

The outer case has a slot for insertion of the coins, set in register with the entry to the coin selection mechanism.

The articles to be delivered are stacked into a ver-

tically extending magazine located into the inner case, along with the coin released mechanism for delivery of the articles.

A shutter mechanism is mounted on the inside face of the outer case to prevent insertion of coins when the machine is empty, and is operated by a weight member placed on top of the stack of articles and provided with a projecting finger that engages the shutter mechanism.

Document GB-A-368.848 discloses a coin freed vending machine having a coin stop formed by opposed walls which are spaced apart a distance slightly less than the diameter of the coin. Pivotal spring controlled detents normally project in front of the coin and are arranged so that when turned about their pivots, due to movement of the coin, they release a drawer for delivery of the articles stacked inside a casing.

On top of the stack of articles there is placed a weight connected to a tape that is secured to a counter-weight. The tape bears a series of numbers and is brought to pass close to a window through which the number can be read to know the number of articles still available. The weight has also a finger projection that, after the last article has been delivered, closes the coin insertion slot.

It is an object of the present invention to provide a mechanical type dispensing apparatus which enables correct working in all operating conditions, and which requires low production and maintenance costs.

Yet another object of the present invention is to provide a dispensing apparatus that can easily be transformed in a money-change machine while keeping the same criteria as far as safety and cheapness are concerned.

The characteristic features of the present invention, which do not come out from what has been stated above, will be set forth in the following, with particular reference to the accompanying drawings, in which:

- Fig. shows a front view of the dispensing apparatus as it is seen from outside;
- Fig.2 shows a top view of the dispensing apparatus;
- Figs 3a,3b,3c show cross-sections of the dispensing apparatus taken along the plane III-III of Fig.1, each in a particular operating stages;
- Fig.4 shows a view taken along the plane IV-IV of Fig.3c.
- Fig.5 shows a top view of a different embodiment;
- Fig.6 shows a view taken along the plane IV-IV of Fig.5.

Referring to the above figures, reference numeral 100 indicates an item dispensing apparatus, of fully mechanical type.

The dispensing apparatus includes a structure 1 made up of a vertical wall 1a and a horizontal wall 1b, arranged so as to form a "L".

The structure 1 is designed for being inserted into a suitable support (that is not shown) and blocked there-

in.

The structure 1 supports a coin acceptor 2 (of known type) wherein there is a first slot 3 sized for the insertion of coins and/or tokens having a prefixed size and corresponding to a certain monetary value (see Fig. 1).

The coin (or token) is first inserted in the slot and then is conveyed to a specially made recess. If it is not considered valid or proper, the coin or token may be given back by bringing it to the outside through a second slot 4 that is situated under the first one, when the user pushes a first push-button 5.

If the coin (or token) is instead considered valid and proper, then it will cause a mechanical block to be released, thus allowing the operation of a mechanism 50 that is designed to withdraw a prefixed number of items 7 and to deliver them to the outside.

The operation of the mechanism 50 can be started by the user that, at a position near to a collecting area 8, pushes a second push-button 6 that is made accessible from outside the structure 1.

The mechanism 50 includes a store compartment 10 extending vertically, that is designed to hold a stack 17 of the goods items 7, resting on a horizontal base 11 fastened to the structure 1.

At a side of the store compartment 10, near to the base 11, there is located a pusher 13 having a proper shape that is moved when the second push-button 6 of the coin acceptor 2 is pushed.

A mobile shutter 14 is constrained to the inner surface of the wall 1a by means of sliding permitting means. The shutter is subjected to the action of elastic means 15 which keep the shutter 14 in a raised position A, so that it is possible to insert a coin or token in the first slot 3.

When the shutter is raised a first coloured sector 140a (for instance a green plate) is visible from outside through a small window 16 that is made in the wall 1a (see Figs. 1,3a,3b,6).

The sector is made integral with the shutter and indicates a "normal condition" working status for the dispensing apparatus 100.

The shutter 14 also features a ledge 14a projecting towards the store compartment 10.

A weight 18 is placed in the store compartment 10 on the top 17b of the stack 17, and features a prominence 18a designed to go in abutment on the ledge 14a, as it will be better explained in the following (see Figures 2,3a,3c,5,6).

In the region beneath the store compartment 10 there is located a chute 30 which leads to the outside passing through a slit 19 made in the wall 1a.

The chute 30 has side panels 31 aimed at guiding the goods items 7.

Working operation of the dispensing apparatus includes, as a first stage, filling the store compartment 10 up with a stack 17 of items 7 and placing the weight 18 on top of it. These actions are performed by assigned personnel (see Fig. 3a).

A user may insert a coin, or other suitable token, in the first slot 3 and then pushes the second push-button 6 which actuates the pusher 13.

The pusher passes through a sized opening 10a, made in the store compartment 10, so as to contact and push a preset number of items 7, which are shifted out of the bottom 17a of the stack 17.

When the items 7 are clear of the base 11, they fall down on the underlying chute 30 and slide thereon up to the collecting area 8 that is located outside the structure 1 (see Fig. 3b).

In this area the items may be taken by the user, as already stated before.

While the pusher 13 is running the forward and backward strokes, the stack 17 rests on the same pusher (see Fig. 3b).

An arm 70, made integral with the pusher 13, lies outside the store compartment 10, parallel to the sliding direction of the same pusher (see Fig. 2).

A transverse striker 130 is fastened to the outer end of the arm 70 and has the task of preventing the dispensing apparatus from being tampered. More precisely the transverse striker prevents the lowermost item 7 of the stack 17 from being illegally withdrawn.

The striker 130 moves in synchrony with the pusher and let the items 7 at the bottom of the stack free when the pusher runs the forward stroke, while preventing the items from being withdrawn through the lower opening of the store compartment when the pusher is at its rest position.

This striker 130 forms, in fact, a barrier that cannot be overcome to reach the items 7 situated in correspondence with the store compartment opening, which as a consequence cannot be illegally withdrawn.

Furthermore, the striker 130 features a flange extending towards the stack 17 of items 7, and aimed at supporting the items 7 when only a few of them remain to form the stack.

When the last group of preset number of items 7 has been delivered, the weight 18 is fully lowered resting on top of the base 11.

As a consequence of this, the prominence 18a, projecting from the weight 18, touches the ledge 14a of the shutter 14 and keeps the shutter in the lowered position B.

When at this position B, the shutter 14 partially covers the first slot 3 of the coin acceptor 2, thus preventing other coins or tokens from being inserted therein (see Figures 3c and 4).

In this situation a second coloured sector 140b, having a colour different then the one of the previously described sector (for instance red), is visible from outside through the window 16 (see Fig.3c). Also the second sector is made integral with the shutter 14, and indicates the "out of order" status for the dispensing apparatus.

Figures 2,3a,3b,3c show the dispensing apparatus 100 described heretofore as it is set for dispensing items 7 having box-like shape, particularly for dispensing an

item each time.

Figures 5 and 6 instead show the dispensing apparatus 100 when it is transformed to a money changer, that is done by a simple modification of the store compartment 10 shape, of the weight 18 and of the pusher 13.

Also the chute may be modified although it would not be necessary for this transformation.

Working operation of this last version of the dispensing apparatus 100 is the same as for the version previously described as well as for a further version (that is not shown in the drawings) in which the dispensing apparatus 100, set in the money-change mode, has a number of store compartments 10 and a pusher 13 properly shaped for simultaneously withdrawing a corresponding number of coins and/or groups of coins.

In the examples shown in the figures, and according to a preferred embodiment, the supporting base 11 does not extend for the whole length of the items projection area, so that the items may be withdrawn with a stroke of the pusher 13 shorter than the length of the items.

This ensures for a better working of the apparatus while the stability is not jeopardized, since the center of gravity of the stack 17 is always situated within the outline of the base 11.

The characterizing features of the improved dispensing apparatus subject of the present invention are well evident from what has been stated above. The dispensing apparatus ensure for a good working operation although it includes only a few constructive elements which are simple but reliable.

The dispensing apparatus does not include electro-mechanical means and therefore it requires low production costs and offers a wide number of possible installations since it does not requires electric power supply.

The subject dispensing apparatus, because of its particular configuration, turns out to be very effective against robbery attempts aimed at gathering items illegally.

In fact, the items cannot be reached by passing through the slit 19.

Claims

1. Improved goods items dispensing apparatus including a structure (1), which supports a mechanical coin acceptor (2) featuring a first slot (3) for insertion of a coin or token, a first push button (5) for giving back coins or tokens, which are not acceptable, by sending them to the outside through a second slot (4) that is situated under the first one, a mechanism (50) designed for withdrawing and delivering a prefixed number of items (7), the said withdrawing and delivering mechanism further including:

at least one store compartment (10) extending

vertically and holding a stack (17) of said goods items (7), the stack resting on a horizontal base (11);

a pusher (13) for displacement of a prefixed number of said good items (7) from the bottom (17b) of said stack (17);

a chute (30) underlying the said store compartment (10) for conveying the said prefixed number of goods items (7) and for transferring them to a collecting area (8) made accessible from outside;

a mobile shutter (14) constrained to the said structure (1) and subjected to the action of elastic means (15) which keep the shutter (14) in a first position (A), in which insertion of a coin or token in the said first slot (3) of the coin acceptor (2) is allowed;

a weight (18) resting on the top (17a) of said stack (17) of items (7), the said weight featuring a prominence (18a) designed to displace the said shutter (14) to a second position (B) and to keep it in such position, so that introduction of a coin or token into the first slot (3) of said coin acceptor (2) is prevented when the stack (17) located inside the store compartment (10) has run out of items (7) or has reached a prefixed height;

said dispensing apparatus being characterised in that there is provided therein a second push button (6) provided for actuating said withdrawing and delivering mechanism (50) and the pusher is activated by said second push button (6) and is movable horizontally so as to pass through a sized opening (10a) made in the said store compartment (10), while the first position of said shutter is a raised position (A) and the second position of said shutter is a lowered position (B).

2. Dispensing apparatus as claimed in claim 1, characterized in that the said pusher (13) is shaped in such a way as to support the stack (17) while the prefixed number of items (7) is being withdrawn from the bottom of the same stack (17).

3. Dispensing apparatus as claimed in claim 1, characterized in that the said shutter (14) has two coloured sectors (140a, 140b) made integral therewith, each of these sectors being visible from outside, through a window (16) made in the structure, when the shutter (14) is in the raised position (A) and when the shutter (14) is in the lowered position (B) respectively.

4. Dispensing apparatus as claimed in claim 1, characterized in that the said pusher (13) has an arm (70) made integral therewith and located outside the said store compartment (10), this arm being ar-

ranged parallel to the sliding direction of the same pusher and supporting a transverse striker (130) shaped in a way such as to allow a free withdrawing of the said prefixed number of items from the bottom (17b) of the stack (17) during the forward stroke of the pusher (13), while preventing any access to the items located at the bottom opening of the store compartment.

5. Dispensing apparatus as claimed in claim 4, characterized in that said transverse striker has a flange extending towards said stack (17), aimed at supporting the said items (7) when only a few of them remain in the said stack.

Patentansprüche

1. Verbesserter Warenausgabeapparat, bestehend aus einem Gehäuse (1) zur Aufnahme einer mechanischen Münzannahmeverrichtung (2) mit einem ersten Schlitz (3) zum Einwurf einer Geld- oder Automatenmünze, einer ersten Drucktaste (5) zur Rückgabe nicht akzeptierter Geld- oder Automatenmünzen mittels Auswurf über einen zweiten Schlitz (4), der sich unterhalb des ersten befindet; einem Mechanismus (50) zur Entnahme und Ausgabe einer vorbestimmten Anzahl von Artikeln (7), wobei der genannte Entnahme- und Ausgabemechanismus ferner umfaßt:

mindestens einen senkrechten Vorratsspeicher (10), in dem ein Stapel (17) der genannten Warenartikel (7) enthalten ist, der auf einer waagrechten Grundfläche (11) aufliegt; einen Schieber (13) zum Wegschieben einer vorbestimmten Anzahl der genannten Artikel (7) vom unteren Ende (17b) des genannten Stapels (17); eine Rutsche (30), die unterhalb des genannten Vorratsspeichers (10) verläuft und die genannte vorbestimmte Anzahl von Artikeln (7) befördert und zu einem von außen zugänglichen Sammelbereich (8) leitet; einen beweglichen Verschuß (14), der an dem genannten Gehäuse (1) befestigt ist und der von einer Federvorrichtung (15) abhängt, die den Verschuß (14) in einer ersten Stellung (A) hält, in der das Einwerfen einer Geld- oder Automatenmünze in den ersten Schlitz (3) der Münzannahmeverrichtung (2) möglich ist; ein Gewicht (18), das auf der Oberseite (17a) des Stapels (17) von Artikeln (7) aufliegt und einen Vorsprung (18a) aufweist, der so geformt ist, daß er den genannten Verschuß (14) in eine zweite Stellung (B) verschiebt und in dieser Stellung hält, so daß der Einwurf einer Geld- oder Automatenmünze in den ersten Schlitz (3)

der genannten Münzannahmeverrichtung (2) verhindert wird, wenn der Stapel (17) im Vorratsspeicher (10) keine Artikel (7) mehr enthält bzw. eine vorbestimmte Höhe erreicht; der genannte Ausgabeapparat ist dadurch gekennzeichnet, daß er eine zweite Drucktaste (6) aufweist, die zur Betätigung der genannten Entnahme- und Ausgabeverrichtung (50) dient und daß der durch die zweite Drucktaste (6) betätigte Schieber in waagrechter Richtung beweglich ist, so daß er durch eine entsprechend bemessene Öffnung (10a) in den genannten Vorratsspeicher (10) eingeführt werden kann; und daß ferner die erste Stellung des Verschlusses eine obere Position (A) und die zweite Stellung des Verschlusses eine untere Position (B) ist.

2. Ausgabeapparat nach Anspruch 1, dadurch gekennzeichnet, daß der genannte Schieber (13) so ausgeführt ist, daß er den Stapel (17) trägt, während die vorbestimmte Anzahl von Artikeln (7) vom unteren Ende des Stapels (17) entnommen wird.
3. Ausgabeapparat nach Anspruch 1, dadurch gekennzeichnet, daß der genannte Verschuß (14) zwei darin integrierte farbige Abschnitte (140a, 140b) aufweist, die beide von außen über ein im Gehäuse ausgespartes Fenster (16) sichtbar sind, und zwar jeweils eine davon, wenn sich der Verschuß (14) in seiner oberen Stellung (A) bzw. in seiner unteren Stellung (B) befindet.
4. Ausgabeapparat nach Anspruch 1, dadurch gekennzeichnet, daß der genannte Schieber (13) einen fest damit verbundenen Arm (70) aufweist, der außerhalb des genannten Vorratsspeichers (10) und parallel zur Gleitrichtung des Schiebers angeordnet ist und einen Queranschlag (130) trägt, der so geformt ist, daß er die ungehinderte Entnahme der vorbestimmten Anzahl von Artikeln vom unteren Ende (17b) des Stapels (17) während der Vorwärtsbewegung des Schiebers (13) ermöglicht und gleichzeitig jeglichen Zugang zu den an der unteren Öffnung des Vorratsspeichers liegenden Artikeln verhindert.
5. Ausgabeapparat nach Anspruch 4, dadurch gekennzeichnet, daß der genannte Queranschlag (130) einen Flansch aufweist, der sich zu dem genannten Stapel (17) hin erstreckt und dazu dient, die genannten Artikel (7) zu stützen, wenn nur noch wenige davon im Stapel vorhanden sind.

Revendications

1. Appareil de distribution d'articles de marchandise

perfectionné comprenant une structure (1), qui supporte un dispositif d'acceptation des pièces de monnaie mécanique (2) présentant une première rainure (3) pour introduire une pièce de monnaie ou un jeton, un premier bouton-poussoir (5) pour rendre les pièces de monnaie ou les jetons qui ne sont pas acceptés, en les envoyant à l'extérieur à travers une deuxième rainure (4) qui est située sous la première, un mécanisme (50) destiné à enlever et à délivrer un nombre préétabli d'articles (7), ledit mécanisme d'enlèvement et de délivrance comprenant en plus :

au moins un compartiment de réserve (10) disposé à la verticale et contenant une pile (17) de ces articles de marchandise (7), la pile reposant sur une base horizontale (11) ;
un poussoir (13) pour le déplacement d'un nombre préétabli de ces articles de marchandise (7) du bas (17b) de ladite pile (17) ;
une glissière (30) située au-dessous de ce compartiment de réserve (10) pour transporter ledit nombre préétabli des articles de marchandise (7) et les transférer vers une zone de ramassage (8) accessible de l'extérieur ;
un volet mobile (14) plaqué à ladite structure (1) et soumis à l'action de moyens élastiques (15) qui maintiennent le volet (14) dans une première position (A), laquelle permet l'introduction d'une pièce de monnaie ou d'un jeton dans ladite première rainure (3) du dispositif d'acceptation des pièces de monnaie (2) ;
un poids (18) reposant sur le dessus (17a) de ladite pile (17) d'articles (7), ledit poids présentant une saillie (18a) destinée à déplacer ledit volet (14) dans une deuxième position (B) et à le maintenir dans cette position, de façon à empêcher l'introduction d'une pièce de monnaie ou d'un jeton dans la première rainure (3) du dispositif d'acceptation des pièces de monnaie (2) en question lorsque la pile (17) située à l'intérieur du compartiment de réserve (10) est à court d'articles (7) ou a atteint une hauteur préétablie ;
ledit appareil de distribution étant caractérisé en ce que il y est prévu un deuxième bouton-poussoir (6) destiné à actionner ledit mécanisme d'enlèvement et de délivrance (50) et le poussoir est actionné par ledit deuxième bouton-poussoir (6) et peut se déplacer horizontalement de façon à passer à travers une ouverture dimensionnée (10a) aménagée dans ledit compartiment de réserve (10), tandis que la première position du volet en question est une position élevée (A) et la deuxième position de ce volet est une position abaissée (B).

ractérisé en ce que ledit poussoir (13) est conformé de façon à supporter la pile (17) pendant que le nombre préétabli d'articles (7) est enlevé du bas de cette même pile (17).

3. Appareil de distribution selon la revendication 1, caractérisé en ce que ledit volet (14) a deux zones colorées (140a, 140b) qui lui sont intégrées, chacune de ces zones étant visibles de l'extérieur, à travers une fenêtre (16) aménagée dans la structure, lorsque respectivement le volet (14) est en position élevée (A) et lorsque le volet (14) est en position abaissée (B).
4. Appareil de distribution selon la revendication 1, caractérisé en ce que ledit poussoir (13) a un bras (70) qui lui est intégré et situé à l'extérieur du compartiment de réserve (10) en question, ce bras étant disposé parallèlement à la direction de glissement de ce même poussoir et supportant une butée transversale (130) conformée de façon à permettre un enlèvement libre du nombre préétabli d'articles en question du bas (17b) de la pile (17) pendant le déplacement en avant du poussoir (13), tout en empêchant le passage aux articles situés sur l'ouverture du fond du compartiment de réserve.
5. Appareil de distribution selon la revendication 4, caractérisé en ce que ladite butée transversale a une bride s'étendant vers ladite pile (17), ayant pour but de supporter lesdits articles (7) lorsque seulement quelques uns d'entre eux restent sur ladite pile.

2. Appareil de distribution selon la revendication 1, ca-

FIG. 1




FIG. 2




FIG. 3a




FIG. 4




FIG. 3b




FIG. 3c




FIG. 6





FIG. 5