



- (51) International Patent Classification:  
G05B 15/00 (2006.01) H04L 12/28 (2006.01)
- (21) International Application Number:  
PCT/US2016/040097
- (22) International Filing Date:  
29 June 2016 (29.06.2016)
- (25) Filing Language:  
English
- (26) Publication Language:  
English
- (30) Priority Data:  
62/186,480 30 June 2015 (30.06.2015) US  
62/186,466 30 June 2015 (30.06.2015) US  
62/186,487 30 June 2015 (30.06.2015) US  
62/186,491 30 June 2015 (30.06.2015) US  
62/186,501 30 June 2015 (30.06.2015) US  
62/186,506 30 June 2015 (30.06.2015) US  
62/186,473 30 June 2015 (30.06.2015) US  
62/186,469 30 June 2015 (30.06.2015) US  
15/196,544 29 June 2016 (29.06.2016) US

(74) Agents: REGAN, Christopher F. et al.; Allen, Dyer, Doppelt, Milbrath & Gilchrist, P.A., 255 S. Orange Avenue, Suite 1401, Orlando, Florida 32801 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LI, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

- (71) Applicant: K4CONNECT INC. [US/US]; 19 West Hargett Street, Suite 300, Raleigh, North Carolina 27601 (US).
- (72) Inventor: GOULD, Jonathan Andrew; 516 Sherrybrook Drive, Raleigh, North Carolina 27610 (US).


Published:

— with international search report (Art. 21(3))

(54) Title: HOME AUTOMATION (HA) SYSTEM INCLUDING DESIRED SCENE IMPLEMENTATION BASED UPON USER-SELECTABLE LIST OF ADDRESSABLE HA DEVICES AND RELATED METHODS



(57) Abstract: A home automation system may include addressable devices and device scene controller. The controller may obtain a first desired scene including a first trigger action and responsive event and present a first user-selectable list of addressable devices capable of implementing the first desired scene. The controller may determine the first user-selected addressable devices, and, upon the first trigger event, perform the first responsive event using the first user-selected addressable devices. The controller may obtain from the cloud a second desired scene including a second trigger action and responsive event, present a second user-selectable list of corresponding addressable devices capable of implementing the second desired scene, determine the second user-selected addressable devices, and upon the second trigger event, perform the second responsive event using the second user-selected addressable devices. When the addressable devices are incapable of implementing the scene, the controller may present a purchase offer for an additional addressable device.



**HOME AUTOMATION (HA) SYSTEM INCLUDING DESIRED SCENE  
IMPLEMENTATION BASED UPON USER-SELECTABLE LIST OF  
ADDRESSABLE HA DEVICES AND RELATED METHODS**

**Technical Field**

**[0001]** The present embodiments are directed to the field of electronics, and more particularly to home automation systems and related methods.

**Background**

**[0002]** There are a number of home automation systems and approaches that seek to permit automated control of electrical devices in a house. The popularity of home automation has been increasing due to the greater availability of smartphones and tablets. As noted in “The Problem With Home Automation’s Internet Of Things (IoT)”, and article appearing in Forbes dated 9/26/2013, home automation was typically for wealthy consumers with an expensive system to control lights, home theater, security, air conditioning, and home audio. This market has expanded with many do it yourself (DIY) products now available, and, although the products are useful, they may be difficult to aggregate. In other words, as explained in the article, difficulties could arise if a consumer bought a Nest thermostat, Kwikset door lock, Phillips Hue lighting device, Lutron light switch, Sonos audio system, and Belkin wireless plugs. The consumer would need to have multiple applications each requiring time to setup, learn, and use. Additionally, the article states that there is no easy way to make devices work together, such as if the consumer wanted to trigger one event using one device based on another event from another device.

**[0003]** Multiple communication protocols may also be problematic. In particular, different devices may operate using different communication protocols, for example, Wifi, Zigbee, Zwave, Insteon, Itron, RadioRA2, and others. This may create additional difficulties for home automation.

**[0004]** One approach to address these shortcomings is for the consumer, which may include a user and/or enterprise, to use a service and device aggregator that provides one application and a consolidated wireless adapter unit. The user would contract with such a provider for multiple years. Unfortunately, as noted in the

article, the consumer may not benefit from the most advanced hardware and software.

**[0005]** Another approach, as noted in the Forbes article, is to provide a single application that attempts to consolidate disparate applications and consolidate wireless adaptors, for example, using each of the different communications protocols. Still further improvements to the operation and integration of devices may be desirable.

### **Summary**

**[0006]** A home automation (HA) system may include a plurality of addressable HA devices at a given location, and an HA device scene controller. The HA device scene controller may be configured to obtain from a user a first desired scene comprising at least one first trigger action and at least one first responsive event, and present a first user-selectable list of corresponding ones of the addressable HA devices capable of implementing the first desired scene. The HA scene controller may also be configured to determine the first user-selected ones of the addressable HA devices and upon occurrence of the at least one first trigger event, perform the at least one first responsive event using the first user-selected ones of the addressable HA devices to thereby implement the first desired scene. The HA device scene controller may also be configured to obtain from the cloud a second desired scene including at least one second trigger action and at least one second responsive event, present a second user-selectable list of corresponding ones of the addressable HA devices capable of implementing the second desired scene, determine the second user-selected ones of the addressable HA devices, and upon occurrence of the at least one second trigger event, perform the at least one second responsive event using the second user-selected ones of the addressable HA devices to thereby implement the second desired scene. Accordingly, scenes may be set up without initial knowledge of the addressable devices for implementing the scene, and the scenes may be shared for implementation using different addressable HA devices, for example.

**[0007]** The HA device scene controller may be configured to obtain the at least one first and second trigger actions without obtaining corresponding ones of the addressable HA devices for implementing the at least one first and second trigger

actions, for example. The HA device scene controller may be configured to obtain the at least one first and second responsive events without obtaining corresponding ones of the addressable HA devices for implementing the at least one first and second responsive events.

**[0008]** The HA system may also include a user-interface device coupled to the HA device scene controller. The user-interface device may include a display, a user-input device, and a user-interface controller coupled to the display and user-input device. The user-interface controller may be configured to display on the display the first and second user selectable lists, and permit, via the user-input device, user-selection of the first and second user-selected ones of the addressable devices.

**[0009]** The HA device scene controller may be configured to generate a notification for the user upon occurrence of the at least one first or second trigger actions, for example. The device scene controller may be configured to wirelessly obtain the at least one first and second trigger actions and the at least one first and second responsive events, for example.

**[0010]** The HA device scene controller may be configured to wirelessly implement the first and second desired scenes. Each of the plurality of addressable HA devices may include one of a motion detector, thermostat, light switch, audio controller, door lock, and camera, for example.

**[0011]** Another aspect is directed to an HA system that may include a plurality of addressable HA devices at a given location and an HA device scene controller. The HA device scene controller is configured to obtain from a user a first desired scene comprising at least one first trigger action and at least one first responsive event and determine when the plurality of addressable HA devices at the given location are not capable of implementing the scene, and present a purchase offer for an additional addressable HA device. The HA device controller is also configured to determine when the plurality of addressable HA devices at the given location are capable of implementing the scene, and present a first user-selectable list of corresponding ones of the addressable HA devices capable of implementing the first desired scene. The HA device controller is further configured to determine the first user-selected ones of the addressable HA devices and upon occurrence of the at least one first trigger event, perform the at least one first responsive event using the

first user-selected ones of the addressable HA devices to thereby implement the first desired scene.

**[0012]** A method aspect is directed to a method of implementing first and second desired scenes in an HA system that includes a plurality of addressable HA devices at a given location. The method may include using an HA device scene controller to obtain from a user the first desired scene including at least one first trigger action and at least one first responsive event and present a first user-selectable list of corresponding ones of the addressable HA devices capable of implementing the first desired scene. The HA scene controller is also used to determine the first user-selected ones of the addressable HA devices and upon occurrence of the at least one first trigger event, perform the at least one first responsive event using the first user-selected ones of the addressable HA devices to thereby implement the first desired scene. The HA scene controller is further used to obtain from the cloud the second desired scene including at least one second trigger action and at least one second responsive event, present a second user-selectable list of corresponding ones of the addressable HA devices capable of implementing the second desired scene, determine the second user-selected ones of the addressable HA devices, and upon occurrence of the at least one second trigger event, perform the at least one second responsive event using the second user-selected ones of the addressable HA devices to thereby implement the second desired scene.

**[0013]** Another method aspect is directed to a method of implementing a first desired scene in an HA system that includes a plurality of addressable HA devices at a given location. The method may include using an HA device scene controller to obtain from a user a first desired scene including at least one first trigger action and at least one first responsive event and determine when the plurality of addressable HA devices at the given location are not capable of implementing the scene, and present a purchase offer for an additional addressable HA device. The HA scene controller may also be used to determine when the plurality of addressable HA devices at the given location are capable of implementing the scene, and present a first user-selectable list of corresponding ones of the addressable HA devices capable of implementing the first desired scene. The HA scene controller may also

be used to determine the first user-selected ones of the addressable HA devices, and upon occurrence of the at least one first trigger event, perform the at least one first responsive event using the first user-selected ones of the addressable HA devices to thereby implement the first desired scene.

### **Brief Description of the Drawings**

**[0014]** FIG. 1a is a schematic diagram of an electronic device integration system in accordance with an embodiment of the present invention.

**[0015]** FIG. 1b is a schematic diagram of an HA system in accordance with an embodiment.

**[0016]** FIG. 2a is a schematic block diagram of a message queue for use in the system of FIG. 1a.

**[0017]** FIG. 2b is a schematic block diagram of an HA system including message queues in accordance with an embodiment.

**[0018]** FIG. 3 is a schematic diagram of an action server for use in the system of FIG. 1a.

**[0019]** FIG. 4 is a schematic diagram of operation of an analytics server for use in the system of FIG. 1a.

**[0020]** FIG. 5 is a schematic diagram of a camera server for use in the system of FIG. 1a.

**[0021]** FIG. 6 is a schematic diagram of a configuration server for use in the system of FIG. 1a.

**[0022]** FIG. 7 is a schematic diagram of a debug server for use in the system of FIG. 1a.

**[0023]** FIG. 8a is a schematic diagram of a discovery server for use in the system of FIG. 1a.

**[0024]** FIG. 8b is another schematic diagram of the discovery server of FIG. 8a.

**[0025]** FIG. 9 is a schematic diagram of a notification server for use in the system of FIG. 1a.

**[0026]** FIG. 10 is a schematic diagram of a loader server for use in the system of FIG. 1a.

- [0027]** FIG. 11 is a schematic diagram of a status server for use in the system of FIG. 1a.
- [0028]** FIG. 12 is a schematic diagram of a web server for use in the system of FIG. 1a.
- [0029]** FIG. 13a is a schematic diagram of a security server in the system of FIG. 1a.
- [0030]** FIG. 13b is another schematic diagram of a security server in accordance with an embodiment.
- [0031]** FIG. 14a is a diagram of a user interface displaying contextual help on a remote device of the system of FIG. 1a.
- [0032]** FIG. 14b is a diagram of a user interface displaying contextual help on a remote device of the system of FIG. 1a.
- [0033]** FIG. 15a is a diagram of a user interface showing addressable devices arranged by room on a remote device of the system of FIG. 1a.
- [0034]** FIG. 15b is a diagram of a user interface showing addressable devices arranged by device type on a remote device of the system of FIG. 1a.
- [0035]** FIG. 15c is a diagram of a user interface showing addressable devices arranged by scene type on a remote device of the system of FIG. 1a.
- [0036]** FIG. 16 is a diagram of a user interface showing a color picker for use with an LED light addressable device of the system of FIG. 1a.
- [0037]** FIG. 17 is a schematic block diagram of a remote device and an LED light bulb addressable device in accordance with an embodiment of the present invention.
- [0038]** FIG. 18 is a schematic diagram of an interface between multiple hub devices in accordance with an embodiment of the present invention.
- [0039]** FIG. 19 is a schematic diagram of bridges in the system of FIG. 1a.
- [0040]** FIG. 20 is a schematic diagram of operation of system of FIG. 1a when a new bridge is added.
- [0041]** FIG. 21a is a diagram illustrating sandboxed processes in the system of FIG. 1a.
- [0042]** FIG. 21b is another schematic diagram illustrating sandboxed processes in the system of FIG. 1a.

- [0043]** FIG. 22 is a diagram illustrating a responsive scene definition in the system of FIG. 1a.
- [0044]** FIG. 23 is a flow diagram illustrating ingredient responsive scenes in the system of FIG. 1a.
- [0045]** FIG. 24 is a diagram of a user interface showing recommended purchases based upon ingredients to complete a scene in the system of FIG. 1a.
- [0046]** FIG. 25 is a diagram of a user interface showing the ability of a user to choose from a list of ingredient blocks for a scene in the system of FIG. 1a.
- [0047]** FIG. 26 is a diagram of a user interface showing suggested device operation blocks based upon user input for a scene in the system of FIG. 1a.
- [0048]** FIG. 27 a diagram of a user interface showing a prompt for user input to choose what device provides an ingredient for a scene in the system of FIG. 1a.
- [0049]** FIG. 28 is a diagram of a user interface showing different scenes for a given set of ingredients or devices in the system of FIG. 1a.
- [0050]** FIG. 29a is a diagram of a user interface showing a prompt for user input to choose devices to map a scene to devices specific to a home in the system of FIG. 1a.
- [0051]** FIG. 29b is a schematic block diagram of operation of an HA device scene controller in the HA system of FIG. 1a.
- [0052]** FIG. 30a is a block diagram of an electronic device integration system in accordance with another embodiment of the present invention.
- [0053]** FIG. 30b is a schematic diagram of an HA system for generating a user health score in accordance with an embodiment.
- [0054]** FIG. 31 is a diagram of a hub device for detecting proximity to a remote device in accordance with an embodiment of the present invention.
- [0055]** FIG. 32 is a schematic diagram of multiple electronic device integration systems in accordance with an embodiment of the present invention.
- [0056]** FIG. 33 is a schematic diagram of an electronic device integration system including a short-range communication protocol ID device in accordance with an embodiment of the present invention.

**[0057]** FIG. 34 is a diagram of a user interface illustrating event generation on a remote device for multiple electronic device integration systems in accordance with an embodiment of the present invention.

**[0058]** FIG. 35 is a schematic diagram of a climate control system in accordance with an embodiment.

**[0059]** FIG. 36 is a graph illustrating operation of the climate control system of FIG. 35.

**[0060]** FIGS. 37a-37e are schematic block diagrams of an HA system illustrating communications between an addressable HA device and a remote access wireless communications device in accordance with an embodiment.

### **Detailed Description**

**[0061]** The present invention will now be described more fully hereinafter with reference to the accompanying drawings, in which preferred embodiments of the invention are shown. This invention may, however, be embodied in many different forms and should not be construed as limited to the embodiments set forth herein. Rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the invention to those skilled in the art. Like numbers refer to like elements throughout, and prime notation is used to indicate similar elements in alternative embodiments.

**[0062]** Referring initially to FIG. 1a, an electronic device integration system is illustratively in the form of a home automation (HA) system **20**, and which is referred to as the K4Connect system. The HA system **20** illustratively includes a plurality of addressable devices **31a-31n**, a home device **32**, a remote device **36**, and cloud device **33**. While an HA system **20** is described herein, it should be understood that the system is not limited to use in a home and may be used in any setting, commercial, industrial, residential, etc.

**[0063]** Addressable devices **31a-31n** may include controllable devices and/or sensors, for example, a motion detector, thermostat, light switch, audio controller, door lock, and/or camera. Of course, the addressable devices may include additional or other devices.

**[0064]** While a cloud device **33** or hardware server is described, it should be understood by those skilled in the art that the processes and functions performed by

the could device may be performed by a processor **46** or by multiple processors in different geographic locations and over different networks in what is understood by those skilled in the art as the cloud. The home device **32** may be a personal computer, tablet computer, standalone computing device, or any other computing device. The HA system **20** may also include a hub device **34** (i.e., a K4Hub). In some embodiments, the hub device **34** and the home device **32** may be within a home **47** and wirelessly connected to a home network, which may provide communication with the Internet. The functions and interconnections of these devices within the system will be described in further detail below.

**[0065]** The K4Home software program runs the K4Connect HA system **20** of home, office, business, and building automation for addressable devices **31a-31n** that can be connected into the program. The K4Home software is available as a software only package that can be loaded onto a personal computer or other small computer devices, for example, the home device **32**. The functions of the K4Home software are executed by respective processors or processing circuitry on one or more devices running the K4Home software, for example, a processor **38** of the home device **32** as will be described below.

**[0066]** The K4Hub **34** is a device that may also run the K4Home software and hosts the system architecture on the device. The K4Hub **34** includes a housing **41** and hub processing circuitry **42** carried by the housing. The K4Hub **34** also includes a plurality of radio ports **43a-43n**, for example, universal serial bus (USB) ports carried by the housing **41** and for coupling to any of a plurality of radio controllers **44a-44n**. The K4Hub **34** runs the system locally and can communicate with the addressable devices **31a-31n** directly instead of routing through a cloud based process. In other words, the hub processing circuitry **42** cooperates with radio controllers **44a-44n** that are plugged in to communicate with addressable devices **31a-31n** based upon the respective protocols.

**[0067]** The radio controllers **44a-44n** may each be for a given radio protocol. For example, a Z-wave radio controller may be plugged into one of the radio ports **43a-43n**, which allows the K4Hub **34** to communicate with Z-wave based addressable devices. A second or third radio controller may be plugged into the

radio ports **43a-43n** of the K4Hub for adding the ability to communicate with controllable devices using second and third radio protocols.

**[0068]** The K4Hub **34** is an improvement on current technology since it reduces the latency and system failures common on current home automation devices that require a network connection. Similarly to the K4Hub **34**, the K4Home software running on a personal computer, for example, the home device **32**, can be augmented with additional home automation communication protocols such as ZigBee and Z-Wave by attaching ports through the K4Hub or computer's USB port.

**[0069]** The K4App is the location of the user interface **35** of the K4Connect HA system **20** and allows the user to access the K4Home software and control the K4Connect system **20** through or from the remote device **36**, for example, a smartphone or tablet device that includes a display **48** and a processor **49** coupled to the display. The user interface **35** may be also accessed by a desktop application for a personal computer and/or by an on-screen application for a television. There may be more than one remote device **36** and each remote device may be a different type of device.

**[0070]** In some embodiments, the remote device **36** may connect "locally" without communicating through or with the cloud device **33**. This may be particularly advantageous because communication may not rely on network connectivity and function locally independent of the Internet. Additionally, communication may be relatively faster and more reliable.

**[0071]** The remote server or cloud device **33**, which runs software referred to as K4Away, is a cloud-based subscription system that provides the connection between the local K4Home software, for example, running on the home device **32** or K4Hub **34**, and the K4App when outside of the local home network, for example running on the remote device **36**. K4Away also provides the connection between the K4Home software and K4Connect system analytics and help system. The K4App may, in some embodiments, connect directly to K4Home, i.e., the home device **32** or K4Hub **34**, without communicating through the cloud device **33** or indirectly without communication through the cloud device.

**[0072]** Referring now to FIG. 1b, the above-described components of the HA system **20** will be described. The HA system **20** includes addressable HA devices

**31a-31n**, each configured to wirelessly communicate using a respective HA wireless communications protocol from among different HA wireless communications protocols. The addressable HA devices **31a-31n** may include any of motion detectors, thermostats, light switches, audio controllers, door locks, and/or cameras. Of course, the addressable HA devices **31a-31n** may include other and/or additional devices.

**[0073]** The HA system **20** also includes HA wireless radio controllers **44a-44n**, each configured to wirelessly communicate using a respective different HA wireless communications protocol also from among the different HA wireless communications protocols. Each HA wireless radio controller **44a-44n** includes circuitry **441a-441n** and a connector **442a-442n** coupled thereto. The HA wireless radio controllers **44a-44n** may be Zigbee controllers, Z-Wave controllers, and/or other types of controllers, for example.

**[0074]** The HA system **20** also includes an HA hub device **34** that includes a housing **41** and wireless radio port connectors **43a-43n** carried by the housing. Each port connector **43a-43n** is configured to couple to a respective connector **442a-442n** of a corresponding HA wireless radio controller **44a-44n**. The port connectors **43a-43n** may be USB connectors, for example, and/or other or additional types of connectors. The HA hub device **34** also includes hub processing circuitry **42** coupled to the wireless radio port connectors **43a-43n**. The hub processing circuitry **42** communicates with the addressable HA devices **31a-31n** based upon the respective HA wireless communications protocols. In some embodiments, the HA wireless radio controllers **44a-44n** may communicate directly with the addressable devices via the HA hub device **34**, for example, instead of routing through a cloud based process, as will be appreciated by those skilled in the art.

**[0075]** A method aspect is directed to a method of communicating in the HA system **20**. The method includes using HA wireless radio controllers **44a-44n** to wirelessly communicate using a respective different HA wireless communications protocol from among the different HA wireless communications protocols. The method also includes using the HA hub device **34** to communicate with the addressable HA devices **31a-31n** based upon the respective HA wireless communications protocols.

**[0076]** Referring now additionally to FIG. 2a, the primary functions of the HA system **20** (i.e., K4Connect) are based around an independent standalone message queue server **50** that is a combination of an independent local message queue **51** located on a device running the K4Home software and a cloud message queue **52** hosted on the cloud device **33** (i.e. K4Away), which provides connectivity to registered devices outside the local home network. Communication between the message queues **51**, **52** and connected addressable devices **31a-31n**, connected servers, and connected bridges use web sockets as the transport medium, for example.

**[0077]** Both the local and cloud message queues **51**, **52** function independently but remain continuously connected so that no matter the user location, communication to and from the connected device, e.g., servers, and bridges is still available. The continuous connection is initiated from the local message queue **51** to reduce security issues that may be inherent when piercing a firewall of a local network. Having the connection originate from inside the firewalled system, for example, allows for the message queues **51**, **52** to more easily connect while maintaining the security integrity of the home system. In other words, each remote device **36** connects to the cloud message queue **52** and not directly to the local message queue **51** or any of the K4Home **32** or K4Hub **34**. Additionally, communication between the local message queue **51** and the cloud message queue **52**, the connected addressable devices **31a-31n**, servers, and bridges may be SSL encrypted including on the local network for increased security. When the K4App, for example, via the remote device **36**, is connected to the cloud or remote server **33**, the continuous connection allows for the user's connection to the cloud server to serve as a direct connection to the local message queue **51**.

**[0078]** The local message queue **51** receives and distributes messages to and from the cloud message queue **52** and to and from the local servers **81** and device bridges **82**. This distribution technique for the messages allows for independence for each component of the program and leaves the logic or prescribed action to the individual servers or bridges. This independence of the components of the program may also reduce the probability of system crashing errors. This also allows for

continuous rolling out of new bridges and compatibility of new devices without updating the complete software package, for example.

**[0079]** As will be appreciated by those skilled in the art, a typical prior art automation integration system exchanges messages either all within the home network or all on the Internet by penetrating through a firewall. The embodiments described herein advantageously provide a hybrid messaging approach that includes the increased speed of “in-home” message processing (processing via the Internet adds delay) and has the increased security of the Internet (does not penetrate a firewall to expose the home network).

**[0080]** Referring now to FIG. 2b, another aspect of the HA system **20** with respect to the local and cloud message queues **51**, **52** will now be described. The HA system **20** includes addressable HA devices **31a-31n** each having associated therewith a respective device capability, device configuration, and device state.

**[0081]** Each device configuration may include at least one of a device address, a device location, and a device identifier, for example. Exemplary device configurations may include an IP address of the device, the location of the device within a house, and channel location (e.g., left, right) in an audio configuration. Of course, the device configuration may include other and/or additional elements.

**[0082]** Each device capability may include at least one of a sensing function, and an output function. For example, with respect to a light switch, the device capability may include the capability to be “on”, “off”, and be at different “dimmer levels.”

**[0083]** Each device state may include a current state from among a plurality of possible states. For example, with respect to a light switch, the current state may be “on”, “off”, and “dimmed to a given level.”

**[0084]** The HA system **20** includes a cloud message queue controller **521** and a cloud message queue memory **522** coupled thereto in the cloud for storing the device configurations, device capabilities, and device states for the plurality of addressable HA devices **31a-31n**. The cloud message queue controller **521** and the cloud message queue memory **522** may be part of the cloud message queue **52**, for example.

**[0085]** The HA system **20** also includes a home device message queue controller **511** and a home device message queue memory **512** coupled thereto for storing the device configurations, device capabilities, and device states for the plurality of addressable HA devices **31a-31n**. The home device message queue controller **511** and the home device message queue memory **512** may be part of the local message queue **51**, for example.

**[0086]** The cloud message queue controller **521** and the home device message queue controller **511** synchronize device configurations, device capabilities, and device states for the addressable HA devices **31a-31n**. The cloud message queue controller **521** exchanges messages with the local message queue controller **511** relating to the addressable HA devices, for example, for communication with the addressable devices **31a-31n** and for synchronization. For example, such messages may include messages related to the operation and control of the addressable HA devices **31a-31n**.

**[0087]** A local client device **36a** or remote device (e.g., running K4App) includes a local client device controller **361a** and local client device memory **362a** coupled thereto for storing the device configurations, device capabilities, and device states for the addressable HA devices **31a-31n** upon synchronization with the local message queue controller **511**. The local client device controller **361a** exchanges messages with the local message queue controller **511** relating to the addressable HA devices **31a-31n**, for example, sensing, response, and control operations.

**[0088]** A cloud client device **36b** or remote device (e.g., running K4App) includes a cloud client device controller **361b** and cloud client device memory **362b** coupled thereto for storing the device configurations, device capabilities, and device states for the addressable HA devices **31a-31n** upon synchronization with the cloud message queue controller **521**. The cloud client device controller **361b** exchanges messages with the cloud message queue controller **521** relating to the addressable HA devices **31a-31n**, for example, sensing, response, and control operations.

**[0089]** As will be appreciated by those skilled in the art, by synchronizing the device configurations, device capabilities, and device states for the addressable HA devices **31a-31n**, or messages, communication with a cloud or local client device **36a, 36b** may be quicker as processing of the messages, responses, status queries,

instructions, etc., for example, can be processed at the cloud or local client device or at the nearest of the cloud or message queue (i.e., the request or communication generally may not have to travel to one or the other of the local or cloud message queues **51, 52**).

**[0090]** A method aspect is directed to a method of communicating with a plurality of addressable HA devices **31a-31n** each having associated therewith a respective device capability, device configuration, and device state. The method includes using a cloud message queue controller **521** and a cloud message queue memory **522** coupled thereto in the cloud for storing the device configurations, device capabilities, and device states for the plurality of addressable HA device. The method also includes using a home device message queue controller **511** and a home device message queue memory **512** coupled thereto for storing the device configurations, device capabilities, and device states for the plurality of addressable HA devices. The cloud message queue controller **521** and the home device message queue controller **511** synchronize device configurations, device capabilities, and device states for the plurality of addressable HA devices **31a-31n**.

**[0091]** Referring now additionally to FIGS. 4-13, the K4Home program, for example executed using the home device **32** or K4Hub **34**, provides for independent servers or functional modules for each of the functions of the HA system **20**. The servers **81** are separated from the bridges **82** running on the HA system **20** for security and may allow independent running of the system as a whole. The servers **81** on the home automation integration system **20** include an action server **69**, analytics server **54**, camera server **61**, configuration server **62**, debug server **63**, discovery server **55**, loader server **64**, message server **65**, notification server **66**, status server **67**, update server **59**, web server **68**, and security server **56**. More servers can be added to the software if new functions are needed. While the term server has been used herein, it should be understood that a server may be one or more standalone software processes that are executed on one or more processors on any device, for example, as described above. The functionality of each server **81** is performed by a processor, controller, and/or related circuitry, particularly on the device which it is executed, for example, the home device processor **38** or the hub device processing circuitry **42**, as will be appreciated by those skilled in the art.

**[0092]** The action server is continuously running on the HA system **20**, and more particularly, the home device **32**, and executes the responsive scenes of the K4Home system or components within the home (FIG. 3). The analytics server **54** logs user and system actions to the cloud storage system or server **33** and receives suggestions of possible responsive scenes the user could implement or actions the user could take to improve their K4Home HA system **20** (FIG. 4).

**[0093]** In the initial K4Home system setup, the analytics server **54** requests advertisements from the servers **81** and bridges **82** on the system. The servers **81** and bridges **82** on the K4Home system **20** return advertisements, which allows for the analytics server **54** to subscribe to the individual servers and bridges. Once subscribed, the servers and bridges **82** send individual events, commands, and variable changes to the analytics server **54**, which keeps a log of the data sent.

**[0094]** At intervals, which may be periodic or regular, the analytics server **54** reports the data collected to the cloud system or cloud device **33** via a private globally unique identifier (GUID). The cloud-based analytics or device **33** processes and reviews the anonymized data, storing the data in a cloud database. This data is then used to review the functions of the K4Home HA system **20** which may reveal any problems that may exist in the software. This HA system **20** can also use the data gathered from the security server to assess any security threats and develop mitigation plans. The cloud-based analysis or cloud device **33** also reviews the K4Home system and recommends devices and responsive scenes to the private GUIDs. Once the information in the cloud has been analyzed and gathered by the cloud device **33** it is pushed back to the local analytics server **54** with the next time to “check-in” to the cloud.

**[0095]** The camera server **61** (FIG. 5) locates camera images/video and streams the images/video to the system. The camera server also acts as an image proxy for remote users not able to directly connect to the camera, for example.

**[0096]** The configuration server **62** (FIG. 6) stores the persistent configuration of the home automation integration system **20**. The configuration server **62** also uses the device descriptions during the device connection process to setup addressable devices **31a-31n** on the HA system **20** in tandem with a device setup wizard. The debug server **63** enables bridge debugging (FIG. 7).

**[0097]** The discovery server **55** (FIG. 8a) finds addressable devices to connect to the K4Connect system **20**. The discovery server **55** uses signatures of devices, for example, addressable devices **31a-31n** in its search to discover devices that are not natively discoverable for connection to the system. With respect to typical prior art home automation integration systems, certain addressable devices do not automatically broadcast their availability and thus have to be manually connected by the user. Manual entry often involves advanced technical knowledge or having to follow detailed complicated instructions to add the device to their home automation systems, for example, manually entering an IP address, device ID, and/or other identifying information. The discovery server **55** reduces these complications.

**[0098]** Example code executed on the discovery server **55** with respect to a network device and a USB device, respectively, are below:

```
<signature cls="com.k4connect.someNetworkDevice" description="Example  
Network Device">
```

```
  <mdns>
```

```
    <services>
```

```
      <service>
```

```
        <name>DeviceName.*</name>
```

```
        <type>http</type>
```

```
        <protocol>tcp</protocol>
```

```
      </service>
```

```
    </services>
```

```
  </mdns>
```

```
  <upnp>
```

```
    <deviceType>urn:Manufacturer:device:sensor:1</deviceType>
```

```
  </upnp>
```

```
  <macs>
```

```

        <mac>ff:ff:ff</mac>

    </macs>

</signature>

<signature cls="com.k4connect.someUsbDevice" description="Example USB Device">

    <udev>
        <devices>
            <device>
                <attributes>
                    <attribute name="ID_VENDOR_ID"
pattern="10c4"/>
                    <attribute name="ID_MODEL_ID"
pattern="ea60"/>
                    <attribute name="DEVNAME"
pattern="^\dev\ttyUSB\d+"/>
                </attributes>
            </device>
        </devices>
    </udev>
</signature>

```

**[0099]** The discovery server **55** is typically always running processes that monitor the system home automation integration **20** either passively waiting for a signal from a new controllable device or scanning the system for signatures of the addressable devices **31a-31n**. The discovery server **55** runs UPNP and MDNS processes that use a text match process from the signatures of the addressable devices **31a-31n** to identify the controllable device. The discovery server **55** also runs multicast processes and connects to these unconnected addressable devices **83**, for example, by a challenge response.

**[0100]** The advantageous elements of the discovery server **55** are the ARP scan and the udev scan. The ARP scan runs a port match for loaded controllable

device signatures and runs a challenge-response process to identify the addressable devices **31a-31n**. For example, discovery server **55** may query a port with data and get an identifying response based upon the query. The ARP scan also identifies the device by MAC address matching. The other advantageous element is the UDEV scan which uses a USB match for devices connected to the hardware running K4Home and running a TTY Match, which identifies the device with a challenge response process. As will be appreciated by those skilled in the art, any number of elements or network characteristics that define a controllable device signature may be used.

**[0101]** Once the discovery server **55** has discovered a new addressable device (i.e., new to the system **20**), it sends notifications over the message queue **51** to the configuration server **62** and notification server **66** (FIG. 7), which then notify the user of the newly discovered addressable device and begins a wizard set-up process. When a new addressable device becomes available (e.g., new to market and not just the system) for which there is not an identifiable signature, a new signature filter may be added to the discovery server **55**.

**[0102]** In some embodiments, advertising from the addressable devices **31a-31n** may be used to limit an addressable device. For example, a controllable speaker device may appear to the home automation integration system **20** as a generic device based upon advertising. However, a query based upon a subset of addresses or signature elements may be used, which may increase the speed of controllable device discovery. For example, signature elements may be used to limit or restrict a device type, and discovery may continue based upon the subset.

**[0103]** Referring now additionally to FIG. 8b, the discovery server **55** will be described with respect to the HA system **20**. The addressable HA devices **31a-31n** each have a respective HA device signature associated therewith and each is configured to wirelessly communicate using respective different wireless communications protocols from among different wireless communications protocols. The addressable HA devices **31a-31n** may include any of motion detectors, thermostats, light switches, audio controllers, door locks, and/or cameras. Of course, the addressable HA devices **31a-31n** may include other and/or additional devices.

**[0104]** The discovery server **55** may be in the form of a controller **551** and a memory **552** coupled thereto. The memory **552** stores HA device signatures for paired and unpaired ones of the addressable HA devices **31a-31n**. The HA device signatures may include, for example, MAC addresses, port data, and/or universal serial bus (USB) identifiers.

**[0105]** The controller **551** polls the addressable HA devices **31a-31n** and determines an unpaired addressable HA device from among the plurality thereof based upon the polling. The controller **551** may poll the addressable HA devices **31a-31n** by polling for a broadcast from the addressable HA devices and/or by scanning for addressable devices responsive to a given one of stored HA device signatures stored in the memory **552**.

**[0106]** The controller **551** also compares the associated HA device signature of the unpaired addressable HA device with the stored HA device signatures. The controller **551** may compare the associated HA device signature of the unpaired addressable HA device with the stored HA device signatures based upon at least one of a universal plug and play (UPnP) process and a multicast domain name system (mDNS) process. Any of the UPnP and mDNS processes may be executed based upon a text match process, for example.

**[0107]** In some embodiments, the addressable HA devices **31a-31n** may each have port data associated therewith, in which case the controller **551** may poll the addressable HA devices based upon an address resolution protocol (ARP) scan, and compare the associated HA device signature of the unpaired addressable HA device with the stored HA device signatures based upon port data from the ARP scan.

**[0108]** Alternatively or additionally, the controller **551** may poll the addressable HA devices **31a-31n** based upon a udev scan, in which case the controller compares the associated HA device signature of the unpaired addressable HA device with the stored HA device signatures based upon the udev scan.

**[0109]** The controller **551**, when there is a match between the HA device signature of the unpaired addressable HA device and one of the stored HA device signatures, permits pairing of the unpaired addressable HA device to communicate with the unpaired addressable HA device using the respective wireless communications protocol. The controller **551** may prompt a user to approve pairing

of the unpaired addressable HA device. The pairing of the unpaired addressable HA device may be based upon a challenge response from an electronic device associated with a user, for example, the remote device **36**.

**[0110]** A communications interface **553** provides communication between the controller **551** and the cloud, for example, the cloud device **33**. The controller **551** communicates with the cloud device **33** via the communications interface **553** to update the stored HA device signatures in the memory **552**.

**[0111]** The HA system **20** also includes radio controllers **44a-44n** coupled to the controller **551**. Each of the addressable devices **31a-31n** is configured to wirelessly communicate with the controller **551** via respective radio controllers **44a-44n**.

**[0112]** A method aspect is directed to a method of permitting pairing of unpaired addressable HA devices **31a-31n** in the HA system **20**. The method includes using the **551** controller and the memory **552** coupled thereto storing a plurality of HA device signatures for paired and unpaired ones of plurality of addressable HA devices to poll the plurality of addressable HA devices and determine an unpaired addressable HA device from among the plurality thereof based upon the polling. The controller **551** and the memory **552** are also used to compare the associated HA device signature of the unpaired addressable HA device **31a-31n** with the stored HA device signatures, and when there is a match between the HA device signature of the unpaired addressable HA device and one of the stored HA device signatures, permit pairing of the unpaired addressable HA device to communicate with the unpaired addressable HA device using the respective wireless communications protocol.

**[0113]** The loader server **64** loads bridges **82** and servers **81** (FIG. 10). The message server **65** runs or operates the message queue **51**. The notification server **66** sends notifications from the system **20** to the user interface **35**, for example, at the remote device **36** (FIG. 9).

**[0114]** The status server **67** serves as a system wide state machine storing a log of last known state without having to poll devices in the system (FIG. 11). This is accomplished by having the status server **67** perform as a standalone state machine tracking the last known states of the system. As will be appreciated by those skilled

in the art, the status server **67** is advantageously an improvement relative to the current common practice where the system stores the state information in the driver stack, for example. The web server **68** runs the user interface content (FIG. 12). In some embodiments, the user interface content may be stored locally.

**[0115]** The security server **56** executes security processes of the home automation integration system **20** (FIG. 13a). The security server **56** listens on open communication ports **84** not being used by the home automation integration system **20**. This allows the security server **56** to log when a device, for example, an addressable device **31a-31n** or remote device **36**, scans or connects to the port. The security server **56** may then ignore any device that is known to scan or connect and is not a threat to the system and log when it receives an unknown or unexpected scan. For example, an open port may be scanned by or connected to a connected user's remote iPhone, but since this is an expected action from an iPhone, the security server **56** does not automatically consider this a threat to the home automation integration system **20**. If a connected home automation or addressable device **31a-31n**, for example, a refrigerator, does the same scan of or connects to the open ports, the security server **56** logs the action, and then reports the logs to the analytics server **54**. The security server **56** is aware of what can be considered normal behavior for an addressable device **31a-31n** by way of a signature file included for all known controllable devices. In other words, because the types of devices, both remote and controllable, coupled to the home automation integration system **20** on network are known, traffic among the devices can be monitored to maintain security. If traffic or communications associated with a particular device is determined to be erratic, the security server **56** may identify the device as being hijacked and/or malware and flagged for reporting to the analytics server **54**. The analytics server **54** uploads the data to the cloud device **33** for security analysis.

**[0116]** An example security server signature that describes what may be considered normal behavior of a network device is below:

```
<signature cls="com.k4connect.someNetworkDevice" description="Example Network Device">
```

```
<behavior>
```

```
<http>
  <url>http://api.someurl.com/*</url>
  <frequency>300</frequency>
</http>
<socket>
  <destination>*</destination>
  <port>80</port>
  <quantity>3</quantity>
</socket>
</behavior>
</signature>
```

**[0117]** The cloud server or cloud device **33** may perform an analysis to assess or classify patterns and recommend actions for the security server **56**. Some examples of actions for the security server **56** to take include notifying the user of abnormal actions of a device, disconnecting a compromised device from the K4Connect system **20**, or ignoring if the action is not malicious. The K4Connect system **20** in some instances may recognize a vulnerability or attack in a manufacturer's smart device and can provide the information about the vulnerability to the manufacturer. Of course, the cloud device **33** may recommend other and/or additional actions for the security server based upon the analysis.

**[0118]** Referring now to FIG. 13b, the security server **56** with respect to the HA system **20** will now be described. The HA system **20** includes addressable HA devices **31a-31n** each having a respective HA device signature associated therewith, which may be stored in a memory **562**. The HA device signatures may include data regarding expected actions of the addressable HA devices **31a-31n**. The HA device signatures may also include MAC addresses, port data, and universal serial bus (USB) identifiers, for example. Of course, the HA device signatures may

include any combination of and/or or additional identifiers that may be used as a basis to characterize operating behavior of the addressable HA devices **31a-31n**.

**[0119]** The addressable HA devices **31a-31n** may include any of motion detectors, thermostats, light switches, audio controllers, door locks, and/or cameras. Of course, the addressable HA devices **31a-31n** may include other and/or additional devices. The addressable devices **31a-31n** wirelessly communicate using respective different wireless communications protocols from among different wireless communications protocols.

**[0120]** The HA system **20** includes an HA security controller **561** coupled to the memory **562** and that communicates with the addressable HA devices **31a-31n** via respective communications ports, for example by scanning or polling the communications ports. A given communications port is not currently being used or is open. When a given addressable HA device **31a-31n** communicates via the given communications port not currently being used, the HA security controller **561** determines whether the given addressable HA device is operating abnormally based upon the respective HA device signature and communicates to the cloud **33** for verification of whether the given addressable HA device is operating abnormally. When the given addressable HA device **31a-31n** is verified to be operating abnormally, the HA security controller **561** terminates communications with the given addressable HA device.

**[0121]** The HA security controller **561** also generates a notification when the given addressable HA device **31a-31n** is verified to be operating abnormally. In some embodiments, the addressable HA devices **31a-31n** each has a manufacturer associated therewith, and the HA security controller **561** may communicate the notification to a respective manufacturer associated with given addressable HA device verified to be operating abnormally. Of course, the HA security controller **561** may communicate the notification to another device and/or entity, as will be appreciated by those skilled in the art.

**[0122]** The HA system **20** may also include a communications interface **563** that provides communication between the HA security controller **561** and the cloud **33**. The HA security controller **561** communicates with the cloud **33** via the

communications interface **563**, for example, to update the stored HA device signatures in the memory **562**.

**[0123]** The HA system **20** also includes radio controllers **44a-44n** coupled to HA security controller **561**. Each of the addressable devices **31a-31n** may be configured to wirelessly communicate with the HA security controller **561** via respective radio controllers **44a-44n**.

**[0124]** A method aspect is directed to a method of communicating in the HA system **20**. The method includes using the HA security controller **561** to communicate with the addressable HA devices **31a-31n** via respective ones of the communications ports, with a given communications port not currently being used. The method also includes using the HA security controller **561** to, when a given one of the addressable HA devices **31a-31n** communicates via the given communications port not currently being used, determine whether the given addressable HA device is operating abnormally based upon the respective HA device signature, communicate to the cloud **33** for verification of whether the given addressable HA device is operating abnormally, and terminate communications with the given addressable HA device and generate a notification when the given addressable HA device is verified to be operating abnormally.

**[0125]** Another aspect is directed to setup wizards of the K4Home software. A setup wizard may provide an increasingly simple and relatively uniform setup process for each device connected to the K4Connect system **20**, and particularly, connected to K4Home. The setup wizard may limit the actionable items on each screen step of the wizard to maintain simplicity. For example, the setup wizard may allow one question and one data input received from that question before moving to the next step in the wizard.

**[0126]** Each setup wizard is based upon prebuilt templates that allow software developers to collect the data for the setting up of a device without having to build new user interface components. Each setup wizard may be customizable for developers and bridge builders, for example. Customization may be achieved by allowing each setup wizard to have a unique style sheet while keeping base styles consistent. Beyond the base styles, the user interface in each setup wizard may be changeable, but it is desirable that these changes be within specific parameters. If

no suitable template is available for the developer, for example, user interface components may be created. Custom templates would still use K4Connect components when available and may not contradict the relatively simple and uniform setup process provided by the K4Home software.

**[0127]** Referring additionally to FIGS. 14a and 14b, each setup wizard may also provide contextual help by supplying a progress bar **71**, for example, on the display **48** of the remote device **36** or as part of the user interface **35**, for example, that includes a help button **72** on the progress bar. The help button **72** links to help that corresponds to the user's current step in the setup wizard. In other words, the user will be presented with different instructions on the display **48** depending on where the user is in the setup process. This may be particularly advantageous in that it aids users in steps in the setup that are frequently problematic and may make the user experience more adaptive and easier than current home automation setups.

**[0128]** Referring now to FIGS. 15a-15c, the user interface **35** may provide several different ways to control the K4Connect system **20** or to control addressable devices **31a-31n** on the K4Connect system. For example, the K4Connect system **20** may be controlled by room (FIG. 15a), by scene (FIG. 15b), and by device types (FIG. 15c). Of course, the K4Connect system **20** may be controlled in other fashions or using other techniques.

**[0129]** The user interface **35**, which may be presented via the display **48** of a remote device **36**, for example, a touch screen display of a mobile phone, allows the user to view addressable devices **31a-31n** by device category or by the location (FIG. 15a) of the addressable device. The user can also switch directly from the addressable device selection from the location to the addressable device category view. The user interface **35** also advantageously tracks the history of the devices used by tracking the last contacted device. This may allow the user to directly access recently used addressable devices **31a-31n** more quickly instead of searching back through prior pages of the user interface. The user interface **35** may also provide increased usability by allowing the entire screen of the remote device **36**, for example, a touch-screen remote device to be used to adjust the addressable device **31a-31n** instead of locating a single point on the touch-screen display for adjustment. In some embodiments, addressable devices 31a-31n may be controlled

via the user interface 35 by way of voice recognition, for example. Other types of control may also and/or additionally be used, for example, biometrics, or gesture (e.g., arm, hand, eye) recognition.

**[0130]** Referring now to FIG. 16, when one or more of the addressable devices **31a-31n** are in the form of a light emitting diode (LED) bulb, the user interface **35** includes an LED color picker **75** function. The LED color picker **75** provides a more accurate method to set colors in controllable multi-color LED light bulbs **31a**. Currently, the user selects a color from a palette and the bulb will adjust to closest color possible. This may result in a variation between what the user selects from the display **48** and the actual output from the multi-color LED light bulb **31a**.

**[0131]** The LED color picker **75** by way of the processor **49** of the remote device **36**, detects the colors the multi-color LED light bulb **31a** is capable of producing and presents those color options to the user. This is done, for example, by determining the CIE delta of the multi-color LED light bulb **31a**. The CIE delta may be determined by the manufacturer, the data for which may be stored in the remote device **36** or received from the cloud device **33**.

**[0132]** Referring to FIG. 17, in another embodiment, when the remote device **36'** includes a camera **86'**, the processor **49'** of the remote device may cooperate with the camera to capture the colors actually illuminated by the multi-color LED light bulb **31a'**. The processor **49'** of the remote device **36'** then displays on the display **48'** the available colors of the multi-color LED light bulb **31a'** based upon the stored CIE delta information or the captured images. Colors are calculated in the CIE triangle versus finding the color at the end of the delta. Additionally, in some embodiments, the remote device signature, as discussed above, in the case of a multi-color LED light bulb may include the CIE delta of the bulb based upon the model number, for example. The user then chooses the exact color from the options on the display **48'** and the multi-color LED light bulb **31a'** changes to selected color. This matches the user expectation to the light bulb output in contrast to the current method which selects a color based upon an approximation.

**[0133]** As will be appreciated by those skilled in the art, the capabilities of the multi-color LED light bulb **31a** are typically much less than what a typical CIE

diagram shows. The embodiment described herein advantageously determines the color displaying capabilities of the multi-color LED light bulb **31a** and allows selection of those actual colors rather than making an approximation.

**[0134]** Referring now additionally to FIG. 18, the user interface **35** also provides an interface for interacting with multiple K4Hubs hubs or hub devices, for example a home hub **34a** and an office hub **34b**. Currently in the home automation market, end users either cannot set up multiple hubs in their homes or the hubs are combined in a cloud system preventing the user from being able to make an obvious distinction between the systems. The K4Connect system **20** advantageously permits the user the option of controlling multiple hubs from the user interface **35** by connecting, for example, automatically, to the local hub and connecting to any other hubs through the cloud.

**[0135]** When connected to a local network, for example, via Wifi, the user interface **35** of a remote device **36** may automatically connect (i.e., without user intervention) to the hub device **34a, 34b** on the same local network. When using a cellular connection or Wifi network that is not connected to a hub device **34a, 34b**, the user interface **35** allows the user to pick which of the multiple systems they would like to view. For example, in a first scenario, a connection to a hub device **34a** located in the user's office. The K4App or user interface **35** controls the addressable devices **31a-31n** from the office hub **34a**, but the user has the option to switch the user interface to control other connected hubs. In a second scenario, when the user is connected only to a cellular network such as an LTE network, the user interface **35** provides an option for the user to choose between the connected hubs if there is more than one, so the user can pick between home hub **34b** or the office hub **34a**. In a third scenario, the user is connected to the home hub **34b** and the user interface **35** automatically controls the addressable devices **31a-31n** at home, but the user can switch to controlling the office hub **34a** on the user interface.

**[0136]** When a new addressable device **31a-31n** is detected by the home device **32** or the hub device **34** (i.e. a device running K4Home), for example, new software for supporting the newly detected addressable device may be downloaded. For example, an "app store" for controllable devices may provide support or drivers for the newly detected controllable device. The "app store" may be hosted by the

cloud server **33** or third party provider, for example. With respect to the app store being available on the cloud server, the cloud server may store in memory addressable device drivers. When a new addressable device **31a-31n** is detected by the home device **32** or hub device **34**, the home or hub device may “pull down” the corresponding driver or software and not an entire software package.

**[0137]** Referring now additionally to FIG. 19, further details of the bridges **82** will now be described. The K4Connect bridges **82** provide a translation layer for the message queue or message queue server **50** to communicate with the addressable devices **31a-31n** connected to the K4Connect system **20**. When a user or a predefined scene executes a command on the K4Connect system **20**, the message queue **50** sends a generic form of the message through the Node.js APIs to the associated bridge **82**. The generic form of the message may be sent through different APIs or by different techniques as will be appreciated by those skilled in the art. The bridge **82** then translates the generic command to the specific command for the addressable device **31a-31n** and sends the translated command to the addressable device.

**[0138]** The independence of the bridges **82** advantageously allows developers to write bridges for nearly any controllable device independently of the whole K4Connect system **20**. After a bridge **82**, which may generally be stored separately from the message queue **50**, is coded, for example, it may be downloaded and integrated into the message queue **50** without having to update the entire K4Connect software program.

**[0139]** More particularly, when a new addressable device **31a-31n** is detected by the home device **32** or hub device **34**, for example, new software for supporting the newly detected controllable device may be downloaded, i.e. a bridge. For example, an “app store” for controllable devices may provide support or the bridge for the newly detected controllable device. The “app store” may be hosted by the cloud server **33** or third party provider, for example. With respect to the app store being available on the cloud device **33**, the cloud device may store in memory addressable device bridges. When a new addressable device **31a-31n** is detected by the home device **32** or hub device **34**, the home or hub device may “pull down” the corresponding bridge or software and not an entire software package.

**[0140]** The independence of each bridge also allows for better usage of bandwidth and storage space on the home K4Connect system **20**. By not downloading an entire software update package every time a bridge is updated, the user and K4Connect preserve Internet bandwidth and data. Also, the ability to only download the bridges **82** that are desired by each user allows the user to preserve memory space on the device running K4Home, e.g. the home device **32** and/or K4Hub **34**. This preserved memory space allows the K4Connect system **20** to provide a relatively large number of bridges for new home automation devices with less concern of bloated software or limited storage space on user devices, for example.

**[0141]** Referring now particularly to FIG. 20, when a new bridge **91** is created and loaded to the K4Connect system **20**, the update servers **59** on each K4Connect system connect to the cloud device **33** or K4Away and are notified when the system performs an update. As will be appreciated by those skilled in the art, the update server **59** may perform an update by communicating with the cloud server and determining based upon communication therewith whether an update exists (e.g., based on date, update ID, etc.) The device signature of the new bridge and the device description are sent to the update server **59**. The file or files associated with the device signature and description are generally much smaller than the complete bridge file, which is downloaded if the new controllable device is ultimately connected to the K4Connect system **20**. The update server **59** sends the device signature to the discovery server **35** and the device description to the configuration server **62**. The device signature allows the discovery server **35** to scan available ports and recognize if a new addressable device **31a-31n** that can be connected by the new bridge **91** is in the home. The device description includes the wizard process, for example, as described above, to set up the new controllable device. When the discovery server **55** finds a new controllable device that can be connected by a new bridge **91**, the discovery server **55** sends a message to the configuration server **62** notifying the configuration server of the new addressable device. The discovery server **55** also sends a new addressable device notification to the notification server **66**, which launches the user interface **35** on the display **48** of the remote device **36** to inform the user of the new addressable device. The bridge

wizard **92** is also launched. The bridge wizard **92** gathers the information for the device description and requested from the configuration server **62**.

**[0142]** Once the information has been gathered and user provides a response, for example via the bridge wizard **92**, the configuration server **62** notifies the loader server **64** of the new configured addressable device. The loader server **64** requests the full bridge download from the update server **59**, and the update server requests the full bridge from the cloud device **33** or K4Away. The update server **59** sends the full bridge download to the loader server **64**, which stores the file and launches the new bridge. The newly connected controllable device is thus connected to the K4Connect system **20**.

**[0143]** Referring now additionally to FIG. 21a, the bridges **82a-82c** of the K4Connect system **20** are also what may be referred to by those skilled in the art as “sandboxed” so that the system may be less subject to interruption should a given bridge fails. If one of the bridges **82a-82c** fails or if the connection to the message queue **50** fails, the remaining system components continue to function. The bridges **82a-82c** execute the communication between themselves and the message queue **50** so that if there is a failure in communication, the bridge will generally restart the communication. If a bridge **82a-82c** has an error, for example, the loader server **64** reloads the bridge **82a-82c**. These sandboxed processes limit or reduce restarting of the entire software program running on the home device **32** or hub device **34** if an error occurs in a bridge **82a-82c**. However, one effect on the K4Connect system **20** may be the inability of controlling the specific addressable devices **31a-31n** associated with the failed bridge **82a-82c**, which may be quickly remedied when the loader server **64** reloads the bridge. The functionality of the message queue **50**, other servers, and other bridges are generally unaffected. As noted above, bridges may be installed on demand, for example, as needed, for communicating with addressable HA devices.

**[0144]** Referring now to FIG. 21b, the “sandboxed” bridges **82a-82c** will now be described with respect to the HA system **20**. The HA system **20** includes addressable HA devices **31a-31n**. The addressable HA devices **31a-31n** may include any of motion detectors, thermostats, light switches, audio controllers, door locks, and/or cameras. Of course, the addressable HA devices **31a-31n** may include

other and/or additional devices. The addressable devices **31a-31n** wirelessly communicate using respective different wireless communications protocols from among different wireless communications protocols.

**[0145]** A processor **641** and a memory **642** associated with the processor may cooperate to perform the functions described above with respect to the sandboxed bridges **82a-82c**. More particularly, the processor **641** and the memory **642** are configured to implement the message queue **50**. That is, the message queue **50** generates generic messages for respective ones of the addressable HA devices **31a-31n**. The processor **641** and the memory **642** also implement sandboxed bridges **82a-82c**. Each sandboxed bridge **82a-82c** converts a generic message from the message queue **50** into a specific message for a given one of the addressable HA devices **31a-31n**. The specific message may be a specific control and/or status message that is specific for the respective sandboxed bridge **82a-82c**.

**[0146]** Upon failure of one of the sandboxed bridges **82a-82c**, the processor **641** and memory **642** implement reloading the failed sandboxed bridge **82a-82c** while maintaining operational the other sandboxed bridges. The processor **641** may determine the failed one sandboxed bridge **82a-82c** based upon communication between the sandboxed bridges and the message queue **50** and/or communication between or among the sandboxed bridges **82a-82c**, for example.

**[0147]** The HA system **20** also includes radio controllers **44a-44n** coupled to the processor **641**. Each of the addressable devices **31a-31n** may be configured to wirelessly communicate with the processor **641** via respective radio controllers **44a-44n**.

**[0148]** A method aspect is directed to a method of maintaining operational a plurality of sandboxed bridges **82a-82c** in the HA system **20**. The method includes using the processor **641** and the memory **642** associated therewith to generate, via the message queue **50**, a plurality of generic messages for respective ones of the plurality of addressable HA devices **31a-31n** and convert a generic message from the message queue into a specific message for a given one of the addressable HA devices using the plurality of sandboxed bridges **82a-82c**. The method also includes using the processor **641** and memory **642** to, upon a failure of one of the plurality of

sandboxed bridges **82a-82c**, reload the failed sandboxed bridge while maintaining operational the other sandboxed bridges.

**[0149]** Referring now additionally to FIG. 22, the K4Home software, which may be executed on the home device **32** or the hub device **34**, also features responsive scenes that function as a list of elements **95** of the K4Connect system **20** that then may induce actions in the addressable devices **31a-31n** connected to the system **20**. The responsive scenes can also return plain language notifications to the user, for example, at the user interface **35**, based on the status of the system **20**.

**[0150]** The standard responsive scenes can be set-up by the user by using a scene wizard. The scene wizard includes a list of addressable devices **31a-31n** and command event variables or triggers. The user, for example via the user interface **35** of the K4App, selects the triggers for the scene, the addressable devices **31a-31n** affected, and the actions or states the addressable devices will take to respond to the scene.

**[0151]** The standard responsive scene may be initiated by a list of triggers detected by the program or by the user activating the scene **93** in the user interface **35**. An example of a command variable or trigger list is as follows: Trigger 1 is a time period, Trigger 2 is a mobile controlling device being connected to the network, Trigger 3 is a set day, and Trigger 4 is a connected motion detector sensing motion.

**[0152]** The scene has specified user defined components or which set of addressable devices **31a-31n** will be contacted for the scene and what state those addressable devices should take. For example, controllable device 1 **31a** is a television (TV), addressable device 2 **31b** is a set of lights in the TV room, addressable device 3 **31c** is a room thermostat in the TV room, and addressable device n **31n** controls operation of a coffee maker. The system **20** generates a command that is sent to the addressable device. The addressable devices **31a-31n** respond based upon the command.

**[0153]** For example, Trigger 1 is activated from 7-9 pm, Trigger 2 is activated when a given user's smartphone or remote device **36** is connected to the local network, Trigger 3 is activated on weekdays, and Trigger 4 is activated by a living room motion detector detecting motion. Based upon the triggers, the user defined

components turn the TV on to a given channel, dim the lights in the TV room, adjust the thermostat to 72 degrees, and begin brewing the evening decaf coffee.

**[0154]** The standard responsive scenes may also be shared between users using the cloud device **33** or K4Away, and a marketplace that lists available scenes. The K4Connect system **20** may also suggest possible other and/or additional addressable devices **31a-31n** to connect to add functionality and more responsive scenes to individual users of K4Home.

**[0155]** Once a user has completed the responsive scene wizard or has added a shared responsive scene, the remote device **36** via the user interface **35** may display a modeled animation of the scene which shows what the scene looks like upon activation. The user may also access an animation of the scene that will function throughout the entire day and their triggers.

**[0156]** Referring now to FIGS 23-29a, another aspect of K4Home is what may be referred to as an ingredient responsive scene based on property based ingredients, which allows the use of different addressable devices that can produce the same properties in the recipes. Instead of a scene being tied to a specific addressable device **31a-31n** for a given function, for example, the scenes are based upon a specific property. This advantageously allows for responsive scenes to be implemented using the same elements that the responsive scene needs, but does not use identical devices.

**[0157]** For example, if a given user wants to know when another user is home, they may set up a responsive scene that identifies the addressable devices **31a-31n** that may be used to indicate whether or not someone is home. For the given user, the addressable device **31a-31n** or ingredient in the responsive scene may be a deactivated alarm system, which when tripped gives the desired properties to trigger the responsive scene. The responsive scene then has the K4Connect system **20** send the given user a notification, for example, a plain language notification, that the other user is home. This scene can then be shared with yet a third user who does not have an alarm system but does have motion detectors **101**, which fall in the same list of devices that can give the desired properties to complete the recipe. In other words, the scene is associated with a desired outcome irrespective of specific addressable devices **31a-31n**. In instances where a recipe is almost completed or

can be augmented by adding more controllable devices, the K4Connect system **20** informs the user, for example, via the user interface **35** on the remote device **36**, of the possible recipe based responsive scene and links them to an online market where the user can download, either free or for purchase, the addressable device **31a-31n**.

**[0158]** Another example of a responsive scene based on the ingredients list is if the system **20** indicates that a recipe has not been met, it can then send a plain language notification that the recipe has not been met. For example, if a person has not arrived at home by a certain time, the recipe includes the ingredients of presence (by way of motion detectors, cameras, and a connected smartphone (i.e., remote device **36**)) and time. The lack of presence at a specific time triggers the scene and alerts the user. Of course, others, for example, a monitoring center and/or other designees, may be alerted.

**[0159]** A user may set up an ingredient responsive scene (Block **114**) or download a shared responsive scene from the cloud device **33**. K4Home then determines whether all the ingredients are present in the K4Connect system **20** (Block **102**). If addressable devices **31a-31n** that can provide ingredients properties are connected to the K4Connect system **20**, the system determines the state (Block **106**) of the addressable devices by polling the addressable devices (Block **103**). If all of the ingredients of the scene are met (Block **104**), then the K4Connect system **20** executes the scene (Block **108**). If the ingredients of the K4Connect system **20** do not meet the conditions (Block **104**), then the system may either poll the property states again (Block **103**) or wait a specified amount of time set by K4Home or the responsive scene. If any of the ingredients/properties are not available in the K4Connect system **20** because an addressable device **31a-31n** that can provide the ingredient is not connected, then K4Home sends a message to the analytics server **54** requesting suggested controllable devices from the cloud device **33** (Block **110**) and may also cooperate to present the user, for example, on the user interface **35**, an opportunity to purchase the suggested controllable devices (FIG. 24). The new addressable devices may be installed at Block **112**.

**[0160]** In another example, a user may download a responsive scene that utilizes a camera to record motion events during a specific time period. For

example, a given user wishes to record when his dog climbs onto the living room couch while the given user is at work from 8am-5pm. The given user then constructs the scene with three ingredients: ability to record video (provided by a camera connected to K4Home), motion (provided by the same camera's built in motion detector), and a time period. The given user then shares this on the responsive scene market place on the K4Away or cloud device **33**. Another user downloads the scene and intends to use the scene for home security at night, for example. The other user has a camera, but not the ability to sense motion. K4Home suggests the other user install independent motion sensors to be able to use the scene and provides a link to the K4Store or the cloud device **33** from which the orders of any of a number of brands and styles of motion detectors may be purchased. The other user then installs the motion sensors, which now enables the responsive scene to be enacted since all ingredients are met. The other user then records any motion in his living room from 10pm-6am using the same base responsive scene while using different devices to provide the ingredients.

**[0161]** For example, a user may generate a responsive scene to provide the idea of "home." The responsive scene may be generated with respect to the user so that, "when I am home, I want light in the living room." The K4Connect system **20** indicates or displays, for example, via a menu, that "there are x devices you can use to determine whether I am home, and here are the devices that provide light." In other words, the scene is constructed first and then the addressable devices **31a-31n** that can make the scene are provided.

**[0162]** Referring now to FIG. 29b, ingredient responsive scenes as they relate to the HA system **20** will now be described. The HA system **20** includes addressable HA devices **31a-31n** at a given location. The addressable HA devices **31a-31n** include any of motion detectors, thermostats, light switches, audio controllers, door locks, and/or cameras. Of course, the addressable HA devices **31a-31n** may include additional and/or other devices.

**[0163]** The HA system **20** also includes an HA device scene controller **581** that obtains from a user, for example, wirelessly, a first desired scene that includes a first trigger action and first responsive event. For example, the first trigger may be "when I arrive home" and the first responsive event may be "turn on the living room

lights”. Indeed, the first trigger action and the first responsive event do not identify which of the addressable HA devices **32a-32n** are responsible for implementing the first trigger action and the first responsive events. The HA device scene controller **581** may obtain the first trigger action and the first responsive event from a user-interface device **360**, for example, and more particularly, a user-input device **351** coupled to a user-interface controller **353** to permit user input. The user interface device **360** may be a remote device, for example, a tablet computer, a smartphone, etc. There may be more than one first trigger action and any number of first responsive events.

**[0164]** The HA device scene controller **581** also presents a first user-selectable list of corresponding ones of the addressable HA devices **31a-31n**, for example, on a display **354** of the user-interface device **360** coupled to the user-interface controller **353**, that are capable of implementing the first desired scene. In other words, the HA device scene controller **581** presents addressable HA devices **31a-31n** that correspond to or will execute the first trigger action and the first responsive event.

**[0165]** The HA device scene controller **581** also determines the first user-selected ones of the addressable HA devices **31a-31n**, and upon occurrence of the first trigger event, performs the first responsive event using the first user-selected addressable HA devices to thereby implement the first desired scene. The first desired scene may be executed wirelessly, for example, the HA device scene controller **581** may be communicate wirelessly with the addressable HA devices **31a-31n** to implement the first desired scene. In some embodiments, the HA device scene controller **581** may generate a notification upon occurrence of the trigger event.

**[0166]** The HA device scene controller **581** also obtains from the cloud **331**, for example, wirelessly, a second desired scene that includes a second trigger action and second responsive event. The second trigger action and second responsive event are obtained without identifying the addressable HA devices **31a-31n** responsible for implementing the second trigger action and second responsive event.

**[0167]** The HA device scene controller **581** may present a second user-selectable list of corresponding addressable HA devices **31a-31n**, for example, on

the display **354**, capable of implementing the second desired scene. In other words, the second scene is obtained as a shared scene, for example from another person's HA system. The HA device scene controller **581** also determines the second user-selected addressable HA devices **31a-31n**, and, similar to that described above, for example, wirelessly, upon occurrence of the second trigger event, performs the second responsive event using the second user-selected addressable HA devices to thereby implement the second desired scene.

**[0168]** The HA device scene controller **581** also may determine when the addressable HA devices **31a-31n** at the given location are not capable of implementing the scene. When this is the case, the HA device scene controller **581** presents a purchase offer, for example on the display **354** for an additional addressable HA device. The user may purchase the additional addressable HA device by clicking on a hyperlink, for example.

**[0169]** A method aspect is directed to a method of implementing first and second desired scenes in an HA system **20**. The method includes using an HA device scene controller **581** to obtain from a user the first desired scene that includes a first trigger action and a first responsive event and to present a first user-selectable list of corresponding addressable HA devices **31a-31n** capable of implementing the first desired scene. The HA device scene controller **581** is also used to determine the first user-selected addressable HA devices **31a-31n**, and upon occurrence of the first trigger event, perform the first responsive event using the first user-selected addressable HA devices to thereby implement the first desired scene.

**[0170]** The HA device scene controller **581** is also used to obtain from the cloud **331** the second desired scene that includes a second trigger action and a second responsive event and to present a second user-selectable list of corresponding addressable HA devices **31a-31n** capable of implementing the second desired scene. The device scene controller **581** is also used to determine the second user-selected ones of the addressable HA devices, and upon occurrence of the at least one second trigger event, perform the second responsive event using the second user-selected addressable HA devices **31a-31n** to thereby implement the second desired scene. In some embodiments, the HA device scene controller **581** is used to determine when the addressable HA devices **31a-31n** at the given location

are not capable of implementing the scene, and to present a purchase offer for an additional addressable HA device.

**[0171]** Development kits as they relate to the K4Connect system **20** will now be described. The K4Connect system **20** provides both software and hardware development kits. The software development kit builds a complete device stack for developers to interact with and handles all communication with the message queue. A built-in bridge editor allows developers to create and edit bridges from a web browser, for example, and a description editor creates device description XML files.

**[0172]** The hardware development kit allows developers to connect controllable devices directly to the message queue without an intermediary bridge. For example, as developers add communication protocols to their controllable devices, the K4Connect system **20**, particularly the communication components thereof, may be integrated into their hardware to bypass a bridge on the system and communicate directly with the message queue.

**[0173]** Further details of the cloud device **33** or K4Away will now be described. In addition to the functions of K4Away already described, K4Away hosts an external API, which provides an interface for devices that cannot connect to Internet based services on their own. When connected to the K4Connect system **20** and K4Away, previously un-networked devices may become accessible to outside services such as, for example, IFTTT, Evernote, and Facebook, through its connection with K4Away.

**[0174]** With respect to security, the security model of the K4Connect system **20** is based upon providing a relatively high level of security for the system. Each phone or remote device **36** is authenticated on two levels. The first level is a device specific allowance added by the system administrator. The second level is the user login on the remote device **36**. This two-layer system reduces occurrences of a login of unauthorized devices even if there is a valid user login.

**[0175]** The K4Connect system **20** also provides security through its privacy method in its analytics data collection. The data is stored on two separate servers. One server holds a token representing the anonymous user while the other server holds the usage and analytic data. The connection between the two servers occurs when authorized by the user for technical help. When the user is sent responsive

scene or device recommendations, the suggestions are typically only sent to the token representing the user. The user remains anonymous at all times. In other words, a portion of the information about a user may be selectively available for providing technical support, similar to a “need-to-know” basis.

**[0176]** The K4Connect system **20** also uses a security method that grants the user complete rights and ownership to the data collected. The K4Connect system **20** collects and analyzes data from the user and stores it on the separate secure servers. After a threshold time period, for example, one year, the data is permanently deleted. This method includes a user override granting the user the ability to permanently delete their data at anytime.

**[0177]** The K4Hub **34** can also be used as a Wifi router connected to a home router so that all the devices connected to the K4Connect system **20** are routed through the private Wifi network of the K4Hub **34**. This advantageously allows for a separation between devices, such as personal computers, connected to the K4Connect system. This separation may reduce the chances of attacks on personal computers from affecting the network among devices of the K4Connect system **20**.

**[0178]** Referring now to FIG. 30a, another aspect is directed to health related devices for use on the K4Connect system **20**”. The use of health related devices in conjunction with the K4Connect system **20**” may be termed K4Life. However, it should be noted that other and/or additional devices, whether health related or not, may be part of the K4Life system. Similar to the K4Connect system described above, the K4Life system **20**” includes addressable devices **31a**”-**31n**”, some of which may be in the form of health devices that measure human health related data, such as, for example, steps walked, blood pressure, weight, and other metrics. In other words, the K4Life system **20**” performs the functions of the K4Connect system described above, and includes further health related functions as will be described in further detail below. For example, health devices may include one or more bed sensors, motion detectors, fitness tracking devices, blood pressure cuffs/monitors, weight scales, and temperature probes, for example. Of course, other and/or additional health devices or sensors, for example from the K4Home system, may be used.

**[0179]** In addition, the K4App provides social interaction, for example, photo sharing and live video chat. More particularly, when a live video chat is started, the K4Life system **20''** may report the start time and duration of the live video chat to a central server, for example, the cloud device **33''** or local server device.

**[0180]** The K4Life system **20''**, for example, the analytics server **54''**, computes a score indicating the overall health of the user, which may be referred as K4Score. The K4Score is determined by combining directly measured health data, activity level measured from the use of addressable devices or health devices **31a''-31n''**, and social engagement measured by the use of the K4App. The K4Score may include or be based upon other and/or additional information. The historical trend of this score may be used to predict improvement or decline in a user's health, for example. Of course, this data may be used for other purposes, for example, communicated to other users such as health care professionals, monitoring stations, etc. For example, a person who is sedentary, has irregular sleep patterns, and little social interaction may be identified as a having potential health issues. One example scenario where the K4Life system **20''** and K4Score may be relatively advantageous is the use of the system by an elderly parent whose children wish to check on the parent's wellbeing or if a user simply wants to keep apprised of their own wellbeing.

**[0181]** In some embodiments, the health or activity data may be viewed by family members or in a group living setting, such as an assisted living facility or by an onsite or remote supervisor. The health data may also be displayed, for example, via the user interface **35''** of the remote device **36''**, to show the health score of an individual user, or an aggregate of a community of users.

**[0182]** Referring now to FIG. 30b, the health related aspects of the K4Connect or HA system **20''** will now be described. The HA system **20''** includes addressable HA devices **31a''-31n''**. The addressable HA devices **31a''-31n''** may include any of motion detectors, thermostats, light switches, audio controllers, door locks, cameras, and/or health-related sensors (e.g. room occupancy sensors, bed sensors, step counters, heart rate monitors, blood pressure monitors, temperature sensors, and weight scales). Of course, the addressable HA devices **31a''-31n''** may include other and/or additional devices. The addressable devices **31a''-31n''** wirelessly

communicate using respective different wireless communications protocols from among of different wireless communications protocols.

**[0183]** The HA system **20''** also includes a user interface device **36''** that permits user social networking and generates user social networking data based thereon, for example, data related to which social networking applications and an amount of time spent using each social networking application. The user interface device **36''** includes a portable housing **361''**, a display **48''** carried by portable housing, wireless communications circuitry **362''** carried by the portable housing, and a user interface device controller **49''** coupled to the display and wireless communications circuitry for performing at least one wireless communications function. For example, the user interface device **36''** may be a smartphone or tablet, and may execute any number of social networking applications, for example, photo sharing, live video chat, and social media applications.

**[0184]** The HA system **20''** also includes a controller **381''** and a memory **382''** coupled thereto that stores measured user health data and determines user physical activity data based upon the addressable HA devices **31a''-31n''**. The physical activity may be determined based upon a period of time period.

**[0185]** The controller **381''** also generates a user health score based upon the user social networking data, user health data, and user physical activity data, and communicates the user health score via the cloud **331''**. The controller **381''** may also generate user health scores based upon the determined physical activity level at intervals within the period of time, for example.

**[0186]** The controller **381''** may, for example, generate a notification when the user health score exceeds a threshold. More particularly, if a user health score is indicative of poor health, a notification, such as, for example, an email, SMS message, visual notification on a display, etc. may be generated and communicated to an electronic device **361''** via the cloud **331''**. In some embodiments, the controller **381''** may generate a notification if there are consecutive declining user health scores over the time period. Once the user health score is communicated to the cloud **331''**, it may be downloaded, for example, by the electronic device **361''** for storing, viewing, analysis, and/or other data processing as will be appreciated by those skilled in the art.

**[0187]** A method aspect is directed to a method of communicating a user health score in the HA system **20''**. The method includes permitting, via a user interface device **36''**, user social networking and generating user social networking data based thereon. The method also includes using the controller **361''** and the memory **362''** coupled thereto to store measured user health data, determine user physical activity data based upon the plurality of addressable HA devices, generate a user health score based upon the user social networking data, user health data, and user physical activity data, and communicate the user health score via the cloud.

**[0188]** Referring now to FIG. 31, the K4Connect system **20'''** may also be used for location determination. The K4Connect system **20'''** may detect mobile devices (i.e., remote devices **36'''**) that are within a specified range of the K4Hub **34'''**. These detections can be reported to a central server, for example, the cloud device or K4Away where they are used to estimate a person or device's location within a home or facility, for example. As more than one K4Hub **34'''** can detect a mobile or remote device **36'''** at a time, the K4Connect system **20'''** reduces duplicate data by comparing the detection strength of overlapping data and determining which K4Hub was closest to the detected person or device. Of course, K4Connect system **20'''** described in this embodiment may be particularly useful for use with the K4Life system described above.

**[0189]** Referring now to FIG. 32, in another embodiment, multiple K4Life (or K4Connect) systems **20a''''-20n''''** may be used collectively in a system that may be referred to as K4Community. The K4Community system advantageously allows the aggregate data from the multiple K4Life or K4Connect systems **20a''''-20n''''**, for example, at the cloud device or K4Away, to be analyzed for comparison within the community. Data from other controllers and/or devices may also be aggregated. Of course, any or each system **20a''''-20n''''** may process or aggregate the data, for example, entirely or in a shared or load balanced arrangement. Additionally, users in the K4Community **20a''''-20n''''** may be able to communicate with each other, and in some embodiments, see how others are performing relative to a given user's performance. As will be appreciated by those skilled in the art, because health related data is being collected and potentially exchanged, the health related data is

maintained anonymous, and may be encrypted, until the user or owner of the health data agrees to share or actually shares it.

**[0190]** In some embodiments, the K4Life or K4Community system may not be limited to health related devices and health related data. For example, the principles of the systems described above may be applied to utility management, for example, apartment utility load control management. In such an embodiment, the sensors or controllable devices may be used to monitor energy and water usage, for example, and build a profile based thereon. Particular tenants that use more utilities relative to other tenants may be identified. Common areas may also be monitored and scored. A score may also be assigned to each tenant.

**[0191]** Referring to FIG. 33, in another embodiment the K4Life system **120** may be used in a health care setting to determine how much time a health care professional is giving a patient or user. In one particular example, the system **120** may be used in a nursing home to monitor how much time a nurse is spending with the user/patient, and when and if the nurse was in the room **147** with the patient. The system **120** and particularly, the hub device **134**, includes a short-range communication protocol controller **199**, such as, for example, Bluetooth. Of course, the hub device **134** may be used interchangeably in this or other embodiments with the home device. Each nurse would also wear an identifying device or tag **197** that includes circuitry **196** configured to communicate with the system via the short-range communication protocol. When the nurse is in the room with the user or patient and is within communication range, the system and tag communicate and the time and duration of communication is logged. This information can be used in a K4Community environment, as will be appreciated by those skilled in the art.

**[0192]** Referring now to FIG. 34, in another embodiment, for example, in a K4Community system such as a healthcare facility, events or tickets that are based upon addressable devices may be generated. Those events may be logged and/or assigned to staff and displayed on a user interface **135'** of a remote device **136'**. When the staff arrives at the room, for example, of the person associated with the event generation, that staff person's time of arrival may be logged, for example, as described above.

**[0193]** While several embodiments have been described as including software that is executed by a processor or processing circuitry of an electronic device, it should be understood by those skilled in the art, that software may include firmware, machine code, or a configuration of the processors or processing circuitry. Moreover, while several embodiments have been described, it will be appreciated that the functions described in any given embodiment may be used with other and/or additional functions, for example, as described in different embodiments. Still further, while the term “home” has been used to describe certain devices and/or locations (e.g. with respect to home automation), it will be appreciated by those skilled in the art, that the system and its components may be used in other locations, such as apartments, health centers, etc. Thus the term “home” is not specifically limited to a user’s home. Moreover, while a processor and/or controller have been described herein, it will be appreciated that a processor and/or controller may include circuitry for execution respective functions and may also include a memory. A memory may also be coupled to the processor and/or controller, for example.

**[0194]** Method aspects include making a home automation integration system as described in any of the embodiments described herein, including K4Connect, K4Life, and K4Community, for example. Other method aspects include operation of the system or the various components thereof as well as performing any of the functions detailed above, for example, integration, communication, display, etc.

**[0195]** Another aspect is directed to a non-transitory computer readable medium that stores instructions for executing any of the functions of the systems and methods described herein. For example, the functionality of the K4App, K4Home, and K4Away may be embodied as computer executable instructions stored on a non-transitory computer readable medium. Of course other functions described herein may be embodied on a non-transitory computer readable medium.

**[0196]** Referring now to FIG. 35, another embodiment is directed to a climate control system **1020** that includes a heating, ventilation, and air conditioning (HVAC) system **1021** for an indoor building area **1022**. The HVAC system **1021** is switchable between operating modes for heating and cooling. The climate control system **1020** includes a home automation (HA) thermostat device **1030** in the indoor building area **1022**. The HA thermostat device **1030** includes a housing **1031** and an indoor

temperature sensor **1032** carried by housing. The indoor temperature sensor **1032** senses an indoor temperature of the indoor building area **1022**.

**[0197]** A temperature controller **1033** is carried by the housing **1031**. The HA thermostat device **1030** also includes wireless communications circuitry **1034** coupled to the temperature controller **1033**. The wireless communications circuitry **1034** may be configured to communicate via Wifi, cellular, or other protocol, for example.

**[0198]** The temperature controller **1033** obtains a setpoint temperature for the indoor building area **1022**. The setpoint temperature may be obtained wirelessly, for example, via the wireless communications circuitry **1034**. The setpoint temperature may be obtained from an input device, a remote electronic device, and/or other device, as will be appreciated by those skilled in the art.

**[0199]** The HA thermostat device **1030** also includes a user setpoint temperature input device **1035** and a display **1036**, both carried by the housing **1031** and coupled to the temperature controller **1033**. The user setpoint temperature input device **1035** may be in the form of a touch display, pushbutton, rotatable dial, or other input device, as will be appreciated by those skilled in the art. The user setpoint temperature input device **1035** may be used to set the setpoint temperature. The temperature controller **1033** may cooperate with the display **1036** to display the indoor temperature and the setpoint temperature.

**[0200]** The setpoint temperature may also be generated or set based upon an HA controller **1037**, for example, as described above, and coupled to the HA thermostat device **1030** and configured to generate the setpoint temperature. As described above, the HA controller **1037** may be coupled to addressable HA devices **1038a-1038n**, for example, motion detectors, lighting, etc. The HA controller **1037** generates the setpoint temperature based upon one of the addressable HA devices **1038a-1038n**. For example, based upon motion detected from a motion detector, the HA controller **1037** may communicate with the HA thermostat device **1030** to set the setpoint temperature (i.e., set the setpoint temperature cooler when someone is home). Of course, the setpoint temperature can be set based upon other types of addressable HA devices **1038a-1038n**.

**[0201]** The temperature controller **1033** also obtains an external temperature from external to the indoor building area **1022**. The external temperature may be obtained wirelessly, for example, via the Internet. The external temperature may be an outside temperature or may be an inside temperature of a room or area that may be considered external to the indoor building area **1022**, for example. In some embodiments, more than one temperature sensor (indoor and/or outdoor) may be used to obtain the external temperature.

**[0202]** The temperature controller **1033** determines a crossing of the external temperature of the setpoint temperature, and switches the HVAC system **1021** between operating modes based upon the crossing of the external temperature of the setpoint temperature and the indoor temperature moving beyond the setpoint temperature by a threshold temperature difference, for example, one degree. Other threshold temperature differences may be used.

**[0203]** Referring now additionally FIG. 36, operation of the climate control system **1020** is illustrated by way of the graph **1040** and corresponding displays **1036a-1036e** that show corresponding indoor temperatures **1043a-1043e** and setpoint temperatures **1044a-1044e** at different points in time identified on the graph. In the graph **1040**, the outside temperature is shown by the line **1041**, while the actual or indoor temperature is shown by the line **1042**. Illustratively, the indoor temperature or room temperature deviates from desired temperature or setpoint temperature momentarily while the external temperature passes through the deadbands **1045**.

**[0204]** A method aspect is directed to a method of operating the climate control system **1020**. The method includes sensing the indoor temperature of the indoor building area **1022** via the indoor temperature sensor **1032**. The method also includes using the HA thermostat device **1030** in the indoor building area **1022** to obtain a setpoint temperature for the indoor building area, obtain an external temperature from external to the indoor building area, determine a crossing of the external temperature of the setpoint temperature, and switch the HVAC system **1021** between operating modes based upon the crossing of the external temperature of the setpoint temperature and an indoor temperature of the indoor building area **1022** moving beyond the setpoint temperature by a threshold temperature difference.

**[0205]** Referring now to FIGS. 37a-37e, in another embodiment of an HA system **2020**, it may be desirable to remotely access the addressable HA devices **2031a-2031n**. Remote access of the addressable HA devices **2031a-2031n**, also known as IOT devices, may be particularly helpful for troubleshooting an issue with a given addressable HA device and/or updating software or a configuration, for example.

**[0206]** The addressable HA devices **2031a-2031n** are typically behind one or more a network address translation (NAT) routers and/or firewalls, and are thus not generally internet accessible, as will be appreciated by those skilled in the art. Accordingly, to access the addressable HA devices **2031a-2031n**, on-demand secure shell (SSH) tunneling may be used.

**[0207]** On-demand SSH tunneling allows a given one of the addressable HA devices **2031a-2031n** to communicate with, for example, through periodic connections, a known host to retrieve tunneling instructions. The tunneling instructions may thus permit remote access to a given addressable HA device with reduced overhead through the SSH protocol, for example. Of course, other protocols, for example, secure protocols, may be used.

**[0208]** To establish a remote connection to an addressable HA or IOT device **2031a-2031n** a request is issued for a given addressable HA device to open a tunnel. This may be performed using on-demand SSH tunneling by way of a remote user, for example, via remote access wireless communications device **2036**, creating a file in a web-visible (e.g. publically accessible) location that is specific to the given addressable HA device (FIG. 37a). The web-visible location may be on a server **2099** or other web-visible location, for example. In an example embodiment, the file may be an Amazon simple storage service (S3) file that is a hash of the given addressable HA device's unique identification and the last unique cloud session identification. The S3 file may include other and/or additional information about the addressable HA device **2031a-2031n**.

**[0209]** A cloud server **2033** may make available the device specific instructions for the given HA device **2031a-2031n** in a known location, for example, on the server **2099** (FIG. 37b). In some embodiments, the device specific instructions may be collocated on the cloud server **2033**.

**[0210]** Addressable HA devices **2031a-2031n** communicate with, for example, by periodically polling, this location. For example, the location may be polled every few minutes. Of course, the addressable HA devices **2031a-2031n** may communicate with or poll the location at longer, shorter, and/or different intervals. Based upon the polling, for example, the addressable HA device **2031a-2031n** finds the tunneling instructions stored and made available for the given addressable HA device (FIG. 37c). In one example, the instructions may be a json file that includes a cloud-visible host/port/username/password. Of course, the instructions may be embodied in a different type of file and/or other data elements may be stored in the instruction file.

**[0211]** The given addressable HA device **2031a-2031n** opens an SSH tunnel to the cloud server **2033** according to the instructions retrieved from the web-accessible location (FIG. 37d). The remote user via the remote access wireless communications device **2036**, may then connect to the cloud-end of the tunnel permitting communication with, for example, by way of logging into, the given addressable HA device **2031a-2031n** as though it were internet-visible (FIG. 37e).

**[0212]** Many modifications and other embodiments of the invention will come to the mind of one skilled in the art having the benefit of the teachings presented in the foregoing descriptions and the associated drawings. Therefore, it is understood that the invention is not to be limited to the specific embodiments disclosed, and that modifications and embodiments are intended to be included within the scope of the appended claims.

**That Which Is Claimed Is:**

1. A home automation (HA) system comprising:  
a plurality of addressable HA devices at a given location;  
an HA device scene controller configured to  
    obtain from a user a first desired scene comprising at least one first trigger action and at least one first responsive event,  
    present a first user-selectable list of corresponding ones of the addressable HA devices capable of implementing the first desired scene,  
    determine the first user-selected ones of the addressable HA devices,  
    upon occurrence of the at least one first trigger event, perform the at least one first responsive event using the first user-selected ones of the addressable HA devices to thereby implement the first desired scene,  
    obtain from the cloud a second desired scene comprising at least one second trigger action and at least one second responsive event,  
    present a second user-selectable list of corresponding ones of the addressable HA devices capable of implementing the second desired scene,  
    determine the second user-selected ones of the addressable HA devices, and  
    upon occurrence of the at least one second trigger event, perform the at least one second responsive event using the second user-selected ones of the addressable HA devices to thereby implement the second desired scene.
2. The HA system of Claim 1 wherein said HA device scene controller is configured to obtain the at least one first and second trigger actions without obtaining corresponding ones of said addressable HA devices for implementing the at least one first and second trigger actions.
3. The HA system of Claim 1 wherein said HA device scene controller is configured to obtain the at least one first and second responsive events

without obtaining corresponding ones of said addressable HA devices for implementing the at least one first and second responsive events.

4. The HA system of Claim 1 further comprising a user-interface device coupled to said HA device scene controller and comprising:  
a display;  
a user-input device; and  
a user-interface controller coupled to said display and user-input device and configured to  
display on said display the first and second user selectable lists,  
and  
permit, via said user-input device, user-selection of the first and second user-selected ones of the addressable devices.

5. The HA system of Claim 1 wherein said HA device scene controller is configured to generate a notification for the user upon occurrence of the at least one first or second trigger actions.

6. The HA system of Claim 1 wherein said HA device scene controller is configured to wirelessly obtain the at least one first and second trigger actions and the at least one first and second responsive events.

7. The HA system of Claim 1 wherein said HA device scene controller is configured to wirelessly implement the first and second desired scenes.

8. The HA system of Claim 1 wherein each of said plurality of addressable HA devices comprises one of a motion detector, thermostat, light switch, audio controller, door lock, and camera.

9. A home automation (HA) system comprising:  
a plurality of addressable HA devices at a given location;  
an HA device scene controller configured to  
obtain from a user a first desired scene comprising at least one first trigger action and at least one first responsive event,  
determine when the plurality of addressable HA devices at the given location are not capable of implementing the scene, and present a purchase offer for an additional addressable HA device,

determine when the plurality of addressable HA devices at the given location are capable of implementing the scene, and present a first user-selectable list of corresponding ones of the addressable HA devices capable of implementing the first desired scene,

determine the first user-selected ones of the addressable HA devices, and

upon occurrence of the at least one first trigger event, perform the at least one first responsive event using the first user-selected ones of the addressable HA devices to thereby implement the first desired scene.

10. The HA system of Claim 9 wherein said HA device scene controller is configured to obtain the at least one first trigger action without obtaining corresponding ones of said addressable HA devices for implementing the first trigger action.

11. The HA system of Claim 9 wherein said HA device scene controller is configured to obtain the at least one first responsive event without obtaining corresponding ones of said addressable HA devices for implementing the at least one first and event.

12. The HA system of Claim 9 further comprising a user-interface device coupled to said HA device scene controller and comprising:

a display;

a user-input device; and

a user-interface controller coupled to said display and user-input device and configured to

display on said display the purchase offer and the first user selectable list, and

permit, via said user-input device, user-selection of the first user-selected ones of the addressable devices.

13. The HA system of Claim 9 wherein said HA device scene controller is configured to generate a notification for the user upon occurrence of the at least one first trigger action.

14. The HA system of Claim 9 wherein said HA device scene controller is configured to wirelessly obtain the at least one first trigger action and the at least one first responsive event.

15. The HA system of Claim 9 wherein said HA device scene controller is configured to wirelessly implement the first and second desired scenes.

16. The HA system of Claim 9 wherein each of said plurality of addressable HA devices comprises one of a motion detector, thermostat, light switch, audio controller, door lock, and camera.

17. A method of implementing first and second desired scenes in a home automation (HA) system comprising a plurality of addressable HA devices at a given location, the method comprising:

using an HA device scene controller to

obtain from a user the first desired scene comprising at least one first trigger action and at least one first responsive event,

present a first user-selectable list of corresponding ones of the addressable HA devices capable of implementing the first desired scene,

determine the first user-selected ones of the addressable HA devices,

upon occurrence of the at least one first trigger event, perform the at least one first responsive event using the first user-selected ones of the addressable HA devices to thereby implement the first desired scene,

obtain from the cloud the second desired scene comprising at least one second trigger action and at least one second responsive event,

present a second user-selectable list of corresponding ones of the addressable HA devices capable of implementing the second desired scene,

determine the second user-selected ones of the addressable HA devices, and

upon occurrence of the at least one second trigger event, perform the at least one second responsive event using the second user-selected ones of the addressable HA devices to thereby implement the second desired scene.

18. The method of Claim 17 wherein the HA device scene controller obtains the at least one first and second trigger actions without obtaining corresponding ones of the addressable HA devices for implementing the at least one first and second trigger actions.

19. The method of Claim 17 wherein the HA device scene controller obtains the at least one first and second responsive events without obtaining corresponding ones of the addressable HA devices for implementing the at least one first and second responsive events.

20. The method of Claim 17 further comprising using a user-interface device coupled to the HA device scene controller to display on a display the first and second user selectable lists, and permit, via a user-input device, user-selection of the first and second user-selected ones of the addressable devices.

21. A method of implementing a first desired scene in a home automation (HA) system comprising a plurality of addressable HA devices at a given location, the method comprising:

using an HA device scene controller to

obtain from a user a first desired scene comprising at least one first trigger action and at least one first responsive event,

determine when the plurality of addressable HA devices at the given location are not capable of implementing the scene, and present a purchase offer for an additional addressable HA device,

determine when the plurality of addressable HA devices at the given location are capable of implementing the scene, and present a first user-selectable list of corresponding ones of the addressable HA devices capable of implementing the first desired scene,

determine the first user-selected ones of the addressable HA devices,

upon occurrence of the at least one first trigger event, perform the at least one first responsive event using the first user-selected ones of the addressable HA devices to thereby implement the first desired scene.

22. The method of Claim 21 wherein the HA device scene controller obtains the at least one first trigger action without obtaining corresponding ones of the addressable HA devices for implementing the at least one first trigger action.

23. The method of Claim 21 wherein the HA device scene controller obtains the at least one first responsive event without obtaining corresponding ones of the addressable HA devices for implementing the at least one first responsive event.

24. The method of Claim 21 further comprising using a user-interface device coupled to the HA device scene controller to display on a display the first user selectable list, and permit, via a user-input device, user-selection of the first user-selected ones of the addressable devices.




FIG. 1A




FIG. 1B

31




FIG. 2A




FIG. 2B




FIG. 3







FIG. 4

6/39

*FIG. 5**FIG. 6**FIG. 7*




FIG. 8A






FIG. 8B

9/39

**FIG. 9****FIG. 10****FIG. 11****FIG. 12**

10/39




FIG. 13A




FIG. 13B




FIG. 14A







FIG. 14B




*FIG. 15A*




*FIG. 15B*




*FIG. 15C*



**FIG. 16**




**FIG. 17**



**FIG. 18**

17/39

**FIG. 19**






FIG. 21A




FIG. 21B




FIG. 22







FIG. 23



**FIG. 24**




**FIG. 25**



USER CAN TYPE A SENTENCE AND  
BLOCKS WILL BE SUGGESTED

**FIG. 26**



**FIG. 27**




FIG. 28




FIG. 29A




FIG. 29B




FIG. 29B (cont.)




FIG. 30A





FIG. 30B



**FIG. 31**





FIG. 32






FIG. 34




FIG. 35




FIG. 36




FIG. 37A




FIG. 37B

38/39




FIG. 37C




FIG. 37D




FIG. 37E

**INTERNATIONAL SEARCH REPORT**

International application No  
PCT/US2016/040097

A. CLASSIFICATION OF SUBJECT MATTER  
INV. G05B15/00 H04L12/28  
ADD.  
According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED  
Minimum documentation searched (classification system followed by classification symbols)  
G05B H04L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)  
EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 8 490 006 B1 (REESER ANDREW [US] ET AL) 16 July 2013 (2013-07-16) abstract column 1, line 40 - column 2, line 8 column 2, line 58 - last line column 3, line 1 - column 5, line 13 column 6, line 1 - line 41; claims 1-18 figures 1-4	1-24
X	US 2015/160797 A1 (SHEARER WADE [US] ET AL) 11 June 2015 (2015-06-11) abstract paragraphs [0005] - [0009], [0037], [0042] - [0044], [0049] - [0051] paragraphs [0053] - [0056], [0060], [0063], [0064], [0071], [0078] claims 1-27 figures 1-18	1-24

Further documents are listed in the continuation of Box C.

See patent family annex.

\* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier application or patent but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- "&" document member of the same patent family

Date of the actual completion of the international search <b>14 September 2016</b>	Date of mailing of the international search report <b>22/09/2016</b>
---	---

Name and mailing address of the ISA/ European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Fax: (+31-70) 340-3016	Authorized officer <b>Lai, Cristiana</b>
--	---

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/US2016/040097

Patent document cited in search report	Publication date	Patent family member(s)	Publication date	
US 8490006	B1	16-07-2013	US 8490006 B1	16-07-2013
			US 8640038 B1	28-01-2014
-----				
US 2015160797	A1	11-06-2015	NONE	
-----				