



(22) Date de dépôt/Filing Date: 2015/08/28

(41) Mise à la disp. pub./Open to Public Insp.: 2016/03/12

(30) Priorité/Priority: 2014/09/12 (US14/484,887)

(51) Cl.Int./Int.Cl. *A61M 25/00* (2006.01),
A61B 17/02 (2006.01), *A61F 2/06* (2013.01),
A61F 2/95 (2013.01)


(71) Demandeur/Applicant:
FREUDENBERG MEDICAL, LLC, US

(72) Inventeurs/Inventors:
FURNISH, SIMON, US;
APPLING, ANTHONY, US

(74) Agent: DICKINSON WRIGHT LLP

(54) Titre : UNE GAINE DE DISPOSITIF D'INTRODUCTION EXTENSIBLE

(54) Title: AN EXPANDABLE INTRODUCER SHEATH



(57) Abrégé/Abstract:

An expandable introducer sheath for use in inserting a medical device into a body vessel of a patient includes a body which extends from a proximal end to a distal end along an axis. The body includes an inner layer, an outer layer, and an expandable reinforcement member which is disposed between said inner and outer layers. The expandable reinforcement member is configured to radially expand as the medical device is axially advanced or retracted through said introducer sheath. Once the medical device has exited the introducer sheath, the expandable reinforcement member facilitates a return of the introducer sheath to its original or unexpanded condition.

AN EXPANDABLE INTRODUCER SHEATH

ABSTRACT OF THE DISCLOSURE

An expandable introducer sheath for use in inserting a medical device into a body vessel of a patient includes a body which extends from a proximal end to a distal end along an axis. The body includes an inner layer, an outer layer, and an expandable reinforcement member which is disposed between said inner and outer layers. The expandable reinforcement member is configured to radially expand as the medical device is axially advanced or retracted through said introducer sheath. Once the medical device has exited the introducer sheath, the expandable reinforcement member facilitates a return of the introducer sheath to its original or unexpanded condition.

AN EXPANDABLE INTRODUCER SHEATH

BACKGROUND OF THE INVENTION

1. Field of the Invention

[0001] The present disclosure relates generally to medical devices and procedures. In particular, the present disclosure relates to expandable medical devices, such as introducer sheaths, for use during medical procedures.

2. Description of the Prior Art

[0002] This section provides background information related to the present disclosure which is not necessarily prior art.

[0003] Numerous procedures have been developed that involve the percutaneous insertion of a medical device into the body of a patient, with the medical device being introduced into the body by a variety of known techniques. For example, access to coronary arteries, carotid arteries, the aorta, and peripheral vessels or other tubular members of the body for percutaneous therapeutic, diagnostic, and guide catheters is often made through introducer sheaths which are positioned into body vessels from outside the bodies. Such access sites include, but are not limited to, the common femoral artery/vein and the radial arteries, as well as the ureter, urethra, intestinal track, veins and other tubular tissues. However, the use of introducer sheaths and/or medical devices which are large relative to the body vessels to which they are inserted poses risks and challenges to both the patient and the physician.

[0004] For example, relative to femoral sheaths and catheters, larger introducer sheaths create sizeable arteriotomies in the femoral artery which cause more trauma to the patient, such as through artery avulsion, and create more challenges in placement of the sheath with risk of dissection. In addition, the forces required by the physician to insert the larger

introducer sheaths and/or medical devices into the body vessel can be higher than desired and create medical issues for the patient if calcification within the body vessel is dislodged during insertion of the introducer sheath and/or medical device.

[0005] Methods of accessing a body vessel with a larger introducer sheath and/or medical device can begin by dilating the vessel with a radially expanding intravascular sheath assembly prior to introducing the medical device. However, such radially expanding sheaths have complex mechanisms, such as ratcheting or balloon mechanisms, that expand and maintain the sheath in an expanded configuration while a medical device with a large diameter is introduced. Further, since the mechanisms effectuate the expansion of the body vessel, they do not provide a user with tactile feedback, and can even pose a risk of dissection during the procedure. Accessing the body vessel remains a challenge with existing expandable sheath assemblies due to the relatively large profile of the medical device inserted which causes longitudinal and radial tearing of the vessel during insertion. As mentioned above, these prior art delivery systems can even dislodge calcified plaque within the vessels during insertion, posing an additional risk of clots caused by the dislodged plaque.

[0006] Accordingly, there remains a need in the art for an improved expandable introducer sheath for use with the percutaneous insertion of a medical device into a body vessel of a patient.

SUMMARY OF THE DISCLOSURE

[0007] This section provides a general summary of the disclosure and is not intended to be a comprehensive disclosure of its full scope, aspects, objectives, and/or all of its features.

[0008] An expandable introducer sheath for use in inserting a medical device into a body vessel of a patient includes a body extending from a proximal end to a distal end along an axis. The expandable introducer sheath includes an inner layer, an outer layer, and an expandable reinforcement member disposed between the inner and outer layers. The expandable reinforcement member is configured to allow for temporary radial expansion of the introducer sheath as a medical device is axially advanced or retracted through the introducer sheath. Once the medical device has exited the introducer sheath, the expandable reinforcement member retracts to its original or static diameter.

[0009] When the introducer sheath is disposed within the body vessel, the radially expansion of the expandable reinforcement member effectuates a lifting, and thus an expansion, of the body vessel. As a result, the expandable reinforcement member allows a medical device which has a larger diameter to be axially advanced through the introducer sheath and into the body vessel. The lifting of the body vessel by way of the expandable reinforcement member avoids the need to push the larger medical device past any calcification that is present within the body vessel, and thus reduces trauma to the body vessel. The radially expandable reinforcement member also provides tactile feedback to a user while serially advancing the medical device through the introducer sheath and into the body vessel.

[0010] Further areas of applicability will become apparent from the description provided herein. The description and specific examples in this summary are intended for purposes of illustration only and are not intended to limit the scope of the present disclosure.

BRIEF DESCRIPTION OF THE DRAWINGS

[0011] The drawings described herein are for illustrative purposes only of selected embodiments, and are not all possible implementations and thus are not intended to limit the scope of the present disclosure.

[0012] Figure 1 is a perspective view of an expandable introducer sheath connected to a hemostatic valve assembly and illustrating an outer layer of the expandable introducer sheath;

[0013] Figure 2 is a perspective view of the expandable introducer sheath illustrating a protective sheath disposed in overlaying and surrounding relationship with the outer layer;

[0014] Figure 3 is a perspective view of the expandable introducer sheath illustrating a longitudinal slit extending along a portion of an outer layer of the introducer sheath;

[0015] Figure 4 is an end view of the expandable introducer sheath illustrating a fold in an inner liner of the introducer sheath;

[0016] Figure 5 is a top view of the expandable introducer sheath illustrating the longitudinal slit in a radially expanded condition;

[0017] Figure 6 is a top view of the expandable introducer sheath illustrating the longitudinal slit in a radially expanded condition;

[0018] Figure 7A is a perspective view of the introducer sheath illustrating a first embodiment of an expandable reinforcement member;

[0019] Figure 7B is a perspective view of the first embodiment of the expandable reinforcement member in a contracted condition;

[0020] Figure 7C is a perspective view of the first embodiment of the expandable reinforcement member in an expanded condition;

[0021] Figure 8A is a perspective view illustrating a second embodiment of the expandable reinforcement member;

[0022] Figure 8B is a top view of the second embodiment of the expandable reinforcement member;

[0023] Figure 9 is a perspective view of a third embodiment of the expandable reinforcement member; and

[0024] Figure 10 is a magnified view of a portion of the third embodiment of the expandable reinforcement member;

DESCRIPTION OF THE ENABLING EMBODIMENTS

[0025] Example embodiments will now be described more fully with reference to the accompanying drawings. The example embodiments are provided so that this disclosure will be thorough and fully convey the scope to those skilled in the art. Numerous specific details are set forth such as examples of specific components, devices, mechanisms, assemblies, and methods to provide a thorough understanding of various embodiments of the present disclosure. It will be apparent to those skilled in the art that specific details need not be employed, that example embodiments may be embodied in many different forms, and that neither should be construed to limit the scope of the disclosure. With this in mind, the present disclosure is generally directed to expandable introducer sheaths of the type used to introduce and withdrawal a medical device (i.e., catheter systems, implants, etc.) into a body vessel of a patient.

[0026] Referring to the Figures, wherein like numerals indicate corresponding parts throughout the several views, an expandable introducer sheath **10** for use in inserting a medical device **12** into a body vessel of a patient includes a body **14** extending from a proximal end **16** to a distal end **18** along an axis **A**. As best shown in Figure 1, in a preferred embodiment, the expandable introducer sheath **10** is secured to a hemostatic valve assembly **20** about the proximal end **16** to dispose the introducer sheath **10** in surrounding and sealed relationship with a passageway of the hemostatic valve assembly **20**. Such an arrangement allows the medical device **12** to serially advance along the axis **A** in sealed relationship from the hemostatic valve assembly **20** to the introducer sheath **10**. In a preferred embodiment, the hemostatic valve assembly **20** can be a variable diameter seal hemostatic valve as described in co-owned U.S. Patent Application Serial No. 14/326,593 entitled "A Medical Valve with a Variable Diameter Seal", the entire disclosure of which is incorporated by reference. However, other valves, such as iris valves, laparoscopic ports, slit valves, or the like, can also be utilized without departing from the scope of the subject disclosure.

[0027] As best shown in Figure 7A, the expandable introducer sheath **10** includes an inner layer **22**, an outer layer **24**, and an expandable reinforcement member **26** disposed between and surrounded by the inner and outer layers **22**, **24**. The expandable reinforcement member **26** is comprised of a shape memory material and is configured to allow for temporary radial expansion relative to the axis **A** of the introducer sheath **10** from an original or static diameter to an expanded diameter as a medical device **12** is axially advanced or retracted through the introducer sheath **10**. Once the medical device **12** has exited the introducer sheath **10**, the shape memory material of the expandable reinforcement member **26** facilitates a return of the introducer sheath **10** to its original or static diameter. In a preferred arrangement, the shape

memory material is a metal alloy such as Nitinol, stainless steel, or the like. However, the shape memory material could also comprise a rigid thermoplastic material conducive to the above-described function without departing from the scope of the subject disclosure.

[0028] The expanding or contracting of the expandable reinforcement member **26** effectuates a corresponding radial expansion or contraction of the outer layer **24**. When the introducer sheath **10** is disposed within the body vessel, the radial expansion of the outer layer **24** effectuates a lifting, and thus an expansion, of the body vessel to allow a larger medical device **12** to be advanced into the body vessel. The lifting of the body vessel by way of the outer layer **24** of the introducer sheath **10** avoids the need to push the larger medical device **12** past any calcification that is present within the body vessel, and thus reduces trauma to the body vessel. The radial expansion of the outer layer **24** by way of the expandable reinforcement member **26** also provides tactile feedback to a user during serial advancement of the medical device **12** through the introducer sheath **10** and into the body vessel.

[0029] As best shown in Figures 1 and 3, in a preferred arrangement, the body **14** of the expandable introducer sheath **10** includes an enlarged portion **28** disposed adjacent the proximal end **16**. The enlarged portion **28** has a first diameter that is sized complementarily to the medical device **12** that will be serially advanced along the axis **A** through the hemostatic valve assembly **20**, the introducer sheath **10** and the body vessel. In this arrangement, the body **14** of the expandable introducer sheath **10** also includes a tapered portion **30** which extends from the distal end **18** to the enlarged portion **28**. The tapered portion **30** has a second diameter smaller than the first diameter for providing a smaller profile of the introducer sheath **10** that facilitates an initial insertion of the introducer sheath **10** into the body vessel. Put another way, the tapered portion **30** of the body **14** accommodates an initial insertion of the introducer sheath **10** into the

body vessel. By way of the enlarged and tapered portions **28, 30**, the body of the introducer sheath **10** can have an original or static outer diameter which decreases or is tapered from the proximal end **16** to the distal end **18**. However, it should be appreciated that the body **14** of the introducer sheath **10** can also be designed without the enlarged and tapered portions **28, 30** and thus have an original or static outer diameter which is substantially constant between the proximal and distal ends **16, 18**.

[0030] As best shown in Figure 4, the body **12** of the expandable introducer sheath **10** includes an inner layer **22** which is disposed radially inward of the expandable reinforcement member **26** and which extends between the proximal and distal ends **16, 18**. The inner layer **22** is comprised of a lubricious, low friction polymeric material for easing axially movement of the medical device **12** through the expandable introducer sheath **10**, and thus easing insertion of the medical device **12** into the body vessel of the patient. By way of example, the inner layer **22** can comprise polytetrafluoroethylene (PTFE), polyimide, polyetheretherketone (PEEK), polyurethane, nylon, polyethylene, polyamide, or the like. However, in a preferred embodiment, the low friction polymeric material of the inner layer is comprised of expandable polytetrafluoroethylene (ePTFE).

[0031] As best shown in Figures 1 and 3, the body **12** of the expandable sheath assembly **10** also includes an outer layer **24** which is disposed radially outward of the expandable reinforcement member **26** and which overlays or surrounds the expandable reinforcement member **26** between the proximal and distal ends **18**. In a preferred embodiment, the outer layer is comprised of a thermoplastic material, such as Pevax[®] (i.e., polyether block amide) or the like. However, an elastomeric material, such as PTFE, polyimide, PEEK, polyurethane, nylon, polyethylene, polyamide, polyether block amides, polyether block ester copolymer, polyesters,

fluoropolymers, polyvinyl chloride, thermoset silicone, latex, poly-isoprene rubbers, polyolefin, or other medical grade polymers, or combinations thereof, can also be utilized without departing from the scope of the subject disclosure.

[0032] As best shown in Figure 2, a protective sheath **32** can be disposed in overlaying and surrounding relationship with the outer layer **24** to provide a protective layer or barrier for the introducer sheath **10** when disposed within the body vessel. In a preferred embodiment, the protective sheath **32** is comprised of ePTFE to allow the protective sheath **32** to radially expand in conjunction with the outer layer **24** and the expandable reinforcement member **26** during axial movement of the medical device **12** through the introducer sheath **10**. The ePTFE protective sheath **32** also adds lubricity and provides a low friction barrier for the introducer sheath that eases its insertion into the body vessel.

[0033] As best shown in Figures 3-6, in an embodiment, the outer layer **24** can be provided with at least cut or slit **34** which extends longitudinally and is disposed between the proximal and distal ends **16, 18** to facilitate radial expansion of the outer layer **24** relative to the axis **A** during axial movement of the medical device through the introducer sheath **10**. For example, the outer layer **24** can be provided with a longitudinal cut or slit **34** which extends from the distal end **18** along a portion of the outer layer **24** and which is preferably aligned with an expansion area of the expandable reinforcement member **26**. When a protective sheath **32** is disposed in overlaying relationship with the outer layer **24**, the protective sheath **32** functions to cover the at least one cut or slit **34**. As best shown in Figure 4, in a preferred embodiment, the inner liner **22** can correspondingly include a fold **36** in an area which aligns with an expansion area of the expandable reinforcement member **26** as well as the at least one cut or slit **34** disposed in the outer layer **24**. The fold **36** of the inner liner **22** facilitates radial expansion as

a medical device **12** is axially advanced through the introducer sheath **10**, and also allows for a reduced inner diameter of the inner layer **22**.

[0034] As best shown in Figures 7A-7C, in a first embodiment, the expandable reinforcement member **26** includes a spine **38** which extends between the proximal and distal ends **16**, **18** and a plurality of ribs **40** which extend radially from the spine **38** and circumferentially about the axis **A**. In accordance with the above mentioned disclosure, the ribs **40** are radially expandable from a contracted position, shown in Figure 7B, to an expanded position, shown in Figure 7C, as the medical device **12** is introduced into the introducer sheath **10**. As mentioned above, the expandable reinforcement member **26** is comprised of stainless steel, Nitinol, or the like and thus the ribs **40** are configured to return or spring back to the contracted position when the medical device **12** exits the introducer sheath **10**. The spine **38** and ribs **40** of the expandable reinforcement member **26** are preferably fabricated by either laser cutting a tube or photoetching and rolling a flat pattern.

[0035] As best shown in Figures 8A and 8B, in a second embodiment, the expandable reinforcement member **26** includes a single wire **42** which extends continuously between the proximal and distal ends **16**, **18**. The continuous, single wire **42** is wrapped or threaded to define a series of loops **44**, with each of the loops **44** extending circumferentially about the axis **A** and interleaved between adjacent loops **44**. In a preferred arrangement, adjacent loops **44** extend in opposite radially circumferential directions relative to one another to allow the adjacent loops **44** to slide relative to one another and effectuate an expansion of the reinforcement member **26** as the medical device **12** is introduced into the introducer sheath **10**.

[0036] As best shown in Figures 9 and 10, in a third embodiment, the expandable reinforcement member **26** includes a plurality of struts **46** disposed in spaced relationship to

one another and each extending longitudinally between the proximal and distal ends **16, 18** in spaced and parallel relationship to the axis **A**. The expandable reinforcement member **26** also includes a plurality of linkages **48** each extending radially between adjacent struts **46**, with each linkage **48** disposed in interleaved relationship with adjacent struts **46**. As best shown in Figure 9, each of the linkages **46** are radially expandable from their contracted or static position as a medical device **12** is introduced into the introducer sheath **10**, and are configured to return or spring back to the contracted position when the medical device **12** exits the introducer sheath **10**. In a preferred arrangement, the struts **346** and linkages **48** of the expandable reinforcement member **26** are preferably fabricated by laser cutting a tube.

[0037] The foregoing description of the embodiments has been provided for purposes of illustration and description. It is not intended to be exhaustive or to limit the disclosure. Individual elements or features of a particular embodiment are generally not limited to that particular embodiment, but, where applicable, are interchangeable and can be used in a selected embodiment, even if not specifically shown or described. The same may also be varied in many ways. Such variations are not to be regarded as a departure from the disclosure, and all such modifications are intended to be included within the scope of the disclosure.

CLAIMS

What is claimed is:

1. An expandable introducer sheath for use in inserting a medical device into a body vessel of a patient comprising:
 - a body extending from a proximal end to a distal end along an axis **A**;
 - said body including an inner layer, an outer layer, and an expandable reinforcement member disposed between said inner and outer layers; and
 - said expandable reinforcement member configured to radially expand as the medical device is axially advanced or retracted through the introducer sheath.
2. An expandable introducer sheath as set forth in claim 1, wherein said expandable reinforcement member includes a spine extending between said proximal and distal ends and a plurality of ribs extending radially from said spine and circumferentially about said axis **A**.
3. An expandable introducer sheath as set forth in claim 1, wherein said expandable reinforcement member includes a single wire which extends continuously between said proximal and distal ends.
4. An expandable introducer sheath as set forth in claim 3, wherein said single wire is wrapped to define a series of loops, with each of said loops in said series of loops extending circumferentially about said axis **A** and being interleaved between adjacent loops of said series of loops.
5. An expandable introducer sheath as set forth in claim 4, wherein said adjacent loops of said series of loops extend in opposite radial circumferential directions relative to one another for allowing said adjacent loops to slide relative to one another and effectuate radial

expansion of said reinforcement member as the medical device is introduced into said introducer sheath.

6. An expandable introducer sheath as set forth in claim 1, wherein said expandable reinforcement member includes a plurality of struts disposed in spaced relationship to one another and each extending longitudinally between said proximal and distal ends and a plurality of linkages each extending radially between adjacent spines.

7. An expandable introducer sheath as set forth in claim 6, wherein said each of the linkages are radially expandable from their contracted or static position as a medical device is introduced into the introducer sheath, and are configured to return or spring back to the contracted position when the medical device exits the introducer sheath.

8. An expandable introducer sheath as set forth in claim 6, wherein said expandable reinforcement member is fabricated by laser cutting a tube.

9. An expandable introducer sheath as set forth in claim 1, wherein said expandable reinforcement member is comprised of a shape memory material to facilitate a return of said expandable reinforcement member to its unexpanded condition following an exit of the medical device from said introducer sheath.

10. An expandable introducer sheath as set forth in claim 9, wherein said expandable reinforcement member is comprised of Nitinol or stainless steel.

11. An expandable introducer sheath as set forth in claim 9, wherein said expandable reinforcement member is comprised of a rigid thermoplastic material.

12. An expandable introducer sheath as set forth in claim 1, wherein said inner layer is comprised of a lubricous, low friction polymeric material.

13. An expandable introducer sheath as set forth in claim 12, wherein said inner layer is comprised of expandable polytetrafluoroethylene (ePTFE).
14. An expandable introducer sheath as set forth in claim 1, wherein said outer layer is comprised of a thermoplastic material.
15. An expandable introducer sheath as set forth in claim 1, further comprising a protective sheath disposed in overlaying and surrounding relationship with said outer layer.
16. An expandable introducer sheath as set forth in claim 14, wherein said protective sheath is comprised of expandable polytetrafluoroethylene (ePTFE).
17. An expandable introducer sheath as set forth in claim 1, wherein said outer layer includes at least one slit which extends longitudinally and is disposed between said proximal and distal ends.
18. An expandable introducer sheath as set forth in claim 17, wherein said inner layer includes a fold disposed in aligned relationship with said at least one slit of said outer layer.
19. An expandable introducer sheath as set forth in claim 1, wherein said body includes an enlarged portion disposed adjacent said proximal end, said enlarged portion having a first diameter being complementary to the medical device.
20. An expandable introducer sheath as set forth in claim 19, wherein said body includes a tapered portion extending from said distal end to said enlarged portion, said tapered portion having a second diameter being smaller than said first diameter of said enlarged portion for providing a smaller profile of said introducer sheath to facilitate an initial insertion into the body vessel.




FIG. 1




FIG. 2




FIG. 3




FIG. 4

FIG. 5










FIG. 6



4/6








FIG. 9




FIG. 10

