



Office de la Propriété

Intellectuelle  
du Canada

Un organisme  
d'Industrie Canada

Canadian  
Intellectual Property  
Office

An agency of  
Industry Canada

CA 2406850 A1 2001/10/11

(21) 2 406 850


(12) DEMANDE DE BREVET CANADIEN  
CANADIAN PATENT APPLICATION

(13) A1

(86) Date de dépôt PCT/PCT Filing Date: 2001/04/03  
(87) Date publication PCT/PCT Publication Date: 2001/10/11  
(85) Entrée phase nationale/National Entry: 2002/10/01  
(86) N° demande PCT/PCT Application No.: US 2001/010907  
(87) N° publication PCT/PCT Publication No.: 2001/074235  
(30) Priorités/Priorities: 2000/04/03 (60/194,140) US;  
2001/02/20 (09/790,204) US

(51) Cl.Int.<sup>7</sup>/Int.Cl.<sup>7</sup> A61B 1/005  
(71) Demandeur/Applicant:  
NEOGUIDE SYSTEMS, INC., US  
(72) Inventeur/Inventor:  
BELSON, AMIR, US  
(74) Agent: BORDEN LADNER GERVAIS LLP

(54) Titre : ENDOSCOPE ORIENTABLE ET METHODE AMELIOREE D'INSERTION  
(54) Title: STEERABLE ENDOSCOPE AND IMPROVED METHOD OF INSERTION



(57) Abrégé/Abstract:

A steerable endoscope has an elongated body (102) with a selectively steerable distal portion (104) and an automatically controlled proximal portion (106). The endoscope body is inserted into a patient and the selectively steerable distal portion is used to select a desired path within the patient's body. When the endoscope body is advanced, an electronic motion controller (140) operates the automatically controlled proximal portion to assume the selected curve of the selectively steerable distal portion. Another desired path is selected with the selectively steerable distal portion and the endoscope body is advanced

**(57) Abrégé(suite)/Abstract(continued):**

again. As the endoscope body is further advanced, the selected curves propagate proximally along the endoscope body, and when the endoscope body is withdrawn proximally, the selected curves propagate distally along the endoscope body. This creates a serpentine motion in the endoscope body that allows it to negotiate tortuous curves along a desired path through or around and between organs within the body.

## (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau(43) International Publication Date  
11 October 2001 (11.10.2001)

PCT

(10) International Publication Number  
WO 01/74235 A1(51) International Patent Classification<sup>7</sup>:

A61B 1/005

(74) Agents: LEARY, James, J. et al.; Leary &amp; Associates, Suite 330, 505 W. Olive Avenue, Sunnyvale, CA 94086 (US).

(21) International Application Number: PCT/US01/10907

(22) International Filing Date: 3 April 2001 (03.04.2001)

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

60/194,140

3 April 2000 (03.04.2000)

US

09/790,204

20 February 2001 (20.02.2001)

US


(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant and

(72) Inventor: BELSON, Amir [IL/US]; Apt. C, 20050 Rodriguez Ave., Cupertino, CA 95014 (US).

[Continued on next page]

(54) Title: STEERABLE ENDOSCOPE AND IMPROVED METHOD OF INSERTION



**(57) Abstract:** A steerable endoscope has an elongated body (102) with a selectively steerable distal portion (104) and an automatically controlled proximal portion (106). The endoscope body is inserted into a patient and the selectively steerable distal portion is used to select a desired path within the patient's body. When the endoscope body is advanced, an electronic motion controller (140) operates the automatically controlled proximal portion to assume the selected curve of the selectively steerable distal portion. Another desired path is selected with the selectively steerable distal portion and the endoscope body is advanced again. As the endoscope body is further advanced, the selected curves propagate proximally along the endoscope body, and when the endoscope body is withdrawn proximally, the selected curves propagate distally along the endoscope body. This creates a serpentine motion in the endoscope body that allows it to negotiate tortuous curves along a desired path through or around and between organs within the body.

WO 01/74235 A1

**WO 01/74235 A1**



**Published:**

- *with international search report*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

## STEERABLE ENDOSCOPE AND IMPROVED METHOD OF INSERTION

### FIELD OF THE INVENTION

5 The present invention relates generally to endoscopes and endoscopic medical procedures. More particularly, it relates to a method and apparatus to facilitate insertion of a flexible endoscope along a tortuous path, such as for colonoscopic examination and treatment.

### BACKGROUND OF THE INVENTION

10 An endoscope is a medical instrument for visualizing the interior of a patient's body. Endoscopes can be used for a variety of different diagnostic and interventional procedures, including colonoscopy, bronchoscopy, thoracoscopy, laparoscopy and video endoscopy.

Colonoscopy is a medical procedure in which a flexible endoscope, or colonoscope, is inserted into a patient's colon for diagnostic examination and/or surgical treatment of the colon.

15 A standard colonoscope is typically 135-185 cm in length and 12-13 mm in diameter, and includes a fiberoptic imaging bundle, illumination fibers and one or two instrument channels that may also be used for insufflation or irrigation. The colonoscope is inserted via the patient's anus and is advanced through the colon, allowing direct visual examination of the colon, the ileocecal valve and portions of the terminal ileum. Insertion of the colonoscope is complicated by the fact  
20 that the colon represents a tortuous and convoluted path. Considerable manipulation of the colonoscope is often necessary to advance the colonoscope through the colon, making the procedure more difficult and time consuming and adding to the potential for complications, such as intestinal perforation. Steerable colonoscopes have been devised to facilitate selection of the correct path through the curves of the colon. However, as the colonoscope is inserted farther and  
25 farther into the colon, it becomes more difficult to advance the colonoscope along the selected path. At each turn, the wall of the colon must maintain the curve in the colonoscope. The colonoscope rubs against the mucosal surface of the colon along the outside of each turn. Friction and slack in the colonoscope build up at each turn, making it more and more difficult to advance and withdraw the colonoscope. In addition, the force against the wall of the colon increases with  
30 the buildup of friction. In cases of extreme tortuosity, it may become impossible to advance the colonoscope all of the way through the colon.

Steerable endoscopes, catheters and insertion devices for medical examination or treatment of internal body structures are described in the following U.S. patents: 4,753,223; 5,337,732; 5,662,587; 4,543,090; 5,383,852; 5,487,757 and 5,337,733.

## SUMMARY OF THE INVENTION

In keeping with the foregoing discussion, the present invention takes the form of a steerable endoscope for negotiating tortuous paths through a patient's body. The steerable endoscope can be used for a variety of different diagnostic and interventional procedures, including colonoscopy, bronchoscopy, thoracoscopy, laparoscopy and video endoscopy. The steerable endoscope is particularly well suited for negotiating the tortuous curves encountered when performing a colonoscopy procedure.

The steerable endoscope has an elongated body with a manually or selectively steerable distal portion and an automatically controlled proximal portion. The selectively steerable distal portion can be selectively steered or bent up to a full 180 degree bend in any direction. A fiberoptic imaging bundle and one or more illumination fibers extend through the body from the proximal end to the distal end. Alternatively, the endoscope can be configured as a video endoscope with a miniaturized video camera, such as a CCD camera, which transmits images to a video monitor by a transmission cable or by wireless transmission. Optionally, the endoscope may include one or two instrument channels that may also be used for insufflation or irrigation.

A proximal handle attached to the elongate body includes an ocular for direct viewing and/or for connection to a video camera, a connection to an illumination source and one or more luer lock fittings that are connected to the instrument channels. The handle is connected to a steering control for selectively steering or bending the selectively steerable distal portion in the desired direction and to an electronic motion controller for controlling the automatically controlled proximal portion of the endoscope. An axial motion transducer is provided to measure the axial motion of the endoscope body as it is advanced and withdrawn. Optionally, the endoscope may include a motor or linear actuator for automatically advancing and withdrawing the endoscope.

The method of the present invention involves inserting the distal end of the endoscope body into a patient, either through a natural orifice or through an incision, and steering the selectively steerable distal portion to select a desired path. When the endoscope body is advanced, the electronic motion controller operates the automatically controlled proximal portion of the body to assume the selected curve of the selectively steerable distal portion. This process is repeated by selecting another desired path with the selectively steerable distal portion and advancing the endoscope body again. As the endoscope body is further advanced, the selected curves propagate proximally along the endoscope body. Similarly, when the endoscope body is withdrawn proximally, the selected curves propagate distally along the endoscope body. This

creates a sort of serpentine motion in the endoscope body that allows it to negotiate tortuous curves along a desired path through or around and between organs within the body.

The method can be used for performing colonoscopy or other endoscopic procedures, such as bronchoscopy, thoracoscopy, laparoscopy and video endoscopy. In addition, the 5 apparatus and methods of the present invention can be used for inserting other types of instruments, such as surgical instruments, catheters or introducers, along a desired path within the body.

### **BRIEF DESCRIPTION OF THE DRAWINGS**

10 FIG 1 shows a prior art colonoscope being employed for a colonoscopic examination of a patient's colon.

FIG 2 shows a first embodiment of the steerable endoscope of the present invention.

FIG 3 shows a second embodiment of the steerable endoscope of the present invention.

FIG 4 shows a third embodiment of the steerable endoscope of the present invention.

15 FIG 5 shows a fourth embodiment of the steerable endoscope of the present invention.

FIG 6 shows a wire frame model of a section of the body of the endoscope in a neutral or straight position.

FIG 7 shows the wire frame model of the endoscope body shown in FIG 6 passing through a curve in a patient's colon.

20 FIGS 8-13 show the endoscope of the present invention being employed for a colonoscopic examination of a patient's colon.

### **DETAILED DESCRIPTION OF THE INVENTION**

FIG 1 shows a prior art colonoscope 500 being employed for a colonoscopic examination 25 of a patient's colon C. The colonoscope 500 has a proximal handle 506 and an elongate body 502 with a steerable distal portion 504. The body 502 of the colonoscope 500 has been lubricated and inserted into the colon C via the patient's anus A. Utilizing the steerable distal portion 504 for guidance, the body 502 of the colonoscope 500 has been maneuvered through several turns in the patient's colon C to the ascending colon G. Typically, this involves a considerable amount of 30 manipulation by pushing, pulling and rotating the colonoscope 500 from the proximal end to advance it through the turns of the colon C. After the steerable distal portion 504 has passed, the wall of the colon C maintains the curve in the flexible body 502 of the colonoscope 500 as it is advanced. Friction develops along the body 502 of the colonoscope 500 as it is inserted, particularly at each turn in the colon C. Because of the friction, when the user attempts to

advance the colonoscope 500, the body 502' tends to move outward at each curve, pushing against the wall of the colon C, which exacerbates the problem by increasing the friction and making it more difficult to advance the colonoscope 500. On the other hand, when the colonoscope 500 is withdrawn, the body 502'' tends to move inward at each curve taking up the slack that developed when the colonoscope 500 was advanced. When the patient's colon C is extremely tortuous, the distal end of the body 502 becomes unresponsive to the user's manipulations, and eventually it may become impossible to advance the colonoscope 500 any farther. In addition to the difficulty that it presents to the user, tortuosity of the patient's colon also increases the risk of complications, such as intestinal perforation.

10

FIG 2 shows a first embodiment of the steerable endoscope 100 of the present invention. The endoscope 100 has an elongate body 102 with a manually or selectively steerable distal portion 104 and an automatically controlled proximal portion 106. The selectively steerable distal portion 104 can be selectively steered or bent up to a full 180 degree bend in any direction. A 15 fiberoptic imaging bundle 112 and one or more illumination fibers 114 extend through the body 102 from the proximal end 110 to the distal end 108. Alternatively, the endoscope 100 can be configured as a video endoscope with a miniaturized video camera, such as a CCD camera, positioned at the distal end 108 of the endoscope body 102. The images from the video camera can be transmitted to a video monitor by a transmission cable or by wireless transmission.

20 Optionally, the body 102 of the endoscope 100 may include one or two instrument channels 116, 118 that may also be used for insufflation or irrigation. The body 102 of the endoscope 100 is highly flexible so that it is able to bend around small diameter curves without buckling or kinking. When configured for use as a colonoscope, the body 102 of the endoscope 100 is typically from 135 to 185 cm in length and approximately 12-13 mm in diameter. The endoscope 25 100 can be made in a variety of other sizes and configurations for other medical and industrial applications.

A proximal handle 120 is attached to the proximal end 110 of the elongate body 102. The handle 120 includes an ocular 124 connected to the fiberoptic imaging bundle 112 for direct viewing and/or for connection to a video camera 126. The handle 120 is connected to an 30 illumination source 128 by an illumination cable 134 that is connected to or continuous with the illumination fibers 114. A first luer lock fitting 130 and a second luer lock fitting 132 on the handle 120 are connected to the instrument channels 116, 118.

The handle 120 is connected to an electronic motion controller 140 by way of a controller cable 136. A steering control 122 is connected to the electronic motion controller 140 by way of

a second cable 138. The steering control 122 allows the user to selectively steer or bend the selectively steerable distal portion 104 of the body 102 in the desired direction. The steering control 122 may be a joystick controller as shown, or other known steering control mechanism. The electronic motion controller 140 controls the motion of the automatically controlled proximal portion 106 of the body 102. The electronic motion controller 140 may be implemented using a motion control program running on a microcomputer or using an application-specific motion controller. Alternatively, the electronic motion controller 140 may be implemented using a neural network controller.

An axial motion transducer 150 is provided to measure the axial motion of the endoscope body 102 as it is advanced and withdrawn. The axial motion transducer 150 can be made in many possible configurations. By way of example, the axial motion transducer 150 in FIG 2 is configured as a ring 152 that surrounds the body 102 of the endoscope 100. The axial motion transducer 150 is attached to a fixed point of reference, such as the surgical table or the insertion point for the endoscope 100 on the patient's body. As the body 102 of the endoscope 100 slides through the axial motion transducer 150, it produces a signal indicative of the axial position of the endoscope body 102 with respect to the fixed point of reference and sends a signal to the electronic motion controller 140 by telemetry or by a cable (not shown). The axial motion transducer 150 may use optical, electronic or mechanical means to measure the axial position of the endoscope body 102. Other possible configurations for the axial motion transducer 150 are described below.

FIG 3 shows a second embodiment of the endoscope 100 of the present invention. As in the embodiment of FIG 2, the endoscope 100 has an elongate body 102 with a selectively steerable distal portion 104 and an automatically controlled proximal portion 106. The steering control 122 is integrated into proximal handle 120 in the form of one or two dials for selectively steering the selectively steerable distal portion 104 of the endoscope 100. Optionally, the electronic motion controller 140 may be miniaturized and integrated into proximal handle 120, as well. In this embodiment, the axial motion transducer 150 is configured with a base 154 that is attachable to a fixed point of reference, such as the surgical table. A first roller 156 and a second roller 158 contact the exterior of the endoscope body 102. A multi-turn potentiometer 160 or other motion transducer is connected to the first roller 156 to measure the axial motion of the endoscope body 102 and to produce a signal indicative of the axial position.

The endoscope 100 may be manually advanced or withdrawn by the user by grasping the body 102 distal to the axial motion transducer 150. Alternatively, the first roller 156 and/or

second roller 158 may be connected to a motor 162 for automatically advancing and withdrawing the body 102 of the endoscope 100.

FIG 4 shows a third embodiment of the endoscope 100 of the present invention, which 5 utilizes an elongated housing 170 to organize and contain the endoscope 100. The housing 170 has a base 172 with a linear track 174 to guide the body 102 of the endoscope 100. The housing 170 may have an axial motion transducer 150' that is configured as a linear motion transducer integrated into the linear track 174. Alternatively, the housing 170 may have an axial motion transducer 150'' configured similarly to the axial motion transducer 150 in FIG 2 or 3. The 10 endoscope 100 may be manually advanced or withdrawn by the user by grasping the body 102 distal to the housing 170. Alternatively, the housing 170 may include a motor 176 or other linear motion actuator for automatically advancing and withdrawing the body 102 of the endoscope 100. In another alternative configuration, a motor with friction wheels, similar to that described above in connection with FIG 3, may be integrated into the axial motion transducer 150''.

15

FIG 5 shows a fourth embodiment of the endoscope 100 of the present invention, which utilizes a rotary housing 180 to organize and contain the endoscope 100. The housing 180 has a base 182 with a rotating drum 184 to guide the body 102 of the endoscope 100. The housing 180 may have an axial motion transducer 150''' that is configured as a potentiometer connected to 20 the pivot axis 186 of the rotating drum 184. Alternatively, the housing 180 may have an axial motion transducer 150'' configured similarly to the axial motion transducer 150 in FIG 2 or 3. The endoscope 100 may be manually advanced or withdrawn by the user by grasping the body 102 distal to the housing 180. Alternatively, the housing 180 may include a motor 188 connected to the rotating drum 184 for automatically advancing and withdrawing the body 102 of the 25 endoscope 100. In another alternative configuration, a motor with friction wheels, similar to that described above in connection with FIG 3, may be integrated into the axial motion transducer 150''.

FIG 6 shows a wire frame model of a section of the body 102 of the endoscope 100 in a 30 neutral or straight position. Most of the internal structure of the endoscope body 102 has been eliminated in this drawing for the sake of clarity. The endoscope body 102 is divided up into sections 1, 2, 3...10, etc. The geometry of each section is defined by four length measurements along the a, b, c and d axes. For example, the geometry of section 1 is defined by the four length measurements  $l_{1a}$ ,  $l_{1b}$ ,  $l_{1c}$ ,  $l_{1d}$ , and the geometry of section 2 is defined by the four length

measurements  $l_{2a}$ ,  $l_{2b}$ ,  $l_{2c}$ ,  $l_{2d}$ , etc. Preferably, each of the length measurements is individually controlled by a linear actuator (not shown). The linear actuators may utilize one of several different operating principles. For example, each of the linear actuators may be a self-heating NiTi alloy linear actuator or an electrorheological plastic actuator, or other known mechanical, 5 pneumatic, hydraulic or electromechanical actuator. The geometry of each section may be altered using the linear actuators to change the four length measurements along the a, b, c and d axes. Preferably, the length measurements are changed in complementary pairs to selectively bend the endoscope body 102 in a desired direction. For example, to bend the endoscope body 102 in the direction of the a axis, the measurements  $l_{1a}$ ,  $l_{2a}$ ,  $l_{3a}$ ...  $l_{10a}$  would be shortened and the 10 measurements  $l_{1b}$ ,  $l_{2b}$ ,  $l_{3b}$ ...  $l_{10b}$  would be lengthened an equal amount. The amount by which these measurements are changed determines the radius of the resultant curve.

In the selectively steerable distal portion 104 of the endoscope body 102, the linear actuators that control the a, b, c and d axis measurements of each section are selectively controlled by the user through the steering control 122. Thus, by appropriate control of the a, b, c 15 and d axis measurements, the selectively steerable distal portion 104 of the endoscope body 102 can be selectively steered or bent up to a full 180 degrees in any direction.

In the automatically controlled proximal portion 106, however, the a, b, c and d axis measurements of each section are automatically controlled by the electronic motion controller 140, which uses a curve propagation method to control the shape of the endoscope body 102. To 20 explain how the curve propagation method operates, FIG 7 shows the wire frame model of a part of the automatically controlled proximal portion 106 of the endoscope body 102 shown in FIG 6 passing through a curve in a patient's colon C. For simplicity, an example of a two-dimensional curve is shown and only the a and b axes will be considered. In a three-dimensional curve all four of the a, b, c and d axes would be brought into play.

25 In FIG 7, the endoscope body 102 has been maneuvered through the curve in the colon C with the benefit of the selectively steerable distal portion 104 (this part of the procedure is explained in more detail below) and now the automatically controlled proximal portion 106 resides in the curve. Sections 1 and 2 are in a relatively straight part of the colon C, therefore  $l_{1a}=l_{1b}$  and  $l_{2a}=l_{2b}$ . However, because sections 3-7 are in the S-shaped curved section,  $l_{3a}< l_{3b}$ , 30  $l_{4a}< l_{4b}$  and  $l_{5a}< l_{5b}$ , but  $l_{6a}> l_{6b}$ ,  $l_{7a}> l_{7b}$  and  $l_{8a}> l_{8b}$ . When the endoscope body 102 is advanced distally by one unit, section 1 moves into the position marked 1', section 2 moves into the position previously occupied by section 1, section 3 moves into the position previously occupied by section 2, etc. The axial motion transducer 150 produces a signal indicative of the axial position of the endoscope body 102 with respect to a fixed point of reference and sends the signal

to the electronic motion controller 140. Under control of the electronic motion controller 140, each time the endoscope body 102 advances one unit, each section in the automatically controlled proximal portion 106 is signaled to assume the shape of the section that previously occupied the space that it is now in. Therefore, when the endoscope body 102 is advanced to the 5 position marked 1',  $l_{1a}=l_{1b}$ ,  $l_{2a}=l_{2b}$ ,  $l_{3a}=l_{3b}$ ,  $l_{4a} < l_{4b}$ ,  $l_{5a} < l_{5b}$ ,  $l_{6a} < l_{6b}$ ,  $l_{7a} > l_{7b}$ ,  $l_{8a} > l_{8b}$ , and  $l_{9a} > l_{9b}$ , and, when the endoscope body 102 is advanced to the position marked 1'',  $l_{1a}=l_{1b}$ ,  $l_{2a}=l_{2b}$ ,  $l_{3a}=l_{3b}$ ,  $l_{4a}=l_{4b}$ ,  $l_{5a} < l_{5b}$ ,  $l_{6a} < l_{6b}$ ,  $l_{7a} < l_{7b}$ ,  $l_{8a} > l_{8b}$ ,  $l_{9a} > l_{9b}$ , and  $l_{10a} > l_{10b}$ . Thus, the S-shaped curve propagates proximally along the length of the automatically controlled proximal portion 106 of the endoscope body 102. The S-shaped curve appears to be fixed in space, as the endoscope body 10 102 advances distally.

Similarly, when the endoscope body 102 is withdrawn proximally, each time the endoscope body 102 is moved proximally by one unit, each section in the automatically controlled proximal portion 106 is signaled to assume the shape of the section that previously occupied the space that it is now in. The S-shaped curve propagates distally along the length of 15 the automatically controlled proximal portion 106 of the endoscope body 102, and the S-shaped curve appears to be fixed in space, as the endoscope body 102 withdraws proximally.

Whenever the endoscope body 102 is advanced or withdrawn, the axial motion transducer 150 detects the change in position and the electronic motion controller 140 propagates the selected curves proximally or distally along the automatically controlled proximal portion 106 of 20 the endoscope body 102 to maintain the curves in a spatially fixed position. This allows the endoscope body 102 to move through tortuous curves without putting unnecessary force on the wall of the colon C.

FIGS 8-13 show the endoscope 100 of the present invention being employed for a 25 colonoscopic examination of a patient's colon. In FIG 8, the endoscope body 102 has been lubricated and inserted into the patient's colon C through the anus A. The distal end 108 of the endoscope body 102 is advanced through the rectum R until the first turn in the colon C is reached, as observed through the ocular 124 or on a video monitor. To negotiate the turn, the selectively steerable distal portion 104 of the endoscope body 102 is manually steered toward the 30 sigmoid colon S by the user through the steering control 122. The control signals from the steering control 122 to the selectively steerable distal portion 104 are monitored by the electronic motion controller 140. When the correct curve of the selectively steerable distal portion 104 for advancing the distal end 108 of the endoscope body 102 into the sigmoid colon S has been selected, the curve is logged into the memory of the electronic motion controller 140 as a

reference. This step can be performed in a manual mode, in which the user gives a command to the electronic motion controller 140 to record the selected curve, using keyboard commands or voice commands. Alternatively, this step can be performed in an automatic mode, in which the user signals to the electronic motion controller 140 that the desired curve has been selected by 5 advancing the endoscope body 102 distally.

Whether operated in manual mode or automatic mode, once the desired curve has been selected with the selectively steerable distal portion 104, the endoscope body 102 is advanced distally and the selected curve is propagated proximally along the automatically controlled proximal portion 106 of the endoscope body 102 by the electronic motion controller 140, as 10 described above. The curve remains fixed in space while the endoscope body 102 is advanced distally through the sigmoid colon S. In a particularly tortuous colon, the selectively steerable distal portion 104 may have to be steered through multiple curves to traverse the sigmoid colon S.

As illustrated in FIG 9, the user may stop the endoscope 100 at any point for examination 15 or treatment of the mucosal surface or any other features within the colon C. The selectively steerable distal portion 104 may be steered in any direction to examine the inside of the colon C. When the user has completed the examination of the sigmoid colon S, the selectively steerable distal portion 104 is steered in a superior direction toward the descending colon D. Once the 20 desired curve has been selected with the selectively steerable distal portion 104, the endoscope body 102 is advanced distally into the descending colon D, and the second curve as well as the first curve are propagated proximally along the automatically controlled proximal portion 106 of the endoscope body 102, as shown in FIG 10.

If, at any time, the user decides that the path taken by the endoscope body 102 needs to be revised or corrected, the endoscope 100 may be withdrawn proximally and the electronic motion 25 controller 140 commanded to erase the previously selected curve. This can be done manually using keyboard commands or voice commands or automatically by programming the electronic motion controller 140 to go into a revise mode when the endoscope body 102 is withdrawn a certain distance. The revised or corrected curve is selected using the selectively steerable distal portion 104, and the endoscope body 102 is advanced as described before.

30 The endoscope body 102 is advanced through the descending colon D until it reaches the left (splenic) flexure F<sub>1</sub> of the colon. Here, in many cases, the endoscope body 102 must negotiate an almost 180 degree hairpin turn. As before, the desired curve is selected using the selectively steerable distal portion 104, and the endoscope body 102 is advanced distally through the transverse colon T, as shown in FIG 11. Each of the previously selected curves is propagated

proximally along the automatically controlled proximal portion 106 of the endoscope body 102. The same procedure is followed at the right (hepatic) flexure F, of the colon and the distal end 108 of the endoscope body 102 is advanced through the ascending colon G to the cecum E, as shown in FIG 12. The cecum E, the ileocecal valve V and the terminal portion of the ileum I can 5 be examined from this point using the selectively steerable distal portion 104 of the endoscope body 102.

FIG 13 shows the endoscope 100 being withdrawn through the colon C. As the endoscope 100 is withdrawn, the endoscope body 102 follows the previously selected curves by propagating the curves distally along the automatically controlled proximal portion 106, as described above. 10 At any point, the user may stop the endoscope 100 for examination or treatment of the mucosal surface or any other features within the colon C using the selectively steerable distal portion 104 of the endoscope body 102.

In one preferred method according to the present invention, the electronic motion controller 140 includes an electronic memory in which is created a three-dimensional mathematical model of the patient's colon or other anatomy through which the endoscope body 102 is maneuvered. The three-dimensional model can be annotated by the operator to record the location of anatomical landmarks, lesions, polyps, biopsy samples and other features of interest. The three-dimensional model of the patient's anatomy can be used to facilitate reinsertion of the 20 endoscope body 102 in subsequent procedures. In addition, the annotations can be used to quickly find the location of the features of interest. For example, the three-dimensional model can be annotated with the location where a biopsy sample was taken during an exploratory endoscopy. The site of the biopsy sample can be reliably located again in follow-up procedures to track the progress of a potential disease process and/or to perform a therapeutic procedure at the 25 site.

In one particularly preferred variation of this method, the electronic motion controller 140 can be programmed, based on the three-dimensional model in the electronic memory, so that the endoscope body 102 will automatically assume the proper shape to follow the desired path as it is advanced through the patient's anatomy. In embodiments of the steerable endoscope 100 that are 30 configured for automatically advancing and withdrawing the endoscope body 102, as described above in connection with FIGS 3, 4 and 5, the endoscope body 102 can be commanded to advance automatically through the patient's anatomy to the site of a previously noted lesion or other point of interest based on the three-dimensional model in the electronic memory.

5 Imaging software would allow the three-dimensional model of the patient's anatomy obtained using the steerable endoscope 100 to be viewed on a computer monitor or the like. This would facilitate comparisons between the three-dimensional model and images obtained with other imaging modalities, for example fluoroscopy, radiography, ultrasonography, magnetic resonance imaging (MRI), computed tomography (CT scan), electron beam tomography or virtual colonoscopy. Conversely, images from these other imaging modalities can be used to map out an approximate path or trajectory to facilitate insertion of the endoscope body 102. In addition, images from other imaging modalities can be used to facilitate locating suspected lesions with the steerable endoscope 100. For example, images obtained using a barium-contrast 10 radiograph of the colon can be used to map out an approximate path to facilitate insertion of the endoscope body 102 into the patient's colon. The location and depth of any suspected lesions seen on the radiograph can be noted so that the endoscope body 102 can be quickly and reliably guided to the vicinity of the lesion.

15 Imaging modalities that provide three-dimensional information, such as biplanar fluoroscopy, CT or MRI, can be used to program the electronic motion controller 140 so that the endoscope body 102 will automatically assume the proper shape to follow the desired path as it is advanced through the patient's anatomy. In embodiments of the steerable endoscope 100 that are configured for automatically advancing and withdrawing the endoscope body 102, the endoscope body 102 can be commanded to advance automatically through the patient's anatomy along the 20 desired path as determined by the three-dimensional imaging information. Similarly, the endoscope body 102 can be commanded to advance automatically to the site of a suspected lesion or other point of interest noted on the images.

25 Although the endoscope of the present invention has been described for use as a colonoscope, the endoscope can be configured for a number of other medical and industrial applications. In addition, the present invention can also be configured as a catheter, cannula, surgical instrument or introducer sheath that uses the principles of the invention for navigating through tortuous body channels.

30 In a variation of the method that is particularly applicable to laparoscopy or thoracoscopy procedures, the steerable endoscope 100 can be selectively maneuvered along a desired path around and between organs in a patient's body cavity. The distal end 108 of the endoscope 100 is inserted into the patient's body cavity through a natural opening, through a surgical incision or through a surgical cannula or introducer. The selectively steerable distal portion 104 can be used to explore and examine the patient's body cavity and to select a path around and between the

patient's organs. The electronic motion controller 140 can be used to control the automatically controlled proximal portion 106 of the endoscope body 102 to follow the selected path and, if necessary, to return to a desired location using the three-dimensional model in the electronic memory of the electronic motion controller 140.

5

While the present invention has been described herein with respect to the exemplary embodiments and the best mode for practicing the invention, it will be apparent to one of ordinary skill in the art that many modifications, improvements and subcombinations of the various embodiments, adaptations and variations can be made to the invention without departing 10 from the spirit and scope thereof.

I claim:

- 1        1. A method of advancing an instrument along a selected path, the method comprising:  
2            selectively steering a distal portion of the instrument to assume a first selected curve  
3        along a desired path; and  
4            advancing the instrument distally while controlling a proximal portion of the instrument  
5        to assume the first selected curve of the distal portion.
  
- 1        2. The method of claim 1, further comprising:  
2            further advancing the instrument distally while controlling the proximal portion to  
3        propagate the first selected curve proximally along the proximal portion of the instrument.
  
- 1        3. The method of claim 1, further comprising:  
2            withdrawing the instrument proximally while controlling the proximal portion to  
3        propagate the first selected curve distally along the proximal portion of the instrument.
  
- 1        4. The method of claim 1, further comprising:  
2            selectively steering the distal portion of the instrument to assume a second selected curve  
3        along the desired path; and  
4            advancing the instrument proximally while controlling the proximal portion to propagate  
5        the first and second selected curves proximally along the proximal portion of the instrument.
  
- 1        5. The method of claim 1, wherein the proximal portion of the instrument is automatically  
2        controlled by an electronic motion controller.
  
- 1        6. The method of claim 5, further comprising:  
2            measuring axial motion of the instrument with an axial motion transducer.
  
- 1        7. The method of claim 1, wherein the proximal portion of the instrument is controlled  
2        such that the first selected curve remains approximately fixed in space as the instrument is  
3        advanced proximally and/or withdrawn proximally.

1        8. The method of claim 1, wherein the instrument is an endoscope inserted into a patient's  
2        body.

1        9. The method of claim 1, wherein the instrument is a colonoscope inserted into a  
2        patient's colon.

1        10. A method of advancing an elongated instrument along a selected path, the elongated  
2        instrument having a multiplicity of controllable sections, including a first section, a second  
3        section and a third section, each section representing one unit of length, the method comprising:  
4                controlling the first section to assume a first selected curve along a desired path;  
5                advancing the elongated instrument distally a distance of approximately one unit of length  
6        while controlling the second section to assume the first selected curve;  
7                controlling the first section to assume a second selected curve along the desired path; and  
8                further advancing the elongated instrument distally a distance of approximately one unit  
9        of length while controlling the second section to assume the second selected curve and  
10        controlling the third section to assume the first selected curve.

1        11. The method of claim 10, further comprising:  
2                controlling the first section to assume a third selected curve along the desired path; and  
3                further advancing the elongated instrument distally a distance of approximately one unit  
4        of length while controlling the second section to assume the third selected curve and controlling  
5        the third section to assume the second selected curve.

1        12. The method of claim 11, further comprising:  
2                withdrawing the elongated instrument proximally a distance of approximately one unit of  
3        length while controlling the first section to assume the third selected curve, controlling the  
4        second section to assume the second selected curve and controlling the third section to assume  
5        the first selected curve.

1        13. The method of claim 10, wherein the proximal portion of the instrument is  
2 automatically controlled by an electronic motion controller.

1        14. The method of claim 10, wherein the elongated instrument is an endoscope inserted  
2 into a patient's body.

1        15. The method of claim 10, wherein the elongated instrument is a colonoscope inserted  
2 into a patient's colon.

1        16. Apparatus comprising:

2            an elongated instrument body having a selectively steerable distal portion and an  
3 automatically controllable proximal portion, the selectively steerable distal portion being  
4 configured to selectively assume a selected curve along a desired path, and the automatically  
5 controllable proximal portion being configured to propagate the selected curve proximally along  
6 the proximal portion of the elongated instrument body as the elongated instrument body is  
7 advanced distally.

1        17. The apparatus of claim 16, wherein the automatically controllable proximal portion is  
2 further configured to propagate the selected curve distally along the proximal portion of the  
3 elongated instrument body as the elongated instrument body is withdrawn proximally.

1        18. The apparatus of claim 16, further comprising:

2            an imaging system for transmitting an image from a distal end to a proximal end of the  
3 elongated instrument body.

1        19. The apparatus of claim 18, wherein the imaging system comprises a fiberoptic  
2 imaging bundle extending from the distal end to the proximal end of the elongated instrument  
3 body.

1        20. The apparatus of claim 18, wherein the elongated instrument body is configured as an  
2 endoscope for insertion into a patient's body.

1        21. The apparatus of claim 18, wherein the elongated instrument body is configured as a  
2 colonoscope for insertion into a patient's colon.

1        22. The apparatus of claim 16, further comprising:  
2            an electronic motion controller for controlling the automatically controllable proximal  
3 portion to propagate the selected curve proximally or distally along the proximal portion of the  
4 elongated instrument body.

1        23. The apparatus of claim 22, further comprising:  
2            an axial motion transducer for measuring axial motion of the elongated instrument body.

1        24. The apparatus of claim 16, further comprising:  
2            an axial motion transducer for measuring axial motion of the elongated instrument body.

1        25. Apparatus comprising:  
2            an elongated instrument body having a multiplicity of controllable sections, including a  
3 first section, a second section and a third section, each section representing one unit of length;  
4 and  
5            an electronic motion controller configured for controlling each of the first section, the  
6 second section and the third section to assume first, second and third portions of a selected curve  
7 when the elongated instrument body is in an initial position, and configured to, when the  
8 elongated instrument advances distally a distance of approximately one unit of length from the  
9 initial position, control the second section to assume the first portion of the selected curve and  
10 the third section to assume the second portion of the selected curve.

1        26. The apparatus of claim 25, wherein the electronic motion controller is further  
2 configured to, when the elongated instrument withdraws proximally a distance of approximately  
3 one unit of length from the initial position, control the first section to assume the second portion  
4 of the selected curve and the second section to assume the third portion of the selected curve.

- 1        27. The apparatus of claim 25, wherein the elongated instrument body further comprises a
- 2        selectively steerable distal portion.
  
- 1        28. The apparatus of claim 25, further comprising:  
2            an axial motion transducer for measuring axial motion of the elongated instrument body.
  
- 1        29. The apparatus of claim 25, further comprising:  
2            an imaging system for transmitting an image from a distal end to a proximal end of the  
3        elongated instrument body.
  
- 1        30. The apparatus of claim 30, wherein the imaging system comprises a fiberoptic  
2        imaging bundle extending from the distal end to the proximal end of the elongated instrument  
3        body.
  
- 1        31. The apparatus of claim 25, further comprising:  
2            an imaging system for transmitting an image from a distal end of the elongated instrument  
3        body to a video monitor.
  
- 1        32. The apparatus of claim 25, wherein the elongated instrument body is configured as an  
2        endoscope for insertion into a patient's body.
  
- 1        33. The apparatus of claim 25, wherein the elongated instrument body is configured as a  
2        colonoscope for insertion into a patient's colon.

1/7





FIG 1  
PRIOR ART

2/7

FIG 2



3/7








FIG. 5

4/7

FIG 6



5/7




FIG 8






FIG 9

6/7



7/7

