



(51) International Patent Classification:

A47L 5/22 (2006.01) A47L 9/24 (2006.01)
A47L 5/24 (2006.01) A47L 9/32 (2006.01)
A47L 9/00 (2006.01) A47L 11/40 (2006.01)
A47L 9/16 (2006.01)

(21) International Application Number:

PCT/GB2021/052707

(22) International Filing Date:

20 October 2021 (20.10.2021)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

2017567.5 06 November 2020 (06.11.2020) GB

(71) Applicant: **DYSON TECHNOLOGY LIMITED**
[GB/GB]; Tetbury Hill, Malmesbury Wiltshire SN16 0RP (GB).

(72) Inventors: **SHAW, Andrew**; Dyson Technology Limited, Tetbury Hill, Malmesbury Wiltshire SN16 0RP (GB). **NEWTON, David**; Dyson Technology Limited, Tetbury Hill, Malmesbury Wiltshire SN16 0RP (GB). **COLE, David**; Dyson Technology Limited, Tetbury Hill, Malmesbury Wiltshire SN16 0RP (GB).

(74) Agent: **BOOTH, Andrew** et al.; Intellectual Property Department, Dyson Technology Limited, Tetbury Hill, Malmesbury Wiltshire SN16 0RP (GB).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, IT, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, WS, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

(54) Title: ROBOTIC VACUUM CLEANING SYSTEM




FIG. 2

(57) Abstract: A vacuum cleaning system comprising a robotic unit (2) comprising a traction arrangement (4), a docking interface and an articulated arm (82) defining an end effector, wherein the end effector comprises a suction tool, and wherein the robotic unit defines a suction flow path which extends from the suction tool to the docking interface. The system further comprises a handheld vacuum cleaner (6) configured to be docked with the docking interface, the handheld vacuum cleaner comprising a vacuum motor for drawing air through the suction flow path when docked with the docking interface.

Published:

— *with international search report (Art. 21(3))*

Robotic Vacuum Cleaning System

Technical Field

5 The invention relates to a robotic vacuum cleaning system.

Background

10 The robotic vacuum cleaner market has grown hugely over the past decade. Changes in lifestyle, increased disposable income, urbanisation and growing focus on labour-saving devices are some of the factors that have boosted market growth, and the trend seems to be set to continue.

15 Whilst the robotisation of vacuum cleaners has seen more products enter the market, the form factor of such robots has not tended to diversify. Generally, robotic vacuum cleaners available on the market are discoidal in shape, with a low height so they can travel underneath furniture in order to clean there. The main technological developments have focussed on improving navigational capabilities to improve autonomy, bin emptying systems and run time. In the main, however, the robotic vacuum cleaner market includes
20 many generally circular machines that offer very little in terms of differentiation.

Some effort has been made to improve the functionality of robot vacuum cleaners to cope with demanding environments. For example, US2020/001468 describes a robotic cylinder-style machine which has a cleaner head that can locomote separately. The cleaner head
25 can therefore driver itself away from the main body of the machine to as to stretch underneath furniture.

US2018/317725 and US2010/0256812 describe discoidal robots which are equipped with robotic arms. However, neither of these examples appears to be a practical application,
30 and the utility of the robotic arm in each case seems to be limited.

It is against this background that the embodiments of the invention have been devised.

SUMMARY OF THE INVENTION

35

According to a first aspect of the invention, there is provided a vacuum cleaning system comprising a robotic unit comprising a traction arrangement, a docking interface and an articulated arm defining an end effector, wherein the end effector comprises a suction tool, and wherein the robotic unit defines a suction flow path which extends from the suction
5 tool to the docking interface. The system further comprises a handheld vacuum cleaner configured to be docked with the docking interface, the handheld vacuum cleaner comprising a vacuum motor for drawing air through the suction flow path when docked with the docking interface.

10 In another aspect, the invention relates to a robotic unit comprising a traction arrangement, a docking interface for receiving a handheld vacuum cleaner, and an articulated arm defining an end effector, wherein the end effector is a cleaner head, and wherein the robotic unit defines a suction flow path which extends from the cleaner head to the docking interface.

15

The handheld vacuum cleaner may further comprise a dust separator, which may be a cyclonic dust separator. Such a configuration of handheld vacuum cleaner may provide a particularly efficient separation system for the cleaning system. Although the system may use a batter pack that is provided in the robotic unit, in some examples, the handheld
20 vacuum cleaner includes a battery pack which it may use to generate suction power when used in conjunction with the robotic unit.

The system may include a user interface display screen that is carried on either the robotic unit and/or the handheld vacuum cleaner. In some examples, the user interface is provided
25 just on the handheld vacuum cleaner. Therefore, the user interface can provide suitable data to the user when operating as a handheld machine, for example battery levels, filter change requirements and so on, but it can provide the user with robot data when the handheld is docked with the robotic unit, for example mapping data, home commands and so on. A single user interface can therefore provide a dual purpose which reduces cost of
30 the machine as a whole and also is a simpler interface for the user.

The suction flow path may be defined at least in part by the articulated arm. This provides a particularly compact configuration and obviates the need for air hoses to be routed externally of the machine.

35

The articulated arm and the handheld vacuum cleaner may comprise respective tool mounts that are configured to engage with the suction tool. The suction tool may be removable from the machines as a result. What is more, the system may include a plurality of interchangeable suction tools, which may be motorised or passive. This provides a particularly flexible system, as the user is able to swap the tools between the robotic unit and the handheld vacuum cleaner depending on the desired use case.

In some examples, the articulated arm is actuatable such that the articulated arm is able to lift the suction tool. This enables the system to clean on levels higher than a floor surface, for example stairs and on furniture.

In one particular configuration, When the handheld cleaner is docked with the robotic unit, a longitudinal axis thereof extends transversely, and optionally perpendicularly, to a ground plane defined by the traction arrangement.

Within the scope of this application it is expressly intended that the various aspects, embodiments, examples and alternatives set out in the preceding paragraphs, in the claims and/or in the following description and drawings, and in particular the individual features thereof, may be taken independently or in any combination. That is, all embodiments and/or features of any embodiment can be combined in any way and/or combination, unless such features are incompatible. The applicant reserves the right to change any originally filed claim or file any new claim accordingly, including the right to amend any originally filed claim to depend from and/or incorporate any feature of any other claim although not originally claimed in that manner.

BRIEF DESCRIPTION OF THE DRAWINGS

The above and other aspects of the invention will now be described, by way of example only, with reference to the accompanying drawings, in which:

Figure 1 is a side view of a vacuum cleaning system, in accordance with an example of the invention, comprising a robotic drive module having a robotic arm, and a handheld vacuum cleaner mounted on the robotic drive module;

Figure 2 is a perspective view of the vacuum cleaning system of Figure 1, with the robotic arm in a fully deployed state;

Figure 3 is a side view of the vacuum cleaning system, with the arm in a deployed state like that in Figure 2;

5 Figure 4 shows the handheld vacuum cleaner in a stick vac configuration;

Figure 5 is a schematic view of the handheld vacuum cleaner on its own, depicting some of its significant internal components;

10 Figures 6a and 6b are perspective views of the vacuum cleaning system when viewed from the rear, where Figure 6a shows the handheld vacuum cleaner docked on the robotic drive module, and Figure 6b shows the handheld vacuum cleaner separated from the robotic drive module;

15 Figure 7 is a perspective view of the robotic drive module from the rear with a dock insert separated from the docking portion, and Figure 8a-c show various view of the dock insert; and

20 Figure 9a shows a perspective view of the vacuum cleaning system from the front, and Figure 9b shows a comparable view but which emphasises an airflow path through the machine.

Note that features that are the same or similar in different drawings are denoted by like reference signs.

25

SPECIFIC DESCRIPTION

A specific embodiment of the invention will now be described in which numerous features will be discussed in detail in order to provide a thorough understanding of the inventive
30 concept as defined in the claims. However, it will be apparent to the skilled person that the invention may be put into effect without the specific details and that in some instances, well known methods, techniques and structures have not been described in detail in order not to obscure the invention unnecessarily.

35 In overview, the invention provides a novel type of robotically-driven surface treating system, which is embodied in the illustrated examples as a vacuum cleaning system. The

cleaning system is a hybrid design which comprises a robotic drive unit or module, and a handheld vacuum cleaner that is removably attachable to the robotic drive module. Moreover, the robotic drive module is equipped with a robotic arm which carries a cleaning tool or head on its distal end. The robotic arm therefore provides the robotic cleaning system with an extended reach so that it can clean under low-lying furniture. A convenient feature of the system is that the cleaning tool which is attachable to the distal end of the robotic arm, can also be attached to the handheld vacuum cleaner, either directly or via a wand extension tube. The cleaning system is therefore particularly convenient because a user can use the handheld vacuum cleaner to carry out spot-cleaning or more wide-spread cleaning tasks, e.g. when it is in stick-vac mode, but then the cleaner head can be installed onto the robotic drive module so that it can carry out autonomous cleaning tasks on a schedule that suits the user. Further features and advantages will become apparent from the discussion that follows.

The illustrated figures show a robotic vacuum cleaner 2 in accordance with an example of the invention. Referring firstly to Figures 1 to 3, the robotic vacuum cleaner 2 comprises two main parts. The first part is a robotic drive section, unit, or module and is labelled generally as '4' and the second part is a handheld vacuum cleaner, which is labelled generally as '6'. As will be appreciated, the handheld vacuum cleaner 6 is separable from the robotic drive module 4 such that the handheld vacuum cleaner 6 can be used on its own as a vacuum cleaning machine when it is undocked from the robotic drive module 4, or it may function together with the robotic drive module 4 to provide an autonomous vacuum cleaner system 6. As can be seen, Figures 1 to 3 show the robotic drive module 4 and the handheld vacuum cleaner 6 in a docked state, whilst Figure 6b shows the robotic drive module 4 and in a separated or undocked state.

In this example, the machine is a vacuum cleaner, but it is also envisaged that various adaptations may be made so that it performs other surface treating functions such as mopping, polishing, sanitiser-spraying and so on. So, the cleaning system in accordance with the invention should also be considered to extend to surface treating appliances or systems. For present purposes, however, the discussion will refer to a vacuum cleaner, but it should be appreciated that the embodiments of the invention may have broader application to general surface treating functionality.

Returning to Figures 1 to 3, it will be appreciated that the robotic drive module 4 and handheld vacuum cleaner 6 are dockable so as to function as a self-propelled robotic

vacuum cleaner. In this respect, the robotic drive module 4 provides the locomotion requirements of the machine, whilst the handheld vacuum cleaner 6 provides the suction power.

5 It is envisaged that each sub-unit may provide its own power, such that the robotic drive module 4 will include an on-board battery pack (not shown) to provide power to its respective drive motors (not shown), whilst the handheld vacuum cleaner 6 includes a battery pack to provide power to its on-board vacuum motor. However, it is also envisaged that power transfer between the robotic drive module 4 and the handheld vacuum cleaner
10 6 would be beneficial, during charging for example. Usefully, therefore, the handheld vacuum cleaner 6 can be used on its own, either in the form of a handheld vacuum cleaner or in the form of a stick-vac machine if the user wants to perform their own cleaning, for example to spot-remove debris from certain areas in the house. However, the handheld vacuum cleaner 6 can be docked onto the robotic drive module 4 such that the two
15 machines then function as an autonomous vacuum cleaner.

At this point it should be appreciated that the robotic drive module 4 would also be provided with a suitable navigation system which would be responsible for mapping, path planning and task scheduling operations. However, this functionality is beyond the scope of this
20 discussion and so further explanation of these aspects will be omitted.

With reference also to Figure 4 and 5, it will be noted that the handheld vacuum cleaner has a form factor of a machine currently marketed by the applicant as the Dyson V10 or V11. Although the overall form factor of the handheld vacuum cleaner 6 is therefore known
25 in the art, a brief overview will now follow for an improved understanding.

The handheld vacuum cleaner 4 comprises a main body 10 having an elongate handle 12, a cyclonic separating unit 14 and a suction inlet 16. As shown the suction inlet 16 is formed as a short nozzle but a cleaning tool or wand extension piece could be releasably attached
30 to the suction inlet 16 as required. The cyclonic separating unit 14 has a longitudinal axis X and extends away from the handle 12 such that the suction inlet 16 is at the end of the cyclonic separating unit 14 which is furthest from the handle 12.

The main body 10 comprises a suction generator 20 including a motor 22 and an impeller
35 24 which are located above and towards the rear of the handle 12. A battery 26 is located beneath the handle 12. As shown, the battery 26 is located at the end of the handle 12.

The handle 12 takes the form of a pistol grip, and a trigger 28 is provided an upper end of the handle 12 for convenient operation. Optionally, and as seen here, a trigger guard 29 extends forwardly from the handle and around the front of the trigger 28. As can be seen, for ergonomic reasons, the handle 12 is generally transverse to the longitudinal axis X of the main body and extends along a handle axis H so as to form an angle θ_1 therewith, which in this example is approximately 110 degrees.

The cyclonic separating unit 14 comprises a primary cyclonic separator 30 and a plurality of secondary cyclonic separators 32, which are positioned downstream from the primary cyclonic separator 30 and are arranged in a circular array about the axis X. Such a configuration is conventional in cyclonic vacuum cleaning technology. The primary cyclonic separator 30 comprises a separator body 34 in the form of a bin having a cylindrical outer wall 36 and an end wall 38, which define at least in part a cyclonic separator chamber 40. The separator chamber 40 is annular in form and extends about the longitudinal axis X. The axis of the separator chamber 40 therefore is coincident with the longitudinal axis X of the machine.

In terms of the flow path through the machine, the suction inlet 16 merges into a central duct 42 that runs centrally through the separator chamber 40, from the end wall 38, along the longitudinal axis X of the machine.

The central duct 42 terminates at a primary cyclone inlet 44 which discharges into the separator chamber 40 near to the top end of the primary cyclonic separator 30. Although not shown clearly in Figure 5, the primary cyclone inlet 44 is angled at a tangent to the motion of air in the separator chamber 40 in use, as is conventional.

The bottom end of the separator chamber 40 near to the end wall 38 and adjacent part of the cylindrical outer wall 36 together define a dirt collector or bin 46, which serves to collect the relatively large particles that are spun out of the circumferential airflow in the separator chamber 40. The end wall 38 is pivotable with respect to the cylindrical outer wall 36 so that it can be opened to discharge collected dirt from the bin 46. It should be noted at this point that the details of the bin opening mechanism and other related details may be conventional and so further discussion on these points will be omitted. This discussion will therefore focus on the main aspects of the handheld vacuum cleaner 6.

As has been mentioned, the cyclonic separating unit 14 includes a set of secondary cyclonic separators or 'cyclones' 32 which have a geometry optimised for separating fine particles from the flow of air through the machine compared to the relative large particles for which the primary cyclonic separator 30 is optimised. Airflow transitions from the separator chamber 40 of the primary cyclonic separator 30 to the secondary cyclones 32 through a cylindrical permeable shroud 48 that extends about the exterior of the central duct 42. The shroud 48 therefore extends about the longitudinal axis X and is coaxial therewith. The shroud 48 is permeable to air, in the form of a perforated panel such as a mesh, for example, and therefore forms an air outlet from the separator chamber 40 which serves to catch fibrous material on the shroud 48.

The shroud 48 encircles a duct 50 which extends longitudinally along the machine and which defines inlets 51 to the plurality of relatively small secondary cyclones 32. In the usual way, the secondary cyclones 32 are generally conical in form and define a dirt outlet at their respective tips 52 which discharge into a fine dust collector 54. In this example, the fine dust collector 54 is defined by the outer cylindrical wall of the cyclonic separating unit 14 in a radial outward position with respect to the main dirt collector 46. In this configuration therefore, when the end wall 38 is opened, the main dirt collector 46 and the fine dust collector 54 are opened so that direct can be emptied from the machine.

In overview, during use the handheld vacuum cleaner 6 is activated by a user pressing the trigger 28 which powers up the suction generator 20. The suction generator 20 therefore establishes a negative pressure differential through the machine which draws air flow through the suction inlet 16, up the central duct 42 and into the separator chamber 40 where it rotates around the longitudinal axis X. The rotational flow in the separator chamber 40 produces a cyclonic action that separates relatively heavy or large dirty particles from the air. Due to the orientation that the handheld vacuum cleaner 6 is typically used, these large dirt particles will tend to collect in the main dirt collector 46. The partially cleaned air then passed through the shroud 48, along the duct 50 and into the secondary cyclones 32 which act to separate smaller and lighter particles of air, which are expelled through the cyclone tips 52. Clean air is drawn out of respective outlets 60 of the secondary cyclones 32 and through the suction generator 20, where it is discharged to atmosphere.

Notably, Figure 5 shows the handheld vacuum cleaner in a 'bare' state, in which it does not have a cleaning tool attached to it. However, it should be appreciated that various cleaning attachments may be coupled to the handheld vacuum cleaner as required. In this

respect, Figure 4 shows the handheld vacuum cleaner 6 with a wand 62 attached, which turns the handheld vacuum cleaner 6 into a stick vacuum cleaner or 'stick-vac'. Here, the distal end of the wand 62 in turn has a motorised cleaner head 64 attached to it, including a rotatable agitator, which is optimised for cleaning hard floors or other floor coverings such as carpets and rugs.

Having described the overall configuration of the handheld vacuum cleaner 6, the discussion will focus on the configuration of the robotic drive module 4. This can be seen combined with the handheld vacuum cleaner 6 in many of the drawings, but it can also be seen on its own in Figures 6b and 7.

The robotic drive module 4 comprises a main body 70 that is flanked by a pair of wheels 72, one on either side of the main body 70. The wheels 72 are circular in this example and comprise a discoidal hub 74, the perimeter of which defines or carries a traction surface 76. The traction surface 76 may be made of a different material than the hub 74 to improve traction on certain surfaces. For example, the traction surface 76 could be a band-like element made of a grippy rubberised material or similar to provide improve traction on hard floors. Although the robotic drive module 4 is provided with circular wheels in this example, it is also envisaged that another type of rolling arrangement could be provided, for example in the form of a tracked drive system. The wheels therefore should be considered to be one type of traction arrangement for the robotic drive module 4.

The wheels 72 are positioned on either side of the main body 70 and have equal diameters. As such, their outer perimeters circumscribe an imaginary cylindrical shape which defines a rolling axis 73, and within which the structure of the main body 70 is contained. More specifically, in the illustrated example, the main body 70 is barrel-like in shape with an outer diameter which is slightly smaller than the outer diameter of the wheels 62. Expressed another way, the main body 70 is generally cylindrical in form and has a diameter approximately the same as the diameter of the wheels 72, in this example.

The main body 70 can be considered to have a forward-facing side 78 and a rearward-facing side 80. The forward-facing side 78 supports a near- or proximal-end of a robotic arm 82. The rearward-face side 80 defines a docking interface, region or portion 84, and this will be described in more detail later. As can be seen, therefore, the general barrel-like shape of the main body 60 is interrupted by suitable recesses 86 for the robotic arm 70 and the docking portion 84.

The robotic arm 82 is movable with respect to the main body 70 and includes an end effector 90 on its distal end to which different types of cleaning tools can be attached. As shown in the Figures, the end of the robotic arm 82 has a motorised cleaner head 92 attached to it. The robotic arm 82 therefore provides a suction flow path for the robotic vacuum cleaner 2 which extends from the end of the robotic arm 82, along the robotic arm 82 to the main body 70 of the robotic drive module 4 and to the handheld vacuum cleaner 6. Figures 9a and 9b illustrate this neatly as side-by-side views with some of the components of the machine removed so that a suction path 94 through the machine can be appreciated.

In the illustrated embodiment, the robotic arm 82 is articulated and can move between two main configuration: a stowed configuration in which the arm is folded up against the robotic drive module 4, and a deployed configuration in which in an extreme position the robotic arm extends generally straight away from the robotic drive module 4 parallel to the floor surface 101. The fully deployed configuration is shown clearly in Figures 2 and 3, and in Figure 3 it will be noted that a major part of the robotic arm 82 extends parallel to the floor surface 101. In this way therefore, the robotic arm 82 takes up minimal space when in the stowed configuration since it is folded compactly against the robotic drive module 4, but it conveniently can extend in front of the robotic drive module 4 by a significant distance so it can stretch under pieces of furniture and into narrow gaps.

As shown, the robotic arm 82 comprises an upper arm portion 100 and a lower arm or 'forearm' portion 102. The upper arm portion 100 has a first end 104 that is coupled to the main body 70 and a second end 106 that is coupled to the forearm portion 102. Similarly, the forearm portion 102 includes a first end 108 that is coupled to the upper arm portion 100 and a second end 110 that defines the end effector 90.

Although the robotic arm 82 may be configured in various ways, it will be noted that in the illustrated embodiment, the upper arm portion 100 has a two-part structure such that it comprises parallel arm members 100a, 100b. This provides the robotic arm 82 with a sturdy construction and a suitable torsional rigidity that is more resistant to flexing and twisting.

The connection between the upper arm portion 100 and the main body 70 is achieved by a pair of sockets 112 defined in the main body 60 which receive respective proximal ends of the pair of upper arm members 100a, 100b to define a shoulder joint 114. Although not

shown in Figures 1-3 the main body 70 may include a suitable drive system to pivot the upper arm portion 100 with respect to the main body 70 at the shoulder joint 114. Similarly, the distal ends of the upper arm members 100a,100b define a yoked elbow joint 116 into which is received an end of the forearm portion 102. The elbow joint 116 is suitably
5 configured to allow the forearm portion 102 to pivot relative to the upper arm portion 100. Separate drive motors (not shown) may be used for this purpose, or the joint 116 may be driven by a drive mechanism powered by the main body 60.

Notably, the shoulder joint 114 and the elbow joint 116 define respective pivot axes, 114',116'. As shown, the pivot axes 114',116' are arranged parallel to the ground plane.
10 As such, the pivot axes 114',116' are also parallel to the rolling axis 73, and perpendicular to the longitudinal axis X of the handheld vacuum cleaner 6. By virtue of the parallel horizontal arrangement of the pivot axes 114',116' the articulated arm 82 is arranged to pivot about both the shoulder joint 114 and the elbow joint 116 through a substantially
15 vertical plane P.

The upper arm portion 100 has a dog-leg shape when viewed from the side, in this illustrated example, and so each of the upper arm members 100a,100b comprises a first section 120 that defines a shallow angle with respect to a second section 122. This is best
20 seen in Figure 3, which shows clearly that a significant part of the upper arm portion 100, that is, the entirety of the second section 122 thereof, is positioned adjacent a floor surface 101 when the robotic arm 82 is in the fully deployed position. This is beneficial because it enables a significant part of the robotic arm 82 to lay flat against an adjacent floor surface 101. The first section 120 of the upper arm members 100a,100b inclines downwardly from
25 the shoulder joint 114 of the main body 70 and then straightens to extend parallel to the floor.

As has been mentioned, the robotic arm 82 can be folded back from its extended or deployed position, shown in Figures 2 and 3, to a stowed state as shown in Figure 1. It
30 can also be controlled to adopt positioned intermediate the two extreme positions. The two-part parallel structure of the upper arm portion 100 is beneficial in this context because it permits the lower arm section 102 to pivot around the elbow joint 116 and nest or sit between the parallel arm members 100a,100b of the upper arm portion 100. This allows a particularly compact stowage arrangement for the robotic arm 82. As can be seen in
35 Figure 1, for example, in the stowed position the lower arm portion 102 is oriented vertically and is flanked by at least a part of the parallel upper arm members 100a,100b, that is to

say by the second sections 122 thereof. What is more, the upper extremity of the robotic arm 82 is not the highest point of the robotic vacuum cleaner 2, since despite its vertical orientation, it is lower than the vertical height reached by the upper extremity of the handheld vacuum cleaner 6, which is indicated by the line V. This can be seen clearly in Figure 1. Expressed in another way, no part of the robotic arm 82 extends above the upper extremity of the robotic vacuum cleaner 2.

The two-part structure of the upper arm portion 100 also provides flexibility in terms of how the airflow path is routed from the cleaner head to the main body 70. For example, one of the upper arm members 100a, 100b can be configured to define the airflow path, whilst the other of the upper arm members 100a, 100b can be configured to carry the required mechanical and electrical components to power the elbow joint 116. Figures 9a and 9b illustrate this clearly in which a first pipe section 130 extends inside the forearm portion 102 vertically upwards from the cleaner head 92 and which bends through a 180 degree angle to form a second pipe section 132 which extends downwardly through one of the arm sections 100a of the upper arm portion 100 and into the main body 70 of the robotic drive module 4.

Having described the robotic arm aspects of the vacuum cleaning system 2, the discussion will now turn to general configuration aspects and docking aspects of the vacuum cleaning system 2.

As has been mentioned above, the main body 70 defines the docking portion 84 which is adapted to accept the handheld vacuum cleaner 6 in such a way as to complete the airflow path through the machine and therefore to provide a source of suction. The handheld vacuum cleaner 6 is arranged in an upright orientation with respect to the floor surface (see Figure 3) when it is docked with the robotic drive module 4. In this way, the longitudinal axis X of the handheld vacuum cleaner 6 is substantially vertical in the illustrated example. Expressed another way, the longitudinal axis X of the handheld vacuum cleaner 6 is generally perpendicular to the floor surface 101, which defines a ground plane. This arrangement provides an ergonomic angle for a user to dock the handheld vacuum cleaner 6 to the robotic drive module 4. This is because a user would tend to hold the handheld vacuum cleaner 2 in such a way to approach the docking portion 84 from above so a vertical docking arrangement is convenient for the user.

As well as being oriented generally vertically, the handheld vacuum cleaner 6 is arranged in the docking portion 84 so that its handle 12 points in the forward direction. That is to say, the linear section of the handle 12 is aligned with a fore-aft axis F of the main body 60. As can be seen in Figures 1-3, the arrangement of the handheld vacuum cleaner 6 in the docking interface 84 and its orientation is such that the handle 12 extends over the top of the main body 70 of the robotic drive module 4. With respect to the floor surface/ground plane 101, the handle 12 is generally horizontal, although it should be appreciated that in the illustrated embodiment the handle 12 is not precisely horizontal but defines a small angle therewith.

As will be apparent particularly from the side views of the vacuum cleaning system 2, the handle 12 extends over the robotic drive module 4, in the fore-aft direction F, to an extent that it passes over and extends beyond the rolling axis 73 that is defined by the wheels 72. Notably, the battery 26 is located at the end of the handle 12 and, in the arrangement shown, when the handheld vacuum cleaner 6 is docked on the robotic drive module 4, the battery 26 can be considered to be in a cantilevered arrangement. As such, the battery 26 is supported on the end of the handle 12, which extends in a horizontal direction when the handheld vacuum cleaner 6 is docked on the robotic drive module 4.

Notably, the handle 12 and battery 26 have a combined length so that the end of the battery 26 is at a horizontal position which is approximately in line with the end of the wheels 72. So, the battery 26 can be considered to extend over the top of at least a part of the robotic drive module 4. Furthermore, it should be noted that the direction in which the handle 12 extends is aligned with the direction of the robotic arm 82, so as to be in parallel therewith.

The handle 12 can therefore be considered to point in the forward direction of the vacuum cleaning system 2. One benefit of this arrangement is that the weight of the battery 26 provides a balancing effect, as the battery 26 is positioned on the other side of the rolling axis 73 to the main body 10 of the handheld vacuum cleaner 6. Together with the mass of the articulated arm 82, this arrangement provides a convenient means to provide balance to the twin-wheeled arrangement of the robotic drive module 4.

It is particularly apparent from Figure 1, for example, that the robotic arm 82 in the stowed position is in a folded upright configuration in which a surface of the robotic arm 80 abuts the distal surface of the battery 26. In effect, therefore, the battery 26 provides a movement backstop for the motion of the robotic arm 82 as it travels into its stowed position.

A further benefit associated with the vacuum cleaning system 2 is due to the exchangeability of the cleaner head 92 between the robotic arm 82 and the handheld vacuum cleaner 4. This provides consistency of cleaning when either machine is used to clean the floor and also provides a more efficient package. To permit the sharing of cleaning head, both the suction inlet 16 of the handheld vacuum cleaner 6 and the end effector 90 of the robotic arm 82 are provided with a connector or tool mount of the same format. Therefore, the same cleaner head 92 can be releasably clicked into place on either machine. As well as motorised cleaner heads, it will be appreciated that the handheld vacuum cleaner 6 may be equipped with other cleaning tools, such as crevice tools or mattress tools as desired by the user. Such cleaning tools may be motorised or non-motorised.

Turning now to Figures 6a, 6b, 7 and Figures 8a-c, the discussion will now focus on the docking aspects of the vacuum cleaning system. Whereas Figure 6a shows the vacuum cleaning system 2 with the handheld vacuum cleaner 6 docked onto the robotic drive module 4, Figures 6a and 7 show the robotic drive module 4 on its own. Notably, however, Figure 6b depicts a dock insert 138 engaged with the robotic drive module 4 whereas Figure 7 shows the dock insert 138 removed from the robotic drive module 4.

The docking portion 84 is defined generally by a floor 140 and a curved wall 142 in the rear side 80 of the main body 70 of the robotic drive module 4. The curved wall 142 is shaped to match approximately the circular geometry of the bin of the handheld vacuum cleaner 6. As a result, the handheld vacuum cleaner 6 appears to partially 'sit' in the robotic drive module 4 in a piggy-back configuration. The floor 140 of the docking portion 84 includes the electrical connection and airflow connection which allows the handheld vacuum cleaner 6 to interface effectively with the robotic drive module 4.

As can be seen in Figure 6b, an airflow connector 144 is defined at the centre of the floor 140 of the docking region 84 and this airflow connector 144 is configured to mate with the suction inlet 16 of the handheld vacuum cleaner 6. Likewise, situated next to the airflow connector 144 is an electrical connector 146 which is configured to be mated with a respective electrical connector 148 of the handheld vacuum cleaner 6.

Whereas the airflow connector 144 completes the airflow path through the machine, from the cleaner head 92, along the robotic arm 82 into the main body 70, through the docking portion 84 and finally to the handheld vacuum cleaner 6, the electrical connector 146 may

provide power and/or data transfer between the robotic drive module 4 and the handheld vacuum cleaner 6. For example, in terms of electrical power, it is an option for the main body 70 to accommodate a larger battery system than the handheld vacuum cleaner 6 so it may be advantageous to enable the robotic drive unit 4 to power the handheld vacuum cleaner 6. Similarly, when the vacuum cleaning system 2 is docked to an appropriate ground-based docking station for the purposes of charging, the handheld vacuum cleaner 6 may be charged through the robotic drive module 4.

The electrical connection between the robotic drive module 4 and the handheld vacuum cleaner 6 may also be used for data transfer. For example, the user may interact with a user interface 150 provided on the handheld vacuum cleaner 6 in order to command operational functions for the vacuum cleaning system 2. Therefore, the electrical connector 146 provides a means for the commands to be transmitted from the handheld vacuum cleaner 6 to the robotic drive module 4 whereupon they can be acted on by the onboard control system (not shown).

In some examples of the invention, it is envisaged that the docking portion 84 may be an integral part of the main body 70 having a fixed configuration so only a single type of handheld vacuum cleaner 6 is able to dock with it. However, in other examples, it is envisaged that the docking portion 84 may be reconfigurable to enable more than one type of handheld vacuum cleaner to dock with it. One way in which this could be achieved is with movable features on the docking portion 84 which would enable a user to configure the docking portion 84 selectably to interface to a particular handheld vacuum cleaner type. For example, the rear wall 142 may feature sliding sections which could be switched between different positions in order to change the geometry of the docking portion 84 thereby providing support to different types of handheld vacuum cleaners.

Another option is shown in the illustrated examples. Here the docking portion 84 is defined at least in part by the removable dock insert 138. The dock insert 138 is able to be swapped with a different dock insert having a geometry that has been designed to match a different type of handheld vacuum cleaner.

The dock insert 138 comprises base section 152 and a rear wall 154 which are shaped so as to complement a correspondingly shaped recess 156 defined in the main body 70 of the robotic drive module 4.

The base section 152 is generally circular in shape and defines a generally flat annular platform 158 for receiving the leading end of the bin of the handheld vacuum cleaner 6. The annular platform 158 surrounds the airflow connector 144 and electrical connector 146.

5

The rear wall 154 extends upwardly from the base section 152 and terminates in a transversely extending cap section 160. The rear wall 154 extends about approximately 25% of the perimeter of the base section 152 so as to fit into the recess 156 in the main body 70. In order to conform to the cylindrical outer surface of the bin of the handheld vacuum cleaner, the rear wall 154 is curved in the horizontal plane with a radius of curvature that is comparable to the radius of the base section 152. The rear wall 154 therefore continues the curvature of the rear wall 142 in the main body 70, portions of which flank the rear wall 154 of the dock insert 138.

15 The cap section 160 has a curved upper surface 162 which extends away from the rear wall 154 in a direction opposite the base section 152. As can be seen by observing Figure 7, the curved upper surface 162 of the cap section 160 matches the curved upper surface of the generally cylindrical main body 70. Therefore, when the dock insert 138 is fitted to the main body 70, the curved upper surface 162 of the dock insert 138 lays flush with, and
20 therefore blends into, the curved upper surface of the main body 70.

Observing Figure 8c, which shows clearly the underside of the dock insert 138, it will be seen that that a rear edge of the base section 152 is provided with an electrical port 164 and an airflow port 166 which correspond to the electrical connector 146 and the airflow connector 144 respectively. Likewise, Figure 7 shows the docking portion 84 without the dock insert 138 and it will be appreciated that the docking portion 84 is provided with a respective electrical port 170 and airflow port 172 which are able to mate with the respective ports 164,166 in the dock insert 138.

30 Various modifications to the illustrated examples are possible without departing from the scope of the invention as defined by the claims.

35

CLAIMS

1. A vacuum cleaning system comprising:
 - 5 a robotic unit comprising a traction arrangement, a docking interface and an articulated arm defining an end effector, wherein the end effector comprises a suction tool,
and wherein the robotic unit defines a suction flow path which extends from the suction tool to the docking interface,
10 a handheld vacuum cleaner configured to be docked with the docking interface, the handheld vacuum cleaner comprising a vacuum motor for drawing air through the suction flow path when docked with the docking interface.
- 15 2. The vacuum cleaning system of Claim 1, wherein the handheld vacuum cleaner further comprises a dust separator.
3. The vacuum cleaning system of Claim 1 or 2, wherein the handheld vacuum cleaner includes a battery pack.
20
4. The vacuum cleaning system of any one of the preceding claims, wherein the handheld vacuum cleaner includes a user interface display screen.
5. The vacuum cleaning system of any one of the preceding claims, wherein the
25 suction flow path is defined at least in part by the articulated arm.
6. The vacuum cleaning system of any one of the preceding claims, wherein the articulated arm and the handheld vacuum cleaner comprise respective tool mounts that are configured to engage with the suction tool.
30
7. The vacuum cleaning system of any one of the preceding claims, wherein the articulated arm is actuatable such that the articulated arm is able to lift the suction tool.
8. The vacuum cleaning system of any one of the preceding claims, wherein the
35 handheld cleaner has a longitudinal axis along which a suction nozzle and a vacuum motor are oriented, wherein the handheld vacuum cleaner is mounted to the docking

interface so that the longitudinal axis extends transversely, and optionally perpendicularly, to a ground plane defined by the traction arrangement.

9. The vacuum cleaning system of any one of the preceding claim, wherein the traction arrangement defines a rolling axis, and wherein the docking interface is provided on a first side of the rolling axis, and wherein the articulated arm extends from the robotic unit from a position on a second side of the rolling axis.

10. The vacuum cleaning system of any one of the preceding claims, further comprising a plurality of interchangeable suction tools, each of the suction tools being configured to connect to the robotic unit and to the handheld vacuum cleaner.

11. A robotic unit comprising a traction arrangement, a docking interface for receiving a handheld vacuum cleaner, and an articulated arm defining an end effector, wherein the end effector is a cleaner head, and wherein the robotic unit defines a suction flow path which extends from the cleaner head to the docking interface.

12. The vacuum cleaning system of Claim 11, wherein the suction flow path is defined at least in part by the articulated arm.

13. The vacuum cleaning system of Claim 11 or 12, wherein the articulated arm is actuatable such that the articulated arm is able to lift the cleaner head.

14. The vacuum cleaning system of any of Claims 11 to 13, wherein the traction arrangement defines a rolling axis, and wherein the docking interface is provided on a first side of the rolling axis, and wherein the articulated arm extends from the robotic unit from a position on a second side of the rolling axis.

1 / 8




FIG. 1




FIG. 2




FIG. 3

4 / 8




FIG. 4




FIG. 5




FIG. 6B




FIG. 6A




FIG. 7




FIG. 8A




FIG. 8B




FIG. 8C




FIG. 9A




FIG. 9B

INTERNATIONAL SEARCH REPORT

International application No
PCT/GB2021/052707

A. CLASSIFICATION OF SUBJECT MATTER		
INV.	A47L5/22	A47L5/24
	A47L9/32	A47L11/40
	A47L9/00	A47L9/16
	A47L9/24	
ADD.		
According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED		
Minimum documentation searched (classification system followed by classification symbols) A47L		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
Electronic data base consulted during the international search (name of data base and, where practicable, search terms used) EPO-Internal, WPI Data		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2010/256812 A1 (TSUSAKA YUKO [JP] ET AL) 7 October 2010 (2010-10-07) cited in the application the whole document -----	1-14
A	EP 2 649 920 A1 (EGENPOWER INC [US]) 16 October 2013 (2013-10-16) the whole document -----	1-14
A	US 2012/189507 A1 (KO JOSEPH Y [US]) 26 July 2012 (2012-07-26) paragraph [0002] - paragraph [0022] -----	1-14
A	US 2020/298415 A1 (SUN JIAJIAN [CN] ET AL) 24 September 2020 (2020-09-24) paragraph [0002] - paragraph [0027] paragraph [0131] -----	1-14
☐ Further documents are listed in the continuation of Box C. ☒ See patent family annex.		
* Special categories of cited documents : "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier application or patent but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "&" document member of the same patent family		
Date of the actual completion of the international search 19 January 2022		Date of mailing of the international search report 28/01/2022
Name and mailing address of the ISA/ European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Fax: (+31-70) 340-3016		Authorized officer Jezierski, Krzysztof

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/GB2021/052707

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2010256812 A1	07-10-2010	CN 102046059 A	04-05-2011
		EP 2322071 A1	18-05-2011
		JP 4512672 B2	28-07-2010
		JP WO2010016210 A1	12-01-2012
		US 2010256812 A1	07-10-2010
		WO 2010016210 A1	11-02-2010

EP 2649920 A1	16-10-2013	CN 103371770 A	30-10-2013
		EP 2649920 A1	16-10-2013
		US 2013269148 A1	17-10-2013

US 2012189507 A1	26-07-2012	NONE	

US 2020298415 A1	24-09-2020	NONE	
