

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau



(10) International Publication Number
WO 2013/088327 A1

(43) International Publication Date
20 June 2013 (20.06.2013)

W I P O | P C T

(51) International Patent Classification:

A61F 2/24 (2006.01)

(21) International Application Number:

PCT/IB20 12/057 138

(22) International Filing Date:

10 December 2012 (10.12.2012)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

61/569,304 12 December 2011 (12.12.2011) US
61/683,736 16 August 2012 (16.08.2012) US

(72) Inventors; and

(71) Applicants : **ALON, David** [IL/IL]; 8 Mishol Hagan, Zichron Yaakov, 30900 Zichron Yaakov (IL). **KUCK, Karl-Heinz** [DE/DE]; 86 Heilwigstrasse, Hamburg, 20249 Hamburg (DE).

(74) Agents: **TSIVION, Yoram** et al; Hatochen 2, Casarea, 3148 Casarea (IL).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,

AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: HEART VALVE REPAIR DEVICE




Fig.1

(57) Abstract: A heart valve annulus repair device having a tissue engaging member and a plurality of anchors. The tissue engaging member includes a loop of wire. Each of the anchors has a pointy front end and a back end and a slot that runs in a front-to-back direction. The anchors are distributed about the loop of wire with the front ends of the plurality of anchors facing the heart valve annulus and with the loop of wire passing through the slots. The device further includes means for implanting the anchors into the heart valve annulus tissue so that the tissue engaging member becomes affixed to the heart valve annulus.

HEART VALVE REPAIR DEVICE

FIELD OF THE INVENTION

[001] The present invention relates to medical devices, in particular, devices for repairing biological valves.

BACKGROUND OF THE INVENTION

[002] The mitral valve is positioned in the heart left side, between the left atrium and the left ventricle. The most typical disease of the mitral valve is insufficiency or regurgitation which occurs when the valve leaflets do not coapt properly. Mitral valve repair by suturing a ring to reduce the annulus diameter is the procedure of choice to correct mitral regurgitation. With the use of current surgical techniques, most regurgitant mitral valves can be repaired or replaced with artificial valve prosthesis.

[003] Currently, mitral valve repair requires an extremely invasive surgical approach that includes a sternotomy, cardio-pulmonary bypass, cardiac arrest, and an incision in the heart itself to expose the mitral valve. Such procedure is associated with high morbidity and mortality. A percutaneous device that can effectively treat the disease without the need for open heart surgery could greatly improve patient benefit and may include other patients that currently cannot be treated with surgery being too old or frail for such invasive procedure.

[004] Most current surgical practices for mitral valve repair involve mitral valve annuloplasty and/or mitral valve valvuloplasty.

[005] Surgical annuloplasty is a technique aimed to reduce the size of the fibrous tissue at the base of the mitral valve, called the annulus. Sometimes the annulus becomes enlarged, enabling blood to back flow up into the left atrium, through the gap between the two separated valve leaflets. The repair is done with sutures to make the opening smaller, helping the two leaflets meet and co-apt again when the valve closes.

[006] Surgical valvuloplasty is a technique aimed to ensure proper closure of the valve leaflets. Leaflet function can be impaired as the result of prolapse of a leaflet due to ruptured chordae. The leaflet reconstruction is done by leaflet resection and reshaped with sutures. In most cases both annuloplasty and valvuloplasty is needed in order to regain optimal mitral valve function.

[007] Due to the invasive nature of the mitral valve surgery, and the high risks involved in the procedure, many heart failure patients are poor surgical candidates. Thus, less invasive methods and devices to reduce mitral valve regurgitation would make this therapy available to many more patients.

[008] US2004/102839, US2004/1022840, US6656221, US6718985, US6723038 and US2004/073302 describe minimal invasive approaches to mitral valve annuloplasty, using percutaneous insertion of device into the left ventricle or into the coronary sinus, in order to decrease the annulus size.

[009] US6626930 and US6575971 disclose a device and method of fastening two pieces of the valve leaflets together, improving competence of the valve.

[010] US2004/243227, US2007/244554, US2008/262609, and US2009/0287304 describe percutaneous devices which attach to the valve annulus via anchoring mechanisms and contract, thereby reducing annulus diameter in a single step.

[011] US2007/016286 discloses a transluminal collapsible heart valve designed to attach to the native annulus of the native regurgitating mitral valve and replace all in a single step. US2012/010700 provides a method for implanting a prosthetic valve apparatus that includes a one way valve and an expandable valve seating. The apparatus is anchored and secured in a newly created orifice near or at the center of the anterior valve leaflet.

[012] Today it is possible to replace an aortic valve (the valve positioned between the left ventricle and aorta) with no surgery through newly developed percutaneous procedures. In these procedures an artificial collapsed valve is delivered through the arteries and positioned inside the diseased native valve, and then expanded to replace it. To date there is yet no acceptable analogous procedure that can do the same for the mitral or tricuspid valves.

[013] Following the success of percutaneous replacement of the aortic valve, many attempts have been made to develop similar devices intended for percutaneous treatment of the mitral valve but due to the fact that this valve annulus is much bigger and amorphously shaped, and there are no lumen walls or calcific leaflets that may function as retaining surfaces like in the aortic valve, make it very difficult to prevent dislodgment of a valve expanded into place in the mitral position. Attaching a valve to the mitral annulus with anchoring features is very challenging for a percutaneous procedure and has not been very successful yet.

[014] Devices that are attached to the mitral annulus and then collapsed to reduce its diameter need to be secured very tightly and accurately to the tissue in order to withhold the high forces that are required to reduce the annulus diameter.

[015] Compared to the aortic valve percutaneous procedures, all the devices and procedures mentioned above have not been successful for the mitral valve yet.

SUMMARY OF THE INVENTION

[016] The present invention relates to a device, method and kit for helping repair a biological valve and is particularly suited for repair of mitral, tricuspid and such valves, though not necessarily limited to such implementations.

[017] In accordance with embodiments of one aspect of the invention there is provided an apparatus for performing a procedure on a heart valve annulus, the heart valve annulus having an original shape, the apparatus comprising: a tissue engaging member including a loop of wire configured to conform with at least a portion of the original shape when the loop of wire is deployed, and a plurality of anchors, each of the plurality of anchors having a pointy front end and a back end, each of the plurality of anchors having a slot that runs in a front-to-back direction, wherein the front ends of the plurality of anchors are configured for implantation into heart valve annulus tissue in a forward direction and wherein the plurality of anchors are configured so that subsequent to implantation, the plurality of anchors resist extraction from the heart valve annulus tissue in a backwards direction, wherein the plurality of anchors are arranged with respect to the loop of wire so that when the loop of wire is deployed the plurality of anchors are distributed about the loop of wire with the front ends of the plurality of anchors facing the heart valve annulus and with the loop of wire passing through the slots in the plurality of anchors. The apparatus further includes means for implanting the plurality of anchors into the heart valve annulus tissue so that the tissue engaging member becomes affixed to the heart valve annulus.

[018] In some embodiments, the loop of wire comprises a closed loop. In some embodiments, the at least a portion of the original shape comprises at least a 270° portion of the original shape. In some embodiments, each of the plurality of anchors includes a barb that, subsequent to implantation, resists extraction from the heart valve annulus tissue in a backwards direction. In some embodiments, each of the plurality of anchors the back end of the slot is enlarged to form an eyelet. In some embodiments, in each of

the plurality of anchors the slot begins near the front end of the anchor and ends near the back end of the anchor, and wherein, during implantation, forward motion of the plurality of anchors is limited when the ends of the slots encounter the loop of wire.

[019] In some embodiments, the tissue engaging member further includes a plurality of tubes threaded onto the loop of wire between the plurality of anchors, wherein an outer surface of the tubes comprises a material that promotes tissue growth. In some embodiments, the tissue engaging member further includes a second loop of wire that is threaded through the inside the plurality of tubes, and wherein the second loop of wire comprises a closed loop.

[020] In some embodiments, at least a portion of the second loop of wire is surrounded by a material that inhibits tissue growth. In some embodiments, the plurality of anchors comprises at least six anchors.

[021] In some embodiments, the means for implanting comprises a plurality of compressed springs configured to, respectively, implant the plurality of anchors into the heart valve annulus tissue so that the tissue engaging member becomes affixed to the heart valve annulus. In some embodiments, the means for implanting comprises a plurality of pull wires configured to, respectively, implant the plurality of anchors into the heart valve annulus tissue so that the tissue engaging member becomes affixed to the heart valve annulus.

[022] In some embodiments, the loop of wire comprises a closed loop, wherein each of the plurality of anchors includes a barb that, subsequent to implantation, resists extraction from the heart valve annulus tissue in a backwards direction, and wherein the plurality of anchors comprises at least six anchors. In some embodiments, the means for implanting comprises a plurality of compressed springs configured to, respectively, implant the plurality of anchors into the heart valve annulus tissue so that the tissue engaging member becomes affixed to the heart valve annulus. In some embodiments, the means for implanting comprises a plurality of pull wires configured to, respectively, implant the plurality of anchors into the heart valve annulus tissue so that the tissue engaging member becomes affixed to the heart valve annulus.

[023] In some embodiments, the apparatus further comprises a catheter having a distal end; and a scaffold comprising a plurality of support arms configured to support the plurality of anchors in position adjacent to the heart valve annulus in a position at which

the means for implanting can implant the plurality of anchors into the heart valve annulus tissue.

[024] In some embodiments, the heart valve annulus is a mitral valve annulus, and the apparatus further comprises: a catheter having a distal end; and a scaffold comprising a plurality of support arms, wherein the scaffold is configured for deployment when the distal end of the catheter is positioned in the left atrium and the scaffold is further configured to support the plurality of anchors in position adjacent to the upper surface of the mitral valve annulus in a position at which the means for implanting can implant the plurality of anchors into the mitral valve annulus, wherein the catheter is configured to push the plurality of anchors towards the upper surface of the mitral valve annulus prior to implanting of the plurality of anchors.

[025] In some embodiments, the apparatus further comprises a balloon configured for delivery in a deflated state via the catheter, and configured for inflation while at least part of the balloon is positioned the left ventricle, and wherein the catheter is configured to pull the balloon towards the mitral valve annulus prior to implanting of the plurality of anchors.

[026] In some embodiments, the apparatus further comprises a balloon configured for delivery in a deflated state via the catheter, wherein when the balloon is inflated, the balloon guides the tissue engaging member into position for implantation into the mitral valve annulus.

[027] In accordance with embodiments of another aspect of the invention there is provided a method for performing a procedure on a heart valve annulus, the heart valve annulus having an original shape. The method comprises the steps of: delivering a loop of wire to the vicinity of heart valve annulus so that the loop of wire conforms with at least a portion of the original shape; delivering a plurality of anchors to the vicinity of heart valve annulus, each of the plurality of anchors having a pointy front end and a back end, each of the plurality of anchors having a slot that runs in a front-to-back direction, wherein the front ends of the plurality of anchors are configured for implantation into heart valve annulus tissue in a forward direction and wherein the plurality of anchors are configured so that subsequent to implantation, the plurality of anchors resist extraction from the heart valve annulus tissue in a backwards direction, wherein the plurality of anchors are distributed about the loop of wire with the front ends of the plurality of anchors facing the heart valve annulus and with the loop of wire passing through the slots

in the plurality of anchors; and implanting the plurality of anchors into the heart valve annulus.

[028] In some embodiments, the loop of wire comprises a closed loop. In some embodiments, the at least a portion of the original shape comprises at least a 270° portion of the original shape. In some embodiments, each of the plurality of anchors the slot begins near the front end of the anchor and ends near the back end of the anchor, and wherein, during the implanting step, forward motion of the plurality of anchors is limited when the ends of the slots encounter the loop of wire.

[029] In some embodiments, the method further comprises the step of delivering a plurality of tubes to the vicinity of heart valve annulus, wherein the plurality of tubes are threaded onto the loop of wire between the plurality of anchors and wherein an outer surface of the tubes comprises a material that promotes tissue growth.

[030] In some embodiments, the method further comprises the step of delivering a second loop of wire to the vicinity of heart valve annulus that is threaded through the inside the plurality of tubes, wherein the second loop of wire comprises a closed loop. In some embodiments, the plurality of anchors comprises at least six anchors.

[031] In some embodiments, the implanting step comprises driving the plurality of anchors into the heart valve annulus using a plurality of springs. In some embodiments, the implanting step comprises driving the plurality of anchors into the heart valve annulus using a plurality of pull wires. In some embodiments, the heart valve annulus is a mitral valve annulus, and the method further comprises the step of pressing the plurality of anchors towards an upper surface of the mitral valve annulus, wherein the pressing step is implemented prior to the implanting step and subsequent to the steps of delivering the loop of wire and delivering the plurality of anchors.

[032] In some embodiments, the method further comprises the step of pulling an inflated balloon that is disposed at least partially in a left ventricle towards the mitral valve annulus, wherein the pulling step and the pressing step are performed simultaneously. In some embodiments, the method further comprises the step of inflating a balloon to guide the anchors into position for implantation into the mitral valve annulus.

[033] In accordance with embodiments of another aspect of the invention there is provided an apparatus for performing a procedure on a mitral valve, the apparatus comprising: a tissue engaging member including a loop of wire configured to contact leaflets of the mitral valve when the loop of wire is deployed, wherein the loop of wire

comprises a closed loop, and a plurality of anchors, each of the plurality of anchors having a pointy front end and a back end, each of the plurality of anchors having a slot that runs in a front-to-back direction, wherein the front ends of the plurality of anchors are configured for implantation into the leaflets in a forward direction and wherein the plurality of anchors are configured so that subsequent to implantation, the plurality of anchors resist extraction from the leaflets in a backwards direction, wherein the plurality of anchors are arranged with respect to the loop of wire so that when the loop of wire is deployed the plurality of anchors are distributed about the loop of wire with the front ends of the plurality of anchors facing the leaflets and with the loop of wire passing through the slots in the plurality of anchors. The apparatus further includes means for implanting the plurality of anchors into the leaflets so that the tissue engaging member becomes affixed to the leaflets.

[034] In some embodiments, each of the plurality of anchors includes a barb that, subsequent to implantation, resists extraction from the leaflets in a backwards direction. In some embodiments, each of the plurality of anchors the slot begins near the front end of the anchor and ends about halfway between the front end of the anchor and the back end of the anchor, and during implantation, forward motion of the plurality of anchors is limited when the ends of the slots encounter the loop of wire.

[035] In some embodiments, the plurality of anchors comprises at least six anchors. In some embodiments, the means for implanting comprises a plurality of compressed springs configured to, respectively, implant the plurality of anchors into the leaflets so that the tissue engaging member becomes affixed to the leaflets.

[036] In some embodiments, the means for implanting comprises a plurality of pull wires configured to, respectively, implant the plurality of anchors into the leaflets so that the tissue engaging member becomes affixed to the leaflets.

[037] In some embodiments, the apparatus further comprises a catheter having a distal end; and a scaffold comprising a plurality of support arms configured to support the plurality of anchors in position adjacent to the leaflets in a position at which the means for implanting can implant the plurality of anchors into the leaflets.

[038] In some embodiments, the apparatus further comprises: a catheter having a distal end; and a scaffold comprising a plurality of support arms, wherein the scaffold is configured for deployment when the distal end of the catheter is positioned in the left ventricle and the scaffold is further configured to support the plurality of anchors in

position adjacent to the leaflets in a position at which the means for implanting can implant the plurality of anchors into the leaflets, wherein the catheter is configured to push the plurality of anchors towards the leaflets prior to implanting of the plurality of anchors.

[039] In some embodiments, the apparatus further comprises: a catheter having a distal end; and a scaffold comprising a plurality of support arms, wherein the scaffold is configured for deployment when the distal end of the catheter is positioned in the left ventricle and the scaffold is further configured to support the plurality of anchors in position adjacent to the leaflets in a position at which the means for implanting can implant the plurality of anchors into the leaflets, wherein the catheter is configured to pull the plurality of anchors towards the leaflets prior to implanting of the plurality of anchors.

[040] In accordance with embodiments of another aspect of the invention there is provided a method for performing a procedure on a mitral valve comprising the steps of: delivering a loop of wire to a vicinity of leaflets of the mitral valve, wherein the loop of wire comprises a closed loop; delivering a plurality of anchors to the vicinity of the leaflets, each of the plurality of anchors having a pointy front end and a back end, each of the plurality of anchors having a slot that runs in a front-to-back direction, wherein the front ends of the plurality of anchors are configured for implantation into the leaflets in a forward direction and wherein the plurality of anchors are configured so that subsequent to implantation, the plurality of anchors resist extraction from the leaflets in a backwards direction, wherein the plurality of anchors are distributed about the loop of wire with the front ends of the plurality of anchors facing the leaflets and with the loop of wire passing through the slots in the plurality of anchors; and implanting the plurality of anchors into the leaflets.

[041] In some embodiments, each of the plurality of anchors the slot begins near the front end of the anchor and ends about halfway between the front end of the anchor and the back end of the anchor, and wherein, during the implanting step, forward motion of the plurality of anchors is limited when the ends of the slots encounter the loop of wire.

[042] In some embodiments, the plurality of anchors comprises at least six anchors. In some embodiments, the implanting step comprises driving the plurality of anchors into the leaflets using a plurality of springs. In some embodiments, the implanting step comprises driving the plurality of anchors into the leaflets using a plurality of pull wires.

[043] In some embodiments, the method further comprises the step of pressing the plurality of anchors towards the leaflets, wherein the pressing step is implemented prior to the implanting step and subsequent to the steps of delivering the loop of wire and delivering the plurality of anchors.

[044] In accordance with embodiments of another aspect of the invention there is provided an apparatus for cinching a heart valve annulus, the heart valve annulus having an original shape, the apparatus comprising: a tissue engaging member including a first loop of wire configured to conform with at least a portion of the original shape when the first loop of wire is deployed, a plurality of anchors, each of the plurality of anchors having a pointy front end and a back end, each of the plurality of anchors having a slot that runs in a front-to-back direction, wherein the front ends of the plurality of anchors are configured for implantation into heart valve annulus tissue in a forward direction and wherein the plurality of anchors are configured so that subsequent to implantation, the plurality of anchors resist extraction from the heart valve annulus tissue in a backwards direction, wherein the plurality of anchors are arranged with respect to the first loop of wire so that when the first loop of wire is deployed the plurality of anchors are distributed about the first loop of wire with the front ends of the plurality of anchors facing the heart valve annulus and with the first loop of wire passing through the slots in the plurality of anchors, a plurality of tubes threaded onto the first loop of wire between the plurality of anchors, wherein an outer surface of the tubes comprises a material that promotes tissue growth, and a second loop of wire that is threaded through the inside the plurality of tubes, the second loop of wire having two ends that are configured so that when the tissue engaging member is affixed to the heart valve annulus, pulling the two ends will cinch the heart valve annulus; and means for implanting the plurality of anchors into the heart valve annulus tissue so that the tissue engaging member becomes affixed to the heart valve annulus.

[045] In some embodiments, at least a portion of the second loop of wire is surrounded by a material that inhibits tissue growth. In some embodiments, the at least a portion of the original shape comprises at least a 270° portion of the original shape. In some embodiments, wherein each of the plurality of anchors includes a barb that, subsequent to implantation, resists extraction from the heart valve annulus tissue in a backwards direction. In some embodiments, in each of the plurality of anchors the back end of the slot is enlarged to form an eyelet. In some embodiments, each of the plurality

of anchors the slot begins near the front end of the anchor and ends near the back end of the anchor, and wherein, during implantation, forward motion of the plurality of anchors is limited when the ends of the slots encounter the first loop of wire.

[046] In some embodiments, the plurality of anchors comprises at least six anchors. In some embodiments, the means for implanting comprises a plurality of compressed springs configured to, respectively, implant the plurality of anchors into the heart valve annulus tissue so that the tissue engaging member becomes affixed to the heart valve annulus. In some embodiments, the means for implanting comprises a plurality of pull wires configured to, respectively, implant the plurality of anchors into the heart valve annulus tissue so that the tissue engaging member becomes affixed to the heart valve annulus.

[047] In some embodiments, each of the plurality of anchors includes a barb that, subsequent to implantation, resists extraction from the heart valve annulus tissue in a backwards direction, wherein the plurality of anchors comprises at least six anchors, and wherein the means for implanting comprises a plurality of compressed springs configured to, respectively, implant the plurality of anchors into the heart valve annulus tissue so that the tissue engaging member becomes affixed to the heart valve annulus. In some embodiments, each of the plurality of anchors includes a barb that, subsequent to implantation, resists extraction from the heart valve annulus tissue in a backwards direction, wherein the plurality of anchors comprises at least six anchors, and wherein the means for implanting comprises a plurality of pull wires configured to, respectively, implant the plurality of anchors into the heart valve annulus tissue so that the tissue engaging member becomes affixed to the heart valve annulus.

[048] In some embodiments, the apparatus further comprises: a catheter having a distal end; and a scaffold comprising a plurality of support arms configured to support the plurality of anchors in position adjacent to the heart valve annulus in a position at which the means for implanting can implant the plurality of anchors into the heart valve annulus tissue.

[049] In some embodiments, the heart valve annulus is a mitral valve annulus, and the apparatus further comprises: a catheter having a distal end; and a scaffold comprising a plurality of support arms, wherein the scaffold is configured for deployment when the distal end of the catheter is positioned in the left atrium and the scaffold is further configured to support the plurality of anchors in position adjacent to the upper

surface of the mitral valve annulus in a position at which the means for implanting can implant the plurality of anchors into the mitral valve annulus, wherein the catheter is configured to push the plurality of anchors towards the upper surface of the mitral valve annulus prior to implanting of the plurality of anchors.

[050] In some embodiments, the apparatus further comprises a balloon configured for delivery in a deflated state via the catheter, and configured for inflation while at least part of the balloon is positioned the left ventricle, and wherein the catheter is configured to pull the balloon towards the mitral valve annulus prior to implanting of the plurality of anchors.

[051] In some embodiments, the apparatus further comprises a balloon configured for delivery in a deflated state via the catheter, wherein when the balloon is inflated, the balloon guides the tissue engaging member into position for implantation into the mitral valve annulus.

[052] In accordance with embodiments of another aspect of the invention there is provided a method for cinching a heart valve annulus, the heart valve annulus having an original shape. The method comprising the steps of: delivering a first loop of wire to the vicinity of heart valve annulus so that the first loop of wire conforms with at least a portion of the original shape; delivering a plurality of anchors to the vicinity of heart valve annulus, each of the plurality of anchors having a pointy front end and a back end, each of the plurality of anchors having a slot that runs in a front-to-back direction, wherein the front ends of the plurality of anchors are configured for implantation into heart valve annulus tissue in a forward direction and wherein the plurality of anchors are configured so that subsequent to implantation, the plurality of anchors resist extraction from the heart valve annulus tissue in a backwards direction, wherein the plurality of anchors are distributed about the first loop of wire with the front ends of the plurality of anchors facing the heart valve annulus and with the first loop of wire passing through the slots in the plurality of anchors; delivering a plurality of tubes to the vicinity of heart valve annulus, wherein the plurality of tubes are threaded onto the first loop of wire between the plurality of anchors and wherein an outer surface of the tubes comprises a material that promotes tissue growth; delivering a second loop of wire to the vicinity of heart valve annulus, wherein the second loop of wire is threaded through the inside the plurality of tubes and has a first end and a second end; implanting the plurality of anchors

into the heart valve annulus; and cinching the second loop of wire by pulling on the first end and the second end.

[053] In some embodiments, the at least a portion of the original shape comprises at least a 270° portion of the original shape. In some embodiments, in each of the plurality of anchors the slot begins near the front end of the anchor and ends near the back end of the anchor, and wherein, during the implanting step, forward motion of the plurality of anchors is limited when the ends of the slots encounter the first loop of wire. In some embodiments, the plurality of anchors comprises at least six anchors.

[054] In some embodiments, the implanting step comprises driving the plurality of anchors into the heart valve annulus using a plurality of springs. In some embodiments, the implanting step comprises driving the plurality of anchors into the heart valve annulus using a plurality of pull wires.

[055] In some embodiments, the heart valve annulus is a mitral valve annulus, and the method further comprises the step of pressing the plurality of anchors towards an upper surface of the mitral valve annulus, wherein the pressing step is implemented prior to the implanting step and subsequent to the steps of delivering the first loop of wire and delivering the plurality of anchors.

[056] In some embodiments, the method further comprising the step of pulling an inflated balloon that is disposed at least partially in a left ventricle towards the mitral valve annulus, wherein the pulling step and the pressing step are performed simultaneously.

[057] In some embodiments, the method further comprises the step of inflating a balloon to guide the anchors into position for implantation into the mitral valve annulus.

BRIEF DESCRIPTION OF THE DRAWINGS

[058] The present invention will be understood and appreciated more fully from the following detailed description taken in conjunction with the appended drawings in which:

[059] Fig. 1 is a front partial cut-away view of an embodiment of a heart valve repair device of the present invention;

[060] Fig. 2 is an enlarged perspective view of the device of Fig. 1;

[061] Fig. 3 is a perspective view of an implant or tissue engaging member of the present device;

[062] Figs. 4-6 are perspective views of an anchor launching mechanism of the device of Fig. 1;

[063] Figs. 7 and 7a are perspective views of anchors of the present device;

[064] Figs. 8-10 are perspective views of an another embodiment of the tissue engaging member;

[065] Figs. 11 and 12 are perspective views of an exemplary delivery system for the present device;

[066] Fig. 13 is a front partially cut-away view of a heart with the implant affixed to a mitral valve from above the valve;

[067] Fig. 14 is a perspective view of a cinching mechanism of the device;

[068] Figs. 15-17 are perspective views of additional embodiments of anchors;

[069] Figs. 18 and 19 are perspective views of embodiments of anchor launching mechanisms;

[070] Figs. 20-22 are front partially cut-away views of a heart with the implant affixed to a mitral valve from below the valve;

[071] Figs. 23-27 and 27a are perspective views of further embodiments of anchor launching mechanisms;

[072] Figs. 29-34 are perspective views of implant deployment mechanisms;

[073] Figs. 35-39 are perspective views illustrating the device in use in conjunction with an implantable device;

[074] Fig. 40 is a perspective partially cut-away view of the heart with the implant deployed for use on a tricuspid valve;

[075] Fig. 41 is a perspective partially cut-away view of the heart with the implant deployed via the left atrium wall;

[076] Fig. 42 is a view illustrating manual cinching of the device after tissue healing; and

[077] Fig. 43 is a perspective partially cut-away view of the heart illustrating mechanical cinching of the device after tissue healing.

[078] The following detailed description of embodiments of the invention refers to the accompanying drawings referred to above. Dimensions of components and features shown in the figures are chosen for convenience or clarity of presentation and are not necessarily shown to scale. Wherever possible, the same reference numbers will be used throughout the drawings and the following description to refer to the same and like parts.

DESCRIPTION OF EMBODIMENTS OF THE INVENTION

[079] A heart valve repair device comprising an implant and delivery system is delivered into the heart in four sequential stages: In the first stage the implant and support scaffold are advanced in a collapsed configuration inside a capsule through the vascular system to the valve annulus (preferably the Mitral annulus but can be also the Tricuspid annulus). In the second stage after positioning the capsule close to the annulus a support scaffold is pushed outside of the capsule and the implant which is attached to the scaffold is spread into a round or D shape circumferential ring onto the valve annulus in 3 optional ways:

[080] 1) On the inflow side of the valve with attachment anchors pointing from the atrium side to the ventricle side;

[081] 2) On the inflow side of the valve with attachment anchors pointing from the ventricle side to the atrium side; and

[082] 3) On the outflow side of the valve with attachment anchors pointing from the ventricle side to the atrium side.

[083] In the third stage after the implant is spread out, all the anchors are launched into the tissue at once or in a sequential manner and affix the implant to the tissue. The same action also separates the implant from the support scaffold and delivery system. In the fourth stage the scaffold is retracted and collapsed back into the delivery capsule and the delivery system is withdrawn out of the body.

[084] It is important to note that in some embodiments the spread implant conforms at least partially to the valve annulus shape, and in some embodiments the spread implant does not conform at all to the valve annulus shape, but is just affixed to the valve leaflets and is retained there for a few minutes until a valve prosthesis is deployed into it as will be described later on.

[085] After the implant is attached to the valve tissue it is possible to treat the valve insufficiency in 5 optional ways:

[086] 1) By direct annuloplasty which impose cinching of the implant attached to the valve annulus, hence reducing the annulus diameter and improving valve leaflets coaptation;

[087] 2) By restricting annulus dilatation over time due to the constant perimeter of the implant which is attached to the valve annulus and gets embedded into the tissue over time through tissue growth;

[088] 3) By facilitating a support ring for valve prosthesis to be implanted at a later procedure after the implant which is attached to the valve annulus gets embedded into the tissue over time through tissue growth;

[089] 4) By performing annuloplasty at a later stage in a different procedure weeks or months later after the implant which is attached to the valve annulus gets embedded into the tissue over time through tissue growth; and

[090] 5) By facilitating a support ring for valve prosthesis that can be implanted into the ring during the same procedure right after the ring is attached to the valve leaflets.

[091] Illustrative embodiments of the invention are described below. In the interest of clarity, not all features/components of an actual implementation are necessarily described.

[092] Fig. 1 shows an embodiment of a mitral valve adjustment/repair implant 10 of the present invention, implanted onto a bio-valve, exemplified by mitral valve M of the heart. Implant 10 comprises: a tissue engaging member 12, comprising a loop 14 of wire and a plurality of tissue anchors 16 associated with the loop and having and an elongated slot 17 (Fig. 5); a scaffold or implant positioning device 18, in this embodiment comprising plurality of support arms 20; and an anchor launching mechanism 22 (Figs. 2-7). Implant 10 is typically positioned in proximity of the mitral valve M via a delivery catheter C. The loop 14 of wire is preferably made of metal wire, but in alternative embodiments the wire may be a non-metallic material. Note that as used herein, "wire" includes metal and/or non-metallic materials.

[093] Figs. 2 shows an enlarged view of the device in Fig. 1 illustrating anchor launching mechanism 22 in a ready for deployment (launching) and deployed state, respectively; Elongated slot 17 of anchors 16 allow loop 14 to be retained by (operably attached to) the anchors - which will be explained further herein below. Fig. 3 shows an embodiment of implant 10 in its configuration when implanted, as will be discussed further below.

[094] Figs. 4-6 show details of anchor launching mechanism 22, which comprises a housing 24, typically cylindrical; an anchor launching biasing mechanism, such as coil spring 26 disposed within the housing; and a spring actuator wire 28, having

a bent distal end 29, passing through elongated slot 17 and protruding through a window 30 of housing 24. Bent distal end 29 maintains spring 26 is a compressed configuration. Actuator wire 28 passes longitudinally/coaxially through coil spring 26. Implant support arms 20 are respectively attached to housings 24, for example by welding. It should be noted that actuator wire 28 can be made of any appropriate material and is not limited to metal.

[095] Housing 24 has an open end 32 and a spring retention end 34, which in some embodiments comprises a crimped portion 36 or other such spring retention mechanism, to provide a launching base for spring 26. In some embodiments, to prevent spring 26 from being ejected from (falling out of) housing 24, spring has a hooked proximal end 38 adapted to hook at retention end 34 of the housing. As can be seen, loop 14 is threaded through each elongated slot 17 of tissue anchors 16. As best seen in Fig. 4, in some embodiments, housing 24 has a pair of elongated recesses 40 at open end 32 whereby loop 14 can pass. Figs. 4 and 5 show anchors 16 in a pre-launch state where spring 26 is compressed, and Fig. 6 shows the anchors in a launched state with the spring in its normally expanded configuration.

[096] As shown, tissue anchors 16 are typically spaced apart all along loop 14 and loop 14 is threaded through elongated slot 17, allowing the tissue anchor to move (be launched), typically more or less perpendicular (although in some embodiments at an angle) with respect to the loop. It should be noted that loop 14 can be made of any appropriate material and is not limited to metal. Note that while eight anchors are depicted in all the illustrated embodiments, the number of anchors can be varied. Preferably at least six anchors are used.

[097] With reference to Fig. 7, in some embodiments, each anchor 16 has a proximal portion 42 including a spring interfacing portion exemplified by a pair of flat shoulders 44. Anchors 16 also have a pointy front end 46, typically with one or more barbs 48. After an anchor is implanted in the forward direction, the barbs 48 resist extraction of the anchor 16 in a backwards direction. In some embodiments, elongated slot 17 has a relatively large or bulbous open portion or eyelet 50 adjacent proximal portion 42, which can be useful to provide additional space for bent distal end 29 to pass through the elongated slot along with loop 14.

[098] Figs. 8-10 shows a modification of the implant wherein loop 14 has a plurality of tissue growth-promotion tubes 52 coaxially surrounding the loop between

anchor positions. In some embodiments, tissue growth-promotion tubes 52 have respective tissue growth inhibiting liners or surfaces 54 (Fig. 10). Tissue growth-promotion tubes 52 are made of a material and/or substance adapted to promote and facilitate the growth of tissue thereon, for example an appropriate fabric or coating. If indeed in the form of liners, tissue growth inhibiting liners 54 are disposed tissue growth-promotion tubes 52, e.g. coaxially, and include tissue growth inhibiting material/substance.

[099] Figs. 9 and 10 additionally show another embodiment wherein there are two loops, the aforementioned loop 14 and a relatively sturdy auxiliary loop 56 to provide additional robustness to the implant if so desired. Fig. 10 shows a modification wherein auxiliary loop further includes a proximal portion 58 that can be used to position the implant 10, in addition to or in place of the above mentioned implant positioning device 18.

[0100] **Operation:** implant 10 is deployed to a position adjacent the bio-valve (e.g. Mitral valve M) via/through delivery catheter C (see Figs. 11 and 12; and also Figs. 1 and 2). When implant 10 is appropriately located, using support arms 20 and/or auxiliary loop 56 with its proximal portion 58, actuator wire 28 of each anchor launching mechanism 22 is retracted thereby withdrawing their bent distal ends 29 from respective windows 30 of housings 24. As a result, springs 26 are released from their compressed state to their expanded state thereby launching tissue anchors 16 into the bio-valve tissue. Typically, pointy end 46 of each anchor 16 enters the tissue, and barbs 48 help to prevent inadvertent detachment of the anchors.

[0101] Fig. 13 illustrates implant 10 connected to the tissue of mitral valve M of the heart after the launching of tissue anchors 16 into the tissue. Implant 10 is positioned on the top of the mitral valve M, as a result of being inserted into the heart in a manner such as shown in Fig. 1, and anchors 16 face generally downward. After the implantation natural tissue growth start to occur all around the parts of implant 10 that are within the tissue notably the anchors, and later on tissue growth will cover also parts of the implant at close proximity to the tissue surface. When tissue growth fills the anchors slot 17 they become mechanically locked within the tissue, and over time the entire implant 10 will get embedded in the valve annulus tissue. Since the implant is largely comprised of loop 14 which is made of non elastic substance, further annulus dilatation over time due to progression of the valve regurgitation disease is prevented.

[0102] With reference to Fig. 14, in some embodiments, the implant further comprises a cinching mechanism 60, for example wherein loop 14 is not in a closed loop configuration rather has generally adjacent free ends 62 and 64. The ring-like portion of loop 14 passes through elongated slots 17 of anchors 16 (and in suitable embodiments, through tissue growth-promotion tubes 52), as before. After sufficient tissue grows on implant 10, which typically takes one week to several months, depending on the tissue growth rate, the implant may be cinched via pulling on one or both of the free ends 62 and/or 64 to reduce the diameter of tissue engaging member 12, (however, in some implementations of the operation, cinching action is not required, and could be excluded from procedure). Free ends 62 and 64 may extend outside the patient's body or remain under the skin at the upper portion of the chest, much like pace maker leads. The tissue growth causes implant 10 to be embedded and integrated to the valve annulus. In addition, tissue growth within elongated slot 17 helps secure anchors 16 and prevents the implant from being dislodged from the valve annulus.

[0103] Fig. 14 further illustrates a D-shaped loop 14, in contrast to the circular or oval shaped loops illustrated in the aforementioned figures. D-shaped loop 14 is particularly suited for use with a human mitral heart valve. In this regard, it should be understood that loop 14 can be configured by choice or design to appropriately correspond to the particular bio-valve for which repair is required.

[0104] Fig. 15 shows another embodiment wherein instead of anchors 16 engaging loop 14 via elongated slot 17, the anchors pass thru a coaxial tube 66 coaxially surrounding the loop - the tube could be, for example a tissue growth promotion tube such as tissue growth-promotion tubes 52. Retention of anchors 16 with coaxial tube 66 is aided by a retention hook 68 at the proximal end of the anchors.

[0105] Figs. 16 and 17 depict an embodiment where anchor 16 has a cylindrical shape, similar to housing 24 and no such housing is required. In this case spring 26 is held in compression between end 34 of cylindrical anchor 16 and a spring launching base, exemplified by a launching base ring 70, attached to implant support arms 20. End 34 now provides the function of the aforementioned flat shoulders 44; and launching base ring provides the function of the aforementioned crimped portion 36. When actuator wire 28 is retracted, its bent distal end 29 (here, illustrated in the form of a half-loop) is retracted from window 30 thereby releasing cylindrical anchor 16 so that spring 26 expands to launch the anchor.

[0106] Figs. 18 and 19 shows implant positioning device 18 configured, *mutatis mutandis*, wherein anchor launching mechanism 22 is adapted to launch anchors 16 into the tissue in a generally upward direction (i.e. from the ventricle side to the atrium side). This embodiment is particularly useful in the case where the tissue engaging member 12 serves as a support to prevent dislodgement of a valve prosthesis that can be expanded into it right after the tissue engaging member 12 has been deployed.

[0107] Figs. 20-24 illustrate embodiments adapted for situations where launching anchors 16 upwardly may also be used in cases where access to the insufficient valve is from below, for example via the Apex (see Fig. 20), is preferable rather than from above. Figs. 20 and 22 show loop 14 disposed under the Mitral valve leaflets and Fig. 21 shows loop 14 disposed onto the Mitral valve leaflets M as the anchors 16 penetrates through the leaflets pointing from the ventricle side to the atrium side.

[0108] Figs. 23 and 24 show the pre-launch and launch situations for upward launching of anchors 16. Fig. 23 further illustrates that catheter C can be used to help orient the angle of housings 24, and thus the launch angle of anchors 16. If the distance between catheter C and loop 14 is relatively small, anchors 16 tends to be positioned and launched at a greater angle (relative to being launched perpendicular to loop 14, as was shown in Figs. 2 and 3, for example). Adjustment of the launch angle, i.e. pivoting of anchors angle, is made possible by the shape of the support arms 20 to which the housing 24 is attached. Fig. 24 also illustrates another modification wherein anchors 16 comprise multiple barbs 48 and wherein elongated slot 17 extends about half-way within the length of the anchors.

[0109] Figs. 25-27 and 27a illustrate particular embodiments wherein anchor launching mechanism 22 is adapted to be used with tissue anchors 16 that are launched in a generally upward direction; and can be actuated by a direct pull, or by a mechanism removed from the valve area. Anchor launching mechanism 22 comprises actuation wire 28 and housing 24, however the mechanism does not include spring 26 disposed in the housing. Regardless, for rapid actuation purposes (anchor launch), anchor launch mechanism 22 may further include an external launch actuator device, typically including a spring (not shown), for example, at the proximal end of catheter C, to pull on actuation wire 28. When the catheter approaches from the inflow side of the valve, and routes the anchors so that they are below the valve with the tip directed from the ventricle side to the atrium side, this configuration and approach to the valve permits pull wires to be used.

[0110] For the purposes of these embodiments, anchor 16 may be modified to further comprise an actuation wire eyelet 72 where-through actuation wire 28. Distal end 29 of actuation wire 28 is threaded through eyelet 72 and typically has a hook-like configuration while disposed within housing 24 (Figs. 25 and 27). Pulling on actuator wire 28 proximal end to pull (launch) anchor 16 as a result of pulling at eyelet 72 (Fig. 26). In such embodiments, housing 24 need not include a window such as window 30, nor does not need a crimped portion 36 or other such spring retention mechanism, as there is no spring in the housing. Figs. 27 and 27a illustrates a modification wherein instead of eyelet 72; each anchor 16 has a actuator-wire distal-end receiving portion such as recess 74, which operates to launch anchors 16 in the same fashion as noted above.

[0111] Figs. 28-30 show embodiments, wherein implant 10 further comprises a loop-arrangement/anchor-orientation mechanism 76 useful for arranging the position and/or shape of loop 14 and/or for orienting the angle of housings 24, and thereby orienting the launch angle of tissue anchors 16. Anchor orientation mechanism 76 includes a plurality of curved arrangement leads 78 respectively attached to at least some of housings 24, for example by welding. Leads 78 may be an extension of implant support arms 20 and may be arranged to cross at a singular intersection point 80. Leads 78 are attached (e.g. by welding) to housing 24. Thus, leads 78 of orientate mechanism 76 are movable to arrange loop 14 in a desired location and depending on the shape of the leads, the angle of housings 24, and thus anchors 16, can be determined.

[0112] Regarding the launch angle of anchors 16, in some embodiments, leads 78 can be attached "ad hoc" prior to insertion into a patient, whereby, depending on the attachment location, arrangement leads 78 also be used to orient anchors 16 i.e. control the angle at which the anchors enter the tissue (i.e. changing the length or shape of one or more leads 78 will thus change the angle of the anchors, e.g. shortening the that length will cause the anchors to point outward, whereas increasing that length will bring intersection point 80 farther from loop 14 and thus angle the anchors more parallel to each other (less outward). In such case, leads 78 will not be welded to housings 24, rather there will be included an "ad hoc" connection or fastening arrangement (not shown), whereby the leads and housings are connected at more than one location along the leads. Arrangement/orientation mechanism 76 can be useful for arranging the shape of loop 14 as well as positioning the loop and orienting the anchor angle. In alternative embodiments, loop-arrangement/anchor-orientation mechanism 76 either has a

predetermined shape, such as a nipple shape (Figs. 29 and 30) or is adapted to allow its shape to be changed; i.e. leads 78 can be bent.

[0113] Figs. 31-34 show embodiments wherein loop arrangement and/or implant positioning device 18 comprises an inflatable balloon 82. The figures show exemplary balloons 82 useful for a) making sure support arms 20 are fully expanded before deploying implant 10, b) make sure that loop 14 is concentric with the valve annulus prior to implantation, and c) facilitating an interference step or backing against which to press to be used for pressing implant positioning device 18 and implant 10 onto the valve annulus before implantation as illustrated in figure 34. Fig. 31 illustrates an oval balloon 82; Figs. 32-34 illustrate a droplet-shaped or bulbous balloon 82.

[0114] As seen in Fig. 34, as well as being useful to orient loop 14 relative to the valve annulus, the balloon can be used to secure the implant positioning device 18 and implant 10 in place during launching of anchors 16. Figs. 32 and 33 also illustrate that balloon 82 can be positioned proximally or distally with respect to loop 14 and implant positioning device 18. Since the balloon can be positioned inside the ventricle and be inflated to a diameter bigger than the diameter of biological valve annulus, it can serve as a backing against which to press positioning device 18 and implant 10 onto the valve annulus before implantation. This will ensure good contact between each of the anchor launching mechanisms 22 and the valve annulus and will create optimal penetration conditions of anchor 16 into the tissue upon launching. Furthermore, the launch angle of anchors 16 (i.e. insertion into the tissue) can be controlled by inflating/deflating balloon 82, with consideration to the size of the biological valve.

[0115] Figs. 35-37 illustrate how a device 100 (e.g., a replacement valve) can be fixed to a native valve annulus or leaflets like the mitral valve M or tricuspid valve. In this embodiment, implant 10 is first implanted and secured with anchors 16 that penetrate the valve leaflets pointing from the ventricle V side toward the atrium A side (hereinafter upwards) as in Fig. 21 and/or Fig. 22. Then, when device 100 is expanded into implant 10, the friction between anchors 16 and the device 100 secures device 100 in place. Since anchors 16 are directed generally upward, the high pressure in ventricle V helps to further enhance the anchoring of implant 10 to the valve leaflets.

[0116] Device 100 in the illustrating figures represents any suitable commercial expandable heart valve prosthesis that can be tracked in a collapsed configuration through the vascular system and delivered to the heart. It can be a self expanding prosthesis or a

balloon expanding prosthesis or any other type of expanding heart valve prosthesis. Fig. 35 further illustrates an exemplary delivery system 101 that can deliver device 100 to the heart.

[0117] Figs. 36 and 37 illustrate how implant 10 can be associated with device 100 for fixing the device to a mitral valve M (or tricuspid valve) leaflets. In this embodiment, implant 10 and device 100 are implanted via the heart's apex P, preferably, in a minimally invasive surgery as illustrated in Fig. 20. As in Fig. 22, implant 10 is first located at the proper location with respect to the bio-valve (mitral in this case) and then secured with anchors 16 facing upward, in accordance with any appropriate embodiment as described herein. After implant 10 is attached to the valve leaflets, device 100 is advanced, as shown in Fig. 36, through a delivery catheter (not shown), and expanded into implant 10 as seen in Fig. 37. Since anchors 16 are directed generally upward, the high pressure in the ventricle V helps to further enhance the anchoring of the implant 10 and device 100 to the valve leaflets. However, for the purpose of this embodiment, wherein implant 10 is configured to be particularly suited to securing a device in place such as device 100, each anchor 16 has a relatively shorter slot 17, typically extending only about half-way along the longitudinal dimension of each anchor, from about half-way along the anchor to relatively close to the anchors' pointy front end 46.

[0118] With reference to Figs. 38 and 39, when device 100 is disposed in the appropriate heart (or other biological) valve and expanded, the contact and sliding motion between the device and anchor 16 changes the angle of the anchors from typically approximately 45 degrees (Fig. 38), although, depending on the angle of support arms 20, to an angle wherein the anchors are more parallel to each other, typically substantially parallel. The movement of anchors 16 is illustrated by arc A-B in Fig. 38. In other words, anchors 16 pivots at the end of slot 17, as in Fig. 7a which is generally at mid-point 84 of the anchors. This angle change provides increased friction between anchors 16 and device 100 thereby securing the device in place.

[0119] To further explain, device 100 is expanded in the bio-valve until the device presses on a non-slotted portion 86 of anchors 16. As a result of pressing on non-slotted portion 86, that portion is forced outward, and thus the tip of the anchors 46 is moved inward, as the anchors pivot around loop 14. Since anchor tips 46 are locked within the tissue of the valve leaflet, the inward motion of the tips pulls the leaflets closer to device 100 and presses the leaflets against the device, thereby enhancing the sealing

and prevent blood flow between the native valve leaflet and the device. It should be understood that device 100 is appropriately sized for the above-described positioning.

[0120] Fig. 40 illustrates deployment of implant 10 in the tricuspid heart valve T and it should be understood that all the features and functions of the implant and delivery system as illustrated in Figs. 1 to 39 are applicable to the tricuspid valve.

[0121] Fig. 41 illustrates deployment of implant 10 through the left atrium wall rather than tracking in through the vascular system, or deploying the implant through the apex of the heart. Again, it should be understood that all the features and functions of the implant and delivery system illustrated in Figs 1 to 39 are applicable to deployment through the atrium wall.

[0122] Fig. 42 illustrates manual cinching of the device in a later procedure after tissue healing has occurred as described above with reference to Fig. 14.

[0123] Fig. 43 illustrates cinching of the device in a later procedure after tissue healing has occurred as described above with reference to Fig. 14. Using a mechanical actuator 110 that is implanted during procedure. The mechanical actuator can be actuated and operated magnetically, electrically or by any other appropriate mechanism from outside of the body.

[0124] It should be understood that the above description is merely exemplary and that there are various embodiments of the present invention that may be devised, *mutatis mutandis*, and that the features described in the above-described embodiments, and those not described herein, may be used separately or in any suitable combination; and the invention can be devised in accordance with embodiments not necessarily described above.

CLAIMS

1. An apparatus for performing a procedure on a heart valve annulus, the heart valve annulus having an original shape, the apparatus comprising:
a tissue engaging member including
a loop of wire configured to conform with at least a portion of the original shape when the loop of wire is deployed, and
a plurality of anchors, each of the plurality of anchors having a pointy front end and a back end, each of the plurality of anchors having a slot that runs in a front-to-back direction, wherein the front ends of the plurality of anchors are configured for implantation into heart valve annulus tissue in a forward direction and wherein the plurality of anchors are configured so that subsequent to implantation, the plurality of anchors resist extraction from the heart valve annulus tissue in a backwards direction, wherein the plurality of anchors are arranged with respect to the loop of wire so that when the loop of wire is deployed the plurality of anchors are distributed about the loop of wire with the front ends of the plurality of anchors facing the heart valve annulus and with the loop of wire passing through the slots in the plurality of anchors; and
means for implanting the plurality of anchors into the heart valve annulus tissue so that the tissue engaging member becomes affixed to the heart valve annulus.
2. The apparatus of claim 1, wherein the loop of wire comprises a closed loop.
3. The apparatus of claim 1, wherein the at least a portion of the original shape comprises at least a 270° portion of the original shape.
4. The apparatus of claim 1, wherein each of the plurality of anchors includes a barb that, subsequent to implantation, resists extraction from the heart valve annulus tissue in a backwards direction.
5. The apparatus of claim 1, wherein in each of the plurality of anchors the back end of the slot is enlarged to form an eyelet.
6. The apparatus of claim 1, wherein in each of the plurality of anchors the slot begins near the front end of the anchor and ends near the back end of the anchor, and wherein, during implantation, forward motion of the plurality of anchors is limited when the ends of the slots encounter the loop of wire.

7. The apparatus of claim 1, wherein the tissue engaging member further includes a plurality of tubes threaded onto the loop of wire between the plurality of anchors, wherein an outer surface of the tubes comprises a material that promotes tissue growth.
8. The apparatus of claim 7, wherein the tissue engaging member further includes a second loop of wire that is threaded through the inside the plurality of tubes, and wherein the second loop of wire comprises a closed loop.
9. The apparatus of claim 8, wherein at least a portion of the second loop of wire is surrounded by a material that inhibits tissue growth.
10. The apparatus of claim 1, wherein the plurality of anchors comprises at least six anchors.
11. The apparatus of claim 1, wherein the means for implanting comprises a plurality of compressed springs configured to, respectively, implant the plurality of anchors into the heart valve annulus tissue so that the tissue engaging member becomes affixed to the heart valve annulus.
12. The apparatus of claim 1, wherein the means for implanting comprises a plurality of pull wires configured to, respectively, implant the plurality of anchors into the heart valve annulus tissue so that the tissue engaging member becomes affixed to the heart valve annulus.
13. The apparatus of claim 1, wherein the loop of wire comprises a closed loop, wherein each of the plurality of anchors includes a barb that, subsequent to implantation, resists extraction from the heart valve annulus tissue in a backwards direction, and wherein the plurality of anchors comprises at least six anchors.
14. The apparatus of claim 13, wherein the means for implanting comprises a plurality of compressed springs configured to, respectively, implant the plurality of anchors into the heart valve annulus tissue so that the tissue engaging member becomes affixed to the heart valve annulus.
15. The apparatus of claim 13, wherein the means for implanting comprises a plurality of pull wires configured to, respectively, implant the plurality of anchors into the heart valve annulus tissue so that the tissue engaging member becomes affixed to the heart valve annulus.
16. The apparatus of claim 1, further comprising;
a catheter having a distal end; and

a scaffold comprising a plurality of support arms configured to support the plurality of anchors in position adjacent to the heart valve annulus in a position at which the means for implanting can implant the plurality of anchors into the heart valve annulus tissue.

17. The apparatus of claim 1, wherein the heart valve annulus is a mitral valve annulus, and wherein the apparatus further comprises:

a catheter having a distal end; and

a scaffold comprising a plurality of support arms, wherein the scaffold is configured for deployment when the distal end of the catheter is positioned in the left atrium and the scaffold is further configured to support the plurality of anchors in position adjacent to the upper surface of the mitral valve annulus in a position at which the means for implanting can implant the plurality of anchors into the mitral valve annulus,

wherein the catheter is configured to push the plurality of anchors towards the upper surface of the mitral valve annulus prior to implanting of the plurality of anchors.

18. The apparatus of claim 17, further comprising a balloon configured for delivery in a deflated state via the catheter, and configured for inflation while at least part of the balloon is positioned the left ventricle, and wherein the catheter is configured to pull the balloon towards the mitral valve annulus prior to implanting of the plurality of anchors.

19. The apparatus of claim 17, further comprising a balloon configured for delivery in a deflated state via the catheter, wherein when the balloon is inflated, the balloon guides the tissue engaging member into position for implantation into the mitral valve annulus.

20. A method for performing a procedure on a heart valve annulus, the heart valve annulus having an original shape, the method comprising the steps of:

delivering a loop of wire to the vicinity of heart valve annulus so that the loop of wire

conforms with at least a portion of the original shape;

delivering a plurality of anchors to the vicinity of heart valve annulus, each of the

plurality of anchors having a pointy front end and a back end, each of the

plurality of anchors having a slot that runs in a front-to-back direction, wherein

the front ends of the plurality of anchors are configured for implantation into

heart valve annulus tissue in a forward direction and wherein the plurality of anchors are configured so that subsequent to implantation, the plurality of anchors resist extraction from the heart valve annulus tissue in a backwards direction, wherein the plurality of anchors are distributed about the loop of wire with the front ends of the plurality of anchors facing the heart valve annulus and with the loop of wire passing through the slots in the plurality of anchors; and

implanting the plurality of anchors into the heart valve annulus.

21. The method of claim 20, wherein the loop of wire comprises a closed loop.
22. The method of claim 20, wherein the at least a portion of the original shape comprises at least a 270° portion of the original shape.
23. The method of claim 20, wherein in each of the plurality of anchors the slot begins near the front end of the anchor and ends near the back end of the anchor, and wherein, during the implanting step, forward motion of the plurality of anchors is limited when the ends of the slots encounter the loop of wire.
24. The method of claim 20, further comprising the step of delivering a plurality of tubes to the vicinity of heart valve annulus, wherein the plurality of tubes are threaded onto the loop of wire between the plurality of anchors and wherein an outer surface of the tubes comprises a material that promotes tissue growth.
25. The method of claim 24, further comprising the step of delivering a second loop of wire to the vicinity of heart valve annulus that is threaded through the inside the plurality of tubes, wherein the second loop of wire comprises a closed loop.
26. The method of claim 20, wherein the plurality of anchors comprises at least six anchors.
27. The method of claim 20, wherein the implanting step comprises driving the plurality of anchors into the heart valve annulus using a plurality of springs.
28. The method of claim 20, wherein the implanting step comprises driving the plurality of anchors into the heart valve annulus using a plurality of pull wires.
29. The method of claim 20, wherein the heart valve annulus is a mitral valve annulus, and wherein the method further comprises the step of pressing the plurality of anchors towards an upper surface of the mitral valve annulus, wherein the pressing step is implemented prior to the implanting step and subsequent to the steps of delivering the loop of wire and delivering the plurality of anchors.

30. The method of claim 29, further comprising the step of pulling an inflated balloon that is disposed at least partially in a left ventricle towards the mitral valve annulus, wherein the pulling step and the pressing step are performed simultaneously.

31. The method of claim 29, further comprising the step of inflating a balloon to guide the anchors into position for implantation into the mitral valve annulus.

32. An apparatus for performing a procedure on a mitral valve, the apparatus comprising:

a tissue engaging member including

a loop of wire configured to contact leaflets of the mitral valve when the loop of wire is deployed, wherein the loop of wire comprises a closed loop, and

a plurality of anchors, each of the plurality of anchors having a pointy front end and a back end, each of the plurality of anchors having a slot that runs in a front-to-back direction, wherein the front ends of the plurality of anchors are configured for implantation into the leaflets in a forward direction and wherein the plurality of anchors are configured so that subsequent to implantation, the plurality of anchors resist extraction from the leaflets in a backwards direction,

wherein the plurality of anchors are arranged with respect to the loop of wire so that when the loop of wire is deployed the plurality of anchors are distributed about the loop of wire with the front ends of the plurality of anchors facing the leaflets and with the loop of wire passing through the slots in the plurality of anchors; and

means for implanting the plurality of anchors into the leaflets so that the tissue engaging member becomes affixed to the leaflets.

33. The apparatus of claim 32, wherein each of the plurality of anchors includes a barb that, subsequent to implantation, resists extraction from the leaflets in a backwards direction.

34. The apparatus of claim 32, wherein in each of the plurality of anchors the slot begins near the front end of the anchor and ends about halfway between the front end of the anchor and the back end of the anchor, and wherein, during implantation, forward motion of the plurality of anchors is limited when the ends of the slots encounter the loop of wire.

35. The apparatus of claim 32, wherein the plurality of anchors comprises at least six anchors.
36. The apparatus of claim 35, wherein the means for implanting comprises a plurality of compressed springs configured to, respectively, implant the plurality of anchors into the leaflets so that the tissue engaging member becomes affixed to the leaflets.
37. The apparatus of claim 35, wherein the means for implanting comprises a plurality of pull wires configured to, respectively, implant the plurality of anchors into the leaflets so that the tissue engaging member becomes affixed to the leaflets.
38. The apparatus of claim 32, further comprising:
a catheter having a distal end; and
a scaffold comprising a plurality of support arms configured to support the plurality of anchors in position adjacent to the leaflets in a position at which the means for implanting can implant the plurality of anchors into the leaflets.
39. The apparatus of claim 32, wherein the apparatus further comprises:
a catheter having a distal end; and
a scaffold comprising a plurality of support arms, wherein the scaffold is configured for deployment when the distal end of the catheter is positioned in the left ventricle and the scaffold is further configured to support the plurality of anchors in position adjacent to the leaflets in a position at which the means for implanting can implant the plurality of anchors into the leaflets,
wherein the catheter is configured to push the plurality of anchors towards the leaflets prior to implanting of the plurality of anchors.
40. The apparatus of claim 32, wherein the apparatus further comprises:
a catheter having a distal end; and
a scaffold comprising a plurality of support arms, wherein the scaffold is configured for deployment when the distal end of the catheter is positioned in the left ventricle and the scaffold is further configured to support the plurality of anchors in position adjacent to the leaflets in a position at which the means for implanting can implant the plurality of anchors into the leaflets,
wherein the catheter is configured to pull the plurality of anchors towards the leaflets prior to implanting of the plurality of anchors.

41. A method for performing a procedure on a mitral valve, the method comprising the steps of:

delivering a loop of wire to a vicinity of leaflets of the mitral valve, wherein the loop of wire comprises a closed loop;

delivering a plurality of anchors to the vicinity of the leaflets, each of the plurality of anchors having a pointy front end and a back end, each of the plurality of anchors having a slot that runs in a front-to-back direction, wherein the front ends of the plurality of anchors are configured for implantation into the leaflets in a forward direction and wherein the plurality of anchors are configured so that subsequent to implantation, the plurality of anchors resist extraction from the leaflets in a backwards direction, wherein the plurality of anchors are distributed about the loop of wire with the front ends of the plurality of anchors facing the leaflets and with the loop of wire passing through the slots in the plurality of anchors; and

implanting the plurality of anchors into the leaflets.

42. The method of claim 41, wherein in each of the plurality of anchors the slot begins near the front end of the anchor and ends about halfway between the front end of the anchor and the back end of the anchor, and wherein, during the implanting step, forward motion of the plurality of anchors is limited when the ends of the slots encounter the loop of wire.

43. The method of claim 41, wherein the plurality of anchors comprises at least six anchors.

44. The method of claim 41, wherein the implanting step comprises driving the plurality of anchors into the leaflets using a plurality of springs.

45. The method of claim 41, wherein the implanting step comprises driving the plurality of anchors into the leaflets using a plurality of pull wires.

46. The method of claim 41, and wherein the method further comprises the step of pressing the plurality of anchors towards the leaflets, wherein the pressing step is implemented prior to the implanting step and subsequent to the steps of delivering the loop of wire and delivering the plurality of anchors.

47. An apparatus for cinching a heart valve annulus, the heart valve annulus having an original shape, the apparatus comprising:
a tissue engaging member including

a first loop of wire configured to conform with at least a portion of the original shape when the first loop of wire is deployed,

a plurality of anchors, each of the plurality of anchors having a pointy front end and a back end, each of the plurality of anchors having a slot that runs in a front-to-back direction, wherein the front ends of the plurality of anchors are configured for implantation into heart valve annulus tissue in a forward direction and wherein the plurality of anchors are configured so that subsequent to implantation, the plurality of anchors resist extraction from the heart valve annulus tissue in a backwards direction, wherein the plurality of anchors are arranged with respect to the first loop of wire so that when the first loop of wire is deployed the plurality of anchors are distributed about the first loop of wire with the front ends of the plurality of anchors facing the heart valve annulus and with the first loop of wire passing through the slots in the plurality of anchors,

a plurality of tubes threaded onto the first loop of wire between the plurality of anchors, wherein an outer surface of the tubes comprises a material that promotes tissue growth, and

a second loop of wire that is threaded through the inside the plurality of tubes, the second loop of wire having two ends that are configured so that when the tissue engaging member is affixed to the heart valve annulus, pulling the two ends will cinch the heart valve annulus; and

means for implanting the plurality of anchors into the heart valve annulus tissue so that the tissue engaging member becomes affixed to the heart valve annulus.

48. The apparatus of claim 47, wherein at least a portion of the second loop of wire is surrounded by a material that inhibits tissue growth.

49. The apparatus of claim 47, wherein the at least a portion of the original shape comprises at least a 270° portion of the original shape.

50. The apparatus of claim 47, wherein each of the plurality of anchors includes a barb that, subsequent to implantation, resists extraction from the heart valve annulus tissue in a backwards direction.

51. The apparatus of claim 47, wherein in each of the plurality of anchors the back end of the slot is enlarged to form an eyelet.

52. The apparatus of claim 47, wherein in each of the plurality of anchors the slot begins near the front end of the anchor and ends near the back end of the anchor, and wherein, during implantation, forward motion of the plurality of anchors is limited when the ends of the slots encounter the first loop of wire.

53. The apparatus of claim 47, wherein the plurality of anchors comprises at least six anchors.

54. The apparatus of claim 47, wherein the means for implanting comprises a plurality of compressed springs configured to, respectively, implant the plurality of anchors into the heart valve annulus tissue so that the tissue engaging member becomes affixed to the heart valve annulus.

55. The apparatus of claim 47, wherein the means for implanting comprises a plurality of pull wires configured to, respectively, implant the plurality of anchors into the heart valve annulus tissue so that the tissue engaging member becomes affixed to the heart valve annulus.

56. The apparatus of claim 47, wherein each of the plurality of anchors includes a barb that, subsequent to implantation, resists extraction from the heart valve annulus tissue in a backwards direction, wherein the plurality of anchors comprises at least six anchors, and wherein the means for implanting comprises a plurality of compressed springs configured to, respectively, implant the plurality of anchors into the heart valve annulus tissue so that the tissue engaging member becomes affixed to the heart valve annulus.

57. The apparatus of claim 47, wherein each of the plurality of anchors includes a barb that, subsequent to implantation, resists extraction from the heart valve annulus tissue in a backwards direction, wherein the plurality of anchors comprises at least six anchors, and wherein the means for implanting comprises a plurality of pull wires configured to, respectively, implant the plurality of anchors into the heart valve annulus tissue so that the tissue engaging member becomes affixed to the heart valve annulus.

58. The apparatus of claim 47, further comprising;
a catheter having a distal end; and
a scaffold comprising a plurality of support arms configured to support the plurality of anchors in position adjacent to the heart valve annulus in a position at which

the means for implanting can implant the plurality of anchors into the heart valve annulus tissue.

59. The apparatus of claim 47, wherein the heart valve annulus is a mitral valve annulus, and wherein the apparatus further comprises:
a catheter having a distal end; and
a scaffold comprising a plurality of support arms, wherein the scaffold is configured for deployment when the distal end of the catheter is positioned in the left atrium and the scaffold is further configured to support the plurality of anchors in position adjacent to the upper surface of the mitral valve annulus in a position at which the means for implanting can implant the plurality of anchors into the mitral valve annulus,
wherein the catheter is configured to push the plurality of anchors towards the upper surface of the mitral valve annulus prior to implanting of the plurality of anchors.

60. The apparatus of claim 59, further comprising a balloon configured for delivery in a deflated state via the catheter, and configured for inflation while at least part of the balloon is positioned in the left ventricle, and wherein the catheter is configured to pull the balloon towards the mitral valve annulus prior to implanting of the plurality of anchors.

61. The apparatus of claim 59, further comprising a balloon configured for delivery in a deflated state via the catheter, wherein when the balloon is inflated, the balloon guides the tissue engaging member into position for implantation into the mitral valve annulus.

62. A method for cinching a heart valve annulus, the heart valve annulus having an original shape, the method comprising the steps of:
delivering a first loop of wire to the vicinity of heart valve annulus so that the first loop of wire conforms with at least a portion of the original shape;
delivering a plurality of anchors to the vicinity of heart valve annulus, each of the plurality of anchors having a pointy front end and a back end, each of the plurality of anchors having a slot that runs in a front-to-back direction, wherein the front ends of the plurality of anchors are configured for implantation into heart valve annulus tissue in a forward direction and wherein the plurality of anchors are configured so that subsequent to implantation, the plurality of

anchors resist extraction from the heart valve annulus tissue in a backwards direction, wherein the plurality of anchors are distributed about the first loop of wire with the front ends of the plurality of anchors facing the heart valve annulus and with the first loop of wire passing through the slots in the plurality of anchors;

delivering a plurality of tubes to the vicinity of heart valve annulus, wherein the plurality of tubes are threaded onto the first loop of wire between the plurality of anchors and wherein an outer surface of the tubes comprises a material that promotes tissue growth;

delivering a second loop of wire to the vicinity of heart valve annulus, wherein the second loop of wire is threaded through the inside the plurality of tubes and has a first end and a second end;

implanting the plurality of anchors into the heart valve annulus; and cinching the second loop of wire by pulling on the first end and the second end.

63. The method of claim 62, wherein the at least a portion of the original shape comprises at least a 270° portion of the original shape.

64. The method of claim 62, wherein in each of the plurality of anchors the slot begins near the front end of the anchor and ends near the back end of the anchor, and wherein, during the implanting step, forward motion of the plurality of anchors is limited when the ends of the slots encounter the first loop of wire.

65. The method of claim 62, wherein the plurality of anchors comprises at least six anchors.

66. The method of claim 62, wherein the implanting step comprises driving the plurality of anchors into the heart valve annulus using a plurality of springs.

67. The method of claim 62, wherein the implanting step comprises driving the plurality of anchors into the heart valve annulus using a plurality of pull wires.

68. The method of claim 62, wherein the heart valve annulus is a mitral valve annulus, and wherein the method further comprises the step of pressing the plurality of anchors towards an upper surface of the mitral valve annulus, wherein the pressing step is implemented prior to the implanting step and subsequent to the steps of delivering the first loop of wire and delivering the plurality of anchors.

69. The method of claim 68, further comprising the step of pulling an inflated balloon that is disposed at least partially in a left ventricle towards the mitral valve annulus, wherein the pulling step and the pressing step are performed simultaneously.

70. The method of claim 68, further comprising the step of inflating a balloon to guide the anchors into position for implantation into the mitral valve annulus.




Fig. 1




Fig. 2




Fig. 3




Fig.5




Fig.4




Fig. 6




Fig. 7a




Fig. 7




Fig.8






Fig.9








Fig. 13




Fig.14





Fig.15






Fig.19




Fig.18




Fig.20




Fig. 21




Fig.22




Fig.23




Fig.24




Fig. 26




Fig. 25





Fig.27a

Fig.27






Fig.29




Fig.30




Fig.31




Fig.33




Fig.32




Fig.34




Fig.35




Fig.37





Fig.36






Fig.40




Fig.41




Fig.42




Fig.43

INTERNATIONAL SEARCH REPORT

International application No

PCT/IB2012/057138

A. CLASSIFICATION OF SUBJECT MATTER
INV. A61F2/24

ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
A61F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 2010/249920 A1 (BOLLING STEVEN F [US] ET AL) 30 September 2010 (2010-09-30) paragraphs [0068] - [0084] ; figures 1A-4C ----- A WO 2008/068756 A2 (VALTECH CARDIO LTD [IL] ; GROSS AMI R [IL] ; BEINART I FTAH [IL] ; ELIACHAR) 12 June 2008 (2008-06-12) cited in the application page 26, line 11 - line 22 page 28, line 30 - page 29, line 6 page 30, line 13 - line 29 page 33, line 7 - page 34, line 4 figures 1A-5D ----- -/-	1-19, 32-40, 47-61
A		1-19, 32-40, 47-61

Further documents are listed in the continuation of Box C.

See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

Date of mailing of the international search report

20 February 2013

28/02/2013

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Geuer, Melani e

INTERNATIONAL SEARCH REPORT

International application No
PCT/IB2012/057138

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 2006/058817 A1 (STARKSEN NIEL F [US] ET AL) 16 March 2006 (2006-03-16) paragraphs [0062] - [0066]; figures 1-19B -----	1-19, 32-40, 47-61
A	US 4 042 979 A (ANGELL WILLIAM W) 23 August 1977 (1977-08-23) column 2, line 17 - column 3, line 46 figures 1-6 -----	47-61

INTERNATIONAL SEARCH REPORT

International application No.
PCT/IB2012/057138

Box No. II Observations where certain claims were found unsearchable (Continuation of item 2 of first sheet)

This international search report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. Claims Nos.: 20-31, 41-46, 62-70 because they relate to subject matter not required to be searched by this Authority, namely:
Rule 39.1(iv) PCT - Method for treatment of the human or animal body by surgery
2. Claims Nos.: because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out, specifically:
3. Claims Nos.: because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box No. III Observations where unity of invention is lacking (Continuation of item 3 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

1. As all required additional search fees were timely paid by the applicant, this international search report covers all searchable claims.
2. As all searchable claims could be searched without effort justifying an additional fees, this Authority did not invite payment of additional fees.
3. As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims for which fees were paid, specifically claims Nos.:
4. No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

The additional search fees were accompanied by the applicant's protest and, where applicable, the payment of a protest fee.

The additional search fees were accompanied by the applicant's protest but the applicable protest fee was not paid within the time limit specified in the invitation.

No protest accompanied the payment of additional search fees.

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/IB2012/057138

Patent document cited in search report	Publication date	Patent family member(s)		Publication date
us 2010249920	AI 30-09-2010	CA 2801344	AI	08-12-2011
		US 2010249920	AI	30-09-2010
		Wo 2011153408	AI	08-12-2011

w0 2008068756	A2 12-06-2008	AU 2007330338	AI	12-06-2008
		CA 2671966	AI	12-06-2008
		EP 2088965	A2	19-08-2009
		JP 2010511469	A	15-04-2010
		US 2008262609	AI	23-10-2008
		US 2009259307	AI	15-10-2009
		Wo 2008068756	A2	12-06-2008

us 2006058817	AI 16-03-2006	NON E		

us 4042979	A 23-08-1977	NON E		
