

[54] AIR CONDITIONING PROCESS
[76] Inventor: Ted R. Brown, 1212 Princeton Ave., Salt Lake City, Utah 84105
[22] Filed: May 11, 1973
[21] Appl. No.: 359,368
Related U.S. Application Data
[63] Continuation-in-part of Ser. No. 172,968, Aug. 19, 1971, abandoned.
[52] U.S. Cl. 62/93, 62/271, 62/91, 62/92
[51] Int. Cl. F25d 17/06
[58] Field of Search 62/271, 91, 92, 93, 94, 62/95


[56] References Cited
UNITED STATES PATENTS
1,749,763 3/1930 Fleisher 62/92
1,863,576 6/1932 Morse 62/271



1,863,577	6/1932	Morse	55/35
1,863,578	6/1932	Morse	55/35
1,909,823	5/1933	Forrest	62/94
2,114,787	4/1938	Smith	62/94
2,355,828	8/1944	Taylor	62/79
2,378,964	6/1945	Williams	72/182
2,811,223	10/1957	Newton	62/92
3,041,842	7/1962	Heinecke	62/95
3,153,914	10/1964	Meckler	62/271

Primary Examiner—William J. Wye
Attorney, Agent, or Firm—H. Ross Workman

[57] ABSTRACT
A process for efficiently conditioning air for beneficial use by sequentially cooling dry air in three distinct steps, e.g., pre-cooling the air out of the presence of moisture, adiabatically cooling the air in the presence of moisture, and refrigerating the air to finally cool the air and coincidentally condense excess moisture.

2 Claims, 3 Drawing Figures








FIG. 2

AIR CONDITIONING PROCESS

This invention is a continuation-in-part of my co-pending application Ser. No. 172,968, filed Aug. 19, 1971, now abandoned.

BACKGROUND

1. Field of the Invention

The present invention relates to the production of low temperature gases such as air for beneficial use in air conditioning.

2. The Prior Art

It is well-known that the efficiency of air conditioning systems is highly dependent upon the temperature of ambient air. In summer months, where the ambient air temperature is high, usually refrigerated air conditioning systems are employed to produce consistently cold air. This is particularly true where high temperatures are accompanied by relatively high humidity levels. So-called "swamp cooler" type air conditioning systems become of almost negligible value when both the temperature and humidity of ambient air are high.

Because of the great difficulty with which air is reduced to a very low temperature in hot summer months, most air conditioning systems have been engineered so as to recirculate and recool the conditioned air instead of continuously cooling fresh air. This procedure has been found necessary to keep the size and attendant costs of air conditioning systems from becoming prohibitive. Until this present invention, an economical and efficient way of substantially reducing the temperature of air or other gas for cooling purposes year-round without refrigeration has not been known.

It is also well-known to condition air by successive cooling, humidifying, drying and recooling steps which are inefficient, complicated and expensive. See, for example, U. S. Pat. No. 1,863,578.

BRIEF SUMMARY AND OBJECTS OF THE INVENTION

The present invention relates to conditioning fresh air by sequentially (1) pre-cooling dry air out of the presence of moisture, (2) adiabatically cooling the air, and (3) refrigerating to finally cool the air and coincidentally condense excess moisture. Surprising efficiency and cooling results from this process using a total fresh air system and treatment of the air in quantities between 400 and 600 cubic feet per minute per ton of net sensible in-space cooling.

It is, therefore, a primary object to efficiently provide air having controlled temperature and humidity for air conditioning.

It is another important object to provide a process for effecting sensible cooling using a total fresh air system.

These and other objects of the present invention will become more fully apparent from the following description and appended claims taken in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIGS. 1, 2 and 3 are schematic flow diagrams illustrating fluid circuits and apparatus for reducing air temperature according to the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

General

Heat exchange processes such as used in air conditioning systems have always been required to have increased capacity in order to adequately cool air when the temperature and/or the humidity of external air climbs as in summer months and on hot days.

While it is relatively easy and comparatively inexpensive to remove heat from gases when the temperature of the gas is high, the difficulty with which heat is removed increases at an astonishing rate when the temperature of the gas is already low. Thus, generally speaking, it is much easier and less expensive to make hot air cool than to make cool air cold using prior art techniques. Historically, the approach used to make cool air cold was to increase the size and capacity of cooling systems.

The present invention includes treating dry warm air out of the presence of moisture to reduce its dew point. Air most efficiently used with the illustrated embodiments has a dew point of not more than 57° which is low compared to the dry bulb temperature of the warm air. This treatment can be performed by pre-cooling in a conventional heat exchanger.

According to the present invention, the temperature of the pre-cooled gas is then adiabatically reduced so that the gas is cold. Adiabatic processes are defined as those processes carried out in such a manner that heat is not exchanged between the system and its surroundings. Thus, the adiabatic cooling step does not require an energy input to reduce the temperature. When the gas is adiabatically cooled according to the present invention, heat is not actually removed from the cooling system but is reduced psychrometrically.

If a stream of gas is intimately mixed with a quantity of recirculating liquid at a given temperature in an adiabatic system, the temperature of the gas will drop and its humidity will increase. Furthermore, the temperature of the recirculating liquid will approach the wet bulb temperature of the gas. The low temperature gas which has been cooled adiabatically is subjected to refrigeration which both further cools the air and coincidentally condenses excess moisture.

When 100 percent fresh (unrecirculated) air is used for cooling, air quantities treated according to the preferred embodiments of the invention must necessarily be limited to a rather narrow range in order to efficiently produce desired cooling to within a range of 53° to 60° F without imposing larger than necessary pre-cooling and refrigeration loads on the air cooling process.

It has been found according to the present invention that approximately 400 to 600 cubic feet of fresh air per minute per ton (CFM/ton) of net sensible in-space cooling is an adequate amount to develop conditioned air at a desirable temperature of between 53° and 60° F. The surprising efficiency of this system can be recognized by observing that conventional fresh air swamp coolers require about 1,000 CFM/ton even with very dry fresh air. The efficiency of the system using this air volume range presumes 100 percent fresh (unrecirculated) air having a dew point of not more than 57° F coincident with dry bulb temperatures of not less than 90° F. Under these climatic conditions, the presently preferred embodiment of the invention produces 53° to

60° F moisture conditioned air with surprising efficiency and without requiring intermediate drying steps.

The FIG. 1 Embodiment

Referring more particularly to FIG. 1, warm dry air is first obtained from a fresh air source, e.g., ambient. To maximize the efficiency of the system, the dew point of the air should be at least as low as 57° F when air having a dry bulb temperature of not less than 90° F is used.

The warm air is first pre-cooled in a heat exchanger 62. The heat exchanger 62 may be any one of a variety of heat exchangers which will not add moisture to the air, one suitable type being the fin-coil heat exchanger often called an extended surface heat exchanger. This type of heat exchanger is very inexpensive to acquire and operate and is very efficient at high temperatures.

Therefore, according to the illustrated embodiment of the invention, the pre-cooled dry air emerging from the heat exchanger 62 is conducted to an air washer 64 which scrubs the air with water or, if desired, other cooling liquid. The water used to scrub the pre-cooled dry air is recirculated through an external circuit 66 continuously. The temperature of the recirculating water in the circuit 66 approaches the wet bulb temperature of the air which enters the air washer 64. Thus, the entering pre-cooled air has its temperature adiabatically reduced from the dry bulb to near the wet bulb temperature in the air washer.

The cold air emerging from air washer 64 is treated with a conventional refrigeration circuit generally designated 70. The refrigeration circuit conventionally comprises a condenser 72 and a compressor 74 with an evaporating coil 76 interposed therebetween. A conventional expansion valve 78 admits refrigerant fluid into the evaporating coil 76.

The use of the refrigeration circuit 70 allows the temperature of air emerging from the air washer to be reduced to the desired temperature range of 53° to 60° F. Also, excess moisture in the air emerging from the air washer 64 is condensed by the evaporating coil 76 to control the moisture content of the effluent, conditioned air. It should be observed that unless the temperature of the air were first adiabatically reduced in the air washer 64, a far larger and more expensive coil 76 and larger refrigeration system 70 would be necessary to obtain the same very cold air temperature developed according to the embodiment of FIG. 1.

The system of FIG. 1 is designed to transport and condition about 400 to 600 CFM/ton net sensible cooling. Using the air having a 57° dew point, temperatures as low as 53° to 60° F may be economically and efficiently achieved. Accordingly, the effluent conditioned air has a surprisingly low temperature and controlled humidity without requiring expensive dehumidifying (warming) and recooling steps.

The FIG. 2 Embodiment

The embodiment of FIG. 2 differs from the embodiment of FIG. 1 principally in that the evaporating coil 76 acts upon the pre-cooled air as it traverses from the heat exchanger 62 to the air washer 64 (i.e., from the pre-cooling to the adiabatically cooling steps). When the pre-cooled air is further cooled, its wet bulb temperature is lowered. Accordingly, upon adiabatic cooling in the air washer 64, its dry bulb temperature is further reduced to about 53° to 60° F.

The moisture content of the effluent from the air washer 64 will be controlled in proportion to the amount of cooling to which the air is subjected in advance of the adiabatic cooling in air washer 64. The dry bulb and wet bulb temperatures imposed upon the air in advance of the adiabatic cooling step will determine the amount of moisture that can be added in the adiabatic cooling step.

The Embodiment of FIG. 3

The embodiment of FIG. 3 differs from the previously described embodiments principally in that the evaporation coil 76 reduces the temperature of recirculating water in the air washer 64. Accordingly, the temperature of the water is reduced sufficiently that both adiabatic and sensible cooling of the air results. The refrigeration system 70 is specifically limited to avoid exclusive refrigerated cooling in the air washer 64 to insure that effluent air is within the range of 53° to 60° F.

Using the embodiments of FIGS. 1-3, cold air in the range of 53° to 60° F for air conditioning or any other desired beneficial use can be obtained with surprising efficiency using a 100 percent fresh air system at maximum outdoor temperatures. Thus, the need for recirculating the same air in order to reduce the costs of cooling is unnecessary. Furthermore, cold air can be obtained without using large and expensive refrigeration systems. The refrigeration system 70 required for this combination of cooling steps has been found to be approximately one-third the size required if conventional recirculating air refrigeration systems are employed. Accordingly, the advantages of a complete fresh air system can be substituted for the lower quality, more expensive recirculating air systems.

The invention may be embodied in other specific forms without departing from its spirit or essential characteristics. The described embodiments are to be considered in all respects only as illustrative and not restrictive and the scope of the invention is, therefore, indicated by the appended claims rather than by the foregoing description. All changes which come within the meaning and range of equivalency of the claims are to be embraced within their scope.

What is claimed and desired to be secured by United States letters patent is:

1. A process for controlling the temperature and moisture content of air having a dew point of not more than 57° corresponding to at least 90° F dry bulb temperature, sequentially

preparing an air flow path accommodating 400-600 CFM/ton net sensible cooling;

drawing fresh dry air exclusively from a fresh air source and through the flow path in the amounts of 400 to 600 CFM/ton net sensible cooling;

pre-cooling the fresh air with a heat exchanger without altering its moisture content;

scrubbing the air with recirculating water to adiabatically cool the air; and

refrigerating the adiabatically cooled air to further cool the air to within a range of 53° to 60° F and coincidentally condensing excess moisture.

2. A process for conditioning air sequentially comprising (a) first cooling 100 percent fresh air having a dew point of not more than 57° corresponding to at least 90° F dry bulb temperature without altering its moisture content; (b) second cooling the air adiabatically by scrubbing the dry air with recirculating water; (c) third cooling the air by refrigeration to within the range of 53° to 60° F with coincidental condensation of excess moisture, all three cooling steps being applied sequentially to air quantities exclusively within the range of 400 to 600 CFM/ton net sensible cooling.

* * * * *

UNITED STATES PATENT OFFICE
CERTIFICATE OF CORRECTION

Patent No. 3,812,685 Dated May 28, 1974

Inventor(s) Ted R. Brown

It is certified that error appears in the above-identified patent and that said Letters Patent are hereby corrected as shown below:

Column 2, line 21, "dew point" should be
--wet bulb temperature--.

Signed and sealed this 1st day of October 1974.

(SEAL)
Attest:

McCOY M. GIBSON JR.
Attesting Officer

C. MARSHALL DANN
Commissioner of Patents