

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date
24 February 2005 (24.02.2005)

PCT

(10) International Publication Number
WO 2005/016092 A1

(51) International Patent Classification⁷: A47J 31/06, 31/40

(21) International Application Number: PCT/IB2004/051337

(22) International Filing Date: 30 July 2004 (30.07.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data: 03102580.2 18 August 2003 (18.08.2003) EP

(71) Applicant (for all designated States except US): KONINKLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(72) Inventor; and

(75) Inventor/Applicant (for US only): D'HONT, Bernardus, P. G. [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

(74) Agent: SCHOUTEN, Marcus, M.; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:

— as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE,

[Continued on next page]

(54) Title: A BEVERAGE MAKING DEVICE HAVING PROTRUSIONS AT THE UPPER WALL OF THE BREWING CHAMBER



(57) Abstract: A beverage making device comprising a brewing chamber (5) for enclosing a pad containing a substance from which the beverage is brewed. The brewing chamber (5) has an upper wall (4) with one or more holes through which heated water can enter the brewing chamber (5). The upper wall (4) can hinge from a substantially horizontal brewing position in which the upper wall (4) is a portion of the wall of the brewing chamber (5) into an open position in which the pad can be removed from the brewing chamber (5). A substantial portion of the surface of said upper wall (4) is provided with protrusions (21). The protrusions have a height of more than 0.5 mm, and the distance between every two neighboring protrusions (21) is less than 12 mm.

WO 2005/016092 A1



EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE,

IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

A beverage making device having protrusions at the upper wall of the brewing chamber

The invention relates to a beverage making device comprising a brewing chamber for enclosing a pad containing a substance from which the beverage is brewed, the brewing chamber having an upper wall with one or more holes through which heated water can enter the brewing chamber, which upper wall can hinge from a substantially horizontal

5 brewing position, in which the upper wall is a portion of the wall of the brewing chamber into an open position in which the pad can be removed from the brewing chamber.

Such a device is described in WO-A-01/15582. The described device

10 comprises a water reservoir and means for heating the water and pumping it towards the holes in the upper wall of the brewing chamber, so that the heated water will enter the brewing chamber under pressure. The brewing chamber is filled with a pad containing a substance, for example ground coffee, and the heated water will pass through the pad, so that the coffee is extracted. After the extraction process, the liquid (coffee) leaves the brewing

15 chamber through an outflow opening in the bottom of the brewing chamber and arrives in a liquid receiving chamber. The liquid receiving chamber comprises an outflow tube extending outside the device, so that the brewed liquid (coffee) can be caught by one or by two cups. The portion of the device comprising the upper wall of the brewing chamber can hinge upwards with respect to the stationary part of the brewing chamber to give access to the

20 brewing chamber, so that a new pad can be placed for a next extraction process. In the upward position of said portion, the part of the device comprising the side wall and the lower wall of the brewing chamber (said stationary part) and the liquid receiving chamber can be removed from the device, for example for cleaning that part or for replacing the part by another, similar part in which the brewing chamber is larger, so that two pads can be placed

25 in it in order to brew enough beverage for two cups instead of one cup.

A beverage can be made in an extraction process by means of the device, for example to produce coffee, or in a dissolving process, for example to produce a chocolate drink. In the case of an extraction process, the extracted substance will remain in the pad and the pad with the extracted substance must be removed from the chamber afterwards. In the

case of a dissolving process, the substance in the pad will disappear during the brewing process, and the empty pad must be removed.

It was found in practice that the wet pad tends to stick to the upper wall when that upper wall is hinged into its open position. This is especially the case when two pads are placed in the brewing chamber: the upper pad then sticks to the upper wall, while the lower pad remains in the stationary part of the brewing chamber. Of course the pad can be removed by hand from the upper wall in its open position, but it is easier to remove the pad or the pads from the stationary part of the brewing chamber. Furthermore, the user of the device expects the pad to remain in the stationary part when he or she opens the brewing chamber and therefore may not notice a pad sticking to the upper wall.

The object of the invention is to provide a beverage making device as described above wherein the pad or, if two pads are present, both pads always remain in the stationary part of the brewing chamber when that chamber is opened.

To accomplish that objective, a substantial portion of the surface of said upper wall is provided with protrusions having a height of more than 0.5 mm, the distance between every two neighboring protrusions being less than 12 mm, preferably less than 10 mm. Said substantial portion preferably accounts for more than 50% of the surface area of said upper wall, and in a preferred embodiment more than 75%. The protrusions may have the form of studs having more or less a cylindrical shape. The protrusions prevent the pad from sticking to the upper wall when the upper wall is hinged upward.

The device disclosed in WO-A-01/15582 is provided with six protrusions at the surface of the upper wall of the brewing chamber, which protrusions are located at considerable distances from each other. It was found in practice that the pad tends to stick to the hinging upper wall in the disclosed device, despite the presence of the protrusions. However, the tendency to stick can be decreased when certain dimensions of the protrusions are applied.

In one preferred embodiment, the distance between every two neighboring protrusions is less than 6 mm, and preferably the height of the protrusions is more than 0.7 mm, more preferably more than 1 mm.

In one preferred embodiment, the transverse section of the protrusions (i.e. the section parallel to the plane of the upper wall) is substantial circular, with a diameter between 0.5 mm and 3 mm, preferably between 1 mm and 2 mm.

Preferably, the distance between every two neighboring protrusions is less than eight times the height of the protrusions, preferably less than five times the height of the protrusions. The higher the protrusions, the greater the distance between the protrusions can be.

5 In one preferred embodiment, at least a portion of the side wall of a protrusion extends at an angle of more than 60°, preferably more than 75°, relative to the plane of said upper wall, and preferably a portion of each protrusion is substantial cylindrical.

In another preferred embodiment, the protrusions are ribs on the surface of the upper wall. These may be straight ribs, but the ribs may also be concentrically circular ribs.

10 The ribs may also have the shape of circular arcs or the like.

To achieve a good access to the brewing chamber when that chamber is opened, said upper wall can hinge through more than 60°, preferably more than 70°, more preferably more than 80°.

15 In one preferred embodiment, a removable part comprising the part of the wall of the brewing chamber other than said upper wall is a portion of a removable part, and said removable part can be taken from the device in order to clean the brewing chamber or to remove the pad.

The invention also relates to a method of making a beverage by means of a beverage making device, wherein a pad containing a substance from which the beverage is to be brewed is placed in a brewing chamber, the brewing chamber having an upper wall with one or more holes through which heated water enters the brewing chamber, wherein said upper wall is hinged after the brewing process from a substantially horizontal brewing position in which the upper wall is a portion of the wall of the brewing chamber into an open position in which the pad can be removed, wherein a substantial portion of the surface of said upper wall is provided with protrusions having a height of more than 0.5 mm, and wherein the distance between every two neighboring protrusions is less than 12 mm, so that the pad will remain in the brewing chamber when the upper wall is hinged into its open position.

30 The invention will now be explained by means of a description of an embodiment of a device for making coffee, in which reference is made to the drawing, in which:

Fig. 1 is a sectional view of a portion of the device,

Fig. 2 shows the device with the brewing chamber in open position,

Fig. 3 is a sectional view of the upper wall of the brewing chamber,

Fig. 4 is a bottom view of the upper wall according to Fig. 3, and

Fig. 5 is a top view of the upper wall according to Fig. 3.

Fig. 1 shows the relevant portion (i.e. the uppermost portion) of a device for making coffee. The other portion of the device, which is not shown, comprises a water container and means for heating the water and pumping a predetermined quantity of the heated water through tube 2 to five holes 3 in the upper wall 4 of the brewing chamber 5. In 10 the sectional view of Fig. 1, only one hole 3 in the upper wall 4 is shown. Brewing chamber 5 has a substantial cylindrical shape, and a disc-like pad (not shown) containing, for example, ground coffee fits in said chamber.

The lower wall 6 of the brewing chamber 5 is provided with a profile 7 so as to form channels for allowing the brewed coffee to arrive at the central part of the bottom of 15 the brewing chamber 5, so that the liquid can flow to the outflow opening 8 in the lower wall 6. The brewed coffee is collected in a liquid receiving chamber 9 and subsequently guided through two outflow tubes 10 extending outside the device to a location where the brewed coffee can be caught by one or by two cups (not shown). There are two outflow tubes 10 parallel to each other, so that each outflow tube 10 can guide brewed coffee to one of two 20 cups, which cups stand near each other. If only one cup is to be filled, both outflow tubes 10 will guide the brewed coffee to the same cup. Since the two outflow tubes 10 are located on either side of the plane of drawing, they are not visible in the sectional views of Fig. 1 and Fig. 2.

The brewing chamber 5 as shown in Fig. 1 has a dimension to accommodate a 25 pad containing ground coffee for brewing coffee for one cup. If two cups of coffee are to be brewed, the part 11 of the device can be replaced by another part 11, which other part (not shown) comprises a thinner lower wall 6, so that the height of the brewing chamber 5 is increased and the brewing chamber 5 can accommodate two pads containing ground coffee, or a bigger pad, to brew enough coffee for two cups.

30 As is shown in Fig. 2 by arrow 12, the device can be opened by hinging the upper part 13 of the device about an axis 14. The upper wall 4 of the brewing chamber 5 is connected to said upper part 13, so that the brewing chamber 5 becomes accessible after opening. A used pad may then be removed and/or a new pad may be placed in the brewing chamber 5. If the next brewing process is to be performed with two pads, the open position of

the brewing chamber allows the replacement of part 11 of the device by another one having a larger brewing chamber 5. To enable the hinging movement of the upper part 13, the tube 2 is made of a flexible material.

5 In the opened position of the device as shown in Fig. 2, the part of the device comprising the brewing chamber 5 (except for its upper wall 4), the liquid receiving chamber 9, and the outflow tubes 10 is removable from the device, so that the part can be cleaned.

The upper wall 4 of the brewing chamber 5 has a disc-like shape and is clamped in a connecting piece 16 comprising a central water duct 17 which is connected to tube 2, as is shown in Figs. 1 and 2. Between the upper wall 4 and the connecting piece 16 10 there is a distribution plate 18, having a disc-like shape and comprising recesses in the material to guide the heated water coming from the tube 2 and the water duct 17 to the five holes 3 in the upper wall 4. Around the connecting piece 16 there is a sealing ring 19 to provide a watertight sealing between the removable part 11 and the upper wall 4 when the brewing chamber 5 is closed (Fig. 1).

15 At the lower side of the upper wall 4, the main portion of the surface of the upper wall 4 is provided with protrusions 21. In this example, the height of the protrusions 21 is about 1 mm, and the distance between the protrusions 21 is about 4 mm.

Fig. 3 is the same sectional view of the upper wall 4 of the brewing chamber 5 as is shown in Figs. 1 and 2, but on a larger scale. The upper wall 4 is made of a synthetic 20 resin material. At its upper side, the upper wall 4 is provided with an annular protrusion 22 which can surround the distribution plate 18 and which clamps in the connecting piece 16.

Fig. 4 is a view of the lower side of the upper wall 4 and shows the distribution of the protrusions 21 over the lower side of the upper wall 4. Fig. 4, and also Fig. 5, furthermore show the locations of the five holes 3 in the upper wall 4.

25 Fig. 5 is a view of the upper side of the upper wall 4. The annular protrusion 22 is provided with a flat (straight) portion 23 corresponding to a flat portion at the edge of distribution plate 18, so that said distribution plate fits between the upper wall 4 and the connecting piece 16 in one position only.

The protrusions 21 at the lower side of the upper wall 4 of the brewing 30 chamber 5 achieve that the wet pad will not stick to the upper wall 4 when the brewing chamber 5 is opened.

The embodiment as described above is only an example; a great many other embodiments are possible, including embodiments in which the protrusions 21 at the lower side of the upper wall 4 of the device have a different shape.

CLAIMS:

1. A beverage making device comprising a brewing chamber (5) for enclosing a pad containing a substance from which the beverage is brewed, the brewing chamber (5) having an upper wall (4) with one or more holes (3) through which heated water can enter the brewing chamber (5), which upper wall (4) can hinge from a substantially horizontal brewing position in which the upper wall (4) is a portion of the wall of the brewing chamber (5) into an open position in which the pad can be removed from the brewing chamber (5), characterized in that a substantial portion of the surface of said upper wall (4) is provided with protrusions (21) having a height of more than 0.5 mm, the distance between every two neighboring protrusions (21) being less than 12 mm.
10
2. A beverage making device as claimed in claim 1, characterized in that the distance between every two neighboring protrusions (21) is less than 6 mm.
3. A beverage making device as claimed in any one of the preceding claims, characterized in that the height of the protrusions (21) is more than 0.7 mm, preferably more than 1 mm.
15
4. A beverage making device as claimed in any one of the preceding claims, characterized in that the transverse section of the protrusions (21) is substantial circular, with a diameter between 0.5 mm and 3 mm, preferably between 1 mm and 2 mm.
20
5. A beverage making device as claimed in any one of the preceding claims, characterized in that the distance between every two neighboring protrusions (21) is less than eight times the height of the protrusions (21), preferably less than five times the height of the protrusions (21).
25
6. A beverage making device as claimed in any one of the preceding claims, characterized in that at least a portion of the side wall of a protrusion (21) extends at an angle of more than 60°, preferably more than 75°, relative to the plane of said upper wall (4).

7. A beverage making device as claimed in any one of the preceding claims, characterized in that a portion of each protrusion (21) is substantially cylindrical.

5 8. A beverage making device as claimed in any one of claims 1 to 6, characterized in that the protrusions (21) are ribs on the surface of the upper wall (4).

9. A beverage making device as claimed in any one of the preceding claims, characterized in that said upper wall (4) can hinge through more than 60°, preferably more 10 than 70°, more preferably more than 80°.

10. A beverage making device as claimed in any one of the preceding claims, characterized by a removable part comprising the part of the wall of the brewing chamber (5) other than said upper wall (4), which removable part can be taken from the device in order to 15 clean the brewing chamber (5) or to remove the pad.

11. A method of making a beverage by means of a beverage making device, wherein a pad containing a substance from which the beverage is to be brewed is placed in a brewing chamber (5), said brewing chamber (5) having an upper wall (4) with one or more 20 holes (3) through which heated water can enter the brewing chamber (5), wherein said upper wall (4) is hinged after the brewing process from a substantially horizontal brewing position in which the upper wall (4) is a portion of the wall of the brewing chamber (5) into an open position in which the pad is removed, characterized in that a substantial portion of the surface of said upper wall (4) is provided with protrusions (21) having a height of more than 0.5 mm, 25 the distance between every two neighboring protrusions (21) being less than 12 mm, so that the pad will remain in the brewing chamber (5) when the upper wall (4) is hinged into its open position.

1/3




FIG.1

2/3




FIG.2

3/3




FIG. 3




FIG. 4




FIG. 5

INTERNATIONAL SEARCH REPORT

ntional Application No
/IB2004/051337A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 A47J31/06 A47J31/40

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 A47J

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category ^o	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	NL 1 020 735 C (KLAASSEN ANTONIUS) 15 July 2002 (2002-07-15) page 5, line 29 – page 7; claims 4-9; figures -----	1-11
X	WO 01/15582 A (KRAAN DIEDERIK ; LEE DE NV SARA (NL)) 8 March 2001 (2001-03-08) page 5, column 8 – page 11; figures -----	1-11
X	EP 0 870 457 A (NESTLE SA) 14 October 1998 (1998-10-14) column 13, line 38 – column 15, line 49; figures 1-3 -----	1-6,8, 10,11
X	US 5 582 730 A (HUGENTOBLER MAX) 10 December 1996 (1996-12-10) the whole document -----	1-11 -/-

 Further documents are listed in the continuation of box C. Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

- *&* document member of the same patent family

Date of the actual completion of the international search

10 November 2004

Date of mailing of the international search report

17/11/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL – 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Van Bastelaere, T

INTERNATIONAL SEARCH REPORT

ational Application No
/IB2004/051337

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 1 247 480 A (MOEVENPICK HOLDING) 9 October 2002 (2002-10-09) paragraph '0031!; figure 6 -----	1-6,11
X	US 2001/052294 A1 (SCHMED ARTHUR) 20 December 2001 (2001-12-20) paragraphs '0020! - '0024!; figures 2,5 -----	1-3,5,6, 8,11

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

/IB2004/051337

Patent document cited in search report		Publication date		Patent family member(s)		Publication date
NL 1020735	C	15-07-2002	NL	1020735 C1		15-07-2002
WO 0115582	A	08-03-2001	NL	1012847 C2		20-02-2001
			AT	278346 T		15-10-2004
			AU	6482800 A		26-03-2001
			EP	1209997 A1		05-06-2002
			JP	2003508103 T		04-03-2003
			WO	0115582 A1		08-03-2001
			US	6748850 B1		15-06-2004
EP 0870457	A	14-10-1998	EP	0604615 A1		06-07-1994
			EP	0870457 A1		14-10-1998
			DK	870457 T3		28-06-2004
			AT	171352 T		15-10-1998
			AT	260066 T		15-03-2004
			AU	671650 B2		05-09-1996
			AU	4414893 A		14-02-1994
			BR	9305586 A		02-05-1995
			CA	2111990 A1		03-02-1994
			WO	9402059 A1		03-02-1994
			DE	69321209 D1		29-10-1998
			DE	69321209 T2		18-02-1999
			DE	69333428 D1		01-04-2004
			DE	69333428 T2		22-07-2004
			DK	604615 T3		14-06-1999
			ES	2122026 T3		16-12-1998
			ES	2213847 T3		01-09-2004
			FI	941256 A		17-03-1994
			HK	1012536 A1		12-05-2000
			JP	3315121 B2		19-08-2002
			JP	6511182 T		15-12-1994
			NO	940248 A		03-02-1994
			NZ	253663 A		28-05-1996
			PT	870457 T		30-07-2004
			US	5649472 A		22-07-1997
			US	5826492 A		27-10-1998
			US	5762987 A		09-06-1998
US 5582730	A	10-12-1996	CH	685667 A5		15-09-1995
			AT	201 U1		26-05-1995
			DE	9415020 U1		03-11-1994
			FR	2711313 A3		28-04-1995
EP 1247480	A	09-10-2002	EP	1247480 A1		09-10-2002
US 2001052294	A1	20-12-2001	AT	225627 T		15-10-2002
			AU	766342 B2		16-10-2003
			AU	4621101 A		20-12-2001
			BR	0102375 A		19-02-2002
			CA	2348252 A1		14-12-2001
			CN	1328804 A		02-01-2002
			CZ	20011814 A3		16-01-2002
			DE	50100037 D1		14-11-2002
			DK	1163869 T3		10-02-2003
			EP	1163869 A1		19-12-2001
			ES	2184726 T3		16-04-2003
			HU	0102449 A2		28-01-2002
			JP	2002028080 A		29-01-2002

INTERNATIONAL SEARCH REPORT

Information on patent family members

ational Application No

/IB2004/051337

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2001052294 A1		PL 348078 A1 PT 1163869 T RU 2220639 C2 TR 200201609 T3	17-12-2001 28-02-2003 10-01-2004 21-08-2002